



HYDROSPRING™

HIGH FLOW SYSTEM

Water Softener and Conditioner

- Softer smoother skin and hair
- Cleaner longer lasting clothes
- Cleaner dishes, spotless silverware
- Saves up to 75% on soaps and cleaning supplies
- Easily clean plumbing fixtures and shower parts
- Protect water using appliances
- Saves energy

Made
TO LAST A LIFETIME!



Optional all in one cabinet



A lifetime of soft, conditioned water from HydroSpring™
With over 75 years of combined experience

HYDRO SPRING™

Valve is certified by: NSF to NSF/ANSI 44 Cation Exchange Water Softeners



HIGH FLOW SYSTEM

Water Softener and Conditioner

Double backwash feature for optimum regeneration, cleaning ability, and efficiency

HydroSpring Digital



U.V. Protected Heavy Duty Non-Corrosive Noryl BY-PASS

1 1/4" Connections

U.V. Protected Heavy Duty Non-Corrosive Noryl Valve

Internals Teflon coated

Water Resistant Cover

Solid State Computer Controlled With L.E.D. Display Step By Step User Friendly Controls

Plain

- SYS-HYDROSPRING-R
- SYS-HYDROSPRING-M
- SYS-HYDROSPRING-L
- SYS-HYDROSPRING-XL



Tank Shroud

- SYS-HYDROSPRING-TS-M
- SYS-HYDROSPRING-TS-L
- SYS-HYDROSPRING-TS-XL



Full Weld Jacket

- SYS-HYDROSPRING-JKT-R
- SYS-HYDROSPRING-JKT-M
- SYS-HYDROSPRING-JKT-L
- SYS-HYDROSPRING-JKT-XL



Plain Cloth Jacket Black

- SYS-HYDROSPRING-NP-PLAIN-M
- SYS-HYDROSPRING-NP-PLAIN-L
- SYS-HYDROSPRING-NP-PLAIN-XL
- SYS-HYDROSPRING-NP-PLAIN-GY-L
- SYS-HYDROSPRING-NP-HS-M
- SYS-HYDROSPRING-NP-HS-L
- SYS-HYDROSPRING-NP-HS-XL



OPTIONAL 2nd Multi Media Tank

Where troublesome water requires additional treatment. Contact your local dealer for more information on adding a 2nd multi-media tank.

SOFT CONDITIONED WATER OUT TO HOUSE

TROUBLED WATER IN FROM SOURCE



KDF-55 or KDF-85: For Chlorine, Heavy Metal, Bacteria, Iron, Hydrogen Sulfide

Coconut Shell GAC: For Chlorine, Taste, Color, Odor

Calcite: For pH adjustment

Synthetic Zeolite: Clarifying Media Prevents Algae Growth

Anthracite: For Sediment Filtration

Choose from a variety of media for your specific needs. Your solution for well water applications, or for removal of a wide range of problems including Iron, Hydrogen Sulfide, Manganese, Heavy Chlorine, Bad Tastes, Bad Colors, or Bad Odors.

	HYDROSPRING-M	HYDROSPRING-L	HYDROSPRING-XL
VALVE FLOW RATE *	30 GPM	30 GPM	30 GPM
SYSTEM FLOW RATE *	27 GPM	27 GPM	27 GPM
BYPASS SIZE	1"	1"	1.25"
SOFTENING CAPACITY	32,000 Grains	48,000 Grains	64,000 Grains
RESIN VOLUME	1.0 CUFT	1.5 CUFT	2.0 CUFT
MEDIA TANK SIZE DXH	9" x 48"	10" x 54"	12" x 52"
BRINE/SALT TANK SIZE	15" x 35" Square	15" x 35" Square	15" x 35" Square
SHIPPING WEIGHT SYSTEM	98 lbs.	125 lbs.	150 lbs.
SHIPPING WEIGHT BRINE	16 lbs.	17 lbs.	18 lbs.
TANK	* Pressure drop at flow rates listed is less than 15 PSI.		

BUILT TO LAST A LIFETIME!

DISTRIBUTED BY:

713.534.9920



Shown with optional stainless jacket © Waterworld USA, Inc. 2023