Professional Installation Recommended

Cat Security™

by Cap City Muffler



Toyota Prius Level 2 (2004 - 2009)

Thank you for your purchase. With the installation of this Cat Security M shield, we hope that you will help prevent any further catalytic converter theft. The included hardware kit will help further secure your catalytic converter and deter thieves.


Package Contents:

- (1) Stainless rail (rear)
- (1) Stainless rail (front)
- (5) 3/16 " Rivets Stainless
- (2) M10 Nut
- (2) M10 Star Lock Washer
- (2) M10 x 80 Flange Bolt

Professional Installation Recommended

Toyota Prius Cat Security™ Install Instructions (rear rail)


STEP 1: Hold up the rear rail and center it with the exhaust pipe. Clamp each side down with locking pliers (vise grips) and then mark your holes. You can then remove and drill or skip removal and drill the holes. Check the next marking after each hole to ensure the rail has not moved





STEP 2:

Install the center rivet and check for hole alignment. Check the exhaust pipe cutout to ensure it is still center as well. Install the remaining rivets, double check clearance and you are good to go!





Professional Installation Recommended

Toyota Prius Cat Security™ Install Instructions (front plate)



STEP 1: There are two bolts in the rear engine mount. Remove one bolt at a time and replace with the M10 x 80 flange supplied in the hardware kit.

STEP 2: Once the bolts are installed, place the front shield on top of the bolts in the engine bay through the point between the drive axle and subframe. The two holes will slide over the new longer bolts that were installed in the previous step.



Use the supplied M10 lock washers and nuts to secure the front plate into place. You can gain access by turning the tire out and reaching through the spot outlined.

FINAL STEP - Install the stickers provided



