# **2020 Ace Speedway Limited Late Model Rules**

# 1) Body

- a. All body parts & pieces per NASCAR rulebook
- b. All Body Dimensions Must meet rulebook at 4" inspection height
- c. New Camaro Body is legal, meeting all specs at 4" inspection height

## 2) Weight

a.	602 Chevy Crate	3050	1350
b.	603 Chevy Crate	3050	1350
c.	604 Chevy Crate	3075	1375
d.	Chevy Steel Head	3100	1375
e.	Ford 347 JR	3075	1375

## 3) Engine & Carb Combo

## **No Super Sucker Spacers Allowed**

a.	602 Chevy Crate	390 carb	1" spacer
b.	603 Chevy Crate	390 carb	1" spacer
c.	604 Chevy Crate	450 carb	¾" adapter plate
d.	Chevy Steel Head	450 carb	¾" adapter plate
e.	Ford 347 JR	390 carb	No spacer

## 4) Chevy Crate Engines

- a. All Chevrolet Crate Engines must be per GM Performance Specs
- b. Exempt- Rod and Main Bearings may be Aftermarket, but same configuration
- c. No coated or Narrowed Bearings
- d. Deck height, Piston must be below deck .015 minimum
- e. Maximum over bore is .030 , replacement pistons must be same configuration and weight
- f. 1.5 Steel Rockers on 603
- g. 1.5 Roller Rockers on 604
- h. Standard single wire Valve spring on 603, GM Specs on seat and open pressures
- i. GM Beehive Springs on 604, GM Specs on seat and open pressures
- j. 603 and 604 installed spring heights per GM Specs
- k. After market shims and spring seats okay
- I. Crate Engine Camshaft will be checked in car at TDC and Max Lift if questionable cam will be removed for further inspection

# 5) Ford 347 JR Crate Engine

a. Ford Crate Engine must meet Ford Motorsports Manual

## 6) Suspension

- a. Coilover & Conventional Springs per LMSC rulebook
- b. Penske Shocks using Standard or High Flow Pistons only
- c. Bump Stops allowed on front only
- d. Tread Width & Wheelbase will be checked at 4" Inspection Height
- e. Spindles Must be Fabricated from multiple pieces and welded
- f. No Billet spindles cut and rewelded
- g. No Offset spindles
- h. Rear Axle Camber Plus or Minus ½ degree max

## 7) Safety

- a. Per LMSC Rulebook
- b. Window Net, Seat Belts and shoulder harness 5 years or newer

#### 8) Any and All Other Items, Parts, Dimensions or Measurements Per LMSC Rulebook

## 9) 2020 Ace Speedway Limited Late Model Tire Rules

- a. Opening night only All cars must purchase and run 4 New Hoosier F-45 Tires from Ace speedway
- b. Once tires are released from impound area, they must be put in grass area directly behind race car, or placed on pit road directly behind racecar or on racecar
- c. No race tires are allowed in trailer or in front of racecar
- d. No hand held or small tanks allowed to fill tires
- e. Must run track air or Compressed Nitrogen from large pressurized bottle
- f. May practice on race tires
- g. Once feature event is over , 15 minute time limit to get race tires to impound
- h. Extra time will be given to top 3 finishers for front stretch interviews and will be removed during post-race inspection at Inspection Tunnel
- i. Every event after opening night 2 New F-45's may be purchased from Ace Speedway
- j. All new tires purchased must be ran that event
- k. Each team is allowed to impound up to 6 tires at a time
- Any team that doesn't race opening night , MUST purchase 2 new and 2 SCUFF tires from Ace Speedway, No Exceptions
- m. Any team may purchase practice tires, BUT they will be marked differently and permanently for practice use only
- n. All new tires must complete at least half of the race distance to be eligible for new tires next event
- o. Any Race tire found to be tampered with or treated with be disqualified, last place money and points
- p. Any practice tires found on racecar during competition will be disqualified, last place money and points

## 10) Ace Speedway Officials reserve the right to adjust or delete any rule for Competition Equality