

3'-0" x 5'-0" DIRECT TRAFFIC DUCTED PULL BOX x 54" DEEP

MATERIAL LIST-K3660-DP54-DT-11

ITEM	PART NO.	DESCRIPTION	REBAR NO. /LOCATE	MOUNT/ WEIGHT
1	PB3660D-B42-05	42" BOTTOM SECTION	CG-3660D-B42-05(74)	4,448 lbs
2	PB3660-T12-DT-11	12" THK TOP SECTION W/A-1433 FRAME CAST-IN - DIRECT TRAFFIC	CG-3660-T12-DT-11	1,700 lbs
3	A-1433	(2) PC. TRAFFIC COVER, 36" x 54" OPENG ALHAMBRA FOUNDRY CAST IRON	MARKED "EDISON"	1,300 lbs
4	KNOCK OUT	6" x 7" DIAMETER SUMP x 1" DEEP	BASE SLAB	(1)
5	KNOCK OUT	28" x 28" DUCTED K.O. x 12" DEEP	BOTTOM SECTION	(2)
6	KNOCK OUT	10" x 16" K.O. x 3" DEEP	BOTTOM SECTION	(4)
7	KNOCK OUT	1" DIA. BLIND GROUND ROD HOLE	BOTTOM SECTION	(2)
8	55-35-06	7/8" DIA. x 6" GALV. VERTICAL PULL IRON	BOTTOM SECTION	(2) CORE MTD.
9	55-20-203	2 TON X 3 3/8" GALV. DOGBONE ANCHORS	BOTTOM SECTION TOP SECTION	(4) CORE MTD. (4) SHELL. MTD.

NOTES:

- PULL BOX DESIGNED PER ASTM C-857 LOAD DESIGNATION A-16 (AASHTO HS-20-44), TRAFFIC LOADING, USING 5,500 PSI CONCRETE AND ASTM A-706 GR. 60 STEEL REINFORCEMENT. PER CALCS. #31395.
- CAST IRON COVER DESIGNED FOR H-20 TRAFFIC LOADING.
- PULL BOX TO BE PLACED ON A MIN. 6" BASE OF CRUSHER RUN FOR EASE OF INSTALLATION AND EVEN LOAD DISTRIBUTION.

MINIMUM EXCAVATION SIZE:
4'-1" x 7'-6" x DEPTH REQD.

