

5 REASONS TO USE TILE SPACERS

1

Aesthetics - Spacers provide uniform spacing between tiles. When filled with suitable grout, makes tile assembly appealing.

2

No lippage - Spacers minimize lippage and chipping of tile corners is reduced.

3

Uniform spacing between tiles - Allows expansion & contraction of tiles, thus no cracking of tiles.

4

Efficient tiling - Use of spacers help in efficient tile laying, maintaining uniform levels. Eliminates readjusting or redoing of tiling.

5

No water seepage- Uniform tile spacing filled with Faralastik-100 Tile Joint doesn't allow water seepage through tile gaps.



Faralastik-100 Epoxy Grout

For Interior & Exterior Applications

Faralastik -100 is a stain free epoxy grout for wall application on tile & stones. Where hygiene is of utmost importance such as bathroom, kitchens, living room, airports and high traffic areas. It is water & chemical resistant joint filler which is available in 36 colors suitable for joints 2mm to 20mm, UV Resistant.

- Advantages :
- 100% Stainfree
 - Strong and durable
 - Chemical and temperature resistant
 - Anti bacterial & Anti Fungal
 - Colour-Fast
 - Easy to Install and Clean
 - Water cleanable When Fresh
 - Non-Cracking or Powdering
 - Available in a Range of 36 Colours
 -

- Recommended For :
- Ceramic floor & Wall Tile
 - Quarry tile
 - Marble
 - Stone
 - Pavers
 - Slate
 - Porcelain tile/Vitrified tile
 -

Coverage : Varies with Tile & Stone size and Grout Width

Packing : 1kg & 5kg units

Colour : 36 Colors

Compliance : Meets the Following Standards *ANSI : 118.3 *EN 13888: RG2 *VOC : Very Low

Tile Size X Thickness	Joint Width							
	in mm	1.5mm	2mm	3mm	4mm	6mm	8mm	10mm
100x100x3	342	264	177	133	90	68	55	46
150x150x4	385	296	198	149	100	75	61	51
200x150x5	348	269	181	136	91	69	55	46
150x300x6	340	263	175	132	88	66	53	44
300x300x6	515	394	263	198	132	100	80	67
450x300x7	530	405	270	202	135	101	81	68
600x450x8	664	506	337	253	169	127	101	85
600x600x8	750	591	394	295	197	148	119	99
600x900x11	654	515	343	258	171	129	103	86
900x900x12	749	590	393	295	197	148	118	99

Approximate sq.ft. coverage for glass mosaic

TILE SIZE	JOINT WIDTH	JOINT DEPTH
20mm x 20mm	1.5mm	2mm

Coverage : Approximate Sq Feet coverage per # 1 unit (5 kg) of Faralastik 100. As per the actual site the consumption vary accordingly. These Figures are for Inductive Purpose.



Faralastik Unsanded Grout

A carefully prepared blend of Portland cement, graded aggregates, polymer fortifiers and color-fast pigments. It is designed for joint width 1mm to 5mm, for porous & absorbent type tiles, non-vitreous clay tiles, and marble & glazed wall tiles. Suitable for internal and external applications.

Applications : Residential, commercial, external facades.

Mixing Ratio : Use approx.400 ml of water or FARALASTIK grout Admix for 1 kg of FARALASTIK Unsanded Grout.

Coverage: Varies with tiles size and grout width.

Packaging: 1kg

For Tile Joints 1mm-5mm

Colour : Available in a range of 36 colours

Compliance : Meets the following standards ANSI : 118.6 EN 13888: CG1 VOC : Very Low

- Advantages :
- Colour-Fast
 - Easy Maintenance
 - Weather Resistant
 - Non-Shrinking
 - Non-Cracking
 - Easy Application and Clean up
 - Non Wet Curing Required When used with FARALASTIK Grout Admix
 - Available in a Range of 36 Colours

- Recommended For :
- Ceramic floor & Wall Tile
 - Quarry tile
 - Marble
 - Stone
 - Pavers
 - Slate
 - Porcelain tile/Vitrified tile
 -

Coverage : Approximate sq.ft coverage per 10 kg Packet.

Tile Size X Thickness	Joint Width			
	1mm	2mm	3mm	4mm
100x100x3	1057	539	366	278
150x150x4	1182	599	404	305
200x150x5	1079	545	368	277
150x300x6	1047	528	356	268
300x300x6	1566	788	529	397
450x300x7	1608	808	542	406
600x450x8	2007	1007	674	504
600x600x8	2341	1174	785	587
600x900x11	2041	1023	684	511
900x900x12	2338	1171	782	585

For Any Support Contact

+91 9211 929 331

sales@faralastik.com

Follow us on



Visit www.faralastik.com

Favicrete Chemie & Company

Office No.212, Parmesh Business Centre -1, Plot No.20, Karkardooma Community Centre , Delhi -110092



Find us!



Premium Faralastik-100 Epoxy Grout & Unsanded Grout

Bright White				Canyon Red				Ivy				Aqua Blue			
Quarry Red				Mayan Red				Sierra Sunrise				Sapphire			
Silk				Sable				Inca Gold				Smoke Grey			
Almond				Hemp				Sage				Cadmium Red			
Antique White				Mushroom				Sky Blue				Saltillo			
Sauterne				Dusty Rose				Mocha				Alpine Bule			
Parchment				Buff				Sandstone				Burgundy			
								Marble Beige				Silver Shadow			
								Midnight Black				Slate Grey			