

GENERAL NOTES

- 1. APPLICABLE CODES:
- 1.1. 2023 FLORIDA BUILDING CODE, BUILDING, 8TH ED.
- 1.2. 2023 FLORIDA BUILDING CODE, ENERGY, 8TH ED.
- 1.3. 2023 FLORIDA BUILDING CODE, MECHANICAL, 8TH ED.
- 1.4. 2023 FLORIDA BUILDING CODE, FUEL GAS, 8TH ED.
- 1.5. 2023 FLORIDA BUILDING CODE, PLUMBING, 8TH ED.
- 1.6. 2023 FLORIDA FIRE PREVENTION CODE, 8TH ED.
- 1.7. 2023 FLORIDA BUILDING, ACCESSIBILITY, 8TH ED.
- 1.8. 2021 NFPA 101 LIFE SAFETY CODE W/ FLORIDA AMENDMENTS.
- 1.9. 2021 NFPA 70 NATIONAL ELECTRIC CODE.
- 1.10. 2021 NFPA 72 NATIONAL FIRE ALARM.
- 2. FIRE SPRINKLER SYSTEM: BUILDING IS FULLY SPRINKLERED.
- 3. SCOPE OF WORK: 440 SQ F.T. (FIRE RISER ROOM)
- 4. DESCRIPTION: SHELL BUILDING. TENANTS WILL APPLY FOR NEW PERMITS AND MODIFY THE SYSTEM TO THEIR SPECIFIC NEED BEFORE MOVING IN.
- 5. OCCUPANCY CLASSIFICATION AND LOAD:
- 5.1. TENANT A: JEWELRY/REALTY OFFICE STORE. 25 OCCUPANTS APPROX.
- 5.2. TENANT B: ALE HOUSE. 300 OCCUPANTS APPROX
- 6. CONSTRUCTION TYPE: II-B
- 7. SPRINKLER MONITORING SYSTEM CLASSIFICATION IS: CENTRAL STATION SERVICE.
- 8. SPRINKLER MONITORING SYSTEM TYPE IS: ADDRESSABLE.
- 9. ALL SPRINKLER MONITORING CIRCUITS TO BE CLASS B, POWER LIMITED.
- 10. VERIFY IN FIELD ALL DIMENSIONS. DO NOT SCALE THE DRAWINGS
- 11. ALL WORK SHALL BE OF HIGHEST QUALITY AND WORKMANSHIP.
- 12. NEW SPRINKLER MONITORING SYSTEM: THE NEW SPRINKLER MONITORING SYSTEM WILL MONITOR TWO (02) FIRE SPRINKLER RISER CONSISTING OF A WATER FLOW SWITCH AND CONTROL VALVE TAMPER SWITCH. THE WATERFLOW BEING MONITORED WILL ACTIVATE NOTIFICATION DEVICES UPON ALARM.
- 13. ALL DEVICES INSTALLED SHALL BE AS SPECIFIED IN THE DEVICE SCHEDULE, ANY INTENDED SUBSTITUTIONS SHALL FIRST BE SUBMITTED FOR REVISION AND APPROVAL.
- 14. INSTALLING CONTRACTOR SHALL VERIFY IN FIELD AND COORDINATE ANY INTERFERENCE WITH OTHER TRADES.
- 15. ALL ELECTRICAL CIRCUITS POWERING ANY AND ALL SPRINKLER MONITORING EQUIPMENT SHALL BE DEDICATED, SHALL HAVE A MEANS OF DISCONNECT EQUIPPED WITH A MECHANICAL LOCK—ON DEVICE, AND BE IDENTIFIED AS "SPRINKLER MONITORING CIRCUIT".
- 16. ALL CONTROL RELAYS SHALL BE LOCATED WITHIN 3' OF THE CONTROLLED DEVICE OR APPLIANCE.
- 17. ALL CONDUIT USED FOR SPRINKLER MONITORING SHALL BE DEDICATED FOR SPRINKLER MONITORING ONLY.
- 18. ALL CONDUIT AND CABLING INSTALLATION SHALL COMPLY WITH THE CURRENT NATIONAL ELECTRIC CODE N.F.P.A. 70.
- 19. ALL WALL, FLOOR AND CEILING PENETRATION SEALINGS SHALL BE RATED FOR THE SAME HOUR RATING AS THE WALL, FLOOR OR CEILING BEING PENETRATED.
- 20. ANY TWO OR MORE VISUAL NOTIFICATION APPLIANCES VISIBLE FROM THE SAME FIELD OF VIEW SHALL FLASH IN SYNCHRONIZATION.
- 21. SPRINKLER MONITORING SYSTEM WILL COMMUNICATE WITH CENTRAL STATION BY MEANS OF A CELLULAR COMMUNICATOR FOR THE PURPOSE OF FIRE DEPARTMENT NOTIFICATION.
- 22. ALL DEVICES INSTALLED IN WET LOCATIONS SHALL BE SUITABLE FOR SUCH AREA.
- 23. CENTRAL MONITORING STATION COMPANY: "CENTURY FIRE PROTECTION", LICENSE NUMBER: EF20001815, U.L.#S-7195-1, PH: 954-772-1700, FAX: 954-772-0500.




SCOPE OF WORK:


- INSTALL ALL ELECTRICAL BOXES, CONDUITS, SLEEVES AND, STUB UPS.
- INSTALL ALL CABLING.
- INSTALL ALL PANELS.
- SET ALL ADDRESSES AND INSTALL ALL INITIATING DEVICES SHOWN ON THE RISER AND FLOOR PLANS..
- SET ALL CANDELA/WATTS AND INSTALL ALL NOTIFICATION DEVICES SHOWN ON THE RISER AND FLOOR PLANS.
- PROGRAM AND TEST ALL PARTS OF THE SPRINKLER MONITORING SYSTEM TO FUNCTION AS SPECIFIED IN THE SEQUENCE OF OPERATION.
- DEMONSTRATE ALL PARTS OF THE SPRINKLER MONITORING SYSTEM WORK AS INTENDED DURING INSPECTIONS WITH AUTHORITY HAVING JURISDICTION.







PROJECT LOCATION



03 SITE KEY PLAN

NOT TO SCALE

1144 S CONGRESS AVE. PALM SPRING

PROJECT No:

CG-FLA-25-005


DATE:

4/5/2025

DWG-0001

SEE DRAWINGS

FA-01



				PANEL	LOAD SUMMAR	Y						STANDBY CUR	RENT (AMPS	S) ALARM CURF	RENT (AMPS)					
			PANEL COMPONENT	SUMMARY			QTY	PART NO		DESCRIPTION		CURRENT DRAW (A)	TOTAL (A)	CURRENT DRAW (A)	TOTAL					
						1	6808 Main Board	1	Main Board		1 x 0.19	= 0.19	1 x 0.25	= 0.25						
								•	CIRCUIT							1 PAN	EL P1 ((808)		
CIRCUIT SUMMARY							DACT1				1 x 0	= 0	1 x 0	= 0	PANEL P1 (6808) SUMMARY REPORT					
							L1 SK				1 x 0.00295	= 0.00295	1 x 0.03785	= 0.03785						
							N1				1 x 0	= 0	1 x 0.0535	= 0.0535	' 1					
									N2			1 x 0	= 0	1 x 0.129	= 0.129					
												TOTAL STANDBY CURRENT	0.19295	TOTAL ALARM CURRENT	0.47035					
				CIRCUIT DETA	ILS AND CALCU	ILATIONS		_				STANDBY (CURRENT	ALARM C	URRENT		POINT VOLTA			
SOURCE	MAX CAPACITY	TOTAL USED CAPACITY	AVAILABLE CAPACITY	CIRCUIT	AWG	SYMBOL	QTY	PART NO	DEVICE SETTING	CIRCUIT LENGTH	CIRCUIT RESISTANCE (Ω/ft)	CURRENT DRAW (A)	TOTAL (A)	CURRENT DRAW (A)	TOTAL (A)	STARTING CALCULATION VOLTAGE	END OF LINE VOLTAGE	VOLTAGE DRO		
6808 Main Board						(AIM)	6	SK-MONITOR				6 x 0.0004	= 0.0024	6 x 0.0055	= 0.033					
				L1 SK	18	(S)	1	SK-PHOTO-W w/B300-6		132' 0.00777	0.00777	1 x 0.0002	= 0.0002 1 x 0	1 x 0.0045	= 0.0045					
						F	1	SK-PULL-DA				1 x 0.00035	= 0.00035	1 x 0.00035 = 0.00035	= 0.00035					
				N1	14	F	1	SSM24-10		50'	0.00307	1 x 0	= 0	1 x 0.0535	= 0.0535	20.4v	20.38v	0.02v		
								₩P	1	P2GRKLED	110cd			1 x 0	= 0	1 x 0.094	= 0.094			
				N2	14	×	1	P2RLED	15cd	- 100' 0.00307	0.00307	1 x 0	= 0	1 x 0.035	= 0.035	- 20.4v	20.33v	0.07v		
					<u> </u>	·	SECONDAR	RY POWER SOU	RCE REQUIREM	MENTS										
													·	DBY TIME = 24 HOUR						
									OF OON DARK	TANDDY! OAD				M TIME = 5 MINUTES	2 411	DDOVU	DE (2) 4	21/7/1		
										STANDBY LOAD ALARM LOAD		0.19295 0.47035	x 24 x 0.08	= 4.63 = 0.04	3 AH 4 AH	PROVII BATTEI		2V / Al		
										RM LOAD SUBTOTA	AL	0.47033	λ 0.00	4.67	AH	RATTE	RIES @	24\/\		
										G FACTOR				x 1.	.25	ואורוסט	VILO (,		

01 BATTERY CALCS
N.T.S.

SECONDARY LOAD REQUIREMENTS (AMP HOURS)

			CURRENT SU	MMARY	POWER SUI	POWER SUMMARY		
			MAX. CIRCUIT CURRENT (A):	3	STARTING CALC. VOLTAGE:	20.40		
			TOTAL CIRCUIT CURRENT (A):	0.0535	MAX. VOLTAGE DROP:	0.02		
			SPARE CIRCUIT CURRENT (A):	2.95	VOLTAGE DROP %:	0.08 %		
P1 N1	LUMP SUM REI	PORT	SPARE CIRCUIT CURRENT %:	98.22 %	MIN. OPERATIONAL VOLTAGE:	16		
			MAX. CARD CURRENT (A):	6	END OF LINE VOLTAGE:	20.38		
			TOTAL CARD CURRENT (A):	0.22035	WIRE RESISTANCE (Ω/KFT):	3.07		
			SPARE CARD CURRENT (A):	5.78	TOTAL CIRCUIT LENGTH (FT):	50		
			SPARE CARD CURRENT %:	96.33 %	TOTAL CIRCUIT RESISTANCE (Ω):	0.307		
		CIRCUIT \	VIRING PROPERTIES: 'V' 14/2 FPLP/R NA	AC 14 AWG, 2 COND. SOLID	COPPER FPLP/R ANALOG UNSHIELDED			
		DISTA	NCE MEASURED USING DRAWN SEGME	ENT LENGTHS WITH 10.00 %	6 ADDITIONAL LENGTH CALCULATED			
SYMBOL	QUANTITY	PART NO	DESCRIPTION	CANDELAS	ALARM CURRENT (A)	TOTAL CURRENT (A		
F	1	SSM24-10	ALARM BELL 10" 24VDC, RED		0.0535	0.0535		
ALCULATION	METHODS:							
OTAL RESISTA	$NCE(\Omega) = WIRE$	RESISTANCE (9	Ω/FT) X 2 X TOTAL CIRCUIT LENGTH (FT)				
OTAL VOLTAG	E DROP = TOTA	L RESISTANCE	(Ω) X TOTAL CIRCUIT CURRENT (A)					
			CURRENT SU	MMARY	POWER SU	MMARY		
			MAX. CIRCUIT CURRENT (A):	3	STARTING CALC. VOLTAGE:	20.40		

<u> </u>			CURRENT SU	IMMARY	POWER SUI	MMARY
			MAX. CIRCUIT CURRENT (A):	3	STARTING CALC. VOLTAGE:	20.40
			TOTAL CIRCUIT CURRENT (A):	0.129	MAX. VOLTAGE DROP:	0.08
			SPARE CIRCUIT CURRENT (A):	2.87	VOLTAGE DROP %:	0.39 %
P1 N2 LUMP SUM REPORT			SPARE CIRCUIT CURRENT %:	95.70 %	MIN. OPERATIONAL VOLTAGE:	16
			MAX. CARD CURRENT (A):	6	END OF LINE VOLTAGE:	20.32
			TOTAL CARD CURRENT (A):	0.22035	WIRE RESISTANCE (Ω/KFT):	3.07
			SPARE CARD CURRENT (A):	5.78	TOTAL CIRCUIT LENGTH (FT):	100
			SPARE CARD CURRENT %:	96.33 %	TOTAL CIRCUIT RESISTANCE (Ω):	0.6140
			WIRING PROPERTIES: 'V' 14/2 FPLP/R NA			
		DISTA	NCE MEASURED USING DRAWN SEGME	ENT LENGTHS WITH 10.00 % AD	DDITIONAL LENGTH CALCULATED	
SYMBOL	QUANTITY	PART NO	DESCRIPTION	CANDELAS	ALARM CURRENT (A)	TOTAL CURRENT (A)
₩ _{WP}	1	P2GRKLED	2-WIRE, COMPACT HORN STROBE, WALL, RED, OUTDOOR	110CD	0.094	0.094
\bigvee_{\square}	1	P2RLED	2-WIRE, HORN STROBE, RED	15CD	0.035	0.035
CULATION N						
AL RESISTA	$NCE(\Omega) = WIR$	RE RESISTANCE (Ω /FT) X 2 X TOTAL CIRCUIT LENGTH (FT)		

02 VOLTAGE DROP CALCS
N.T.S.

LABEL	PART NO	APPLICATION	RESISTANCE MFT	AWG	DESCRIPTION
Α	18/2 FPLP/R	SLC	7.77	18	2 COND. SOLID COPPER FPLP/R ADDRESSABLE
Т	RJ-11	RJ-11	16.14	22	4 COND. UNSHIELDED COMMUNICATIONS CABLE
V	14/2 FPLP/R	NAC	3.07	14	2 COND. SOLID COPPER FPLP/R ANALOG UNSHIELDED
Z	18/2 FPLP/R	IDC	7.77	18	2 COND. SOLID COPPER FPLP/R ANALOG UNSHIELDED

	CELLULAR COMM		2228 N CONGRESS	AVE WATER FLOW SW•Z1•1 EOL 47k 2228 N CONGF	RESS AVE TAMPER SW•Z1•1 EOL 47k 2232 N CONGRES	SS AVE WATER FLOW SW•Z1•1 EOL 47k 2232 N C	CONGRESS AVE TAMPER SW•Z1•1 EOL 47k
FIRE ALARM CONTROL PANEL 1T 1A	P1•L1 SK•D001		1 SK•M002 P1•L1 SK•M003 KFLOW CELL TROUBLE		P1•L1 SK•M005 2228 N CONGRESS AVE TAMPER SW AIM 1A 1A	P1•L1 SK•M006 2232 N CONGRESS AVE WATER FLOW SW	P1•L1 SK•M007 2232 N CONGRESS AVE TAMPER SI
DEDICATED 120V 20 AMP CIRCUIT	P1•N2•01 15cd	P1•N2•02 EOL 4.7k 110cd WP	BACKFLOW•Z1•	1 BACKFLOW•Z1•2 EOL 47k			
1V-	P1•N1•01 EOL 4.7k						GROUND FLOOR

5.84 AH


	DEVICE LEGEND									
SYMBOL	QUANTITY	MANUFACTURER	PART NO	DESCRIPTION						
FACU	1	SILENT KNIGHT	6808	INTELLIGENT FIRE ALARM CONTROL PANEL WITH COMMUNICATOR						
CELL	1	TELGUARD	TG-7FS	COMMERCIAL FIRE CELLULAR ALARM COMMUNICATOR FOR LTE NETWORKS, TELCO						
(AIM)	6	SILENT KNIGHT	SK-MONITOR	MONITOR MODULE						
F	1	SILENT KNIGHT	SK-PULL-DA	DUAL ACTION PULL STATION						
S	1	SILENT KNIGHT	SK-PHOTO-W W/B300-6	WHITE, LOW-PROFILE PHOTOELECTRIC SENSOR W/BASE						
WF	2	GENERIC	WATERFLOW SWITCH	EXISTING (BY OTHERS)						
VS	2	GENERIC	VALVE TAMPER SUPERVISORY SWITCH	EXISTING (BY OTHERS)						
O _X	2	GENERIC	VALVE TAMPER SUPERVISORY SWITCH	EXISTING (BY OTHERS)						
₩P	1	SYSTEM SENSOR	P2GRKLED	2-WIRE, COMPACT HORN STROBE, WALL, RED, OUTDOOR						
$\bigvee_{}$	1	SYSTEM SENSOR	P2RLED	2-WIRE, HORN STROBE, RED						
F	1	SYSTEM SENSOR	SSM24-10	ALARM BELL 10" 24VDC, RED						
SS 120v	1	DITEK	DTK-120HW	OVERVOLTAGE PROTECTOR CIRCUIT PROTECTION-120V						
SS 2 24v	1	DITEK	DTK-2MHLP24BWB	2 PAIR / 4 WIRE SURGE MODULE W/BASE FOR PIV, NAC, IDC ETC.						
DOC	1	SPACE AGE ELECTRONICS	SSU00689	FIRE ALARM DOCUMENT BOX						

REVISION SCHEDULE CONTRACTOR:

	1144 S CONGRESS AVE. PALM SPRINGS FL. 3340 954-228-7539 Fax 954-482-0472
PROJECT No:	
CG-FLA-25-00)5
ATE:	
4/5/2025	
WG FILE:	
DWG-0001	
SCALE:	

SEE DRAWINGS

FA-03



PROJECT No:

CG-FLA-25-005

DATE:

4/5/2025

DWG-0001

SCALE:

SEE DRAWINGS

Sheet:

FA-04

REVISION SCHEDULE

01 02 03 03 04 05

CONTRACTOR: