

## Unlocking a Delta VFD

Before any parameters can be changed/set in the Delta MS300 VFD the Parameter lock must be unlocked; see instructions below.

*The factory password is 1234 but you must enter the numbers in reverse order.*

1. Hit the Enter button and using the Down Arrow set the screen to 00.\_ \_
2. After you see 00.\_ \_ push the Enter button and the screen will now show 00.00, use the Up Arrow to change the screen to show 00.07
3. When the screen shows 00.07 push the Enter button and you will see 0
4. Push in the Mode button until the 0 flashes, then use the Up Arrow to change from 0 to a blinking 4
  - Now push the Down/ Over button and you will see a blinking 0 in the space for a second digit. Using the Up button change that setting from 0 to 3, then using the Down/Over button move over another space and change that 0 to 2 and once more using the Down/Over you will see another 0, use the Up button to change that 0 to 1.
5. The screen should now show 1234, at this point hit Enter and you have unlocked the Parameter lock and can make any necessary changes.

Enter-↓00.-Enter-00.00-↑00.07-Enter-0-Mode-0 Flashes-↑4 Blinking↓←0-↑3- ↓←-0- ↑-2-↓←-0-↑-1-Enter

\*\*\*\*\*If you reset the power you will also relock the Parameter settings so if you need to make more changes you will need to go through the unlock process once again.\*\*\*\*\*