

Optical Coagulation Analyzer (OCG-102)

for Professional Point of Care



Feature Highlights

- Portable and convenient
- Dried-reagent test strips stored at room temperature for ready to use
- Build-in chargeable batteries for the circumstances without power supply
- Disposable test strip prevents cross contamination
- Stable external QC control
- Connect with LIS by Ethernet port for uploading test data
- Print results via external printer
- Cost effective to coagulation analysis test

Storage and transportation conditions

Temperature: -10 ℃ ~50 ℃

Relative humidity: 10%~90%

(without condensation)

Configurations

- Memory: 300 test results and 12 QC test results
- Display: 3.5 inch color touch screen
- Power supply:

Adapter Input: 100-240Vac, 50/60Hz, 0.5A Max

Adapter output: 9V, 2A Power input: 9V, 18W

- Batteries operation: Two 3.7V 18650 lithium batteries
- Batteries life: 300 complete charge-discharge cycles, depending on the frequency of use
- Printer: External serial port printer
- Dimension: 220 × 175 × 130 mm
- · Weight: 850g (without batteries)

Operation conditions

Temperature: 10 ℃ ~32 ℃

Relative humidity: 10%~80%

(without condensation)

Specifications



Test item: PT INR/APTT/ACT/TT/FIB

Sample type: Citrated venous whole blood

Sample volume: 20 µL

Time to result: ≤5 minutes

Precision: CV≤5%