



Face Mask Cover with Ties and Filter Slot

Supplies:

Fabric - 9x18 inches Stabilizer - Pellon SF 101 - 9x18 inches Ties - 1/4 inch Double Fold Bias Tape - 1/4 inches 1/4 Nose Piece - Bread Twisty Tie

www.cutiepiequiltsbyalana.com

Cut fabric to 9×18 inches and line back with a stabilizer like Pellon SF101.



Step 2

Fold the fabric at the top and bottom towards the wrong side 1/4 inch and iron. Repeat for a second fold.







Sew 1/8 inch seam across the top and the bottom to hold down the folds.





Step 4

Place the fabric right side up and fold the bottom up 1/2 inch. Bring the top down to meet the bottom fold. Coil each strap and insert at each of the four corner inside (at yellow clips).







Sew 1/4 inch seam down each of the sides. Flip right sides out and iron flat.







Step 6

Tuck the nose piece (twisty tie) underneath the top flap and sew along the previous seam. Sew a short seam 1 1/2 inches in on both sides to keep the nosepiece from sliding.







Begin your middle pleat by pinching I inch above the middle of the mask and fold down. Next do the top and bottom pleats.



Step 8

Begin at the top corner of the mask and sew a generous 1/4 inch seam around the right, bottom, and left sides of the mask. Pivot at each corner.







Once your sew 3 sides and arrive back at the top of the mask, turn the mask around and sew back along your seam, retracing your steps to add another layer of strength.





Step 10

Give the pleats a little press with the iron, and you are done! The insert slot will be accessible from the back of the mask.



