



Technical Specifications

Transmitter type:	Crystal controlled 2-stage
Calibration tolerance:	± 2.5kHz
Frequency stability:	± 2.5kHz, -20°C to 40°C
Pulse rate and width:	Typical on time 20ms, off time 1.1-2.0sec (controlled by astable circuit)
Pulse rate variation:	5%/volt, ± 20% for temperatures -20°C to +40°C
Battery:	Silver Oxide
Activation:	By removing magnet
Encapsulation:	Electrical resin, water-proof, specific gravity: 1.12

MODEL	BATTERY	BATTERY CAPACITY (days)			DIMENSIONS (mm)					WEIGHT (grams)	PRICE GROUP
		30 ppm*	40 ppm	55 ppm	A	B	C	D	E		
A4320	377	58	34	25	8	23	5	5	9	2.2	C
A4330	392	94	55	40	10	24	6	5	9	2.5	C
A4350	389	198	116	85	14	28	6	5	9	4.0	C
A4360	386	257 ⁺	150	110	14	28	7	5	9	4.5	C
A4370	357HC	441 ⁺	258	189	14	28	9	5	9	4.9	C

* 15 ms pulse width

⁺ Factors other than battery capacity may reduce life.

Warranty life is 50% of battery capacity.