

GAUGE Lubricants®

DIESEL ENGINE OIL:

Blended with selected quality 100% virgin Base oil and high-quality additives contains an oxidant, inhibitor, along with detergent dispersant and wear protection.

- Improve fuel economy in new and old vehicles.
- Keeps engine clean and protect against sludge, varnish, rust and wear.
- Resistance against viscosity breakdown.

1)- GAUGE SAE-40 API-CH4

2)- GAUGE SAE 15W-40 API CI4/SL

3)- GAUGE SAE 10W-40 API CI4/SL

SL #	Charisteristic Units	Test Methods	SAE-40	15W-40	10W-40
1	Density @ 15 oC	ASTM D1298	0.89	0.889	0.87
2	Viscosity @ 40 oC	ASTM D445	144	122	90
3	Viscosity @ 100 oC	ASTM D445	14.5	15.5	13.5
4	Viscosity Index	ASTM D2270	98	128	144
5	Flah Point COC, oC	ASTM D 92	230	230	236
6	Pour Point, oC	ASTM D97	-7	-17	-25
7	Total Base Numer, mgKOH/g	ASTM D2896	11	12	12
8	Color	ASTM D1500	3	2.5	2
9	Appearance	ASTM D4176	C&B	C&B	C&B

*Exact specification may slightly vary from above, but within international standards.

Packaging: 500ml, 1Ltr, 5ltr, 20ltr and 200ltrs drums.

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided.