

GAUGE Lubricants®

Hydraulic oil: AW/ISO/VG (HVI)

For industrial, construction and agricultural equipment.

Is engineered to prevent corrosion and wear of hydraulic cylinder and resist oxidation during use.

- High resistance to oxidation eliminates deposit formation.
- Superior water separation properties to allow for easy removal of water.
- Formulated to resist chemical break down, foaming and wear during heavy use.

1)- GAUGE Hydraulic oil AW/ISO 32

2)- GAUGE Hydraulic oil AW/ISO 46

3)- GAUGE Hydraulic oil AW/ISO 68

Also, available (AW/ISO 100, 150, 220, 320, 460, 680)

SL #	Charisteristic Units	Test Methods	32	46	68
1	Density @ 15 oC	ASTM D1298	0	0	0
2	Viscosity @ 40 oC	ASTM D445	29-34	44-48	64-70
3	Viscosity @ 100 oC	ASTM D445	5-6	6-7	8-9
4	Viscosity Index	ASTM D2270	98+	100+	105+
5	Flah Point COC, oC	ASTM D 92	220	225	230
6	Pour Point, oC	ASTM D97	-11	-13	-13
7	Total Base Numer, mgKOH/g	ASTM D2896	-	-	-
8	Color	ASTM D1500	2	2.5	2.5
9	Appearance	ASTM D4176	C&B	C&B	C&B

*Exact specification may slightly vary from above, but within international standards.

Packaging: 5ltr, 20ltrs and 200ltrs drums.

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided.