

## GAUGE Lubricants®

### **PETROL ENGINE OIL: fully synthetic**

Blended with superior quality fully synthetic base oil and superior quality additives contains full zinc, an oxidant, inhibitor, along with detergent dispersant and wear protection.

Recommended for use in modern 4,6 and 8 value cylinder multicom, multi value engines including VVT, also meets API services SL/SM/SN/CF, ILSAC GF4, GF5, ACEA A3/B4, MB226.5/229.3

- Designed to protect engines that operate under the most extreme conditions.
- Fortified to meet the oxidation and thermal stability and hot running engines.
- Shear resistance against viscosity breakdown.

1)- GAUGE fully synthetic SAE 5W-30 API SL/SN/SM

2)- GAUGE fully synthetic SAE 10W-40 API SL/SN/SM

SL #	Charisteristic Units	Test Methods	5W-30	10W-40	
1	Density @ 15 oC	ASTM D 1298	0.86	0.87	
2	Viscosity @ 40 oC	ASTM D445	60	98	
3	Viscosity @ 100 oC	ASTM D445	11	14	
4	Viscosity Index	ASTM D2270	150+	150	
5	Flah Point COC, oC	ASTM D 92	230	230	
6	Pour Point, oC	ASTM D97	-25	--20	
7	Total Base Numer, mgKOH/g	ASTM D2896	11	11	
8	Color	ASTM D1500	2	2	
9	Appearance	ASTM D4176	C&B	C&B	

\*Exact specification may slightly vary from above, but within international standards.

Packaging: 500ml, 1Ltr, 4ltr, 5ltr, 20ltrs and 200ltrs drums.

**Health and Safety:** Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided.