

GAUGE Lubricants®

PETROL ENGINE OIL:

Blended with selected quality 1005 virgin Base oil and high quality additives contains an oxidant, inhibitor, along with detergent dispersant and wear protection.

- Improve fuel economy in new and old vehicles.
- Keeps engine clean and protect against sludge, varnish, rust and wear.
- Resistance against viscosity breakdown.

1)- GAUGE SAE-40 API-SL

2)- GAUGE SAE 20W-50 API SL/CF

3)- GAUGE SAE 20W-40 4 STROKE

SL #	Charisteristic Units	Test Methods	SAE-40 PETROL	20W-50 PETROL	20W-50 4T
1	Density @ 15 oC	ASTM D 1298	0.89	0.891	0.891
2	Viscosity @ 40 oC	ASTM D 445	144	155	155
3	Viscosity @ 100 oC	ASTM D 445	14.5	18.5	18.5
4	Viscosity Index	ASTM D 2270	98	118	118
5	Flah Point COC, oC	ASTM D 92	230	236	236
6	Pour Point, oC	ASTM D 97	-7	-13	-13
7	Total Base Numer, mgKOH/g	ASTM D 2896	11	11	11
8	Color	ASTM D 1500	3	3	3
9	Appearance	ASTM D 4176	C&B	C&B	C&B