

TOPGRIT

2024

CATALOGUE



PREMIUM QUALITY

Quality is Our PRIDE

Due to the insistence on high quality and affordable pricing, Yanre Fitness stands out among manufacturers throughout China and worldwide. It's a reputation we are proud of.

RAW MATERIALS

Our attention to production quality is second to none. Our standards include using 3mm thickness pipe, using the best component parts and applying the most efficient assembly process. That's why our products stand the test of time.

AWARDS

We have received a number of awards for excellence of product quality (just list a few):

- Award for excellence in public sports in China
- Award for best enterprise
- Award for excellence in public sports in Anhui

SELF-DESIGN

They Copy, We Design

If quality is the soul of a company, then innovation is its heartbeat.

From the towering parabola designed 73 series to the simplest device for sky yoga, our standards of detail and quality can be seen in every welded joint, powder-coated finish, the material used, and the training angle.

We believe that training equipment should feel just right for the user. That's why we have been dedicated to build smooth and sturdy equipment, giving the user a sense of comfort and confidence that helps them get the best possible workout.

OVER 40 PATENTS

We hold more than 40 product patents (just list a few):

- Utility Model Patent Certificates Appearance
- Design Patent Certificates

实用新型专利证书
Certificate of Utility Model Patent

中华人民共和国国家知识产权局
STATE INTELLECTUAL PROPERTY OFFICE OF THE PEOPLE'S REPUBLIC OF CHINA

Model: 55F01

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Ergonomic design, accurate trajectory, smooth operation. two kinds of handle grips provide more exercise modes
4. Full shroud, 4mm thickness ABS virgin material, strong and durable
5. The weight selector is on the right side of the user, safe and convenient.
6. Cushion filled with MC high resilience foam material, high-grade PU leather, surface,, and integral ABS guard cover.
7. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
8. unified eye-catching color mark, in line with the safety requirements of equipment.

SPECIFICATIONS

N.W.: 249kg

Weight stacks: 90KG-18pcs / 180lbs-18pcs

Installation size: L1638*W1360*H1625mm



Model: 55F02

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Ergonomic design, accurate trajectory, smooth operation. two kinds of handle grips provide more exercise modes
4. Full shroud, 4mm thickness ABS virgin material, strong and durable
5. The weight selector is on the right side of the user, safe and convenient.
6. Cushion filled with MC high resilience foam material, high-grade PU leather, surface,, and integral ABS guard cover.
7. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
8. Unified eye-catching color mark, in line with the safety requirements of equipment.
9. POM material pulley , CNC processing, customized high quality bearing to withstand High-intensity and long-term use

SPECIFICATIONS

N.W.:243kg

Weight stacks : 90KG-18pcs / 180lbs-18pcs

Installation size : L1473*W716*H2340mm



Model: 55F03

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Ergonomic design, accurate trajectory, smooth operation. two kinds of handle grips provide more exercise modes
4. Full shroud, 4mm thickness ABS virgin material, strong and durable
5. The weight selector is on the right side of the user, safe and convenient.
6. Cushion filled with MC high resilience foam material, high-grade PU leather, surface,, and integral ABS guard cover.
7. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
8. Unified eye-catching color mark, in line with the safety requirements of equipment.

SPECIFICATIONS

N.W.:214kg

Installation size: 1235*715*2005mm

Weight stacks: 80kg-16pcs/160lbs-16pcs



Model: 55F04

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Ergonomic design, accurate trajectory, smooth operation. two kinds of handle grips provide more exercise modes
4. Full shroud, 4mm thickness ABS virgin material, strong and durable
5. The weight selector is on the right side of the user, safe and convenient.
6. Cushion filled with MC high resilience foam material, high-grade PU leather, surface,, and integral ABS guard cover.
7. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
8. Unified eye-catching color mark, in line with the safety requirements of equipment.

SPECIFICATIONS

N.W.: 203kg

Weight stacks: 70KG-14pcs/140lbs-14pcs

Installation size:L1120*W1260*H1625mm



Standig Biceps/Triceps

Model: 55F05

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Ergonomic design, accurate trajectory, smooth operation. two kinds of handle grips provide more exercise modes
4. Full shroud, 4mm thickness ABS virgin material, strong and durable
5. The weight selector is on the right side of the user, safe and convenient.
6. Cushion filled with MC high resilience foam material, high-grade PU leather, surface,, and integral ABS guard cover.
7. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
8. Unified eye-catching color mark, in line with the safety requirements of equipment.

SPECIFICATIONS

N.W.: 233kg

Weight stacks: 100KG-20pcs/200lbs-20pcs

Installation size: L1407*W804*H2227mm



Model: 55F06

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Full shroud, 4mm thickness ABS virgin material, strong and durable
4. The weight selector is on the right side of the user, safe and convenient.
5. Cushion filled with MC high resilience foam material, high-grade PU leather, surface, and integral ABS guard cover.
6. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
7. Unified eye-catching color mark, in line with the safety requirements of equipment.
8. Adjustable leg pad for different users

SPECIFICATIONS

N.W.: 219kg

Weight stacks: 100KG-20pcs/200lbs-20pcs

Installation size: L1787*W1213*H2227mm



Model: 55F07

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Ergonomic design, accurate trajectory, smooth operation. two kinds of handle grips provide more exercise modes
4. Full shroud, 4mm thickness ABS virgin material, strong and durable
5. The weight selector is on the right side of the user, safe and convenient.
6. Cushion filled with MC high resilience foam material, high-grade PU leather, surface,, and integral ABS guard cover.
7. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
8. Unified eye-catching color mark, in line with the safety requirements of equipment.

SPECIFICATIONS

N.W.:246kg

Installation size: 1665*1200*2425mm

Weight stacks: 80kg-16pcs/160lbs-16pcs



Ab crunch/Back extension

Model: 55F08

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Ergonomic design, accurate trajectory, smooth operation. two kinds of handle grips provide more exercise modes
4. Full shroud, 4mm thickness ABS virgin material, strong and durable
5. The weight selector is on the right side of the user, safe and convenient.
6. Cushion filled with MC high resilience foam material, high-grade PU leather, surface,, and integral ABS guard cover.
7. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
8. Unified eye-catching color mark, in line with the safety requirements of equipment.

SPECIFICATIONS

N.W.: 198kg

Weight stacks: 70KG-14pcs/140lbs-14pcs

Installation size: L1130*W1039*H1625mm



Leg extension/Lying leg curl

Model: 55F09

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Ergonomic design, accurate trajectory, smooth operation. two kinds of handle grips provide more exercise modes
4. Full shroud, 4mm thickness ABS virgin material, strong and durable
5. The weight selector is on the right side of the user, safe and convenient.
6. Cushion filled with MC high resilience foam material, high-grade PU leather, surface,, and integral ABS guard cover.
7. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
8. Unified eye-catching color mark, in line with the safety requirements of equipment.

SPECIFICATIONS

N.W. : 221kg

Weight stacks: 90KG-18pcs/180lbs-18pcs

Installation size: L1690*W950*H1625mm



Model: 55F10

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Ergonomic design, accurate trajectory, smooth operation. two kinds of handle grips provide more exercise modes
4. Full shroud, 4mm thickness ABS virgin material, strong and durable
5. The weight selector is on the right side of the user, safe and convenient.
6. Cushion filled with MC high resilience foam material, high-grade PU leather, surface,, and integral ABS guard cover.
7. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
8. Unified eye-catching color mark, in line with the safety requirements of equipment

SPECIFICATIONS

N.W.:204kgs

Installation size: 1620*715*1625mm

Weight stacks: 80kg-16pcs/160lbs-16pcs



Model: 55F11

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Ergonomic design, accurate trajectory, smooth operation. two kinds of handle grips provide more exercise modes
4. Full shroud, 4mm thickness ABS virgin material, strong and durable
5. The weight selector is on the right side of the user, safe and convenient.
6. Cushion filled with MC high resilience foam material, high-grade PU leather, surface,, and integral ABS guard cover.
7. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
8. Unified eye-catching color mark, in line with the safety requirements of equipment.

SPECIFICATIONS

N.W.: 271kg

Weight stacks: 100KG-20pcs/200lbs-20pcs

Installation size: L1610*W990*H1625mm



Model: 55F12

FEATURES

1. Main frame adopts 118*75*3.0mm semi elliptical pipe, functional area adopts 120*50*3.0mm flat oval pipe, movement arm adopts 80*40*3.0mm, joint pipe is 50*100*3.0mm flat oval pipe. All pipes are Q235 qualified.
2. Dual function training, conversion is simple, fast and safe.
3. Ergonomic design, accurate trajectory, smooth operation. two kinds of handle grips provide more exercise modes
4. Full shroud, 4mm thickness ABS virgin material, strong and durable
5. The weight selector is on the right side of the user, safe and convenient.
6. Cushion filled with MC high resilience foam material, high-grade PU leather, surface,, and integral ABS guard cover.
7. Wire cable imported from Japan , 7*19 coated wire can withstand 1400kg tension.
8. Unified eye-catching color mark, in line with the safety requirements of equipment.

SPECIFICATIONS

N.W.:204kgs

Installation size: 1620*715*1625mm

Weight stacks: 80kg-16pcs/160lbs-16pcs



TOPGRIT



www.mavalditradinginc.com



2B Jemara Bldg., Katipunan Ave.,
Brgy., San Bartolome, Quezon City



sales@mavalditradinginc.com



02-825-28952

