



SILENTTYPE (SR)



Features:

The optional generator set (SR) complies with CE safety standards, with special sheet metal surface technology, 3-5 years outdoor powder coating warranty and optional galvanized steel. 6-24 hours 100% load power, single layer fuel tank (optional double layer fuel tank), supporting tank capacity expansion design, suitable for rental, factory, outdoor, indoor and other applications.

Steady and strong design

- Strong supported chassis design of small vibration and stable running.
- Anti-collision design can meet the safety need.
- Strong lift design can reach the requirement of heavy load.

Safe and reliable running guarantee

Proper inlet and outlet air system design ensure the reliability of genset running in silent condition.

Environment friendly

• Removable full bunded fuel tank(option) prevent any leakage and easy for maintenance. silent type design meets the noise requirement.

Humanized operation and maintenance design

- Large inspecting and repairing space meets customer need.
- Top lifting point and fork lift holes are easy for transportation.
- Convenient external fuel filler device and optional transform interface is easy for customer to add fuel.
- Humanized operating interface and fully functionalized control system meets the needs of different kinds of customers.

Refined processing and surface treatment craft ensure the appearance of high quality and esthetics.

Engine: PERKINS / CUMMINS / VOLVO / KUBOTA / MTU / DOOSAN

All kinds of Chinese brand engines and others.











Standard genset details:

- Independent control panel, powerful and reliable system protection function.
- Emergency stop button
- Top center lifting ring
- Waterproof rubber strip
- Scientific and proper air inlet and outlet system
- · High-efficiency, Fire safety and foam soundproof
- Built-in large horizontal silencer
- High-intensity shock absorber
- · 6-24 hours 100% load power, single layer fuel tank, support tank capacity expansion design.
- · Power cable outlet design
- Built-in sprinkler
- Battery power switch (Anti-reverse charge, security protection)
- High-temperature ceramic insulation sets
- Mobile & hot protection fan & front radiator protection
- · Bottom traction tube for drag and drop and anti-skid, Bottom forklift holes for easy remove
- Vent cap
- External refueling port
- Domestic fuel inlet/outlet pipe and fuel gauge
- Standard hinges and door locks
- Access door with rock wool

Optional

- Special air inlet and outlet system
 Connector
 Super silent design
- 24h fuel tank, support tank capacity expansion design.
- The configuration of special climate, Desert, Island climate, Extremely cold, High altitude etc.
- Remote service cloud ("More Power" APP)
- Double layer fuel tank
- Galvanized canopy available
- Minimum operating noise level of 60dBA@7m







