

Tubes & Fittings




Scaffolding Tube



Item No	Description	Weight (Kgs)
10.09	0.9M Scaffolding Tube	3.27
10.08	1.2M Scaffolding Tube	4.36
10.07	1.5M Scaffolding Tube	5.45
10.06	1.8M Scaffolding Tube	6.54
10.05	2.5M Scaffolding Tube	9.08
10.04	3.0M Scaffolding Tube	10.90
10.03	4.0M Scaffolding Tube	14.53
10.02	5.0M Scaffolding Tube	17.79
10.01	6.0M Scaffolding Tube	21.35

Scaffolding Boards



Metal Boards
SPECIFICATION:
 Height: 38 mm & 45mm
 Width 210 mm & 225 mm
 Length: 1.0 m to 4.0 m (without hook type)
 Thickness: 1.2 mm/1.5mm/1.8mm/2.0mm
 Standard: BS1139/EN74
 Finishing: Hot Dipped Galvanized



Single Coupler
SPECIFICATION:
 Height: 38 mm & 45mm
 Width 210 mm & 225 mm
 Length: 0.73 m to 4.0 m (with hook type)
 Thickness: 1.2 mm/1.5mm/1.8mm/2.0mm
 Standard: BS1139/EN74
 Finishing: Hot Dipped Galvanized

Scaffolding Fittings



Single Coupler
SPECIFICATION:
 Size: 48.3mm Standard:
 En74 Finishing: Zinc Plated



Double Coupler
SPECIFICATION:
 Size: 48.3mm Standard:
 BS1139/EN74 Finishing: Zinc
 Plated / Hot Dipped Galvanized



Swivel Coupler
SPECIFICATION:
 Size: 48.3mm Standard:
 BS1139/EN74 Finishing: Zinc
 Plated / Hot Dipped
 Galvanized



Beam Clamp
SPECIFICATION:
 Size: 48.3mm
 Standard: Bs1139 / Bs1139 - 2.2
 /AS1576.2-91 Finishing: Zinc Plated /
 Hot Dipped Galvanized.



Base Plate
SPECIFICATION:
 Plate Size: 150mm x 150mm
 Plate Thickness: 5mm / 6mm
 Rod Size: 12mm (Dia) x 100mm (Height)
 Standard: BS1139/EN74
 Finishing: Hot Dipped Galvanized



Board Retaining Coupler
SPECIFICATION:
 Size: 48.3mm Standard:
 BS1139/EN74 Finishing: Zinc
 Plated / Hot Dipped Galvanized



Sleeve Coupler
SPECIFICATION:
 Size: 48.3mm Standard:
 BS1139/EN74 Finishing:
 Zinc Plated / Hot
 Dipped Galvanized



Joint Pin Coupler
SPECIFICATION:
 Size: 48.3mm Standard:
 BS1139/EN74 Finishing: Zinc
 Plated / Hot Dipped Galvanized

Scaffolding Accessories



Adjustable Base Jack
SPECIFICATION:
 Height: 600mm - 760mm
 Plate Size: 150mm x 150mm



Castor Wheel
SPECIFICATION:
 Height: 600mm - 760mm
 Plate Size: 150mm x 150mm
 Thickness: 5mm/6mm
 Standard: BS1139/EN74
 Finishing: Hot Dipped Galvanized

CMW Asia Construction and
 Development Corp.

BROCHURE

Services:

Scaffolding
 Scaffold Design
 Rope Access
 Construction
 Manpower

Contact Details:

sales.marketing@cmw-asiascaffolding.com
 www.cmwasiascaffolding.com
 09479993737 | 09197589139
 0132 Tabangao Ambulong, Lobo Road,
 Batangas City