

We support our "clients" success by bringing British standard of safety , expertise , and incorporating Philippine manpower skills in their projects.

# TUBE AND FITTING BROCHURE

.....

SCAFFOLDING  
ROPE ACCESS  
CONSTRUCTION  
MANPOWER



CMW ASIA | All Rights Reserved.



Landline: (043) 341 2273

Phone: 0917 501 9918 | 0915 325 385

0132 Tabangao Ambulong, Lobo Road,  
Batangas City, Philippines



Do You Have A  
**HEIGHT ACCESS PROBLEM?**  
We Can Help.

## OUR HISTORY - OUR VISION - OUR MISSION

Founded in 2016, CMW Asia management has vast experience in the international industrial services industry. CMW Asia has gained immediate footing in the Philippine setting with its reputation as a trustworthy supplier and service provider.

Our Vision is to bring in British standard of safety, expertise, and management and incorporating Philippine manpower skills in its projects.

Our Mission is to improve the profitability of our clients and their industrial assets by efficiency in the overall scaffolding management. We use the highest of quality of materials that meet the specifications and material characteristics of our clients and their working environments, specifically:

- British and Japanese standard tube and fitting materials
- Various system type and ring lock scaffolds

### SCAFFOLDING TUBE

The scaffolding tube provides the vertical support for the scaffold & strictly conforms to BS EN standards.



Item No	Description	Weight (Kgs)
10.09	0.9M Scaffolding Tube	3.27
10.08	1.2M Scaffolding Tube	4.36
10.07	1.5M Scaffolding Tube	5.45
10.06	1.8M Scaffolding Tube	6.54
10.05	2.5M Scaffolding Tube	9.08
10.04	3.0M Scaffolding Tube	10.90
10.03	4.0M Scaffolding Tube	14.53
10.02	5.0M Scaffolding Tube	17.79
10.01	6.0M Scaffolding Tube	21.35

### SCAFFOLDING FITTINGS

#### SINGLE COUPLER

**SPECIFICATION:**

Size: 48.3mm  
Standard: EN74  
Finishing: Zinc Plated



#### DOUBLE COUPLER

**SPECIFICATION:**

Size: 48.3mm  
Standard: BS1139/EN74  
Finishing: Zinc Plated / Hot Dipped Galvanized



#### SWIVLE COUPLER

**SPECIFICATION:**

Size: 48.3mm  
Standard: BS1139/EN74  
Finishing: Zinc Plated / Hot Dipped Galvanized



#### BASE PLATE

**SPECIFICATION:**

Plate Size: 150mm x 150mm  
Plate Thickness: 5mm / 6mm  
Rod Size: 12mm (Dia) x 100mm (Height)  
Standard: BS1139/EN74  
Finishing: Hot Dipped Galvanized



#### SLEEVE COUPLER

**SPECIFICATION:**

Size: 48.3mm  
Standard: BS1139/EN74  
Finishing: Zinc Plated / Hot Dipped Galvanized



#### BEAM CLAMP

**SPECIFICATION:**

Size: 48.3mm  
Standard: BS1139 / BS1139 - 2.2 / AS1576.2-91  
Finishing: Zinc Plated / Hot Dipped Galvanized.



#### BOARD RETAINING COUPLER

**SPECIFICATION:**

Size: 48.3mm  
Standard: BS1139/EN74  
Finishing: Zinc Plated / Hot Dipped Galvanized



#### JOINT PIN COUPLER

**SPECIFICATION:**

Size: 48.3mm  
Standard: BS1139/EN74  
Finishing: Zinc Plated / Hot Dipped Galvanized


### SCAFFOLDING BOARDS

#### METAL BOARDS

**SPECIFICATION:**

Height: 38mm & 45mm  
Width: 210mm & 225mm  
Length: 1.0m to 4.0m (without hook type)

Thickness: 1.2mm/1.5mm/1.8mm/2.0mm  
Standard: BS1139/EN74  
Finishing: Hot Dipped Galvanized



#### SINGLE COUPLER

**SPECIFICATION:**

Height: 38mm & 45mm  
Width: 210mm & 225mm  
Length: 0.73m to 4m (with hook type)

Thickness: 1.2mm/1.5mm/1.8mm/2.0mm  
Standard: BS1139/EN74  
Finishing: Hot Dipped Galvanized



### SCAFFOLDING ACCESSORIES

#### ADJUSTABLE BASE JACK

Adjustable Base Jack is used to distribute the load of scaffolding structure. Inserted at the base of standard placed at forged jack nut.

**SPECIFICATION:**

Height: 600mm - 760mm  
Plate Size: 150mm x 150mm



#### ADJUSTABLE BASE JACK

Castor Wheel can be used with 48.3mm outside diameter scaffold tube and with various system scaffolds. Wheels can be firmly secured to the tube to prevent displacement.

**SPECIFICATION:**

Height: 600mm - 760mm  
Plate Size: 150mm x 150mm

Thickness: 5mm/6mm  
Standard: BS1139/EN74

Finishing: Hot Dipped Galvanized

