

HIGH-QUALITY REMANUFACTURED

BETTIS® ACTUATORS

Southern Valve & Control is a high-quality remanufacturer of Bettis Actuators. Our leadership team has decades of valve actuator experience, including design, testing, manufacturing, sales, and modification. We're dedicated to the Reseller and Distributor model. We support various industries including Oil & Gas, Chemical Processing, Power Generation, Paper & Pulp, Industrial and Municipal.

CONTACT US TODAY!

SALES@SOVALVECONTROL.COM 337-608-8824 1109 MAURICE RD. BROUSSARD, LA 70518



SOVALVECONTROL.COM

BETTIS® ACTUATORS



ALL SVC REMANUFACTURED ACTUATORS ARE BACKED BY A 2-YEAR WARRANTY



G-SERIES

Power Source: Pneumatic

Product Type: Pneumatic Actuator

Actuation: Fail-Safe, Quarter-turn, Spring-Return, Double-Acting

Control Type: On/off

Valve Type: Ball, Butterfly, Plug, Triple Offset Valves, ¼ Turn Devices

Temperature: Standard Range, Optional High Temp or Low Temp Seals

Torque/Thrust: Spring-return to 3,000,000 lbs-in,

Double-acting to 6,000,000 lbs-in

Operating Pressure: Pneumatic 40 to 220 psig



CBB-SERIES

Power Source: Pneumatic

Product Type: Pneumatic Actuator

Actuation: Fail-Safe, Quarter-turn, Spring-Return, Double-Acting

Control Type: On/off

Valve Type:Ball, Butterfly, Plug, Triple Offset Valves, ¼ Turn Devices **Temperature:**Standard range, Optional High Temp or Low Temp Seals

Torque/Thrust: Spring-return to 3,000,000 lbs-in,

Double-acting to 6,000,000 lbs-in

Operating Pressure: Up to 150 psig



CBA-SERIES

Power Source: Pneumatic

Product Type: Pneumatic Actuator

Actuation: Fail-Safe, Quarter-turn, Spring-Return, Double-Acting

Control Type: On/off

Valve Type: Ball, Butterfly, Non-Lubricated Plug, ¼ Turn Devices

Temperature: Standard Range, Optional High Temp or Low Temp Seals

Torque/Thrust: Spring-return to 10,457 lbs-in,

Double-acting to 20,598 lbs-in

Operating Pressure: Pneumatic 40 to 150 psig



ALL SVC REMANUFACTURED ACTUATORS ARE BACKED BY A 2-YEAR WARRANTY



PRESSURE GUARD

Product Type: Manual Hydraulic Self-Contained

Product Type: Emergency Shutdown (ESD)

Actuation: Fail Safe, Quarter Turn, Spring-Return

Control Type: On/Off Fails Open or Closed

Valve Type: Ball, Butterfly, Plug, Triple Offset, ¼ Turn Valves
Temperature: Standard Low Temperature, Optional High Temp


Torque/Thrust: From 2,710 lbs-in. to 299,084 lbs-in

Operating Pressure: Min 200 psi, to 2,218 psi (Depending on Model Number)

IN ADDTION TO COMPLETE, REMANUFACTURED ACTUATORS WE ALSO OFFER THE FOLLOWING:

- ✓ Individual G-Series Modules (Springs, Power Module and Drive Module)
- **✓** Hydraulic Overrides
- Repair Kits (All Models)
- **✓** High Temp and Low Temp Seal Kits (All Models)
- **✓** Standard to Low Temp or Standard to High Temp conversion
- **✓** Repair and Reconditon of Customer Owned Equipment (All Models)

OUR BETTIS ACTUATOR SERVICES



FULL REMANUFACTURED

We provide a complete remanufactured actuator with 2-year warranty.

REPAIRS

You provide the actuator, and we'll replace all seals, repair or replace wear parts, and relubricate with a 2-year warranty.

REPAIRS BY EXCHANGE

Get a replacement actuator fast! Receive a fully remanufactured actuator with 2-year warranty in exchange for your old actuator upon receipt.