

GOVERNMENT OF ANDHRA PRADESH



BUILDINGS SoR: 2025-26

SCHEDULE OF RATES FOR BUILDINGS WORKS

FOR THE YEAR 2025-26

ALL ENGINEERING
DEPARTMENTS

Office of the Engineer-In-Chief (R&B) Buildings& RSW
Convener-Member,
Committee of Chief Engineers-Buildings-SoR

Procs.No. 20938/SOR/DCE(B)/EE(B)/DEE(B)/AEE/2021, Dt. 06.05.2025

Sub:- Printing of Buildings-SoR for all the Engineering Departments specific to the functioning of Building works – Buildings-SoR:2025-26– Communication of Buildings-SoR – Reg.,

Ref:- 1. G.O.Rt.No.95, T, R&B (R.1) Dept, dt:18.01.2015.
2. Minutes of Committee of Chief Engineers meetings for finalizing the Building-SoRs held on 16.04.2025

The Government of Andhra Pradesh have constituted a Committee of Engineer -in-Chiefs /Chief Engineers of Engineering departments dealing with Building works for finalizing and communicating Buildings-SoR (Civil & Electrical) vide G.O. 1st cited.

In accordance therewith, the Committee has in their concluding meeting dt:16.04.2025 finalized and approved the Buildings-SoR: 2025-26.

The rates for the Building items (Civil, Water Supply & Sanitary and Electrical items) are to be followed henceforth by all the concerned departments for building works. The rates for Labour, Common Material & Work items, Public Health items, Conveyance Rates of Materials & Hire charges are applicable as per approved and published Common SoR-2025-26 .

The Heads of Departments mentioned below are authorized to print the Buildings-SoR: 2025-26. Unauthorized printing & selling of the Buildings-SoR is strictly prohibited.

The Buildings SoR 2025-26 will come into force along with common SoR from the date decided by the BoCE.

The receipt of the proceedings may please be acknowledged.

Enclosures: Buildings SoR: 2025-26 as above

Sd/- XXXXXXXXXXXX 06.05.2025
Chief Engineer (R&B) Buildings, RSW ,
RR,& LW,
Convener-Member,
Committee of Chief Engineers-Buildings-SoR

To

- 1) Engineer-In-Chief, Public Health Engineering, Member, Flat No.504 &601, Garuda Enclave, Tadepalli , Guntur-522501.
- 2) Engineer-In-Chief,Panchayathraj, Member, Administration, PMGSY,APRRP- AIB,VQC,ZP compound, opp PWD Grounds, MG Road, Vijayawada - 520002.
- 3) Engineer-In-Chief,Tribal Welfare , Member, D.No.40-6-22A, Kandhari Hotel Road, Adjacent to Southern Spice, Revenue Colony, Vijayawada-520010.

- 4) Chief Engineer, A.P. Housing Board, Member,D.No. 5-21, Prasadampadu, Elururoad, Vijayawada -521108
- 5) Chief Engineer, A.P.Housing Corporation, S.P's river view apartments, 2nd floor, Tadepalli , Amaravati-522501..
- 6) Chief Engineer, APSRTC,RTC House, 1st Floor of PNBS,Vijayawada.
- 7) Chief Engineer, A.P. Medical Services and Infrastructure Developmen Corporation, Member, Autonagar, Mangalagiri, 522503. Andhrapradesh
- 8) Chief Engineer, Police Housing Corporation, AP, Member, Tadepalli, Vijayawada
- 9) Chief Engineer (R&B) Electrical, Member, M.G.Road, Vijayawada.
- 10) Chief Engineer, Civil TTD, Member, Administrative Building, KT Road, Tirupathi, 517501 -AP.
- 11) Chief Engineer, O/o Vijayawada Municipal Corporation, Canal road, Krishnalanka, Vijayawada ,520001A.P.

Copy to

1. The Engineer-in-Chief (Admn ,), R&B Department, M.G road, Vijayawada.
2. The Chief Engineer (QC), R&B Department, M.G road , Vijayawada .
3. The Chief Engineer (COT), 76-16-4A/1,1st floor, Iron Yard, Opp. to Ramayalam, Gollapudi, Vijayawada-520012.
4. The Chief Engineer, APRSCL, D.No.5-21, Hostel Road, Prasadampadu, Vijayawada-521108.
5. The Chief Engineer, APEWIDC, Door No.9-76 ,Sai fortune Heights , Block A, Vaddeswaram Village, Guntur District - 522 502.

INDEX FOR BUILDINGS SoR: 2025-26
(Civil, Water Supply & Sanitary, Electrical and Electro-Mechanical items)

Sl. No:	DESCRIPTION	Page No:	
		From	To
BUILDINGS – SoR:2025-26			
	Letter Dt. 15.06.2022 for Communication of Buildings SoR 2025-26 (Civil, Water Supply & Sanitary, Electrical and Electro-Mechanical items)	ii	iii
1	Index for Buildings SoR 2025-26 (Civil, Water Supply & Sanitary, Electrical and Electro-Mechanical items)	1	5
2	Preamble of BuildingsSoR-2025-26(Civil, Water Supply & Sanitary, Electrical and Electro-Mechanical items)	6	9
3	Building Civil Items - Buildings-SoR-2025-26	10	208
4	Note	209	209
5	Water Supply & Sanitary Items - Buildings-SoR-2025-26	210	258
6	Electrical and Electro-Mechanical Items – Buildings-SoR-2025-26		
7	Common SoR- 2025-26 for Labour Rates, Common Material & Work items, Conveyance Rates of Materials & Hire charges		
8	Public Health SoR 2025-26		

INDEX FOR BUILDING CIVIL ITEMS

Sl. No	SECTION	DESCRIPTION OF THE ITEM	FROM	TO
A		BRICKS & BUILDING BLOCKS	11	13
I	SUB-SECTION	ORDINARY CLAY BRICKS		
II	SUB-SECTION	FLY-ASH CEMENT/LIME SOLID BLOCKS		
III	SUB-SECTION	AUTOCLAVED CONCRETE BLOCKS		
B		NATURAL FLOORING STONES	13	14
I	SUB-SECTION	LOCALLY AVAILABLE FLOORING STONES		
II	SUB-SECTION	NATURAL FLOORING STONES - MARBLE		
III	SUB-SECTION	NATURAL FLOORING STONES - GRANITE		
C		WALL & FLOOR TILES	14	20
I	SUB-SECTION	NON-PORCELAIN CERAMIC FLOOR TILES		
II	SUB-SECTION	PORCELAIN VITRIFIED FLOOR TILES		
III	SUB-SECTION	CERAMIC WALL TILES		
IV	SUB-SECTION	PORCELAIN WALL TILES		
V	SUB-SECTION	GLASS MOSAIC TILES		
VI	SUB-SECTION	WALL CLADDING TILES		
VII	SUB-SECTION	EPOXY FLOORING, COVING		
D.		PAVING & INTERLOCKING TILES	20	23
I.	SUB-SECTION	TERRAZZO FLOOR TILES (PLAIN & CHEQUERED)		
II.	SUB-SECTION	CEMENT CONCRETE FLOOR TILES (PLAIN & CHEQUERED)		
III.	SUB-SECTION	PRE-CAST CONCRETE BLOCKS FOR PAVING		
IV.	SUB-SECTION	VINYL FLOORING		
E.		TIMBER & ROOFING MATERIALS	23	24
I	SUB-SECTION	MEDIUM TEAK WOOD		
II	SUB-SECTION	BEST TEAK WOOD		
III	SUB-SECTION	BURMA TEAK WOOD		
IV	SUB-SECTION	ASSAM TEAK WOOD		
V	SUB-SECTION	SAL/ COUNTRY WOOD		
VI	SUB-SECTION	ROOFING MATERIAL		

Sl. No	SECTION	DESCRIPTION OF THE ITEM	FROM	TO
F.		STEEL MATERIALS	25	27
I	SUB-SECTION	MILD STEEL MATERIALS		
II	SUB-SECTION	GALVANIZED STEEL MATERIALS		
III	SUB-SECTION	STAINLESS STEEL MATERIALS		
G.		FIXTURES FOR DOORS & WINDOWS	27	34
I	SUB-SECTION	TOWER BOLTS		
II	SUB-SECTION	HINGES		
III	SUB-SECTION	DOOR HANDLES		
IV	SUB-SECTION	ALDROPS		
V	SUB-SECTION	LATCHES		
VI	SUB-SECTION	DOOR CLOSURES		
VII	SUB-SECTION	FLOOR SPRINGS		
VIII	SUB-SECTION	MORTICE LOCKS		
IX	SUB-SECTION	OTHER ACCESSORIES		
H.		CONSTRUCTION CHEMICALS & ADMIXTURES	34	73
I	SUB-SECTION	REPAIRING & TREATMENT WORKS		
II	SUB-SECTION	INTERGRAL WATERPROOFING COMPOUND		
III	SUB-SECTION	PLASTICIZERS AND WATER REDUCING AGENT		
IV	SUB-SECTION	GROUTS		
V	SUB-SECTION	BONDING AGENTS		
VI	SUB-SECTION	SEALANTS		
VII	SUB-SECTION	PROTECTIVE WATERPROOF COATINGS / CEMENT BASED COATINGS :		
VIII	SUB-SECTION	ANTI CORROSIVE AGENTS		
IX.	SUB-SECTION	CURING COMPOUND & MISCELLANEOUS CHEMICALS		

Sl. No	SECTION	DESCRIPTION OF THE ITEM	FROM	TO
I.		GLASS MATERIALS	74	75
I	SUB-SECTION	PLAIN GLASS PANES		
II	SUB-SECTION	PIN HEADED GLASS PANES		
J.		PAINTS & POLISHES	75	78
I	SUB-SECTION	PRIMERS, FILLERS & BASES		
II	SUB-SECTION	DISTEMPER PAINTS		
III	SUB-SECTION	EMULSION BASED PAINTS		
IV	SUB-SECTION	SOLVENT BASED PAINTS		
V	SUB-SECTION	OIL BASED ENAMEL PAINTS		
VI	SUB-SECTION	TEXTURE PAINTS		
VII	SUB-SECTION	SPECIAL PAINTS		
K.		PARTICLE BOARDS	78	83
I	SUB-SECTION	MELAMINE FACED PLAIN PARTICLE BOARD		
II	SUB-SECTION	INSULATING PARTICLE BOARDS		
III	SUB-SECTION	MEDIUM DENSITY FIBRE BOARDS		
IV	SUB-SECTION	CEMENT BONDED PARTICLE BOARDS		
L.		PLYWOODS, LAMINATES & VENEERS	83	85
I	SUB-SECTION	MOISTURE RESISTANT (MR) GRADE		
II	SUB-SECTION	BOILING WATER RESISTANT (BWR) GRADE		
III	SUB-SECTION	VENEERED DECORATIVE PLYWOOD		
IV	SUB-SECTION	LAMINATES		
V	SUB-SECTION	COMMERCIAL VENEERS		
M.		CEILINGS, WALL PARTITIONS & WALL LININGS	85	108
I	SUB-SECTION	FALSE CEILINGs - TILES/ SHEETS		
II	SUB-SECTION	FALSE CEILINGs - SECTIONS & ACCESSORIES		
III	SUB-SECTION	WALL LINING & PANELLING		
IV	SUB-SECTION	PARTITIONS		

Sl. No	SECTION	DESCRIPTION OF THE ITEM	FROM	TO
N.		DOORS, SHUTTERS & FRAMES	109	147
I	SUB-SECTION	DOOR FRAMES		
II	SUB-SECTION	DOOR SHUTTERS WITHOUT FRAMES		
III	SUB-SECTION	DOORS WITH SHUTTERS & FRAMES		
IV	SUB-SECTION	CUP-BOARD DOORS		
P.		WINDOWS	148	174
I	SUB-SECTION	OPENABLE WINDOWS		
II	SUB-SECTION	SLIDING WINDOWS		
III	SUB-SECTION	VENTILLATORS		
Q.		STRUCTURAL GLAZING & CURTAIN WALLING	175	177
I	SUB-SECTION	FIXED GLAZING		
II	SUB-SECTION	STRUCTURAL GLAZING		
III	SUB-SECTION	CURTAIN WALLING		
S.	SECTION	DISMANTLING	177	178
T.	SECTION	READY MIX CONCRETE		
U.	SECTION	EXPANSION JOINT FILLERS	178	178
V.	SECTION	LABOUR CHARGES	179	184
W.	SECTION	MISCELLANEOUS ITEMS	184	192
X.	SECTION	MACHINERY & OTHER HIRE CHARGES	192	194
Y.	SECTION	POST TENSIONING WORKS	194	194
Z	SECTION	EXPANSION JOINTS	195	202
ZA	SECTION	ENERGY EFFICIENT ITEMS		
AB	SECTION	PEB's		
		CENTERING AND SCAFFOLDING CHARGES	203	208
		NOTE	209	209
		LIST OF RECOMMENDED BRANDS/ MANUFACTURERS		
		WATER SUPPLY AND SANITARY ITEMS	210	258

BUILDINGS SoR: 2025-26

(Civil, Water Supply & Sanitary, Electrical and Electro-Mechanical items)

PREAMBLE

1.0 INTRODUCTION

The Government have issued orders vide. G.O.Rt.No.95, T, R&B (R.1Buildings) Dept., dt:18.01.2015 constituting a Committee comprising of Chief Engineers of departments in-charge of execution of building works for finalization of Schedule of Rates for Buildings (Civil, Water Supply & Sanitary and Electrical and Electro-Mechanical items). The meeting of the above “SoR Committee of Chief Engineers for Buildings (Civil, Water Supply & Sanitary, Electrical and Electro-Mechanical items)” was convened several times during the year 2025 and finalized on 16.04.2025 with an objective to finalize and release the Buildings- SoR: 2025-26.

For Labour Rates the labour commissioner of AP recommendations are taken into account. BoCE labour rates are referred. For different sections of materials, market rates are obtained utilizing the services of member departments.

Meetings were conducted with the members of SABCA (Andhra Pradesh) to receive the feedback, certain market trends and data on need for updating the SoR rates for the year 2025-26

The market and price indices were found to be volatile and fluctuating. The base prices of the materials impacted by the variation due to HSD/ Petrol is considered. Similarly, the impact of international price variations due to recent developments were also considered.

The rates and procedures followed in Telangana SoR 2025-26 and the present rates taken in the guidance .

2.0 APPLICABILITY OF COMMON SoR – 2025-26

The rates of labour, common materials & work items, Public Health items, conveyance rates of materials & hire charges approved and published in Common SoR-2025-26 remain applicable. The specifications, stipulations & all other conditions of Common-SoR other than those specified in this context remain applicable.

3.0 QUOTATION ITEMS

Requests for inclusion of new items have been examined with respect to the market trends, technological changes, need for use and general practices. For those items where specific quotations from the manufacturers, suppliers or vendors are received, lowest quoted rates are considered and specifications were included in Buildings SoR: 2025-26.

4.0 OVERHEADS & CONTRACTORS PROFIT

- a. The provision of ‘Over Heads and Contractor’s Profit @ 13.615% shall be allowed in all the data items of the estimates and rates of the finished items in building works where ‘Contractors All Risk’ policy is dispensed with.
- b. It is reiterated that the provision of ‘Over Heads and Contractor’s Profit’ is applicable to Building works since the advent of the AP. Revised standard data-2009, which is approved by the Government in G.O.Ms.No.49 I&CAD (PW-Reforms) Dept., dated: 02-03-2009 and this component shall be operative on all the data items of the estimates and rates of the finished items published in **Buildings SoR for all original works and Renovation works subject** to the fulfillment of the conditions given

below:

- i. Site accommodation, setting up plant, access road, water supply, electricity and general site arrangements.
- ii. Office furniture, equipment and communications.
- iii. Expenditure on:
 - a) Corporate office of contractor.
 - b) Technical agents for site supervision. (Reimbursement to the technical agents provision is dispensed with where 'over heads and contractor's profit' provision is included in the data rates)
 - c) Documentation and "**as built**" drawings.
 - d) Mobilization/ de-mobilization of resources.
 - e) Labour camps with minimum amenities and transportation to work sites.
 - f) Light vehicles for site supervision including administrative and managerial requirements.
 - g) Laboratory equipment and quality control including field and laboratory testing. (**For all the works costing more than Rs.2 Crores contractors have to establish Quality Control laboratory**)
 - h) Minor T & P and survey instruments and setting outworks, including verification of line, dimensions, etc.
 - i) Watch and ward.
 - j) Traffic management/ Safety management during construction.
 - k) Expenditure on safeguarding environment.
- iv. Sundries.
- v. Financing Expenditure.
- vi. Sales/ Turn over tax is replaced with GST wef 01.07.2017. The rates arrived in this SoR are only basic rates which are exclusive of all taxes. However, as per the suggestion of BoCE, the provision towards Works Contract Tax as per applicable GST rates shall be added in the estimates.
- vii. Work Insurance/ compensation - Works insurance is dispensed with vide G.O. Ms. No: 61 Irrigation & CAD (PW: Reforms) Department Dt. 25-06-2013. Further, It is decided not to insist upon insuring all the building works as provision for this component is already deleted from the 'Overheads & Contractor's Profit' in building works.

5.0 OTHER GUIDELINES

1. Municipal Area Allowance, Agency or Tribal area allowance or any such allowance on the labour components of civil, water supply & sanitary items, Electrical and Electro-Mechanical items of building works shall be allowed wherever applicable as per the guidelines and preamble of Common SoR: 2025-26. For the building work estimates taken up in the notified Area Development Authorities constituted by the Government, the Area Allowance on the labour components of civil, water supply & sanitary items, Electrical and Electro-Mechanical items of building works may be allowed on specific recommendation from such Area Development Authorities.
2. For the structures where the Standard and High Strength Concretes vide IS: 456-2000 is required, mix design shall be carried out and rates may be arrived as per the rate analysis appended in the A.P. Revised Standard Data-2009.
3. Certain items in the SoR are deleted due to change in the specification and some not in use / non- availability in the market etc., Further some new items are added
4. The Electrical and Electro-Mechanical items and corresponding rates, as proposed by the Chief Engineer (R&B) Electrical have been considered in the Buildings SoR-2025-26.
5. The specifications of the aggregates for sizes and gradation and its adoption shall be as per IS 383-1970 and IS 2386 (Part 1 to Part 8).
6. No allowance towards 'Labour Importation & Labour Amenities' shall be added to the data as they are included in the provision of 'Over heads and contractor's profit'.
7. For all the materials, the basic rates given in the Buildings SoR are 'landing prices' at

the site which are exclusive of all taxes, except where mentioned specifically.

8. For Water Supply Sanitary items, the rates are enhanced over SoR 2024-25 rates by 0.8 %.
9. UPVC pipes were included in water supply and sanitary items.
10. PEB structures were incorporated in AB section
11. The estimate preparing and sanctioning authorities are requested to invariably enclose (i) quarry maps showing the shortest distance from the work site to the quarry from where materials are proposed to be carted and (ii) certificates of quality, quantity, and availability of materials in the identified quarries, for all those lead items of estimate at the time of technical sanctions.
12. For the materials where the basic rates are mentioned as 'quarry rates' in the Buildings SoR lead charges are to be added for the lead distances from the approved quarries as applicable. Wherever the term "carriage" or "conveyance" is used in schedule item, it shall be taken to include actual leads, lifts, loading, unloading and stacking to the satisfaction of the technical sanctioning authority while making the price-adjustments.
13. The conveyance charges per unit quantity of the materials are worked out, and provided in the schedule of rates reckoning
 - i) for head loads with increment of 50 m upto 150m
 - ii) for mechanical conveyance with increment of 1 KM.
14. For building works taken up in the hill areas where the materials are conveyed on ghat roads, the lead distance may be taken as 2.0 times of the existing length of the road for the purpose of leads only for conveyance of materials based on the certificate for the Ghat Road given by the Superintending Engineer concerned.
15. Loading and unloading charges are not payable for conveyance by head load.
16. Loading and Unloading charges are not payable for conveyance by mechanical means, for disposal of excavated material unless specified.
17. The rates for unloading of materials except earth, sand, gravel, coarse aggregate, rubble, size stone and cut stone, are inclusive of stacking wherever applicable.
18. The input rate for the water charges taken in Common Standard Schedule of Rates for the basic data is for the sources at site, any water lead as applicable may be allowed as per the conveyance charges.
19. Unless otherwise specified, all material rates shall be exclusive of all taxes, duties, levies, royalty/seigniorage.
20. Any errors, omissions, corrections or suggestions shall be brought to the notice of the 'COMMITTEE OF THE CHIEF ENGINEERS (Buildings SoR)' for corrective action.
21. For any new items to be included in the 'Schedule of Rates', recommendations with specific remarks of the respective departments should reach the 'Committee of Chief Engineers' well in advance.
22. The CWC (Ministry of Irrigation) has recommended that "where standard or schedule of rates are revised or where is necessary to do so, the primary guiding principle should be escalation in labour and material cost and not on trend of rates quoted by the contractors". The 'Committee of Chief engineers' (Buildings SoR) have considered the practicality and adoptability of the 'Buildings-SoR' in construction of the building projects in finalizing the 'Buildings-SoR'.
23. Wherever feasible, more emphasis is given to the technical specifications for the SoR items by removing the brand names of the manufacturers from the specification.
24. The technical specifications and the rates of the corresponding items given in the SoR are for the guidance only. The estimate preparing authorities are requested to obtain literature for usage / application of construction / water proofing materials, epoxies etc, from the manufacturers or authorized suppliers in the contract documents as per the requirement.
25. Steel Centering & Scaffolding charges for Shear walls, RCC walls and Water tank walls are incorporated in this Buildings SoR 2025-26. The rates given in the SoR are for both faces of the respective members. The measurement of centering charges shall be in 'sqm' for one face only and the centering charges given are for two faces of centering.
26. Double Grooved and Precoated extruded Mineral (Cement) roof tiles are introduced.

27. Clarity on nomenclature of Floors for data calculations is given as below

For	To Read
GF	F1
FF	F2
SF	F3
TF	F4

28. A separate section for Post Tensioning works is introduced.

6.0 CONCLUSION

1. The Committee of Chief Engineers on Buildings-SoR: 2025-26 (Civil & Electrical) has met in the chambers of Chief Engineer (R&B) Buildings& RSW, several times during the year 2025 and approved the Buildings SoR:2025-26, without any tax elements based on the representations received from various Engineering Departments. GST shall be provided as per GST Act in Part-B of the estimate during preparation of estimates.
2. SSR Rates for Civil, Sanitary & water supply and Electrical Items are purely for the guidance of the officers in preparation of estimates vide Para 113 of APPWD code. Authority who prepares the estimate is however responsible for proper rates as envisaged in Para 45 of APPWD code.
3. The rates published in the Buildings SoR are ceiling rates and the estimate preparing authorities are responsible for the correctness and reasonableness of the Technical Specifications and Rates adopted in the estimates.

BUILDING ITEMS

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
A.SECTION			BRICKS & BUILDING BLOCKS (ex-quarry price - excluding cost of conveyance, loading & unloading)		
I. SUB- SECTION			ORDINARY CLAY BRICKS		
1	MAT-00721	BMT-A.01	Common burnt clay bricks of class as per Table-1 of IS:1077-1992 Non-Modular of traditional size 23 x 11 x 7 cm	1000 Nos	8548
2	MAT-00748	BMT-A.02	Common burnt clay bricks of class as per Table-1 of IS:1077-1992 Modular of traditional size 19 x 9 x 9 cm	1000 Nos	9413
		II. SUB-SECTION	FLY-ASH CEMENT/LIME SOLID BLOCKS (ex-quarry price - excluding cost of conveyance, loading & unloading)		
3	MAT-00749	BMT-A.03	Fly ash cement/lime solid blocks with compressive strength of 75 kg/sq.cm - IS:12894-1990 - CLASS - 7.5 - 290 x 225 x 140 mm	Each	31
4	MAT-00750	BMT-A.04	Fly ash cement/lime solid blocks with compressive strength of 75 kg/sq.cm - IS:12894-1990 - CLASS - 7.5 - 290 x 200 x 140 mm	Each	31
5	MAT-00751	BMT-A.05	Fly ash cement/lime solid blocks with compressive strength of 75 kg/sq.cm - IS:12894-1990 - CLASS - 7.5 - 290 x 150 x 140 mm	Each	26
6	MAT-00752	BMT-A.06	Fly ash cement/lime solid blocks with compressive strength of 75 kg/sq.cm - IS:12894-1990 - CLASS - 7.5 - 290 x 112/100 x 140 mm	Each	21
7	MAT-00753	BMT-A.07	Fly ash cement/lime solid blocks with compressive strength of 75 kg/sq.cm - IS:12894-1990 - CLASS - 7.5 - 225 x 100 x 60 mm	Each	11
8	MAT-00754	BMT-A.08	Fly ash cement/lime solid blocks with compressive strength of 75 kg/sq.cm - IS:12894-1990 - CLASS - 7.5 - 145 x 225 x 140 mm	Each	16
9	MAT-00755	BMT-A.09	Fly ash cement/lime solid blocks with compressive strength of 75 kg/sq.cm - IS:12894-1990 - CLASS - 7.5 - 145 x 200 x 140 mm	Each	17
10	MAT-00756	BMT-A.10	Fly ash cement/ lime solid blocks with compressive strength of 50 kg/sq.cm - IS:12894-1990 - CLASS - 5 -290 x 225 x 140 mm	Each	33

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
11	MAT-00757	BMT-A.11	Fly ash cement/ lime solid blocks with compressive strength of 50 kg/sq.cm - IS:12894-1990 - CLASS - 5 -290 x 200 x 140 mm	Each	26
12	MAT-00758	BMT-A.12	Fly ash cement/ lime solid blocks with compressive strength of 50 kg/sq.cm - IS:12894-1990 - CLASS - 5 - Fly ash cement/ lime solid blocks with compressive strength of 50 kg/sq.cm - IS:12894-1990 - CLASS - 5 -290 x 150 x 140 mm	Each	26
13	MAT-00759	BMT-A.13	Fly ash cement/ lime solid blocks with compressive strength of 50 kg/sq.cm - IS:12894-1990 - CLASS - 5 -290 x 112/100 x 140 mm	Each	17
14	MAT-00760	BMT-A.14	Fly ash cement/ lime solid blocks with compressive strength of 50 kg/sq.cm - IS:12894-1990 - CLASS - 5 -225 x 100 x 60 mm	Each	09
15	MAT-00761	BMT-A.15	Fly ash cement/ lime solid blocks with compressive strength of 50 kg/sq.cm - IS:12894-1990 - CLASS - 5 -145 x 225 x 140 mm	Each	15
16	MAT-00762	BMT-A.16	Fly ash cement/ lime solid blocks with compressive strength of 50 kg/sq.cm - IS:12894-1990 - CLASS - 5 -145 x 200 x 140 mm	Each	14
17	MAT-00763	BMT-A.17	Supply of well burnt cinder aggregates as per IS: 2686-1977	1 Cum	706
III. SUB- SECTION			AUTOCLAVED CONCRETE BLOCKS <i>(landing cost - including cost of conveyance, loading & unloading)</i>		
			Supply of Aerated (Cellular) Autoclaved Concrete Blocks conforming to IS:2185 (Part-3) - 1984 and IS:6441-1972 of Compressive strength 3 N/mm²		
18	MAT-00764	BMT-A.18	600 x 200 x 100 mm	Each	44
19	MAT-00765	BMT-A.19	600 x 200 x 150 mm	Each	66
20	MAT-00766	BMT-A.20	600 x 200 x 200 mm	Each	88
21	MAT-00767	BMT-A.21	600 x 200 x 230 mm	Each	101
22(a)	MAT-05337	BMT-A.22	Supply of Cement based, Polymer modified Pre-mixed dry jointing mortar for laying AAC Blocks – Masonry Glue 110 or equivalent	1Kg	12.5
22(b)		BMT-A.23	Supply of Cement based, Polymer	1Kg	12.5

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			modified Pre-mixed bonding coat for plastering on smooth concrete/masonry surfaces.		
22(c)		BMT-A.24	Supply of Cement based, Polymer modified Pre-mixed dry plastering mortar for plastering walls, columns, ceilings.	1Kg	12.5
22(d)		BMT-A.25	Supply of Cement based, Polymer modified Pre-mixed dry mortar for fixing tiles on walls & floors	1Kg	12.5
B.SECTION			NATURAL FLOORING STONES (ex-quarry price – excluding cost of conveyance, loading & unloading)		
I.SUB- SECTION			LOCALLY AVAILABLE FLOORING STONES		
23	MAT-00768	BMT-B.01	Kadapa slab 40 mm thick and size not less than 0.457 M x 0.457 M	1 Sqm	136
24	MAT-00769	BMT-B.02	Kadapa slab 50 mm thick and size not less than 0.457 M x 0.457 M	1 Sqm	158
25	MAT-00770	BMT-B.03	Shahabad /Tandur Rough Stone slabs of minimum of 25 mm thick	10 Sqm	1255
26	MAT-00771	BMT-B.04	Shahabad / Tandur Rough Stone slabs of minimum 40 mm thick	10 Sqm	1638
27	MAT-00772	BMT-B.05	Polished Shahabad/ Tandur stone slabs of 15 to 18 mm thick	10 Sqm	2075
28	MAT-00773	BMT-B.06	Polished black Kadapa slabs minimum of 15 mm thick (0.457x0.457M)	10 Sqm	1910
29	MAT-00774	BMT-B.07	Polished Bethamcherla pure (marble type) white stone minimum 25 mm thick (0.254Mx0.254M)	10 Sqm	5000
30	MAT-00775	BMT-B.08	Polished Bethamcherla coloured stone minimum 25 mm thick (0.254M x0.254M)	10 Sqm	3480
31	MAT-00784	BMT-B.17	Polished black Kadapa slabs of all sizes between 25 - 30 mm thickness	10 Sqm	2000
II.SUB- SECTION			NATURAL FLOORING STONES –MARBLE		
32	MAT-00779	BMT-B.12	Polished Marble slabs of Dongari/ Adanga/ Marodh/ Rajgangpur etc., variety of thickness between 16 mm to 20 mm of sizes from 600 mm to 900 mm	1 sqm	810
33	MAT-00780	BMT-B.13	Polished Marble slabs of Dongari/ Adanga/ Marodh/ Rajgangpur etc., variety of thickness between 16 mm to 20 mm of sizes up to 600 mm	1 sqm	662
34	MAT-00781	BMT-B.14	Polished Marble slabs of any variety and	1 sqm	1115

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			gang saw cut (Such as Dongari/ Adanga/ Marodh/ Rajgangpur etc) 16 mm to 20 mm (average) thick (0.610 M width of any length)		
35	MAT-00782	BMT-B.15	Polished Marble Tiles of 8 - 10 mm thickness of all sizes and varieties	1 sqm	532
			NATURAL FLOORING STONES –GRANITE		
36		BMT-B.09 to BMT-B.16	DELETED		
		BMT-B.17	Galaxy Granite 18-20 mm thick upto 2.43M (Premium Quality)	1 sqm	2260
		BMT-B.18	Telephone Black Granite 18-20 mm thick upto 2.43M	1 sqm	1922
		BMT-B.19	Anti - skid Granite (Black) 18-20 mm thick upto 2.43M (For Stair case)	1 sqm	1585
		BMT-B.20	Tan brown Granite 18-20 mm thick upto 2.43M	1 sqm	850
		BMT-B.21	Cheeta Brown Granite 18-20 mm thick upto 2.43M	1 sqm	1245
		BMT-B.22	Jasmine Red 18-20 mm thick upto 2.43M	1 sqm	1245
		BMT-B.23	Moon White 18-20 mm thick upto 2.43M	1 sqm	1360
		BMT-B.24	Cheery Red 18-20 mm thick upto 2.43M	1 sqm	1130
		BMT-B.25	Multi red colour Granite 18-20 mm thick upto 2.43M	1 sqm	1245
C.SECTION			WALL & FLOOR TILES (Landing cost – including loading, cost of conveyance, unloading)		
I.SUB- SECTION			NON-PORCELAIN CERAMIC FLOOR TILES		
40	MAT-00785	BMT-C.01	Supply of Non-skid red or white full body Ceramic floor tiles of Size 300 mm x 300 mm and thickness between 7-8 mm and 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	396.40

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
	1	2	3	4	5
41	MAT-00786	BMT-C.02	Supply of Non-skid red or white full body Ceramic floor tiles of Size 450 mm x 450 mm and thickness between 7-8 mm and 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	390.00
42	MAT-00787	BMT-C.03	Supply of Non-skid red or white full body Ceramic floor tiles of Size 600 mm x 600 mm and thickness between 8-10 mm and 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	520.00
43	MAT-00788	BMT-C.04	Supply of Non-skid red or white full body Ceramic floor tiles of Scratch free-stain free and scratch free-nano finish of Size 600 mm x 600 mm and thickness between 8-10 mm and 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	530.00
II. SUB- SECTION			PORCELAIN VITRIFIED FLOOR TILES		
44	MAT-00789	BMT-C.05	ITEM DELETED		
45	MAT-00790	BMT-C.06	Supply of soluble salt porcelain vitrified tiles screen printed and polished of size 600 x 600 mm and thickness between 8-10 mm 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs.	1 sqm	425.00
46	MAT-00791	BMT-C.07	Supply of Nano polished /stain free soluble salt porcelain vitrified tiles screen printed of size 600 x 600 mm and thickness between 8-10 mm 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	462.00
47	MAT-00792	BMT-C.08	ITEM DELETED		
			Supply of Double charged / multi charged stain free full body porcelain vitrified tiles with double layer pigment of 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
	1	2	3	4	5
48	MAT-00793	BMT-C.09	Supply of Double charged / multi charged stain free full body porcelain vitrified tiles with double layer pigment of Size 600 x 600 mm and thickness between 8-10 mm and 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 Sqm	625.00
49	MAT-00794	BMT-C.10	Supply of Double charged / multi charged stain free full body porcelain vitrified tiles with double layer pigment of Size 800 x 800 mm and thickness between 9-11 mm and 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 Sqm	770.00
50	MAT-00795	BMT-C.11	ITEM DELETED		
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
51	MAT-00796	BMT-C.12	Supply of digital / polished glazed full body porcelain vitrified tiles with any type of design texture such as marble finish, wooden, bamboo, stone finishes etc., scratch less, stain free and Size 800 x 800 mm and thickness between 9-11 mm of 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	770.00
52	MAT-00797	BMT-C.13	Supply of digital / polished glazed full body porcelain vitrified tiles with any type of design texture such as marble finish, wooden, bamboo, stone finishes etc., scratch less, stain free and Size 900 x 900 mm and thickness between 9-11 mm of 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	960.00
52(a)		BMT-C.13(a)	Supply of glazed vitrified tiles with matt finish of size 600 x600mm and thickness between 9-10 mm 1st quality conforming to IS: 13711,IS: 13712,IS: 13630 (Parts 1 to 15) of any color and finish in all shades and designs .	1 sqm	825.00
53 to 59		BMT-C.14 to BMT-C.20	ITEMS DELETED		

III.SUB- SECTION			CERAMIC WALL TILES		
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
	1	2	3	4	5
60	MAT-00805	BMT-C.21	Supply of glazed red or white full body ceramic wall tiles of Size 200 x 300 mm / 245 mm x 325 mm and thickness 6 mm and 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	330.00
61	MAT-00806	BMT-C.22	Supply of glazed red or white full body ceramic wall tiles of Size 300 x 450 mm / 320 mm x 400 mm and thickness 6 mm and 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	426.00
62	MAT-00807	BMT-C.23	Supply of glazed red or white full body ceramic wall tiles of Size 300 x 600 mm and thickness between 6-8 mm and 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	556.00
IV.SUB-SECTION			PORCELAIN WALL TILES		
63	MAT-00808	BMT-C.24	Supply of glazed full body porcelain wall tiles of size 300 x 600 mm with any type of design texture such as marble finish, wooden, bamboo, stone finishes etc., scratch less, stain free and thickness between 6-8 mm 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	597.00
64	MAT-00809	BMT-C.25	Supply of digital / polished glazed full body porcelain wall tiles of size 300 x 600 mm with any type of design texture such as marble finish, wooden, bamboo, stone finishes etc., scratch less, stain free and thickness between 6-8 mm 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	599.00

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
	1	2	3	4	5
65	MAT-00810	BMT-C.26	Supply of digital / polished glazed full body porcelain highlighter wall tiles of size 300 x 600 mm with any type of design texture such as marble finish, wooden, bamboo, stone finishes etc., scratch less, stain free and thickness between 6-8 mm 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	605.00
66	MAT-00811	BMT-C.27	Supply of screen printed glazed full body porcelain wall tiles of size 300 x 600 mm with any type of design texture such as marble finish, wooden, bamboo, stone finishes etc., scratch less, stain free and thickness between 6-8 mm 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	631.00
67	MAT-00812	BMT-C.28	Supply of glazed full body porcelain wall tiles of size 400 x 600 mm with any type of design texture such as marble finish, wooden, bamboo, stone finishes etc., scratch less, stain free and thickness between 6-8 mm 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	710.00
68 to 70		BMT-C.29 to BMT-C.31	ITEMS DELETED		
71	MAT-00816	BMT-C.32	Providing and fixing wall dado with epoxy emulsion grout/ synthetic/ resin based adhesive in specified thick and pointing with specified colour epoxy grout excluding cost of tiles	1 sqm	345
72	MAT-00817	BMT-C.33	Providing and fixing wall dado with cement based adhesive in specified thick and pointing with specified colour epoxy grout excluding cost of tiles	1 sqm	177
73	MAT-00818	BMT-C.34	Providing and fixing flooring with full depth jointing and pointing to the Vitrified/ Ceramic Tile flooring in specified thick for tiles of any sizes with epoxy emulsion grout/ synthetic / resin adhesive in width of 3-5 mm with Nylon spacers excluding cost of tiles.	1 sqm	352

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
	1	2	3	4	5
74	MAT-00819	BMT-C.35	Providing and fixing flooring with full depth jointing and pointing to the Vitrified/ Ceramic Tile flooring in specified thick for tiles of any sizes with cement based adhesive in width of 3-5 mm with Nylon spacers excluding cost of tiles .	1 sqm	178
75	MAT-00820	BMT-C.36	Providing and fixing flooring with full depth jointing and pointing to the Marble/ Granite flooring for any sizes with epoxy emulsion grout/ synthetic / resin based adhesive in width of 3-5 mm excluding cost of tiles.	1 sqm	645
76	MAT-00821	BMT-C.37	Providing and fixing flooring with full depth jointing and pointing to the Marble/ Granite flooring for any sizes with cement based adhesive in width of 3-5 mm excluding cost of tiles.	1 sqm	350
77		BMT-C.50	Breeze blocks of size 8'x8" and thickness 60mm	1 sqm	45
78		BMT-C.51	Ventilations of size 12"x18" and thickness 40mm	1 sqm	101
79		BMT-C.52	Ventilations of size 12"x24" and thickness 40mm	1 sqm	135
V.SUB- SECTION			GLASS MOSAIC TILES		
79 to 81		BMT-C.38 to BMT-C.40	ITEMS DELETED		
VI.SUB- SECTION			WALL CLADDING TILES		
82	MAT-00825	BMT-C.41	Supply of glazed full body porcelain tiles for external cladding purposes of any size and thickness between 6-10 mm 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs.	1 sqm	594
83	MAT-00826	BMT-C.42	Supply of glazed red or white full body ceramic tiles for external cladding purposes of any size and thickness between 5-7 mm 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	468
84	MAT-00827	BMT-C.43	Supply of glazed red or white full body ceramic tiles for external cladding purposes of any size and thickness between 10-12 mm 1st quality conforming to IS:13711, IS:13712, IS:13630 (Parts 1 to 15) of any colour and finish in all shades and designs	1 sqm	578

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
	1	2	3	4	5
85	MAT-00828	BMT-C.44	ITEM DELETED		
86	MAT-08731	BMT-C.45	Brick tiles of size 230mm x 75 mm and 12mm thick	1 sqm	475
87	MAT-08732	BMT-C.46	Natural stone (Bethamcherla or equivalent) of size not exceeding 300mm x300mm and 18-20mm thick	1 sqm	595
88	MAT-08733	BMT-C.47	Terracotta tiles size 125mm x 200mm and 12-15mm thick	1 sqm	426
VII SUBSECTION			EPOXY FLOORING, COVING		
89	MAT-08734	BMT-C.48	Supply and application of epoxy flooring of light green or light blue colour seamless joint free finish with 3mm thickness and anti slip & water washable chemical resistance durable and non particle shedding with attractive finishing	1 sqm	1220
90	MAT-08735	BMT-C.49	Supply and application of epoxy coving 50mmx50mm width at the corners of the walls	1 RM	530
VIIISUB-SECTION			ROOF TILES		
91		BMT-C.53	Supply and installation of Double grooved and precoated extruded mineral (cement) roof tiles of size 420 mmx330 mm of corrugated profile tiles with variable overlapping for coverage of 1-1.2 per tile with European standards BEEN 490:2004		
91 (a)		BMT-C.53(a)	Monotone colour ; Orange, red	1 Sqm	1250
91(b)		BMT-C.53 (b)	Dual colours : Antique Red, Grey, Brown etc	1 Sqm	1390
91(c)		BMT-C.53 (c)	Premium Colors : Antique green and blue	1 Sqm	1720
92		BMT-C.54	Supply and installation of precoated extruded mineral (cement) ridge tiles and other fittings of same brand		
92. (a)		BMT-C.54 (a)	Monotone colour ; Orange, red	1 Sqm	566
92. (b)		BMT-C.54(b)	Dual colours : Antique Red, Grey, Brown etc	1 Sqm	639
92. (c)		BMT-C.54 (c)	Premium Colors : Antique green and blue	1 Sqm	735

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
	1	2	3	4	5
93		BMT-C.55	Supply of Imported Heat reflective cum Water Proof Sheet Veltiun RadenSheild of thickness 550 micron+/-10 microns with Nail Sealant for complete water tightness, Poly proplene Spun bound layer for better strength and Aluminium Foil for Heat Reflection of size per roll is 1.25X50m for coverage of 62.5 Sqmtrs with required tape for joints and overlapping.	1 Sqm	745
94		BMT-C.56	Supply of Imported UV Resistant & Flame Resistant Stretchable Corrugated surface with Special adhesive for avoiding Cement Motor under Ridges size of Roll is 5MX25Cms	1 Sqm	1090
95		BMT-C.57	Supply of High Quality Aluminium Bent valleys which can easy foldable as per site condition to prevent back flow of rain Water Back Flow and to avoid leakages at Valley Area of size 1.2MX36Cm of any Reputed make	1 sqm	960
D.SECTION			PAVING & INTERLOCKING TILES		
I.SUB- SECTION			TERRAZZO FLOOR TILES (PLAIN & CHEQURED) (landing cost - including cost of conveyance, loading & unloading)		
96	MAT-00829	BMT-D.01	Supplying precast terrazzo chequered tiles conforming to IS: 13801 using marble aggregates of size 10 mm , sand, marble powder, white cement pigments etc., with terrazzo topping not less than 6 mm of tiles overall size not less than 20 mm thick of any coloured shades.	1 sqm	331
97	MAT-00830	BMT-D.02	Supplying precast terrazzo tiles conforming to IS: 13801 using marble aggregates of size 10 mm , sand, marble powder, white cement pigments etc., with terrazzo topping not less than 6 mm of tiles overall size not less than 20 mm thick white shades.	1 sqm	347
98	MAT-00831	BMT-D.03	Supplying precast terrazzo plain tiles conforming to IS: 13801 using marble aggregates of size 10 mm , sand, marble powder, white cement pigments etc., with terrazzo topping not less than 6 mm of tiles overall size not less than 20 mm thick any coloured shades.	1 sqm	357

II.SUB- SECTION			CEMENT CONCRETE FLOOR TILES (PLAIN & CHEQUERED)		
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
	1	2	3	4	5
99	MAT-00832	BMT-D.04	Supplying plain Cement Concrete general purpose tiles conforming to IS: 13801 using aggregates, cement, pigments of size 300 x 300 mm and thickness 20 mm of any shades.	1 Sqm	268
100	MAT-00833	BMT-D.05	Supplying Chequered Cement Concrete heavy duty tiles conforming to IS: 13801 using aggregates, cement, pigments of size 300 x 300 mm and thickness 20 mm of any shades.	1 Sqm	315
101	MAT-00834	BMT-D.06	Supplying plain Cement Concrete general purpose tiles conforming to IS: 13801 using aggregates, cement, pigments of size 300 x 300 mm and thickness 25 mm of any shades.	1 Sqm	326
102	MAT-00835	BMT-D.07	Supplying Chequered Cement Concrete heavy duty tiles conforming to IS: 13801 using aggregates, cement, pigments of size 300 x 300 mm and thickness 25 mm of any shades.	1 Sqm	366
103	MAT-00836	BMT-D.08	Supplying plain Cement Concrete general purpose tiles conforming to IS: 13801 using aggregates, cement, pigments of size 400 x 400 mm and thickness 25 mm of any shades.	1 Sqm	342
104	MAT-00837	BMT-D.09	Supplying Chequered Cement Concrete heavy duty tiles conforming to IS: 13801 using aggregates, cement, pigments of size 400 x 400 mm and thickness 25 mm of any shades.	1 Sqm	347
105	MAT-00838	BMT-D.10	Supply of high strength Cement Concrete plain Step tile with edge half rounded and grooved conforming to IS: 13801 using aggregates, cement, pigments of regular colour, design and of 25 mm thickness	1 Sqm	525
106	MAT-00839	BMT-D.11	Supply of high strength Cement Concrete terrazzo/pre-polished/chequered Step tiles with edge rounded and grooved conforming to IS: 13801 using aggregates, cement, pigments of any premium colour, design and of 25 mm thickness	1 Sqm	552
III.SUB- SECTION			PRE-CAST CONCRETE BLOCKS FORPAVING		
107	MAT-00840	BMT-D.12	Supply of precast concrete blocks for paving of M-30 grade and thickness not less than 50 mm for Non-traffic areas conforming to IS 15658:2006 in all shapes and designs as per the manufacturer's specification	1 Sqm	368

108	MAT-00841	BMT-D.13	Supply of precast concrete blocks for paving of M-35 grade and thickness not less than 60 mm for Light traffic areas conforming to IS 15658:2006 in all shapes and designs as per the manufacturer's specification	1 Sqm	410
109	MAT-00842	BMT-D.14	Supply of precast concrete blocks for paving of M-40 grade and thickness not less than 80 mm for Medium traffic areas conforming to IS 15658:2006 in all shapes and designs as per the manufacturer's specification	1 Sqm	578
110	MAT-00843	BMT-D.15	Supply of precast concrete blocks for paving of M-50 grade and thickness not less than 100 mm for Heavy traffic areas conforming to IS 15658:2006 in all shapes and designs as per the manufacturer's specification	1 Sqm	641
111	MAT-00844	BMT-D.16	Supply of precast concrete blocks for paving of M-55 grade and thickness not less than 120 mm for very heavy traffic areas conforming to IS 15658:2006 in all shapes and designs as per the manufacturer's specification	1 Sqm	735
112	LAB-01180	BMT-D.17	Labour charges for laying & fixing of precast concrete blocks for paving of all grades, any thickness, all sizes & shapes including all labour charges for loading & unloading, laying to desired lines and levels complete excluding cost of cement, sand, water, electricity etc	1 Sqm	210
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
	1	2	3	4	5
113	MAT-08736	BMT-D.21	Supply of Glass Fibre Reinforced Concrete Tiles of size 300 x 300 mm /400 x 400 mm and thickness of not less than 25mm heavy duty conforming to IS 13801 in all shapes and designs as per the manufacturer's specification	1 Sqm	448
114	MAT-08737	BMT-D.22	Supply of Glass Fibre Reinforced Concrete Pavers of size 225 x 175 mm and thickness of not less than 60mm heavy duty conforming to IS 15658:2006 in all shapes and designs as per the manufacturer's specification	1 Sqm	606
IV.SUB-SECTION			VINYL FLOORING		

115	MAT-05338	BMT-D.18	Vinyl Flooring Sheets/ tiles having a nominal total thickness of 2 mm with a wearing surface impregnated polyurethane homogeneous mixture of PVC, Plasticizers, Urethane, color pigments with wearing resistance and Fire Resistance as per standards	1 Sqm	622
116	MAT-05339	BMT-D.19	Vinyl Composition Floor Tiles of size 305 mm x 305 mm having an overall thickness of 2.0mm with a wearing surface impregnated polyurethane homogeneous mixture of PVC, Plasticizers, Urethane, color pigments with wearing resistance and Fire Resistance as per standards	1 Sqm	642
117	MAT-05340	BMT-D.20	Vinyl Flooring Sheets or tiles having a nominal total thickness of 1.5 mm with a wearing surface impregnated polyurethane homogeneous mixture of PVC, Plasticizers, Urethane, color pigments with wearing resistance and Fire Resistance as per standards	1 Sqm	396
118		BMT-D.21	Grass pavers of size 10"x10" and thickness 60mm	1 Sqm	53
119		BMT-D.22	Grass pavers of size 12"x12" and thickness 60mm	1 Sqm	74
120		BMT-D.23	Roof cool tiles of size 10"x10" and thickness 15mm	1 Sqm	32
	E.SECTION		TIMBER & ROOFING MATERIALS <i>(Landing cost – including cost of conveyance, loading & unloading) Note: Before proposing the Teak Wood/Items, the estimating authorities shall obtain prior approval from the competent authority</i>		
I.SUB- SECTION			MEDIUM TEAK WOOD		
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
	1	2	3	4	5
121	MAT-00846	BMT-E.01	Medium Teak Wood scantlings: up to 2.0 M	1 cum	86688
122	MAT-00847	BMT-E.02	Medium Teak Wood scantlings: 2.0 to 3.0 M	1 cum	99288
123	MAT-00848	BMT-E.03	Medium Teak Wood scantlings: above 3.0 M	1 cum	111834

124	MAT-00849	BMT-E.04	Medium Teak Wood Plancks: any thickness	1 cum	17489
II.SUB- SECTION			BEST TEAK WOOD		
125	MAT-00850	BMT-E.05	Best Teak Wood scantlings: up to 2.0 M	1 cum	144749
126	MAT-00851	BMT-E.06	Best Teak Wood scantlings: 2.0 to 3.0 M	1 cum	153216
127	MAT-00852	BMT-E.07	Best Teak Wood scantlings: above 3.0 M	1 cum	166673
128	MAT-00853	BMT-E.08	Best Teak Wood Plancks: any thickness	1 cum	191722
III.SUB- SECTION			BURMA TEAK WOOD		
129	MAT-00854	BMT-E.09	Burma Teak Wood scantlings: up to 2.0 M	1 cum	193108
130	MAT-00855	BMT-E.10	Burma Teak Wood scantlings: 2.0 to 3.0 M	1 cum	204603
131	MAT-00856	BMT-E.11	Burma Teak Wood scantlings: above 3.0 M	1 cum	219451
132	MAT-00857	BMT-E.12	Burma Teak Wood Plancks: any thickness	1 cum	232996
IV.SUB- SECTION			ASSAM TEAK WOOD		
133	MAT-00858	BMT-E.13	Assam Teak Wood scantlings: any length	1 cum	53654
134	MAT-00859	BMT-E.14	Assam Teak Wood Plancks: any thickness	1 cum	79384
V.SUB- SECTION			SAL/ COUNTRY WOOD		
135	MAT-00860	BMT-E.15	Sal Wood scantlings: any length	1 cum	55780
136	MAT-00861	BMT-E.16	Sal Wood Plancks: any thickness	1 cum	79384
VI.SUB- SECTION			ROOFING MATERIAL		
137	MAT-00862	BMT-E.17	A.C sheet Corrugated 6 mm thick	1 sqm	247
138	MAT-00863	BMT-E.18	A.C sheet plain 4 mm thick	1 sqm	173
139	MAT-00864	BMT-E.19	A.C sheet plain 6 mm thick	1 sqm	182
140	MAT-00865	BMT-E.20	Plain or Corrugated Galvanized iron sheets as per IS 277 (0.1 mm to 0.8 mm thickness)	1 kg	77
141	MAT-00866	BMT-E.21	Supply of UV resistant multi-wall polycarbonate sheets for roofing of any colour - 6 mm thick	1 Sqm	1311
142	MAT-00867	BMT-E.22	Aluminium universal glazing set 40 mm wide for jointing and fixing polycarbonate sheets	1 RM	129
143	MAT-05341	BMT-E.23	Supply of UV resistant multi -wall polycarbonate sheets for roofing of any colour -10 mm thick.	1 Sqm	1462

F.SECTION			STEEL MATERIALS (Landing cost –including loading, cost of conveyance,unloading)		
I.SUB- SECTION			MILD STEEL MATERIALS		
144	MAT-00895	BMT-F.29	Supply & fixing of Rolling shutter made of 80 x 1.25 mm machine rolled CRCA laths, interlocked together through their entire length and jointed together at the ends by end-locks, mounted on specially designed pipe shaft of 50mm dia nominal bore MS B class pipe with brackets, plates, guide channels, stoppers, bottom locking plates and arrangements for inside & outside locking with push-pull operations including cost of hood cover and springs complete, painted with one coat of approved steel primer, locks, ball bearings, all accessories etc complete for finished item of work as per special spn: 1108	1 Sqm	4517
145	MAT-00896	BMT-F.30	Supplying & fixing collapsible steel shutters with vertical, double channel of 20 x10x2 mm of 100 mm centre ,Bracers with flat iron 40x40x6 mm with 38 mm dia steel pulleys, the top, bottom and side vertical frames of the collapsible gate with 65x65mmx8mm MS Angle and middle guide rail at site height with 65mmx8mm MS flat for the pulleys to guide and fixed with locking arrangements, stoppers, handles, all accessories all fixtures and painted with one coat of approved steel primer etc., complete for finished item of work as per special spn 1105	1 Sqm	3923
146	MAT-00875	BMT-F.09	Expanded metal sheets as per IS-412-1962- Light Weight-25 mm(SWM)x75 mm (LWM)3.25 mm Wide and 1.25 mm thick	1 Sqm	185
147	MAT-00876	BMT-F.10	Expanded metal sheets as per IS-412-1962- Light Weight-20 mm(SWM)x60 mm(LWM) 2.50 mm Wide and 1.25 mm thick	1 Sqm	185
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
148	MAT-00877	BMT-F.11	Expanded metal sheets as per IS-412-1962- Light Weight-20 mm(SWM)x50 mm(LWM) 2.50 mm Wide and 1.25 mm thick	1 Sqm	185

149	MAT-00878	BMT-F.12	Expanded metal sheets as per IS-412-1962- Medium Weight-25 mm(SWM)x75 mm(LWM) 3.25 mm Wide and 1.60 mm thick	1 Sqm	256
150	MAT-00879	BMT-F.13	Expanded metal sheets as per IS-412-1962- Medium Weight-20 mm(SWM)x60 mm(LWM) 2.50 mm Wide and 1.60 mm thick	1 Sqm	255
151	MAT-00880	BMT-F.14	Expanded metal sheets as per IS-412-1962- Medium Weight-20 mm(SWM)x50 mm(LWM) 2.50 mm Wide and 1.60 mm thick	1 Sqm	255
152	MAT-00881	BMT-F.15	Expanded metal sheets as per IS-412-1962- Heavy Weight-25 mm(SWM)x75 mm(LWM) 3.25 mm Wide and 2.24 mm thick	1 Sqm	272
153	MAT-00882	BMT-F.16	Expanded metal sheets as per IS-412-1962- Heavy Weight-20 mm(SWM)x60 mm(LWM) 2.50 mm Wide and 2.24 mm thick	1 Sqm	272
154	MAT-00883	BMT-F.17	Expanded metal sheets as per IS-412-1962- Heavy Weight-20 mm(SWM)x50 mm(LWM) 2.50 mm Wide and 2.24 mm thick	1 Sqm	272
156	MAT-00894	BMT-F.28	Rabbit wire mesh (chicken mesh) of not less than 30 gauge	1 Sqm	24
157	MAT-00869	BMT-F.02	Country Nails	1 Kg	81
158	MAT-00870	BMT-F.03	Wire Nails	1 Kg	81
159	MAT-00871	BMT-F.04	Mild Steel Tubes & pipes of all diameters as per IS-1161	1 Kg	88
159	MAT-00873	BMT-F.07	Supplying Galvanized Steel Barbed wire conforming to IS 278 - 1978 : Type A - IOWA Type Designation as per standard specification	1 Kg	116
160	MAT-00874	BMT-F.08	Supplying Galvanized Steel Barbed wire conforming to IS 278 - 1978 : Type B - Glidden Type Designation as per standard specification	1 Kg	106
161	MAT-00884	BMT-F.18	Galvanized Iron fly proof wire mesh of not less than 20 gauge	1 Sqm	275
162	MAT-00886	BMT-F.20	Hot dipped Galvanised Iron Chain link mesh 8 gauge - (4.0 mm) as per IS: 2721-1979: 2"x2" (50 mm x 50 mm) - 8 Gauge	1 Sqm	574
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
II.SUB- SECTION			GALVANIZED STEEL MATERIALS		
163	MAT-00887	BMT-F.21	Hot dipped Galvanised Iron Chain link mesh 8 gauge - (4.0 mm) as per IS: 2721-1979: 2½"x2½" (63 mm x 63 mm) - 8 Gauge	1 Sqm	504

164	MAT-00888	BMT-F.22	Hot dipped Galvanised Iron Chain link mesh 8 gauge - (4.0 mm) as per IS: 2721-1979: 3"x3" (76 mm x 76 mm) - 8 Gauge	1 Sqm	441
165	MAT-00889	BMT-F.23	Hot dipped Galvanised Iron Chain link mesh 8 gauge - (4.0 mm) as per IS: 2721-1979: 4"x4" (102 mm x 102 mm) - 8 Gauge	1 Sqm	310
166	MAT-00890	BMT-F.24	Hot dipped Galvanised Iron Chain link mesh 8 gauge - (4.0 mm) as per IS: 2721-1979 - PVC Coated - 2"x2" (50 mm x 50 mm) - 8 Gauge	1 Sqm	729
167	MAT-00891	BMT-F.25	Hot dipped Galvanised Iron Chain link mesh 8 gauge - (4.0 mm) as per IS: 2721-1979 - PVC Coated - 2½"x2½" (63 mm x 63 mm) - 8 Gauge	1 Sqm	608
168	MAT-00892	BMT-F.26	Hot dipped Galvanised Iron Chain link mesh 8 gauge - (4.0 mm) as per IS: 2721-1979 - PVC Coated - 3"x3" (76 mm x 76 mm) - 8 Gauge	1 Sqm	512
169	MAT-00893	BMT-F.27	Hot dipped Galvanised Iron Chain link mesh 8 gauge - (4.0 mm) as per IS: 2721-1979 - PVC Coated - 4"x4" (102 mm x 102 mm) - 8 Gauge	1 Sqm	399
III.SUB- SECTION			STAINLESS STEEL MATERIALS		
170	MAT-00872	BMT-F.06	Stainless Steel Tubes, sections, plates, sheets & pipes of all sizes & diameters for - 304 Grade	1 Kg	466
171	MAT-00885	BMT-F.19	Stainless steel fly proof wire mesh of not less than 20 gauge	1 Sqm	625
172 to 180		BMT-F.32 A to H	ITEM DELETED		
G.SECTION			FIXTURES FOR DOORS & WINDOWS		
I.SUB- SECTION			TOWER BOLTS		
181	MAT-00906	BMT-G.01	Brass Tower Bolt-10 mm Bolt (IS:204) 100 mm Long	Each	189
182	MAT-00907	BMT-G.02	Brass Tower Bolt-10 mm Bolt (IS:204) 150 mm Long	Each	303
183	MAT-00908	BMT-G.03	Brass Tower Bolt-10 mm Bolt (IS:204) 200 mm Long	Each	402
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
184	MAT-00909	BMT-G.04	Brass Tower Bolt-10 mm Bolt (IS:204) 250 mm Long	Each	469
185	MAT-00910	BMT-G.05	Brass Tower Bolt-10 mm Bolt (IS:204) 300 mm Long	Each	562
186	MAT-00911	BMT-G.06	Aluminium Tower Bolt-10 mm Bolt (IS:204) 75 mm Long	Each	63

187	MAT-00912	BMT-G.07	Aluminium Tower Bolt-10 mm Bolt (IS:204) 100 mm Long	Each	74
188	MAT-00913	BMT-G.08	Aluminium Tower Bolt-10 mm Bolt (IS:204) 150 mm Long	Each	95
189	MAT-00914	BMT-G.09	Aluminium Tower Bolt-10 mm Bolt (IS:204) 200 mm Long	Each	124
190	MAT-00915	BMT-G.10	Aluminium Tower Bolt-10 mm Bolt (IS:204) 250 mm Long	Each	150
191	MAT-00916	BMT-G.11	Aluminium Tower Bolt-10 mm Bolt (IS:204) 300 mm Long	Each	181
192	MAT-00917	BMT-G.12	Aluminium Tower Bolt-10 mm Bolt (IS:204) 350 mm Long	Each	384
193	MAT-00918	BMT-G.13	Aluminium Tower Bolt-10 mm Bolt (IS:204) 450 mm Long	Each	572
194	MAT-00919	BMT-G.14	MS-Powder Coated Tower Bolt-10 mm Bolt (IS:204) 100 mm Long	Each	32
195	MAT-00920	BMT-G.15	MS-Powder Coated Tower Bolt-10 mm Bolt (IS:204) 150 mm Long	Each	47
196	MAT-00921	BMT-G.16	MS-Powder Coated Tower Bolt-10 mm Bolt (IS:204) 200 mm Long	Each	63
197	MAT-00922	BMT-G.17	MS-Powder Coated Tower Bolt-10 mm Bolt (IS:204) 250 mm Long	Each	84
198	MAT-00923	BMT-G.18	MS-Powder Coated Tower Bolt-10 mm Bolt (IS:204) 300 mm Long	Each	105
II.SUB- SECTION			HINGES		
199	MAT-00924	BMT-G.19	Brass Butt hinges (IS:205)- 75 mm Long	Each	88
200	MAT-00925	BMT-G.20	Brass Butt hinges (IS:205)- 100 mm Long	Each	252
201	MAT-00926	BMT-G.21	Brass Butt hinges (IS:205)- 125 mm Long	Each	300
202	MAT-00927	BMT-G.22	Brass Butt hinges (IS:205)- 150 mm Long	Each	384
203	MAT-00928	BMT-G.23	Aluminium Butt hinges (IS:205)- 75 mm Long	Each	95
204	MAT-00929	BMT-G.24	Aluminium Butt hinges (IS:205)- 100 mm Long	Each	119
205	MAT-00930	BMT-G.25	Aluminium Butt hinges (IS:205)- 125 mm Long	Each	142
		BMT-G.88	GI Powder Coated Friction Stay hinges of 10" Long for windows	Each	247
		BMT-G.89	GI Powder Coated Friction Stay hinges of 10" Long for windows	Each	352
		BMT-G.90	Supplying SS 304 Grade Heavy Duty pivot Hinges for windows	Each	95
		BMT-G.91	GI Powder Coated Friction stay hinges of 10" Longfor windows	Each	252
		BMT-G.92	Continuous Piano Hinges Powder coated Mild steelas per IS-3818 : 1992 of nominal size 25 mm (B) of thickness 0.8 to 1.0 mm	Each	40

		BMT-G.93	Box hinges for cup boards	Each	51
		BMT-G.94	GI Powder Coated Friction stay hinges of 14" Long for windows	Each	352
		BMT-G.95	Stainless Steel Butt hinges (IS:12817)- 75 mm Long	Each	74
		BMT-G.96	Stainless Steel Butt hinges (IS:12817)- 100 mm Long	Each	130
		BMT-G.97	Stainless Steel Butt hinges (IS:12817)- 125 mm Long	Each	137
		BMT-G.98	Stainless Steel Butt hinges (IS:12817)- 150 mm Long	Each	177
		BMT-G.99	Supplying SS 304 Grade Heavy Duty pivot Hinges for windows	Each	95
		BMT-G.100	Labour Charges for removing and refixing with complete servicing of the MS windows	Sqm	539
		BMT-G.101	Supplying EPDM Gasket for windows panels to the PPS shutter	RM	37
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
206	MAT-00931	BMT-G.26	Aluminium Butt hinges (IS:205)- 150 mm Long	Each	153
207	MAT-00932	BMT-G.27	MS-Powder Coated Butt hinges (IS:205)- 75 mm Long	Each	13
208	MAT-00933	BMT-G.28	MS-Powder Coated Butt hinges (IS:205)- 100 mm Long	Each	25
209	MAT-00934	BMT-G.29	MS-Powder Coated Butt hinges (IS:205)- 125 mm Long	Each	37
210	MAT-00935	BMT-G.30	MS-Powder Coated Butt hinges (IS:205)- 150 mm Long	Each	48
211		BMT-G.80	Providing and fixing stainless steel (SS-304 grade) friction hinges to the side/top hung uPVC windows, of approved quality, with necessary stainless steel screws etc. as per direction of Engineer-in-charge.		
212	MAT-05342	BMT-G.80.A	200 x 19 x 1.9 mm	Each	331
213	MAT-05343	BMT-G.80.B	250 x 19 x 1.9 mm	Each	377
214	MAT-05344	BMT-G.80.C	300 x 19 x 1.9 mm	Each	406
215	MAT-05345	BMT-G.80.D	350 x 19 x 1.9 mm	Each	548
216	MAT-05346	BMT-G.80.E	400 x 19 x 1.9 mm	Each	580
III.SUB- SECTION			DOOR HANDLES		

217	MAT-00936	BMT-G.31	Aluminium Door Handles (IS:208) 75 mm Long	Each	69
218	MAT-00937	BMT-G.32	Aluminium Door Handles (IS:208) 100 mm Long	Each	79
219	MAT-00938	BMT-G.33	Aluminium Door Handles (IS:208) 125 mm Long	Each	116
220	MAT-00939	BMT-G.34	Aluminium Door Handles (IS:208) 150mm Long	Each	134
221	MAT-00940	BMT-G.35	MS-Powder Coated Door Handles (IS:208) 125 mm Long	Each	44
222	MAT-00941	BMT-G.36	MS-Powder Coated Door Handles (IS:208) 150 mm Long	Each	57
223	MAT-00963	BMT-G.58	Brass fancy handles 150 mm	Each	371
224	MAT-00964	BMT-G.59	Brass fancy handles 200 mm	Each	513
225	MAT-00965	BMT-G.60	Brass fancy handles 250 mm	Each	920
226	MAT-00966	BMT-G.61	Brass fancy handles 300 mm	Each	1124
227	MAT-00967	BMT-G.62	Brass fancy handles 450 mm	Each	1825
228	MAT-00977	BMT-G.72	Keyless lockset for toilet doors with CP or PC knob handles (complete set) Knob handles	Each	397

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
229	MAT-00978	BMT-G.73	Keyless lockset for toilet doors with brass knob handles	Each	815
230	MAT-05347	BMT-G.81	Providing and fixing casement handle made of zinc alloyed (white powder coated) for uPVC casement window with necessary screws etc.complete.	Each	249
		BMT-G.107	MS-Powder Coated Door Handles (IS:208) 150 mm Long	Each	56
		BMT-G.108	Stainless Steel Door Handles 100 mm Long	Each	117
		BMT-G.109	Stainless Steel Door Handles 125 mm Long	Each	137
		BMT-G.110	Stainless Steel Door Handles 150 mm Long	Each	167
		BMT-G.111	Stainless Steel Door Handles 200 mm Long	Each	191
IV..SUB-SECTION			ALDROPS		
231	MAT-00942	BMT-G.37	Brass Aldrop (IS:2681) 300 mm long	Each	1378
232	MAT-00943	BMT-G.38	Brass Aldrop (IS:2681) 350 mm long	Each	2632
233	MAT-00944	BMT-G.39	Brass Aldrop (IS:2681) 450 mm long	Each	3840
234	MAT-00945	BMT-G.40	Aluminium Aldrop (IS:2681) 200 mm long	Each	306
235	MAT-00946	BMT-G.41	Aluminium Aldrop (IS:2681) 250 mm long	Each	362

236	MAT-00947	BMT-G.42	Aluminium Aldrop (IS:2681) 300 mm long	Each	368
237	MAT-00948	BMT-G.43	MS-Powder Coated Aldrop (IS:2681)200 mm long	Each	116
238	MAT-00949	BMT-G.44	MS-Powder Coated Aldrop (IS:2681)250 mm long	Each	150
239	MAT-00950	BMT-G.45	MS-Powder Coated Aldrop (IS:2681) 300 mm long	Each	179
V.SUB-SECTION			LATCHES		
240	MAT-00953	BMT-G.48	Aluminium Flat Latches: 200 mm long	Each	135
241	MAT-00954	BMT-G.49	Aluminium Flat Latches: 250 mm long	Each	149
242	MAT-00955	BMT-G.50	Aluminium Flat Latches: 300 mm long	Each	173
243	MAT-00956	BMT-G.51	MS-Powder Coated Flat Latches: 250 mm long	Each	70
244	MAT-00957	BMT-G.52	MS-Powder Coated Flat Latches: 300 mm long	Each	89
245	MAT-00973	BMT-G.68	Brass latch heavy 300 mm	Each	709
246	MAT-00974	BMT-G.69	Brass latch heavy 350 mm	Each	847
247	MAT-00975	BMT-G.70	Brass latch heavy 450 mm	Each	1040
VI..SUB-SECTION			DOOR CLOSURES		
248	MAT-00968	BMT-G.63	Providing and fixing Cast Iron Body Bottle Type Hydraulic Door Closer (IS: 3564) with double speed adjustment, with necessary accessories and screws etc. complete	Each	1005

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
249	MAT-00979	BMT-G.74	Providing and fixing Aluminium Extruded Section Body Tubular Type Hydraulic Door Closer (IS: 3564) with double speed adjustment with necessary accessories and screws etc. complete (Type-1: for width of doors up to 700 mm)	Each	1232
250	MAT-00980	BMT-G.75	Providing and fixing Aluminium Extruded Section Body Tubular Type Hydraulic Door Closer (IS: 3564) with double speed adjustment with necessary accessories and screws etc. complete (Type-2: for width of doors 701 to 850 mm)	Each	1384
251	MAT-00981	BMT-G.76	Providing and fixing Aluminium Extruded Section Body Tubular Type Hydraulic Door Closer (IS: 3564) with double speed adjustment with necessary accessories and screws etc. complete (Type-3: for width of doors 851 to 1000 mm)	Each	1579
VII.SUB-SECTION			FLOOR SPRINGS		
252	MAT-00969	BMT-G.64	Double action Stainless steel cover plate and cast body iron floor spring (IS 6315- Table-1)	Each	2236
253	MAT-00970	BMT-G.65	Double action Brass cover plate and cast brass body floor spring (IS 6315- Table-1)	Each	4428
254	MAT-00982	BMT-G.77	Providing and fixing double action brass cast hydraulic floor spring (IS:6315-Table 1) for doors including cost of cutting floors as required, embedding in floors and S.S./ Brass cover plates with brass pivot and single piece M.S. Sheet outer box with slide plate etc. complete (door weight capacity up to 130 kgs)	Each	4498
255	MAT-00983	BMT-G.78	Providing and fixing double action brass cast hydraulic floor spring (IS:6315-Table 1) for doors including cost of cutting floors as required, embedding in floors and S.S.cover plates with brass pivot and single piece M.S. Sheet outer box with slide plate etc. complete (door weight capacity up to 80 kgs)	Each	3198
256	MAT-00984	BMT-G.79	Providing of brass cast body Floor Spring IS: 6315 sleek in size with the S.S. / Brass Cover plates of Length 320 mm x Breadth 130 mm size along with the Top Patch, Bottom Patch, Door Lock and Pivot with Double Cylinder etc. complete for Heavy duty Glass doors.	Each	12962
VIII SUB-SECTION			MORTICE LOCKS		
257	MAT-00971	BMT-G.66	Heavy duty mortise lock 6/7 levers (IS:2209) with PC or CP handles complete set	Each	984

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
258	MAT-00972	BMT-G.67	Heavy duty mortise lock 6/7 levers (IS:2209) with brass heavy handles	Each	2359
IX.SUB- SECTION			OTHER ACCESSORIES		
259	MAT-00958	BMT-G.53	MS-Powder Coated - Door Stoppers	Each	54
260	MAT-00962	BMT-G.57	Heavy duty Aluminium Door stopper	Each	70
261	MAT-00951	BMT-G.46	Brass Door Stoppers	Each	214
262	MAT-00976	BMT-G.71	Friction stay hinges for windows	Each	117
263	MAT-00961	BMT-G.56	Deluxe window stay Aluminium	Each	146
264	MAT-00952	BMT-G.47	Brass Windows Stay	Each	228
265	MAT-00959	BMT-G.54	Supply & fixing drapery rods (25.4 mm) 1" x 21 G Powder coated with PVC rings	RM	137
266	MAT-00960	BMT-G.55	Supply & fixing drapery bracket - brass powder coated	pair	503
267	MAT-05348	BMT-G.82	Providing and fixing zinc alloyed (white powder coated) touch lock for uPVC sliding window with necessary screws etc. Complete	Each	1944
268	MAT-05349	BMT-G.83	Providing and fixing steel roller for uPVC sliding window with necessary screws etc. complete.	Each	113
269	MAT-05350	BMT-G.84	Providing and fixing steel roller for uPVC sliding door with necessary screws etc. complete.	Each	180
270	MAT-05351	BMT-G.85	Providing and fixing steel (white power coated) crescent lock for uPVC sliding window/ door with necessary screws etc. complete.	Each	198
H.SECTION			WATER PROOFING CHEMICALS &ADMIXTURES <i>Literature for usage / application of construction / water proofing materials,epoxies etc, may be obtained from manufacturers.</i>		
289	MAT-01021	BMT-H.37	Anti corrosion CRPPC (Corrosion Resistant) inhibitive admixture. Note: The user departments who ever are preparing the estimate, have to satisfy themselves with the performance and result of the product before proposing the item.)	1 Ltr	365

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
336	MAT-05352	BMT-H. 66	Pre construction Anti termite is a process in which chemical toxic to subterrean termites is apply/ inject into soil during early stage of building Construction 2. Treatment of soil Beneath the building and around the foundations conduct and chemical use as per BIS - IS 6313 (Part -2) 2013 code specification & CIB RC registered termiticide which creates a continuous chemical barrier beneath the building which kills or repels termites & impervious to termite entry Imidacloprid 30.5% SC (IS 63131) dissolve 2.1 ml/1 liter of water and apply emulsion/solution @ 7.5 Litres/Square meter (Sqm) of internal, external vertical surface of the columns , plinth beams (Back filling) walls and floor junction, external perimeters, along retaining wall @ 5.0 Liters/Sqm of the horizontal surface of basement top surface of the basement filling below flooring bed (Plinth) & @ 2.0 Litres/ Line meter at expansion joints. The substructure of a depth of 500mm around columns & 300mm deep around plinth beams, basements & floor filling area including excavation channel along the wall & rodding etc. cost & Conveyance of all materials to the site, cost of labour for sparying, rodding etc. complete for furnished item of work as per the approval of the Engineer-in-charge	1 Sqm	179
337		BMT-H. 67	ITEM DELETED		
I.SUB- SECTION			REPAIRING AND TREATMENT WORKS		
		BMT-H.68	SURFACE PREPARATION		
			Cleaning of the surface : For Waterproofing treatment		
338	MAT-05353	BMT-H.68.A	(If the surface is sound & hard Condition) The surface must be clean and sound duly removing of existing treatments clean from dirt, dust and other contaminations by power grinding wire brushing , air blower & jetwater cleaning.	Sqm	75

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
339	MAT-05354	BMT-H.68.B	(If the surface is detoriated or damage / existing tiles or block laying) Chipping with pneumatic power chiseling equipment and until to ahcieve the hard mother concrete surface. Duly removing of debris, cleaning of the surface from dirt, dust and other foreign matters & water jet cleaning.	Sqm	167
340	MAT-05355	BMT-H.68.C	if the surface has existing damaged bituminous felt / APP membrane. Chipping and removing of existing bituminous tarfelt / membrane with chiseling equipments, grinding / wire brusing the surface duly removing the felt completely. Duly removing of debris, cleaning of the surface from dirt, dust and other foreign matters & waterjet cleaning.	Sqm	117
			SPECIALISED CHEMICAL WATERPROOFING TREATMENTS FOR TERRACE		
			WHEREVER FLOORING SURFACE IS HAVING MAJOR HAIR LINE CRACKS DEVELOPED, SEVERE LEAKAGES		
			TAKEN PLACE AND REQUIRED TO REDUCE THE ROOM TEMPERATURES - SELF ASSESSED TREATMENTS TO IDENTIFY EACH LAYER OF TREATMENTS : REFER THE RATES FOR CLEANING AND CRACK FILLING UNDER THE HEAD OF THE WORKS Item Code BMT-H.68 SURFACE PREPARATION SUB HEADING : CLEANING OF THE SURFACE FOR WATERPROOFING TREATMENT.		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
341 (a)	MAT-05356	BMT-H.69	SPECIALISED FIVE LAYER SYSTEM OF WATERPROOFING TREATMENT TO THE TERRACE a). Ist Layer Black coloured chemical treatment : Providing and application of one coat of High bonding, flexible bituminous polyurethane blended bituminous coating with –5 systems Confirming to ASTM-G 154 - 2000 or equivalent Ist Layer diluting with water at 1 : 1 ratio as a primer coat at a consumption of 200ml per Sqm. b). IInd Layer : Providing and laying of Fibre Mesh 40 GSM, with 1 Mtr width and 50mm overlap on the primed surface. c). IIIrd Layer Grey coloured coating : Providing and application of one coat of Acrylic rubberized elastomeric flexible waterproof grey coating with –5 systems ASTM-C 836 or equivalent or equivalent diluting with 50% of water at a consumption of 400ml per Sqm. d) IVth Layer white coloured coating : Providing and application of one coat of High solid, cold applied, Fibre reinforced acrylic elastomeric waterproof membrane off white coating –Roofcare prc 5 systems Confirming to ASTM-G 154 -2000 or equivalent coating (add the water upto 200ml) (Consumption of 350ml per Sqm). Vth Layer super white reflective coating : Application of one coat of 100% pure acrylic solar reflective pure white coating with systems Confirming to ASTM -C 297 or equivalent solar reflective coating diluting with 20% of water (Consumption of 300ml per Sqm). e) Note : THE ABOVE TREATMENT WILL BE GUARANTEED FOR 5 YEARS	Sqm	609

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
341 (b)		BMT-H.69 (b)	SPECIALISED FIVE LAYER SYSTEM OF WATERPROOFING TREATMENT TOTHE TERRACE Providing and laying five layers waterproofing cum heat reflective treatment over the old / new roof slab/ terrace, all as directedby Department Engineer-in-charge with the following specification and should be complain with the following technical parameters for the system - Density: 1.3 Gm/cc, Solids content: 68% $\pm$ 2% byweight, Elongation at break ASTM D 638: 200% (for the system), Adhesion to substrate ASTM D 4541: >1.5 N/mm2, Water penetration DIN 1048: no leak at 7 bars, Tear resistance ASTM D 1004-76: 17N/mm2, Tensile strength ASTM D 412- 87:6.0N/mm2 a) First Layer - Supply and Apply penetrative cum bonding primer as base primer cum sealer coat using modified with waterand cement at the ratio 2:1:3 (MIXPRIME AC 100 : water : cement) by volume with a slow speed mixer machine. This compound shall be applied with sufficient thickness to cover the holes/pores/cracks @ 1.000 Liter / SQM SQM) and the raw primer should be complain with ASTM 4541 and the Solid content 49% <u>+2%</u> b) Second Layer – Supply and apply of 2 x2 mm welded with alkaline resistant coated / non-woven 40 Gsm verging fiber mesh MIXMAT GFM 50 or equivalent for a minimum over lap of 100 mm embedded in the primer coat c) Third Layer - Supply and apply of bonding cum water tight acrylic high viscous white primer equivalent @ 0.250 Kg / SQM (dilution or modification not recommended) should be complain withDensity: 1.1gm/cc, Solids content: 50 % $\pm$ 2% by weight, Elongationat break ASTM D 638: >300%, Adhesion to substrate ASTM D 4541: >1 N/mm2, Tensile strength ASTM D 638: >1.5 N/mm2, Reduction in chloride ion ingress: 94%@28 days d) Fourth Layer – Supply and apply of high elastomeric acrylic waterproofing	Sq.m	609

			cum weather proof high viscous white liquid membrane equivalent @ 0.500 Kg / SQM (dilution or modification not recommended) should be comply with Density: 1.30 gm/cc , Solids content: 68% ± 2% by weight, Elongation at break ASTM D638: 400%, Tensile strength ASTM D 412: 1.8N/mm², Adhesion to substrate ASTM D 4541: >1 N/mm², Water penetration DIN1048: no leak at 7 bars (+ve side), Water vapor transmission ASTM E96: 19g/m²/day, Crack bridging ASTM C836: No cracks up to 2mm thick. E) Fifth Layer - Supply and apply of fiber reinforced flexible high grade pure acrylic modified waterproofing cum heat reflective high viscous white liquid membrane equivalent @ 0.500 Kg / SQM (dilution or modification not recommended) Density: 1.3 gm/cc Solids content: 68% ± 2% by weight, Elongation at break ASTM D 638: 200% , Adhesion to substrate ASTM D 4541: >1.3 N/mm², Water penetration DIN 1048: no leak at 7 bars, Tear resistance ASTM D 1004-76: 15N/mm² , Tensile strength ASTM D 412-87: 3.0N/mm², Solar reflectance –ASTM G173 – 92 %, Water vapor transmission ASTM E 96 – 19 Kg / M² / day. Note: - 1) No dilution or modification recommended for item No.b,c,d and e . 2) All materials should be procured as per the consumption with respect of the work order. 3) The application should be carried out by an approved agency.) The contractor should provide 5 years material warranty from the Manufacturer and 5 year warranty from the applicator or combined		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			WHEREVER FLOORING SURFACE IS HAVING HAIR LINE CRACKS DEVELOPED, SEVERE LEAKAGES AND FOUND VERY SLIGHTLY MORTAR DEBONDED WITH ORIGINAL SLAB - TAKEN PLACE : REFER THE RATES FOR CLEANING AND CRACK FILLING UNDER THE HEAD OF THE WORKS RAINSEAL FRC SPECIALISED HIGH STRENGTH FIBRE REINFORCED ACRYLIC ELASTOMERIC AND HEAT RESISTANT LIQUID MEMBRANE COATING CHEMICALS Confirmed ASTM C 836/89A & ASTM C 297 FOR TERRACE.		
342	MAT-05357	BMT-H.70	SPECIALISED HIGH STRENGTH CELLULOSE FIBRE REINFORCED ACRYLIC ELASTOMERIC LIQUID MEMBRANE COATING FOR TERRACE : a). Providing and application of one coat of High Solid, Cold applied Acrylic Elastomeric Liquid Membrane Coating / diluting with water at 1 : 0.50 ratio as a primer coat at a consumption of 200ml per Sqm. b). Providing and laying of Non woven polyester reinforced fibre mesh of 40 GSM, with 1 Mtr width and 50mm overlap on the primed surface. c) Providing and application of one coat of High strength cellulose fibre reinforced Acrylic Elastomeric Liquid Membrane coating with diluting with water at 20% as a base coat application at a consumption of 400ml per Sqm.	Sqm	580
			WHEREVER FLOORING SURFACE IS HAVING HAIR LINE CRACKS DEVELOPED, SEVERE LEAKAGES AND FOUND SOME PLACES MORTAR DEBONDED WITH ORIGINAL SLAB - TAKEN PLACE :		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			REFER THE RATES FOR CLEANING AND CRACK FILLING UNDER THE HEAD OF THE WORKS BMT-H.68 © and BMT-H.83 chemical complies with ASTM C 297.		
343(a)	MAT-05358	BMT-H.71	SPECIALISED HIGH PERFORMANCE ACRYLIC POLYMER MODIFIED ELASTOMERIC CEMENTITIOUS WATERPROOF COATING TO THE TERRACE a). Providing and application of one coat of High performance Acrylate penetrative water barrier primer –)diluting with water at 1 : 0.50 ratio as a primer coat at a consumption of 200ml per Sqm. b). Providing and laying of Non woven polyster reinforced fibre mesh of 40 GSM, with 1 Mtr width and 50mm overlap on the primed surface. c) Providing and application of one coat of Two part system of high performance acrylic polymer modified elastomeric cementitious waterproof coating mixing of powder and liquid as per packing at 1:2 ratio. (add the water upto 200ml) at aconsumption rate of 300 Grams mix. d). Providing and application of one coat of Two parts system fibre Reinforced Acrylic Cementitious Coatings with mixing of powder and liquid as per packing at 1:2 ratio (add the water upto 200ml) at a consumption rate of 300 Grams mix.	Sqm	541

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
343(b)		BMT-H.71(b)	SPECIALISED HIGH PERFORMANCE ACRYLIC POLYMER MODIFIED ELASTOMERIC CEMENTITIOUS WATERPROOFING SYSTEM COATING TO THE WET AREA / TOILET / BATH ROOM . a) First Layer - Supply and Apply penetrative cum bonding primer as base primer cum sealer coat using equivalent modified with water and cement at the ratio 2:1:3 (MIXPRIME AC 100 : water : cement) by volume with a slow speed mixer machine. This compound shall be applied with sufficient thickness to cover the holes/pores/cracks @ 1.000 Liter /SQM and the raw primer should be comply with ASTM 4541 and the Solid content 49% <u>+2%</u> b) Second Layer – Supply and apply of 2 x2 mm welded with alkaline resistant coated / non-woven 40 Gsm verging fiber mesh or equivalent for a minimum overlap of 100 mm embedded in the primer coat c) Third Layer - Supply and apply of first coat of two component (Powder + Liquid) system of high performance acrylic polymer modified elastomeric cementitious waterproofing system or equivalent @ 1.000 Kg / SQM (mix the powder and liquid with the help of a slow speed mixer for a period of 2 to 3 minutes up to get a homogeneous mix- dilution or modification not recommended) should be comply with BS 1881 Part 5 1983 (ISAT 476 Part 6), DIN 1048 Part 5 1991, BSEN 12390-8 2000, ASTM D 412-92 d) Fourth Layer –Supply and apply of second coat of two component (Powder + Liquid) system of high performance acrylic polymer modified elastomeric cementitious waterproofing system equivalent @ 1.000 Kg / SQM (mix the powder and liquid with the help of a slow speed mixer for a period of 2 to 3 minutes up to get a homogeneous mix- dilution or modification not recommended) should be comply with BS 1881 Part 5 1983 (ISAT	Sq.m	542

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			476 Part 6), DIN 1048 Part 5 1991, BSEN 12390-8 2000, ASTM D 412-92. Note: - 1) No dilution or modification recommended for item Nos.b,c,d and e . 2) All materials should be procured as per the consumption with respect of the work order. 3) The application should be carried out by an approved agency. 4) The contractor should provide 5 years material warranty from the Manufacturer and 5 year warranty from the applicator or combined		
344	MAT-05359	BMT-H.72	<i>WHEREVER FLOORING SURFACE IS HAVING MAJOR HAIR LINE CRACKS DEVELOPED, SEVERE LEAKAGES TAKEN PLACE AND REQUIRED TO REDUCE THE ROOM TEMPERATURES - SELF ASSESSED TREATMENTS TO IDENTIFY EACH LAYER OF TREATMENTS : REFER THE RATES FOR CLEANING AND CRACK FILLING UNDER THE HEAD OF THE WORKS</i>	Sqm	312
			a). Providing and application of one coat of High bonding, flexible bituminous polyurethane blended black coating with Complies with ASTM 836 - DN 1048 diluting with water at 1 : 1 ratio as a primer coat at a consumption of 200ml per Sqm. b). Providing and laying of Non woven GEO Fabric 40 GSM, with 1 Mtr width and 50mm overlap on the primed surface. c). Providing and application of one coat of Acrylic rubberized elastomeric flexible waterproof grey coating with – ASTM G 154 - 2000 diluting with 50% of water at a consumption of 400ml per Sqm. d) Providing and application of one coat of High solid, cold applied, Fibre reinforced acrylic elastomeric waterproof membrane off white coating –		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			Complies with ASTM C 297 (add the water upto 200ml) (Consumption of 350ml per Sqm). e) Application of one coat of 100% pure acrylic solar reflective pure white coating with - ROOFCARE COOL (Insulator) / POWER n COOL (EBT) / BRUSHBOND COOL COAT (Fosroc)/ZORISHIELD XL (PMCC) / SIKa COOL COAT (Sika) //WATERSHIELD COOL COAT diluting with 20% of water (Consumption of 300ml per Sqm).		
			FOR WATERPROOFING OF PORTABLE WATER TANKS / RESERVOIRS / SUMP/ TERRACE / SIDE WALLS : REFER THE RATES FOR CLEANING AND CRACK FILLING UNDER THE HEAD OF THE WORKS		
345	MAT-05360	BMT-H.73	SPECIALISED ACRYLIC CEMENTITIOUS ELASTOMERIC WATERPROOF COATING TREATMENT Complies with ASTM C 297 : Providing and Application of two coats of Acrylic cementitious elastomeric waterproof coating with- Roofcoat or equivalent like high elastomeric acrylic polymer modified cementitious waterproof system.	Sqm	401
			FOR WATERPROOFING OF TERRACE / SIDE WALLS : REFER THE RATES FOR CLEANING AND CRACK FILLING UNDER THE HEAD OF THE WORKS		
346	MAT-05361	BMT-H.74	SPECIALISED ACRYLIC CEMENTITIOUS ELASTOMERIC WATERPROOF COATING TREATMENT Complies with ASTM C 297 : Providing and Application of two coats of Acrylic cementitious elastomeric waterproof coating with -	Sqm	449

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			<i>WATERSHIELD COAT PC like high elastomeric acrylic polymer modified cementitious waterproof system.</i>		
			WHEREVER HIGH FLEXIBLE HIGH BONDED NECESSARY FOR WATERPROOFING OF TERRACE / SLOPED ROOFS / ACC SHEETS etc., FOR A GUARANTEE OF 5 YEARS REFER THE RATES FOR CLEANING AND CRACK FILLING UNDER THE HEAD OF THE WORKS		
347	MAT-05362	BMT-H.75	SPECIALISED HIGH SOLID, COLD APPLIED, ACRYLIC WATERPROOF COATING TO THE EXTERNAL WALLS Acrylic elastomeric waterproof exterior coatings Complies with ASTM C 836 / 89 A : Providing and application of two coats of High solid, cold applied, Acrylic Elastomeric Liquid Membrane Coating with – 20% of water mixing with required colour stainers.	Sqm	449
			<i>WHEREVER REQUIRED FOR WATERPROOFING OF TERRACE / SLOPED ROOFS / ACC SHEETS etc., FOR A GUARANTEE OF 3 YEARS REFER THE RATES FOR CLEANING AND CRACK FILLING UNDER THE HEAD OF THE WORKS</i>		
348	MAT-05363	BMT-H.76	SPECIALISED HIGH BONDING, FLEXIBLE BITUMINOUS POLYURETHANE BLENDED BITUMINOUS COATING Complies with ASTM C 836 - DN 1048 : Providing and application of two coats of High bonding, flexible bituminous polyurethane blended bituminous coating with diluting with 20% of water.	Sqm	411

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			EXPANSION JOINT TREATMENT:		
349	MAT-05364	BMT-H.77	Preparation of the surface: For existing expansion joint treatment Chipping of the existing treatments over the expansion joints concrete / brick masonry with pneumatic power chiseling equipment and until to achieve the hard mother concrete surface. Chipping and removing of existing bituminous mastic board upto 25mm deep. Duly removing of debris, cleaning of the surface from dirt, dust and other foreign matters	RMT	291
350	MAT-05365	BMT-H.78	SPECIALISED POLYSULPHIDE SEALANT TREATMENT TO THE EXPANSION JOINTS ON TERRACE: (Size: 25mm x 12mm) Application of one coat of-High performance specially designed SBR latex polymer-based bonding agent- or equivalent mixing with cement as per manufacturers c]. Providing and application of Acrylic Polymer modified reinstatement concrete/mortar admixture with - to finish the damaged edges of joint and making the groove. d]. Providing and fixing of masking tape on top of the joint both sides. e]. Providing and fixing of Back up support material of Polyethelene foam to leave the depth of 12mm on the joint. f]. Providing and application of one coat of polysulphide primer with – Polysulphide primer on inner edge on joints. g]. Providing and application of Two part Polysulphide sealant to a width of 25mm and 12mm depth with -	RMT	755

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			with BS 4254 - 83 or equivalent with putty knife and neat finish. h]. Removing of masking tape and providing and application of two coats of Acrylic elastomeric cementitious coating with - ROOFSEAL PS (Armstrong) / POWER n SEAL PS (EBT) /NITOSEAL PS 200 (Fosroc)/ ZORISEAL PS (PMCC) / SIKA POLYSULPHIDE (Sika) / WATERSHIELD PS		
			FOR ARRESTING WATER FLOW LEAKAGES, LEAKAGES OF CONSTRUCTION JOINTS OF RESERVOIRS / PUMP ROOMS / POWER HOUSE / PENSTOCK / CANAL DUCTS AND OTHER WATER RETAINING STRUCTURES EXECUTION IN THE PRESENCE OF WATER.		
351	MAT-05366	BMT-H.79	LABOUR CHARGES FOR SPECIALISED EXPANSIVE ACQUA-REACTIVE WATER BARRIER GROUTING (1). Drilling of holes with Electrical Drilling machine up to the required depth i.e., (12mm to 14mm dia sized holes) (2). Fixing of pressure retaining aluminum / steel packers fixing with Instant setting leakproof plugging compound (3). Grouting of holes with Air Compressed Injection equipment with single component aliphatic polyurethane grout compound- (4). After removing the pipes sealing of the holes with polymer putty – with Cement	Each	289

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
352	MAT-05367	BMT-H.80	Supply of chemicals for specialised expansive aqua reactive water barrier grout -	Kg	1753
			FOR STRENGTHENING AND SEAL THE POROSITY OF THE CONCRETE TO ARREST THE LEAKAGES, DAMPNESS , LEAKAGES OF CONSTRUCTION JOINTS FOR TERRACE / CEILING / RCC RETAINING WALLS / BASEMENT FLOORINGS / WATER TANKS / RESERVOIRS / TOILETS etc.,		
353	MAT-05368	BMT-H.81	SPECIALISED INJECTION GROUTING WITH CEMENT AND FREE FLOW ADDITIVES : a]. Drilling of holes with power drilling machine to the required depth [12mm to 14mm dia holes] b]. Fixing of Rubber Nozzles with cement and quick setting, Rapid hardening compound putty - Rapidstrong qs or equivalent. c]. Grouting of holes with 140 PSI Grout pump with cement slurry mixing with Specialized Free flow, Non-shrink Grout additive - 250 Grams per bag of 50 Kgs Cement add required water to make slurry form. d]. After completion of grouting, Remove the Rubber nozzles e]. Later sealing of the hole with polymer cement putty .	Each	173
			FOR STRENGTHENING AND SEAL THE POROSITY OF THE CONCRETE TO ARREST THE LEAKAGES, DAMPNESS , LEAKAGES OF		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			ONSTRUCTION JOINTS : (FOR TERRACE /CEILING / RCC RETAINING WALLS / BASEDMENT FLOORINGS / WATER TANKS / RESERVOIRS / TOILETS etc.,)		
354	MAT-05369	BMT-H.82	SPECIALISED INJECTION GROUTING WITH CEMENT AND CRYSTALLIZATION ADMIXTURES : a]. Drilling of holes with power drilling machine to the required depth [12mm to 14mm dia holes] b]. Fixing of Rubber Nozzles with cement and quick setting, Rapid hardening compound putty Rapidstrong qs or equivalent c]. Grouting of holes with 140 PSI Grout pump with cement slurry mixing with Specialized crystallization compound-Roofex gp or equivalent @ 5% by weight of cement. d]. After completion of grouting, Remove the Rubber nozzles e]. Later sealing of the hole with polymer cement putty	Each	262
			CRACKS AT TERRACE / BEAM & WALLS JUNCTIONS - SEALING THE JOINTS WITH POLYURETHANE SEALANT :		
355	MAT-05370	BMT-H.83	SPECIALISED POLYURETHANE SEALANT TREATMENT : a). Making "U" Groove (width and depth of 6mm x 6mm) b). Filling of the groove with polyurethane sealant	RMT	383
			CRACKS AT INTERNAL / EXTERNAL WALLS - SEALING THE CRACKS WITH ACRYLIC CAULKING COMPOUND		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
356	MAT-05371	BMT-H.84	SPECIALISED ACRYLIC CAULKING SEALANT TREATMENT : a). Making "U" Groove (width and depth of 6mm x 6mm) b). Filling of the groove with Acrylic caulking compound	RMT	211
357		BMT-H.128	Providing and fixing of expansion joint system related with floor location: The joints system will be of extruded aluminum base members, self aligning / self centering arrangement and support plates etc. as per ASTM B221-02. The system shall be such that it provides floor to floor /floor to wall expansion control system for various vertical location in load application areas that accommodates multi directional seismic movement without stress to it's components. System shall consist of metal profiles with a universal aluminium base member designed to accommodate various project conditions and finish floor treatments. The cover plate shall be designed of width and thickness required to satisfy projects movement and loading requirements and secured to base members by utilizing manufacturer's pre-engineered self-centering arrangement that freely rotates / moves in all directions. The Self – centering arrangement shall exhibit circular sphere ends that lock and slide inside the corresponding aluminum extrusion cavity to allow freedom of movement and flexure in all directions including vertical displacement. Provision of Moisture Barrier Membrane in the Joint System to have watertight joint is mandatory requirement all as per the manufactures design (Material shall confirm to ASTM 6063.) (Floor Joint of 200 mm gap)	RMT	7549
358		BMT-H.129	Providing and fixing of expansion joint system related with wall joint (internal/ external) location: The joints shall be of extruded aluminum base members, self aligning / centering arrangement and support plates as per ASTM B221- 02. The material shall be such that it provides an Expansion Joints system suitable for vertical wall to wall / wall to corner application, both new and existing construction in buildings &	RMT	5159

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			complexes with no slipping down tendency amongst the components of the Joint System. The Joint System shall utilize light weight aluminium profiles exhibiting minimal exposed aluminium surfaces mechanically snap locking the multi cellular to facilitate movement. (Material shall confirm to ASTM 6063.) (Wall Joint of 200 mm gap)		
359			Providing and fixing of expansion joint system of approved make and manufactures for various roof locations: The joints shall be of extruded aluminium base members with self aligning and self centering arrangement support plates as per ASTM B221-02. The system shall be such that it provides water tight roof to roof / roof to corner joint cover expansion control system that is capable of accommodating multi directional seismic movement without stress to its components. System shall consist of metal profile that incorporates a universal aluminium base member designed to accommodate various project conditions and roof treatments. The cover plate shall be designed of width and thickness required to satisfy movement and loading requirements and secured to base members by utilizing manufacturer's pre-engineered self-centering arrangement that freely rotates / moves in all directions.		
			The Self centering arrangement shall exhibit circular sphere ends that lock and slide inside the corresponding aluminum extrusion cavity to allow freedom of movement and flexure in all directions including vertical displacement. The Joint System shall resist damage or deterioration from the impact of falling ice, exposure to UV, airborne contaminants and occasional foot traffic from maintenance personnel. Provision of Moisture Barrier Membrane in the Joint System to have water tight joint is mandatory requirement. Material shall confirm to ASTM 6063.		
360		BMT-H.130	Roof Joint of 200 mm gap	RMT	5600
361		BMT-H.131	Roof Joint of 250 mm gap	RMT	7600

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
	1	2	3	4	5
	NEW Item	BMT-H.134	Old Terrace Screed Repair with UV Resistant Waterproof coating below 500 Sq.m Providing and Applying high performance solar reflective & Acrylate silicon based Waterproofing coating which is single component, cold applied, water based acrylic and UV resistant water proofing treatment to the Existing Roof screed surface applied @ 1.5 l/m2 in 3 coats to achieve 1mm DFT, having tensile strength 2N/ mm2 confirming to ASTM D 412; Elongation at break ≥ 200%, Abrasion resistance 21mg confirming to ASTM D 4060 and Crack bridging ability up to 2 mm, including surface preparation, priming the surface with 1 coat diluted with water in the ratio 2:1 spreading @ 0.125 L/m2 as self-priming coat in the SSD condition and spreading 45 gsm glass fibre mesh of 2.5 mm x 2.5 mm sandwiched between the first and second coat completely as per specification. The finished cost to include surface preparation, making coving at Junction, treatment of cracks completely as per specification	Sqm	629.00
	NEW Item	BMT-H.135	Old Terrace Screed Repair with UV Resistant Hybrid PU Waterproof coating above 500 Sq.m Providing and Applying high strength, hybrid polyurethane Waterproofing coating which is two component, cold applied, water based acrylic and UV resistant water proofing treatment to the Existing Roof screed surface applied @ 1.6 L/m2 in 3 coats to achieve 1mm DFT, having tensile strength with 45 gsm glass fibre mesh 10N/mm2 , Elongation ≥ 200%, confirming to ASTM D 2370; Abrasion resistance 15mg confirming to ASTM D 4060 and Crack bridging ability up to 3 mm, including surface preparation, ensure surface in SSD condition for first coat and spreading 45 gsm glass fibre mesh of 2.5 mm x 2.5 mm sandwiched between the first and	Sqm	822.00

			second coat completely as per specification. The finished cost to include surface preparation, making coving at Junction, treatment of cracks completely as per specification.		
	NEW Item	BMT-H.136	Old Terrace tile surface repair with UV Resistantn hybrid waterproofing coating Providing and Applying Polyurethane hybrid liquid applied GRIHA certified Waterproofing coating with flutyne protection technology, single component, cold applied, water based acrylic and UV resistant water proofing treatment to the Existing Roof having Tile or any non-porous surface applied @ 1.5 l/m2 in 2 coats to achieve 1mm DFT, having tensile strength with 45 gsm glass fibre mesh 4N/mm2 confirming to ASTM D 412; Elongation at break ≥ 300% and Crack bridging ability up to 3mm, SRI Index 106 as per ASTM E 1980- 01, Water permeability @5 bar – Nil as per EN12390 - 8:2019, including surface preparation, priming the surface with single component high-performance waterborne tile primer which is suitable for non - porous surface at a rate of 0.14 L/m2 and spreading 45 gsm glass fibre mesh of 2.5 mm x 2.5 mm sandwiched between the first and second coat completely as per specification. The finished cost to include surface preparation, making coving at Junction, treatment of cracks completely as per specification.	Sqm	892.00
	NEW Item	BMT-H.137	Old Terrace with Lime mortar/week surfa ce waterproofing with TPO membrane Providing and laying 1.5 mm thick TPO Membrane over old terrace having week surface/Lime mortar. The membrane is manufactured using hot-melt extrusion process for complete scrim encapsulation. It is reinforced with a strong, polyester reinforced fabric center (scrim) and a tough thermoplastic polyolefin compounded top ply and the bottom. It should have UV resistant top white colour which has a very high resistance to weather agents and UV rays. TPO membrane shall be plasticizer, chlorine & pthalate free, and should exceed /meet specifications of ASTM D6878. Membrane should be mechanically fixed to the substrate by independent plates and fasteners. TPO Roof Membrane should be lapped and seamed using hot air heat welding equipment after mechanically	Sqm	1295.00

			fastening the overlaps. Membrane should have following minimum properties, Breaking Strength min. 220lbf (976N) as per ASTM D751, Elongation break of reinforcement > 15 % as per ASTM D751, and Tear Strength 55lbf (245N) as per ASTM D751. The finished cost including surface preparation, application of TPO membrane over the 200GSM Geo- textile and termination of TPO membrane using 2mm thick aluminium strip sealing with PU sealant at the top of strip completely as per specification.		
	NEW Item	BMT-H.138	Newly Constructed Bathroom/toilet/balcony/ utility with Cementatius Waterproof coating below 300 Sq.m Providing and Applying CFTRI approved two component flexible polymer modified acrylic cementitious waterproofing coating with a mix ratio of (1 Liquid: 2 Powder), to the RCC surface like bathroom, toilet, balcony & utility area applied @ 1.7kg/m² in 2 coats to achieve 1mm DFT, having Elongation at break >50% as per ASTM D 412, Tensile strength >1N/mm² as per ASTM D 412, Adhesion strength: 0.80 N/mm² as per ASTM D 4541, crack bridging upto 1mm as per ASTM C 836, Water penetration (5 bar pressure) as per BS EN 12390. The finished cost to include surface preparation, making coving of 50 mm X 50mm at all right angles of wall Junction with Polymer Repair Mortar and lay 45 gsm glass fibre mesh over the angle fillet when the first coat is still wet, treatment of cracks completely as per specification..	Sqm	349.00
	NEW Item	BMT-H.139	Newly Constructed Roof/Bathroom/Toilet/ balcony/utility with Cementatius Waterproof coating below 500 Sq.m Providing and Applying CFTRI approved two component flexible polymer modified acrylic cementitious waterproofing coating with a mix ratio of (5 Liquid :7 Powder) to the RCC surface like Roof, bathroom, toilet, balcony & utility area applied @ 2.2kg/m² in 2 coats to achieve 1.2mm DFT, having Elongation at break >120% as per ASTM D 412, Tensile strength >1N/mm² as per ASTM D 412, Adhesion strength: 0.80N/mm² as per ASTM D 4541, crack bridging upto 2mm as per ASTM C 836. The finished cost to include surface preparation, making coving of 50 mm X 50mm at all right angles of wall Junction with Polymer Repair Mortar and lay 45 gsm glass fibre mesh over the angle fillet	Sqm	494.00

			when the first coat is still wet, treatment of cracks completely as per specification.		
	NEW Item	BMT-H.140	Newly Constructed Roof/Podium with 1K PU Waterproof coating upto 2000 Sq.m Providing and Applying single component Polyurethane based cold applied seamless waterproofing coating to the RCC surface like Roof & Podium area applied @ 2.4kg/m² in 3 coats to achieve 1.5mm DFT, including a prime coat of solvent free, medium viscous, epoxy primer @0.2L/m² and protection with 120gsm Geo- textile over the 7 days cured waterproofing membrane. The Waterproofing material shall have Solids > 85%, Tensile strength >2 Mpa as per ASTM D 412, Elongation at break >400% confirms to ASTM C 1305 for crack bridging ability (no cracks up to 3.2mm) Shore A Hardness >55 as per ASTM D 2240, Adhesion to peel after water immersion as per ASTM C 794 at 5.2N. Resistance to root penetration as per UNE CN/ TS 14416. The finished cost to include surface preparation, making coving of 50 mm X 50mm at all right angles of wall Junction with Polymer Repair Mortar and lay 60gsm Geo-textile over the angle fillet when the first coat is still wet, treatment of cracks and laying 120GSM Geo-textile as separation/protective layer over the fully cured PU coating completely as per specification.	Sqm	972.00
	NEW Item	BMT-H.141	Newly Constructed Roof/Podium with 2K PU Waterproof coating above 2000 Sq.m Providing and applying two component Polyurethane based cold applied seamless waterproofing coating to the RCC surface like Roof & Podium area applied @ 2.1kg/m² in single coat using 3mm notched trowel to achieve 1.5mm DFT, including a prime coat of solvent free, medium viscous, epoxy primer @0.2L/m² and protection with 120gsm Geo-textile over the 7 days cured waterproofing membrane. The Waterproofing material shall have Solids > 98%, Tensile strength >6 Mpa, Elongation at break >600% as per ASTM D 412, crack bridging ability (no cracks up to 3.2mm) confirms to ASTM C 1305, Puncture resistance >300N as per ASTM E154, Shore A Hardness >70 as per ASTM D 2240, Adhesion to peel after water immersion as per ASTM C 794 at 5.2N. Resistance to root penetration. The finished	Sqm	1301.00

			cost to include surface preparation, making coving of 50 mm X 50mm at all right angles of wall Junction with Polymer Repair Mortar and lay 60gsm Geo-textile over the angle fillet when the first coat is still wet, treatment of cracks and laying 120GSM Geo-textile as separation/protective layer over the fully cured PU coating completely as per specification.		
	NEW Item	BMT-H.142	STP (inside) waterproofing with Anticorrosive & Protective Coating Providing and Applying two component flexible polymer modified acrylic cementitious waterproofing coating with a mix ratio of (5 Liquid :7 Powder) to the RCC surface of the STP tank applied @ 2.2kg/m2 in 2 coats to achieve 1.2mm DFT, having Elongation at break >120% as per ASTM D 412, Tensile strength >1N/ mm2 as per ASTM D 412, Adhesion strength: 0.80N/mm2 as per ASTM D 4541, crack bridging upto 2mm as per ASTM C 836. The finished cost to include surface preparation, making coving of 50 mm X 50mm at all right angles of wall Junction with Polymer Repair Mortar and lay 45 gsm glass fibre mesh over the angle fillet when the first coat is still wet, treatment of cracks completely as per specification. Followed by applying 15 mm thick dimensionally stable fibrous reinforced cementitious structural grade dual shrinkage Polymer Mortar on as protective plastering @ 29kg/m2. The material having Compressive strength of 38 MPa at 28 days as per EN 12190, Adhesive Bond Test, >1.5 Mpa as per EN 1542, followed by Water curing by sprinkling water for 3 times a day for 5- 7 days. followed by applying two component coal tar epoxy-based coating on inside surface of Sewage & Effluent treatment tank @ 0.30 kg/m2 in 2 coats to achieve a DFT of 200 microns when fully cured. Ensure that this coating is applied over the protective plaster. The material shall have Scratch resistance, for 7kg load as per ASTM : D 7027 - 05, Chemical resistance, immersion in dilute acid alkali & salt solutions – 7 days confirms to ASTM : C 868, Salt Spray resistance confirms to ASTM : B 117	Sqm	1499.00

	NEW Item	BMT-H.143	UGT/OHT (inside) waterproofing with Anti-microbial Coating Waterproofing: Providing and Applying CFTRI approved two component flexible polymer modified acrylic cementitious waterproofing coating with a mix ratio of (5 Liquid :7 Powder) to the RCC surface of the UGT/ OHT tank applied @ 2.2kg/m2 in 2 coats to achieve 1.2mm DFT, having Elongation at break >120% as per ASTM D 412, Tensile strength >1N/ mm2 as per ASTM D 412, Adhesion strength: 0.80N/mm2 as per ASTM D 4541, crack bridging upto 2mm as per ASTM C 836. The finished cost to include surface preparation, making coving of 50 mm X 50mm at all right angles of wall Junction with Polymer Repair Mortar and lay 45 gsm glass fibre mesh over the angle fillet when the first coat is still wet, treatment of cracks completely as per specification. Followed by applying 15 mm thick dimensionally stable fibrous reinforced cementitious structural grade dual shrinkage Polymer Mortar on as protective plastering @ 29kg/m2. The material having Compressive strength of 38 MPa at 28 days as per EN 12190, Adhesive Bond Test, >1.5 Mpa as per EN 1542, followed by Water curing by sprinkling water for 3 times a day for 5- 7 days. Followed by applying two component, water-based food grade epoxy resin coating on inside surface of Potable water tank having anti- algae, antifungal, Non-toxic, hygiene cum damp-proof coating Certified by CFTRI as per 21 CFR 175 – 300 of US – FDA, having mixing Ratio (Base: Hardener: Water) – 1:1:1 to be applied @ 0.35 Kg/m2 in 2 coats. Ensure that this coating is applied over the protective plaster. The Waterproofing material shall have Specific Gravity: 1.2, Water vapor permeance: 244.48 g/m2/24 hrs, as per IS 7809/Pt 2/1977, Adhesion strength: 2 N/mm2 as per ASTM D 4541: 02. The finished cost to include surface preparation completely as per specification	Sqm	1481.00
	NEW Item	BMT-H.144	Acrylic anti-carbonation coating for New Concrete (Bridges & Flyover) Providing and Applying Acrylic anti-carbonation coating on concrete surface, which is single component, cold applied, water based acrylic polymer and Specially formulated to Protect RCC substrate that is directly exposed to atmospheric conditions like UV radiation, heavy rain, industrial pollution & carbonation. Apply without any dilution @ 0.25L/m2 in 2 coats to achieve DFT of 225 microns, The coating shall have Confirms in accordance with IRC SP:80-2008, Chloride Ion penetration –	Sqm	306.00

			Concrete Guard (Coulombs) 575 as per ASTM C 1202 : 2019, SRI value of 104 as per ASTM E 1980 : 19 and Crack bridging ability up to 2mm, including priming the surface with 1 coat diluted with water in the ratio 1:1 spreading @ 0.125 L/m2 as self-priming coat. The finished cost to include surface preparation, treatment of cracks completely as per specification as per the direction of the Engineer In charge.		
	NEW Item	BMT-H.145	Exterior Wall Waterproof cum Decorative Coating Providing and Applying high build exterior waterproof coating for external wall, parapet & Chajja, which is single component, cold applied, Reactive Acrylate copolymer technology. Apply one base coat of universal elastomeric exterior waterproof coating @0.25L/m2 and 2nd coat with Acrylic emulsion top coat which can be tinted to any colour @ 0.17L/m2, including 2 coats DFT will be min. 170 microns, The material having followed technical properties: Attains hairline crack bridging up to 2 mm as per EN 1062 part 7, Elongation of >100 % as per ASTM D 412; Tensile strength 2.50 Mpa per ASTM D 412, including priming the surface with 1 coat of Efflorescence resistant penetrating primer dilute with water in the ratio 2:1 spreading at the rate of 0.125 l/m2 in the SSD condition. The finished cost to include surface preparation, making coving at Junction, treatment of cracks completely as per specification.	Sqm	256.00
	NEW Item	BMT-H.146	Treating mild Dampness in Interior Walls Providing and Applying Acrylic Co Polymer single component specially designed waterproof protective coating that prevents damp patches on walls without any dilution at rate of 0.25kg/m2 in 2 coats to achieve total dry film thickness of 170 microns DFT. The material having followed technical properties: crack bridging ability up to 1mm as per EN 1062, Tensile strength $\geq$ 2N/mm2 as per ASTM D 412, adhesion strength 1.5N/ mm2 as per ASTM D4541. The finished cost including surface preparation completely as per specification.	Sqm	247.00
	NEW Item	BMT-H.147	Treating Severe Dampness & Rising dampness in Walls Providing and Applying two component flexible polymer modified acrylic cementitious waterproofing coating with a mix ratio of (5 Liquid :7 Powder) to the RCC surface or walls applied @ 2.2kg/m2 in 2 coats to achieve 1.2mm DFT, having Elongation at break >120% as per ASTM D 412, Tensile strength >1N/ mm2 as per ASTM D 412, Adhesion strength: 0.80N/mm2 as per ASTM D 4541, crack	Sqm	1191.00

			bridging upto 2mm as per ASTM C 836. The finished cost to include surface preparation & treatment of cracks completely as per specification. Followed by applying 15 mm thick dimensionally stable fibrous reinforced cementitious structural grade dual shrinkage Polymer Repair Mortar on internal wall damp patches @ 29kg/m2. The material having Compressive strength of 38 MPa at 28 days as per EN 12190, Adhesive Bond Test, >1.5 Mpa as per EN 1542, followed by Water curing by sprinkling water for 3 times a day for 5- 7 days. Ensure that removing internal wall plaster up to the brick level. Extend up to minimum 2 feet in wide in excess to the damp patches. clean the effected surface followed by waterproof coating should be applied across the entire surface and apply a coat of spatter dash bond coat over cured coating. The dashing shall consist of (1-part SBR : 1 Part cement: 2 part wash sand) mixed to thick slurry and kept well stirred prior to applying the Polymer Repair Mortar. The finished cost to include surface preparation completely as per specification.		
	NEW Item	BMT-H.148	Treating Active leakage from Concrete walls Providing and grouting with single component Polyurethane Foam injection grout at dripping leakage locations, grout mixed at ratio of 10:1 (10 parts of Resin: 1 part accelerator) at the rate of 0.40kg/nozzle which will foam after reaction with water/ moisture, cream time <20 seconds, rise time <30 seconds, foam expansion more than 30 times. It has a mixed viscosity of <350 cP as per ASTM D 2196. Allow the PU foam grout to cure for 5 -10 mins. Providing and grouting with two component Polyurethane based resin injection grout mixed at ratio of 2:1 (2 parts of Base: 1 part Hardener) which will injected through same nozzle at the rate of 0.30kg/nozzel which gives Adhesion strength >2.5 MPa, Adhesion in wet concrete >1.5MPa, Elongation >80%. It has a mixed viscosity of <350 cP as per ASTM D 2196. The finished cost to include surface preparation, fixing of non-return valve injection packers at dripping leakage locations and damp patch locations, seal the nozzles with polyester resin anchor grout Instant leak plug 0.2kg/nozzle. All the application procedure shall be as per the direction of the Engineer In charge.	Nozzle	1989.00
	NEW Item	BMT-H.149	Structural Strengthening with Epoxy Injection Grout Providing and grouting with two component low viscous Moisture Insensitive Epoxy Injection Grout to strengthen the structure at cocrete cracks. The material having	Nozzle	1548.00

			mixing ratio - (Base : Hardener) - 100:60 (by weight) at the rate of 0.50kg/nozzle, which gives compressive strength of 70N/mm² in 7days as per BS6319:part 2, Flexural strength of 30N/mm² in 7days as per BS6319:part 3, Tensile strength of 15N/mm² in 7days as per BS6319:part 7, epoxy resin based injection grout meets the requirement of BS 6319 & ASTM C 881. The finished cost to include surface preparation, fixing of non-return valve injection packers at concrete cracks, seal the nozzles with polyester resin anchor grout Instant leak plug 0.2kg/nozzle. All the application procedure shall be as per the direction of the Engineer In charge.		
	NEW Item	BMT-H.150	Retaining wall/ UG tank wall (outside) Waterproofing with SBS Membrane Providing and laying water proofing treatment to the Retaining wall, water retaining structures outside with fully bonded 1.6mm Thick SBS modified self-adhesive, cross laminated HDPE lining waterproofing membrane, conforming to IS 16471:2017 Type A, requirements of UG waterproofing structures, The SBS membrane shall have Mass per Unit Area > 1.8 Kg/m² as per ASTM D 5147, Puncture resistance > 200 N as per ASTM E 154, Elongation > 180% as per ASTM D 412-06, Tensile Strength > 4 Mpa as per ASTM D 412- 06, Tear resistance > 20 N/mm as per ASTM D 4073, Hydrostatic pressure 50M as per DIN 1048. The lap with HDPE membrane shall be 100mm treated with TS tape, followed by the installation of 8-10mm THK polyethylene dimpled drain board having compressive strength > 400kN/m² (as per ISO 25619-2). The finished cost includes surface preparation, making coving and a coat of solvent based bituminous primer @ 0.25l/m² on entire surface before laying membrane completely as per specification.	Sqm	927.00
	NEW Item	BMT-H.151	Underground structures waterproofing with HDPE membrane Providing and laying water proofing treatment to the Rafts, Below grade slab, Lift pits, water retaining structures with fully bonded 1.5 mm thick HDPE waterproofing pressure sensitive adhesive membrane over PCC before laying raft concrete having higher puncture resistance of 1000N as per ASTM E 154, confirming to BS 8102 & IS 16471:2017, requirements of UG waterproofing structures. Laying adjacent sheets by keeping overlap of 75mm, end overlaps to	Sqm	786.00

			be treated using double sided tape. The membrane shall have Tensile strength >25 Mpa as per ASTM D 412, Elongation > 500% as per ASTM D 412, Hydrostatic head resistance >70m head of water as per ASTM D 5385, Low Temperature Flexibility: -25 deg C, Peel Adhesion to Concrete >880 N/m as per ASTM D 903 Modified, UV Exposure > 45 Days. The finished cost including surface preparation completely as per specification.		
	NEW Item	BMT-H.152	Expansion Joint Treatment with Seal Tape Providing and laying with 1.0 mm thick FPO membrane to seal the expansion joint. The tape having mechanical properties like, Elongation>500%, Tensile Strength >12N/mm², Tear Strength >200N, Water tightness 400 kPa/72hrs confirming to DIN EN 1928-B. Ensure that apply Two part Epoxy Adhesive @ 1.4kg/m to get 1-2mm thick on the prepared surface before placing the tape and after placing seal with same epoxy adhesive which having Bond Strength with concrete 1.5N/mm², Compressive Strength @ 7 days, ≥45N/mm² as per BS 6319 Part 2, Tensile Strength @ 7 days, ≥18N/mm² as per BS 6319 Part 7, Shear Strength @ 7 days, ≥8N/mm² as per BS 6319 Part 4, Flexural Strength @ 7 days, N/mm² as per BS 6319 Part 3. The finished cost including surface preparation, filling foam backer rod, applying masking tape on both sides of the joint & polysulphide sealant filling on gap completely as per specification.	Rm	1848
	NEW Item	BMT-H.153	Corrugated Metal Sheets waterproofing cum Heat reflective coating Providing and applying heat reflective environmental friendly, 100% Pure Acrylic elastomeric waterproof coating on metal sheets. Replace roof fasteners, as required and needed. Sealing up of all lapping joints, gaps, flashing and capping with 2 component PMMA base waterproof Coating @3kg/m² including metal primer @.1L/m² and fleece at a 150mm wide strip. Preparing the surface by cleaning with a brush and removing the rust using a chloride-free chemical. Apply one coat of anti-corrosive primer at 0.15L/m² for GI/ Metal surfaces and apply one coat of solvent-free, medium-viscous, epoxy primer at 0.15L/m² for powder- coated surfaces. Apply 2 coats of 100% Pure Acrylic waterproofing coating @ 0.8L/m² having Elongation 190% as per ASTM D 412, tensile strength 1.5 N/mm², SRI Index 108 as per ASTM E 1980-01. The finished cost to include surface preparation completely as per specification.	Sqm	1250

	NEW Item	BMT-H.154	Expansion Joint filling with Polysulphide sealant upto 30mm width - Horizontal Providing and laying with two-part elastomeric fuel resistance, UV resistant, Non-toxic once cured, resistant to flame, pouring grade liquid polysulphide sealant to fill the expansion joint, Control joints in parking area, construction joint in airport runway, Tanks, bridges & concrete roads. The sealant shall have Elongation min. 450% confirms to ASTM D 412, movement accommodation for butt joint 25% & for lap joints 50%. The sealant should meets the requirement of BS 5212, BS 4254 & ISO:11600. Ensure that apply a coat of polysulphide sealant primer @0.5L/m2 to get better adhesion on prepared surface before placing the sealant. The finished cost including surface preparation, filling foam backer rod, applying masking tape on both sides of the joint & polysulphide sealant filling on gap completely as per specification.		
		BMT-H.154(A)	30mm Width	Rm	453
		BMT-H.154(B)	20mm Width	Rm	302
		BMT-H.154(C)	10mm Width	Rm	151
	NEW Item	BMT-H.155	Expansion Joint filling with Polysulphide sealant upto 30mm width - Vertical Providing and laying with two-part elastomeric UV resistant, non-toxic gun grade liquid polysulphide sealant to fill the expansion joint, sealing joints in water retaining structure. The sealant shall have Elongation min. 500% confirms to ASTM D 412, movement accommodation for butt joint 25% & for lap joints 50%. The sealant should meets the requirement of BS 4254 & ISO:12118. Ensure that apply a coat of polysulphide sealant primer @0.5L/m2 to get better adhesion on prepared surface before placing the sealant. The finished cost including surface preparation, filling foam backer rod, applying masking tape on both sides of the joint & polysulphide sealant filling on gap completely as per specification.		
		BMT-H.155(A)	30mm Width	Rm	545
		BMT-H.155(B)	20mm Width	Rm	363
		BMT-H.155(C)	10mm Width	Rm	182

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
		II.SUB-SECTION	INTERGRAL WATERPROOFING COMPOUND		
362	MAT-05372	BMT-H.85	Integral Cement Waterproofing Admixture for Concrete Slabs and mortar plastering works. (Dosage : 100ml Per bag of 50 Kgs Cement) Complies with I.S. 2645-2003	1 Ltr	221
363	MAT-05373	BMT-H.86	Liquid Concentrated Micronized Cement waterproofing Compound for Slabs, mortar plastering and water retained structures. (Dosage : 500ml per bag of 50 Kgs Cement) Complies with I.S. 2645-2003	1 Ltr	139
		II.SUB-SECTION	PLASTICIZERS AND WATER REDUCING AGENT		
364	MAT-05374	BMT-H.87	Concrete plasticizers and Water reducing admixture (not air entraining agent) (Dosage : 15-20ml per bag of 50 Kgs Cement)- Complies with I.S. 9103-99 Ideal to use as concrete admixture for workability retension of slump and control water cement ratio of M 20 + grade concrete for slabs /roads works and other concrete works	1 Ltr	233
			SUPER PLASTICIZERS AND WATER REDUCING CONCRETE ADMIXTURES		
365	MAT-05375	BMT-H.88	Super plasticizer and water reducing concrete admixture base on Ligno Sulphide Complies with IS 9103 & ASTM C 494 (Dosage : 200ml to 300mlper bag of 50 Kgs Cement) For M25 + grade concrete works like Road Projects / Canal linings/ Dams / Reservoirs / Building's concrete works.	1 Ltr	86
366	MAT-05376	BMT-H.89	High performance super plasticizer and water reducing admixture based on lignosulphide and napthalene blended	1 Kg	89

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			Complies with 9103/4-99 (Dosage : 300ml to 500ml Per Bag of 50 Kgs Cement) For M30+ grade concrete works like Road Projects / Canal linings/ Dams / Reservoirs / Building's concrete works.		
367	MAT-05377	BMT-H.90	High performance super plasticizer and water reducing admixture based on naphthalene blended Complies with 9103/4-99 (Dosage : 300ml to 500ml Per Bag of 50 Kgs Cement) For M40+ grade concrete Works like road projects / Canal linings / Dams / Reservoirs / Building's concrete works	1 Kg	95
			SELF COMPACTING CONCRETE ADMIXTURES		
368	MAT-05378	BMT-H.91	High strength super plasticizers and water reducing agent based on polycarboxylic technology. Complies with IS 9103/ASTM C 494 (300ml to 1 Ltr Per Bag of 50 Kgs Cement) For M-40+ + concrete structures in coastal areas, for early high strength.	1 Kg	132
			RETARDING ADMIXTURES		
369	MAT-05379	BMT-H.92	Super plasticizer, high range water reducing and retarding concrete admixture of naphthalene blended. (Complies with 9103-99) (Dosage : 300ml to 500ml Per bag of 50 Kgs Cement) For delaying of initial setting time and M 40+ Grade concrete works.	1 Kg	100
			CORROSION INHIBITOR ADMIXTURE		
370	MAT-05380	BMT-H.93	High strength super plasticizer and corrosion inhibitor for concrete (Complies with IS 9103-99 & EN 1504-9 Method 11.3) (Dosage : 200ml to 500ml Per Bag of 50 Kgs Cement) For Concreting under extreme corrosion effected areas / coastal areas / industrial constructions to protect the steel reinforcement. Anti Corrosion and leak proof Crack Proof,Water Proof, Concrete Hardener Admixture liquid.	1 Kg	115
			AIR ENTRAINING AGENT		
371	MAT-05381	BMT-H.94	Hi-power concentrated Air Entraining,	1 Ltr	190

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			Plasticizing & Water reducing compound Complies with IS 9103-99 & ASTM C 260 (Dosage 20ml per bag of 50 Kgs Cement) Ideal to use for the construction of Bridges, Barrages, Dams, Tunnels, Piles, Foundations, Towers etc.,		
372	MAT-05382	BMT-H.95	Two component High Power Polyester Resin Anchor Grout Compound Complies with ASTM-827 /SNF.CRDC-621 (Yield 0.5 Ltrs / 1 Kg Pack) For Anchoring / fix the steel bars into the rocks, concrete for foundations, extension of concrete.	1 Kg	372
IV. SUB-SECTION			GROUTS		
373	MAT-05383	BMT-H.96	Non-shrink Free flow high strength precision grout Complies with BS 1881 Part 1161983. For machinery / thin sections of concrete joints Filling.	1 Kg	42
374	MAT-05384	BMT-H.97	Low viscosity Epoxy resin injection grout -Two parts system. Complies with BS 6920 / ASTM 881-78 (Density 1.07 Kg Per Ltr) For Structural strengthening, filling of honey comb / voids in the concrete.	1 Kg	919
375	MAT-05385	BMT-H.98	Non-shrink, free flow, high strength grout admixture Dosage : 250 Grams Per Bag of 50 Kgs Cement. (Complies with B.S.1881 Part 1161983)	1 Kg	70
376	MAT-05386	BMT-H.99	High performrance, High build expansive acqua-reactive water barrier polyurethane grout.	1 Kg	1742
V. SUB- SECTION			BONDING AGENTS		
377	MAT-05387	BMT-H.100	Acrylic based bonding adhesive (Mix: 1:1 ratio of cement) Coverage : 50 SFT/Ltr/Coat Depending on the substrate On terrace old concrete to new mortar / screed.	1 Ltr	177
378	MAT-05388	BMT-H.101	Styrene butadiene rubber based bonding agent for mortar/ concrete	1 Ltr	516

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			(Mix: 1:1 ratio of cement) For ceiling / concrete repairs and bonding. Coverage : 50 SFT/Ltr/Coat Depending on the substrate		
379	MAT-05389	BMT-H.102	Structural element concrete bonding agent old to new concrete epoxy bonding agent : (Two Parts system of Epoxy Bonding adhesive) Complies with ASTM-C 881 Coverage : 20 – 25 SFT / Kg /Coat For Structural concrete repairs / bonding.	1 Kg	1001
VI. SUB-SECTION			SEALANTS		
380	MAT-05390	BMT-H.103	Single component polyurethane sealant (Gungrade/ Pour Grade) Complis with : ASTM C 920 -95 Type S / Grade NS, Class 25, and BS ; 5212 Ideal to use for Filling of runways / buildings, expansion joints, construction joints, Terrace Cracks, Sealing joints at doors, windows, facades, frames, crack etc.,	600ml	556
381	MAT-05391	BMT-H.104	Two part polysulphide sealant (Gun / Pour Grade) Complies with ASTM C 920 - 95 / DIN 18549 TT - 5 - 00227 E/BS 4254 -83 Ideal to use for Expansion / construction joints of runways, buildings etc.,	1 Kg	469
382	MAT-05392	BMT-H.105	Acrylic Latex Caulking Compound Complies ASTM-C-834-91 Ideal for exterior and interior crack filling works, Excellent bonding strength to adjoining surface.	1 Kg	365
VII. SUB-SECTION			PROTECTIVE WATERPROOF COATINGS / CEMENT BASED COATINGS :		
383	MAT-05393	BMT-H.106	Two component sysem High durable cementitious acrylic based waterproofing systems : Complies with ASTM D 4541 / BS EN 12390 / DN 1048 (2 to 3 Sqm in two coats) For Terrace, Water Tanks, Walls Waterproof Coatings of Two Part System.	1 Ltr	163
384	MAT-05394	BMT-H.107	Acrylic Polymer Elastomeric	1 Ltr	404

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			Cementitious Waterproof Coatings Surface treatments for Terrace, Water Tanks, Walls, Reservoirs Waterproofing Coatings.Complies with ASTM D4541 / BS EN 12390. (Coverage :50 to 60 SFT / Ltr / coat)		
			PURE ACRYLIC ELASTOMERIC COATINGS		
385	MAT-05395	BMT-H.108	Single component, High solid, cold applied, Acrylic elastomeric waterproof membrane coating Complies with ASTM C 836 / 89A & ASTM C 297 (Coverage : 50 to 60 SFT Per/Ltr/Coat) Wherever highly flexible, crack Bridging,waterproofing required for Terrace, Walls Highly Flexible Waterproof Liquid Membrane pure Acrylic Coatings. (for brush / spray application add 20% water per Ltr)	1 Ltr	492
386	MAT-05396	BMT-H.109	Rubberized elastomeric flexible waterproof coating Complies with ASTM 836 / 89 A & ASTM C 297 Coveage : 40 to 50 SFT / Ltr / coat (for brush / spray application add 20% water per Ltr)	1 Ltr	345
			BITUMINOUS COATING		
387	MAT-05397	BMT-H.110	Polyurethane blended Bituminous waterproof coating system - Complies with ASTM C 836 /D 638 / DIN - 1048 / ASTM D 1004 - 76 (Coverage :40 to 50 SFT / Kg / coat) Ideal to use as waterproof of RCC substrates, Roofs, Sloped roofs, Basements. Provides jointless and seamless membrane waterproofing. (for brush / spray application add 20% water per Ltr)	1 Kg	652
388	MAT-05398	BMT-H.111	High Performance Acrylic blended Bituminous waterproof coating systems. Complies with ASTM C 836 (Coverage : 40 to 50 SFT / Ltr / coat) (for brush / spray application add 20% water per Ltr)	1 Kg	403
			SOLAR REFLECTIVE COATING		
389	MAT-05399	BMT-H.112	Pure Acrylic Solar Reflective insulator coating Complies with ASTM - G - 154 : 2000 & ASTM E 903 / EN 1062 - 3 requirement of EN 1504 / 2 : EN 1062 -	1 Ltr	231

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			6 Coverage : 15 SFT / Ltr / 3 Coats (for brush / spray application add 20% water per Ltr		
			EPOXY COATINGS		
390	MAT-05400	BMT-H.113	Two component Water thinnable Food Neutral Epoxy coating (Complies with ASTM - C- 881 / EN 13813) Coverage : 70 to 80 SFT per Ltr / coat Ideal to use as internal coatings for potable water tanks, reservoirs, sumps and walls. Part - I 1 Kg : Part -II 1/2 Kg dilute with 1 Ltr of water	1 Kg	486
			POLYURETHANE COATING		
391	MAT-05401	BMT-H.114	Single component cold applied polyurethane waterproof coating - Complies with ASTM 836 / EN 1062-3 requirement of EN 1504 - 2 Coverage : 300 Grams Per coat / Sqm. brush / spray application add 20% water per Ltr	1 Kg	462
		VIII. SUB-SECTION	ANTI CORROSIVE AGENTS		
392	MAT-05402	BMT-H.115	Acrylic based Anti corrosive coating To protect the exposed reinforcement/steel structures against corrosion. Coverage : 40 SFT Per Ltr / Coat.	1 Ltr	400
393	MAT-05403	BMT-H.116	Rust converter–rust encapsulating coating for steel During repairs to protect, to convert the rust of reinforcement / steel. Coverage : 50 SFT Per Ltr / Coat	1 Ltr	558
394	MAT-05404	BMT-H.117	High range zinc rich epoxy resin primer for reinforcement steel protection against corrosion. Coverage : 4 Sq.Mtr. /Ltr / Coat	1 Kg	565
IX. SUB-SECTION			CURING COMPOUND&MISCELLANEOUS CHEMICALS		
395	MAT-05405	BMT-H.118	Acrylic blended water based concrete curing compounds Complies with ASTM - C - 309 Class - A Types I & II Coverage : 3.5 to 4 Sqm / Kg / Coat	1 Kg	70

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			CONCRETE REPAIR ADMIXTURES		
396	MAT-05406	BMT-H.119	Acrylic polymer modified reinstatement concrete /mortar admixture Dosage : 1 to 2 Ltrs Per Bag of 50 Kgs Cement can be mixed with required aggregates To achieve trusted High Strength Concreting / Structural rehabilitation / concrete repairs.	1 Ltr	515
			CRYSTALLIZATION COMPOUND		
397	MAT-05407	BMT-H.120	Concrete waterproofing with crystallization system by blocking inner pores and cavities of concrete. Coverage : 1.25 Kg per Sqm / Coat For Negative Water Pressure Treatments like Cellar / Ceiling areas etc.,	1 Kg	412
			PLUGGING COMPOUND		
398	MAT-05408	BMT-H.121	Fast setting cement based plugging compound. To arrest water flow leakages. (Powder Form :mix with water direct application	1 Kg	100
			SHOTCRETE / GUNITING ADMIXTURE		
399	MAT-05409	BMT-H.122	Set Accelerator for sprayed concrete and plasticizer Complies with IS 9103-99 / ASTM C 494 Type C / BS 5075 Dosage : 1 Kg to 3 Kgs per Bag of 50 Kgs Cement Depend on setting time required For shotcrete / Gunniting / Emergency concrete works	1 Kg	100
400	MAT-05410	BMT-H.123	Quick setting, rapid hardening and water proofing compound Complies with ASTM C 494 Type C / IS 9103 -99 & BS 5075. Dosage : 1 Kg to 3 Kgs Per Bag of 50 Kgs Cement Depend on setting time For emergency works/Anti wash and under water concreting.	1 Ltr	90
			MICRO CONCRETE		
401	MAT-05411	BMT-H.124	High strength non-shrink cementitious micro concrete	1 Kg	45
			TILE ADHESIVES / GROUTS		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
402	MAT-05412	BMT-H.125	Tile Adhesive. Confirms to IS 15477-2004 for both type I & II / BS : EN 12004 CTT adhesive. For excellence adhesion, improved workability waterproof and also heat resistant tile fixing adhesive. At 3mm thickness 65-70 SFT	1 Kg	65
403	MAT-05413	BMT-H.126	Three component system epoxy grout for Vitrified tiles, Ceramic tiles and stones B.S. 5980 : 1980 / BS EN 120004, R 2 T. Depends upon tile dimension and grout width	1 Kg	798
404	MAT-05414	BMT-H.127	Polymer Modified Tile Grout Complies with BS EN 13888, CG 2AW 4 - 4.5 Sqm / Kg of 150 mm x 150mm tile size mix 1 Part Water with 4 Parts Powder Pack	1 Kg	70
405		BMT-H.133	SPECIALISED POLYSULPHIDE / POLYURETHANE / HIGHBRED ACRYLIC / SEALANT TREATMENT TO THE OLD / EXISTING EXPANSION JOINT IN THE TERRACE, COLUMN, BEAM 1. Cut and remove the existing expansion joint in the screed for a minimum width of 200 mm and a depth of screed (up to the mother slab) by using diamond disc cutting machine and dispose the debris as per the department instruction. All elevated kerb wall both sides of the expansion joint along with the top free laying slab, cover etc as per the site conditions under the scope of the main contractor / client 2. Remove the existing filling for a minimum depth of 40 mm using sharp knife (approximate size 25 x 40 mm) as per the site condition. 3. If the site condition allows to insert backer rod, remove the existing filling for a minimum depth of 70 mm from the top (the clear filling of sealant should be 40 mm) and insert inside the joint. 4. Clean the surface with air blower up to receive a dust free surface and make sure the surface is sound dry or the moisture content is less than 5 %. 5. Apply one coat of Penetrative	RMT	2719

			Primer and allow touching dry. 6. Fill the joint by using a sealant gun / notch trowel as per site condition up to the required depth and width and allow to dry for a minimum period of 1 day as per the climatic condition. 7. Apply two coat of penetrative sealer coat site mixed primer - mix with portable water and OP Cement in the ratio of 2:1:3 cement by using slow speed mixer machine with paddle for a period of 2 to 3 minutes up to receive a homogeneous mix) @ 1.000 Liter per SQM in the entire screed removed portion (vertical and horizontal faces) of 200 mm along with saturated (saturated with MixPRIME AC100: Water: OP Cement in the ratio of 2:1:1) in between the two coats and allow to cure for a period of 6 hours. 8. Do the necessary levelling plastering with cement sand mortar 1:2:4 (6 mm aggregate) screed along with the addition of MixBOND SBR Super and PLAST FIBER 3S as per the following for a minimum thickness of removal. a. Mix the MixBOND SBR Super @ 2 Liter / Bag Cement in the ratio of 1:4 Mortar (Pre mix the admixture in the portable water for preparing the mortar) b. Add 100 Gram PLASTFIBRE 3S in the above liquid and stirred well with a slow speed drill with paddle. c. Prepare the cement sand screed in the ratio of 1:2:4 with above prepared liquid for the suitable consistency. d. Necessary curing and drying for a minimum period of 4 days. 9. In wet condition, provide a dummy expansion joint on the top of the screed for a minimum size of 10 x 10 mm by using sharp trowel 10. Apply one coat of Penetrative in the entire surface of the dummy joint and allow to touch dry for a period of 30 minutes. Fill the in the joint by using a sealant gun / notch trowel as per site condition up to the required depth and width		

			Procedure for Waterproofing System – 500 mm width 1. Apply one coat of penetrative sealer coat site mixed - mix with portable water and OP Cement in the ratio of 2:1:3 (Two part MixPRIME AC100 : One Part water : 3 Part OP cement by using slow speed mixer machine with paddle for a period of 2 to 3 minutes up to receive a homogeneous mix) @ 1.000 Liter per SQM as per the porosity of the prepared mother slab by using roller brush / hand brush / Sprayer and allow to dry for a period of 6 to 8 Hrs after the laying of tensile reinforcement mat. 2. Lay the (as per site condition) on the top in the wet condition. In such a way place the MixMAT GFM 70/50 on the prepared surface and applied the slurry over also obtain the same technical property. 3. Apply one coat of penetrative primer @ 0.250 Liter per SQM by using roller brush / hand brush / sprayer and allow drying for a period of 6 Hrs. 4. Application of Base Coat Water Proofing System with @ 0.500 Kg / SQM by using roller brush / hand brush / sprayer and allow to dry for a period of 6 Hrs. 5. Application of Top Coat Water Proofing System with @ 0.500 Kg / SQM by using roller brush / hand brush / sprayer and allow to final curing for a period of 2 to 3 days equivalent compline with BS 5254, ASTM C 834, ASTM C 1253, ASTM D 4541, ASTM D 1117, ASTM D 5729 Note: - 1) No dilution or modification recommended except item no 7,8 and 1 in HR5 System. 2) The all materials should be procured as per the consumption with respect of the work order. 3) The application should be carried out by an approved agency. 4) The contractor should provide 5 years material warrantee from the Manufacturer and 5-year warrantee from the applicator or combined 5) The all-civil work such as cutting (elevated kerb wall with slab), removing cleaning and screed with cement sand and aggregate including all materials and labours should be under the scope of the main contractor / client as per the site condition and our requirement to complete the expansion joint treatment as per the BOQ / Tender document.		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
I.SECTION			GLASS MATERIALS (Landing cost – including loading, cost of conveyance & unloading)		
I.SUB- SECTION			PLAIN GLASS PANES		
406	MAT-01052	BMT-I.01	Plain Float Glass 4 mm thick	1 sqm	479
407	MAT-01053	BMT-I.02	Plain Float Glass 5 mm thick	1 sqm	585
408	MAT-01054	BMT-I.03	Plain Float Glass 6 mm thick	1 Sqm	735
409	MAT-01055	BMT-I.04	Plain Float Glass 8 mm thick	1 Sqm	1050
410	MAT-01056	BMT-I.05	Plain Float Glass 10 mm thick	1 Sqm	1218
411	MAT-01057	BMT-I.06	Plain Float Glass 12 mm thick	1 Sqm	1449
II..SUB- SECTION			PIN HEADED GLASS PANES		
412	MAT-01064	BMT-I.13	Pin headed Glass 4 mm thick	1 sqm	372
413	MAT-01065	BMT-I.14	Pin headed Glass 5 mm thick	1 sqm	489
III..SUB- SECTION			TINTED GLASS PANES		
414	MAT-01058	BMT-I.07	Tinted - Bronze/ Green Glass 4 mm thick	1 sqm	620
415	MAT-01059	BMT-I.08	Tinted - Bronze/ Green Glass 5 mm thick	1 sqm	735
416	MAT-01060	BMT-I.09	Tinted - Bronze/ Green Glass 6 mm thick	1 Sqm	876

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
417	MAT-01061	BMT-I.10	Tinted - Bronze/ Green Glass 8 mm thick	1 Sqm	1223
418	MAT-01062	BMT-I.11	Tinted - Bronze/ Green Glass 10 mm thick	1 Sqm	1533
419	MAT-01063	BMT-I.12	Tinted - Bronze/ Green Glass 12 mm thick	1 Sqm	1911
IV..SUB-SECTION			FROSTED/ GROUND GLASS PANES		
420	MAT-01066	BMT-I.15	Frosted / Ground Glass 4 mm thick	1 sqm	609
421	MAT-01067	BMT-I.16	Frosted / Ground Glass 5 mm thick	1 sqm	775
V..SUB- SECTION			TOUGHENED PANES		
422	MAT-01068	BMT-I.17	Toughened Plain Glass 5 mm (including Glass)	1 sqm	846
423	MAT-01069	BMT-I.18	Toughened Plain Glass 6 mm (including Glass)	1 sqm	963
424	MAT-01070	BMT-I.19	Toughened Plain Glass 8 mm (including Glass)	1 sqm	1170
425	MAT-01071	BMT-I.20	Toughened Plain Glass 10 mm (including Glass)	1 sqm	1430
426	MAT-01072	BMT-I.21	Toughened Plain Glass 12 mm (including Glass)	1 sqm	1620
J.SECTION			PAINTS & POLISHES (Landing cost – including loading, cost of conveyance & unloading)		
I.SUB-SECTION			PRIMERS, FILLERS & BASES		
427	MAT-01073	BMT-J.01	Supply of water based Cement Primer of Interior Grade- 1	1 Kg	80.5
428	MAT-01074	BMT-J.02	Supply of water based Cement Primer of Exterior Grade- 2	1 Kg	92.5
429	MAT-01104	BMT-J.31	Supply of wall putty of White Cement or Polymer or Cement based	20 Kg	420
430	MAT-01075	BMT-J.03	Supply of Red Oxide Primer Paint for iron works of Grade -1	1 Litre	168
431	MAT-01076	BMT-J.04	Supply of Zinc Chromate Yellow Oxide Primer paint for iron works	1 Litre	172
432	MAT-01077	BMT-J.05	Supply of Wood Primer	1 Litre	189
433	MAT-01078	BMT-J.06	Supply of Metal paste (Putty) for steel works	1 Kg	142
434	MAT-01079	BMT-J.07	Supply of Putty for wood work	1 Kg	115
435	MAT-01080	BMT-J.08	Supply of White Lead	1 Kg	129

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.).
1		2	3	4	5
436	MAT-01081	BMT-J.09	Supply of Synthetic clear Varnish	1 Litre	178
437	MAT-01082	BMT-J.10	Supply of Spirit	1 Litre	80
438	MAT-01083	BMT-J.11	Supply of Linseed Oil	1 Litre	67
439	MAT-01084	BMT-J.12	Supply of thinner for melamine polish/ french polish	1 Litre	120
440	MAT-01085	BMT-J.13	Supply of thinner for Poly-urethane polish	1 Litre	186
441	MAT-01086	BMT-J.14	Supply of French Polish	1 Litre	120
442	MAT-01087	BMT-J.15	Supply of ready made Wax Polish	1 Kg	552
443	MAT-01091	BMT-J.19	Supply of wood adhesive compound	1 Kg	170
444	MAT-01100	BMT-J.27	Supply of anti-corrosive grade - 1 bitumen paint of black colour	1 Litre	120
II.SUB-SECTION			DISTEMPER PAINTS		
445	MAT-01092	BMT-J.20	Supply of Dry Powder Distemper	1 Kg	19
446	MAT-01093	BMT-J.21	Supply of acrylic based Oil Bound washable Distemper	1 Kg	40
447	MAT-01099	BMT-J.26	Supply of paint grade white lime for wash	25 Kg	314
448	MAT-01095	BMT-J.23	Supply of Water proof Cement paint	1 Kg	58
449	MAT-01098	BMT-J.25	Supply of water proof Cement paint pack	25 Kg	1124
III.SUB- SECTION			EMULSION BASED PAINTS		
450	MAT-01097	BMT-J.24	Supply of acrylic emulsion paint interior grade having VOC (Volatile Organic Compound) content less than 50 grams/ liter.	1 Litre	175
451	MAT-01107	BMT-J.34	Supply of acrylic emulsion paint exterior grade with silicon additives having VOC (Volatile Organic Compound) content less than 50 grams/ liter.	1Lit	184
452	MAT-01108	BMT-J.35	Supply of acrylic emulsion paint weather proof water-based , modified acrylic with silicon additives exterior grade having VOC (Volatile Organic Compound) content less than 50 grams/ liter.	1Lit	258
IV.SUB- SECTION			SOLVENT BASED PAINTS		
453	MAT-01094	BMT-J.22	Supply of synthetic polymer luxury plastic emulsion paint of superior grade having VOC (Volatile Organic Compound) content less than 50 grams/	1 Litre	400

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			liter.		
V.SUB- SECTION			OIL BASED ENAMEL PAINTS		
454	MAT-01102	BMT-J.29	Supply of ready mixed Synthetic Enamel paints in all shades Grade - I having VOC (Volatile Organic Compound) content less than 50 grams/ liter.	1 Litre	176
455	MAT-01103	BMT-J.30	Supply of ready mixed Synthetic Enamel paints in all shades Grade - II having VOC (Volatile Organic Compound) content less than 50 grams/ liter.	1 Litre	205
VI.SUB- SECTION			TEXTURE PAINTS		
456	MAT-01105	BMT-J.32	Exterior Texture.	25 Kg	453
457	MAT-01106	BMT-J.33	Gold line Exterior Texture	25 Kg	1176
VII.SUB-SECTION			SPECIAL PAINTS		
459	MAT-01088	BMT-J.16	Supply of Melamine Polish	1 Litre	239
460	MAT-01089	BMT-J.17	Supply of Interior Grade Poly-Urethane Polish	1 Litre	400
461	MAT-01090	BMT-J.18	Supply of Exterior Grade Poly-Urethane Polish	1 Litre	924
462	MAT-01101	BMT-J.28	Supply of grade-1 aluminium paint	1 Litre	265
463	MAT-05415	BMT-J.36	Acrylic spray plaster in paste form made with specially selected inert mineral fillers, antifungal agents to protect the material the acrylic binding medium used gives good surface adhesion any grade Spray Plaster - Superfine (Interior Grade)	25Kg	400
464	MAT-05416	BMT-J.37	Acrylic coarse spray plaster in paste form made with specially selected inert mineral fillers, antifungal agents to protect the material the acrylic binding medium used gives good surface adhesion interior gradeAcrylic coarse	25Kg	468
465	MAT-05417	BMT-J.38	Supply of acrylic emulsion paint interior premium grade having VOC (Volatile Organic Compound) content less than 50 grams/liter	1 Liter	315
466	MAT-05418	BMT-J.39	Supply of Base coat as primer for natural textures and natural stone based paints - Exterior GradeBASE COAT	1Kg	93
467	MAT-05419	BMT-J.40	Acrylic spray plaster in paste form made with specially selected inert mineral fillers, antifungal agents to	25Kg	319

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			protect the material the acrylic binding medium used gives good surface adhesion exterior grade Spray Plaster (Exterior)		
468	MAT-05420	BMT-J.41	Supply of acrylic emulsion paint exterior premium grade with silicon additives having VOC (Volatile Organic Compound) content less than 50 grams/liter.Alltimate	1 Liter	183
469		BMT-J.42	Poly-urethane paint	1 Liter	299
K - SECTION			PARTICLE BOARDS (Landing cost – including loading, cost of conveyance, unloading)		
		I.SUB-SECTION	MELAMINE FACED PLAIN PARTICLE BOARDS		
470	MAT-01109	BMT-K.01	Melamine faced Single Deco PPB- 8 mm thick	1Sqm	639
471	MAT-01110	BMT-K.02	Melamine faced Single Deco PPB- 12 mm thick	1Sqm	740
472	MAT-01111	BMT-K.03	Melamine faced Single Deco PPB- 18 mm thick	1Sqm	853
473	MAT-01112	BMT-K.04	Melamine faced Single Deco PPB- 25 mm thick	1Sqm	950
474	MAT-01113	BMT-K.05	Melamine faced Single Deco PPB- 35 mm thick	1 Sqm	1563
475	MAT-01114	BMT-K.06	Melamine faced Twin Deco PPB- 8 mm thick	1 Sqm	683
476	MAT-01115	BMT-K.07	Melamine faced Twin Deco PPB- 12 mm thick	1 Sqm	844
477	MAT-01116	BMT-K.08	Melamine faced Twin Deco PPB-18 mm thick	1 Sqm	974
478	MAT-01117	BMT-K.09	Melamine faced Twin Deco PPB-25 mm thick	1 Sqm	1055
479	MAT-01118	BMT-K.10	Melamine faced Twin Deco PPB-35 mm thick	1 Sqm	2040
II.SUB- SECTION			INSULATING PARTICLE BOARDS		
480	MAT-01119	BMT-K.11	Natural Colour-Insulating Board - 12 mm thick	1 Sqm	265
481	MAT-01120	BMT-K.12	Natural Colour-Insulating Board - 18 mm thick	1 Sqm	389
482	MAT-01121	BMT-K.13	Natural Colour-Insulating Board - 25 mm thick	1 Sqm	445
483	MAT-01122	BMT-K.14	White Insulating Board - 12 mm thick	1 Sqm	293
484	MAT-01123	BMT-K.15	White Insulating Board - 18 mm thick	1	421

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
				Sqm	
485	MAT-01124	BMT-K.16	White Insulating Board - 25 mm thick	1 Sqm	385
III.SUB- SECTION			MEDIUM DENSITY FIBRE BOARD		
486	MAT-01125	BMT-K.17	Medium Fibre Board: Interior Grade - 6 mm thick	1 Sqm	394
487	MAT-01126	BMT-K.18	Medium Fibre Board: Interior Grade - 8 mm thick	1 Sqm	465
488	MAT-01127	BMT-K.19	Medium Fibre Board: Interior Grade - 12 mm thick	1 Sqm	585
489	MAT-01128	BMT-K.20	Medium Fibre Board: Interior Grade - 15 mm thick	1 Sqm	748
490	MAT-01129	BMT-K.21	Medium Fibre Board: Interior Grade - 18 mm thick	1 Sqm	839
491	MAT-01130	BMT-K.22	Medium Fibre Board: Interior Grade - 25 mm thick	1 Sqm	1299
492	MAT-01131	BMT-K.23	Medium Fibre Board: Interior Grade - 30 mm thick	1 Sqm	1573
493	MAT-01132	BMT-K.24	Medium Fibre Board: Interior Grade - 35 mm thick	1 Sqm	1723
494	MAT-01133	BMT-K.25	Medium Fibre Board: Exterior Grade - 6 mm thick	1 Sqm.	536.8
495	MAT-01134	BMT-K.26	Medium Fibre Board: Exterior Grade - 8 mm thick	1 Sqm.	535
496	MAT-01135	BMT-K.27	Medium Fibre Board: Exterior Grade - 12 mm thick	1 Sqm.	829
497	MAT-01136	BMT-K.28	Medium Fibre Board: Exterior Grade - 15 mm thick	1 Sqm.	1024
498	MAT-01137	BMT-K.29	Medium Fibre Board: Exterior Grade - 18 mm thick	1 Sqm.	1127
499	MAT-01138	BMT-K.30	Medium Fibre Board: Exterior Grade - 25 mm thick	1 Sqm.	1545
500	MAT-01139	BMT-K.31	Medium Fibre Board: Exterior Grade - 30 mm thick	1 Sqm.	1929
501	MAT-01140	BMT-K.32	Medium Fibre Board: Exterior Grade - 35 mm thick	1 Sqm.	2249
502	MAT-01141	BMT-K.33	MDF Board: Plain-Interior - 9 mm thick	1 Sqm	383
503	MAT-01142	BMT-K.34	MDF Board: Plain-Interior - 12 mm thick	1 Sqm	436
504	MAT-01143	BMT-K.35	MDF Board: Plain-Interior - 18 mm thick	1 Sqm	487

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
505	MAT-01144	BMT-K.36	MDF Board: Plain-Interior - 25 mm thick	1 Sqm	545
506	MAT-01145	BMT-K.37	MDF Board: Plain-Interior - 30 mm thick	1 Sqm	960
507	MAT-01146	BMT-K.38	MDF Board: Plain-Interior - 35 mm thick	1 Sqm	1152
508	MAT-01147	BMT-K.39	MDF Board: Plain-Exterior - 9 mm thick	1 Sqm	396
509	MAT-01148	BMT-K.40	MDF Board: Plain-Exterior - 12 mm thick	1 Sqm	517
510	MAT-01149	BMT-K.41	MDF Board: Plain-Exterior - 18 mm thick	1 Sqm	667
511	MAT-01150	BMT-K.42	MDF Board: Plain-Exterior - 25 mm thick	1 Sqm	913
512	MAT-01151	BMT-K.43	MDF Board: Plain-Exterior - 30 mm thick	1 Sqm	1180
513	MAT-01152	BMT-K.44	MDF Board: Plain-Exterior - 35 mm thick	1 Sqm	1383
514	MAT-01153	BMT-K.45	MDF Board: Interior-One Side Laminated -9 mm thick	1 Sqm	618
515	MAT-01154	BMT-K.46	MDF Board: Interior-One Side Laminated -12 mm thick	1 Sqm	693
516	MAT-01155	BMT-K.47	MDF Board: Interior-One Side Laminated -18 mm thick	1 Sqm	795
517	MAT-01156	BMT-K.48	MDF Board: Interior-One Side Laminated -25 mm thick	1 Sqm	895
518	MAT-01157	BMT-K.49	MDF Board: Interior-One Side Laminated -30 mm thick	1 Sqm	1235
519	MAT-01158	BMT-K.50	MDF Board: Interior-One Side Laminated -35 mm thick	1 Sqm	738
520	MAT-01159	BMT-K.51	MDF Board: Exterior-One Side Laminated -9 mm thick	1 Sqm	695
521	MAT-01160	BMT-K.52	MDF Board: Exterior-One Side Laminated -12 mm thick	1 Sqm	803
522	MAT-01161	BMT-K.53	MDF Board: Exterior-One Side Laminated -18 mm thick	1 Sqm	843
523	MAT-01162	BMT-K.54	MDF Board: Exterior-One Side Laminated -25 mm thick	1 Sqm	1035
524	MAT-01163	BMT-K.55	MDF Board: Exterior-One Side Laminated -30 mm thick	1 Sqm	1395
525	MAT-01164	BMT-K.56	MDF Board: Exterior-One Side Laminated -35 mm thick	1 Sqm	650
526	MAT-01165	BMT-K.57	MDF Board: Interior-Both Side Laminated -9 mm thick	1 Sqm	649

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
527	MAT-01166	BMT-K.58	MDF Board: Interior-Both Side Laminated -12 mm thick	1 Sqm	773
528	MAT-01167	BMT-K.59	MDF Board: Interior-Both Side Laminated -18 mm thick	1 Sqm	897
529	MAT-01168	BMT-K.60	MDF Board: Interior-Both Side Laminated -25 mm thick	1 Sqm	1106
530	MAT-01169	BMT-K.61	MDF Board: Interior-Both Side Laminated -30 mm thick	1 Sqm	1353
531	MAT-01170	BMT-K.62	MDF Board: Interior-Both Side Laminated -35 mm thick	1 Sqm	766
532	MAT-01171	BMT-K.63	MDF Board: exterior-Both Side Laminated -9 mm thick	1 Sqm	745
533	MAT-01172	BMT-K.64	MDF Board: exterior-Both Side Laminated -12 mm thick	1 Sqm	878
534	MAT-01173	BMT-K.65	MDF Board: exterior-Both Side Laminated -18 mm thick	1 Sqm	1037
535	MAT-01174	BMT-K.66	MDF Board: exterior-Both Side Laminated -25 mm thick	1 Sqm	1124
536	MAT-01175	BMT-K.67	MDF Board: exterior-Both Side Laminated -30 mm thick	1 Sqm	1378
537	MAT-01176	BMT-K.68	MDF Board: exterior-Both Side Laminated -35 mm thick	1 Sqm	1418
IV.SUB- SECTION			CEMENT BONDED PARTICLEBOARD		
538	MAT-01177	BMT-K.69	Cement bonded particle board conforming to IS 14276- 6 mm thick	1 sqm	281
539	MAT-01178	BMT-K.70	Cement bonded particle board conforming to is 14276- 8 mm thick	1 sqm	306
540	MAT-01179	BMT-K.71	Cement bonded particle board conforming to is 14276- 10 mm thick	1 sqm	446.35
541	MAT-01180	BMT-K.72	Cement bonded particle board conforming to is 14276- 12 mm thick	1 sqm	463
542	MAT-01181	BMT-K.73	Cement bonded particle board conforming to is 14276- 16 mm thick	1 sqm	473
543	MAT-05423	BMT-K.109	Cement bonded particle board conforming to is 14276- 18 mm thick	1 Sqm	735
544	MAT-01182	BMT-K.74	Cement bonded particle board conforming to is 14276- 20 mm thick	1 sqm	810
545	MAT-01183	BMT-K.75	Cement bonded particle board conforming to is 14276- 25 mm thick	1 sqm	892
546	MAT-01184	BMT-K.76	Cement bonded particle board conforming to is 14276- 30 mm thick	1 sqm	1163
547	MAT-01185	BMT-K.77	Cement bonded particle board conforming to is 14276- 40 mm thick	1 sqm	1402

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
549	MAT-01186	BMT-K.78	Pre laminated cement bonded particle board-6 mm thick	1 sqm	443
550	MAT-01187	BMT-K.79	Pre laminated cement bonded particle board-8 mm thick	1 sqm	683
551	MAT-01188	BMT-K.80	Pre laminated cement bonded particle board- 10 mm thick	1 sqm	814
552	MAT-01189	BMT-K.81	Pre laminated cement bonded particle board- 12 mm thick	1 sqm	882
553	MAT-01190	BMT-K.82	Pre laminated cement bonded particle board- 16 mm thick	1 sqm	982
554	MAT-01191	BMT-K.83	Cement Bonded Particale DESIGNER BOARD Available Designs 1. Lumber 2. Quadra 3. Murk Standard size 8'X4' 10'X4'- 6mm thick	1 sqm	332
555	MAT-01192	BMT-K.84	Cement Bonded Particale DESIGNER BOARD Available Designs 1. Lumber 2. Quadra 3. Murk Standard size 8'X4' 10'X4'- 8mm thick	1 sqm	396
556	MAT-01193	BMT-K.85	Cement Bonded Particale DESIGNER BOARD Available Designs 1. Lumber 2. Quadra 3. Murk Standard size 8'X4' 10'X4'- 10mm thick	1 sqm	395
557	MAT-01194	BMT-K.86	Cement Bonded Particale DESIGNER BOARD Available Designs 1. Lumber 2. Quadra 3. Murk Standard size 8'X4' 10'X4'- 12mm thick	1 sqm	635.95
558	MAT-01195	BMT-K.87	Cement Bonded Particale DESIGNER BOARD Available Designs 1. Lumber 2. Quadra 3. Murk Standard size 8'X4' 10'X4'- 16mm thick	1 sqm	823.77
559	MAT-01196	BMT-K.88	Cement Bonded Board conforming to IS:14862-2000 - 4mm Thick	1 Sqm	193.2
560	MAT-01197	BMT-K.89	Cement Bonded Board conforming to IS:14862-2000 - 6mm Thick	1 Sqm	260
561	MAT-01198	BMT-K.90	Cement Bonded Board conforming to IS:14862-2000 - 8mm Thick	1 Sqm	343
562	MAT-01199	BMT-K.91	Cement Bonded Board conforming to IS:14862-2000 - 10mm Thick	1 Sqm	394
563	MAT-01200	BMT-K.92	Cement Bonded Board conforming to IS:14862-2000 - 12mm Thick	1 Sqm	488
564	MAT-01201	BMT-K.93	Cement Bonded Board conforming to IS:14862-2000 - 14mm Thick	1 Sqm	518
565	MAT-01202	BMT-K.94	Cement Bonded Board conforming to IS:14862-2000 - 16mm Thick	1 Sqm	518
566	MAT-01203	BMT-K.95	Cement Bonded Board conforming to IS:14862-2000 - 18mm Thick	1 Sqm	624

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
567	MAT-01204	BMT-K.96	Cement Bonded Board conforming to IS:14862-2000 - 20mm Thick	1 Sqm	708
568	MAT-01213	BMT-K.105	ITEM DELETED		
569	MAT-05421	BMT-K.106	50 mm thick SOLID WALL PANEL Sandwich panels made of light weight FRACC non-asbestos fibre reinforced cement concrete	1 Sqm	1124
570	MAT-05422	BMT-K.107	75 mm thick SOLID WALL PANEL Sandwich panels made of light weight FRACC non-asbestos fibre reinforced cement concrete	1 Sqm	1395
		Note: Items BMT-K.97 , BMT-K.98,BMT-K.99,BMT-K.100,BMT-K.101,BMT-K.102,BMT-K.103,BMT-K.104 are removed in the section K and are brought as new items in the Section L as BMT-L.21,BMT-L.22,BMT-L.23,BMT-L.24,BMT-L.25,BMT-L.26,BMT-L.27,BMT-L.28.			
L.SECTION			PLYWOOD (Landing cost – incuding loading, cost of conveyance, unloading)		
I.SUB- SECTION			MOISTURE RESISTANT (MR) GRADE		
571	MAT-01216	BMT-L.01	3 Ply - 4 mm thick Plywood(IS:303) MR Grade	1 Sqm	350
572	MAT-01217	BMT-L.02	5 Ply - 6 mm thick Plywood(IS:303) MR Grade	1 Sqm	420
573	MAT-01218	BMT-L.03	5 Ply - 8 mm thick Plywood(IS:303) MR Grade	1 Sqm	539
574	MAT-01219	BMT-L.04	5 Ply - 9 mm thick Plywood(IS:303) MR Grade	1 Sqm	539
575	MAT-01220	BMT-L.05	9 Ply - 12 mm thick Plywood(IS:303) MR Grade	1 Sqm	657
576	MAT-01221	BMT-L.06	9 Ply - 15 mm thick Plywood(IS:303) MR Grade	1 Sqm	750
577	MAT-01222	BMT-L.07	9 Ply - 18 mm thick Plywood(IS:303) MR Grade	1 Sqm	780
II.SUB- SECTION			BOILING WATER RESISTANT (BWR)GRADE		
578	MAT-01223	BMT-L.08	3 Ply - 4 mm thick Plywood(IS:303) BWR/BWP Grade	1 Sqm	400
579	MAT-01224	BMT-L.09	5 Ply - 6 mm thick Plywood(IS:303) BWR/BWP Grade	1 Sqm	498
580	MAT-01225	BMT-L.10	5 Ply - 8 mm thick Plywood(IS:303) BWR/BWP Grade	1 Sqm	614
581	MAT-01226	BMT-L.11	5 Ply - 9 mm thick Plywood(IS:303) BWR/BWP Grade	1 Sqm	614

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
582	MAT-01227	BMT-L.12	9 Ply - 12 mm thick Plywood(IS:303) BWR/BWP Grade	1 Sqm	755
583	MAT-01228	BMT-L.13	9 Ply - 15 mm thick Plywood(IS:303) BWR/BWP Grade	1 Sqm	916
584	MAT-01229	BMT-L.14	9 Ply - 19 mm thick Plywood(IS:303) BWR/BWP Grade	1 Sqm	1008
III.SUB- SECTION			VENEERED DECORATIVE PLYWOOD		
585	MAT-01230	BMT-L.15	3 Ply-4 mm thick One side Teak Veneer Decorated Plywood (IS:1328)	1 Sqm	652
586	MAT-01231	BMT-L.16	5 Ply - 6 mm thick One side Teak Veneer Decorated Plywood (IS:1328)	1 Sqm	797
587	MAT-01232	BMT-L.17	5 Ply - 9 mm thick One side Teak Veneer Decorated Plywood (IS:1328)	1 Sqm	929
588	MAT-01233	BMT-L.18	9 Ply - 13 mm thick One side Teak Veneer Decorated Plywood (IS:1328)	1 Sqm	1353
589	MAT-01234	BMT-L.19	5 Ply - 9 mm thick Both sides Teak Veneer Decorated Plywood (IS:1328)	1 Sqm	1381
590	MAT-01235	BMT-L.20	9 Ply - 12 mm thick Both sides Teak Veneer Decorated Plywood (IS:1328)	1 Sqm	1213
IV.SUB- SECTION			LAMINATES		
591	MAT-01205	BMT-L.21	Laminate Sheets - Glossy Finish: 1 mm thick	1 Sqm	432
592	MAT-01206	BMT-L.22	Laminate Sheets - Glossy Finish: 1.50 mm thick	1 Sqm	579
593	MAT-01207	BMT-L.23	Laminate Sheets - Glossy Finish: 1.80 mm thick	1 Sqm	580
594	MAT-01208	BMT-L.24	Laminate Sheets - Mat Finish: 1 mm thick	1 Sqm	453
595	MAT-01209	BMT-L.25	Laminate Sheets - Mat Finish: 1.50 mm thick	1 Sqm	590
596	MAT-01210	BMT-L.26	Laminate Sheets - Mat Finish: 1.80 mm thick	1 Sqm	583
V.SUB- SECTION			COMMERCIAL VENEERS		
597		BMT-L.27	Teak Veneer Lamination - 4 mm thick - Pencil Grains	1 Sqm	508
598		BMT-L.28	Teak Veneer Lamination - 4 mm thick - Natural Grains	1 Sqm	905
		BMT-L.29	Providing Wood Polymer Composite (WPC) solid, frostywhite single extruded factory made 2.44 mt x 1.22 mt boards in		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
599	MAT-05424	BMT-L.29.A	6 MM thickness (Density 550 kg/Cum, Weight 9.5Kg)	sqmt	776
600	MAT-05425	BMT-L.29.B	11 MM thickness (Density 500 kg/Cum, Weight 16.5Kg)	sqmt	1275
601	MAT-05426	BMT-L.29.C	18 MM thickness (Density 650 kg/Cum, Weight 35Kg)	sqmt	2098
M.SECTION			CEILINGS, WALL PARTITIONS &WALL LININGS		
I.SUB-SECTION			FALSE CEILINGS- TILES / SHEETS		
602	MAT-01236	BMT-M.01	Gypsum Board tiles of size notless than 0.595 M x 0.595 M of 12.5 mm thick as per IS 2095 -1992	1 Sqm	311
603	MAT-01237	BMT-M.02	Gypsum Board tiles of size notless than 0.595 M x 0.595 M of 9 mm thick as per IS 2095 -1992	1 Sqm	291
604	MAT-01238	BMT-M.03	Gypsum Board Plain sheet 12.5 mm thick as per IS 2095 -1993	1 Sqm	240
605	MAT-01263	BMT-M.28	14 mm - Mineral Fiber sheet 600 x 600 of Board / Tegular Edge tiles with a Humidity Resistance of 80% RH, Average NRC 0.50, Light Reflectance >80%, Thermal Conductivity $\lambda = 0.052$ to 0.057 w/mk, Fire Performance Class 0/Class 1	1 Sqm	610
606	MAT-01264	BMT-M.29	15 mm - Mineral Fiber sheet 600 x 600 of Board / Tegular Edge tiles with a Humidity Resistance of 90% RH, Average NRC 0.50, Light Reflectance >80%, Thermal Conductivity $\lambda = 0.052$ to 0.057 w/mk, Fire Performance Class 0/Class 1	1 Sqm	742
607	MAT-01265	BMT-M.30	16 mm - Tegular Edge 600 x 600 of Board / Tegular/ Micro look Edge tiles with a Humidity Resistance of 99% RH, Average NRC 0.60, Light Reflectance >88%, Thermal Conductivity $\lambda = 0.052$ to 0.057 w/mk, Fire Performance Class 0/Class 1	1 Sqm	750
608	MAT-01266	BMT-M.31	12 mm - Mineral Fiber sheet 600 x 600 (Square / Tegular) Edge tiles	1 Sqm	505
609	MAT-01271	BMT-M.36	Supply of Thermocole sheets 12 mm thick	1 Sqm	55
610	MAT-01272	BMT-M.37	Supply of Thermocole sheets 19 mm thick	1 Sqm	291
611	MAT-01275	BMT-M.40	Calcium Silicate Boards - 6mm thick	1 Sqm	291

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
612	MAT-01276	BMT-M.41	Calcium Silicate Boards - 8mm thick	1 Sqm	381
613	MAT-01277	BMT-M.42	Calcium Silicate Boards - 10mm thick	1 Sqm	479
614	MAT-01278	BMT-M.43	Calcium Silicate Boards - 12mm thick	1 Sqm	609
615	MAT-01286	BMT-M.51	Supplying and fixing of false ceiling using Plaster of paris Boards 12 mm thick with standard GI ceiling angles, sections perimeter channels including cost and conveyance of all materials and labour charges etc complete	1 Sqm	459
616	MAT-01287	BMT-M.52	Supplying and fixing of false ceiling using Plaster of paris Boards 10 mm thick with standard GI ceiling angles, sections perimeter channels including cost and conveyance of all materials and labour charges etc complete	1 Sqm	385
617	MAT-01288	BMT-M.53	Designer ceiling Cement Boards - thickness 3.2 mm	1 Sqm	250
618	MAT-01289	BMT-M.54	High pressure steam cured Cement Boards 4 mm thick	1 Sqm.	159
619	MAT-01290	BMT-M.55	High pressure steam cured Cement Boards 6 mm thick	1 Sqm.	230
620	MAT-01291	BMT-M.56	High pressure steam cured Cement Boards 8 mm thick	1 Sqm.	298
621	MAT-01292	BMT-M.57	High pressure steam cured Cement Boards 10 mm thick	1 Sqm.	381
622	MAT-01293	BMT-M.58	High pressure steam cured Cement Boards 12 mm thick	1 Sqm.	294
623	MAT-01294	BMT-M.59	High pressure steam cured Cement Boards 14 mm thick	1 Sqm.	510
624	MAT-01295	BMT-M.60	High pressure steam cured Cement Boards 16 mm thick	1 Sqm.	535
625	MAT-01296	BMT-M.61	High pressure steam cured Cement Boards 18 mm thick	1 Sqm.	570
626	MAT-01297	BMT-M.62	High pressure steam cured Cement Boards 20 mm thick	1 Sqm.	706
627	MAT-01298	BMT-M.63	High pressure steam cured designer Cement Boards 4 mm thick	1 Sqm.	204
628	MAT-01299	BMT-M.64	High pressure steam cured designer Cement Boards 6 mm thick	1 Sqm.	319
629	MAT-01305	BMT-M.70	Supply and fixing of CEMENT BONDED PARTICLE BOARDS (IS 14276) false ceiling using 8MM CEMENT BONDED PARTICLE BOARDS with galvanized	1 Sqm	1129

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			and pre painted steel T section of size 24mm x 38mm x 0.3 mm for main T duty pre punched to accept cross T section of size 24mm x 30mm x 0.3 mm duly punched at both ends for insertion into main T. The grid size will be 610mm x 610mm. The frame work (grid) is suspended to the roof by using G.I flat of 0.60mm or 14-gauge G.I wire with necessary fixers to the roof and frame work. CEMENT BONDED PARTICLE BOARDS lay on the grid. The cost inclusive of necessary hardware, labor, one coat of primer (Both side) and two coats of smooth finish on visible side.		
630	MAT-01314	BMT-M.79	Providing and fixing false ceiling consisting of 600mmX600mm, Solid PVC insulation panels having wall thickness of 1mm thick plain PVC rigid foam sheet and EPS as defined in of desired thickness depending on insulation required shall be insert in a frame work made using anodized aluminium Tee section of sizes 1"X1" (25X25mm, 19 gauge or 1mm thick) in square pattern of grid sizes of 2'X2' (600X600mm). The aluminium framework is supported from the ceiling with the help of G.I. hook and G.I. wire/6mm.M.S. rods of required sizes to maintain proper level etc. the aluminium framework is supported on side wall with the use of aluminium 1"X1" (25X25mm) angles, complete as per direction of Engineer-in-Charge, manufacture's specification & drawing	1 sqm	1371
631	MAT-01315	BMT-M.80	Mineral Fibre Ceiling Tile of 0.595 mm x 0.595 mm of 13 mm thick Square Edge - Fissura Fine Model	1 Sqm	389
632	MAT-01316	BMT-M.81	Mineral Fibre Ceiling Tile of 0.595 mm x 0.595 mm of 13 mm thick Square Edge - Speckle Model	1 Sqm	395
633	MAT-01317	BMT-M.82	Mineral Fibre Ceiling Tile of 0.595 mm x 0.595 mm of 13 mm thick Square Edge - Textura Model	1 Sqm	425
634	MAT-01318	BMT-M.83	Mineral Fibre Ceiling Tile of 0.595 mm x 0.595 mm of 15 mm thick Standard Regular Edge	1 Sqm	499
635	MAT-01319	BMT-M.84	Mineral Fibre Ceiling Tile of 0.595 mm x 0.595 mm of 15 mm thick Fissura Fine Model	1 Sqm	573

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
636	MAT-01320	BMT-M.85	Mineral Fibre Ceiling Tile of 0.595 mm x 0.595 mm of 15 mm thick Speckle Model	1 Sqm	627
637	MAT-01321	BMT-M.86	Mineral Fibre Ceiling Tile of 0.595 mm x 0.595 mm of 15 mm thick Textura Model	1 Sqm	873
638	MAT-01322	BMT-M.87	Supply and fixing of PVC false ceiling on MS/GI made skeleton framework. The frame shall be 24 X 48mm MS tube section fixed along with the wall. The entire frame work shall be concealed with PVC section having overall dimensions of 6 X 250mm with a wall thickness of 1mm $\pm$ 0.3mm with tongue and groove system, provided with necessary arrangements for electrical connections, complete, for finished item of work.	1 Sqm.	1570
639		BMT-M.96	Absorptive false ceiling Supply and installation of 12.5mm thick micro perforated gypsum plaster board of 3mm square perforations (minimum 13% of perforated area) backed with 50mm thick 1000 GSM polyester wool Construction of Frame work: Frame work shall consists of GI perimeter channels of size 0.55mm thick (having one flange of 20mm and another flange of 30mm) fixed along with perimeter of the beam or walls with the help of nylon sleeves and screws at 600mm c/c. Then suspend GI main channels of size 45 mm (0.9mm thick with 2 flanges of 15mm each) from the soffit at 1200mm c/c by using soffit angle of size 25mm x 10mm x 0.55mm thick fixed to true ceiling by using suitable fasteners. Cross channels of size 0.55mm thickness having knurled web of 51.5mm and two flanges of 26mm each with lips of 10.5mm are then fixed to the main channel with the help of connecting clips and in a direction perpendicular to the main channel at 300mm c/c Cavity Filling: Ceiling frame work shall be back lined by using polyester wool having density of 1000 GSM and 50mm thick Boarding:	1 Sqm.	2470

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			A layer of 12.5mm thickness fiber reinforced micro perforated gypsum plaster board of size 1200 x 2400 mm having perforations of minimum of 13% is fixed on to frame work. Micro perforated gypsum boards used shall have RH 90% and fire rating A2-s1, d0 Finishing: Ensure that board is fixed in plumb level, screw fix gypsum plaster board to channel, cover screw with compound and sand the surface. Joints of gypsum plaster board to be finished by using jointing tapes and compound. Final finishing is done with two coats of acrylic emulsion paint.		
640		BMT-M.97	Reflective false ceiling Supply and installation of 12.5mm thick plain gypsum plaster board Construction of Frame work: Frame work shall consists of GI perimeter channels of size 0.55mm thick (having one flange of 20mm and another flange of 30mm) fixed along with perimeter of the beam or walls with the help of nylon sleeves and screws at 600mm c/c. Then suspend GI main channels of size 45 mm (0.9mm thick with 2 flanges of 15mm each) from the soffit at 1200mm c/c by using soffit angle of size 25mm x 10mm x 0.55mm thick fixed to true ceiling by using suitable fasteners. Cross channels of size 0.55mm thickness having knurled web of 51.5mm and two flanges of 26mm each with lips of 10.5mm are then fixed to the main channel with the help of connecting clips and in a direction perpendicular to the main channel at 300mm c/c. Boarding: A layer of 12.5mm thickness Plain gypsum plaster board of size 1200 x 2400mm having minimum density 550kg/m³ is fixed on to frame work. Finishing: Ensure board is in plumb level, screw fix gypsum plaster board to channel, cover screw with compound and sand the surface. Joints of gypsum plaster board to be finished by using jointing tapes and compound. Final finishing is done with two coats of acrylic emulsion paint.	1 Sqm	3426

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
		BMT-M.104	Providing supply and fixing of eco-friendly light weight calcium silicate false ceiling system in module size of 600x600mm with Galvanized iron powder coated 24mm T grid system. Eco friendly light weight calcium silicate tiles shall be made of non-cementitious hydrated wet molded calcium silicate slurry, reinforced with fibers and natural fillers. Free from formaldehyde and other harmful materials. Does not contain any toxic ingredients. Tiles shall be GRIHA accredited product suitable for green building applications. False ceiling tiles shall have following properties: (a). Surface: All tiles are prime coated on both sides. Standard factory finish in two coats white dispersion type, solvent free paint. (b). Dimensions: 595x595x15mm thick integral densified tegular/butt edged. Size referred to are always module sizes. (c). Thickness: 15mm thick integral densified tegular/butt edges with 26mm wide collar at all around the edge resting portion and 10mm thick at quadrant of the body size of 543x543mm. (d). Density of material: 350 kg/m³ at the quadrant 10mm thick portion and 450 kg/m³ at all around the integral densified edges. (Average density 370 kg/m³ as per ECBC code 2017). (e). Relative Humidity: 100% RH as per ASTM C 473-03. (f). Fire resistance: Non-combustible as per BS 476 part 4, Fire performance as per BS 476 Part 6 for fire propagation & class 1 as per BS 476 part 7 for surface spread of flame. (g). Thermal conductivity: 0.048 W/mK to 0.052 W/m²K as per IS 3346/1980 and as per ECBC code 2017. (h). Recycled content: shall have 46-50% recycled content. (i). Acoustic control: Sound Attenuation 30-32dB. Noise reduction coefficient (NRC) as per IS 8225:1987 for semi perforated tile: 0.5 for fully perforated tile: 0.75 (j). Light reflectance: >85%. (k). Weight: 5-5.5kg/m². False ceiling tiles shall be laid in true horizontal level suspended on inter locking metal T grid hot dipped galvanized iron sections of 0.33mm sheet of thickness galvanized @ 120 grams per sqm including all sides comprising of main T runners of size 24x38mm of length	1 Sqm	1365

			3000mm, cross T of size 24x32mm of length 1200mm and secondary intermediate cross T of size 24x32mm of length 600mm to form grid module of size 600x600mm. This grid shall be suspended from ceiling using GI slotted cleats of size 25x35x1.6mm fixed to ceiling with 12.5mm dia and 50mm long dash fasteners connected to 4mm GI adjustable rods with galvanized steel level clips of size 85x30x0.8mm spaced 1200mm Centre to Centre fixed to main T runner. Frame also consist of GI perimeter wall angle of size 24x24x0.40mm of length 3000mm to be fixed on periphery wall/partition with the help of plastic rawl plugs at 450mm Centre to Centre and 40mm long dry wall SS screws. The work shall be carried out as per specifications, drawing and as per directions of the Engineer- in-charge.		
		BMT-M.105	Providing, supply and fixing of eco-friendly light weight calcium silicate false ceiling system in module size of 600x600mm with Galvanized iron Silhouette profile black reveal powder coated 15mm T grid system. Eco friendly light weight calcium silicate tiles shall be made of non-cementitious hydrated wet molded calcium silicate slurry, reinforced with fibers and natural fillers. Free from formaldehyde and other harmful materials. Does not contain any toxic ingredients. Tiles shall be GRIHA accredited product suitable for green building applications. False ceiling tiles shall have following properties: (a). Surface: All tiles are prime coated on both sides. Standard factory finish in two coats white dispersion type, solvent free paint. (b). Dimensions: 595x595x15mm thick integral densified micro look edged. Size referred to are always module sizes. (c). Thickness: 15mm thick integral densified micro look edges with 26mm wide collar at all around the edge resting portion and 10mm thick at quadrant of the body size of 543x543mm. (d). Density of material: 350 kg/m³ at the quadrant 10mm thick portion and 450 kg/m³ at all around the integral densified edges. (Average density 370 kg/m³ as per ECBC code 2017). (e). Relative Humidity: 100% RH as per ASTM C 473-03. (f). Fire resistance: Non-combustible as per BS 476 part 4, Fire performance as per BS 476 Part 6 for fire propagation & class 1 as per BS 476 part 7 for surface spread of flame. (g). Thermal conductivity: 0.048 W/mK to 0.052 W/m²K as per IS 3346/1980 and as per ECBC code 2017.	1 Sqm	1460

			(h). Recycled content: shall have 46-50% recycled content. (i). Acoustic control: Sound Attenuation 30-32dB.Noise reduction coefficient (NRC) as per IS 8225:1987for semi perforated tile: 0.5for fully perforated tile: 0.75. (j). Light reflectance: >85%. (k). Weight: 5-5.5kg/m2. False ceiling tiles shall be laid in true horizontal level suspended on inter locking metal T grid silhouette black reveal profile of hot dipped galvanized iron powder coated sections of 0.40 mm sheet thickness galvanized @ 120 grams per sqm including all sides comprising of main T runners of size 15x42mm of length 3000mm, cross T of size 15x42mm of length 1200mm and secondary intermediate cross T of size 15x42mm of length 600mm to form grid module of size 600x600mm. This grid shall be suspended from ceiling using GI slotted cleats of size 25x35x1.6mm fixed to ceiling with 12.5mm dia and 50mm long dash fasteners connected to 4mm GI adjustable rods with galvanized steel level clips of size 85x30x0.8mm spaced 1200mm Centre to Centre fixed to main T runner. Frame also consist of GI perimeter wall angle of size 22x19x0.40 mm of length 3000mm to be fixed on periphery wall/ partition with the help of plastic rawl plugs at 450mm Centre to Centre and 40mm long dry wall SS screws. The work shall be carried out as per specifications, drawing and as per directions of the Engineer-in-charge.		
		BMT-M.106	Providing, supply and fixing of Anti-Microbial Bio-Safe coated eco-friendly light weight calcium silicate false ceiling system in module size of 600x600mm with Galvanized iron powder coated 24mm T grid system.Eco friendly light weight calcium silicate tiles shall be made of non-cementitious hydrated wet molded calcium silicate slurry, reinforced with fibers and natural fillers. Free from formaldehyde and other harmful materials. Does not contain any toxic ingredients. Tiles shall be GRIHA accredited product suitable for green building applications. Tiles shall have Anti-Microbial Bio-Safe Coating on front and back sides of tiles and found to be completely protected from Bacteria, Fungi, Yeast, and Mold when exposed to these organisms both room temperature and AC temperature. Tiles should be protected and is free from colony forming units. Anti-microbial Bio- Safe coated tiles shall have following properties: (a). Surface: All tiles are prime coated on both sides. Standard factory finish in two coats white dispersion type, solvent free paint.	1 Sqm	1636

			(b). Dimensions: 595x595x15mm thick tegular/butt edged. Size referred to are always module sizes. (c). Thickness: 15mm thick integral densified tegular/butt edges with 26mm wide collar at all around the edge resting portion and 10mm thick at quadrant of the body size of 543x543mm. (d). Density of material: 350 kg/m³ at the quadrant 10mm thick portion and 450 kg/m³ at all around the integral densified edges. (Average density 370 kg/m³ as per ECBC code 2017). (e). Relative Humidity: 100% RH as per ASTM C 473-03. (f). Fire resistance: Non-combustible as per BS 476 part 4, Fire performance as per BS 476 Part 6 for fire propagation & class 1 as per BS 476 part 7 for surface spread of flame. (g). Thermal conductivity: 0.048 W/mK to 0.052 W/m²K as per IS 3346/1980 and as per ECBC code 2017. (h). Recycled content: shall have 46-50% recycled content.(i). Sound Attenuation: 30-32dB. (j). Light reflectance: >85%.(k). Weight: 5-5.5kg/m². (1). Antibacterial activity and efficacy value: shall have morethan 2.0 as per JIS-Z2801 (m). Fungal growth: no fungal growth observed with rating as per ASTM G-21. False ceiling tiles shall be laid in true horizontal level suspended on inter locking metal T grid of hot dipped galvanized iron sections of 0.33mm sheet thickness galvanized @ 120 grams per sqm including all sides comprising of main T runners of size 24x38mm of length 3000mm, cross T of size 24x32mm of length 1200mm and secondary intermediate cross T of size 24x32mm of length 600mm to form grid module of size 600x600mm. This grid shall be suspended from ceiling using GI slotted cleats of size 25x35x1.6mm fixed to ceiling with 12.5mm dia and 50mm long dash fasteners connected to 4mm GI adjustable rods with galvanized steel level clips of size 85x30x0.8mm spaced 1200mm Centre to Centre fixed to main T runner. Frame also consist of GI perimeter wall angle of size 24x24x0.40mm of length 3000mm to be fixed on periphery wall/partition with the help of plastic rawl plugs at 450mm Centre to Centre and 40mm long dry wall SS screws. The work shall be carried out as per specifications, drawing and as per directions of the Engineer-in-charge.		

II.SUB- SECTION			FALSE CEILINGs- SECTIONS &ACCESSORIES		
641	MAT-01239	BMT-M.04	G.I. Ceiling Angle - 25 mm x 10 mm x 0.55 mm	1 RM	83
642	MAT-01240	BMT-M.05	G.I. Ceiling Section 51.5 mm x 26 mm x 10.5 mm x 0.55 mm thick	1 RM	116
643	MAT-01241	BMT-M.06	G.I. Intermediate Section 45 mm x 15 mm x 15 mm x 0.9 mm	1 RM	85
644	MAT-01242	BMT-M.07	G.I. Perimeter Channel - 20 mm x 27 mm x 30 mm (web) of 0.55 mm thick	1 RM	76
645	MAT-01243	BMT-M.08	G.I.-Precoated Fine line Grid 25 mm x 25 mm x 0.7 mm	1 RM	69
646	MAT-01244	BMT-M.09	G.I.-Precoated Fine line Grid 15 mm x 25 mm x 0.7 mm	1 RM	62
647	MAT-01245	BMT-M.10	GI - Precoated - T-Sec- 24 mm x 38 mm x 0.7 mm thick	1 RM	67
648	MAT-01246	BMT-M.11	Hot dipped GI Angle - Precoated - Grid: 19 mm x 19 mm	1 RM	40
649	MAT-01247	BMT-M.12	Polyester painted GI - T Section - 24 x 32 mm	1 RM	58
650	MAT-01248	BMT-M.13	Polyester painted GI - T Section - 24 x 25 mm	1 RM	53
651	MAT-01249	BMT-M.14	Polyester painted GI - T Section - 24 mm x 27 mm	1 RM	54
652	MAT-01250	BMT-M.15	Aluminium Angle : 24 mm x 24 mm	1 RM	36
653	MAT-01251	BMT-M.16	Anodised Aluminium T Section : 24 x 24.5 x 2.4 mm	1 RM	36
654	MAT-01252	BMT-M.17	Connecting Clips	1 Each	12
655	MAT-01253	BMT-M.18	Rawl Plug	1 Each	5
656	MAT-01254	BMT-M.19	6 mm Nylon Rawl Plug	1 Each	5
657	MAT-01255	BMT-M.20	Soffit Cleats	1 Each	6
658	MAT-01256	BMT-M.21	Drywall Screws - 25 mm	1 Each	5
659	MAT-01257	BMT-M.22	Jointing Compound	1 Kg	35

660	MAT-01258	BMT-M.23	Jointing Paper Tape	1 RM	7
661	MAT-01259	BMT-M.24	Drywall Top Coat	1 Litre	164
662	MAT-01260	BMT-M.25	Universal Holding Clips	1 Each	
663	MAT-01261	BMT-M.26	4 mm Dia GI Connecting Rod	1 RM	16
664	MAT-01262	BMT-M.27	2 mm Dia GI Connecting Rod	1 RM	11
	III.SUB-SECTION		WALL PANELLS & WALL LININGS		
665	MAT-01274	BMT-M.39	Providing wooden panelling 12 mm thick one side laminated sheet fixed on wooden frame of BT wood size 50.8 mm x 25.4 mm (2"x1") at distance of 609.6mm (2'-0") intervals of both ways providing 3/4" x 1/2" (19.05 mm x 12.7 mm) size BT wood ornamental cover beading and necessary screws, fevicol glue complete for finished item of work.	1 Sqm	1837
666	MAT-01267	BMT-M.32	Perforated wall panels channeled wood works sheets of width 128 mm,thickness of 16mm and length 2440 mmmade of a high density particle board substrate with a laminated facing as per the approved shade /Species & Finish and a melamine balancing layer on the reverse side, with a special perforation pattern fluted perforation on the visible surface with a minimum sag resistance of RH90 and a fire rating class of 1 as per Part 7 of BS 476 with a "tongue-and-grooved" edges and the back of the perforated panel is with sound absorbing non-woven acoustical fleece	1 Sqm	2918
667	MAT-01300	BMT-M.65	Supply and fixing of wall panelling(water, fire and Termite proof) with frame work made of GI stud profile of size 48 x 40x10 x 0.6 mm thick placed at every 610 mm C/C intervals fixed vertically in between floor and roof 'U' track of size 50 x 30 x 0.6 mm thick dulyfixed with self expansion screws and with 8 mm thick E-board / 6 mm thick E- board classic claddd around with self tapping self embedding screws fixed at every 300 mm (centres) leaving a 3 mm gap between two panels of width 2'-0". The Gap will be covered with a decorative beading. Surface will begiven a smooth finish over a coat of primer. - With 8 mm Designer CEMENT BONDED BOARD	1 Sqm.	1162

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
668	MAT-01301	BMT-M.66	ITEM DELETED		
669	MAT-01306	BMT-M.71	Supply and fixing CEMENT BONDED PARTICLE BOARDS (IS 14276) wall paneling using 10 MM CEMENT BONDED PARTICLE BOARDS with frame work made of GI stud section of size 48mm x 35mm x 0.55mm thick placed at every 610 mm C/C intervals vertically and at 1200mm internals horizontally fixed to the wall by means of self expansion screws and caps. CEMENT BONDED PARTICLE BOARDS is to be fixed to frame by means of self tapping screws placed at every 300 mm intervals leaving 3mm gap between two panels. The cost inclusive of one coat of primer and two coats of smooth finish and cost & conveyance of all materials, labor charges etc. complete as per the direction of Engineer in charge.	1 Sqm	1527
670	MAT-01309	BMT-M.74	Supply and fixing of CEMENT BONDED PRE-LAMINATED PARTICLE BOARDS wall paneling using 12 MM CEMENT BONDED PRE-LAMINATED PARTICLE BOARDS with frame work made of G.I stud section of size 48mm x 35mm x 0.55mm thick placed at every 610mm intervals vertically and at 1200mm internals horizontally fixed to the wall by means of self expansion screws and caps. LAM is to be fixed to frame by means of self-taping screws placed at every 300mm intervals leaving 3mm gap between two panels. The cost inclusive of Conveyance of materials, Labor charges etc., complete as per the direction of Engineer in charge	1 Sqm	2111

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
671	MAT-01312	BMT-M.77	Providing and fixing INSULATED PVC WALL PANELING shall consist of PVC insulated panels having wall thickness of 1mm /1.5mm/2mm PVC sheet and the desired thickness of EPS (dependent on the insulation required) screwed into the wall using screws of adequate length. The screws shall be placed at a distance of 150mm and shall be 25mm from the edge of the insulated panel on all from sides of the panel. The PVC strips of 5mm thick PVC sheet of width 75mm feathered at the edges shall be stuck using solvent cement adhesive at the places where two panels are joined, so as to cover the screw of both the panels, using solvent cement. 90 heat bent strips of 5mm thick PVC sheets of width 75mm X75mm feathered at the edges shall be stuck at wall joints / pillars etc. ,complete as per direction of Engineer- in-Charge, manufacture's specification & drawing	1 Sqm	2127
672	MAT-01313	BMT-M.78	Providing and fixing plain PVC rigid foam sheet wall panelling of thickness 5mm consisting of panels having size 1220mm X2440mm stuck on inner frame work of 25mm wide strips of 5mm thick PVC rigid foam sheet. The strips should have in their centre a groove of 6mm width and 2mm depth for sinking the head of the screw used to fix the strips to the wall and should be placed vertically at equal intervals of 405/407mm centre to centre. The PVC strips shall be fixed to the wall using 65mm long M.S. screws through the groove in the strip by using PVC fasteners. The distance between two screws shall not be more than 300mm. a groove of 2mm may be left at the joint of two panels for aesthetic looks. This framework is done for making existing wall surface in ensured level and for sticking the wall panelling sheet (panel) on it. The exact size of the panel and correspondingly of the grid may be varied depending on the size of the wall. However it must be ensured that a strips of 5mm thick PVC sheet of width 75mm feathered at the edges shall be stuck at the places where two panels are joined, using solvent cement. , complete as per direction of Engineer-in-Charge,	1 Sqm	2100

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			manufacture's specification & drawing		
673	MAT-01323	BMT-M.88	Supply and fixing of wall panelling on the framework of wooded rippers of 24 X 24mm of required size. The entire framework shall be panelled with PVC section having overall dimensions of 6 X 250mm with a wall thickness of 1mm $\pm$ 0.3mm. The panels are joined with tongue and groove system. Necessary cut-outs for electrical connections to be provided at required places complete, for finished item of work.	1 Sqm.	1571
			Supply and fixing of wall lining fixing to GI channels of perimeter channel 30mm x 27mm x 0.55 thick and ceiling channels of 51.1mm x 26mm x 10.5mm x 0.55mm thick and fixing and finishing using joint compound and glass fibre tape complete finish as per specification without painting for finished item of work:		
674	MAT-01282	BMT-M.47	A) using 8mm thick Calcium silicate boards	1 Sqm	889
675	MAT-01283	BMT-M.48	B) Using 10mm thick Calcium silicate boards	1 Sqm	955
676	MAT-01284	BMT-M.49	C) Using 12mm thick Calcium silicate boards	1 Sqm	1076
677	MAT-05430	BMT-M.95	Providing and fixing in position wall panelling to all heights with eco friendly light weight calcium silicate panels/tiles Globe Design of size 595mm x 595mm having square/butt edge having NRC(Noise Reduction Coefficient) of 0.5 to 0.75 as per IS 8225:1987, Light reflectance of 85%(minimum), Non Combustible as per BS:476 (part-4), fire performance as per BS:476 (part-6&7), humidity resistance of 100% and thermal conductivity < 0.043 W/m K as per ASTM 518:1991, comprising of a frame made from especially fabricated galvanised mild steel sheet 0.50 mm thick pressed section (galvanizing @120 grams per sqm including both sides) i.e.vertical studs of size 48 x 34 x 36 mm are placed at 600mm center to center in a floor and ceiling channel section of size 50 x 32mm fixed to the floor and soffit at 600mm centers using 12mm dia,50mm long wedge type expanded zinc alloy dash fastner with 10mm bolt. Glasswool of 50mm	1 Sqm	2385

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			thickness is then to be inserted in the slots and finally calcium silicate non combustible panels/tiles are to be screwfixed with self tapping pan head nickel coated mild steel screws of size 13 x 3.2mm on to this grid leaving an even groove of 1 mm between the panels. The joints between the panels are to be duly jointed and finished using recommended jointing calcium silicate based compound & fiber joint tape roll 50mm wide (90 metre)roll and two coats of primer suitable for panelling as per manufacturer's specification as per direction of Engineer-in-Charge all complete.(With 15 mm thick integral densified fully perforated light weight calcium silicate panels/tiles)		
678		BMT-M.98	Wall-Absorptive wall panelling Supply and installation of 17mm thick micro perforated wood having 2mm perforation and 8mm pitch backed with polyester wool of density 1000GSM x 50mm thick with Laminared finish Construction of Frame work: Frame work consists of 25mm thick GI wall channels with fully knurled surface of 0.55mm thick 80mm width, having two equal flanges of 26mm. A GI wall channel is fixed to the walls in horizontal direction with the help of suitable fastners at 600mm c/c then another 25mm thick GI wall channel is fixed vertically over the horizontally laid wall channel at 600mm c/c Cavity Filling: The frame work shall be back lined by using polyester wool having a density of 1000 GSM and 50mm thick Boarding: 17mm thick micro perforated wood having 2mm perforation and 8mm pitch is fixed on the frame work. Finishing: Ensure board is in plumb level and screw heads to be covered with compound and sand the surface. The screws are painted with manufacturer supplied paint matching the colour of the board/panel. The finishing of board is of veneer finish.	1 Sqm	5345

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
679		BMT-M.99	Wall-Reflective wall panelling Supply and installation of 12 mm thick B.W.P ply finished with 1 mm thick laminate on all visible sides backed with 50mm thick 1000 GSM polyester wool insulation Construction of Frame work: Frame work consists of minimum 50mm GI stud with fully knurled surface of 0.55 mm thick, 50mm width and two equal flanges of 34mm is fixed on to the GI support made of required height, First the wall plate is fixed on to the wall using suitable fastners at every 1200mm C/C in both the directions and an MS hollow box section of 40mmx40mm with 5mm thick is welded to the wall plate, this is used to give the support to the MS gride of 600mmx600mm which is placed at a distance of 480mm from the wall. Cavity Filling: The frame work shall be back lined by using polyester fiber having a density of 1000 GSM and 50mm thick held in position by using GI weld mesh Boarding: 12mm thick Laminared plywood (8mm plywood and 1mm laminate) of approved finish is then fixed to GI frame work by using suitable fasteners and ensure proper level of the panel surface. Finishing: Ensure plywood is in plumb level and finish by using laminate of approved shade and colour	1 Sqm	3512
680			Supply and installation of 17mm thick micro perforated wood having 2mm perforation and 8mm pitch backed with polyester wool of density 1000GSM x 50mm thick with Laminated finish Construction of Frame work: Frame work consists of 25mm thick GI wall channels with fully knurled surface of 0.55mm thick 80mm width, having two equal flanges of 26mm. A GI wall channel is fixed to the walls in horizontal direction with the help of suitable fasteners at 600mm c/c then an another 25mm thick GI wall channel is fixed vertically over the horizontally laid wall channel at	1 Sqm	6005

			600mm c/c. Cavity Filling: The frame work shall be back lined by using polyester wool having a density of 1000 GSM and 50mm thick. Boarding: 17mm thick micro perforated wood having 2mm perforation and 8mm pitch is fixed on the frame work. Finishing : Ensure board is in plumb level and screw heads to be covered with compound and sand the surface. The screws are painted with manufacturer supplied paint matching the color of the board/panel. The finishing of board is of veneer finish. Note : 1. Vendors to submit all test certificates (Acoustics and fire),2. Refer drawings for over all depth of the system		
			Supply and installation of 12 mm thick B.W.P ply finished with 1 mm thick laminate on all visible sides backed with 50mm thick 1000 GSM polyester wool insulation. Construction of Frame work : Frame work consists of minimum 50mm GI stud with fully knurled surface of 0.55 mm thick, 50mm width and two equal flanges of 34mm is fixed on to the GI support made of required height, First the wall plate is fixed on to the wall using suitable fasteners at every 1200mm C/C in both the directions and an MS hallow box section of 40mmX40mm with 5mm thick is welded to the wall plate, this is used to give the support to the MS gride of 600mmX600mm which is placed at a distance of 480mm from the wall. Cavity Filling : The frame work shall be back lined by using polyester fiber having a density of 1000 GSM and 50mm thick held in position by using GI weld mesh Boarding : 12mm thick Laminated plywood (8mm plywood and 1mm laminate) of approved finish is then fixed to GI frame work by using suitable fasteners and ensure proper level of the panel surface.Finishing : Ensure plywood is in plumb level and finish by using laminate of approved shade and color	1 Sqm	4202
681		BMT-M.100	Supply and fixing of 50 mm Thick wall panels (sandwich wall panels) with 5 mm thick Cement bonded particle boards Facings and light weight EPS concrete core materials	1 Sqm	1036
682		BMT-M.101	Supply and fixing of 75 mm Thick wall panels (sandwich wall panels) with 5 mm thick Cement bonded particle boards	1 Sqm	1555

			Facings and light weight EPS concrete core materials		
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
683		BMT-M.102	Supply and fixing of Pre-Laminated Cement Bonded Particle Board (Bison Lam) Conformir 15786 - 18 Mm Thick	1 Sqm	1261
684		BMT-M.103	Supply & erection of open shelves using cement bond particle board (Bison Panel) confirming to IS 14276 with 20mm thick t for sides & shelves, 8mm back liner with 15 "depth, Each shelf height 12" to 15" with all hardware screws & nails	1 Sqm	2330
		IV	PARTITIONS		
685	MAT-01273	BMT-M.38	Supply & fixing 75mm thick metal stud partition using 12.5 mm thick Gypboard conforming to IS 2095-1982 screw fixed to either side to 48 mm studs of 0.55 mm thick with the 50 mm floor and ceiling channel 0.55 mm and the joints duly finished with joint compound, papertape and two coats Dry wall top coat as per specification.	1 Sqm	1224
686	MAT-01279	BMT-M.44	Supply and Fixing 66mm thick metal stud partition screw fixed to either side of 48mm studs of 0.55mm thick with 50mm floor and ceiling channel 0.55mm and the joints duly finished with joining compound, glass fibre tape and two coats dry wall top coat as per specification finished Item of work- using 8mm thick Calcium silicate boards	1 Sqm	1405

687	MAT-01280	BMT-M.45	Supply and Fixing 66mm thick metal stud partition screw fixed to either side of 48mm studs of 0.55mm thick with 50mm floor and ceiling channel 0.55mm and the joints duly finished with joining compound, glass fibre tape and two coats dry wall top coat as per specification finished Item of work - Using 10mm thick Calcium silicate boards	1 Sqm	1527
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
688	MAT-01281	BMT-M.46	Supply and Fixing 66mm thick metal stud partition screw fixed to either side of 48mm studs of 0.55mm thick with 50mm floor and ceiling channel 0.55mm and the joints duly finished with joining compound, glass fibre tape and two coats dry wall top coat as per specification finished Item of work - Using 12mm thick Calcium silicate boards	1 Sqm	1762
689	MAT-01285	BMT-M.50	Supply and Fixing 66mm thick metal stud partition using 2 layers of 12mm thick Calcium silicate boards screw fixed to either side to 48mm studs of 0.55mm thick with 50mm floor and ceiling channel 0.55mm. The boards joints are to be staggered to avoid through passage. Ceramic wool of 50mm thick, 64kg/m3 density is to be placed in cavity of the partition. The joints duly finished with joining compound, glass fibre tape and two coats dry wall top coat as per specification with out painting for finished item of work	1 Sqm	4362

691	MAT-01302	BMT-M.67	Supply and fixing double skin CEMENT BOARD partition with Frame work made of GI stud profile of size 48 x 40 x 10 x 0.6 mm thick placed at every 610 mm C/C intervals and 915 mm horizontal intervals duly fixed with self expansion screws, the E-board of 8 mm thick cladded around with self tapping self embedding screws fixed at every 300 mm (centres) leaving 3 mm gap between two panels of width 2'-0" (610 mm). The gap will be covered with decorative moulding surface will be given a smooth finish over cement primer. The rate is inclusive of cost and conveyance of all materials and labour charges etc. complete.	1 Sqm.	1975
692	MAT-01303	BMT-M.68	Providing and fixing of 50mm thick SOLID WALL PANEL Sandwich panels made of light Weight FRACC two 4mm thick non-asbestos fibre reinforced cement sheets on either side of the lightweight concrete core composed of Portland cement binders with tongue and groove arrangement. The bottom of the panel shall be fixed to the floor channel made up of 1 mm thick GI channels of size 14x50x25 mm fixed to the existing floor with 6x60mm nylon self expansion screws at 600 mm C/C and top of the panel fixed with ceiling channel made out of 1mm thick GI Channel of size 38x50x38mm duly fixed to the existing ceiling with 6x60mm nylon self expansion screws at 600 mm C/C. All the tongue and groove joints of the panels have to be properly cleaned and both the panels have to be fixed by applying the mixture of fly ash and sodium silicate in between and Everest jointing compound all the exposed joints. The rate includes cost of 50mm SOLID WALL PANELS, G.I. Floor and ceiling channel. The panels can be flushed by using paper tape and Everest jointing compound all complete	1 sqm	1855

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
693	MAT-01304	BMT-M.69	Providing and fixing of 75mm thick SOLID WALL PANEL Sandwich panels made of light Weight FRACC two 4mm thick non-asbestos fibre reinforced cement sheets on either side of the lightweight concrete core composed of Portland cement binders with tongue and groove arrangement. The bottom of the panel shall be fixed to the floor channel made up of 1 mm thick GI channels of size 14x75x25 mm fixed to the existing floor with 6x60mm nylon self expansion screws at 600 mm C/C and top of the panel fixed with ceiling channel made out of 1mm thick GI Channel of size 38x75x38mm duly fixed to the existing ceiling with 6x60mm nylon self expansion screws at 600 mm C/C. All the tongue and groove joints of the panels have to be properly cleaned and both the panels have to be fixed by applying the mixture of fly ash and sodium silicate in between and Everest jointing compound all the exposed joints. The rate includes cost of 75mm SOLID WALL PANEL panels, G.I. Floor and ceiling channel. The panels can be flushed by using paper tape and Everest jointing compound all complete.	1 Sqm.	2304
694	MAT-01307	BMT-M.72	Supply and fixing CEMENT BONDED PARTICLE BOARDS (IS 14276) double skin partition using with 10 MM CEMENT BONDED PARTICLE BOARDS made out of G.I. track section of size 50mmx 35mm x 0.55 mm for fixing to the roof and floor and stud section of size 48mm x 35mm x 0.55mm placed in track section vertically at 610mm intervals and at 1200mm intervals horizontally fixed to the wall by means of self expansion screws and	1 Sqm	1985

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			caps to the wall and roof. CEMENT BONDED PARTICLE BOARDS is to be fixed both sides of frame work by using self tapping screws fixed at every 300mm intervals to the frame work leaving 3 mm gap between two panels. The cost inclusive with one coat of primer and two coats of smooth finish and cost and conveyance of all materials to site, labor charges etc., complete as per the direction of Engineer in charge.		
695	MAT-01308	BMT-M.73	Supply and fixing of CEMENT BONDED PRE-LAMINATED PARTICLE BOARDS double skin partition using with 10 mm CEMENT BONDED PRE-LAMINATED PARTICLE BOARDS made out of G.I track section of size 50 mm x 35mm x 0.55mm for fixing to the roof and floor and stud section of size 48mm x 35mm x 0.55mm placed in track section vertically at 610mm intervals and at 1200mm internals horizontally. The frame is fixed by means of self expansion screws and caps to the wall / roof. LAM is to be fixed both sides of the frame work by using 2mm thick electro plated CR flat section leaving 3mm gap between two panels. The cost inclusive of cost and conveyance of all materials to sites, other materials incidentals and labour charges as per the direction of Engineer in charges.	1 Sqm	3072
696	MAT-01310	BMT-M.75	Supply and fixing of CEMENT BONDED PRE-LAMINATED PARTICLE BOARDS aluminum glazed partitions using 10 MM CEMENT BONDED PRE-LAMINATED PARTICLE BOARDS and 5 mm thick plain glass to full height. Using with LAM to a height of 0.91 meter at bottom panel and remaining height with glass and aluminum sections anodized to 12 to 15 microns and of sections of size 37mm x 62mm and 1.5mm thickness with one meter centre to centre duly fixed with clip beading on both sides including fixing the frame to pillars by M.S. flats, bolts and nuts including cost and conveyance of all materials etc., complete as directed during execution.	1 Sqm	3730
697	MAT-01311	BMT-M.76	Providing and fixing 50mm thick SEMI HEIGHT SOLID PVC PARTITION consisting of 49mm sandwich PVC panel made out of 36mm high density	1 sqm	3940

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			expanded polystyrene sheet(E.P.S.- Thermocole) stuck on both side with 2mm thick plain/printed /prelam PVC rigid foam sheets reinforced with frame work made from 35mmX5mm M.S. Angle. In between two M.S. Angles 5mm thick plain/printed/prelam heat moulded PVC 'C' channel of size 50X100mm with feathered edges shall be fixed on the floor & 50X75mm with feathered edges plain/printed /prelam PVC 'C' channel. In between adjoining EPS sandwiched PVC partitions panel 5mm thickX75mm width plain/printed/prelam PVC sheet feathered at edges shall be stuck on front & back face using solvent cement etc. in places where two partitions meet to form an 'L' shape the panels are joined 5mm thick plain/printed/prelam heat moulded "Rajshri" PVC 'L' section of size 75mmX75mm with feathered edges shall be fixed on front & back side. This is done to maintain the symmetry of design. An additional 5mm thick PVC strip of 40mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive, complete as per direction of Engineer-in-Charge, manufacture's specification & drawing		
698	MAT-01324	BMT-M.89	Supply and fixing of PVC Double Skin Partition. The entire framework shall be carried out by mild steel section having overall dimensions of 24 X 48mm with a wall thickness of 1.2mm. The entire framework shall be concealed with PVC section having overall dimensions of 6 X 250mm with a wall thickness of 1mm ± 0.3mm both sides. Glass provision/Door provision can be provided along the partition wherever required. Partitions can be made full or half as per requirement complete, for finished item of work.	Sqm.	2776
			Supply and fixing of partitions made of seccolor pre-painted steel (base steel as per IS 513 of 0.58 mm thick 'D' quality, galvanized as per IS 277 with Zinc of 120 GSM). Primer coated with epoxy primer of 5-7 microns thick, finish painted with a polyester paint of 12-16 microns thick alkyd backer. Section for outer frame should be 46x52mm,		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			section for shutter should be 46x46mm, section for mullion should be 46x70mm, section for beading should be 18x25mm and section for middle and bottom rail (Lock Rail and Kick Rail) of size should be 23x130mm. The partition should be paneled with 9mm pre-laminated particle board to a height of 0.91m from the bottom, and remaining height with 5mm thick plain glass With Ethyl Propylene Diamine Monomer (EPDM) Gaskets. The sections are to be cut to length, mitre joined with corner bracket Centre mullions are to be fixed using mullion cap. Gaskets made of Ethyl Propylene Diamine Monomer (EPDM). Corner brackets made of CRCA with zinc phosphate. Mullion caps made of Glass filled nylon. The above frames should be fixed to the concrete/masonry wall by means of self expanding screws, and complete for finished item of work.		
699	MAT-01325	BMT-M.90	Fixed Partition: Outer frame section size of 46x52mm, mullion section should be of 46x70mm, fixed beading should be of 18x25mm.	1 sqm	5617
700	MAT-01326	BMT-M.91	Fixed Partition with Door: Outer frame section size of 46x52mm, mullion section should be of 46x70mm, fixed beading should be of 18x25mm, section for shutter should be of 46x46mm and section for middle & bottom should be of size 23x130mm.	1 sqm	5781
			DRY WALL PARTITION WITH 50 MM THICK V-PANEL		
701	MAT-01327	BMT-M.92	CEMENT BONDED PARTICLE PLANK- 8 mm- Available size-150 mm X2440mm and 200mm X 2440mm	1 Sqm	692
702	MAT-01328	BMT-M.93	CEMENT BONDED PARTICLE PLANK- 10 mm- Available size-150 mm X2440mm and 200mm X 2440mm	1 Sqm	712
703	MAT-01329	BMT-M.94	CEMENT BONDED PARTICLE PLANK- 12 mm- Available size-150 mm X2440mm and 200mm X 2440mm	1 Sqm	984
		Note: Items BMT-M.33, BMT-M.34, and BMT-M.35 are removed in the section M and are brought as new items in the Section D as BMT-D.18, BMT-D.19 and BMT-D.20.			

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
N.SECTION			DOORS (Landing cost – including loading, cost of conveyance, unloading)		
I.SUB- SECTION			DOOR FRAMES		
704	MAT-05431	BMT-N.80	Powder Coated Mild Steel Hallow single rebate door frames manufactured using cold roll formed process steel sheet of 1.25 mm thick bright (Cold Rolled Close Annealed (CRCA) and profile size of 105 x 60 mm conforming to IS 4351 - 2003 including pretreatment, Galvanized as per IS:277, zinc phosphating finished with Thermosetting Polyurethane paint of Aliphatic Grade providing high levels of scratch resistance and durability/Epoxy polyester powder for powder coating paint thickness 60 – 65 microns(Dry film thickness)Stainless Steel Ball Bearing Butt Hinges 3 mm thick fixed flush to the frame with Hinges, Base Ties, Holdfast Lugs, Mortar Guards, shock absorbers and provision for Tower Bolts, Aldrops, Lock & Strike plates etc. for both single and double shutter doors	1 RM	893
705	MAT-05432	BMT-N.81	Mild Steel Hallow single rebate general purpose door frames manufactured using cold roll formed process steel sheet of 1.25 mm thick bright (Cold Rolled Close Annealed (CRCA) and profile-B of size 105 x 60 mm conforming to IS 4351 - 2003 including pretreatment, phosphating with Hinges, Base Ties, Holdfast Lugs, Mortar Guards, shock absorbers and provision for Tower Bolts, Aldrops, Lock & Strike plates etc. for both single and double shutter doors	1 Rm	494
706	MAT-01330	BMT-N.01	Providing and fixing factory made polyvinyl chloride (PVC) Door Frame of the size 50 x 47mm with a wall thickness of 5mm, made out of extruded 10 mm rigid PVC foam sheet, mitre cut at two corners and joined with 2nos. of 150mm long brackets of 15x15mm M.S. square tube. The two vertical door profiles are to be reinforced with 19x19mm M.S. Square tube of 19 gauge. The door frame shall be fixed to the wall using 65/100mm long M.S. Screws through the frame by using PVC fasteners. A minimum of 4nos. of screws to be provided for each vertical member & minimum 2nos. for horizontal member etc. complete as per	1 Rm	453

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			manufacturers specification and direction of Engineer-in-Charge for finished item of work		
707	MAT-01334	BMT-N.05	SINGLE SIDE PRELAM SOLID PANEL PVC DOOR FRAME (CHOUKHAT): Providing and fixing factory made Pac single side Prelam door frame of the size 50X47 mm with a wall thickness of 5mm, made out of extruded 5mm rigid Pac single side prelam sheet, meter cut at two corners and joined with 2nos. of 150mm long brackets of 1515mm MS.Square tube. The two vertical door profiles are to be reinforced with 19X19mm MS. square tube of 19guage. The door frame shall be fixed to the wall using 65/100mm long MS. Screws through the frame by using Pac fasteners. a minimum of 4nos. of screws to be provided for each vertical member and minimum 2nos. for horizontal member etc. complete as per manufacture specification and direction of Engineer-in-charge.	1 Rm	476
708	MAT-01361	BMT-N.32	Supply and fixing of door frame made of hollow extruded PVC section having dimensions of 40 X 57mm with the wall thickness of 2mm +/- 0.2mm duly reinforced with seasoned wood plank at the hinges side. The door frame top 2 corners shall be metri-cut/ welded. PVC DOOR FRAME	1 RM	276
709	MAT-01362	BMT-N.33	Supply and fixing of door frame made of hollow extruded PVC section having dimensions of 40 X 46 mm with the wall thickness of 2mm +/- 0.2mm duly reinforced with seasoned wood plank at the hinges side. The door frame top 2 corners shall be mitre cut/welded	1 RM	255
710	MAT-01363	BMT-N.34	Supply & fixing of Door frames made of all formed sections of 1.25mm thick CRCA section, size should be 50x60mm with 32mm rebate. The corner of the frame should be welded. The frame should be painted with one coat of primer and finished painted with pure polyester paint. The frame should be provided with approved quality butt hinges of 3 Nos. complete for finished item.: Single shutter 3'-0" x 7'-0" (914.4x2133.6mm) outer frame section size of 50 x 60 mm	1RM	310

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
711	MAT-01364	BMT-N.35	Supply & fixing of Door frames made of all formed sections of 1.25mm thick CRCA section, size should be 50x60mm with 32mm rebate. The corner of the frame should be welded. The frame should be painted with one coat of primer and finished painted with pure polyester paint. The frame should be provided with approved quality butt hinges of 3 Nos. complete for finished item.: Double shutter 5'-0" x 7'-0" (1524 x 2133.6mm) outer frame section size of 50 x 60 mm	1 RM	310
712	MAT-01365	BMT-N.36	Supplying & fixing of Door frame made of roll formed section of 1.25 mm thick CRCA section, size should be 50 x 60 mm with 32 mm rebate. The corner of the frame should be welded. The frame should be painted with one coat of primer and finished painted with pure polyester paint. The frame should be provided with approved quality butt hinges of 3 Nos. Complete for finished item of work.: Single shutter 3'-0" x 7'-0" (914.4x2133.6mm) outer frame section size of 50 x 75 mm	1 RM	350
713	MAT-01366	BMT-N.37	Supplying & fixing of Door frame made of roll formed section of 1.25 mm thick CRCA section, size should be 50 x 60 mm with 32 mm rebate. The corner of the frame should be welded. The frame should be painted with one coat of primer and finished painted with pure polyester paint. The frame should be provided with approved quality butt hinges of 3 Nos. Complete for finished item of work.: Single shutter 5'-0" x 7'-0" (1524x2133.6mm) outer frame section size of 50 x 75 mm	1 RM	350
714	MAT-01367	BMT-N.38	Providing and fixing door frames fabricated from sections made of galvanized steel powder coated (base steel as per IS 513, galvanised as per IS 277 with zinc of 120 grams / square metre), the factory made section are powder coated with pure polyester powder of 50-60 microns thick with total coated thickness of 1.25 mm, size of door frame section is of 105 x 60 mm with a rebate of 38 mm to accommodate 35 mm thick door shutter, with groove to insert gasket in the frame section, frame section filled with polyurethane foam,	1 RM	956

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			cut to length, and joined by way of welding, each frame provided with: a) 2mm thick MS powder coated butt hinges of 100 mm long – 3 Nos. for single shutter, 6 Nos. for double shutter. b) CRCA electroplates stiffeners of 6 Nos. – 3 in each vertical. c) 40 mm x 200 mm x 1.2 mm hold fasts screwed to stiffeners – 6 Nos. with split end tail. d) Nylon Aldrop Receiver – 1 No. for single shutter frame. e) Tie Rod – 1 No		
715	MAT-01368	BMT-N.39	Providing and fixing of door frames factory made, internal door frames without threshold, fabricated from pre painted cold roll formed section 100 mm x 60 mm made of galvanized (base steel as per IS-513 'D' quality galvanized as per IS-277 with Zinc of 120 Gms/sqm) steel colour coated sections with total coated thickness of 1 mm primer coated with epoxy primer of 5-7 microns thick finish painted with polyester paint of 12-16 microns and back coated with alkyd backer of 5-7 microns, the frame section filled with polyurethane (PU Foam) of 40 kg/Cu.m and the sections cut to length and mitre joined by means of 1.25 mm thick CRCA electroplated corner brackets of size 75 x 75 mm and 1.25 mm thick electroplated stiffeners of size 150 mm for fixing hold fasts and hinges with MS Powder coated fittings a) 6 Nos M.S. Z Type hold fasts made of 30 mm x 3 mm MS flat of 230 mm long, 3 Nos each size expandable PVC covered screw type fasteners b) 2.5 mm x 300 mm long 'T' hinges /2.5 mm x 50 mm x 50 mm x 100 mm two way butt hinges (3 Nos for single leaf or 2 Nos for Double leaf/leaf) c) 12 mm dia MS tie rod at bottom with necessary size of nuts on either side.	1 RM	624
716	MAT-01383	BMT-N.54	Providing & fixing internal prelaminated PVC door frame of size 100 x 45 mm with a wall thickness of 5mm, made of extruded 5 mm Prelam PVC foam sheet, mitred cut at two corners and joined with two nos. of 150mm long brackets of 15 x 15 mm MS square tube, two vertical door profiles reinforced with 40 x 20 MS Tube of 19 guage throughout the frame and the door frame fixed to the wall using 65/100mm long MS screws through the	1 RM	773

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			frame by using PVC fasteners with a minimum of 3 nos of screws provided for each vertical member and two nos. for horizontal, etc complete as per drawing and direction of Engineer in Charge		
717	MAT-01401	BMT-N.72	PVC Door frame made out of PVC material conforming to IS:10151:1982. The door frame shall be made from extruded PVC Section in overall dimensions of 40mm x 48mm having wall thickness of 1.1mm +/-0.3mm with usual process variation corresponding to Sintex code number RUPS 414. The frame shall be Reinforced with special polymeric reinforcement as shown in drawing to take up necessary hardware. The corner joint shall be mitre cut and welded or joined by means of concealed cleats with necessary screws fittings. A tie rod to be provided at bottom. [Laminated Profile]	Per Rmt.	280
718		BMT-N.83	Providing and fixing factory made solid Wood Polymer Composite (WPC) single extruded Door Frame section of size with encapsulation of 8MM rigid layer on all the six surfaces. The door frame will have a rebat of 32MM.		
719	MAT-05434	BMT-N.83.A	Door Frame section of 45x75 MM . The two Vertical members are to be joined together with the horizontal member using 8x50 MM long MS Star full thread screws to be used with reverse forward speed control hand drilling machine. The ready/assembled door frame is fixed to the wall using hold fast or bolt fasteners. A minimum of 4 No.s of screws to be provided for each vertical member & minimum 2no.s for horizontal member.	1 Rm	601
720	MAT-05435	BMT-N.83.B	Door Frame section of 45x90 MM . The two Vertical members are to be joined together with the horizontal member using 8x60 MM long MS Star full thread screws to be used with reverse forward speed control hand drilling machine. The ready/assembled door frame is fixed to the wall using hold fast or bolt fasteners. A minimum of 4 No.s of screws to be provided for each vertical member & minimum 2no.s for horizontal member.	1 Rm	844

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
721	MAT-05436	BMT-N.83.C	Door Frame section of 63.5x100 MM .The two Vertical members are to be joined together with the horizontal member using 8x75 MM long MS Star full thread screws to be used with reverse forward speed control hand drilling machine. The ready/assembled door frame is fixed to the wall using hold fast or bolt fasteners. A minimum of 4 No.s of screws to be provided for each vertical member & minimum 2no.s for horizontal member.	1 Rm	1001
722	MAT-05433	BMT-N.82	Supply and fixing of factory made Bathroom door frames without threshold, fabricated from pre-painted cold roll formed section 50mm x 50 mm made of galvanized (base steel as per IS – 513 'D' quality, galvanized as per IS-277 with Zinc of 120 Gms/sqm) steel colour coated sections with total coated thickness of 1 mm, primer coated with epoxy primer of 5-7 microns thick, finish painted with polyester paint of 12-16 microns and back coated with alkyd backer of 5-7 microns and the frame section filled with polyurethane (P.U. Foam) of 40 Kg/Cum; and the sections cut to length and mitre joined by means of 1.25mm thick CRCA electroplated corner brackets of size 75 x 75 mm and 1.25mm thick electroplated stiffeners of size 150mm for fixing hold fasts and hinges together with the following MS Power coated fitting (Supply and fixing) of approved make. (a) 6 Nos M.S. Z. Type hold fasts made of 30mm x 3 mm MS flat of 230mm long, 3 Nos each side expandable PVC covered screw type fasteners. (b) 2.5 mm x 300 mm long 'T' hinges / 2.5mm x 50 mm x 100mm two way but hinges (3 Nos for single leaf or 2 Nos for Double leaf /leaf) (c) 12 mm Dia MS tie rod at bottom with necessary size of nuts on either side.	1 RM	503
II.SUB- SECTION			DOOR SHUTTERS WITHOUTFRAMES		
723	MAT-01341	BMT-N.12	Flush door shutters, solid bond wood block board type with teak ply on both faces .: 25 mmthick conforming to IS:2202	1 sqm	2260
724	MAT-01342	BMT-N.13	Flush door shutters, solid bond wood block board type with teak ply on both	1 sqm	2342

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			faces.: 30 mmthick conforming to IS:2202		
725	MAT-01343	BMT-N.14	Flush door shutters, solid bond wood block board type with teak ply on both faces.: 35 mmthick conforming to IS:2202	1 sqm	2517
726	MAT-01344	BMT-N.15	Flush door shutters, solid bond wood block board type with commercial ply on both faces.: 25 mmthick conforming to IS:2202	1 sqm	1244
727	MAT-01345	BMT-N.16	Flush door shutters, solid bond wood block board type with commercial ply on both faces.: 30 mmthick conforming to IS:2202	1 sqm	1300
728	MAT-01346	BMT-N.17	Flush door shutters, solid bond wood block board type with commercial ply on both faces.: 35 mmthick conforming to IS:2202	1 sqm	1580
729	MAT-01347	BMT-N.18	Flush door shutters, solid bond wood block board type with commercial ply on both faces.: 40 mmthick conforming to IS:2202	1 sqm	1775
730	MAT-01348	BMT-N.19	Flush door shutters, solid bond wood block board type with teak veneer on one face and commercial ply on another face (lipping): 20 mmthick conforming to IS:2202	1 sqm	1860
731	MAT-01349	BMT-N.20	Flush door shutters, solid bond wood block board type with teak veneer on one face and commercial ply on another face (lipping): 25 mmthick conforming to IS:2202	1 sqm	2000
732	MAT-01350	BMT-N.21	Flush door shutters, solid bond wood block board type with teak veneer on one face and commercial ply on another face (lipping): 30 mmthick conforming to IS:2202	1 sqm	1920
733	MAT-01351	BMT-N.22	Flush door shutters, solid bond wood block board type with teak veneer on one face and commercial ply on another face (lipping): 35 mmthick conforming to IS:2202	1 sqm	2095
734	MAT-01352	BMT-N.23	Flush door shutters, solid bond wood block board type with teak veneer on one face and commercial ply on another face (lipping): 40 mmthick conforming to IS:2202	1 sqm	2467
735	MAT-01354	BMT-N.25	Supply and fixing Cement Bonded Particle Board (IS 14276) single door	1 Sqm	2239

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			shutter using with 16MM Cement Bonded Particle Board with all-round "U" section of size 12mmx18mmx12mm made from 0.6 mm thick galvanized, color quoted cold rolled steel profiles with necessary screws fixed at every 304.8 mm intervals. The cost inclusive of MS Nickel coated Aldrops of size 255 mm long 2 Nos., 200 mm long tower bolts 1 No., 125 mm handles 2 Nos. 300 mm long "T" hinge cost and conveyance of all materials at site and applying 1 coat primer, 1 coat of luppum and 2 coats of synthetic enamel paint as per approved design for finished item of work.		
736	MAT-01355	BMT-N.26	Supply and fixing of Cement Bonded Particle Board(IS 14276) door shutters using with 16MM Cement Bonded Particle Board with all round style "U" size of 20mmx18mm x20mm made from 0.6mm thick galvanized pre-painted cold rolled steel profiles with Cement Bonded Particle Board separating two shutter with 30mmx18mmx30mm Stepped lipping with necessary screws fixed at every 1'-0" (304.8mm) intervals. Ms Nickel coated 250 mm long aldrops 2 no's, MS powder coated 250mm long tower bolt 2no's , & 2no's MS powder coated 125 mm long grip handle. Including cost and conveyance of all materials at site and applying one coat of primer, 2 coats of lappum and 2 coats of synthetic enamel paint as per approved design for finished item of work.	1 Sqm	2256
737	MAT-01408	BMT-N.79	Supply and fixing of CEMENT BONDED PARTICLE BOARD double door shutter using 16 MM CEMENT BONDED PARTICLE BOARD LAM with all round "U" section size of 20mm x 18mm x20mm made from 0.6mm thick galvanized pre-painted cold ro steel profiles with CEMENT BONDED PARTICLE BOARD LAM separating two shutter with 30mm x lled 20mm x 30mm stepped lipping with necessary screws fixed at every 1'0" (304.8mm) intervals. The cost inclusive of MS Nickel coated 250mm long aldrops 2no's, MS powder coated 125mm long grip handle, 2 no's M.S.P.C. Door stopper. Including cost and conveyance	1 Sqm	3250

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			of all materials at site labor charges etc., complete finished item of work.		
738	MAT-01359	BMT-N.30	Supply and fixing of CEMENT BONDED PRE-LAMINATED PARTICLE BOARDS door shutter made out of U sections of size 12x14x12 made from 0.6mm thick pps sections with 12MM CEMENT BONDED PRE-LAMINATED PARTICLE BOARDS with necessary screws fixed at every 1'.0" intervals. The hardware consists of 250mm long aldrops – 2 Nos. 150mm Handle- 1 No , 150 mm long ms powder coated tower bolt 1 no. nickle coated. The cost is inclusive of all incidentals, labor transportation charges.	1 Sqm	2672
739	MAT-01392	BMT-N.63	Supply and fixing of BOARD (conforming to IS 14862) door shutter with all-round style "U" lipping size 15 x 18 x 15 mm made from 0.8 mm thick powder coated cold rolled steel profiles with 16 mm thick V-BOARD with necessary screws fixed at 1'-0" interval 250 mm long aldrops 2 nos. M.S. nickel coated 250 mm long 1 no. M.S. Tower Bolts Including cost and conveyance of all materials at site and applying 1 coat of primer, 2 coats of luppum and 2 coats of synthetic enamel paint as per approved design for finished item of work.	1 Sqm	1607
740	MAT-01356	BMT-N.27	Supply and fixing of Cement Bonded Particle Board (IS 14276) LAM double door shutter using 16 MM CEMENT BONDED PRE-LAMINATED PARTICLE BOARDS with all round "U" section size of 20mm x 18mm x 20mm made from 0.6mm thick galvanized pre-painted cold rolled steel profiles with Cement Bonded Particle Board (IS 14276) LAM separating two shutter with 30mm x 20mm x 30mm stepped lipping with necessary screws fixed at every 1'0" (304.8mm) intervals. The cost inclusive of MS Nickel coated 250mm long aldrops 2no's, MS powder coated 125mm long grip handle, 2 no's M.S.P.C. Door stopper. Including cost and conveyance of all materials at site labour charges etc., complete finished item of work.	1 Sqm	2239
741	MAT-01376	BMT-N.47	Moulded panel solid core flush doors using water-resistant hardwood fibre	1 Sqm	1867

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			HDF / MDF fibre boards skins of 2.5 mm thick doors - 30 mm thick		
742	MAT-01377	BMT-N.48	Moulded panel solid core flush doors using water-resistant hardwood fibre HDF / MDF fibre boards skins of 2.5 mm thick doors - 35 mm thick	1 Sqm	2068
743	MAT-01378	BMT-N.49	Solid core membrane flush doors using rigid PVC membrane of 0.3 mm thick of different elegant shades doors - 30 mm thick	1 Sqm	1538
744	MAT-01379	BMT-N.50	Solid core membrane flush doors using rigid PVC membrane of 0.3 mm thick of different elegant shades doors - 35 mm thick	1 Sqm	1650
745	MAT-01335	BMT-N.06	Providing and fixing 35mm thick BRAND FACTORY MADE MOULDED DOOR SHUTTER consisting of solid core single leaf flush door of 30mm thickness, lipped with 15mm (5mmX3) thick X 30mm width on one stiles and top rails and 10mm (5mmX2) thick X 30mm width on the other stiles and bottom rails. The inner panel laminated with 2mm thick termite proof, water proof and fire resistant moulded Pac sheet with 2,4,6 raised panel design in different panel and / or prelam colours on one side after routing the moulded design on flush door and 2mm prelam Pac sheet on other side using rubber adhesive on flush door and solvent cement adhesive on Pac lipping etc. complete as per direction of Engineer-in-Charge, manufacture specification and drawing	1 sqm	3255
746	MAT-01360	BMT-N.31	Supply and fixing of door shutters made of rigid PVC extruded hollow section of 20mm X 200 mm with the wall thickness of 1.0mm +/- 0.1mm equally divided into 4 no's with tongue and groove locking arrangements. The shutter frame is made of 30mm X 79mm with the wall thickness of 1.5mm +/-0.15mm section mitre-cut and joined at 4 corners with 125mm X 225mm plastic brackets. The shutter shall be horizontally reinforced with 2 no's of 8mm PVC rods. Teak wood batons shall be reinforced inside the door shutter during the fabrication of the door shutter at those points wherever the hardware is fixed onto the door shutter.	Sqm.	1980

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
747	MAT-01381	BMT-N.52	Supply & Fixing SOLID STEEL DOOR door shutter made out of G I Precoated Sheet with an average wall thickness of 0.35 mm on both sides. MS Tube having dimensions of 19 x 19 mm is inserted along the hinge side of the door, core of the door shutter filled with High Density Polyurethane foam injected with the help of hydraulic injection method, four sides of the door covered with G I Precoated Sheet and the hardware locations reinforced with suitable wooden blocks as per drawing and stickers indicating location of the hardware pasted at appropriate places, etc complete	1 Sqm	1904
748	MAT-01393	BMT-N.64	Supply and fixing of BOARD (conforming to IS 14862) 12 mm thick door shutter of size 6'0" x 2'6" with half-round style "U" lipping size 15 x 14 x 15 mm made from 0.8 mm thick powder coated cold rolled steel profiles with necessary screws fixed at 1'-0" interval 250 mm long aldrops 2 nos. M.S. nickel coated 250 mm long 1 no. M.S. Tower Bolts Including cost and conveyance of all materials at site and applying 1 coat of primer, 2 coats of luppum and 2 coats of synthetic enamel paint as per approved design for finished item of work.	1 Sqm	1574
749	MAT-01397	BMT-N.68	Providing of 35mm thick Facotry made Prelaminated ABS (Acrolonitrile Butadyne Styrene) Door shutter moulded in different designs, consisting of all round Frame made out of water proof solid foam PVC bar of size 20x32mm, reinforced by 32x 32mm - 2 nos. for vertical made out of LVL (Laminated Veneer Lumber), core material of 32 mm thick high density craft paper honey comb board, sandwiched on both sides with prelaminate ABS sheet thickness of 1.5mm . PVC edge banding of size 0.45mm on the vertical sides.for each shutter and ISI make S.S round lock complete for finished item of work	1 Sqm	7350
III.SUB- SECTION			DOORS WITH SHUTTERS & FRAMES		
750	MAT-01331	BMT-N.02	Providing and fixing 30mm thick Solid panel PVC door shutter consisting of frame made out of M.S. tubes of 19	1 Sqm	2290

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			gauge thickness and size of 19mm x 19mm for stiles, & 15mm x 15mm for top & bottom rails. M.S. frame shall have a coat of steel primers of approved make and manufacture. M.S. frame shall be covered with 5mm thick heat moulded PVC 'C' channel of size 30 x 50mm forming stiles, and 5mm thick, 75mm wide PVC sheets for top rail, lock rail & bottom rail on either side, and 10mm (5mm x 2) thick, 20mm wide cross PVC sheet as gap insert for top rail & bottom rail. Panelling of 5mm thick PVC sheet to be fitted in the M.S. frame welded / sealed to the stiles & rails with 30mm wide x 5mm thick PVC sheet beading on either side, and joined together with solvent cement adhesive etc. An additional 5mm thick PVC strip of 20mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive. Complete as per direction of Engineer-in-charge, manufacturer's specification & drawing for finished item of work .		
751	MAT-01332	BMT-N.03	Providing and fixing 30mm thick BRAND FACTORY MADE BOTHSIDE PRELAM SOLID PANEL PVC DOOR SHUTTER consisting of frame made out of MS. Tubes of 19gauge thickness and size of 19mmX19mm for stiles, top and bottom rails. MS. Frame shall have a coat of steel primers of approved make and manufacture. MS. Frame covered with 5mm thick heat moulded Prelam Pac 'C' channel of size 30mm thickness, 70mm width out of which 50mm shall be flat and 20mm shall be tapered in 450 angle on either side forming stiles; and 5mm thick, 95mm wide Prelam Pac sheet out of which 75mm shall be flat and 20mm shall be tapered in 450 on the inner side to form top and bottom rail 115mm wide Prelam Pac sheet out of which 75mm shall be flat and 20mm shall be tapered on both sides to form lock rail. Top, bottom and lock rail shall be provided either side of the panel. 10mm (5mmX2) thick, 20mmwide cross Pac sheet shall be provided as gap insert for top and bottom rail. Panelling of 5mm thick both side Prelam Pac sheet to be fitted in the MS. Frame welded/ sealed to the stiles	1 sqm	3190

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			& rails with 7mm(5mm+2mm) thick X 15mm wide Pac sheet beading on inner side, and joined together with solvent cement adhesive etc. an additional 5mm thick Pac strip of 20mm width is to be stuck on the interior side of the 'C' channel using Pac solvent cement adhesive etc. complete as per direction of Engineer – in-charge, manufacture specification and drawing.		
752	MAT-01333	BMT-N.04	Providing and fixing 30mm thick BRAND FACTORY MADE SOLID SINGLE SIDE PRELAM PANEL PVC DOOR SHUTTER consisting of frame made out of MS. Tubes of 19gauge thickness and size of 19mmX19mm for stiles, and 15mmX15mm for top and bottom rails. The MS. Frame shall have a coat of steel primers of approved make and manufacture. MS. Frame covered with 5mm thick heat moulded single side Prelam Pac 'C' channel of size 30mmX50mm to form stiles. 5mm thick & 75mm wide single side prelim Pac sheets shall be for the top, bottom and lock rails. Panelling of 5mm thick one side Pac sheet to be fitted in the MS. Frame and sealed to the front (prelam side) stiles and rails (which should have a 5mm 45 bent portion as beading) and attached to the back(white/ivory) stiles and rails which should have a 10mm 90 bent portion as beading) using 2nos. 15mm wide X 5mm thick Pac sheet beading inside the 90 bent beading. All stiles, rails and beadings are to be joined to the panel using solvent cement etc. an additional 5mm thick Pac strip of 20mm width to be stuck on the interior side of the 'C' channel using Pac solvent cement adhesive and 10mm(5mmX2) thick, 20mm wide cross Pac sheet to be fitted as gap insert for top and bottom rail etc. complete as per direction of Engineer – in-Charge, manufacture specification and drawing.	1 sqm	2364
753	MAT-01336	BMT-N.07	MOULDED PVC DOOR - WOOD FREE Providing and fixing 30mm thick Brand factory made Moulded door shutter-wood free consisting of frame made out of MS. tubes 19gauge thickness and size of 25mmX25mm for stiles, top and bottom rails. MS. Frame shall have a	1 sqm	2830

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			coat of steel primers. The inner panel shall consist of 25mm thick High density EPS conforming to IS 4671-1984 bounded with 2mm thick termite proof, water proof and fire resistant moulded Pac sheet with 2,4,6 raised panel design in different plain and / or prelam colours after routing to the moulded design on one side and 2mm plain and / or prelam Pac sheet on other side of the EPS. The edge of panel to be sealed with lipping of 10mm wide PVC sheet bottom (made by sticking 2 rigid foam sheet of 5mm thickness using Pac solvent cement) and stiles sides 25mm(5mmX5) thick and 30mm width Pac sheet fitted along Ms. Tube for lock provision for lock height 5mm thick Pac sheet of size 150mmX100mm fixed with upper and lower face of inner side of EPS Panel etc. Complete as per direction of Engineer – in-Charge, manufacture specification and drawing		
754	MAT-01337	BMT-N.08	Providing and fixing 30mm thick BRAND FACTORY MADE WIRE MESH SOLID PVC DOOR SHUTTER consisting of frame made out of M.S. tubes of 19 gauge thickness and size of 19mmX19mm for stiles and 15mm for top, lock & bottom rails. MS. Frame shall have a coat of steel primers of approved make and manufacture. 19mmX19mm M.S. square tubes shall be covered with 5mm thick heat moulded PVC 'C' channel of size 30mm thickness, 90mm width out of which 75mm shall be flat and 15mm shall be flat and 15mm shall be bent in 900 on the inner side to from top and bottom rail land 130mm wide PVC sheet out of which 100mm shall be flat and 154mm shall be bent in 900 on both side to from lock rail, 10mm(5mmX2) thick, 20mm wide cross PVC sheet as gap insert for top rail & bottom rail. Panel will be of G.I.wire mesh of 24gauge to be fitted in by 'C' channel of size 35mm X10mm on the either side in the stiles. The inner side 'C' channel is fixed by 19mmX19mm MS. Tube on both sides with screws. The wire mesh in top bottom & lock rail is sealed with 15mm X 15mm tube with G.I.wire 10mm(5mmX2) thick PVC strip of 25mm width is to be stuck& nails on	1 sqm	2323

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			both side of G.I. wire mesh interior at the top, bottom & lock rail. An additional 5mm thick PVC strip of 20mm width is to be stuck on the interior side of the 'C' channel using PVC solvent cement adhesive etc. complete as per direction of Engineer-in-charge, manufacturer's specification & drawings		
755	MAT-01394	BMT-N.65	Providing and fixing frame made from 1.2 mm powder coated cold rolled steel profiles of overall section size of 60 mm x 45 mm with 21 mm rivet for shutter with necessary stiffeners hinges and screws. BOARD (IS 14862) shutter with all-round style "U" lipping of size 15 x 18 x 15 mm made from 0.8 mm thick CRCA powder coated steel profile with 16 mm thick V-board with necessary screws fixed at every 1'-0" interval 250 mm long aldrops 2 nos. M.S. nickel coated 250 mm long 1 no. M.S. Tower Bolts Including cost and conveyance. One coat of primer, 2 coats of luppum and 2 coats of synthetic enamel paint as per approved colour, labour charges etc.	1 Sqm	2196
756	MAT-01357	BMT-N.28	Providing and fixing of door frame made from cold roll formed sections made of galvanized (Base steel as per IS277 with zinc of 120 Gms/sqm) colour coated steel sections with total coated thickness of 1mm, primer coated with epoxy primer coat of 5-7 microns thick, finish paint with polyester paint of 12-16 microns. The Section for door frame is to be filled with polyurethane (P.U) form of 40kg/m ³ . Overall size of frame section should be of 50mm x 50mm. With necessary corner brackets, stiffeners, hinges, and screws. Cement Bonded particle board shutter "Single Leaf" with all round styles "U" section of size 12m x 18m x 12mm made from 0.6 mm thick galvanized, colour coated cold rolled steel profiles with 16mm thick Cement Bonded particle Board with necessary screws fixed at every 1'-0" (304.8mm) intervals. The cost inclusive of MS nickel coated Aldrop of size 250mm long 2nos. 200mm long tower bolt 1no., 125mm handles 2nos., cost and conveyance of all materials at site and applying one coat primer, one coat of luppum and two coats of synthetic enamel paint as per approved design	1 Sqm	4900

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			for finished item of work		
-		-	DOORS FRAMES (COLOUR COATED STEEL SECTIONS) & SHUTTER USING CEMENT BONDED PARTICLE BOARD AS PER IS 14276:	-	
757 TO 760		BMT-N.40 to BMT-N.43	ITEM DELETED		
761	MAT-01373	BMT-N.44	Supplying and fixing door shutter, with shutter frame and infill panel made from PVC material conforming to IS: 10151-1982, the shutter frame made out of PVC extruded sections having overall dimension of 47 mm x 33 mm with wall thickness of 1.2mm + 0.3mm with usual process variation, the shutter frame with tapered shape to provide better grip to the infill panel end to drain out the water The Infill panel is made out of PVC Sections having Overall Dimensions of 200 mm x 20 mm with wall thickness of 1mm + 0.2mm, the shutter frames mitre cut and joined at the corner, by providing Polymeric " L " type corners to take hardware & fixtures fixed with 10-20mm counter sunk fully threaded parallel shank steel screws, all the hardware locations reinforced with special polymeric bars as per drawings, stickers showing locations of different hardware pasted on the shutter, the infill panels joined by tongue and groove method.	1 Sqm	1168
762	MAT-01374	BMT-N.45	Providing & Fixing of Scientific Doors with metal door frames and door shutters made of galvanize steel (base steel as per IS 513 of 0.58 mm thick D quality, galvanized as per IS 277 with Zinc of 120 GSM)coated with Zinc Phosphate Primer to receive any paint on site or finished with Thermosetting Polyurethane paint of Aliphatic Grade providing high levels of scratch resistance and durability/Epoxy polyester powder for powder coating paint thickness 50-60 microns (Dry film thickness) outer frame section of 100 x 58 mm x 1.2 mm thick, shutter section of 0.80 mm thick galvanized steel sheet pressed (roll formed) for 46mm thick fully flush, double skin door shell seam joints at stile edges, in-fill of honeycomb kraft paper used to give the required	1 Sqm	11020

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			rigidity and effective acoustic insulation with 6" Tower bolt – 1 No., 6" D handles – 2 Nos., 10" Aldrop – 1 No., Butt Hinges – 3 Nos, Mortise Lock of approved quality – 1 No, frames fixed to the concrete/masonry wall by means of self expanding screws complete for finished item of work for Single leaf Door		
764	MAT-01375	BMT-N.46	Providing & Fixing of Scientific Doors with metal door frames and door shutters made of galvanize steel (base steel as per IS 513 of 0.58 mm thick D quality, galvanized as per IS 277 with Zinc of 120 GSM). coated with Zinc Phosphate Primer to receive any paint on site or finished with Thermosetting Polyurethane paint of Aliphatic Grade providing high levels of scratch resistance and durability/Epoxy polyester powder for powder coating paint thickness 50-60 microns (Dry film thickness) outer frame section of 100 x 58 mm x 1.2 mm thick, shutter section of 0.80 mm thick galvanized steel sheet pressed (roll formed) for 46mm thick fully flush, double skin door shell seam joints at stile edges, in-fill of honeycomb kraft paper used to give the required rigidity and effective acoustic insulation with 6" Tower bolt – 2 Nos., 6" D handles – 2 Nos., 10" Aldrop – 1 No., Butt Hinges – 6 Nos, Mortise Lock of approved quality – 1 No, frames fixed to the concrete/masonry wall by means of self expanding screws complete for finished item of work for Double leaf Door	1 Sqm	11500
765	MAT-01380	BMT-N.51	Providing & fixing 30 mm thick solid panel PVC door shutter consisting of frame made out of 19 guage M.S tube of 19 x 19 mm for stiles, top & bottom rail, with a coat of primer of approved make. M.S. Frame covered with 5 mm thick heat moulded PVC "C" channel of size of 30 x 50 mm forming stiles, 5 mm thick 75 mm wide PVC sheet for top, lock & bottom rail on either side 20 mm wide cross PVC sheet as gap insert for top & bottom rail, panelling of 10mm(+/-)(5mm+5mm)" thick PVC sheet fitted in the M.S. frame welded /sealed to the stiles, on either side joined together with solvent cement adhesive etc., additional 5 mm thick	1 Sqm	3439

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			PVC strip of 20 mm width stuck on the interior side of the C channel using solvent cement, complete as per direction of Engineer-in-charge, manufacturers specification.		
		BMT-N.98	Supply of factory made of Double Skin Pass Galvanized Powder Coated Single Rebate Doorframe and single shutter/Double shutter for General applications made of Double Skin Pass Galvanized Sheet confirming to Base Steel as per IS 513 of 'D' Quality Galvanized as per IS 277 with Zinc coating of 120 GSM , Pure polyester Powder Coated Paint of 60-65Microns(DFT)Thick. Frame: Single rebate Door Frame of size 100 mm X 78 mm with 1.00 mm thick Double Skin Pass Galvanized sheet Roll formed into Closed Box Profile with Suitable lock-seam joints and proper stitching procedures having a Design Architrave of 20 mm width and accommodate a 46 mm thick Door shutter and the sections cut to length , Miter joined with corner bracket and EPDM Gaskets using self-expanding Screws . The Door frames are filled with an infill material of Polyurethane foam (PUF) of Density 32 to 36 kg / m3. Groove in Door Frame shall be provided to hold EPDM Gasket so that the Door shutters shall rest on the EPDM Gasket when the Door shutters are closed. EPDM gasket makes the Door weather resistant. The door frame shall be provided with hinge jamb, lock jamb, head jamb and with Suitable Anchors per frame. Door frame Stiffeners for Hinge: Stiffener of Skin pass Galvanized Sheet of 3 mm thick shall be welded to the pressed angle from inner side of the Door Frame and shutter using projection welding / Fixing with Screws from Gasket groove. Stiffener plate shall be threaded to the required size of machine screw (M6 × 20 CSK) conforming to IS 1365, 2.2/1.8 mm joggling depth on a 3 mm hinge plate. Door Frame Stiffener of pressed 'C' channels and Skin pass Galvanized steel Sheet of thickness 1.60 mm and of sufficient width and length or 1.2 mm thick (Skin pass Galvanized steel Sheet) sheet of required width and	1 Sqm	10360

		height as per the iron mongery, shall be provided inside the Door frame at suitable places to fix fittings and fixtures, such as aldrop, tower bolt, sliding bolt, door stopper, door closer, etc, (Stiffeners only) Shutter : The Single Door Shutter shall be made of 0.8 mm thick Double Skin pass Galvanized Sheet formed and shall be of 46 mm thick fully flush, double skin door shell with Lock Seam joints at stile edges, top and bottom edge skins bent inwards in U shape filled with in-fill of Honeycomb Kraft Paper and coated with Pure polyester powder coating of thickness 60 – 65 microns, providing high levels of scratch resistance and durability, as per IS 4351 (2003),and IS 13871. Honey comb kraft paper : In-fill of Door shutter shall be with honey comb kraft paper of 16 mm cell size, 140 gsm, Core thickness of 44.5 mm, Humidity of 6 to 10 percent and compression strength 150/200 kpa at 23°C and 130 °C respectively. The product shall conform to EMPHA and ISO standards. The skin panels of the door and Honeycomb Kraft Paper shall be bonded with GLUE. The glue shall comply with A2/IMO standards. Door shutter Stiffeners : Stiffener of pressed 'C' channels and Skin pass Galvanized steel Sheet of thickness 1.60 mm of sufficient width and length or 1.2 mm thick (Skin pass Galvanized steel Sheet) rectangular box cross sectional stiffener between the two skins of the door shutter (to the full inner thickness of the door shutter) of required width and height as per the iron mongery, shall be provided inside the shutter at suitable places to fix fittings and fixtures, such as aldrop, tower bolt, sliding bolt, door stopper, door closer, etc., (stiffners only) The slots and holes shall be pierced into the Door Frame and shutter and necessary fixing arrangements shall be provided. Hardware and Accessories : 10" 'D'Handle – 1 Pair., Ball Bearing Butt Hinges – 3 No's, Mortise Lock / 10" Aldrop – 1 No., 6" Tower Bolt – 1 No., All Hardware and Screws Should be Stainless Steel 304 Grade.		

			The unit cost includes - loading, cost of conveyance, unloading		
		BMT-N.99	Supply of factory made of Double Skin Pass Galvanized Powder Coated Single Rebate Door frame and Single shutter/Double shutter for Scientific applications made of Double Skin Pass Galvanized Sheet confirming to Base Steel as per IS 513 of 'D' Quality Galvanized as per IS 277 with Zinc coating of 120 GSM , Pure polyester Powder Coated Paint of 60-65 Microns (DFT) Thick. Frame : Single rebate Door Frame of size 100 mm X 78 mm with 1.00 mm thick Double Skin Pass Galvanized sheet Roll formed into Closed Box Profile with Suitable lock-seam joints and proper stitching procedures having a Design Architrave of 20 mm width and accommodate a 46 mm thick Door shutter and the sections cut to length , Miter joined with corner bracket and EPDM Gaskets using self-expanding Screws . The Door frames are filled with an infill material of Polyurethane foam (PUF) of Density 32 to 36 kg / m³. Groove in Door Frame shall be provided to hold EPDM Gasket so that the Door shutters shall rest on the EPDM Gasket when the Door shutters are closed. EPDM gasket makes the Door weather resistant. The door frame shall be provided with hinge jamb, lock jamb, head jamb and with Suitable Anchors per frame. Door frame Stiffeners for Hinge: Stiffener of Skin pass Galvanized Sheet of 3 mm thick shall be welded to the pressed angle from inner side of the Door Frame and shutter using projection welding / Fixing with Screws from Gasket groove. Stiffener plate shall be threaded to the required size of machine screw (M6 × 20 CSK) conforming to IS 1365, 2.2/1.8 mm joggling depth on a 3 mm hinge plate. Door Frame Stiffener of pressed 'C' channels and Skin pass Galvanized steel Sheet of thickness 1.60 mm and of sufficient width and length or 1.2 mm thick (Skin pass Galvanized steel Sheet) sheet of required width and	1 Sqm	10370

		height as per the iron mongery, shall be provided inside the Door frame at suitable places to fix fittings and fixtures, such as aldrop, tower bolt, sliding bolt, door stopper, door closer, etc, (Stiffeners only) Shutter : The Single Door Shutter shall be made of 0.8 mm thick Double Skin pass Galvanized Sheet formed and shall be of 46 mm thick fully flush, double skin door shell with Lock Seam joints at stile edges, top and bottom edge skins bent inwards in U shape filled with in-fill of Honeycomb Kraft Paper and coated with Pure polyester powder coating of thickness 60 – 65 microns, providing high levels of scratch resistance and durability, as per IS 4351 (2003), and IS 13871. Honey comb kraft paper : In-fill of Door shutter shall be with honey comb kraft paper of 16 mm cell size, 140 gsm, Core thickness of 44.5 mm, Humidity of 6 to 10 percent and compression strength 150/200 kpa at 23°C and 130 °C respectively. The product shall conform to EMPHA and ISO standards. The skin panels of the door and Honeycomb Kraft Paper shall be bonded with GLUE. The glue shall comply with A2/IMO standards. Door shutter Stiffeners : Stiffener of pressed 'C' channels and Skin pass Galvanized steel Sheet of thickness 1.60 mm of sufficient width and length or 1.2 mm thick (Skin pass Galvanized steel Sheet) rectangular box cross sectional stiffener between the two skins of the door shutter (to the full inner thickness of the door shutter) of required width and height as per the iron mongery, shall be provided inside the shutter at suitable places to fix fittings and fixtures, such as aldrop, tower bolt, sliding bolt, door stopper, door closer, etc., (stiffners only) The slots and holes shall be pierced into the Door Frame and shutter and necessary fixing arrangements shall be provided. Hardware and Accessories : 10" 'D'Handle – 1 Pair., Ball Bearing Butt Hinges – 3 No's, Mortise Lock / 10" Aldrop – 1 No., 6" Tower Bolt – 1 No., All Hardware and Screws Should be Stainless Steel 304 Grade		

			Vision Glass : with vision glass on door shutter with Double Glazed 6mm thick clear float glass or clear toughened glass in standard sizes 200mmX300mm/ 450mmX750mm/ 450mmX450mm / 350mmX 750mm or circular size of 450mm Dia The unit cost includes - loading, cost of conveyance, unloading		
		BMT-N.100	Supply of factory made of Double Skin Pass Galvanized Powder Coated Single Rebate Door frame for general applications made of Double Skin Pass Galvanized Sheet confirming to Base Steel as per IS 513 of 'D' Quality Galvanized as per IS 277 with Zinc coating of 120 GSM , Pure polyester Powder Coated Paint of 60-65 Microns (DFT) Thick. Frame : Single rebate Door Frame of size 100 mm X 78 mm with 1.00 mm thick Double Skin Pass Galvanized sheet Roll formed into Closed Box Profile with Suitable lock-seam joints and proper stitching procedures having a Design Architrave of 20 mm width and accommodate a 46 mm thick Door shutter and the sections cut to length , Miter joined with corner bracket and EPDM Gaskets using self-expanding Screws . The Door frames are filled with an infill material of Polyurethane foam (PUF) of Density 32 to 36 kg / m3. Groove in Door Frame shall be provided to hold EPDM Gasket so that the Door shutters shall rest on the EPDM Gasket when the Door shutters are closed. EPDM gasket makes the Door weather resistant. The door frame shall be provided with hinge jamb, lock jamb, head jamb and with Suitable Anchors per frame. Door frame Stiffeners for Hinge: Stiffener of Skin pass Galvanized Sheet of 3 mm thick shall be welded to the pressed angle from inner side of the Door Frame and shutter using projection welding / Fixing with Screws from Gasket groove. Stiffener plate shall be threaded to the required size of machine screw (M6 × 20 CSK) conforming to IS 1365, 2.2/1.8 mm joggling depth on a 3 mm hinge plate. Stiffeners for fittings and fixtures: Stiffener of pressed 'C' channels and Skin pass Galvanized steel Sheet of thickness 1.60 mm	1RM	1011

			and of sufficient width and length or 1.2 mm thick (Skin pass Galvanized steel Sheet) sheet of required width and height as per the iron mongery, shall be provided inside the Door frame at suitable places to fix fittings and fixtures, such as aldrop, tower bolt, sliding bolt, door stopper, door closer, etc, (Stiffeners only). The slots and holes shall be pierced into the door Frame and necessary fixing arrangements shall be provided. Hardware and Accessories: Ball Bearing But Hinges – 3 No's, All Hardware and Screws Should be Stainless Steel 304 Grade. The unit cost includes - loading, cost of conveyance, unloading		
		BMT-N.101	Supply of Factory made of Single Rebate Stainless Steel Door frame and Single shutter/ Double Shutter for Scientific applications made of Stainless Steel Grade 304 of Hairline Finish Frame : Single rebate Door Frame of size 100 mm X 78 mm with 1 mm thick Stainless Steel Grade 304 sheet Roll formed into Closed Box Profile with Suitable lock-seam joints and proper stitching procedures having a Design Architrave of 20 mm width and accommodate a 46 mm thick Door shutter and the sections cut to length , Mitre joined with corner bracket and EPDM Gaskets using self-expanding Screws . The Door frames are filled with an infill material of Polyurethane foam (PUF) of Density 32 to 36 kg / m3. Groove in Door Frame shall be provided to hold EPDM Gasket so that the Door shutters shall rest on the EPDM Gasket when the Door shutters are closed. EPDM gasket makes the Door weather resistant. The door frame shall be provided with hinge jamb, lock jamb, head jamb and with Suitable Anchors per frame.	1 Sqm	17825

			Door frame Stiffeners for Hinge: Stiffener of Stainless Steel Grade 304 sheet of 3 mm thick shall be welded to the pressed angle from inner side of the Door Frame and shutter using projection welding / Fixing with Screws from Gasket groove. Stiffener plate shall be threaded to the required size of machine screw (M6 × 20 CSK) conforming to IS 1365, 2.2/1.8 mm joggling depth on a 3 mm hinge plate. Door Frame Stiffener of pressed 'C' channels and Stainless Steel Grade 304 sheet of thickness 1.60 mm and of sufficient width and length or 1.2 mm thick (Skin pass Galvanized steel Sheet) sheet of required width and height as per the iron mongery, shall be provided inside the Door frame at suitable places to fix fittings and fixtures, such as aldrop, tower bolt, sliding bolt, door stopper, door closer, etc, (Stiffeners only) Shutter : The Single Door Shutter shall be made of 0.8 mm thick Stainless Steel Grade 304 Sheet formed and shall be of 46 mm thick fully flush, double skin door shell with Lock Seam joints at stile edges, filled with in-fill of Honeycomb Kraft Paper. Honey comb kraft paper : In-fill of Door shutter shall be with honey comb kraft paper of 16 mm cell size, 140 gsm, Core thickness of 44.5 mm, Humidity of 6 to 10 percent and compression strength 150/200 kpa at 23°C and 130 °C respectively. The product shall conform to EMPHA and ISO standards. The skin panels of the door and Honeycomb Kraft Paper shall be bonded with GLUE. The glue shall comply with A2/IMO standards. Door shutter Stiffeners : Stiffener of pressed 'C' channels and Skin pass Stainless Steel Grade 304 Sheet of thickness 1.60 mm of sufficient width and length or 1.2 mm thick rectangular box cross sectional stiffener between the two skins of the door shutter (to the full inner thickness of the		

			door shutter) of required width and height as per the iron mongery, shall be provided inside the shutter at suitable places to fix fittings and fixtures, such as aldrop, tower bolt, sliding bolt, door stopper, door closer, etc,. (stiffners only) The slots and holes shall be pierced into the Door Frame and shutter and necessary fixing arrangements shall be provided. Hardware and Accessories : 10" 'D'Handle – 1 Pair., Ball Bearing Butt Hinges – 3 No's, Mortise Lock / 10" Aldrop – 1 No., 6" Tower Bolt – 1 No., All Hardware and Screws Should be Stainless Steel 304 Grade Vision Glass : with vision glass on door shutter with Double Glazed 6mm thick clear float glass or clear toughned glass in standard sizes 200mmX300mm/ 450mmX750mm/ 450mmX450mm / 350mmX 750mm or circular size of 450mm Dia The unit cost includes - loading, cost of conveyance, unloading		
766	MAT-01382	BMT-N.53	Supplying & fixing SINGLE PANEL 30 mm thick PVC DOOR, door shutters with shutter frame and Infill panel made from PVC material, the shutter frame made out of PVC extruded sections having overall dimensions of 60 mm x 30 mm with wall thickness of 1.3 mm $\pm$ 0.3 mm, with the Infill panel made out of multi chambered seamless hollow PVC extruded panel having overall dimensions of 610 mm x 20 mm having wall thickness 1 mm $\pm$ 0.2 mm with the shutter frame meter cut and joined at corners and all the hardware locations reinforced with special polymeric bars as per drawing including providing special PVC bracket on hinge side, etc complete	1 Sqm	2931

767	MAT-01384	BMT-N.55	Supply & Fixing of Powder Coated Mild Steel doors, frames & shutters made of Skin pass galvanized Iron sheet conforming to Base Steel as per IS 513 "D" Quality, Galvanized as per IS 277 with Hot Zinc Coating of 120 grams / Sq.Mtr with powder coating of thickness 60-65 Microns, frame with 1.2mm thick Skin pass Galvanized Iron sheet formed to single rebate profile of ize 100 mm X 58 mm and filled with in-fill Polyurethane foam, the Door Shutters are with 0.80 mm thick Skin pass Galvanized Iron Sheet formed to provide a 46 mm thick fully flush, double skin door shell with Lock Seam joints at stile edges, fitted with in-fill of Honeycomb Kraft Paper and coated with polyester powders of Pure polyester/ epoxy polyester or polyurethane powder for powder coating of thickness 60 – 65 microns and are coated with Zinc Phosphate Primer to receive any paint on site or finished with Thermosetting Polyurethane paint of Aliphatic Grade providing high levels of scratch resistance and durability, the Shutter provided with 6 MM clear float vision glass in Circular, Square or Rectangular shapes, Stainless Steel Ball Bearing Butt Hinges 3 mm thick fixed flush to the frame and shutter	1 Sqm	10100

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			(Profile 102x76x3mm thick).Mortise Sash Lock with Lever Handles, Mortise Dead Bolt, etc for industrial, commercial, residential, cleanroom applications		
768	MAT-01385	BMT-N.56	Supply & Fixing of Stainless steel doors, frames & shutters made of stainless steel grade 304 of hairline finish, frame with 1.2mm thick formed to single rebate profile of ize 100 mm X 58 mm and filled with in-fill Polyurethane foam, the Door Shutters are with 0.80 mm thick Stainless steel Sheet formed to provide a 46 mm thick fully flush, double skin door shell with Lock Seam joints at stile edges, fitted with in-fill of Honeycomb Kraft Paper, the Shutter provided with 6 MM clear float vision glass in Circular, Square or Rectangular shapes, Stainless Steel Ball Bearing Butt Hinges 3 mm thick fixed flush to the frame and shutter (Profile 102x76x3mm thick).Mortise Sash Lock with Lever Handles, Mortise Dead Bolt, etc for industrial, commercial, residential, cleanroom applications.	1 Sqm	17400
769	MAT-01386	BMT-N.57	Supply & Fixing of Powder Coated Fire Rated doors, frames & shutters made of Skin pass galvanized Iron sheet conforming to Base Steel as per IS 513 "D" Quality, Galvanized as per IS 277 with Hot Zinc Coating of 120 grams / Sq.Mtr with powder coating of thickness 60-65 Microns, frame with 1.2mm thick Skin pass Galvanized Iron sheet formed to double rebate profile of ize 143 mm X 58 mm with maximum bending radius of 1.4 mm and filled with in-fill Polyurethane foam, the Door Shutters are with 0.80 mm thick Skin pass Galvanized Iron Sheet formed to provide a 46 mm thick fully flush, double skin door shell with Lock Seam joints at stile edges, fitted with in-fill of Honeycomb Kraft Paper and coated with polyester powders of Pure polyester/ epoxy polyester or polyurethane powder for powder coating of thickness 60 – 65 microns and are coated with Zinc Phosphate Primer to receive any paint on site or finished with Thermosetting Polyurethane paint of Aliphatic Grade providing high levels of scratch resistance and durability, the Shutter provided with 6 MM clear float vision	1 Sqm	14595

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			glass in Circular, Square or Rectangular shapes, Stainless Steel Ball Bearing Butt Hinges 3 mm thick fixed flush to the frame and shutter (Profile 102x76x3mm thick).Mortise Sash Lock with Lever Handles, Mortise Dead Bolt, etc for 120 minutes Fire Rated door conforming to IS:3614 (Part2) 1992		
770	MAT-01387	BMT-N.58	Supply & Fixing of Powder Coated Fire Rated doors, frames & shutters made of Skin pass galvanized Iron sheet conforming to Base Steel as per IS 513 "D" Quality, Galvanized as per IS 277 with Hot Zinc Coating of 120 grams / Sq.Mtr with powder coating of thickness 60-65 Microns, frame with 1.2mm thick Skin pass Galvanized Iron sheet formed to double rebate profile of ize 143 mm X 58 mm with maximum bending radius of 1.4 mm and filled with in-fill Polyurethane foam, the Door Shutters are with 0.80 mm thick Skin pass Galvanized Iron Sheet formed to provide a 46 mm thick fully flush, double skin door shell with Lock Seam joints at stile edges, fitted with in-fill of Honeycomb Kraft Paper and coated with polyester powders of Pure polyester/ epoxy polyester or polyurethane powder for powder coating of thickness 60 – 65 microns and are coated with Zinc Phosphate Primer to receive any paint on site or finished with Thermosetting Polyurethane paint of Aliphatic Grade providing high levels of scratch resistance and durability, the Shutter provided with 6 MM clear float vision glass in Circular, Square or Rectangular shapes, Stainless Steel Ball Bearing Butt Hinges 3 mm thick fixed flush to the frame and shutter (Profile 102x76x3mm thick).Mortise Sash Lock with Lever Handles, Mortise Dead Bolt, etc for 60 minutes Fire Rated door conforming to IS:3614 (Part2) 1992	1 Sqm	13806
771	MAT-01388	BMT-N.59	Supply & Fixing of Stainless steel Fire Rated doors, frames & shutters made of Stainless steel of 304 grade hairline finish, frame with 1.2mm thick Stainless steel of 304 grade hairline finish sheet formed to double rebate profile of ize 143 mm X 58 mm with maximum bending radius of 1.4 mm and filled with in-fill Polyurethane foam, the Door	1 Sqm	22500

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			Shutters are with 0.80 mm thick Stainless steel of 304 grade hairline finish Sheet formed to provide a 46 mm thick fully flush, double skin door shell with Lock Seam joints at stile edges, fitted with in-fill of Honeycomb Kraft Paper and coated with polyester powders of Pure polyester/ epoxy polyester or polyurethane powder for powder coating of thickness 60 – 65 microns and are coated with Zinc Phosphate Primer to receive any paint on site or finished with Thermosetting Polyurethane paint of Aliphatic Grade providing high levels of scratch resistance and durability, the Shutter provided with 6 MM clear float vision glass in Circular, Square or Rectangular shapes, Stainless Steel Ball Bearing Butt Hinges 3 mm thick fixed flush to the frame and shutter (Profile 102x76x3mm thick).Mortise Sash Lock with Lever Handles, Mortise Dead Bolt, etc for 120 minutes Fire Rated door conforming to IS:3614 (Part2) 1992		
772	MAT-01389	BMT-N.60	Supply & Fixing of Stainless steel Fire Rated doors, frames & shutters made of Stainless steel of 304 grade hairline finish, frame with 1.2mm thick Stainless steel of 304 grade hairline finish sheet formed to double rebate profile of ize 143 mm X 58 mm with maximum bending radius of 1.4 mm and filled with in-fill Polyurethane foam, the Door Shutters are with 0.80 mm thick Stainless steel of 304 grade hairline finish Sheet formed to provide a 46 mm thick fully flush, double skin door shell with Lock Seam joints at stile edges, fitted with in-fill of Honeycomb Kraft Paper and coated with polyester powders of Pure polyester/ epoxy polyester or polyurethane powder for powder coating of thickness 60 – 65 microns and are coated with Zinc Phosphate Primer to receive any paint on site or finished with Thermosetting Polyurethane paint of Aliphatic Grade providing high levels of scratch resistance and durability, the Shutter provided with 6 MM clear float vision glass in Circular, Square or Rectangular shapes, Stainless Steel Ball Bearing Butt Hinges 3 mm thick fixed flush to the	1 Sqm	20150

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			frame and shutter (Profile 102x76x3mm thick).Mortise Sash Lock with Lever Handles, Mortise Dead Bolt, etc for 60 minutes Fire Rated door conforming to IS:3614 (Part2) 1992		
773	MAT-01390	BMT-N.61	Supply & Fixing of Lead Lined Clean room doors frames and shutters made of Skin pass galvanized Iron sheet (Conform to Base Steel as per IS 513 "D" Quality, Galvanized as per IS 277 with Hot Zinc Coating of 120 grams / Sq.Mtr).with powder coating of thickness 60-65 Microns, frame of 1.60mm thick galvanized steel sheet (Conform to IS 277) formed to Single/double rebate profile of size 100mm X 58mm/ 143x58mm, door frames with a single / multi Layer of Lead sheet varying thickness from 3mm /1mm to 2mm depends on radiation level, the shutter with 1.2 mm thick Galvanized Steel Sheet (Conform to IS 277) formed to provide a 46mm thick fully flush, double skin door shell with Lock Seam joints at stile edges with a single / multi Layer of Lead sheet varying thickness from 3mm /1mm to 2mm depends on radiation level, the lead sheets extend the full width and height of the door, Lead thickness is equal to the shielding in the adjacent wall, the door frames and door shutters are coated with polyester powders of Pure polyester/ epoxy polyester or polyurethane powder for powder coating of thickness 60 – 65 microns, coated with Zinc Phosphate Primer to receive any paint on site or finished with Thermosetting Polyurethane paint of Aliphatic Grade providing high levels of scratch resistance and durability, hardware with Stainless Steel Ball Bearing Butt Hinges 3 mm thick fixed flush to the frame and shutter etc complete for finished item	¹ Sqm	17088
774	MAT-01391	BMT-N.62	Supply & Fixing of Lead Lined Stainless steel Clean room door frames and shutters made of Stainless steel grade of 304 hairline finish, frame with 1.60mm (16SWG) thick hairline finish Stainless steel grade of 304 formed to Single/double rebate profile of size 100 mm x 58mm/ 143 x 58 mm, door frames with a single / multi	¹ Sqm	26150

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			Layer of Lead sheet varying thickness from 3mm /1mm to 2mm depends on radiation level, the shutter with 1.2 mm thick hairline finish Stainless steel grade of 304 formed to provide a 46mm thick fully flush, double skin door shell with Lock Seam joints at stile edges with a single / multi Layer of Lead sheet varying thickness from 3mm /1mm to 2mm depends on radiation level. The lead sheets extend the full width and height of the door. Lead thickness is to be equal to the shielding in the adjacent wall. Hardware can be provided with Stainless Steel Ball Bearing Butt Hinges 3 mm thick fixed flush to the frame and shutter etc complete for finished item of work		
775	MAT-01395	BMT-N.66	ITEM DELETED		
776	MAT-01396	BMT-N.67	A) Specification for Foamed PVC Door Frame & ABS Shutters: Providing of Factory made prelaminated FPVC (Foamed Polyvinyl Chloride) Door frame of the size 105x40mm with a wall thickness of 10mm made out of extruded rigid FPVC profile mitre joined with 6 Nos. of 50mm long screw. The door frame shall be fixed to the wall by using 80mm long screws through the frame with the help of PVC fasteners of 3 no's to be provided for each vertical member, GI stiffeners of ("U" channel of size 29x9x1mm, 150mm long) -3 no's at hinge point, Frame reinforcement of ("U" GI channel of size 46x22x.06mm), Bottom tie rod of ("U" GI channel size of 15x15x1mm) etc. complete as per manufacturers specification for finished item of work. Maximum door frame size : 980 x 2070 . B) Providing of 35mm thick Factory made Prelaminated ABS (Acrylonitrile Butadiene Styrene) Door shutter moulded in different designs, consisting of all round Frame made out of water proof solid foam PVC bar of size 20x32mm, reinforced by 32x 32mm - 2 nos. for vertical made out of LVL (Laminated Veneer Lumber), core material of 32 mm thick high density craft paper honey comb board, sandwiched on both sides with prelaminated ABS sheet thickness of 1.5mm . PVC edge banding of size	Each	16013

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			0.45mm on the vertical sides. Hardware made out of steel coated butterfly hinges - 3 Nos. for each shutter and ISI make S.S round lock completes for finished item of work. Maximum shutter size of : 910 x 2030 mm		
777	MAT-01398	BMT-N.69	Supply and fixing of Bath room / Toilet door shutter with 16mm laminated (IS 14276) door shutter with all-round 'U' lipping of PPS section of size 12mm X 18mmX 12mmX0.6mm thickness with a hardware of 12mm dia X200mm long aluminum aldop – 2 nos(ISI make)2 No of 125mm long handles(ISI make) and also 3 no Of IS304 grade Patee Hinges 3mmX12mmX180mm long with pole receiver of 10mm dia pole X40mm long welded on 2mm X40mm(ss304) plates works as receiver for RT patte hinges. The price inclusive of all material at site	1 Sqm	2877
778	MAT-01399	BMT-N.70	Supply and fixing of toilet door shutter with frame made of M.S. door frame of 5mmX48mmX48mm (L angel) as all-round frame the frame is coated with one coat of red oxide and two coats of enamel of approved color. For shutter and the shutter is made with 16mm laminatedshutter with all-round 'U' Lipping of PPS section of 12mmX18mmX12mmX0.60mm, along hardware of 200m long and 12mm dia aluminum aldop(ISI make)2 Nos, 2Nos of 125m m handle, 3 Nos of RT patte hinges IS 304gr SS 2mmX12mmX180mm long with a pole receiver of 10mmDia X 40mm by welded on 3mmX40mm SS 304, plate it works as receiver for RT Patee hinges it is welded to M.S. angle . M.S. angle will be fixed to wall of self expandable screws and caps.	1 Sqm	4460
779	MAT-01402	BMT-N.73	Door shutter with shutter frame and Infill panel made from PVC material conforming to IS: 10151:1982. The shutter frame is made out of PVC extruded sections having overall dimensions of 100mm X 30mm, with two self extruded grooves at 40mm & 50mm on front surface. The Infill panel is made out of multi chambered seamless hollow PVC extruded panel having overall dimensions of 610 mm X 20 mm. The shutter frame shall be meter cut and	Sqm.	1168

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			joined at corners by means of plastic brackets. Stickers showing locations of different hardware will be pasted on the shutter. ALL Dimensions are in MM.		
780	MAT-01403	BMT-N.74	The shutter frame made out of PVC extrude section having overall dimensions of 59mm x 24mm with wall thickness of 1.0mm +/-0.3mm with usual process variation corresponding to the Sintex Code No.DWUF-302. The shutter frame is given tapered shape to provide better grip to the infill panel and to drain out the water. The infill panel is made out of seamless one piece multi chambered PVC extruded section having overall dimension of 610mm x 20mm with wall thickness of 1mm +/-0.2mm with usual process variation corresponding to the Sintex code No.SPUF-128. The shutter frame shall be mitre cut and joined at the corner polymeric "L" Type corners shall be provided at the corners to take up hardware & fixtures and shall be fixed with 19 x 8mm counter sunk-fully threaded parallel shank steel screws. All the hardware locations shall be reinforced with special polymeric Bars.	1 Sqm	2250
781to 784		BMT-N.75 to BMT-N.78	ITEMs DELETED		
785	MAT-01338	BMT-N.09	Providing and fixing PVC door cladding to the flush doors shutters. For the new doors it shall be pasted with Fevicol SSR 998 or nailed to the old doors. complete as per direction of Engineer – in – charge, manufacturers specification and drawing - 1 mm thick	1 sqm	389
786	MAT-01339	BMT-N.10	Providing and fixing PVC door cladding to the flush doors shutters . For the new doors it shall be pasted with Fevicol SSR 998 or nailed to the old doors. complete as per direction of Engineer – in – charge, manufacturers specification and drawing - 1.5 mm thick	1 sqm	449
787	MAT-01340	BMT-N.11	Providing and fixing PVC door cladding to the flush doors shutters . For the new doors it shall be pasted with Fevicol SSR 998 or nailed to the old doors. complete as per direction of Engineer – in – charge, manufacturers specification and drawing - 2.0 mm thick	1 sqm	519
788		BMT-N.84	Providing and fixing factory made uPVC		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			any colour casement/Casementcum fixed glazed door comprising of uPVC multi-chambered frame, sash and mullion (where ever required) extruded profiles duly reinforced with 1.60 ± 0.2 mm thick galvanized mild steel section made from roll forming process of required length (shape & size according to Upvc profile), uPVC extruded glazing beads of appropriate dimension, EPDM gasket/ TPV, zinc alloy (white powder coated) 3D hinges and one handle on each side of panels along with zinc plated mild steel multi point locking having transmission gear, cylinder with keeps and one side key, G.I. fasteners 100 x 8 mm size for fixing frame to finished wall and necessary stainless steel screws, etc. Profile of frame & sash shall be mitred cut and fusion welded at all corners, mullion (if required) shall be also fusion welded including drilling of holes for fixing hardware's and drainage of water etc. After fixing frame the gap between frame and adjacent finished wall shall be filled with weather proof silicon sealant over backer rod of required size and of approved quality, all complete as per approved drawing & direction of Engineer-in-Charge inclusive of cost of Single / double glass panes and silicon sealant . Note: For uPVC frame, sash and mullion extruded profiles minus 5% tolerance in dimension i.e. in depth & width of profile shall be acceptable. Variation in profile dimension in higher side shall be accepted but no extra payment on this account shall be made.		
789	MAT-05437	BMT-N.84.A	Casement door with 3D hinges made of (big series) frame 67x 64 mm & sash 67 x 110 mm both having wall thickness of 2.3 ± 0.2 mm and single glazing bead / double glazing bead of appropriate dimension. (Area of door upto 2.00 sqm).	1 sqm	9062
790	MAT-05438	BMT-N.84.B	Casement door with top hung ventilator with 3D and S.S. friction hinges (400 x 19 x 1.9 mm) made of (big series) frame	1 sqm	9356

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			67 x 64 mm, sash 67 x 110 mm & mullion 67 x 80 mm all having wall thickness of 2.3 ± 0.2 mm and single glazing bead / double glazing bead of appropriate dimension.(Area of door upto 2.50 sqm)		
791		BMT-N.85	Providing and fixing factory made uPVC any colour sliding glazed door comprising of uPVC multi-chambered frame with in-built roller track and sash extruded profiles duly reinforced with 1.60 ± 0.2 mm thick galvanized mild steel section made from roll forming process of required length (shape & size according to uPVC profile), appropriate dimension uPVC extruded glazing beads, uPVC extruded interlock and uPVC extruded inline sash adaptor (if required), EPDM gasket/TPV, wool pile, zinc alloy (white powder coated) handle with key on one side of extreme panels along with zinc plated mild steel multi point locking having transmission gear with keeps, zinc alloy (white powder coated) crescent lock (if required), stainless steel (SS 304 grade) body with adjustable double nylon rollers (weight bearing capacity to be 120 kg), G.I fasteners 100 x 8 mm size for fixing frame to finished wall and necessary stainless steel screws etc. Profile of frame & sash shall be mitred cut and fusion welded at all corners, including drilling of holes for fixing hardware's and drainage of water etc. After fixing frame the gap between frame and adjacent finished wall shall be filled with weather proof silicon sealant over backer rod of required size and of approved quality, all complete as per approved drawing & direction of Engineer-in-Charge inclusive of cost of Single / double glass panes, wire mesh and silicon sealant . Note: For uPVC frame and sash extruded profiles minus 5% tolerance in dimension i.e. in depth & width of profile shall be acceptable. Variation in profile dimension in higher side shall be accepted but no extra payment on this account shall be made.		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
792	MAT-05439	BMT-N.85.A	Two track two panels sliding door made of (big series) frame 67 x 50 mm & sash 46 x 82 mm both having wall thickness of 2.3 ± 0.2 mm and single glazing bead / double glazing bead of appropriate dimension. (Area of door above 2.00 sqm upto 5.00 sqm)	1 sqm	6652
793	MAT-05440	BMT-N.85.B	Three track three panels sliding door with fly proof S.S wire mesh (Two nos. glazed & one no. wire mesh panels) made of (big series) frame 116 x 45 mm & sash 46 x 82 mm both having wall thickness of 2.3 ± 0.2 mm and single glazing bead / double glazing bead of appropriate dimension. (Area of door above 2.00 sqm upto 5.00 sqm)	1 sqm	8220
794	MAT-05441	BMT-N.86	Providing and fixing of factory made of High Density High Moisture Resistant Wood Fibre (HDHMR) single shutter Duradoor made up of FRAME: Door frame manufactured with High Density High Moisture Resistant Wood Fibre (HDHMR) of 36mm width x 100mm depth, laminated with 0.2mm thick PVC Foil using hot press and PUR adhesive, fitted with Gasket for energy efficiency and noise protection, affixed to the wall using high strength expandable PU Foam/ self-expandable wall fixing screws. Max dimensions in MM of 280 (depth) x 2440 (height) SHUTTER: Factory made 41mm thick shutter sandwiched with High Density High Moisture Resistant Wood Fibre (HDHMR) of 5.5mm thick skin on both sides and HDHMR of 30mm thickness as skeleton, core of high density Honey Comb and Laminated Veneer Lumber (LVL) for holding the lock body and hardware, laminated with 0.2mm thick PVC Foil and edge-banded with 1mm thick PVC edge-band using hot press and PUR adhesives. Max dimensions in MM of 1200 (width) x 41 (thickness) x 2400 (height), ARCHITRAVE: Factory made Architrave of size 80mm x 12mm fitted to pre-made grooves within the frame for added aesthetics. Four design variants available, made with Density High Moisture Resistant Wood	1 sqm	11939

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			Fibre(HDHMR) of different thicknesses depending on the design variant, laminated with 0.2mm thickPVC Foil using hot press and PUR adhesive, fitted to the wall using strong quick actingadhesives. HARDWARE & ACCESSORIES: Imported hardware including door handles – 1 no, cylindrical magnetic lock -1 no ,SS hinges – 3 nos. Including cost and conveyance of all material, Hardware, Labour charges and transportation complete for finished item of work		
795	MAT-05442	BMT-N.87	Supply and fixing of Bath/Toilet Door frame and shutter with 8mm laminated (IS.15786)using with 50mmx35mmx1.3mmthick aluminum door frame of weight 220grm per Rft with a rebate of 30 mm for provision for shutter , shutter made with 45mmx25mmx1.3mm thick aluminum section of weight 210grms per Rft with 8mm groove to accommodate 8mm thick laminated (IS.15786) and shutter having 3nos of ss 304gr Butt hinges of 100mm long, 100mm aluminum handles -2nos, and also 2 nos of 200mmx12mm aluminum aldrops ,the rates inclusive of all labor fixing at site and 50microns Ivory powder coated for aluminum door frame and shutter sections etc complete finished item of work .	1 sqm	5787
796	MAT-05443	BMT-N.92	Providing and fixing 28 -30 MM thick solid Wood Polymer Composite(WPC) single extruded door shutter with 3MM top and bottom rigid layer with an overall density of 750kg/Cum. It will be fixed to the frame using 3 inch /4 inch hinges. A minimum of 4 hinges will be required for fixing the door with the frame	1 sqm	3688
		BMT-N.93	DELETED		
		BMT-N.94	DELETED		
		BMT-N.95	DELETED		
		BMT-N.96	DELETED		

801		BMT-N.97	DELETED		
	IV.SUB-SECTION		CUP-BOARD DOORS		
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
802	MAT-01353	BMT-N.24	Supply and fixing of Cement Bonded Particle Board (IS 14276) cup board frames and shutters and using 16mm Cement Bonded Particle Board duly painted both sides with one coat of primer and two coats of synthetic / enamel paint of approved shade and brand including fixing of hardware like M.S. powder coated Piano hinges of size 18mm x 18mm, brass ball catches, Aluminum tower bolts and handles , Godrej locks, Fevicol, screws and nails including cost and conveyance of all materials, labor charges, all incidental and operational charges etc., complete for finished item of work at site as per the directions of Engineer in Charge.	1 sqm	2651
803	MAT-01358	BMT-N.29	Supply and fixing of Cement Bonded Particle Board (IS 14276) box type cup board using Cement Bonded Particle Board for making frame of size 100mm x 35mm using two sandwiched 16MM boards, one Cement Bonded Particle Board and one CEMENT BONDED PRE-LAMINATED PARTICLE BOARDS with plain 35mm wood lipping. The Shutters are made of 16MM thick CEMENT BONDED PRE-LAMINATED PARTICLE BOARDS (Pre-Laminated Cement Bonded Particle Board) of approved shade inclusive of hardware like M.S. powder coated Piano hinges of size ¾" x ¾" , Aluminum powder coated handles of size 4" (101.6mm), Aluminum tower bolt 4" (101.6mm) Godrej locks, screws, wood lipping and Fevicol etc., complete finish item of work.	1 Sqm	4273

804	MAT-01400	BMT-N.71	Supply and fixing of cupboard shutter using teakwood scantling of size 50mm X50mm teakwood as outer frame and 50mm X 30 mm of size teakwood for shutter frames , 8mm thick Bison Lam as panel to each shutter consist of 2 Nos 75mm long tower bolt – 2 nos 75 mm big handle the and other shutter will have 1 no of cupboard lack , 1 No of 75 mm long handle and 75mm10mmX1mm thick SS hinges- 2 Nos for each shutter. The above frame will be fixed to the wall with screws, the rate inclusive of screws, handle, etc., complete at site of work.	1 Sqm	4500
805		BMT-N.89	Supply and fixing of SINGLE PANEL 30mm thick door shutters(NANDI or equivalent) made of rigid PVC extruded hollow section of 20mm X 635mm with the wall thickness of 1.0mm+/- 0.1mm. The shutter frame is made of 30mmX79mm with the wall thickness of 1.5mm +/- 0.15mm section mitre-cut and joined at 4 corners with 125mmX225mm plastic brackets. Teak wood batons shall be reinforced inside the door shutter during the fabrication of the door shutter at those points wherever the hardware is fixed on to the door shutter	1 Sqm	2920
806		BMT-N.90	Supply and fixing of door frame (NANDI or EQUIVALENT) made of hollow extruded PVC section having dimensions of 40 X 57mm with the wall thickness of 2mm +1- 0.2mm duly reinforced with seasoned wood plank at the hinges side. The door frame top 2corners shall be metri-cut/ welded. PVC DOOR FRAME	1 Sqm	257
807		BMT-N.91	Supplying & fixing SINGLE PANEL 30mm thick PVC DOOR frame (NANDI or EQUIVALENT), door shutters with shutter frame and Infill panel made from PVC material, the shutter frame made out of PVC extruded sections having overall dimensions of 105 mm x 30 mm with wall thickness of 1.3mm ± 0.3 mm, with the Infill panel made out of multi chambered seamless hollow PVC extruded panel having overall dimensions of 610 mm x 20 mm having wall thickness 1 mm ± 0.2 mm with the shutter frame meter cut and joined at corners and all the hardware locations reinforced with special polymeric bars/wooden Battens as per drawing including providing special PVC bracket/Wooden Battens on hinge side etc complete	1 Sqm	3039

	P.SECTION		WINDOWS (Landing cost – including loading, cost of conveyance, unloading)		
		I.SUB-SECTION	OPENABLE WINDOWS		
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
808			Supply and fixing of pre-painted steel openable windows base steel as per IS 513 of -0.58 mm thick 'D' quality, galvanized as per IS 277 , finish painted with a polyester paint of 12-16 microns thick and back coated with 5-7 microns thick alkyd backer, section for outer frame of 46 x 52 mm section and for shutter of 46 x 46 mm section for mullion 46 x 70 mm, and section for beading should be 18 x 25 mm with 5 mm thick plain float glass fitted with Ethyl propylene Diamine monomer Gasket (EPDM) and handle made of high grade aluminium powder coated with frames fixed to the concrete /masonry wall by means of self expanding screws including 10 mm square guard bars with 6" pitch complete for finished item of work .		
809	MAT-01409	BMT-P.01	Windows: Single shutter 2'0 x 4'0 (609.6 x 1219.2 mm) Outer frame section size of 46 x 52 mm shutter frame section size of 46 x 46 mm	1 sqm	6492
810	MAT-01410	BMT-P.02	Windows: Double shutter 3'-0" x 4'-0" (914.4mm x 1219.2 mm) outer frame section size of 46 x 52 mm shutter frame section size of 46 x 46 mm	1 Sqm	6492
811	MAT-01411	BMT-P.03	Windows: Double shutter 3'-0" x 4'-0" (914.4mm x 1219.2 mm) outer frame section size of 46 x 52 mm shutter frame section size of 46 x 46 mm Mullion section size of 46 x 70 mm	1 Sqm	6908
812	MAT-01412	BMT-P.04	Windows: Double shutter 4'-0" x 4 '-0" (1219.2x12.19.2mm) outer frame section size of 46 x 52 mm shutter frame section size of 46 x 46 mm	1 Sqm	6687
813	MAT-01413	BMT-P.05	Windows: Double shutter 4'-0" x 4 '-0" (1219.2x1219.2mm) outer frame section size of 46 x 52 mm shutter frame section size of 46 x 46 mm Mullion section size of 46 x 70 mm	1 Sqm	6671
814	MAT-01414	BMT-P.06	Windows: Double shutter 4'-6" x 4 '-6" (1371.6x1371.6mm) outer frame section size of 46 x 52 mm shutter frame section size of 46 x 46 mm Mullion section size of 46 x 70 mm	1 Sqm	6166

815	MAT-01415	BMT-P.07	Windows: Centre fixed both side openable shutter 5'-0" x 4'-0" (1524x1219.2mm) outer frame section size of 46 x 52 mm shutter frame section size of 46 x 46 mm Mullion section size of 46 x 70 mm fixed beading section size of 18 x 25 mm	1 Sqm	6166
816	MAT-01416	BMT-P.08	Windows: Centre fixed both side openable shutter 6'-0" x 4'-0" (1828.8x1219.2mm) outer frame section size of 46 x 52 mm shutter frame section size of 46 x 46 mm Mullion section size of 46 x 70 mm fixed beading section size of 18 x 25 mm	1 Sqm	6351
S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
817	MAT-01417	BMT-P.09	Windows: Centre fixed both side openable shutter 6'-0" x 4'-6" (1828.8x1371.6mm) outer frame section size of 46 x 52 mm shutter frame section size of 46 x 46 mm Mullion section size of 46 x 70 mm fixed beading section size of 18 x 25 mm	1 Sqm	6620
			Providing and fixing of Openable Windows made of pre-painted steel (Base steel as per IS 513 of 0.58 mm thick galvanized as per IS 277 with Zinc of 120 GSM), primer coated with epoxy primer of 5-7 microns thick, finish painted with a polyester paint of 12-16 microns thick and back coated with 5-7 microns thick alkyd backer and section for outer frame of 48 x 50 mm, centre mullion of 48 x 50 mm, section for shutter of 48 x 25 mm and the fixed glass beading section should be 12 x 12 mm and the outer frame and mullions to have rebate for glazed shutter with a 20 mm provision for guard bars/grills and the sections cut to length metre joined with corner bracket, centre mullion fixed with mullion cap, handle, stay, 2 nos. of stainless steel heavy duty pivot hinges provided per shutter and windows fitted with 5 mm thick plain float glass with rubber gaskets including fixing the frames in concrete/masonry wall by means of self expanding screws, Including 10mm Square guard bars with 6" (152.4mm) pitch etc., complete for finished item of work.		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
818	MAT-01424	BMT-P.16	Single shutter Window 2'0"x4'0" (609.6mm x 1219.2mm). Outer frame section size of 48x50mm shutter frame section size of 48 x 25 mm.	1 Sqm	5938
819	MAT-01425	BMT-P.17	Double shutter Window with vertical mullion 3'0" x 4'0" (914.4mm x 1219.2mm) outer frame section size of 48x50mm shutter frame section size of 48 x 25 mm. Mullion section size of 48x50mm.	1 Sqm	6251
820	MAT-01426	BMT-P.18	Double shutter Window with vertical member 4'0" x 4'0" (1219.2mm x 1219.2mm) outer frame section size of 48x50mm shutter frame section size of 48 x 25 mm and mullion section should be of 48x50mm.	1 Sqm	6356
821	MAT-01427	BMT-P.19	Centre fixed both side openable shutter window 5'0"x4'0" (1524mm x 1219.2mm). Outer frame section size of 48x50mm. Shutter frame section size of 48 x 25 mm. Mullion section size of 48x50mm. Fixed beading section size of 12x12mm.	1 Sqm	5669
822	MAT-01428	BMT-P.20	Centre fixed both side openable shutter window 6'0"x4'0" (1828.8mm x 1219.2mm). Outer frame section size of 48x50mm. Shutter frame section size of 48 x 25 mm. Mullion section size of 48x50mm. Fixed beading section size of 12 x 12mm.	1 Sqm	4655

			Providing & Fixing of Openable Windows with Fly-mesh made of pre-painted steel (Base Steel as per IS 513 of 0.58 mm thick galvanized as per IS 277 with zinc of 150 GSM) primer coated with epoxy primer of 5-7 microns thick, finish painted with a polyester paint of 12-16 microns thick and back coated with 5-7 microns thick alkyd backer and the section for outer frame of 72 x 55mm, centre mullion of 72 x 50mm, section for fixed glass beading section of 12 x 12 mm and section for shutters of 48 x 25 mm and outer frame & mullion sections with rebate for glazed shutters, fly mesh and a 20 mm provision for guard bars/grills and fly mesh shutter section of 20 x 40 mm and the sections cut to length metre joined with corner bracket, centre mullions fixed with mullion cap, stay, handles, latch 2 Nos of heavy duty stainless steel pivot hinges per shutter and panelled with 5mm thick plain float glass and S.S. Mesh for fly mesh shutter (304 grade), fitted using rubber gaskets including fixing the windows in the concrete/masonry wall by means of self expanding screws, including 10mm Square guard bars with 6" (152.4mm) pitch , complete for finished item of work		
823	MAT-01429	BMT-P.21	Single shutter Window 2'0"x4'0" (609.6mm x 1219.2mm). Outer frame section size of 72x50mm shutter frame section size of 48 x 25 mm.	1 Sqm	5297
824	MAT-01430	BMT-P.22	Double shutter Window with vertical mullion 3'0" x 4'0" (914.4mm x 1219.2mm) outer frame section size of 72x50mm shutter frame section size of 48 x 25 mm. Mullion section size of 72x50mm.	1 Sqm	7907
825	MAT-01431	BMT-P.23	Double shutter Window with vertical member 4'0" x 4'0" (1219.2mm x 1219.2mm) outer frame section size of 72x50mm shutter frame section size of 48 x 25 mm and mullion section should be of 72x50mm.	1 Sqm	7191
826	MAT-01432	BMT-P.24	Centre fixed both side openable shutter window 5'0"x4'0" (1524mm x1219.2mm). Outer frame section size of 72x50mm. Shutter frame section size of 48 x 25 mm. Mullion section size of 72x50mm. Fixed beading section size of 12 x 12 mm.	1 Sqm	6486

827	MAT-01433	BMT-P.25	Centre fixed both side openable shutter window 6'0"x4'0" (1828.8mm x1219.2mm). Outer frame section size of 72x50mm. Shutter frame section size of 48 x 25 mm. Mullion section size of 72x50mm. Fixed beading section size of 12 x 12 mm.	1 Sqm	6681
828	MAT-01438	BMT-P.30	ITEM DELETED		
829	MAT-01439	BMT-P.31	ITEM DELETED		
830	MAT-01440	BMT-P.32	Galvanized powder coated Casement Windows with openable shutters duly manufactured using pressed steel sections in mild steel conforming to IS 513 of having 1.0 mm thick and galvanized as per IS 277 of 120 GSM surface treatment with pure polyester powder coating of 30-40 microns thick and section for outer frame of 60x50mm, centre for mullion of 62x50mm, section for shutter of 52 x 22 mm, outer frame and mullions to have one side rebate for glazed shutter of size 24 mm and 10x10 mm square guard bars provided at 125 mm c/c the sections assembled with bolt & nut assembly with zinc-electroplated M-5 bolts, GI Handle of size 80 mm x 15 mm -1 No per shutter, 2 nos of stainless steel heavy duty pivot hinges of size 3" of SS 304 Grade per shutter, window panes with 5 mm thick plain float glass and fixed with glass beading section of 10x12 mm size with 0.8 mm thick powder coated aluminium 'U' channel and window frames fixing to the concrete/masonry wall arrangement with self expanding screws, complete for finished item of work - 1220 x 1372 or below size	1 Sqm	6071

831	MAT-01441	BMT-P.33	Galvanized powder coated Casement Windows with openable shutters duly manufactured using pressed steel sections in mild steel conforming to IS 513 of having 1.0 mm thick and galvanized as per IS 277 of 120 GSM surface treatment with pure polyester powder coating of 30-40 microns thick and section for outer frame of 60x50mm, centre for mullion of 62x50mm, section for shutter of 52 x 22 mm, outer frame and mullions to have one side rebate for glazed shutter of size 24 mm and 10x10 mm square guard bars provided at 125 mm c/c the sections assembled with bolt & nut assembly with zinc-electroplated M-5 bolts, GI Handle of size 80 mm x 15 mm -1 No per shutter, 2 nos of stainless steel heavy duty pivot hinges of size 3" of SS 304 Grade per shutter, window panes with 5 mm thick plain float glass and fixed with glass beading section of 10x12 mm size with 0.8 mm thick powder coated aluminium 'U' channel and window frames fixing to the concrete/masonry wall arrangement with self expanding screws, complete for finished item of work - 1530 x 1372 or above size	1 Sqm	5172
832	MAT-01442	BMT-P.34	Galvanized powder coated Casement Windows with openable shutters duly manufactured using pressed steel sections in mild steel conforming to IS 513 of having 1.0 mm thick and galvanized as per IS 277 of 120 GSM surface treatment with pure polyester powder coating of 30-40 microns thick and section for outer frame of 88x50mm, centre for mullion of 62x88 mm, section for glass and fly-proof mesh shutter of 52 x 22 mm, outer frame and mullions to have two sides rebate for glazed shutter of size 24 mm and 10x10 mm square guard bars provided at 125 mm c/c the sections assembled with bolt & nut assembly with zinc-electroplated M-5 bolts, GI Handle	1 Sqm	7309

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			of size 80 mm x 15 mm -1 No per shutter, 2 Nos of stainless steel heavy duty pivot hinges of size 3" of SS 304 Grade per shutter, window panes with 5 mm thick plain float glass and fixed with glass beading section of 10x12 mm size with 0.8 mm thick powder coated aluminium 'U' channel and fly-proof mesh of SS 304 grade fixed with 18 mm x 12 mm BT wood beading and window frames fixing arrangement to the concrete/masonry wall with self expanding screws, complete for finished item of work - 1220 x 1372 or below size		
833	MAT-01443	BMT-P.35	Galvanized powder coated Casement Windows with openable shutters duly manufactured using pressed steel sections in mild steel conforming to IS 513 of having 1.0 mm thick and galvanized as per IS 277 of 120 GSM surface treatment with pure polyester powder coating of 30-40 microns thick and section for outer frame of 88x50mm, centre for mullion of 62x88 mm, section for glass and fly-proof mesh shutter of 52 x 22 mm, outer frame and mullions to have two sides rebate for glazed shutter of size 24 mm and 10x10 mm square guard bars provided at 125 mm c/c the sections assembled with bolt & nut assembly with zinc-electroplated M-5 bolts, GI Handle of size 80 mm x 15 mm -1 No per shutter, 2 Nos of stainless steel heavy duty pivot hinges of size 3" of SS 304 Grade per shutter, window panes with 5 mm thick plain float glass and fixed with glass beading section of 10x12 mm size with 0.8 mm thick powder coated aluminium 'U' channel and fly-proof mesh of SS 304 grade fixed with 18 mm x 12 mm BT wood beading and window frames fixing arrangement to the concrete/masonry wall with self expanding screws, complete for finished item of work - 1530 x 1372 or above size	1 Sqm	6930
834	MAT-01444	BMT-P.36	Providing & Fixing of Mesh windows made of pre-painted steel (Base Steel as per IS 513 of 0.58mm thick galvanized as per IS 277 with zinc of 120 GSM), primer coated with epoxy primer of 5-7 microns thick, finish painted with a polyester paint of 12-16 microns thick and back coated with 5-7	1 Sqm	4835

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			microns thick alkyd backer, section for outer frame of 47 x 36 mm, centre mullion of 60 x 36 mm, section mesh beading 18 x 6 mm and Fly mesh shutter section of 20 x 40 mm, the sections cut to length meter joined with corner bracket and centre mullions fixed with mullion cap, handles, latch, 2 Nos of heavy duty stainless steel pivot hinges per S.S. Mesh for fly mesh shutter (304 grade) including fixing the frames in the concrete/masonry wall by means of self expanding screws complete for finished item of work.		
			Providing and fixing of Openable / Casement Windows made of pre-painted steel (Base steel as per IS 513 of 0.80 mm thick galvanized as per IS 277 with Zinc of 120 GSM), finish painted with a polyester paint of 60-65 microns thick and section for outer frame of 80 x 45 mm, centre mullion of 80 x 60 mm, section for shutter of 52 x 25 mm x 0.6 mm thick, outer frame and mullions to have rebate for glazed shutter with a provision for guard bars/grills and the sections cut to length metre joined with corner bracket, centre mullion fixed with mullion cap, 1 No. of High grade nylon latch handle, window stopper, 2 nos. of with MS Powder coated /SS ball bearing butt Hinges provided per shutter and windows fitted with 4 mm thick plain float glass with rubber gaskets including fixing the frames in concrete/masonry wall by means of self expanding screws, Including 10 mm Square guard bars with 6" (152.4mm) pitch etc., complete for finished item of work.		
835	MAT-01454	BMT-P.46	Single openable shutter window size of 2' 0" x 4' 0" (609.6 x 1219.2mm) outer frame section size of 80 x 45mm, shutter frame section size of 52 x 25mm thick	1 sqm	5456
836	MAT-01455	BMT-P.47	Double openable shutter window Size of 3' 0" x 4' 0" (914.4mm x 1219.2mm) outer frame section size of 80 x 45mm, shutter frame section size of 52 x 25mm, vertical mullion section size of 80 x 60 mm	1 sqm	5838
837	MAT-01456	BMT-P.48	Double openable shutter window size of 4'0" x 4'0" (1219.2mm x 1219.2mm)	1 sqm	5838

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			outer frame section size 80 x 45mm, shutter frame section size of 52 x 25 mm ,Vertical mullion section size of 80 x 60 mm		
838	MAT-01457	BMT-P.49	Double Openable Shutter and Center Fixed window of size 5'0 x 4'0 (1524 x 1219.2mm)outer frame section size of 80mm x 45mm, shutter frame section size of 52 x 25mm ,Vertical mullion section size of 80 x 60 mm, beading section size of 9 x 12mm to be provided for glass holding	1 sqm	5127
839	MAT-01458	BMT-P.50	Double Openable Shutter and Center Fixed window of size 6'0 x 4'0 (1829.6 x 1219.2mm)outer frame section size of 80mm x 45mm , shutter frame section size of 52 x 25mm ,Vertical mullion section size of 80 x 60 mm, beading section size of 9 x 12mm to be provided for glass holding	1 sqm	5127
			Note: The above rates are for normal finish, 10% extra may be allowed for Wood Grain finish		
			Providing and fixing of Openable / Casement Windows with fly mesh made of pre-painted steel (Base steel as per IS 513 of 0.80 mm thick galvanized as per IS 277 with Zinc of 120 GSM), finish painted with a polyester paint of 60-65 microns thick and section for outer frame of 100 x 45 mm, centre mullion of 100 x 60 mm, section for shutter of 52 x 25 mm x 0.6 mm thick, section for fly-shutter of 52 x 25 mm x 0.6 mm thick and fitted with stainless steel 32 gauge fly mesh of 304 grade with 144 holes per sq.inch and mullions to have double rebate for glazed shutter and fly-shutter with a provision for guard bars/grills and the sections cut to length metre joined with corner bracket, centre mullion fixed with mullion cap, 1 No. of High grade nylon latch handle, window stopper, 2 nos. of with MS Powder coated /SS ball bearing butt Hinges provided per shutter and windows fitted with 4 mm thick plain float glass with rubber gaskets including fixing the frames in concrete/masonry wall by means of self expanding screws, Including 10 mm Square guard bars with 6" (152.4mm) pitch etc., complete for finished item of work.		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
840	MAT-01459	BMT-P.51	Single openable shutter window size of 2' 0" x 4' 0" (609.6 x 1219.2mm) outer frame Double rebate section size of 100 x 45mm, Glazed and flymesh shutter profile section size of 52 x 25mm	1 sqm	5127
841	MAT-01460	BMT-P.52	Double openable shutter window Size of 3' 0" x 4' 0" (914.4mm x 1219.2mm) outer frame Double rebate section size of 100 x 45mm, Glazed and flymesh shutter profile section size of 52 x 25mm, vertical mullion section size of 100 x 60 mm	1 sqm	5486
842	MAT-01461	BMT-P.53	Double openable shutter window size of 4'0" x 4'0" (1219.2mm x 1219.2mm) outer frame Double rebate section size of 100 x 45mm, Glazed and flymesh shutter profile section size of 52 x 25mm, vertical mullion section size of 100 x 60 mm	1 sqm	7233
843	MAT-01462	BMT-P.54	Double Openable Shutter and Center Fixed window of size 5'0 x 4'0 (1524 x 1219.2mm)outer frame section size of 80mm x 45mm , shutter frame section size of 52 x 25mm ,Vertical mullion section size of 100 x 60 mm , beading section size of 9 x 12mm to be provided for glass holding	1 sqm	7627
844	MAT-01463	BMT-P.55	Double Openable Shutter and Center Fixed window of size 6'0 x4'0 (1829.6 x 1219.2mm)outer frame section size of 80mm x 45mm , shutter frame section size of 52 x 25mm ,Vertical mullion section size of 100 x 60 mm , beading section size of 9 x 12mm to be provided for glass holding	1 sqm	7192
			Note: The above rates are for normal finish, 10% extra may be allowed for Wood Grain finish		
845	MAT-01481	BMT-P.73	ITEM DELETED		
			Supplying and fixing of WINDOWS with Pre laminated Cement Bonded Particle boards and Pre-Painted Steel Sections (PPS)fabricated from pre-painted Cold rolled formed sections made of galvanized steel color coated sections (Base steel as per IS-512 D quality, galvanized as per IS-277 with Zinc of 120 gram/sqm) with total coated thickness of 0.58mm primer coated with epoxy primer of 5-7 microns thick, finish painted with polyester paint of		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			12-16 microns and back coated with alkyd backer of 5-7 microns), sections for outer frame and centre mullion (duly filled with PU foam of 40 kg/Cum) of 60mm x 50mm, with provision for fixing glazed shutter and the section for glazed/paneled of size 48 mm x 25 mm and another section of size 60 mm x 23 mm provided for separating glazed and paneled portion, the section cut to length and miter jointed with plastic corner brackets and with corner brackets for window outer frames of 50mm x 60mm, the mullion section fixed to the frame with plastic mullion cap and stiffener plates of size 60 mm x 50 mm made of 1.25mm thick CRCA electroplated provided to fix window frames to concrete/masonry, gasket for fixing glass and 10mm both sides pre-laminated cement bonded particle board and 5 mm thick color pin headed glass provided for glazing and providing guard bars of 10 mm square rods duly welded at 150 mm pitch to MS flat section of size 18 mm and 3 mm thick, and fixed to wall by means of self expansion nylon Cap (75) and electroplated wooden screws of size 100 mm, together with aluminum powder coated fittings, A) 75mm long grip handles 1 no per shutter, B) 75 mm long tower bolts 2 nos. per shutter, C) Heavy duty SS Pivot hinges 2 no's per shutter, D) MS Powder coated telescopic stay 1 no per shutter.		
846	MAT-01484	BMT-P.76-A	Pre Laminated Cement Bonded Particle Board WINDOWS – Single shutter 2'0"x4'0" outer frame section size of 50mm x 60mm shutter frame section size of 48mm x 25mm.	1 Sqm	6649
847	MAT-01485	BMT-P.76-B	Pre Laminated Cement Bonded Particle Board WINDOWS –Double shutter 3'0" x 4'0" outer frame section size of 50mm x 60mm shutter frame section size of 48mm x 25mm mullion section size of 50mm x 60mm for outer frame.	1 Sqm	6741
848	MAT-01486	BMT-P.76-C	Pre Laminated Cement Bonded Particle Board WINDOWS – Double shutter 3'0" x 3'0" outer frame section size of 50mm x 60mm shutter frame section size of 48mm x 25mm Mullion section size of 50mm x 60mm for outer frame.	1 Sqm	7015

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
849	MAT-01487	BMT-P.76-D	Pre Laminated Cement Bonded Particle Board WINDOWS – Double shutter 4'0"x4'0" outer frame section size of 50mm x 60mm shutter frame section size of 48mm x 25mm Mullion section size of 50mm x 60mm for outer frame.	1 Sqm	6478
		II.SUB-SECTION	SLIDING WINDOWS		
850	MAT-01434	BMT-P.26	Providing and fixing Pre painted Steel sliding Window/Door fabricated from roll formed sections made of Galvanized steel colour coated /powder coated (Base Steel as per IS 513 'D' quality galvanized as per IS 277 with Zinc of 120 Gms./ Sq.mtr) with total coated thickness of 0.58mm. Primer Coat with epoxy primer of 5-7 microns thick, finished paint with a polyester paint of 12-16 microns thick and back coated with Alkyd backer of 5-7 microns or powder coated with pure polyester powder up to 50-60 microns thick. The External Section for two track Sliding Window should be of 44 x 59mm with a provision for bottom track insert profile of 10x9 mm made of aluminium. Section for Window glass shutter should be of 35x49mm, Section for Window Euro groove should be of 25x24mm made of plastic to accommodate standard accessories, and section for window lap strip should be of 21x4mm made of plastic. Section for Door shutter should be of 35x67mm, Section for Door Euro Groove 25x31mm made of plastic to accommodate standard accessories and size of lap strip should be of 39x41mm. The Window/Door to be panelled with 5mm thick plain float glass. The gaskets are to be made of Ethyl Propylene Diamine Manomer [EPDM]. Corner Brackets for internal and external frame to be made of glass filled nylon. Touch lock to be provided for Window Shutter. Sections are to be cut to length, joined and assembled by means of corner brackets. The above frame to be fixed to Brick/Concrete masonry by using Nylon self-expanding caps and driving MS electroplated 80mm screws into the caps through frames. The Grill for safety for windows to be made of 10mm thick square rod bars with 152mm pitch for	1 Sqm	7377

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			complete item of work . For Door there will be no Safety Grill including cost and conveyance of all materials, accessories, labour charges for transportation, erection at site complete for finished item of work.		
851	MAT-01435	BMT-P.27	ITEM DELETED		
852	MAT-01436	BMT-P.28	ITEM DELETED		
853	MAT-01437	BMT-P.29	ITEM DELETED		
854	MAT-01445	BMT-P.37	Providing and fixing COMPOSITE SLIDING WINDOW fabricated from roll formed sections made of Galvanized Steel colour Coated/Powder Coated (Base Steel as per IS 513 "D" quality, Galvanized as per IS 277 with Zinc of 120 grams /Sq.Mtr.) with total coated thickness of 0.58 mm, powder coated with pure Polyester Powder up to 50-60 microns thick and the section for external frame bottom of 68 x 25mm (Aluminium), External frame sides & Top of 68 x 25 mm (Aluminium), section for shutter of 59 x 23mm and Lap Strip of 30 x 7.5mm (uPVC) cut to length and mitre joined with L-bracket and 5 mm plain float Galss with Ethyl Propylene Diamine Monomer (EPDM) gasket, the corner bracket for external frame made of Aluminium 'L'-Angle, Corner Bracket for internal frame made of Polypropylene, Crescent Latch, Rollers, & EPDM Gaskets for shutters, wool pile for lap strip, Bump Stop Base & Rubber for shutter stopper including fixing to brick/concrete masonry using Nylon self-expanding caps and driving MS electroplated 80mm long screws into the caps through frames and fixing 10mm square guard bars with 6" pitch centre to centre (152.4mm) completed for finished item of work	1 Sqm	6609
			Providing and fixing of Two shutter Sliding Windows made of Galvanized Steel (Base Steel as per IS 513, D quality, galvanized as per IS 277 with Zinc of 120 GSM), using factory made section powder coated with Pure polyester powder upto 50-60 microns thick with total coated thickness of 0.58 mm for Outer Frame and 0.58 mm thickness for Sliding Shutter Section, the Outer Frame for Two Tracks with Grill		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			provision size of 90 mm x 50 mm and without grill provision is of 75 mm x 50 mm and the Window Shutter section of 0.58 mm x 36 mm and the outer Frame with two integrated guide tracks of 12mm width and 24mm deep for provision to slide the Shutter / sash frame and facilitates with a water drain outlet component made of PVC and the shutter frame fitted with 5mm thick plain float glass of reputed make and fixed with EPDM weathering seal resistant accessories and handle made of Alumimium 1 No. per each shutter and cut to length miter joined with corner brackets including installation of window system at site using anchor fasteners, Silicon sealant applied at the Outer frame corners inclusive of conveyance of all materials accessories, labour charges, and erection at site with complete finished item of work.		
855	MAT-01446	BMT-P.38	a) Window with Two Sliding Shutters and without Grill Outer Frame Size 75 mm x 50 mm.	1 Sqm	7089
856	MAT-01447	BMT-P.39	b) Window with Two Sliding Shutters and with Grill Outer Frame Size 90 mm x 50 mm have a rebate of 15mm x 5 mm to fit grill made of 10mm MS Sq Rods for horizontal bars welded at a regular pitch of 150mm to 12mm x 6 mm MS flat.	1 Sqm	7241
			Providing and fixing of Three shutter Sliding Windows made of Galvanized Steel (Base Steel as per IS 513, D quality, galvanized as per IS 277 with Zinc of 120 GSM), using factory made section powder coated with Pure polyester powder upto 50-60 microns thick with total coated thickness of 0.58 mm for Outer Frame and 0.58 mm thickness for Sliding Shutter Section, the Outer Frame for three tracks with grill provision size of 105 mm x 50 mm and without grill provision is of 90 mm x 50 mm and the Window Shutter section of 58 mm x 36 mm and the outer Frame with two integrated guide tracks of 12mm width and 24mm deep for provision to slide the Shutter / sash frame and facilitates with a water drain outlet component made of PVC and the shutter frame fitted with 5mm thick plain		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			float glass of reputed make and fixed with EPDM weathering seal resistant accessories and handle made of Alumimium 1 No. per each shutter and cut to length miter joined with corner brackets including installation of window system at site using anchor fasteners, Silicon sealant applied at the Outer frame corners inclusive of conveyance of all materials accessories, labour charges, and erection at site with complete finished item of work.		
			Window with 3 shutters (center fixed shutter / Center sliding shutter / center Fly mesh shutter) and with Grill Window made of Outer Frame of Size 105 mm x 50 mm. Grill made of 10mm MS Square Rods for horizontal bars at a regular pitch of 150mm welded to MS flat of 12 x 6 mm.		
857	MAT-01448	BMT-P.40	i) Center Shutter Fixed: center shutter frame made of section with size 20mm x 47mm should be fitted with 5mm thick plain float glass of reputed make, EPDM gasket all around the glass and fixed to the Outer Frame with the supporting section of size 29mm x 20mm of 0.58mm thick fixed horizontally on top and bottom of the shutter frame.	1 Sqm	7178
858	MAT-01449	BMT-P.41	ii) Center Shutter Sliding: center shutter frame made of section of size 20mm x 47mm should be fitted with 5 mm thick plain float glass of reputed make. The supporting guide section of size 15mm x 19mm of 0.58mm thick fixed horizontally at top and bottom of shutter frame and slides along the bottom and top guide tracks made of sections size 24mm x 20mm of 0.58mm thick and 29mm x 20mm of 0.58mm thick	1 Sqm	7976
859	MAT-01450	BMT-P.42	iii) Center Fly mesh Shutter Sliding: Section for Fly mesh Shutter frame should be of size 20mm x 40mm of 0.58mm thick and fitted with SS mesh (304 Grade). The supporting guide section of size 29mm x 20mm of 0.58mm thick at the bottom and 15mm x 19mm of 0.58mm thick at the top fixed horizontally to the Fly mesh frame and slides along the bottom and top guide tracks made of sections size 20mm x 20mm of 0.58mm and 29mm x 20mm of 0.58mm.	1 Sqm	7976

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			Window with 3 shutters (Center fixed shutter / Center sliding shutter / center Fly mesh shutter) and without Grill Window made of Outer Frame of size 90mm x 50mm.		
860	MAT-01451	BMT-P.43	i) Center Shutter Fixed: center shutter frame made of section with size 20mm x 47mm of 0.58mm thick should be fitted with 5mm thick plain float glass of reputed make, EPDM gasket all around the glass and fixed to the Outer Frame with the supporting section of size 29mm x 20mm of 0.58mm thick fixed horizontally on top and bottom of the shutter frame.	1 Sqm	6691
861	MAT-01452	BMT-P.44	ii) Center Shutter Sliding: center shutter frame made of section with size 20mm x 47mm of 0.58mm thick should be fitted with 5 mm thick plain float glass of reputed make. The supporting guide section of size 15mm x 19mm of 0.58mm thick fixed horizontally at top and bottom of shutter frame and slides along the bottom and top guide tracks made of sections size 24mm x 20mm of 0.58mm thick and 29mm x 20mm of 0.58mm thick.	1 Sqm	7231
862	MAT-01453	BMT-P.45	iii) Center Fly mesh Shutter Sliding: Section for Fly mesh shutter frame should be of size 20mm x 40mm and fitted with SS mesh (304 Grade). The supporting guide section of size 29mm x 20mm of 0.58mm thick at the bottom and 15mm x 19mm of 0.58mm thick at the top fixed horizontally to the Fly mesh frame and slides along the bottom and top guide tracks made of sections size 20mm x 20mm of 0.58mm thick and 29mm x 20mm of 0.58mm thick.	1 Sqm	7208
835 to 837			ITEM DELETED		
838		BMT-P.78	Providing and fixing factory made uPVC any colour casement/casementcum fixed glazed windows comprising of uPVC multi-chambered frame,sash and mullion (where ever required) extruded profiles duly reinforced with 1.60 ± 0.2 mm thick galvanized mild steel section made from rollforming process of required length (shape & size according to uPVCprofile), uPVC extruded glazing beads of appropriate		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			dimension, EPDM gasket, stainless steel (SS 304 grade) friction hinges, zinc alloy (white powder coated) casement handles, G.I fasteners 100 x 8 mm size for fixing frame to finished wall, plastic packers, plastic caps and necessary stainless steel screws etc. Profile of frame & sash shall be mitred cut and fusion welded at all corners, mullion (if required) shall be also fusion welded including drilling of holes for fixing hardware's and drainage of water etc. After fixing frame the gap between frame and adjacent finished wall shall be filled with weather proof silicon sealant over backer rod of required size and of approved quality, all complete as per approved drawing & direction of Engineer-in-Charge inclusive of cost of Single / double glass panes and silicon sealant . Note: For uPVC frame, sash and mullion extruded profiles minus 5% tolerance in dimension i.e. in depth & width of profile shall be acceptable. Variation in profile dimension in higher side shall be accepted but no extra payment on this account shall be made.		
867	MAT-05444	BMT-P.78.A	Casement window double panels with top fixed with S.S. friction hinges (350 x 19 x 1.9 mm) made of (small series) frame 47 x 50 mm, sash 47 x 68 mm & mullion 47 x 68 mm all having wall thickness of 1.9 ± 0.2 mm and single glazing bead of appropriate dimension. (Area of window upto 2.50 sqm).	Sqm	7006
868	MAT-05445	BMT-P.78.B	Casement cum fixed panel window having both end single casement panel, middle fixed panels and at top completely fixed ventilator with S.S friction hinges (350 x 19 x 1.9) made of (big series) frame 67 x 60 mm, sash 67 x 80 mm & mullion 67 x 80 mm all having wall thickness of 2.3 ± 0.2 mm and single glazing bead/double glazing bead of appropriate dimension. (Area of window above 3.00 sqm upto 5.00 sqm).	Sqm	7225
	MAT-05446	BMT-P.79	Providing and fixing factory made uPVC any colour fixed glazed windows / Ventilators comprising of uPVC multi-		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			chambered frame and mullion (where ever required) extruded profiles duly reinforced with 1.60± 0.2 mm thick galvanized mild steel section made from roll forming process of required length (shape & size according to uPVC profile), uPVC extruded glazing beads of appropriate dimension, EPDM gasket/TPV, G.I fasteners 100 x 8 mm size for fixing frame to finished wall, plastic packers, plastic caps and necessary stainless steel screws etc. Profile of frame shall be mitred cut and fusion welded at all corners, mullion (if required) shall be also fusion welded including drilling of holes for fixing hardware's and drainage of water etc. After fixing frame the gap between frame and adjacent finished wall shall be filled with weather proof silicone sealant over backer rod of required size and of approved quality, all complete as per approved drawing & direction of Engineer-in-Charge inclusive of cost of Single / double glass panes and silicon sealant. Note: For uPVC frame, sash and mullion extruded profiles minus 5% tolerance in dimension i.e. in depth & width of profile shall be acceptable. Variation in profile dimension in higher side shall be accepted but no extra payment on this account shall be made.		
869		BMT-P.79.A	Fixed windows / Ventilators made of (small series) frame 47 x 50mm & mullion 47 x 68 mm both having wall thickness of 1.9 ± 0.2 mm and single glazing bead of appropriate dimension.	1 Sqm	6456
870		BMT-P.80	Providing and fixing factory-made uPVC any colour sliding glazed window upto 1.50 m in height dimension comprising of uPVC multi-chambered frame with in-built roller track and sash extruded profiles duly reinforced with 1.60 ± 0.2 mm thick galvanized mild steel section made from roll forming process of required length (shape & size according to uPVC profile), appropriate dimension of uPVC extruded glazing beads and uPVC extruded interlocks, EPDM gasket/TPV, wool pile, zinc alloy (white		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			powder coated) touch locks with hook, zinc alloy body with single nylon rollers (weight bearing capacity to be 40 kg), G.I fasteners 100 x 8 mm size for fixing frame to finished wall and necessary stainless steel screw etc. Profile of frame & sash shall be mitred cut and fusion welded at all corners, including drilling of holes for fixing hardware's and drainage of water etc. After fixing frame the gap between frame and adjacent finished wall shall be filled with weather proof silicon sealant over backer rod of required size and of approved quality, all complete as per approved drawing & direction of Engineer-in-Charge inclusive of cost of Single / double glass panes, wire mesh and silicon sealant . Note: For uPVC frame and sash extruded profiles minus 5% tolerance in dimension i.e. in depth & width of profile shall be acceptable. Variation in profile dimension in higher side shall be accepted but no extra payment on this account shall be made.		
871	MAT-05447	BMT-P.80.A	Two track two panels sliding window made of (small series) frame 52 x 44 mm & sash 32 x 60 mm both having wall thickness of 1.9 ± 0.2 mm and single glazing bead of appropriate dimension. (Area of window upto 1.75 sqm)	1 Sqm	6698
872	MAT-05448	BMT-P.80.B	Three track three panels sliding window with fly proof SS wire mesh (Two nos. glazed & one no. wire mesh panels) made of (small series) frame 92 x 44 mm & sash 32 x 60 mm both having wall thickness of 1.9 ± 0.2 mm and single glazing bead of appropriate dimension (Area of window upto 1.75 sqm).	1 Sqm	9000
873	MAT-05449	BMT-P.80.C	Two track two panels sliding window made of (big series) frame 67 x 50 mm & sash 46 x 62 mm both having wall thickness of 2.3 ± 0.2 mm and single glazing bead / double glazing bead of appropriate dimension. (Area of window above 1.75 sqm)	1 Sqm	6960

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			upto 2.50 sqm).		
874	MAT-05450	BMT-P.81	Providing and fixing factory made uPVC any colour sliding glazed window above 1.50 m in height dimension comprising of uPVC multi-chambered frame with in-built roller track and sash extruded profiles duly reinforced with 1.60 ± 0.2 mm thick galvanized mild steel section made from rollforming process of required length (shape & size according to uPVC profile), appropriate dimension of uPVC extruded glazing beads, uPVC extruded interlocks and uPVC extruded Inline sash adaptor (if required), EPDM gasket/TPV, wool pile, zinc alloy (white powder coated) handle on one side of extreme panel along with zinc plated mild steel multi pointlocking having transmission gear with keeps, zinc alloy (white powdercoated) touch lock with hook (if required for wire mesh panel), stainless steel (SS 304 grade) body with adjustable double nylon rollers (weightbearing capacity to be 120 kg), G.I fasteners 100 x 8 mm size for fixing frame to finished wall and necessary stainless steel screws etc. Profile of frame & sash shall be mitred cut and fusion welded at all corners, including drilling of holes for fixing hardware's and drainage of water etc. After fixing frame the gap between frame and adjacent finished wall shall be filled with weather proof silicon sealant over backer rod of required size and of approved quality, all complete as per approved drawing & direction of Engineer-in-Charge inclusive of cost of Single / double glass panes, wire mesh and silicon sealant . Two track two panels sliding window made of (big series) frame 67 x 50 mm & sash 46 x 62 mm both having wall thickness of 2.3 ± 0.2 mm and single glazing bead / double glazing bead of appropriate dimension. (Area of window above 2.50 sqm upto 4.00 sqm.) Note: For uPVC frame and sash extruded profiles minus 5% tolerance in dimension i.e. in depth & width of profile shall be	1 Sqm	7484

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			acceptable. Variation in profile dimension in higher side shall be accepted but no extra payment on this account shall be made.		
		BMT-P.82	Double Skin powder coated GI openable/casement single rebate Windows with 5mm thick Polycarbonate sheet SIZE OF WINDOW 1.50 M X 1.35M (three openable shutters) Providing and fixing of powder coated Openable/Casement GI Window of size 1.50mx1.35m (three openable shutters). Window frame having two horizontals & four verticals (Base steel as per IS513 of 0.60mm thick galvanized as per IS 277 with Zinc of 120 GSM), powder coated paint of 60-65microns(DFT) thick and section for double Skin outer frame of 80 mm x 65 mm x 0.6mm thick including architrave of 20mm, centre mullions of 80mm x 60mm x 0.6mm thick and section for Double Skin shutter of 52mm x 25 mm x 0.6 mm thick, outer frame and mullions to have rebate for glazed shutter and the sections cut to length metre joined with corner bracket, center mullion fixed with mullion cap, shutter with 5mm thick Polycarbonate Solid clear UV resistant sheet of reputed make (UV stabilized, transparent & solid section) with EPDM rubber gaskets including fixing the frames in concrete/masonry wall by means of self-expanding screws, Including 10mm Square guard bars with 14Nos horizontals & two verticals, beading section size of 9 x 12mm to be provided in shutter for Polycarbonate sheet holding, including infill material of polyurethane foam (PUF) and all fixers like 100mm long SS handle -3 Nos, 125mm long SS tower bolts-6Nos, 75mm long SS ball bearing butt Hinges-9Nos, 200mm long SS latch type window stopper -3Nos (all fixers should be stainless steel 304 grade) including all stiffeners ,supporting plates, SS 304 screws, Nylon caps, EPDM rubber gasket etc., complete for finished item of work. and including cost & conveyance of all materials and all labour charges like loading, unloading, and fixing of powder coated Galvanized Steel Window etc., complete for finished item of work. Window Frame: Frame having four verticals & two horizontals, around frame section of size; 80mmx65mm x 0.6mm thick including architrave of 20mm and center mullions section of size; 80mmx60mm x 0.6mm thick. (2Nos), with single rebate.	1 Sqm	13065

			Shutters (3 Nos): Shutter section of size 52mm x25 mm x 0.6 mm thick with 5mm thick Polycarbonate Solid Clear UV resistant sheet of reputed make (UV stabilized, transparent & solid section) Infill Material: polyurethane foam (PUF) Grill : Grill having 14 Nos of 10mm sq rods (horizontal) and 2Nos of 10mm Sq rods (verticals), 10mm sq rods should be inserted into outer frame & center mullions as directed by the Engineering in charge, Fixers: 100mm long SS handle -3 Nos, 125mm long SS tower bolts-6 Nos, 75mm long SS ball bearing butt Hinges 9 Nos, 200mm long SS latch type window stopper -3 Nos Note ; all fixers should be stainless steel 304 Shall confirm to the BIS codes: - IS 1038:1983: Steel doors and windows, IS 4351:2003: Steel Door and window shutters, IS 13871:1993: Powder coating, IS 277: Galvanized Steel Sheets, IS 513: Cold reduced low carbon steel sheets IS ; 1081: Fixing and glazing of Steel Doors and Windows, IS 14443 (1997): Polycarbonate sheets and all other relevant codes of BIS. This Item shall carry a warranty period of 5 (Five) Years from the date of supply and fixing.		
		BMT-P.83	Supply of factory made of Double Skin Pass Galvanized Powder coated openable / casement Double rebate Window of (all sizes) having horizontal & vertical frames, Base steel as per IS 513 of 0.60 mm thick 'D' Quality Double Skin Pass galvanized Iron Sheet as per IS 277, with Zinc coating of 120 GSM, Pure Polyester powder coated paint of 60 - 65 microns (DFT) thick and Closed Box Type section for outer frame of 100 mm x 65 mm x 0.6 mm thick including Design architrave (Inside / Outside) of 20 mm, Closed Box Type section for centre mullions of 100 mm x 65 mm x 0.6 mm thick, Closed Box Type section for Glazed shutter of 60 mm x 25 mm x 0.6 mm thick and Closed Box Type section for Fly mesh shutter of 60 mm x 25 mm x 0.6 mm thick, all Closed Box Type section are Roll formed with Suitable lock-seam joints shall be provided with proper stitching procedures. Welding, soldering, screws, bolts and nuts shall be avoided during Manufacturing and Assembling Process. The outer frame and mullions to have rebate for glazed shutter and Flymesh Shutter, the sections cut to length, miter joined with corner bracket, centre mullion fixed with mullion cap, Glazed shutter with Glazing Sheet with Ethyl Propylene Diamine Monomer (EPDM) gaskets section size of 8 mm x 10 mm to be provided in shutter for Glazing Sheet holding, Flymesh shutter with Stainless Steel 304 grade Mesh with 2.6 mm Dia		

			Aluminium wire for Strengthening Mesh to avoid Waviness and Ethyl Propylene Diamine Monomer (EPDM) gaskets including fixing the Outer frame in concrete / masonry wall by means of self-expanding screws, Aluminium Profile Size of 10.2 mm X 13.00 mm to be provided in Shutter for 2.6 mm Aluminium Wire, Flymesh ,EPDM Gasket Holding ,Ethyl Propylene Diamine Monomer (EPDM) gaskets section size of 4 mm x 6 mm to be provided in shutter for Flymesh holding, including infill material of polyurethane foam (PUF) and all including all stiffeners ,supporting plates, Stainless Steel 304 grade screws, Nylon caps, EPDM rubber gasket etc Flymesh in Flymesh Shutter : Stainless Steel 304 Grade – 32 Gauge with 144 Holes per Sq. Inch Grill : Grill having 10 mm Sq Bright Bars and 10 mm Sq Bright Bars should be inserted into outer frame & centre mullions Without Screws Fixing. Fixers: 100 mm long Stainless Steel 304 grade 'D' handle - 1 No. for Each Glazed Shutter and Flymesh Shutter, 125 mm long Stainless Steel 304 grade 'S' Type Tower Bolts - 1 No's for Each Glazed Shutter and 125 mm long Stainless Steel 304 grade Tower Bolts - 1 No's for Each Flymesh Shutter, 75 mm long Stainless Steel 304 grade butt Hinges - 3 No's for Each Glazed Shutter and Flymesh Shutter, 200 mm long Stainless Steel 304 grade latch type window stopper - 1 No. for Each Glazed / Flymesh Shutter. Infill material of Polyurethane (PUF) shall be provided in Window frame Box Profile, Mullion Box Profile and Shutter Box Profile. Density of Polyurethane Foam shall be 32 to 36 kg / m³. Weather Gasket for outer frame & Mullions: Groove in Frame and Mullion shall be provided to hold EPDM Gasket so that the shutters will not hit/rest on the frame and Mullion when the shutters are closed. The window shutter shall rest on the EPDM Gasket when closed. And to make the window as weather resistant. In the shutter suitable size U shaped Ethyl Propylene Diamine Monomer (EPDM) gaskets shall be provided to hold the Glazing sheet. Landing cost – including loading, cost of conveyance, unloading		
		BMT-P.83.A	Window with Glazing Sheet in Shutter: 5 mm thick Toughened Plain Glass 5 mm.	Sqm	15624
		BMT-P.83.B	Window with Glazing Sheet in Shutter: 4 mm thick Float Glass.	Sqm	14939

		BMT- P.84	Supply of Factory made of Double Skin Pass Galvanized Iron Powder coated openable / casement Single rebate Window of (all sizes) having horizontal & vertical frames , Base steel as per IS 513 of 0.60 mm thick 'D' Quality Double Skin Pass galvanized Iron Sheet as per IS 277, with Zinc coating of 120 GSM, Pure Polyester powder coated paint of 60 - 65 microns (DFT) thick and Closed Box Type section for outer frame of 80 mm x 65 mm x 0.6 mm thick including Design architrave (inside / outside) of 20 mm, Closed Box Type section for centre mullions of 80 mm x 65 mm x 0.6 mm thick and Closed Box Type section for shutter of 60 mm x 25 mm x 0.6 mm thick, all Closed Box Type section are Roll formed with Suitable lock-seam joints shall be provided with proper stitching procedures. Welding, soldering, screws, bolts and nuts shall be avoided during Manufacturing and Assembling Process. The outer frame and mullions to have rebate for glazed shutter and the sections cut to length, miter joined with corner bracket, centre mullion fixed with mullion cap, shutter with Glazing Sheet with Ethyl Propylene Diamine Monomer (EPDM) gaskets including fixing the Outer frame in concrete / masonry wall by means of self- expanding screws, Ethyl Propylene Diamine Monomer (EPDM) gaskets section size of 8.0 mm x 10.0 mm to be provided in shutter for Glazing Sheet holding, including infill material of polyurethane foam (PUF) and all fixers including all stiffeners ,supporting plates, Stainless Steel 304 grade screws, Nylon caps, EPDM rubber gasket etc., Grill: Grill having of 10 mm Sq Bright Bars (horizontals and Verticals) and 10 mm Sq Bright Bars should be inserted into outer frame & centre mullions Without Screws Fixing. Fixers: 100 mm long Stainless Steel 304 grade 'D' handle - 1 No. for Each Shutter, 125 mm long Stainless Steel 304 grade 'S' Type Tower Bolts - 2 No's for Each Shutter, 75 mm long Stainless Steel 304 grade Butt Hinges - 3 No's for Each Shutter, 200 mm long Stainless Steel 304 grade latch type window stopper - 1 No. for Each Shutter. Infill material of Polyurethane (PUF) shall be provided in Window frame Box Profile, Mullion Box Profile and Shutter Box Profile. Injected Polyurethane Foam (PUF) procedure shall be adopted. Density of Polyurethane Foam shall be 32 to 36 kg / m³. Weather Gasket for outer frame & Mullions: Groove in Frame and Mullion shall be provided to hold EPDM Gasket so that the shutters will not hit/rest on the		

			frame and Mullion when the shutters are closed. The window shutter shall rest on the EPDM Gasket when closed. And to make the window as weather resistant. In the shutter suitable size U shaped Ethyl Propylene Diamine Monomer (EPDM) gaskets shall be provided to hold the Glazing sheet. Landing cost – including loading, cost of conveyance, unloading		
		BMT-P.84.A	Window with Glazing Sheet in Shutter: 5 mm thick Toughened Plain Glass 5 mm.	Sqm	10061
		BMT-P.84.B	Window with Glazing Sheet in Shutter: 4 mm thick Float Glass.	Sqm	9307
		III.SUB-SECTION	VENTILLATORS		
			Providing and fixing of top hung Ventilators made of pre-painted steel (Base steel as per IS 513 of 0.80 mm thick galvanized as per IS 277 with Zinc of 120 GSM), finish painted with a polyester paint of 60-65 microns thick and section for outer frame of 80 x 45 mm, centre mullion of 80 x 60 mm, section for shutter of 52 x 25 mm x 0.6 mm thick, outer frame and mullions to have rebate for glazed shutter with a provision for guard bars/grills and the sections cut to length metre joined with corner bracket, centre mullion fixed with mullion cap, 1 No. of High grade nylon latch handle, window stopper, 2 nos. of with MS Powder coated /SS ball bearing butt Hinges provided per shutter and windows fitted with 4 mm thick plain float glass with rubber gaskets including fixing the frames in concrete/masonry wall by means of self expanding screws, Including 10 mm Square guard bars with 6" (152.4mm) pitch etc., complete for finished item of work.		
875	MAT-01464	BMT-P.56	Single openable ventilator shutter size of 2' 0" x 2' 0" (609.6 x 609.6mm) outer frame section size of 80 x 45mm, shutter frame section size of 52 x 25mm thick	1 sqm	7024
876	MAT-01465	BMT-P.57	Double openable ventilator shutter Size of 4' 0" x 2' 0" (1219.2mm x 609.6mm) outer frame section size of 80 x 45mm, shutter frame section size of 52 x 25mm, vertical mullion section size of 80 x 60 mm	1 sqm	7024
877	MAT-01466	BMT-P.58	Double openable fix shutter size of 4'0" x 3'0" (1219.2mm x 914.4mm) outer frame section size of 80 x 45mm , shutter frame section size of 52 x 25 mm , Vertical mullion section size of 80 x 60 mm	1 sqm	7024

878	MAT-01467	BMT-P.59	Single fixed Louvers Ventilator size of 2' 0" x 2' 0" (609.6 x 609.6mm) outer frame box section size of 80 x 45mm	1 sqm	4832
879	MAT-01468	BMT-P.60	Double fixed Louvers ventilator Size of 4' 0" x 2' 0" (1219.2mm x 609.6mm) outer frame box section size of 80 x 45mm, vertical mullion section size of 80 x 60 mm	1 sqm	4832
880	MAT-01469	BMT-P.61	Double fixed Louvers Ventilator size of 4'0" x 3'0" (1219.2mm x 914.4mm) outer frame box section size of 80 x 45mm , Vertical mullion section size of 80 x 60 mm	1 sqm	4602
			Note: The above rates are for normal finish, 10% extra may be allowed for Wood Grain finish		
			Providing and fixing of top hung Ventilator with fly mesh made of pre-painted steel (Base steel as per IS 513 of 0.80 mm thick galvanized as per IS 277 with Zinc of 120 GSM), finish painted with a polyester paint of 60-65 microns thick and section for outer frame of 100 x 45 mm, centre mullion of 100 x 60 mm, section for shutter of 52 x 25 mm x 0.6 mm thick, section for fly-shutter of 52 x 25 mm x 0.6 mm thick and fitted with stainless steel 32 gauge fly mesh of 304 grade with 144 holes per sq.inch and mullions to have double rebate for glazed shutter and fly-shutter with a provision for guard bars/grills and the sections cut to length metre joined with corner bracket, centre mullion fixed with mullion cap, 1 No. of High grade nylon latch handle, window stopper, 2 nos. of with MS Powder coated /SS ball bearing butt Hinges provided per shutter and windows fitted with 4 mm thick plain float glass with rubber gaskets including fixing the frames in concrete/masonry wall by means of self expanding screws, Including 10 mm Square guard bars with 6" (152.4mm) pitch etc., complete for finished item of work.		
881	MAT-01470	BMT-P.62	Single openable ventilator shutter window size of 2' 0" x 2' 0" (609.6 x 609.6mm) outer frame section size of 100 x 45mm, Glazed and flymesh shutter frame section size of 52 x 25mm thick	1 sqm	8658
882	MAT-01471	BMT-P.63	Double openable ventilator shutter window Size of 4' 0" x 2' 0" (1219.2mmx 609.6mm) outer frame section size of 100 x 45mm, Glazed and flymesh	1 sqm	8658

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			shutter frame section size of 52 x 25mm, vertical mullion section size of 100 x 60 mm		
883	MAT-01472	BMT-P.64	Double openable fix shutter window size of 4'0" x 3'0" (1219.2mm x 914.4mm) outer frame section size 100 x 45mm , Glazed and flymesh shutter frame section size 52 x 25 mm , Vertical mullion section size of 100 x 60 mm	1 sqm	8016
884	MAT-01473	BMT-P.65	Single fixed Louvers Ventilator window size of 2' 0" x 2' 0" (609.6 x 609.6mm) outer frame box section size of 100 x 45mm, flymesh shutter frame section size 52 x 25 mm	1 sqm	5779
885	MAT-01474	BMT-P.66	Double fixed Louvers ventilator window Size of 4' 0" x 2' 0" (1219.2mm x 609.6mm) outer frame box section size of 100 x 45mm, flymesh shutter frame section size 52 x 25 mm, vertical mullion section size of 100 x 60 mm	1 sqm	5779
886	MAT-01475	BMT-P.67	Double fixed Louvers Ventilator window size of 4'0" x 3'0" (1219.2mm x 914.4mm) outer frame box section size 100 x 45mm , flymesh shutter frame section size 52 x 25 mm Vertical mullion section size of 100 x 60 mm	1 sqm	5779
			<i>Note: The above rates are for normal finish, 10% extra may be allowed for Wood Grain finish</i>		
			Supplying and fixing of Top Hung Ventilators made of pre - painted steel (base steel as per IS 513 of -0.58 mm thick 'D' quality, galvanized as per IS 277 with zinc of 120 GSM) primer coated with epoxy primer of 5-7 microns thick, finish painted with a polyester paint of 12-16 microns thick and back coated with 5-7 microns thick alkyd backer, section for outer frame of 46 x 52 mm section and for shutter of 46 x 46 mm section for mullion 46 x 70 mm, The Ventilator to be panelled 4 mm pinhead glass with Ethyl propylene Diamine monomer Gasket (EPDM) and the sections cut to length mitre joined with corner bracket mullions fixed using mullion cap and with handle made of high grade aluminium powder coated and nylon receiver, corner brackets made of CRCA with Zinc Phosphate, Mullion caps made of glass filled nylon, frames fixed to the concrete /masonry		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			wall by means of self expanding screws including 10 mm square guard bars with 6" pitch complete for finished item of work.		
887	MAT-01418	BMT-P.10	Ventilators: Top Hung 2'-0" x 2'-0" (609.6x609.6mm) outer frame section size of 46mm x 52 mm shutter frame section size of 46mm x 46 mm	1 Sqm	7747
888	MAT-01419	BMT-P.11	Ventilators: Top Hung 4'-0" x 2'-0" (1219.2x609.6mm) outer frame section size of 46 x 52 m shutter frame section size of 46 x 46 mm Mullion section size of 46 x 70 mm	1 Sqm	7747
889	MAT-01420	BMT-P.12	Ventilators: Top Hung 4'-0"x 3'-0" (1219.2x914.4mm) outer frame section size of 46 x 52m m shutter frame section size of 46 x 46 mm Mullion section size of 46 x 70 mm	1 Sqm	7747
			Supplying and fixing of Fixed Louvered Ventilators made of pre - painted steel (base steel as per IS 513 of -0.58 mm thick 'D' quality, galvanized as per IS 277 with zinc of 120 GSM) primer coated with epoxy primer of 5-7 microns thick, finish painted with a polyester paint of 12-16 microns thick and back coated with 5-7 microns thick alkyd backer, The section for louvered ventilators should be of of 33 x 56 mm Box section paneled with 4 mm pinhead glass with Ethyl propylene Diamine monomer Gasket (EPDM) and the sections cut to length mitre joined with corner bracket . corner brackets made of CRCA with Zinc Phosphate. The frames to be fixed to the concrete /masonry wall by means of self expanding screws including 10 mm square guard bars with 6" pitch complete for finished item of work.		
890	MAT-01421	BMT-P.13	Ventilators: Fixed louvers 2'-0" x 2'-0" (609.6x609.6mm)(Box section) outer frame section size of 33 x 56 mm	1 Sqm	5115
891	MAT-01422	BMT-P.14	Ventilators: Fixed louvers 4'-0" x 2'-0" (1219.2 x 609.6 mm) (Box section) outer frame section size of 33 x 56 mm Mullion section size of 33 x 56 mm	1 Sqm	5115
892	MAT-01423	BMT-P.15	Ventilators: Fixed louvers 4'-0" x 3'-0" (1219.2 x 914.4 mm) (Box section) outer frame section size of 33 x 56 mm Mullion section size of 33 x 56 mm	1 Sqm	5115

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
865 to 868		BMT-P.68 to P.75	ITEMS DELETED		
893	MAT-01488	BMT-P.77	Providing and fixing 3 Track 3 Shutter Pre painted Steel sliding Window/Door fabricated from roll formed sections made of Galvanized steel colour coated /powder coated (Base Steel as per IS 513 'D' quality galvanized as per IS 277 with Zinc of 120 Gms./ Sq.mtr) with total coated thickness of 0.58mm. Primer Coat with epoxy primer of 5-7 microns thick, finished paint with a polyester paint of 12-16 microns thick and back coated with Alkyd backer of 5-7 microns or powder coated with pure polyester powder up to 50-60 microns thick. The External Section for Three Track Three Sliding Shutter should be of 44 x 107mm with a provision for bottom track insert profile of 10x9 mm made of aluminium. Section for Window glass shutter should be of 35x49mm, Section for Window Euro groove should be of 25x24mm made of plastic to accommodate standard accessories, and section for window lap strip should be of 21x4mm made of plastic. Section for Mesh Shutter should be of 35x49mm. Section for Door shutter should be of 35x67mm, Section for Door Euro Groove 25x31mm made of plastic to accommodate standard accessories and size of lap strip should be of 39x41mm. The Window/Door to be panelled with 5mm thick plain float glass. The gaskets are to be made of Ethyl Propylene Diamine Manomer [EPDM]. Corner Brackets for internal and external frame to be made of glass filled nylon. Touch lock to be provided for Window Shutter. Sections are to be cut to length, joined and assembled by means of corner brackets. The above frame to be fixed to Brick/Concrete masonry by using Nylon self-expanding caps and driving MS electroplated 80mm screws into the caps through frames. The Grill for safety for windows to be made of 10mm thick square rod bars with 152mm pitch for complete item of work . For Door there will be no Safety Grill including cost and conveyance of all materials, accessories, labour charges for	1 Sqm	8253

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			transportation, erection at site complete for finished item of work.		
Q.SECTION			STRUCTURAL GLAZING		
		I.SUB-SECTION	FIXED GLAZING		
894	MAT-01496	BMT-Q.08	ITEM DELETED		
895	MAT-01497	BMT-Q.09	ITEM DELETED		
II.SUB- SECTION			STRUCTURAL GLAZING		
896	MAT-01489	BMT-Q.01	Providing and fixing Structural Glazing fabricated from Roll formed sections made of Pre-painted Steel / Powder coated (Base steel as per IS 513 of 'D' quality, galvanized as per IS 277 with Zinc of 120 Gm/Sqm) with total coated thickness of 0.72 mm and the glass holding section made of 304 grade stainless steel of 0.58 mm thick galvanised steel section as stiffeners inside the colour coated steel powder coated sections as per the design requirement & calculations to suit wind pressures as given in IS: 875, the primer coat with epoxy primer of 5 – 7 microns thick, finish painted with a polyester paint of 12-16 microns thick and back coated with Alkyd backer of 5-7 microns or powder coated with pure polyester powder up to 50-60 microns thick and the vertical section of 50 mm x 99 mm x 0.72 mm, 33 mm x 56 mm x 0.72 mm for frame horizontal section, stiffener section of 47 mm x 97 mm x 1 mm, cover profiles sections of 20 mm x 58 mm x 0.58 mm, glass holding section of 37 mm x 37 mm & 37 mm x 18 mm including fixing 5mm thick Ocean Blue reflective glass, brackets made of CRCA powder coated/Electroplated to connect vertical to horizontal, vertical to slab, to fix verticals at top & bottom as per site requirement and gasket made of Ethyl Propylene Diamine Monomer, U.V. resistant silicon sealant including fixing in concrete/masonry wall with self-expanding cap & screws inclusive of cost and conveyance of all materials to site, all labour charges, incidental charges, cost of all consumables etc. and fixing charges complete for finished item of work.	1 Sqm	7860

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
897	MAT-01490	BMT-Q.02	Providing and fixing Top Hung shutters in Structural Glazing fabricated from Roll formed sections made of Pre-painted Steel / Powder coated (Base steel as per IS 513 of 'D' quality, galvanized as per IS 277 with Zinc of 120 Gm/Sqm) with total coated thickness of 0.72 mm and the glass holding section made of 304 grade stainless steel of 0.58 mm thick, duly providing stiffeners inside the colour coated steel/powder coated sections as per the design requirement, calculations to suit wind pressures as given in IS 875 and primer coat with epoxy primer of 5-7 microns thick and back coated with Alkyd backer of 5-7 microns or powder coated with pure polyester powder up to 50-60 microns thick and the outer frame of 20 mm x 58 mm x 0.58 mm, shutter sections of 57 mm x 33 mm x 0.72 mm, stiffener sections of 55 mm x 31 mm x 1mm, hinges – 2 Nos for each shutter and aluminium Stays – 2 Nos. for each shutter, aluminium Handle – 1 no. for each shutter including cost and conveyance of all materials to site, all labour charges, incidental charges, cost of all consumables etc. and fixing charges etc for finished item of work	1 Sqm	6280
III SUB- SECTION			CURTAIN WALLING		
898	MAT-01491	BMT-Q.03	Supplying and fixing of curtain Glazing made of pre painted steel (base steel as per IS 513 of 0.58 mm thick D quality, galvanized as per IS 277 with Zinc of 120 GSM) Primer coated with epoxy primer of 5-7 microns thick, finish painted with a polyester paint of 12- 16 microns thick and back coated with 5-7 microns thick alkyd backer using the section for outer frame of 46 x 52 mm, section for mullion of 46 x 70 mm and section for beading of 18 x 25 mm and the glazing with 5 mm thick plain float glass fitted with Ethyl Propylene diameine Monomer (EPDM) gaskets and the sections cut to length, mitre joined with corner bracket, centre mullions fixed suing mullion cap including handle made of high grade Aluminium powder coated and nylon receiver, corner brackets made of CRCA with zinc phosphating, mullion caps made of Glass filled nylon including fixing the	1 Sqm	6522

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			frames in the concrete / masonry wall with self expanding screws, etc., complete for finished item.- Fixed Glazing 2'-0" x 2'-0" (609.6x609.6mm) grid outer frames section size of 46 x 52 mm		
903	MAT-01492	BMT-Q.04	Mullion section size of 46 x 70mm Beading section size of 18 x 25 mm - Fixed Glazing 2'-0" x 3'-0" (609.6x914.4mm) grid outer frame section size of 46 x 52 mm	1 Sqm	6280
904	MAT-01493	BMT-Q.05	Mullion section size of 46 x 70mm Beading section size of 18 x 25 mm Fixed Glazing 3'-0" x 3'-0" (914.4x914.4mm) grid outer frame section size of 46 x 52 mm	1 Sqm	5102
905	MAT-01494	BMT-Q.06	Mullion section size of 46 x 70mm Beading section size of 18 x 25 mm Fixed Glazing 3'-0" x 4'-0" (914.4x1219.2mm) grid outer frame section size of 46 x 52 mm	1 Sqm	5102
906	MAT-01495	BMT-Q.07	ITEM DELETED		
S.SECTION			DISMANTLING clearing away and carefully stacking materials useful for reuse.		
908	MAT-01498	BMT-S.01	Stone masonry in cement mortar	1 Cum	597
909	MAT-01499	BMT-S.02	Terracing work in roofs or floors	10 Sqm	252
910	MAT-01500	BMT-S.03	Flat stones in roof or floors including lifting	10 Sqm	219
911	MAT-01501	BMT-S.04	Pan tiled or Mangalore tiled roof without roof timbers.	10 Sqm	183
912	MAT-01502	BMT-S.05	Flat and pan tiles or Mangalore tiles over flat tiles without roof timbers	10 Sqm	219
913	MAT-01503	BMT-S.06	Wrought and framed timber in roofs or floors	1 Cum	316
914	MAT-01504	BMT-S.07	Old lime mortar plaster	10 Sqm	72
915	MAT-01505	BMT-S.08	Old cement mortar plaster	10 Sqm	90
916	MAT-01506	BMT-S.09	Dry rough stone revetment for aprons and stacking within 40 M lead	1 Cum	108
917	MAT-01507	BMT-S.10	Revetment for aprons and stacking grouted within 40 lead	1 Cum	79
918	MAT-01508	BMT-S.11	Kadapa slabs or Shahabad stone slabs	10	101

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			flooring on sand bed	Sqm	
919	MAT-01509	BMT-S.12	Through scraping of old plastered surface	10 Sqm	66
920	MAT-01510	BMT-S.13	Washing of plastered surface with soap, soda and water (or with soda lime and water)	10 Sqm	21
921	MAT-01511	BMT-S.14	clean removal of lime plaster from walls and raking out joints 20mm deep or from terraced roof and raking out joints 100 mm deep	10 Sqm	66
922	MAT-01512	BMT-S.15	Clean removal of cement plaster from walls and raking out joint 200 mm deep	10 Sqm	81
T.SECTION			READY MIX CONCRETE		DELETED
U.SECTION			EXPANSION JOINT FILLERS		
923	MAT-01513	BMT-U.01	Supply of high performance expansion joint filler board conforming to M.O.S.T - 18 mm THICK	1 Sqm	413
924	MAT-01514	BMT-U.02	Supply of high performance expansion joint filler board conforming to M.O.S.T - 20 mm THICK	1 Sqm	574
925	MAT-01515	BMT-U.03	Supply of high performance expansion joint filler board conforming to M.O.S.T - 25 mm THICK	1 Sqm	798
926	MAT-01516	BMT-U.04	Supply of expansion joint filler board for buildings, columns, beams and slabs 20 mm THICK	1 Sqm	300
927	MAT-01517	BMT-U.05	Supply of expansion joint filler board for buildings, columns, beams and slabs 25 mm THICK	1 Sqm	370
928	MAT-01518	BMT-U.06	Supply of expansion joint filler board for buildings, columns, beams and slabs 50 mm THICK	1 Sqm	745
929	MAT-01519	BMT-U.07	Supply of back up to cold applied sealant in construction and longitudinal joint - 10 mm OD	1 RM	13
930	MAT-01520	BMT-U.08	Supply of back up to cold applied sealant in construction and longitudinal joint - 12 mm OD	1 RM	15
931	MAT-01521	BMT-U.09	Supply of back up to cold applied sealant in construction and longitudinal joint - 15 mm OD	1 RM	17
932	MAT-01522	BMT-U.10	Supply of back up to cold applied sealant in construction and longitudinal joint - 20 mm OD	1 RM	24
933	MAT-01523	BMT-U.11	Supply of back up to cold applied sealant in construction and longitudinal	1 RM	30

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			joint - 25 mm OD		
V.SECTION			LABOUR CHARGES		
934	MAT-01524	BMM-V.01	Bailing out water for earth work excavation /concrete for foundation below water level. (For building items only) - Other than sandy soil - 0.0 M to 1.0 M	1 cum	327
935	MAT-01525	BMM-V.02	Bailing out water for earth work excavation /concrete for foundation below water level. (For building items only) - Other than sandy soil - 1.0 M to 2.0 M	1 cum	386
936	MAT-01526	BMM-V.03	Bailing out water for earth work excavation /concrete for foundation below water level. (For building items only) - Other than sandy soil - 2.0 M to 3.0 M	1 cum	450
937	MAT-01527	BMM-V.04	Bailing out water for earth work excavation / for concrete foundation below water level. (For building items only) Sandy soil - 0.0 M to 1.0 M	1 cum	518
938	MAT-01528	BMM-V.05	Bailing out water for earth work excavation /for concrete foundation below water level. (For building items only) Sandy soil - 1.0 M to 2.0 M	1 cum	804
939	MAT-01529	BMM-V.06	Bailing out water for earth work excavation /concrete for foundation below water level. (For building items only) Sandy soil - 2.0 M to 3.0 M	1 cum	971
940	LAB-00418	BMM-V.07	Labour charges for making, fabricating office furniture, racks, work-station furniture, cup-board shutters with ply-wood/ MDF sheets, decolam/ veneer laminations including fixing cutting, making, assembling, fixing hinges, fixing fixtures, fixing locks, pasting sheets/ laminations fixing in position with necessary screws excluding cost of materials, accessories, fittings	1 Sqm	815
941	LAB-00419	BMM-V.08	Labour charges for making, fabricating kitchen furniture, cup-boards with shutters, box cup-boards, box racks, with ply-wood/ MDF sheets, decolam/ veneer laminations including fixing cutting, making, assembling, fixing hinges, fixing fixtures, fixing locks, pasting sheets/ laminations fixing in position with necessary screws excluding cost of materials, accessories, fittings	1 Sqm	1245

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
942	LAB-00503	BMM-V.09	Rounding the edges of Kadapa / Shahabad stone slabs of any thickness including polishing the same	1 Rm	142
943	LAB-00504	BMM-V.10	Half Rounding the edges of Marble/ Granite stone slabs of all thicknesses including polishing the same.	1 Rm	429
944	LAB-00505	BMM-V.11	Full Rounding the edges of Marble/ Granite stone slabs of all thicknesses including polishing the same.	1 Rm	556
945	LAB-00506	BMM-V.12	Machine Cutting charges - for Marble/ Granite slabs up to 50 mm thick by mechanical device.	1 RM	24
946	LAB-00507	BMM-V.13	Flat nosing to Kadapa/ Shahabad stone slabs of any thick	1 Rm	68
947	LAB-00420	BMM-V.14	Labour charges for fabricating steel works like Window Grills, Compound Wall Grills, Iron Doors, Windows including cost of welding rods, power charges, excluding cost of fixing in position	1 Kg	37
948	LAB-00421	BMM-V.15	Labour charges for fixing Iron Doors, Iron Windows and Window Grills in position	1 Kg	7
949	LAB-00422	BMM-V.16	Labour charges for fabricating all heavy steel works like Trusses, Stanchions, Heavy Beams and Girders including cost of welding rods, power charges, etc excluding cost of fixing in position	1 Kg	33
950	LAB-00423	BMM-V.17	Labour charges for fixing heavy iron grills, Trusses, Stanchions, Heavy Beams and Girders erecting in position and fixing by using chain pulley blocks, Derek pole arrangements and cranes etc., complete in position	1 Kg	28
951	LAB-00424	BMM-V.18	Labour charges for Fabrication of stainless steel railing works using stainless steel welding rods including buffing, polishing, lacquer finishing, to present seamless finish	1 Kg	177
952	LAB-00425	BMM-V.19	Labour charges for Fabrication of stainless steel sheet cladding works using stainless steel welding rods including buffing, polishing, lacquer finishing, to present seamless finish	1 sqm	2365
953	LAB-00426	BMM-V.20	Labour charges for Glass designing works on any thickness of Glass including fixing at site - Etching works	1 Sqm	1287

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
954	LAB-00427	BMM-V.21	Labour charges for Glass designing works on any thickness of Glass including fixing at site - Reverse Etchingwork	1 Sqm	1592
955	LAB-00428	BMM-V.22	Labour charges for Glass designing works on any thickness of Glass including fixing at site - Acid wash works	1 Sqm	1989
956	LAB-00429	BMM-V.23	Labour charges for fixing Flush door shutters of any thickness to the existing door frame including fixing the fixtures to the door shutter excluding cost of shutter	1 Sqm	516
957	LAB-00430	BMM-V.24	Labour charges for fixing glass panes of any thickness to the existing door / window panes including fixing the beading excluding cost of beading	1 Sqm	386
958	LAB-00431	BMM-V.25	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Fully panelled doors external or internal including frame	1 sqm	2115
959	LAB-00432	BMM-V.26	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Glazed and panelled doors including fixing glass including frame	1 sqm	1999
960	LAB-00433	BMM-V.27	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Framed and planked doors including frame	1 sqm	1753
961	LAB-00434	BMM-V.28	charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Lugged, braced and planked doors including frame	1 sqm	1385
962	LAB-00435	BMM-V.29	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Flush type door shutter including frame	1 sqm	1058
963	LAB-00436	BMM-V.30	Labour charges for wrought and put up including fixing in position frames of any	1 sqm	1354

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Windows glazed including outer frame and shutter frame		
964	LAB-00437	BMM-V.31	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Windows panelled including outer frame and shutter frame	1 sqm	2040
965	LAB-00438	BMM-V.32	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Windows ledged, braced and planked including outer frame	1 sqm	1393
966	LAB-00439	BMM-V.33	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Windows framed and planked including outer frame and shutter frame	1 sqm	1666
967	LAB-00440	BMM-V.34	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Ventilators glazed, fixed with double frame with wire netting including frame	1 sqm	1122
968	LAB-00441	BMM-V.35	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Swing ventilators glazed including outer frame and shutter frame	1 sqm	1418
969	LAB-00442	BMM-V.36	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Teak wood Weld mesh doors and windows including outer frame and shutter frame	1 sqm	847
970	LAB-00443	BMM-V.37	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary	1 sqm	929

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			fixtures etc. for Teak wood G.I or .AC sheet door & windows including outer frame and shutter frame		
971	LAB-00444	BMM-V.38	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Fully panelled doors external or internal including frame	1 sqm	2083
972	LAB-00445	BMM-V.39	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Glazed and panelled doors including fixing glass including frame	1 sqm	1956
973	LAB-00446	BMM-V.40	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Framed and planked doors including frame	1 sqm	1869
974	LAB-00447	BMM-V.41	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Lugged, braced and planked doors including frame	1 sqm	1622
975	LAB-00448	BMM-V.42	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Flush type door shutter including frame	1 sqm	1269
976	LAB-00449	BMM-V.43	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Windows glazed including outer frame and shutter frame	1 sqm	1015
977	LAB-00450	BMM-V.44	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Windows panelled including outer frame and shutter frame	1 sqm	1266

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
978	LAB-00451	BMM-V.45	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Windows ledged, braced and planked including outer frame	1 sqm	1887
979	LAB-00452	BMM-V.46	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Windows framed and planked including outer frame and shutter frame	1 sqm	1289
980	LAB-00453	BMM-V.47	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Ventilators glazed, fixed with double frame with wire netting including frame	1 sqm	1539
981	LAB-00454	BMM-V.48	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Swing ventilators glazed including outer frame and shutter frame	1 sqm	1091
982	LAB-00455	BMM-V.49	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood Weld mesh doors and windows including outer frame and shutter frame	1 sqm	1364
983	LAB-00456	BMM-V.50	Labour charges for wrought and put up including fixing in position frames of any size, shutters for doors, windows, ventilators including fixing all necessary fixtures etc. for Other than teakwood G.I or .AC sheet door & windows including outer frame and shutter frame	1 sqm	313
984	LAB-00508	BMM-V.51	Grooves 2-3 mm	1 Rm	78
W.SECTION			MISCELLANEOUS ITEMS		
986	MAT-01575	BMS-W.01	Supplying Aluminium anodised Sections for Doors, partitions, windows, Ventilators (including annodization cost)	1 Kg	368
987	MAT-01576	BMS-W.02	Sun Control film to the glazed windows partition including labour charges.	1 sqm	376

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
987	MAT-01577	BMS-W.03	Aluminium Venetian Blinds horizontal 25.4 mm wide with all accessories.	1 sqm	958
988	MAT-01578	BMS-W.04	Aluminium Venetian Blinds horizontal 20.0 mm wide with all accessories.	1 sqm	912
989	MAT-01579	BMS-W.05	Venetian blinds Vertical blinds 100 mm wide with all accessories.	1 sqm	1548
990	MAT-01580	BMS-W.06	Rubber Beading	1 RM	3
991	MAT-01581	BMS-W.09	Chlorpyrifos/ Lindane emulsifiable concentrate of 20%	1 Litre	261
992	MAT-01582	BMS-W.10	Soft Brush	Each	170
993	MAT-01583	BMS-W.11	Wire Brush	Each	38
994	MAT-01584	BMS-W.12	Supplying and fixing aluminium composite cladding with skin material 0.25 mm thick aluminium sheet cover material natural polyethylene aluminium cladding panel fixed with extruded aluminium basis frame (50x25x1.5mm) angle cleats, weather sealants, rivets, GI brackets all as approved, using suitable bolts on structural steel work including necessary accessories complete in all respects including all scaffolding and labour charges etc., complete for finished item of work but excluding cost of structural steel fabrication, if any, ACP Cladding - 3 mm thk	1 Sqm	2627
995	MAT-01585	BMS-W.13	Supplying and fixing aluminium composite cladding with skin material 0.25 mm thick aluminium sheet cover material natural polyethylene aluminium cladding panel fixed with extruded aluminium basis frame (50x25x1.5mm) angle cleats, weather sealants, rivets, GI brackets all as approved, using suitable bolts on structural steel work including necessary accessories complete in all respects including all scaffolding and labour charges etc., complete for finished item of work but excluding cost of structural steel fabrication, if any, ACP Cladding - 4 mm thk	1 Sqm	2865
996	MAT-01586	BMS-W.14	Supplying and fixing aluminium composite cladding with skin material 0.5 mm thick aluminium sheet cover material natural polyethylene aluminium cladding panel fixed with extruded aluminium basis frame (50x25x1.5mm) angle cleats,	1 Sqm	3214

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			weather sealants, rivets, GI brackets all as approved, using suitable bolts on structural steel work including necessary accessories complete in all respects including all scaffolding and labour charges etc., complete for finished item of work but excluding cost of structural steel fabrication, if any, ACP Cladding - 4 mm thk		
997	MAT-01587	BMS-W.15	CEMENT JALI - 25 mm thick	1 sqm	238
998	MAT-01588	BMS-W.16	CEMENT JALI - 40 mm thick	1 sqm	309
999	MAT-01589	BMS-W.17	CEMENT JALI - 50 mm thick	1 sqm	424
1000	MAT-01590	BMS-W.18	Aluminium sheet 24 Gauge	1 Sqm	308
1001	MAT-01591	BMS-W.19	7.5mm thick Aluminium Grill (as approved by the department) 3.58 Kg/Sqm.	1 Sqm	1129
1002	MAT-01592	BMS-W.20	Mastic pad 2'0 " x 4'0" (0.60M x 1.2M) of 1" (25.4 mm) thick	1 Sqm	1007
1003	MAT-01593	BMS-W.21	Mastic pad 2'0 " x 4'0" (0.60M x 1.2M) of 1/2" (12.7 mm) thick	1 Sqm	577
1004			Supply of hot pressed compression moulded sign plates for making road signs ass per the approved dimensions of National Highway Authority Of India, complete, for finished item of work.		
1005	MAT-01594	BMS-W.22	Circular sign plate Dia 400mm.	Each.	586
1006	MAT-01595	BMS-W.23	Circular sign plate Dia 600mm.	Each.	1540
1007	MAT-01596	BMS-W.24	Circular sing plate Dia 870mm	Each.	3088
1008	MAT-01597	BMS-W.25	Triangular sign plate 600mm.	Each.	791
1009	MAT-01598	BMS-W.26	Triangular sign plate 900mm.	Each.	1787
1010	MAT-01599	BMS-W.27	Square sign plate 600mm.	Each.	1433
1011	MAT-01600	BMS-W.28	Square sign plate 1000mm.	Each.	5318
1012	MAT-01601	BMS-W.29	ITEM DELETED		
			Design, fabrication & supply of light weight pre engineered buildings for a maximum span of 9 metres with 50 x 50 x 2.8 mm M.S hollow square tubes for columns, trusses & purlins walls with sandwich panels made up of 2 Nos 10mm thick cement bonded particle/ fibre boards with 25mm thick 12 kg/cum density expanded polystyrene in between encased in 1.25 mm thick 24x7x26 mm 'W' tracks in bottom & top and 'H' section for sides with doors,		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			windows & ventilators, roofing with 26 gauge pre painted profiled sheets fixed with self tapping/ drilling screws, painting with enamel paint for steel items, OBD for interiors and ace for exteriors & providing base plates, templates & anchor bolts along with civil foundation designs & drawings for the finished item of work		
1013	MAT-01602	BMS-W.30	Steel Structure: - Structure is made up of 50x50X 2.8 mm/33x66x2.8mm thick hollow M.S. sections for Trusses, columns, and purlins. - Columns	1 RM	436
1014	MAT-01603	BMS-W.33	Sandwich panels: Sandwich panels of 50 mm thick with 25 mm thermocol of 12 kg / cum, fixed in between 2 Nos 10 mm cement bonded wood particle / fibre boards properly fixed together with 30 mmx30mmx30mm wood pieces along width & length wherever necessary	1 Sqm	1574
1015	MAT-01604	BMS-W.34	U' Tracks & 'H' Section:- Bottom & Top 'U' Tracks are made of 1.25 mm thick 120 GSM G.I. Sheet of size 24x51x26 mm size.	1 RM	170
1016	MAT-01605	BMS-W.35	Fabricated 'H' sections are made up of 2 Nos 1.25 mm thick C.R. Of 40 mm width for flanges and 1 Nos of 2 mm thick C.R. of 50 mm width plate for web. will be used	1 RM	245
1017	MAT-01606	BMS-W.36	Sandwich Panel joinery is made up of couplers or equivalent made from 0.6 mm G.I. roll formed section to hold 2 Nos of 10 mm board on both sides with 25 mm thermocol in between.	1RM	280
1018	MAT-01607	BMS-W.37	Window:- windows are made up of 51 x51 mm step 'U' section made from 1.25 thick MS Cold rolled Steel Sheet and Windows Shutters & Grill are made of 48x25mm mm size pre painted section with 4 mm glass complete with necessary hardware. Grills are made from 8 mm square rod at 100 mm spacing.	1 Sqm	5052
1019	MAT-01608	BMS-W.38	Door Frames :-51 X 51 Stepped ' U' section made from 1.25 mm thick C.R. section with a 32 mm rebate for 30 mm flush door and Door Shutters with 30 mm thick block board / flush doors with boiling water proof plywood complete with necessary Hard ware.	1 Sqm	4605
1020	MAT-01609	BMS-W.39	Ventilators:- Ventilators are made of	1	

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			51x51 mm step 'U' section made From 1.25 mm thick C.R. sheet with fixed louvers and glass.	Sqm	5152
1021	MAT-01610	BMS-W.40	Painting:-1) Steel structure is to be painted with 2 coats of Grade I enamel paint.	1 Sqm	137
1022	MAT-01611	BMS-W.41	2) Exterior walls are painted with one coast of primer and 2 coats of exterior emulsion paint .	1 Sqm	123
1023	MAT-01612	BMS-W.42	3) Interiors are painted with 1+2 coat of O.B.D.	1 Sqm	103
1024	MAT-01613	BMS-W.43	Toilets: - Toilets are provided as per plan with a provision for fixing the wash basin, W.C. etc only is made with M.S. steel section secured to the walls with toilet bracket provision excluding cost of WC/ Wash basin etc	Each	1198
1025	MAT-01614	BMS-W.44	Sun shades: - Sun shades will be provided wherever necessary with 300 mm more than the width of window. 25x25 mm angle frame to cover 450 mm in the front and the sides. 10mm cement bonded particle board will be fixed on the frame work and sealed with green paste or equivalent.	Each	4036
1026	MAT-01615	BMS-W.45	Roofing: - Roofing will be provided with 0.5mm thick galvanized / pre painted G.I. profiled sheets fixed to the purlins with 14 size self drilling screws with neoprene washer. Side laps are stitched with self tapping / drilling screws. End laps are to be sealed with 25x3 mm Butyl tape. The sheets are provided with anti capillary groove.	1 Sqm	912
1027	MAT-01617	BMS-W.47	Preparing gabions with jungle wood	Each	4
1028	MAT-01618	BMS-W.48	Planting plants	Each	3
1029	MAT-01619	BMS-W.49	Pruning plants	Each	4
1030	MAT-01620	BMS-W.50	Maintaining avenues including fencing, weeding, mulching, watering etc per plant.	Each	9
1031	MAT-01621	BMS-W.51	- do - When scattered in hot weather with extra conveyance from March to June	Each	10
1032	MAT-01622	BMS-W.52	Hoisting or lowering of slab	1 cum	142
1033	MAT-01623	BMS-W.53	Dressing faces of granite stone (double line dressing)	1 Sqm	233
1034	MAT-01624	BMS-W.54	Dressing faces of other than granite	1	146

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			stone(double line dressing)	Sqm	
1035	MAT-01625	BMS-W.55	Supply of Pre-painted Galvalume Trapezoidal Profile Roofing sheets with 0.50mm thickness, Coating: Alu-Zinc coating AZ150 GSM. Tensile Strength: 550 MPA. Paint coating: Regular Modified Polyester painting. Painting Thickness (Top): 18 to 20 Microns, (Bottom): 5 to 7 Microns. Sheet Width: 1.020, Length: Maximum 12 Meters with Regular Range Colours	1 Sqm	444
1036	MAT-01626	BMS-W.56	Supply of Pre-painted Galvalume Trapezoidal Profile Roofing sheets with 0.47mm thickness, Coating: Alu-Zinc coating AZ150 GSM. Tensile Strength: 550 MPA. Paint coating: Regular Modified Polyester painting. Painting Thickness (Top): 18 to 20 Microns, (Bottom): 5 to 7 Microns. Sheet Width: 1.020, Length: Maximum 12 Meters with Regular Range Colours	1 Sqm	417
1037	MAT-01627	BMS-W.57	Supply of Pre-painted Galvanized Trapezoidal Profile Roofing sheets with 0.50mm thickness, Coating: Zinc coating Z120 GSM. Tensile Strength: 300 MPA. Paint coating: Regular Modified Polyester painting. Painting Thickness (Top): 18 to 20 Microns, (Bottom): 5 to 7 Microns. Sheet Width: 1.020, Length: Maximum 12 Meters with Regular Range Colours	1 Sqm	340
1038	MAT-01628	BMS-W.58	Supply of Pre-painted Galvanized Trapezoidal Profile Roofing sheets with 0.47mm thickness, Coating: Zinc coating Z120 GSM. Tensile Strength: 300 MPA. Paint coating: Regular Modified Polyester painting. Painting Thickness (Top): 18 to 20 Microns, (Bottom): 5 to 7 Microns. Sheet Width: 1.020, Length: Maximum 12 Meters with Regular Range Colours	1 Sqm	340
1039	MAT-01629	BMS-W.59	Supply of Roof Accessories medium size: Ridge, Barge Cap, Corner Trim, L-Flashing, Down Pipes, Gutter etc., with 0.50mm thick, Width: 0.585, Length: Maximum 2½ Meters	1 RM	304
1040	MAT-01630	BMS-W.60	Supply of Roof Accessories medium size: Ridge, Barge Cap, Corner Trim, L-Flashing, Down Pipes, Gutter etc., with 0.47mm thick, Width: 0.585, Length: Maximum 2½ Meters	1 RM	276

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
1041	MAT-01631	BMS-W.61	75 mm long screws -	1 Each	5
1042	MAT-01632	BMS-W.62	G.I scam bolts & nuts	1 Each	7
1043	MAT-01633	BMS-W.63	G.I bolts & nuts	1 Each	7
1044	MAT-01634	BMS-W.64	G.I 'J' bolts 8 mm dia	1 Each	12
1045	MAT-01635	BMS-W.65	G.I Washers	1 Each	3
1046	MAT-01636	BMS-W.66	Limpet washers (for scam & 'J' bolts)	1 Each	3
1047	MAT-01637	BMS-W.67	Bitumen washers	1 Each	3
1048	MAT-01638	BMS-W.68	White Cement	1 Kg	34
1049	MAT-01639	BMS-W.69	MS Z Hold fasts - 300 mm long of 40 x40 x 5 mm ISA	1 Each	43
1050	MAT-01640	BMS-W.70	Rubber/ Nylon door stop bushes	1 Each	12
1051	MAT-01641	BMS-W.71	Nylon rollers for sliding glasses/ alluminium windows	1 Each	19
1052	MAT-01642	BMS-W.72	Powder coating or colour annodization-any section	1 RM	59
1053	MAT-01643	BMS-W.73	Continuous Piano Hinges Powder coated Mild steel as per IS-3818 : 1992 of nominal size 25 mm (B) of thickness 0.8 to 1.0 mm	1 RM	43
1054	MAT-01644	BMS-W.74	Box hinges for cup boards	1 Each	53
1055	MAT-01645	BMS-W.75	Magnetic Catchers	1 Each	19
1056	MAT-01646	BMS-W.76	Drilling holes in hard rock surfaces up to 18mm dia	1 RM	240
1057	MAT-01647	BMS-W.77	Drilling holes in hard rock above 18mmdia	1 RM	334
1058	MAT-01648	BMS-W.78	Making holes up to 18mm dia in RCC/any stones up to 50 mm thick	1 Each	41
1059	MAT-01649	BMS-W.79	Making holes above 18mm dia in RCC/any stones above 50 mm thick	1 Each	57
1060	MAT-01650	BMS-W.80	Pressure grouting the drilled holes with neat cement slurry or with approved epoxy bonding agent using pump	1 Each	58
1061	MAT-01651	BMS-W.81	ITEM DELETED		
1062	MAT-01652	BMS-W.82	ITEM DELETED		

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			CASURINA BALLIES / STEEL BARRICADING		
1063	LAB-00552	BMS-W.83	Fixing steel barricading with MS Angle Iron Pegs and GI Pipes with nuts & bolts duly excavating pits and its removal after the function is over including transporting of the entire barricading materials from the Divisional stores to the barricading site duly engaging labour to load, transport and unload the materials at barricading site & as per the schedule given by the departmental authorities and loading back into the trucks, unloading at Divisional stores, accounting for the received materials, labour for loading, unloading, fixing, handling etc, complete for finished item of work		44
			2-TIER (3 days)	1 RM	
		BMS-W.84	Providing barricading arrangement with casurina ballies as per the design duly excavating pits and its removal after the function is over including hire charges of the barricading materials as per the schedule given by the departmental authorities complete for finished item of work		
1064	LAB-00553	BMS-W.84.A	2-TIER (2 days)	1 RM	55
1065	LAB-00554	BMS-W.84.B	2-TIER (3 days)	1 RM	56
1066	LAB-00555	BMS-W.84.C	2-TIER (4 days)	1 RM	56
1067	LAB-00556	BMS-W.84.D	3-TIER (2 days)	1 RM	58
1068	LAB-00557	BMS-W.84.E	3-TIER (3 days)	1 RM	58
1069	LAB-00558	BMS-W.84.F	3-TIER (4 days)	1 RM	59
			Testing charges		
		BMS-W.85	Coarse Aggregates		
1070	LAB-00559	BMS-W.85.A	Gradation Test	1 No.	657
1071	LAB-00560	BMS-W.85.B.	Aggregate Impact Value Test	1 No.	657
1072	LAB-00561	BMS-W.85.C	Flakiness and Elongation Indices Tests	1 No.	765
1073	LAB-00562	BMS-W.85.D	Water absorption Test	1 No.	603
1074	LAB-00563	BMS-W.85.E	Abrasion Test	1 No.	932
1075	LAB-00564	BMS-W.85.F	Specific Gravity Test	1 No.	657
		BMS-W.86	Fine Aggregates		
1076	LAB-00565	BMS-W.86.A	Sieve Analysis Test	1 No.	657

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
1077	LAB-00566	BMS-W.86.B	Bulking & Moisture content	1 No.	657
1078	LAB-00567	BMS-W.86.C	Specific Gravity Test	1 No.	657
		BMS-W.87	Cement		
1079	LAB-00568	BMS-W.87.A	Fineness of cement Test	Each	657
1080	LAB-00569	BMS-W.87.B	Initial & Final setting time of cement	Each	657
		BMS-W.88	Bricks		
1081	LAB-00570	BMS-W.88.A	Compressive strength of Bricks	Each	383
1082	LAB-00571	BMS-W.88.B	Water absorption Test for Brick	Each	603
		BMS-W.89	Concrete		
1083	LAB-00572	BMS-W.89.A.	Compressive strength of concrete i.e Cube strength test	Each	383
1084	LAB-00573	BMS-W.89.B	Design mix of one grade		17507
1085	LAB-00574	BMS-W.89.C	Design mix of Two grades		28448
1086	LAB-00575	BMS-W.89.D	Design mix of three grades		39389
1087	LAB-00576	BMS-W.89.E	Design mix of four grades		47048
1088	LAB-00577	BMS-W.89.F	Design mix of five grades		55801
			Steel		
1089	LAB-00578	BMS-W.90	Tensile Strength of Each Dia 1 set (3 rods)	Each	765
		BMS-W.91	Soils		
1090	LAB-00579	BMS-W.91.A	G.S.B Mix design	Each	5471
1091	LAB-00580	BMS-W.91.B	W.M.M Mix design	Each	6675
1092	LAB-00581	BMS-W.91.C	B.M Mix design	Each	8209
1093	LAB-00582	BMS-W.91.D	SDBC/BC	Each	8863
1094	LAB-00583	BMS-W.91.E	UD samples	Each	1969
1095	LAB-00584	BMS-W.91.F	Soils MDD and CBR	Each	4047
		Note: Item BMS-W.46 is removed in the section W and is brought as new item in the Section N as BMT-N.82.			
X. SECTION			MACHINERY CHARGES, HIRE CHARGES FOR CENTRING		
1096	MAT-01653	BMC-X.01	Machine charges of rubbing/ polishing floor	1 day	2384
1097	HIR-00206	BMC-X.02	Power Saw Cutter - Hand Operated - Hire charges	1 Hr	144
1098	HIR-00207	BMC-X.03	Power Drill - Hand Operated - Hire Charges	1 Hr	132
1099	MAT-01656	BMC-X.04	Grinding Mortar (Spl Grinding)	1 day	1223
1100	MAT-01657	BMC-X.05	Casuarina Balli Props - 3" to 4" dia - 12'-0" Height	Each	86
1101	MAT-01658	BMC-X.06	Casuarina Balli Props - 4" to 8" dia - 20'-	Each	137

S. No	CFMS code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
			0" Height		
1102	MAT-01659	BMC-X.07	Wall Plate Brackets / beam bottom supports	Each	246
1103	MAT-01660	BMC-X.08	Wedge Plate fixture	Each	14
1104	MAT-01661	BMC-X.09	Runner beams of approximately 4" x 4" size	RM	484
1105	MAT-01662	BMC-X.10	Steel Plates for form works	1 Sqm	1795
1106	MAT-01663	BMC-X.11	Scaffolding Pipes & Centering accessories	1 Kg	140
1107	MAT-01664	BMC-X.12	Scaffold Boards - Bamboo scaffolds - Bamboos - 8'0" long	Each	152
1108	MAT-01665	BMC-X.13	Hire charges for stationary Concrete pump conforming to IS 21573 Part-1: 2006 to deliver the fresh green concrete	1 Hr	393
1109	MAT-01666	BMC-X.14	Concrete delivery pipes conforming to IS 15947 Part I: 2012 to be connected to the pump to delivery point (150 mm Diameter) hire charges per 10 RM	1 Hr	6
		BMC-X.15	Providing rigid steel cup lock scaffolding system using steel pipes, adjustable Jack screw props, RHS spans, couplers, bracings and horizontal connecting members, supporting brackets, RHS span beams as per the approved scaffolding designs & plan and other accessories as per the IS Norms and stability calculations including hire charges for cup lock scaffolding pipes, RHS spans, runners, wooden members and cost and conveyance of all other consumable accessories, taxes etc complete for finished item of work Note: - Centering & scaffolding charges for steel scaffolding with pipes, jack props, centering for unsupported heights of every 610 mm height above 3.66 M may be allowed at 16.666% more than the basic material hire charges and relevant labour charges of the applicable floor and item For SHEAR WALLS, RCC WALLS, WATER TANK WALLS		
			Centering charges for Deck Sheets - 9 Ply - 19 mm thick Plywood conforming to IS:303 BWR Grade ; Unsupported Height up to 3.66 M -		1615

			MS Cup lock System + Marine Grade Plywood shuttering		
			Centering charges with MS Steel Plate - form work : Unsupported Height up to 3.66 M - MS Cup lock System + MS Plate shuttering		1630
			Centering with Aluminum anodized sheets and sections conforming to IS: 11857 – 1986 : Unsupported Height up to 3.66 M - MS Cup lock System + Aluminum Plate shuttering		1953
Y SECTION			POST TENSIONING WORKS		
1110		BMC-Y.01	Supply of Freyssinet type wedge action anchorage cone block, couplers, anchor heads and wedges of cast iron make shot blasting finish complete assembly of size 400 x 300 mm as per IS 1343 : 2012	1 No	2299
1111		BMC-Y.02	Supply of GI corrugated sheathing duct of 0.3mm thick of 90 mm size for installing the tendons for bonded post tensioning work as per IS 1343 : 2012	1 RM	61
1112		BMC-Y.03	Supply of HDPE grout hose with flanges for bonded post tensioning work as per IS 1343 : 2012	1 RM	37
1113		BMC-Y.04	Design and execution of post tensioning work, including supplying, laying of HT tendon strands, decoiling, the strands, cutting to the required lengths, laying of HT strands in sheathing (GI corrugated ducts 0.3mm thick) jointing with couplers and inserting the strands, profiling, fixing live end anchorages, making dead end anchorages, including flowering the strands, fixing tendon support bars, supervising the fixing of antibursting reinforcement, stressing the cables using hydraulic jack, end trimming, grouting the cables, with cement slurry, mixed with admixtures	1 MT	229767
			with required tools, plants, and machineries, and consumables etc., including all leads, lifts, coordination, with the post- tensioning agency, preparation of drawings, obtaining approval from the Engineer-in-Charge with supply of approved grade tendons but excluding the cost of concrete, reinforcement steel, shuttering, anchors, sheathing duct etc.,		

Z SECTION			EXPANSION JOINTS		
			Providing and fixing of expansion joint system related with floor location as per drawings and direction of Engineer-In-Charge. The joints system will be of extruded aluminum base members, self aligning / self centering arrangement and support plates etc. as per ASTM B221-02. The system shall be such that it provides floor to floor / floor to wall expansion control system for various vertical location in load application areas that accommodates multi directional seismic movement without stress to its components. System shall consist of metal profiles with a universal aluminum base member designed to accommodate various project conditions and finish floor treatments. The cover plate shall be designed of width and thickness required to satisfy projects movement and loading requirements and secured to base members by utilizing manufacturer's pre-engineered self-centering arrangement that freely rotates / moves in all directions. The Self – centering arrangement shall exhibit circular sphere ends that lock and slide inside the corresponding aluminum extrusion cavity to allow freedom of movement and flexure in all directions including vertical displacement. Provision of Moisture Barrier Membrane in the Joint System to have watertight joint is mandatory requirement all as per the manufactures design and as approved by Engineer - in- Charge (Material shall confirm to ASTM 6063)		
		BMT-Z.01	Expansion Joint - Floor joint 200mm wide	RM	7896
		BMT-Z.02	Expansion joint- Floor joint 250mm wide	RM	9476
			Providing and fixing of expansion joint system related with wall joint (internal/ external) location as per drawings and direction of Engineer-In- Charge. The joints shall be of extruded aluminum base members, self aligning / centering arrangement and support plates as per ASTM B221- 02. The material shall be such that it provides an Expansion Joints System suitable for vertical wall to wall/ wall to corner application, both new and existing construction in office Buildings & complexes with no slipping down tendency amongst the components of the Joint System. The Joint System shall utilize light weight aluminum profiles exhibiting minimal exposed aluminum surfaces mechanically snap locking the multi		

			cellular to facilitate movement. (Material shall confirm to ASTM 6063)		
		BMT-Z.03	Expansion joint- wall joint 200mm wide	RM	3777
		BMT-Z.04	Expansion joint- wall joint 250mm wide	RM	5294
			Providing and fixing of expansion joint system of approved make and manufactures for various roof locations as per approved drawings and direction of Engineer-In-Charge. The joints shall be of extruded aluminum base members with, self aligning and self centering arrangement support plates as per ASTM B221-02. The system shall be such that it provides watertight roof to roof/roof to corner joint cover expansion control system that is capable of accommodating multidirectional seismic movement without stress to its components. System shall consist of metal profile that incorporates a universal aluminum base member designed to accommodate various project conditions and roof treatments. The cover plate shall be designed of width and thickness required to satisfy movement and loading requirements and secured to base members by utilizing manufacturer's pre-engineered self-centering arrangement that freely rotates / moves in all directions. The Self centering arrangement shall exhibit circular sphere ends that lock and slide inside the corresponding aluminum extrusion cavity to allow freedom of movement and flexure in all directions including vertical displacement. The Joint System shall resists damage or deterioration from the impact of falling ice, exposure to UV, airborne contaminants and occasional foot traffic from maintenance personnel. Provision of Moisture Barrier Membrane in the Joint System to have water tight joint is mandatory requirement. Material shall confirm to ASTM 6063.		
		BMT-Z.05	Expansion joint- Roof joint 200mm wide	RM	5861
		BMT-Z.06	Expansion joint- Roof joint 250mm wide	RM	7377
AA SECTION			ENERGY EFFICIENT ITEMS		
SUB-SECTION -IX			External wall insulation with Polyurethane foam (PUF) slab		
		BMT-ZA.01	Providing and fixing polyurethane foam (PUF) slab 40mm thick average with PU slab density 36+/-2 kg/m³ for external wall insulation including necessary polymerized plaster reinforced with glass fibre mesh,	1sqm	1283

			epoxy based bonding adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete		
SUB-SECTION -X			External wall insulation with Polyurethane foam (PUF) spray		
		BMT-ZA.02	Providing and fixing cast in situ polyurethane foam (PUF) spray of 40mm / 50mm thick with PU foam spray density 35+/-5 kg/m ³ for external wall insulation including necessary adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM of machinery etc., complete	1sqm	1317
SUB-SECTION -XI			External wall insulation with Extruded Polystyrene (XPS) thermal insulation board		
		BMT-ZA.03	Providing and fixing Extruded Polystyrene (XPS) thermal insulating boards of 25mm thick for external wall insulation including necessary fasteners etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM of machinery etc., complete	1sqm	514
		BMT-ZA.04	Providing and fixing Extruded Polystyrene (XPS) thermal insulating boards of 50mm thick for external wall insulation including necessary fasteners etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM of machinery etc., complete	1sqm	816
		BMT-ZA.05	Providing and fixing Extruded Polystyrene (XPS) thermal insulating boards of 75mm thick for external wall insulation including necessary fasteners etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM of machinery etc., complete	1sqm	1157
		BMT-ZA.06	Providing and fixing Extruded Polystyrene (XPS) thermal insulating boards of 100mm thick for external wall insulation including necessary fasteners etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM of machinery etc., complete	1sqm	1499
SUB-SECTION -XII			Cavity wall insulation with Glass Wool Slab		
		BMT-ZA.07	Providing and fixing polyurethane foam (PUF) spray with PU foam spray of 40mm thick having density 35+/-5 kg/cum density for insulation of cavity wall with including necessary fasteners etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	643

		BMT-ZA.08	Providing and fixing polyurethane foam (PUF) spray with PU foam spray of 50mm thick having density 35+/-5 kg/cum density for insulation of cavity wall with including necessary fasteners etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	944
SUB-SECTION -XIII			Cavity wall with Glass Wool Slab		
		BMT-ZA.09	Providing and fixing glass wool slab of 12mm thick - resin bonded with density 48kg/ cum for insulation of cavity wall, fixed using GI wire 200 SWG, GI chicken mesh 12.50mm x 24 SWG including necessary criss-cross GI wire mesh,raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	532
			Providing and fixing glass wool slab of 25mm thick - resin bonded with density 48kg/ cum for insulation of cavity wall, fixed using GI wire 200 SWG, GI chicken mesh 12.50mm x 24 SWG including necessary criss-cross GI wire mesh,raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	675
			Providing and fixing glass wool slab of 50mm thick - resin bonded with density 48kg/ cum for insulation of cavity wall, fixed using GI wire 200 SWG, GI chicken mesh 12.50mm x 24 SWG including necessary criss-cross GI wire mesh,raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	797
SUB-SECTION -XIII			Cavity wall with Rock Wool Slab		
		BMT-ZA.10	Providing and fixing rock wool slab - resin bonded rock wool slab of 25mm thick having density 36+/-5 kg/cum for insulation of cavity wall with including necessary criss-cross GI wire, mesh,raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	444
			Providing and fixing rock wool slab - resin bonded rock wool slab of 40mm thick having density 36+/-5 kg/cum for insulation of cavity wall with including necessary criss-cross GI wire, mesh,raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	476

			Providing and fixing rock wool slab - resin bonded rock wool slab of 50mm thick having density 36+/-5 kg/cum for insulation of cavity wall with including necessary criss-cross GI wire, mesh,raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	496
			Providing and fixing rock wool slab - resin bonded rock wool slab of 65mm thick having density 36+/-5 kg/cum for insulation of cavity wall with including necessary criss-cross GI wire, mesh,raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	530
			Providing and fixing rock wool slab - resin bonded rock wool slab of 75mm thick having density 36+/-5 kg/cum for insulation of cavity wall with including necessary criss-cross GI wire, mesh,raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	551
			Providing and fixing rock wool slab - resin bonded rock wool slab of 100mm thick having density 36+/-5 kg/cum for insulation of cavity wall with including necessary criss-cross GI wire, mesh,raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	787
SUB-SECTION -XIV			Cavity wall insulation with Extruded Polystyrene (XPS)		
		BMT-ZA.11	Providing and fixing extruded polystyrene (XPS) 50mm thick thermal insulating boards having density 36+/-5 kg/cum for insulation of cavity wall including necessary criss-cross GI wire, mesh,raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	1041
			Providing and fixing extruded polystyrene (XPS) 60 mm thick thermal insulating boards having density 36+/-5 kg/cum for insulation of cavity wall including necessary criss-cross GI wire, mesh,raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete	1sqm	1062
			Providing and fixing extruded polystyrene (XPS) 70mm thick thermal insulating boards having density 36+/-5 kg/cum for insulation of cavity wall including necessary criss-cross GI wire, mesh,raw plugs, adhesive etc., complete with all lead and lift,	1sqm	1386

			transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM etc., complete		
		BMT-ZA.12	Providing and fixing extruded polystyrene (XPS) 25mm thick thermal insulating boards having density 32 kg/cum for insulation of cavity wall including necessary criss-cross GI wire, mesh, raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM complete.	1sqm	716
			Providing and fixing extruded polystyrene (XPS) 50mm thick thermal insulating boards having density 32 kg/cum for insulation of cavity wall including necessary criss-cross GI wire, mesh, raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM complete.	1sqm	1041
			Providing and fixing extruded polystyrene (XPS) 75mm thick thermal insulating boards having density 32 kg/cum for insulation of cavity wall including necessary criss-cross GI wire, mesh, raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM complete.	1sqm	1410
			Providing and fixing extruded polystyrene (XPS) 100mm thick thermal insulating boards having density 32 kg/cum for insulation of cavity wall including necessary criss-cross GI wire, mesh, raw plugs, adhesive etc., complete with all lead and lift, transportation charges, loading unloading charges, all taxes, cost of all materials, labour, HOM complete.	1sqm	1777
SUB-SECTION -XVII			Over deck insulation with polyurethane foam (PUF) slab		
		BMT-ZA.13	40 mm thick with PU slab density 36+/-2 kg/m ³ insulation for over	1sqm	365
		BMT-ZA.14	50 mm thick with PU slab density 36+/-2 kg/m ³ insulation for over	1sqm	604
		BMT-ZA.15	60 mm thick with PU slab density 36+/-2 kg/m ³ insulation for over	1sqm	859
		BMT-ZA.16	70 mm thick with PU slab density 36+/-2 kg/m ³ insulation for over	1sqm	1109
SUB-SECTION -XVIII			Over deck insulation with polyurethane foam (PUF) spray		
		BMT-ZA.17	40mm thick with PU foam spray	1sqm	626
		BMT-ZA.19	60mm thick with PU foam spray	1sqm	1361
		BMT-ZA.20	70mm thick with PU foam spray	1sqm	1701

SUB-SECTION -XIX			Over deck thermal insulation of roof with expanded Polystyrene (EPS)		
		BMT-ZA.21	Expanded polystyrene (EPS) 50mm thick	1sqm	591
		BMT-ZA.22	Expanded polystyrene (EPS) 70mm thick	1sqm	696
		BMT-ZA.23	Expanded polystyrene (EPS) 90mm thick	1sqm	769
		BMT-ZA.24	Expanded polystyrene (EPS) 110mm thick	1sqm	874
		BMT-ZA.25	Expanded polystyrene (EPS) 120mm thick	1sqm	928
SUB-SECTION -XX			Over deck with glass wool slab		
		BMT-ZA.26	Resin bonded glass wool slab 12 mm thick having density 48kgs/ m ³	1sqm	981
		BMT-ZA.27	Resin bonded glass wool slab 25 mm thick having density 48kgs/ m ³	1sqm	1123
		BMT-ZA.28	Resin bonded glass wool slab 50 mm thick having density 48kgs/ m ³	1sqm	1246
SUB-SECTION -XXI			Over deck insulation with rock wool slab		
		BMT-ZA.28	25mm resin bonded rock wool slab having density 48kgs/ m ³	1sqm	634
		BMT-ZA.29	40mm resin bonded rock wool slab having density 48kgs/ m ³	1sqm	664
		BMT-ZA.30	50mm resin bonded rock wool slab having density 48kgs/ m ³	1sqm	682
		BMT-ZA.31	65mm resin bonded rock wool slab having density 48kgs/ m ³	1sqm	711
		BMT-ZA.32	75mm resin bonded rock wool slab having density 48kgs/ m ³	1sqm	736
		BMT-ZA.33	100mm resin bonded rock wool slab having density 48kgs/ m ³	1sqm	792
SECTION AB			PEB STRUCTURES		
		BMT-ZB.01	Pre Engineered Building (PEB): Secondary members which includes Purlins, Girts, Edge Angle, etc. Members formed from Galvanized Coils of 275 GSM and will conform to the physical specifications of ASTM A572/ A572M (Grade 50) or equivalent and shall have a minimum yield strength of 345 MPA	1MT	81667
		BMT-ZB.02	Galvanized Roofing Deck sheets with 1mm thickness, Coating: Zinc coating Z125 / Z275/ Z 500 GSM. Yield Strength: E250. crest to crest width 130 mm length 12 meters : profile width 982mm and profile depth 44mm	1KG	135

			CR steel as per IS-513 HR steel as per IS 1079 and Galvanized Steel as per IS 277		
		BMT-ZB.03	Labor charges for fixing Galvanized Roofing Deck sheets to structural beams and columns for laying RCC slab	1KG	6
		BMT-ZB.04	High Strength friction grip bolts of 8.8 Grade with electroplated & yellow passivation for PEB structure.	1KG	118
		BMT-ZB.05	Cost of Electroplating	1KG	20
		BMT-ZB.06	Cutting Cores in 125 mm thick RCC Slabs 75 mm dia.	Each	236
		BMT-ZB.07	Cutting Cores in 125 mm thick RCC Slabs 100 mm dia	Each	288
		BMT-ZB.08	Cutting Cores in 125 mm thick RCC Slabs 150 mm dia.	Each	367
		BMT-ZB.09	Labor charges for cutting & fixing Thermocol & Cement Bonded Board for Wrapping around PEB columns	1sqm	105

- 1 All the items to be used on the works shall be of first quality & ISI marked wherever possible and as approved, workmanship shall be as approved by the Engineer-In-charge of the work.
- 2 Supply Rates for all the materials are based on market rates excluding GST.
- 3 SSR Rates for Building items are purely for the guidance of the officers in preparation of estimates vide para.113 of APPWD code. Authority who prepares the estimate is however responsible for proper rates as envisaged in para.45 of APPWD code.

LEGEND:

"BMT" -X.XX,

"BMM"-X.XX,

"BMS"-X.XX,

"BMC"-X.XX

xxx- "A".XX - Denotes the Section

XXX-X."01" - Denotes the Serial Number of the Item in the corresponding Section

SI	NAME OF THE STRUCTURAL MEMBER	Material Hire charges	Labour charges	Centring Charges for 2019-20	Unit of Measurement
1	2	3	4	5	6
HIRE CHARGES FOR CENTERING AND SCAFFOLDING					
A	FOOTINGS	Rs. 301	Rs. 672	Rs. 973	per 1 cum
B	BED BLOCKS, BANDS	Rs. 67	Rs. 363	Rs. 430	per 1 cum
C	PEDESTALS	Rs. 343	Rs. 1069	Rs. 1412	per 1 cum
D	PLINTH BEAMS	Rs. 1453	Rs. 1620	Rs. 3073	per 1 cum
HIRE CHARGES FOR CENTERING & SCAFFOLDING - Unsupported Height upto 3.66 M Steel scaffolding pipes, jack Props, wallers, Foot plates, brackets, steel Centering Plates, etc.,					
E	LINTELS	Rs. 1233	Rs. 1720	Rs. 2953	per 1 cum
F	CHAJJAS - SUNSHADES	Rs. 243	Rs. 264	Rs. 507	per 1 sqm
G	COLUMNS	Rs. 371	Rs. 2415	Rs. 2786	per 1 cum
H	BEAMS	Rs. 2179	Rs. 2027	Rs. 4206	per 1 cum
I	SLABS - Up to 150 mm thick	Rs. 247	Rs. 241	Rs. 488	per 1 sqm
J	SLABS - above 150 mm - Up to 300 mm thick	Rs. 254	Rs. 248	Rs. 502	per 1 sqm
K	SLABS - above 300 mm thick	Rs. 265	Rs. 260	Rs. 525	per 1 sqm
L	WAFFLE - (GRID) SLABS (Rib Beams with Slabs)	Rs. 897	Rs. 834	Rs. 1731	per 1 sqm
M	PERGOLA SLABS (Only Rib Beams)	Rs. 629	Rs. 585	Rs. 1214	per 1 sqm
N	ARCH BEAMS - up to 1.5 M Span	Rs. 2477	Rs. 2304	Rs. 4781	per 1 cum
O	ARCH BEAMS - above 1.5 M Span	Rs. 2512	Rs. 2336	Rs. 4848	per 1 cum
P	DOME SLABS	Rs. 4005	Rs. 3723	Rs. 7728	per 1 cum
Q	HELICAL STAIRCASES	Rs. 305	Rs. 284	Rs. 589	per 1 sqm
Q	SHEAR WALLS, RCC WALLS, WATER TANK WALLS	Rs. 472	Rs. 510	Rs. 982	per 1 sqm

HIRE CHARGES FOR CENTERING & SCAFFOLDING - Unsupported Height upto 3.66 M Casurina Ballies, Bamboos, Wooden Reapers, Runners, Wood Posts, Wall Plates etc.,					
E	LINTELS	Rs. 826	Rs. 1332	Rs. 2158	per 1 cum
F	CHAJJAS - SUNSHADES	Rs. 163	Rs. 204	Rs. 367	per 1 sqm
G	COLUMNS	Rs. 249	Rs. 1871	Rs. 2120	per 1 cum
H	BEAMS	Rs. 1458	Rs. 1569	Rs. 3027	per 1 cum
I	SLABS - Up to 150 mm thick	Rs. 165	Rs. 186	Rs. 351	per 1 sqm
J	SLABS - above 150 mm - Up to 300 mm thick	Rs. 170	Rs. 193	Rs. 363	per 1 sqm
K	SLABS - above 300 mm thick	Rs. 178	Rs. 201	Rs. 379	per 1 sqm
L	WAFFLE - (GRID) SLABS (Rib Beams with Slabs)	Rs. 601	Rs. 646	Rs. 1247	per 1 sqm
M	PERGOLA SLABS (Only Rib Beams)	Rs. 421	Rs. 453	Rs. 874	per 1 sqm
N	ARCH BEAMS - up to 1.5 M Span	Rs. 1657	Rs. 1784	Rs. 3441	per 1 cum
O	ARCH BEAMS - above 1.5 M Span	Rs. 1681	Rs. 1808	Rs. 3489	per 1 cum
P	DOME SLABS	Rs. 2681	Rs. 2884	Rs. 5565	per 1 cum
Q	HELICAL STAIRCASES	Rs. 205	Rs. 220	Rs. 425	per 1 sqm

SI	NAME OF THE STRUCTURAL MEMBER	Material Hire charges	Labour charges	Centring Charges for 2018-19	Unit of Measurement
1	2	3	4	5	6
HIRE CHARGES FOR ACCESS SCAFFOLDING - upto 3.66 M using Casurina Ballies, Bamboos, Wooden Reapers, Runners, Wood Posts, Wall Plates etc., for BRICK MASONRY/ STONE MASONRY - 1 sqm (Wall Area)					
A	1st - Floor	Rs. 10.78	Rs. 84.62	Rs. 95.40	per 1 sqm
B	2nd - Floor	Rs. 10.78	Rs. 121.18	Rs. 131.96	per 1 sqm
C	3rd - Floor	Rs. 10.78	Rs. 157.72	Rs. 168.50	per 1 sqm
D	4th - Floor	Rs. 10.78	Rs. 194.27	Rs. 205.05	per 1 sqm
E	5th - Floor	Rs. 10.78	Rs. 230.81	Rs. 241.59	per 1 sqm
F	6th - Floor	Rs. 10.78	Rs. 267.35	Rs. 278.13	per 1 sqm
G	7th - Floor	Rs. 10.78	Rs. 303.88	Rs. 314.66	per 1 sqm
H	8th - Floor	Rs. 10.78	Rs. 340.43	Rs. 351.21	per 1 sqm
I	9th - Floor	Rs. 10.78	Rs. 376.98	Rs. 387.76	per 1 sqm
J	10th - Floor	Rs. 10.78	Rs. 413.51	Rs. 424.29	per 1 sqm
K	11th - Floor	Rs. 10.78	Rs. 450.06	Rs. 460.84	per 1 sqm
L	12th - Floor	Rs. 10.78	Rs. 486.61	Rs. 497.39	per 1 sqm

M	13th - Floor	Rs.	10.78	Rs.	523.15	Rs.	533.93	per 1 sqm
N	14th - Floor	Rs.	10.78	Rs.	559.68	Rs.	570.46	per 1 sqm
O	15th - Floor	Rs.	10.78	Rs.	596.23	Rs.	607.01	per 1 sqm

HIRE CHARGES FOR ACCESS SCAFFOLDING - upto 3.66 M using Casurina Ballies, Bamboos, Wooden Reapers, Runners, Wood Posts, Wall Plates etc., for PLASTERING to WALLS - 1 sqm

SI	NAME OF THE STRUCTURAL MEMBER	Material Hire charges	Labour charges	Centring Charges for 2018-19	Unit of Measurement
1	2	3	4	5	6

A	1st - Floor	Rs.	1.08	Rs.	8.47	Rs.	9.55	per 1 sqm
B	2nd - Floor	Rs.	1.08	Rs.	12.12	Rs.	13.20	per 1 sqm
C	3rd - Floor	Rs.	1.08	Rs.	15.77	Rs.	16.85	per 1 sqm
D	4th - Floor	Rs.	1.08	Rs.	19.43	Rs.	20.51	per 1 sqm
E	5th - Floor	Rs.	1.08	Rs.	23.08	Rs.	24.16	per 1 sqm
F	6th - Floor	Rs.	1.08	Rs.	26.73	Rs.	27.81	per 1 sqm
G	7th - Floor	Rs.	1.08	Rs.	30.38	Rs.	31.46	per 1 sqm
H	8th - Floor	Rs.	1.08	Rs.	34.05	Rs.	35.13	per 1 sqm
I	9th - Floor	Rs.	1.08	Rs.	37.70	Rs.	38.78	per 1 sqm
J	10th - Floor	Rs.	1.08	Rs.	41.35	Rs.	42.43	per 1 sqm
K	11th - Floor	Rs.	1.08	Rs.	45.01	Rs.	46.09	per 1 sqm
L	12th - Floor	Rs.	1.08	Rs.	48.66	Rs.	49.74	per 1 sqm
M	13th - Floor	Rs.	1.08	Rs.	52.31	Rs.	53.39	per 1 sqm
N	14th - Floor	Rs.	1.08	Rs.	55.97	Rs.	57.05	per 1 sqm
O	15th - Floor	Rs.	1.08	Rs.	59.62	Rs.	60.70	per 1 sqm

HIRE CHARGES FOR STAGE SCAFFOLDING - upto 3.66 M using Casurina Ballies, Bamboos, Wooden Reapers,Runners, Wood Posts, Wall Plates etc., for CEILING PLASTERING - 1 sqm								
A	1st - Floor	Rs.	2.57	Rs.	16.94	Rs.	19.51	per 1 sqm
B	2nd - Floor	Rs.	2.57	Rs.	24.04	Rs.	26.61	per 1 sqm
C	3rd - Floor	Rs.	2.57	Rs.	31.13	Rs.	33.70	per 1 sqm
D	4th - Floor	Rs.	2.57	Rs.	38.23	Rs.	40.80	per 1 sqm
E	5th - Floor	Rs.	2.57	Rs.	45.33	Rs.	47.90	per 1 sqm
F	6th - Floor	Rs.	2.57	Rs.	52.42	Rs.	54.99	per 1 sqm
G	7th - Floor	Rs.	2.57	Rs.	59.52	Rs.	62.09	per 1 sqm
H	8th - Floor	Rs.	2.57	Rs.	66.62	Rs.	69.19	per 1 sqm
I	9th - Floor	Rs.	2.57	Rs.	73.72	Rs.	76.29	per 1 sqm
J	10th - Floor	Rs.	2.57	Rs.	80.81	Rs.	83.38	per 1 sqm
K	11th - Floor	Rs.	2.57	Rs.	87.91	Rs.	90.48	per 1 sqm
L	12th - Floor	Rs.	2.57	Rs.	95.01	Rs.	97.58	per 1 sqm
M	13th - Floor	Rs.	2.57	Rs.	102.03	Rs.	104.60	per 1 sqm
N	14th - Floor	Rs.	2.57	Rs.	109.19	Rs.	111.76	per 1 sqm
O	15th - Floor	Rs.	2.57	Rs.	116.30	Rs.	118.87	per 1 sqm

CENTERING & SCAFFOLDING CHARGES- FLOOR WISE RATES for Steel scaffolding pipes, jack Props, Steel Centering Plates,etc., for unsupported height 3.66M																
FLOOR		LINTELS	CHAJJAS - SUNSHADES	COLUMNS	BEAMS	SLABS - Up to 150 mm thick	SLABS - above 150 mm - Up to 300 mm thick	SLABS - above 300 mm thick	WAFFLE - (GRID) SLABS (Rib Beams with Slabs)	PERGOLA SLAB (Only Rib Beams)		ARCH BEAMS - up to 1.5 M Span	ARCH BEAMS - above 1.5 M Span	DOME SLABS	HELICAL STAIRCASES	SHEAR WALLS, RCC WALLS, WATER TANK WALLS
Material Hire for any Floor	H	1233	243	371	2179	247	254	265	897	629		2477	2512	4005	305	472
Labour Charges for 1st Floor	L	1720	264	2415	2027	241	248	260	834	585		2304	2336	3723	284	510
Total Hire Charges (H+L)	T	2953	507	2786	4206	488	502	525	1731	1214		4781	4848	7728	589	982
1st - Floor	L	1720	264	2415	2027	241	248	260	834	585		2304	2336	3723	284	510
2nd - Floor	L	1892	290	2657	2230	265	273	286	917	644		2534	2570	4095	312	561
3rd - Floor	L	2064	317	2898	2432	289	298	312	1001	702		2765	2803	4468	341	612
4th - Floor	L	2236	343	3140	2635	313	322	338	1084	761		2995	3037	4840	369	663
5th - Floor	L	2408	370	3381	2838	337	347	364	1168	819		3226	3270	5212	398	714
6th - Floor	L	2580	396	3623	3041	362	372	390	1251	878		3456	3504	5585	426	765
7th - Floor	L	2752	422	3864	3243	386	397	416	1334	936		3686	3738	5957	454	816
8th - Floor	L	2924	449	4106	3446	410	422	442	1418	995		3917	3971	6329	483	867
9th - Floor	L	3096	475	4347	3649	434	446	468	1501	1053		4147	4205	6701	511	918
10th -Floor	L	3268	502	4589	3851	458	471	494	1585	1112		4378	4438	7074	540	969
11th -Floor	L	3440	528	4830	4054	482	496	520	1668	1170		4608	4672	7446	568	1020
12th -Floor	L	3612	554	5072	4257	506	521	546	1751	1229		4838	4906	7818	596	1071
13th -Floor	L	3784	581	5313	4459	530	546	572	1835	1287		5069	5139	8191	625	1122
14th -Floor	L	3956	607	5555	4662	554	570	598	1918	1346		5299	5373	8563	653	1173
15th -Floor	L	4128	634	5796	4865	578	595	624	2002	1404		5530	5606	8935	682	1224
Note: - Centering & scaffolding charges for steel scaffolding with pipes, jack props, steel centring plates for unsupported heights of every 610 mm height above 3.66 M, may be allowed at 16.666% more than the basic material hire charges and relevant labour charges of the applicable floor and item																

CENTERING & SCAFFOLDING CHARGES- FLOOR WISE RATES for Casurina Ballies, Bamboos, Wooden Reapers, Runners, Wood Posts, Wall Plates, Steel Centring Plates etc., for unsupported height 3.66 M														
FLOOR		LINTELS	CHAJJAS - SUNSHADES	COLUMNS	BEAMS	SLABS - Up to 150 mm thick	SLABS - above 150 mm - Up to 300 mm thick	SLABS - above 300 mm thick	WAFFLE - (GRID) SLABS (Rib Beam with Slabs)	PERGOLA SLABS (Only Rib Beams)	ARCH BEAMS - up to 1.5M Span	ARCH BEAMS - above 1.5 M Span	DOME SLABS	HELICAL STAIRCASES
Material Hire for any Floor	H	826	163	249	1458	165	170	178	601	421	1657	1681	2681	501
Labour Charges for 1st Floor	L	1332	204	1871	1569	186	193	201	646	453	1784	1808	2884	220
Total Hire Charges (H+L)	T	2158	367	2120	3027	351	363	379	1247	874	3441	3489	5565	721
1st - Floor	L	1332	204	1871	1569	186	193	201	646	453	1784	1808	2884	220
2nd - Floor	L	1465	224	2058	1726	205	212	221	711	498	1962	1989	3172	242
3rd - Floor	L	1598	245	2245	1883	223	232	241	775	544	2141	2170	3461	264
4th - Floor	L	1732	265	2432	2040	242	251	261	840	589	2319	2350	3749	286
5th - Floor	L	1865	286	2619	2197	260	270	281	904	634	2498	2531	4038	308
6th - Floor	L	1998	306	2807	2354	279	290	302	969	680	2676	2712	4326	330
7th - Floor	L	2131	326	2994	2510	298	309	322	1034	725	2854	2893	4614	352
8th - Floor	L	2264	347	3181	2667	316	328	342	1098	770	3033	3074	4903	374
9th - Floor	L	2398	367	3368	2824	335	347	362	1163	815	3211	3254	5191	396
10th - Floor	L	2531	388	3555	2981	353	367	382	1227	861	3390	3435	5480	418
11th - Floor	L	2664	408	3742	3138	372	386	402	1292	906	3568	3616	5768	440
12th - Floor	L	2797	428	3929	3295	391	405	422	1357	951	3746	3797	6056	462
13th - Floor	L	2930	449	4116	3452	409	425	442	1421	997	3925	3978	6345	484
14th - Floor	L	3064	469	4303	3609	428	444	462	1486	1042	4103	4158	6633	506
15th - Floor	L	3197	490	4490	3766	446	463	482	1550	1087	4282	4339	6922	528

Note:-

- 1) All Materials conforming to ISI or relevant International Standards shall be used in all CIVIL, Water Supply & Sanitary Fittings, Electrical and Electro-Mechanical Works.
- 2) Concerned departments shall approve the materials either from the manufacturer or from its authorized /certified dealer only and also to approve the brands of the products / materials to be adopted in their estimates at their end. In case common approval is required by the committee, concerned authority shall propose with all the details after thorough verification, to the committee for considering the proposal.
- 3) SoR rates for Civil and Water supply & Sanitary items are purely for guidance of the officers in preparation of estimates vide para 113 of APPWD Code. Authority who prepares the estimate is, however responsible for proper rates as envisaged in Para 45 of APPWD Code.
- 4) The rates published in the Buildings SoR 2025-26 are the ceiling rates only and the estimate preparing authorities are responsible for the correctness and reasonableness of the rates and technical specifications adopted in the estimates.

WATER SUPPLY & SANITARY ITEMS

WATER SUPPLY & SANITARY ITEMS

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
1		2	3	4	5
A			S.W.G. PIPES & FITTINGS		
1	MAT-01667	BMW-A.01	Supplying, laying, jointing and testing 101.6 mm SWG SP-1 pipes of ISI make conforming to ISI 651 & 4127 with airtight cement joints in CM 1.5:1 prop. Including excavation of trenches and socket pits in any soil (except rock requiring blasting) up to 1524 mm(5'0") depth and refilling with watering and tamping.	1 RM	423
2	MAT-01668	BMW-A.02	Supplying, laying, jointing and testing 101.6 mm SWG SP-1 pipes of ISI make conforming to ISI 651 & 4127 with airtight cement joints in CM 1:5:1 prop. including excavation of trenches and socket pits in any soil (except rock requiring blasting) up to 914.4 mm (3'0") depth and refilling with watering and tamping.	1 RM	421
3	MAT-01669	BMW-A.03	Supplying, laying, jointing and testing 152.4 mm SWG SP-1 pipes of ISI make conforming to ISI 651 & 4127 with airtight cement joints in CM 1.5:1 prop. including excavation of trenches and socket pits in any soil (except rock requiring blasting) up to 1524 mm(5'0") depth and refilling with watering and tamping.	1 RM	625
4	MAT-01670	BMW-A.04	Supplying, laying, jointing and testing 152.4 mm SWG SP-1 pipes of ISI make conforming to ISI 651 & 4127 with airtight cement joints in CM 1.5:1 prop. including excavation of trenches and socket pits in any soil (except rock requiring blasting) up to 914.4 mm (3'0")) depth and refilling with watering and tamping.	1 RM	614
5	LAB-00411	BMW-A.05	labour charges only for laying, jointing and testing SWG pipes of any dia with airtight cement joints including excavation of trenches and socket pits in any soil up to 914.4 mm (3'0") depth (except rock requiring blasting) and refilling with watering and tamping.	1 RM	279
6	LAB-00412	BMW-A.06	labour charges only for laying, jointing and testing SWG pipes of any dia with airtight cement joints including excavation of trenches and socket pits in any soil up to 1524 mm (5'-0") depth (except rock requiring blasting) and refilling with watering and tamping.	1 RM	345
7	MAT-01671	BMW-A.07	a)Supplying, laying, jointing and testing 152.4 mmCC bed 1:2:4 Prop: using 19.05mm gauge graded granite metal chips and cradling 101.6 mm SWG pipe line all round to have 76.2 mm thick cover over the sockets.	1 RM	229
8	LAB-00413	BMW-A.08	b) - do - labour charges only	1 RM	13
9	MAT-01672	BMW-A.09	a)Supplying , laying, jointing and testing 152.4 mmCC bed 1:2:4 Prop: using 19.05mm gauge graded granite metal chips and cradling 152.4 mm SWG pipe line all round to have 76.2 mm thick cover over the sockets.	1 RM	318
10	LAB-00414	BMW-A.10	b) - do - labour charges only	1 RM	62
11	MAT-01673	BMW-A.11	a) Supplying & Laying 101.6 mm SWG channels with cement mortar joints with suitable brick masonry for fixing the channels in position	1 RM	89

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
12	LAB-00150	BMW-A.12	b) - do - labour charges only	1 RM	45
13	MAT-01674	BMW-A.13	a) Supplying & Laying 152.4 mm SWG channels with cement mortar joints with suitable brick masonry for fixing the channels in position	1 RM	164
14	LAB-00151	BMW-A.14	b) - do - labour charges only	1 RM	65
15	MAT-01675	BMW-A.15	Supply of SWG SP-1 Pipe conforming to ISI 651- 4" dia (101.6mm)	1 RM	169
16	MAT-01676	BMW-A.16	Supply of SWG SP-1 Pipe conforming to ISI 651- 6" dia (152.4mm)	1 RM	294
17	MAT-01677	BMW-A.17	Supply of SWG SP-1 Pipe conforming to ISI 651-8" dia (203.2mm)	1 RM	452
18	MAT-01678	BMW-A.18	Supply of SWG SP-1 Pipe conforming to ISI 651- 10" dia (254 mm)	1 RM	828
19	MAT-01679	BMW-A.19	Supply of SWG SP-1 Pipe conforming to ISI 651- 12" dia (300 mm)	1 RM	1193
20	MAT-01680	BMW-A.20	Supply of SWG SP-1 Pipe conforming to ISI 651- 14" dia (350 mm)	1 RM	1624
21	MAT-01681	BMW-A.21	Supply of SWG SP-1 Pipe conforming to ISI 651- 16" dia (400 mm)	1 RM	1957
22	MAT-01682	BMW-A.22	Supply of SWG SP-1 Pipe conforming to ISI 651- 18" dia (450 mm)	1 RM	2363
23	MAT-01683	BMW-A.23	Supply of SWG SP-2 Pipe conforming to ISI 651- 4" dia (101.6mm)	1 RM	209
24	MAT-01684	BMW-A.24	Supply of SWG SP-2 Pipe conforming to ISI 651- 6" dia (152.4mm)	1 RM	310
25	MAT-01685	BMW-A.25	Supply of SWG SP-2 Pipe conforming to ISI 651-8" dia (203.2mm)	1 RM	558
26	MAT-01686	BMW-A.26	Supply of SWG SP-2 Pipe conforming to ISI 651- 10" dia (254 mm)	1 RM	877
27	MAT-01687	BMW-A.27	Supply of SWG SP-2 Pipe conforming to ISI 651- 12" dia (300 mm)	1 RM	1348
28	MAT-01688	BMW-A.28	Supply of SWG SP-2 Pipe conforming to ISI 651- 14" dia (350 mm)	1 RM	1747
29	MAT-01689	BMW-A.29	Supply of SWG SP-2 Pipe conforming to ISI 651- 16" dia (400 mm)	1 RM	2012
30	MAT-01690	BMW-A.30	Supply of SWG SP-2 Pipe conforming to ISI 651- 18" dia (450 mm)	1 RM	2568
31	MAT-01691	BMW-A.31	Supply of SWG SP-3 Pipe conforming to ISI 651- 4" dia (101.6mm)	1 RM	267
32	MAT-01692	BMW-A.32	Supply of SWG SP-3 Pipe conforming to ISI 651- 6" dia (152.4mm)	1 RM	387
33	MAT-01693	BMW-A.33	Supply of SWG SP-3 Pipe conforming to ISI 651-8" dia (203.2mm)	1 RM	684
34	MAT-01694	BMW-A.34	Supply of SWG SP-3 Pipe conforming to ISI 651- 10" dia (254 mm)	1 RM	1040

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
35	MAT-01695	BMW-A.35	Supply of SWG SP-3 Pipe conforming to ISI 651- 12" dia (300 mm)	1 RM	1453
36	MAT-01696	BMW-A.36	Supply of SWG SP-3 Pipe conforming to ISI 651- 14" dia (350 mm)	1 RM	1844
37	MAT-01697	BMW-A.37	Supply of SWG SP-2 Pipe conforming to ISI 651- 16" dia (400 mm)	1 RM	2122
38	MAT-01698	BMW-A.38	Supply of SWG SP-3 Pipe conforming to ISI 651- 18" dia (450 mm)	1 RM	2887
39	MAT-01699	BMW-A.39	Supply of SWG Bends conforming to IS standards -100 mm dia	Each	85
40	MAT-01700	BMW-A.40	Supply of SWG Bends conforming to IS standards -150 mm dia	Each	157
41	MAT-01701	BMW-A.41	Supply of SWG Bends conforming to IS standards -200 mm dia	Each	296
42	MAT-01702	BMW-A.42	Supply of SWG Bendsconforming to IS standards -250 mm dia	Each	599
43	MAT-01703	BMW-A.43	Supply of SWG Bends conforming to IS standards -300 mm dia	Each	762
44	MAT-01704	BMW-A.44	Supply of SWG Bends conforming to IS standards -350 mm dia	Each	951
45	MAT-01705	BMW-A.45	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 100 x 100	Each	164
46	MAT-01706	BMW-A.46	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 150 x 100	Each	240
47	MAT-01707	BMW-A.47	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 150 x 150	Each	263
48	MAT-01708	BMW-A.48	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 200 x 100	Each	374
49	MAT-01709	BMW-A.49	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 200 x 150	Each	437
50	MAT-01710	BMW-A.50	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 200 x 200	Each	501
51	MAT-01711	BMW-A.51	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 250 x 100	Each	588
52	MAT-01712	BMW-A.52	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 250 x 150	Each	777
53	MAT-01713	BMW-A.53	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 250 x 200	Each	961
54	MAT-01714	BMW-A.54	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 250 x 250	Each	1151
55	MAT-01715	BMW-A.55	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 300 x 100	Each	839
56	MAT-01716	BMW-A.56	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 300 x 150	Each	1075
57	MAT-01717	BMW-A.57	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 300 x 200	Each	1310

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
58	MAT-01718	BMW-A.58	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 300 x 250	Each	1546
59	MAT-01719	BMW-A.59	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 300 x 300	Each	1782
60	MAT-01720	BMW-A.60	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 350 x 100	Each	1047
61	MAT-01721	BMW-A.61	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 350 x 150	Each	1342
62	MAT-01722	BMW-A.62	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 350 x 200	Each	1636
63	MAT-01723	BMW-A.63	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 350 x 250	Each	1929
64	MAT-01724	BMW-A.64	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 350 x 300	Each	2225
65	MAT-01725	BMW-A.65	Supply of SWG Junctions (T's & Y's) conforming to IS standards with length of barrel 60 cm for - 350 x 350	Each	2517
66	MAT-01726	BMW-A.66	Supply of SWG Plugs conforming to IS standards for 100 mm dia	Each	31
67	MAT-01727	BMW-A.67	Supply of SWG Plugs conforming to IS standards for 150 mm dia	Each	59
68	MAT-01728	BMW-A.68	Supply of SWG Plugs conforming to IS standards for 200 mm dia	Each	112
69	MAT-01729	BMW-A.69	Supply of SWG Plugs conforming to IS standards for 250 mm dia	Each	194
70	MAT-01730	BMW-A.70	Supply of SWG Plugs conforming to IS standards for 300 mm dia	Each	308
71	MAT-01731	BMW-A.71	Supply of SWG Plugs conforming to IS standards for 350 mm dia	Each	386
72	MAT-01732	BMW-A.72	Supplying & fixing 150 mm x 100 mm SWG gully traps conforming to ISI 651 & 4127 with C.I Grating & Cost. Brick masonry in CM 1:6 prop. Intermediate chamber and fitted with 304.8 mm x 288.6 mm (12"x9") C.I Frame and hinged cover	Each	538
73	MAT-01733	BMW-A.73	Supply of SWG Gully Traps (Round & Square) conforming to IS standards 150 x 100 mm	Each	242
74	LAB-00152	BMW-A.74	Labour charges for fixing and laying the SWG Junctions/ Plugs/ Bends of any dia with airtight cement joints as per standard practice	Each	38
75	MAT-01734	BMW-A.75	Supply of SWG Saddles conforming to IS standards 150 x 100 mm		172
76	MAT-01735	BMW-A.76	Supply of SWG Saddles conforming to IS standards 200 x 100 mm		296
77	MAT-01736	BMW-A.77	Supply of SWG Saddles conforming to IS standards 250 x 100 mm		478

		B	MAN HOLES & INSPECTION CHAMBERS -AS PER - IS 4111 : Part 1 : 1986		
Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
78	MAT-05233	BMW-B.01	Constructing 904.0 mm (3'0") dia solid block masonry inspection chamber as per IS - 4111: Part-1:1986 with cement mortar (1:6) prop using fly-ash blocks of 225 mm thick from approved source having a minimum crushing strength of 10 N/sq.mm including plastering with cement mortar 1:3 prop; ½" thick both inside and outside fitted with 20" dia RCC manhole covers and frames including excavating pits up to a depth of 904 mm (3'-0") in all sorts of soils (excluding rock) and laying cement concrete (1:4:8) 150 mm thick using 40 mm HBG Metal and P.C.C. 1:2:4 benching and channel 100 mm thick as per Standard specification and including cost and conveyance of all materials like cement, sand, bricks, water etc., to site, cost of seigniorage charges on all materials and all incidental and operational, labour charges like mixing cement mortar, constructing masonry, lift charges, curing etc., complete for finished item of work as per Standard specification.	Each	6367
79	MAT-05234	BMW-B.02	Constructing 904.0 mm (3'0") dia solid block masonry inspection chamber as per IS - 4111: Part-1:1986 with cement mortar (1:6) prop using fly-ash blocks of 225 mm thick from approved source having a minimum crushing strength of 10 N/sq.mm including plastering with cement mortar 1:3 prop; ½" thick both inside and outside fitted with 20" dia RCC manhole covers and frames including excavating pits up to a depth of 1524 mm (5'-0") in all sorts of soils (excluding rock) and laying cement concrete (1:4:8) 150 mm thick using 40 mm HBG Metal and P.C.C. 1:2:4 benching and channel 100 mm thick as per Standard specification and including cost and conveyance of all materials like cement, sand, bricks, water etc., to site, cost of seigniorage charges on all materials and all incidental and operational, labour charges like mixing cement mortar, constructing masonry, lift charges, curing etc., complete for finished item of work as per Standard specification.	Each	10020
80	MAT-05235	BMW-B.03	Constructing 904.0 mm (3'0") dia brick masonry inspection chamber as per IS - 4111: Part-1:1986 with cement mortar (1:6) prop using 2nd Class Clay Bricks of 225 mm thick from approved source having a minimum crushing strength of 5 N/sq.mm including plastering with cement mortar 1:3 prop; ½" thick both inside and outside fitted with 20" dia RCC manhole covers and frames including excavating pits up to a depth of 904 mm (3'-0") in all sorts of soils (excluding rock) and laying cement concrete (1:4:8) 150 mm thick using 40 mm HBG Metal and P.C.C. 1:2:4 benching and channel 100 mm thick as per Standard specification and including cost and conveyance of all materials like cement, sand, bricks, water etc., to site, cost of seigniorage charges on all materials and all incidental and operational, labour charges like mixing cement mortar, constructing masonry, lift charges, curing etc., complete for finished item of work as per Standard specification.	Each	6167
81	MAT-05236	BMW-B.04	Constructing 904.0 mm (3'0") dia brick masonry inspection chamber as per IS - 4111: Part-1:1986 with cement mortar (1:6) prop using 2nd Class Clay Bricks of 225 mm thick from approved source having a minimum crushing strength of 5 N/sq.mm including plastering with cement mortar 1:3 prop;	Each	9634

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
			½" thick both inside and outside fitted with 20" dia RCC manhole covers and frames including excavating pits up to a depth of 1524 mm (5'-0") in all sorts of soils (excluding rock) and laying cement concrete (1:4:8) 150 mm thick using 40 mm HBG Metal and P.C.C. 1:2:4 benching and channel 100 mm thick as per Standard specification and including cost and conveyance of all materials like cement, sand, bricks, water etc., to site, cost of seigniorage charges on all materials and all incidental and operational, labour charges like mixing cement mortar, constructing masonry, lift charges, curing etc., complete for finished item of work as per Standard specification.		
82	MAT-01737	BMW-B.05	Constructing 914.4 mm x 457.2 mm (3'0"x1'6") brick in CM 1:6 prop. Masonry Inspection chamber up to 914.4 mm (3'0") and fitted with light weight 914.4 mm x 457.2 mm (3'0"x1'6") C.I frame and cover of 40 Kg.	Each	6005
83	MAT-01738	BMW-B.06	Constructing 457.2 mm x 457.2 mm (1'6"x1'6") brick in CM 1:6 prop. Masonry. Inspection chamber up to 914.4 mm (3'0") and fitted with light weight 457.2 mm x 457.2 mm (1'6"x1'6") C.I frame and cover of 20 Kg.	Each	3619
84	MAT-01739	BMW-B.07	a) Making drainage connection in the existing inspection including all repairs	Each	120
85	LAB-00157	BMW-B.08	b) - do - labour charges only	Each	89
		C	C.I. PIPES & FITTINGS -AS PER - IS 1729:1979 (Materials shall be procured from the list of approved Brands/ Manufacturers/ Suppliers)		
			Supplying and fixing of C.I. Single/ Double Socket soil pipes ISI marked conforming to IS:1729-1979 of reputed make with cement caulked joints and fixing as per site requirements including painting black with Japan paint and fixing with necessary wooden blocks fixed in the masonry walls in cement mortar (1½:1) and including fixing of M.S. clamps if necessary with required no. of Bombay nails etc., complete		
86	MAT-01740	BMW-C.01	3" dia (76.2 mm) Single Socket	1 RM	760
87	MAT-01741	BMW-C.02	4" dia (101.6mm) Single Socket	1 RM	983
88	MAT-01742	BMW-C.03	6" dia (152.4mm) Single Socket	1 RM	1552
89	MAT-01743	BMW-C.04	3" dia (76.2 mm) Double Socket	1 RM	824
90	MAT-01744	BMW-C.05	4" dia (101.6mm) Double Socket	1 RM	1089
91	MAT-01745	BMW-C.06	6" dia (152.4mm) Double Socket	1 RM	1781
92	LAB-00158	BMW-C.07	Labour charges only for fixing of C.I. Single/ Double Socket soil pipes of any dia with cement caulked joints and fixing as per site requirements including painting black with Japan paint and fixing with necessary wooden blocks fixed in the masonry walls in cement mortar and including fixing of M.S. clamps if necessary with required nails	1 RM	285
93	MAT-01746	BMW-C.08	Supplying & fixing CI Plain bends 1st quality ISI marked conforming to IS:1729-1979 with cement caulked joints and fixing as per site requirements with standard practice for 3" dia (76.2 mm)	Each	294

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
94	MAT-01747	BMW-C.09	Supplying & fixing CI Plain bends 1st quality ISI marked conforming to IS:1729-1979 with cement caulked joints and fixing as per site requirements with standard practice for 4" dia (101.6 mm)	Each	368
95	MAT-01748	BMW-C.10	Supplying & fixing CI Plain bends 1st quality ISI marked conforming to IS:1729-1979 with cement caulked joints and fixing as per site requirements with standard practice for 6" dia (152.4 mm)	Each	603
96	MAT-01749	BMW-C.11	Supplying & fixing CI Plug (Door) bends 1st quality ISI marked conforming to IS:1729-1979 with cement caulked joints and fixing as per site requirements with standard practice for 3" dia (76.2 mm)	Each	360
97	MAT-01750	BMW-C.12	Supplying & fixing CI Plug (Door) bends 1st quality ISI marked conforming to IS:1729-1979 with cement caulked joints and fixing as per site requirements with standard practice for 4" dia (101.6 mm)	Each	443
98	MAT-01751	BMW-C.13	Supplying & fixing CI Plug (Door) bends 1st quality ISI marked conforming to IS:1729-1979 with cement caulked joints and fixing as per site requirements with standard practice for 6" dia (152.4 mm)	Each	954
99	LAB-00159	BMW-C.14	Labour charges only for fixing CI Plain/ Plug (Door) bends with cement caulked joints and fixing as per site requirements with standard practice	Each	90
100	MAT-01752	BMW-C.15	Supplying and fixing of 76.2 mm (3") CI soil single junction with plug : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	456
101	MAT-01753	BMW-C.16	Supplying and fixing of 101.6 mm (4") CI soil single junction with plug : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	702
102	MAT-01754	BMW-C.17	Supplying and fixing of 152.4 mm (6") CI soil single junction with plug : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	1640
103	MAT-01755	BMW-C.18	Supplying and fixing of 76.2 mm (3") CI soil plain single junction : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	386
104	MAT-01756	BMW-C.19	Supplying and fixing of 101.6 mm (4") CI soil plain single junction : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	520
105	MAT-01757	BMW-C.20	Supplying and fixing of 152.4 mm (6") CI soil plain single junction : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	1226
106	LAB-00160	BMW-C.21	Labour charges only fixing CI soil single junctions with cement caulked joints and fixing as per site requirements with standard practice	Each	127
107	MAT-01758	BMW-C.22	Supplying and Fixing of 76.2 mm (3") CI soil Double junction with plug : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	683
108	MAT-01759	BMW-C.23	Supplying and Fixing of 101.6 mm (4") CI soil Double junction with plug : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	826

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
109	MAT-01760	BMW-C.24	Supplying and Fixing of 152.4 mm (6") CI soil Double junction with plug : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	1909
110	MAT-01761	BMW-C.25	Supplying and Fixing of 76.2 mm (3") CI soil plain Double junction : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	592
111	MAT-01762	BMW-C.26	Supplying and Fixing of 101.6 mm (4") CI soil plain Double junction : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	773
112	MAT-01763	BMW-C.27	Supplying and Fixing of 152.4 mm (6") CI soil plain Double junction : conforming to IS:1729-1979 with cement caulked joints and fixing	Each	1789
113	LAB-00161	BMW-C.28	Labour charges only fixing CI soil Double junctions with cement caulked joints and fixing as per site requirements with standard practice	Each	125
114	MAT-01764	BMW-C.29	Supplying and Fixing of 75mm C.I. Offsets 1st quality conforming to IS:1729-1979 with cement caulked joints and fixing-for 76.20 mm (3") C.I. Pipe	Each	290
115	MAT-01765	BMW-C.30	Supplying and Fixing of 75mm C.I. Offsets 1st quality conforming to IS:1729-1979 with cement caulked joints and fixing-for 101.6 mm (4") C.I. Pipe	Each	403
116	MAT-01766	BMW-C.31	Supplying and Fixing of 75mm C.I. Offsets 1st quality conforming to IS:1729-1979 with cement caulked joints and fixing-for 152.4 mm (6") C.I. Pipe	Each	867
117	MAT-01767	BMW-C.32	Supplying and Fixing of 115 mm C.I. Offsets 1st quality conforming to IS:1729-1979 with cement caulked joints and fixing- for 76.20 mm (3") C.I. Pipe	Each	344
118	MAT-01768	BMW-C.33	Supplying and Fixing of 115 mm C.I. Offsets 1st quality conforming to IS:1729-1979 with cement caulked joints and fixing- for 101.6 mm (4") C.I. Pipe	Each	454
119	MAT-01769	BMW-C.34	Supplying and Fixing of 115 mm C.I. Offsets 1st quality conforming to IS:1729-1979 with cement caulked joints and fixing- for 152.4 mm (6") C.I. Pipe	Each	889
120	MAT-01770	BMW-C.35	Supplying and Fixing of 150 mm C.I. Offsets 1st quality conforming to IS:1729-1979 with cement caulked joints and fixingfor 76.20 mm (3") C.I. Pipe	Each	397
121	MAT-01771	BMW-C.36	Supplying and Fixing of 150 mm C.I. Offsets 1st quality conforming to IS:1729-1979 with cement caulked joints and fixingfor 101.6 mm (4") C.I. Pipe	Each	511
122	MAT-01772	BMW-C.37	Supplying and Fixing of 150 mm C.I. Offsets 1st quality conforming to IS:1729-1979 with cement caulked joints and fixingfor 152.4 mm (6") C.I. Pipe	Each	1032
123	LAB-00162	BMW-C.38	Labour charges only fixing CI soil Offsets with cement caulked joints and fixing as per site requirements with standard practice	Each	57
124	MAT-01773	BMW-C.39	Supplying & fixing CI floor traps 1st quality ISI marked conforming to IS:1729-1979 with C.P. Grating fixing with white cement as per site requirements with standard practicefor nominal dia 75 mm (3") and grating size 165 mm dia of weight not less than 5.5 Kgs	Each	520

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
125	MAT-01774	BMW-C.40	Supplying & fixing CI floor traps 1st quality ISI marked with C.P. Grating fixing with white cement as per site requirements with standard practice for nominal dia 100 mm (4") and grating size 100 mm dia of weight not less than 6 Kgs	Each	636
126	MAT-01775	BMW-C.41	Supplying & fixing CI floor traps 1st quality ISI marked conforming to IS:1729-1979 with C.P. Grating fixing with white cement as per site requirements with standard practice for nominal dia 75 mm (3") and grating size 100 mm dia of weight not less than 4.0 Kgs	Each	323
127	LAB-00163	BMW-C.42	Labour charges only for fixing CI Nahany/ Floor traps with C.P. Grating fixing with white cement as per site requirements with standard practice	Each	64
128	MAT-01776	BMW-C.43	Boxing of Nahany traps in RCC floors	Each	180
129	MAT-01777	BMW-C.44	Boxing of W.C Trap in R.C.C floors	Each	360
130	MAT-01778	BMW-C.45	Supplying & fixing CI Collars (double socket) 1st quality ISI marked conforming to IS:1729-1979 with cement caulked joints and fixing as per site requirements with standard practice for 76.20 mm (3") C.I. Pipe	Each	171
131	MAT-01779	BMW-C.46	Supplying & fixing CI Collars (double socket) 1st quality ISI marked conforming to IS:1729-1979 with cement caulked joints and fixing as per site requirements with standard practice for 101.6 mm (4") C.I. Pipe	Each	215
132	MAT-01780	BMW-C.47	Supplying & fixing CI Collars (double socket) 1st quality ISI marked conforming to IS:1729-1979 with cement caulked joints and fixing as per site requirements with standard practice for 152.4 mm (6") C.I. Pipe	Each	617
		D	VITREOUS CHINAWARE - SANITARY APPLIANCES as per IS:2556 – 1974 (Materials shall be procured from the list of approved Brands/ Manufacturers/ Suppliers)		
133	MAT-01781	BMW-D.01	Supplying & Fixing Indian pattern white glazed W.C 1st quality ISI marked conforming to IS:2556-Part-3-1981 with "P" or "S" trap: 580 mm Long	Each	1045
134	MAT-01782	BMW-D.02	Supplying & Fixing Indian pattern white glazed W.C 1st quality ISI marked conforming to IS:2556-Part-3-1981 with "P" or "S" trap: 630 mm Long	Each	1045
135	LAB-00164	BMW-D.03	Labour charges only for fixing Indian pattern W.C with "P" or "S" trap	Each	378
136	MAT-01783	BMW-D.04	Supplying & Fixing Orissa Pan white glazed W.C 1st quality ISI marked conforming to IS:2556-Part-3-1981 with "P" or "S" trap: 580 mm x 440 mm x 260 mm	Each	1564
137	MAT-01784	BMW-D.05	Supplying & Fixing Orissa Pan white glazed W.C 1st quality ISI marked conforming to IS:2556-Part-3-1981 with "P" or "S" trap: 630 mm x 450 mm	Each	1640
138	LAB-00165	BMW-D.06	Labour charges only Fixing Orissa pan W.C with "P" or "S" trap	Each	473
139	MAT-01785	BMW-D.07	Supplying & Fixing porcelain foot rest for squatting I.W.C. (Rectangular pair) of sizes 250 mm x 125 mm x 15 mm thick each foot rest 1st quality ISI marked conforming to IS:2556-Part-10:1974	Pair	240

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
140	LAB-00166	BMW-D.08	Labour charges only for fixing porcelain foot rest for squatting I.W.C. (Rectangular pair)	Pair	87
141	MAT-01786	BMW-D.09	Providing Brick masonry seat for Orissa pan/ Indian W.C. using 2nd class bricks as per standard practice	Each	306
142	MAT-01787	BMW-D.10	Providing Cement Concrete Squatting plate for Orissa pan/ Indian W.C. in P.C.C. 1:2:4 as per standard practice	Each	91
143	MAT-01788	BMW-D.11	Supplying & Fixing low down porcelain flushing tank 10 Lit Capacitywith internal components	Each	2488
144	LAB-00167	BMW-D.12	Labour charges only for fixing low down porcelain flushing tank with internal components	Each	661
145	MAT-01789	BMW-D.13	Supplying and Fixing European ISI Water Closet of 1st quality conforming to IS:2556-Part-2-1973 ofwhite glazedwith 'P'trap	Each	1995
146	MAT-01790	BMW-D.14	Supplying and Fixing European ISI Water Closet of 1st quality conforming to IS:2556-Part-2-1973 ofwhite glazedwith 'S'trap	Each	1905
147	LAB-00168	BMW-D.15	Labour charges only for fixing European Water Closet with 'P' or 'S' trap as per standard practice	Each	331
148	MAT-01791	BMW-D.16	Supplying and Fixing best Indian make plastic seat and lid for European water closets with rubber or plastic Buffers as per IS 2548-1996	Each	857
149	LAB-00169	BMW-D.17	Labour charges only for fixing plastic seat and lid for European water closet	Each	96
150	MAT-01792	BMW-D.18	Supply, Installation and commissioning approved make floor mounted Close coupled EWC suit CASCADE model 'P' or 'S' trap with dual flush porcelain cistern fixed on EWC with all internal parts of dual flush cistern, ultra solid seat cover of approvedmake with rubber buffer and cap 15 mm angle stop cock 450 mm long PVC inter connection pipe wall flanges all of approved make etc. complete for finished item of work in all respects:White Colour	Each	9232
151	MAT-01793	BMW-D.19	Supply, Installation and commissioning approved make floor mounted Close coupled EWC suit CASCADE model 'P' or 'S' trap with dual flush porcelain cistern fixed on EWC with all internal parts of dual flush cistern, ultra solid seat cover of approvedmake with rubber buffer and cap 15 mm angle stop cock 450 mm long PVC inter connection pipe wall flanges all of approved make etc. complete for finished item of work in all respects: Coloured - Grade - I/ Grade - II	Each	13461
152	MAT-01794	BMW-D.20	Supply, Installation and commissioning approved make floor mounted close coupled EWC suit CASCADE model 'P' or 'S' trap with dual flush porcelain cistern fixed on EWC with all internal parts of dual flush cistern, ultra solid seat cover of approvedmake with rubber buffer and cap 15 mm angle stop cock 450 mm long PVC inter connection pipe wall flanges all of approved make etc. complete for finished item of work in all respects: Special Colour - Grade - III	Each	17130
153	MAT-01795	BMW-D.21	Supplying & Fixing Indian make Flat Back Wash Hand Basin1st quality conforming to IS:2556-Part-4:1972 with waste fittings like rubber plug, chain,32 mm nominal size C.P. Fitting with parallel pipe thread conforming to IS:2963-	Each	2632

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
			1979 and fitted with 15 mm nominal bore Chromium Plated Pillar Tap of 1st quality Indian make 400 grams or equivalent complete with standard CI brackets including wooden block: 660 x 460 mm - Single C.P. Pillar cock		
154	MAT-01796	BMW-D.22	Supplying & Fixing Indian make Flat Back Wash Hand Basin 1st quality conforming to IS:2556-Part-4:1972 with waste fittings like rubber plug, chain, 32 mm nominal size C.P. Fitting with parallel pipe thread conforming to IS:2963-1979 and fitted with 15 mm nominal bore Chromium Plated Pillar Tap of 1st quality Indian make 400 grams or equivalent complete with standard CI brackets including wooden block: 630 x 450 mm - Single C.P. Pillar cock	Each	2337
155	MAT-01797	BMW-D.23	Supplying & Fixing Indian make Flat Back Wash Hand Basin 1st quality conforming to IS:2556-Part-4:1972 with waste fittings like rubber plug, chain, 32 mm nominal size C.P. Fitting with parallel pipe thread conforming to IS:2963-1979 and fitted with 15 mm nominal bore Chromium Plated Pillar Tap of 1st quality Indian make 400 grams Seiko/ Senior/ Nice/ Esso or equivalent complete with standard CI brackets including wooden block: 630 x 450 mm - Double C.P. Pillar cock	Each	2851
156	MAT-01798	BMW-D.24	Supplying & Fixing Indian make Flat Back Wash Hand Basin 1st quality conforming to IS:2556-Part-4:1972 with waste fittings like rubber plug, chain, 32 mm nominal size C.P. Fitting with parallel pipe thread conforming to IS:2963-1979 and fitted with 15 mm nominal bore Chromium Plated Pillar Tap of 1st quality Indian make 400 grams Seiko/ Senior/ Nice/ Esso or equivalent complete with standard CI brackets including wooden block: 550 x 400 mm - Single C.P. Pillar cock	Each	1750
157	MAT-01799	BMW-D.25	Supplying & Fixing Indian make Flat Back Wash Hand Basin 1st quality conforming to IS:2556-Part-4:1972 with waste fittings like rubber plug, chain, 32 mm nominal size C.P. Fitting with parallel pipe thread conforming to IS:2963-1979 and fitted with 15 mm nominal bore Chromium Plated Pillar Tap of 1st quality Indian make 400 grams Seiko/ Senior/ Nice/ Esso or equivalent complete with standard CI brackets including wooden block: 550 x 400 mm - Double C.P. Pillar cock	Each	2117
158	MAT-01800	BMW-D.26	Supplying & Fixing Indian make Flat Back Wash Hand Basin 1st quality conforming to IS:2556-Part-4:1972 with waste fittings like rubber plug, chain, 32 mm nominal size C.P. Fitting with parallel pipe thread conforming to IS:2963-1979 and fitted with 15 mm nominal bore Chromium Plated Pillar Tap of 1st quality Indian make 400 grams Seiko/ Senior/ Nice/ Esso or equivalent complete with standard CI brackets including wooden block: 450 x 300 mm - Single C.P. Pillar cock	Each	1532
159	MAT-01801	BMW-D.27	Supplying & Fixing Indian make Flat Back Wash Hand Basin 1st quality conforming to IS:2556-Part-4:1972 with waste fittings like rubber plug, chain, 32 mm nominal size C.P. Fitting with parallel pipe thread conforming to IS:2963-	Each	1972

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
			1979 and fitted with 15 mm nominal bore Chromium Plated Pillar Tap of 1st quality Indian make 400 grams Seiko/ Senior/ Nice/ Esso or equivalent complete with standard CI brackets including wooden block: 450 x 300 mm - Double C.P. Pillar cock		
160	LAB-00170	BMW-D.28	Labour charges only for fixing Indian make Flat Back Wash Hand Basin with waste fittings like rubber plug, chain, 32 mm nominal size C.P. Fitting Pillar Taps complete with standard CI brackets including wooden block	Each	400
161	MAT-01802	BMW-D.29	Supplying and Fixing Pedestal for Wash Hand Basin	Each	1212
162	LAB-00171	BMW-D.30	Labour charges only for fixing pedestal for wash hand basin	Each	170
163	MAT-01803	BMW-D.31	Supplying & Fixing 31.75 mm C.P bottle trap (Heavy type)	Each	437
164	LAB-00172	BMW-D.32	Labour charges only for fixing bottle trap to the wash hand basin	Each	57
165	MAT-01804	BMW-D.33	Supplying & Fixing white glazed flat back Bowl urinals of size 440 mm x 265 mm x 315 mm with internal flushing rim fixed with screws complete Indian make conforming to IS:2556-1995	Each	906
166	MAT-01805	BMW-D.34	Supplying & Fixing white glazed flat back half stall urinals 1st quality conforming to IS:2556-1995 with standard C.P. Spreader of overall size 95 x 95 x 57 mm conforming to IS:2556-Part6, Sec-6-1974 fixed with screws complete Indian make : 410 x 265 x 305 mm	Each	2666
167	MAT-01806	BMW-D.35	Supplying & Fixing white glazed flat back half stall urinals 1st quality conforming to IS:2556-1995 with standard C.P. Spreader of overall size 95 x 95 x 57 mm conforming to IS:2556-Part6, Sec-6-1974 fixed with screws complete Indian make : 590 x 375 x 380 mm	Each	2959
168	LAB-00173	BMW-D.36	Labour charges only Fixing flat back Bowl/ Half stall urinals with fixing C.P. Spreader and screws complete	Each	160
169	MAT-01807	BMW-D.37	Supplying & Fixing Indian make white glazed vitreous china porcelain sink conforming to IS:2556-Part-5-1994 on cantilever brackets with waste fittings like rubber plug, chain, 32 mm nominal size C.P. Fitting with parallel pipe thread conforming to IS:2963-1979 : 600 x 400 x 250	Each	4828
170	MAT-01808	BMW-D.38	Supplying & Fixing Indian make white glazed vitreous china porcelain sink conforming to IS:2556-Part-5-1994 on cantilever brackets with waste fittings like rubber plug, chain, 32 mm nominal size C.P. Fitting with parallel pipe thread conforming to IS:2963-1979 : 750 x 450 x 250	Each	5414
171	LAB-00174	BMW-D.39	Labour charges only for fixing Vitreous china porcelain sinks with waste fittings, rubber plug, chain, cantilever brackets etc.	Each	400
172	MAT-01809	BMW-D.40	a) S & F 609.6 x 457.2 x 254 mm RCC terrazzo finished sink (or constructed at site with 50.8mm thick) brass plug and chain including CI cantilever brackets	Each	788
173	LAB-00175	BMW-D.41	b) - do - labour charges only	Each	282

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
		E	TAPS & FAUCETS(Materials shall be procured from the listof approved Brands/ Manufacturers/ Suppliers)		
174	MAT-01810	BMW-E.01	a) S & F 12.7 mm NP stop cock Indian makeheavy duty	Each	454
175	LAB-00176	BMW-E.02	b) - do - labour charges only	Each	37
176	MAT-01811	BMW-E.03	a) S & Fconcealed stop cock 12.7 mm (1/2") Indian Make heavy duty	Each	520
177	LAB-00177	BMW-E.04	b) - do - labour charges only	Each	55
178	MAT-01812	BMW-E.05	a) S & Fangle stop cock 12.7 mm diafirst quality Indian Make heavy duty	Each	457
179	LAB-00178	BMW-E.06	b) - do - labour charges only	Each	55
180	MAT-01813	BMW-E.07	a) S&F 12.7 mm N.P bib tap Indian make heavy dutys Long body	Each	391
181	LAB-00179	BMW-E.08	b) - do - labour charges only	Each	37
182	MAT-01814	BMW-E.09	a) S&F 12.7mm N.P bib tap Indian make 3heavy duty sort body	Each	250
183	LAB-00180	BMW-E.10	b) - do - labour charges only	Each	37
184	MAT-01815	BMW-E.11	a)S & F 31.75 mm brass plumber Union best Indian first quality	Each	69
185	LAB-00181	BMW-E.12	b) - do - labour charges only	Each	18
186	MAT-01816	BMW-E.13	a) S & F 12.7 mm brass stop cock Indian make heavy duty long body	Each	224
187	LAB-00182	BMW-E.14	b) - do - labour charges only	Each	37
188	MAT-01817	BMW-E.15	a) S & F 12.7 mm brass stop cock Indian make heavy duty short body	Each	198
189	LAB-00183	BMW-E.16	b) - do - labour charges only	Each	37
190	MAT-01818	BMW-E.17	a) S & F 12.7 mm brass bib cock Indian make heavy duty long body	Each	224
191	LAB-00184	BMW-E.18	b) - do - labour charges only	Each	37
192	MAT-01819	BMW-E.19	a) S & F 12.7 mm brass bib cock Indian make heavy duty short body	Each	198
193	LAB-00185	BMW-E.20	b) - do - labour charges only	Each	37
194	MAT-01820	BMW-E.21	S & F CP Long body bib cock fancy type deluxe heavy duty 12.7 mm dia Indian make	Each	612
195	MAT-01821	BMW-E.22	S & F CP Short body bib cock fancy type deluxeheavy duty 12.7 mm dia Indian make	Each	587

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
196	MAT-01822	BMW-E.23	S & F 12.7mm heavy duty dia high neck pillar cock 1st quality Indian make	Each	1111
197	MAT-01823	BMW-E.24	a)S & F 12.7 mm heavy duty NP Swan Neck Pillar cock	Each	1111
198	LAB-00186	BMW-E.25	b) - do - labour charges only	Each	50
199	MAT-01824	BMW-E.26	a)S & F 12.7 mm heavy duty NP Sink cock	Each	1109
200	LAB-00187	BMW-E.27	b) - do - labour charges only	Each	44
201	MAT-01825	BMW-E.28	S&F 12.7 mm dia NP pillar cock heavy duty 1st quality Indian make	Each	584
202	MAT-01826	BMW-E.29	S&F 12.7 mm dia NP push cock 1st quality	Each	262
203	MAT-01827	BMW-E.30	S&F 12.7 mm dia NP lift cock 1st quality	Each	229
204	MAT-01828	BMW-E.31	a)S & F 38.1 mm C.P.waste coupling Half or Full Thread 1st Quality Indian make Parryware or equivalent	Each	229
205	LAB-00188	BMW-E.32	b) - do - labour charges only	Each	37
206	MAT-01829	BMW-E.33	a) S & F 31.75 mm PVC bottle trap	Each	141
207	LAB-00189	BMW-E.34	b) - do - labour charges only	Each	37
208	MAT-01830	BMW-E.35	a)S& F 38.1 mm brass plumber union	Each	69
209	LAB-00190	BMW-E.36	b) - do - labour charges only	Each	18
210	MAT-01831	BMW-E.37	a)S & F 19.05 mm heavy duty NP stop cock Indian make with ISI mark	Each	584
211	LAB-00191	BMW-E.38	b) - do - labour charges only	Each	1111
		F	G.I. PIPES & FITTINGS(Materials shall be procured from the list of approved Brands/ Manufacturers/ Suppliers)		
212	MAT-01832	BMW-F.01	S& F Glunion 12.7 mm 1st Quality	Each	43
213	MAT-01833	BMW-F.02	S& F Glunion 19.05 mm 1st Quality	Each	52
214	MAT-01834	BMW-F.03	S& F Glunion 25.4 mm 1st Quality	Each	78
215	MAT-01835	BMW-F.04	S& F Glunion 31.75 mm 1st Quality	Each	96
216	MAT-01836	BMW-F.05	S& F Glunion 38.1 mm 1st Quality	Each	115
217	MAT-01837	BMW-F.06	S& F Glunion 50.8 mm 1st Quality	Each	144
218	MAT-01838	BMW-F.07	S& F GI connector 25.4 mm dia	Each	86
219	MAT-01839	BMW-F.08	S& F 12.7 mm GI 'T' A class 1st quality	Each	53
220	MAT-01840	BMW-F.09	S& F 31.75mm dia GI bend 1st quality	Each	78
221	MAT-01841	BMW-F.10	S & F 31.75 mm dia GI 'T' 1st Quality	Each	77
222	MAT-01842	BMW-F.11	a) S & F 25.4 mm copper ball cock ith PVC ball Indian make ISI mark	Each	452
223	LAB-00192	BMW-F.12	b) - do - labour charges only	Each	56
224	MAT-01843	BMW-F.13	a) S & F 19.05 mm copper ball cock ith PVCball Indian make ISI mark	Each	370
225	LAB-00193	BMW-F.14	b) - do - labour charges only	Each	49

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
226	MAT-01844	BMW-F.15	a)S & F 12.7 mm copper ball cock ith PVC ball Indian make ISI mark	Each	243
227	LAB-00194	BMW-F.16	b) - do - labour charges only	Each	56
228	MAT-01845	BMW-F.17	a)S & F Gunmetal Gate (GM peet) valve as per IS - 778 Class - I, Indian make heavy type - 25 mm NB Size	Each	1175
229	LAB-00195	BMW-F.18	b) - do - labour charges only	Each	56
230	MAT-01846	BMW-F.19	a)S & F Gunmetal Gate (GM peet) valve as per IS - 778 Class - I, Indian make heavy type - 20 mm NB Size	Each	819
231	LAB-00196	BMW-F.20	b) - do - labour charges only	Each	56
232	MAT-01847	BMW-F.21	a)S & F Gunmetal Gate (GM peet) valve as per IS - 778 Class - I, Indian make heavy type - 15 mm NB Size	Each	609
233	LAB-00197	BMW-F.22	b) - do - labour charges only	Each	56
234	MAT-01848	BMW-F.23	a)S & F Gunmetal Gate (GM peet) valve as per IS - 778 Class - I, Indian make heavy type - 32 mm NB Size	Each	1783
235	LAB-00198	BMW-F.24	b) - do - labour charges only	Each	48
236	MAT-01849	BMW-F.25	a)S & F Gunmetal Gate (GM peet) valve as per IS - 778 Class - I, Indian make heavy type - 40 mm NB Size	Each	2409
237	LAB-00199	BMW-F.26	b) - do - labour charges only	Each	84
238	MAT-01850	BMW-F.27	a)S & F Gunmetal Gate (GM peet) valve as per IS - 778 Class - I, Indian make heavy type - 50 mm NB Size	Each	3526
239	LAB-00200	BMW-F.28	b) - do - labour charges only	Each	112
240	MAT-01851	BMW-F.29	a)S & F Gunmetal Gate (GM peet) valve as per IS - 778 Class - I, Indian make heavy type - 65 mm NB Size	Each	5442
241	LAB-00201	BMW-F.30	b) - do - labour charges only	Each	133
242	MAT-01852	BMW-F.31	a)S & F Gunmetal Gate (GM peet) valve as per IS - 778 Class - I, Indian make heavy type - 80 mm NB Size	Each	8059
243	LAB-00202	BMW-F.32	b) - do - labour charges only	Each	165
244	MAT-01853	BMW-F.33	a) Supplying & fixing Gunmetal (GM) Horizontal Check (Non return) Valve as per IS-778 I-class heavy duty - 15 mm NB Size	Each	454
245	LAB-00203	BMW-F.34	b) - do - labour charges only	Each	69
246	MAT-01854	BMW-F.35	a) Supplying & fixing Gunmetal (GM) Horizontal Check (Non return) Valve as per IS-778 I-class heavy duty - 25 mm NB Size	Each	1028
247	LAB-00204	BMW-F.36	b) - do - labour charges only	Each	84
248	MAT-01855	BMW-F.37	a) Supplying & fixing Gunmetal (GM) Horizontal Check (Non return) Valve as per IS-778 I-class heavy duty - 40 mm NB Size	Each	2086
249	LAB-00205	BMW-F.38	b) - do - labour charges only	Each	140
250	MAT-01856	BMW-F.39	a) Supplying & fixing Gunmetal (GM) Horizontal Check (Non return) Valve as per IS-778 I-class heavy duty - 50 mm NB Size	Each	2848
251	LAB-00206	BMW-F.40	b) - do - labour charges only	Each	141
252	MAT-01857	BMW-F.41	a) Supplying & fixing Gunmetal (GM) Horizontal Check (Non	Each	659

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
			return) Valve as per IS-778 I-class heavy duty - 20 mm NB Size		
253	LAB-00207	BMW-F.42	b) - do - labour charges only	Each	68
254	MAT-01858	BMW-F.43	a) Supplying & fixing Gunmetal (GM) Vertical Check (Non return) Valve as per IS-778 I-class heavy duty - 15 mm NB Size	Each	428
255	LAB-00208	BMW-F.44	b) - do - labour charges only	Each	68
256	MAT-01859	BMW-F.45	a) Supplying & fixing Gunmetal (GM) Vertical Check (Non return) Valve as per IS-778 I-class heavy duty - 20 mm NB Size	Each	555
257	LAB-00209	BMW-F.46	b) - do - labour charges only	Each	68
258	MAT-01860	BMW-F.47	a) Supplying & fixing Gunmetal (GM) Vertical Check (Non return) Valve as per IS-778 I-class heavy duty - 25 mm NB Size	Each	833
259	LAB-00210	BMW-F.48	b) - do - labour charges only	Each	68
260	MAT-01861	BMW-F.49	a) Supplying & fixing Gunmetal (GM) Vertical Check (Non return) Valve as per IS-778 I-class heavy duty - 32 mm NB Size	Each	1145
261	LAB-00211	BMW-F.50	b) - do - labour charges only	Each	68
262	MAT-01862	BMW-F.51	a) Supplying & fixing Gunmetal (GM) Vertical Check (Non return) Valve as per IS-778 I-class heavy duty - 40 mm NB Size	Each	1381
263	LAB-00212	BMW-F.52	b) - do - labour charges only	Each	107
264	MAT-01863	BMW-F.53	a) Supplying & fixing Gunmetal (GM) Vertical Check (Non return) Valve as per IS-778 I-class heavy duty - 50 mm NB Size	Each	2186
265	LAB-00213	BMW-F.54	b) - do - labour charges only	Each	68
266	MAT-01864	BMW-F.55	a)S & F Gunmetal (GM) Ball valve with SS Ball and SS Spindle as per IS - Class - I, Indian make heavy type - 15 mm NB Size	Each	460
267	LAB-00214	BMW-F.56	b) - do - labour charges only	Each	68
268	MAT-01865	BMW-F.57	a)S & F Gunmetal (GM) Ball valve with SS Ball and SS Spindle as per IS - Class - I, Indian make heavy type - 20 mm NB Size	Each	597
269	LAB-00215	BMW-F.58	b) - do - labour charges only	Each	68
270	MAT-01866	BMW-F.59	a)S & F Gunmetal (GM) Ball valve with SS Ball and SS Spindle as per IS - Class - I, Indian make heavy type - 25 mm NB Size	Each	871
271	LAB-00216	BMW-F.60	b) - do - labour charges only	Each	68
272	MAT-01867	BMW-F.61	a)S & F Gunmetal (GM) Ball valve with SS Ball and SS Spindle as per IS - Class - I, Indian make heavy type - 32 mm NB Size	Each	1576
273	LAB-00217	BMW-F.62	b) - do - labour charges only	Each	68
274	MAT-01868	BMW-F.63	a)S & F Gunmetal (GM) Ball valve with SS Ball and SS Spindle as per IS - Class - I, Indian make heavy type - 40 mm NB Size	Each	2359

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
275	LAB-00218	BMW-F.64	b) - do - labour charges only	Each	68
276	MAT-01869	BMW-F.65	a)S & F Gunmetal (GM) Ball valve with SS Ball and SS Spindle as per IS - Class - I, Indian make heavy type - 50 mm NB Size	Each	4106
277	LAB-00219	BMW-F.66	b) - do - labour charges only	Each	68
278	MAT-05237	BMW-F.67	a) S& F 15 mm Nominal Bore GI pipe Light Grade properties & weight as per IS 1239 ISI mark with GI fittings including the cost of pipe & its fittings & labour charges complete	1 RM	182
279	LAB-00221	BMW-F.68	b) - do - labour charges only	1 RM	51
280	MAT-05238	BMW-F.69	a) S& F 20 mm Nominal Bore GI pipe Light Grade properties & weight as per IS 1239ISI mark with GI fittings including the cost of pipe & its fittings & labour charges complete	1 RM	207
281	LAB-00223	BMW-F.70	b) - do - labour charges only	1 RM	51
282	MAT-05239	BMW-F.71	a) S& F 25 mm Nominal Bore GI pipe Light Grade properties & weight as per IS 1239ISI mark with GI fittings including the cost of pipe & its fittings & labour charges complete	1 RM	271
283	LAB-00225	BMW-F.72	b) - do - labour charges only	1 RM	51
284	MAT-05240	BMW-F.73	a) S& F 32 mm Nominal Bore GI pipe Light Grade properties & weight as per IS 1239ISI mark with GI fittings including the cost of pipe & its fittings & labour charges complete	1 RM	38
285	LAB-00227	BMW-F.74	b) - do - labour charges only	1 RM	51
286	MAT-05241	BMW-F.75	a) S& F 40 mm Nominal Bore GI pipe Light Grade properties & weight as per IS 1239 ISI mark with GI fittings including the cost of pipe & its fittings & labour charges complete	1 RM	421
287	LAB-00229	BMW-F.76	b) - do - labour charges only	1 RM	56
288	MAT-05242	BMW-F.77	a) S& F 50 mm Nominal Bore GI pipe Light Grade properties & weight as per IS 1239 ISI mark with GI fittings including the cost of pipe & its fittings & labour charges complete	1 RM	461
289	LAB-00231	BMW-F.78	b) - do - labour charges only	1 RM	84
290	MAT-05243	BMW-F.79	a) S& F 15 mm Nominal Bore GI pipe Medium Grade properties & weight as per IS 1239 ISI mark with GI fittings including the cost of pipe & its fittings & labour charges complete	1 RM	201
291	LAB-00233	BMW-F.80	b) - do - labour charges only	1 RM	51
292	MAT-05244	BMW-F.81	a) S& F 20 mm Nominal Bore GI pipe Medium Grade properties & weight as per IS 1239ISI mark with GI fittings including the cost of pipe & its fittings & labour charges complete	1 RM	222
293	LAB-00235	BMW-F.82	b) - do - labour charges only	1 RM	51
294	MAT-05245	BMW-F.83	a) S& F 25 mm Nominal Bore GI pipe Medium Grade properties & weight as per IS 1239ISI mark with GI fittings	1 RM	289

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
			including the cost of pipe & its fittings & labour charges complete		
295	LAB-00237	BMW-F.84	b) - do - labour charges only	1 RM	51
296	MAT-05246	BMW-F.85	a) S& F 32 mm Nominal Bore GI pipe Medium Grade properties & weight as per IS 1239 ISI mark with GI fittings including the cost of pipe & its fittings & labour charges complete	1 RM	402
297	LAB-00239	BMW-F.86	b) - do - labour charges only	1 RM	51
298	MAT-05247	BMW-F.87	a) S& F 40 mm Nominal Bore GI pipe Medium Grade properties & weight as per IS 1239 ISI mark with GI fittings including the cost of pipe & its fittings & labour charges complete	1 RM	448
299	LAB-00241	BMW-F.88	b) - do - labour charges only	1 RM	56
300	MAT-05248	BMW-F.89	a) S& F 50 mm Nominal Bore GI pipe Medium Grade properties & weight as per IS 1239 ISI mark with GI fittings including the cost of pipe & its fittings & labour charges complete	1 RM	488
301	LAB-00243	BMW-F.90	b) - do - labour charges only	1 RM	85
302	MAT-01870	BMW-F.91	S & F 65 mm Nominal Bore GI pipe Medium Grade properties & weight as per IS 1239 with GI fittings such as elbows tees couplings, nipples, plugs including excavation for trenches and refilling the trenches complete except for GI bends union and GI connectors with checkout and socket Tata or Zenith make or equivalent.	1 RM	844
303	MAT-01871	BMW-F.92	a) S & F 12.7 mm holder bat clamps	Each	15
304	LAB-00244	BMW-F.93	b) - do - labour charges only	Each	11
305	MAT-01872	BMW-F.94	a) S & F 19.05 mm holder bat clamps	Each	22
306	LAB-00245	BMW-F.95	b) - do - labour charges only	Each	11
307	MAT-01873	BMW-F.96	a) S & F 25.4 mm holder bat clamps	Each	29
308	LAB-00246	BMW-F.97	b) - do - labour charges only	Each	11
309	MAT-01874	BMW-F.98	a) S & F 38.1 mm holder bat clamps	Each	32
310	LAB-00247	BMW-F.99	b) - do - labour charges only	Each	13
311	MAT-01875	BMW-F.100	a) S& F 12.7x 152.0 mm NP shower rose heavy	Each	181
312	LAB-00248	BMW-F.101	b) - do - labour charges only	Each	24
313	MAT-01876	BMW-F.102	a) S& F 12.7x 137.0 mm NP shower rose heavy	Each	173
314	LAB-00249	BMW-F.103	b) - do - labour charges only	Each	26
315	MAT-01877	BMW-F.104	a) S& F 12.7x 101.6 mm NP shower rose heavy	Each	165
316	LAB-00250	BMW-F.105	b) - do - labour charges only	Each	29
317	MAT-01878	BMW-F.106	a) S & F 12.7 x 88.9 CP fancy shower	Each	291

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
318	LAB-00251	BMW-F.107	b) - do - labour charges only	Each	29
319	MAT-01879	BMW-F.108	a) Supplying & fixing 12.7 mm GI drain pipe with plug for tanks (Mud valve) including making a hole	Each	49
320	LAB-00252	BMW-F.109	b) - do - labour charges only	Each	29
321	MAT-01880	BMW-F.110	a) Supplying & fixing 19.05 mm GI drain pipe with plug for tanks (Mud valve) including making a hole	Each	69
322	LAB-00253	BMW-F.111	b) - do - labour charges only	Each	26
323	MAT-01881	BMW-F.112	a) Supplying & fixing 25.4 mm GI drain pipe with plug for tanks (Mud valve) including making a hole	Each	80
324	LAB-00254	BMW-F.113	b) - do - labour charges only	Each	30
325	MAT-01882	BMW-F.114	a) Taking branch water connection from the existing 25.4 mm GI pipe including cutting threading, etc, complete with fitting	Each	154
326	LAB-00255	BMW-F.115	b) - do - labour charges only	Each	30
327	MAT-01883	BMW-F.116	a) Taking branch water connection from the existing 19.05 mm GI pipe including cutting threading, etc, complete with fitting,	Each	89
328	LAB-00256	BMW-F.117	b) - do - labour charges only	Each	46
329	MAT-01884	BMW-F.118	a) Taking branch water connection from the existing 12.7 mm GI pipe including cutting threading, etc, complete with fitting,	Each	68
330	LAB-00257	BMW-F.119	b) - do - labour charges only	Each	39
331	MAT-01885	BMW-F.120	Supplying & fixing leather washers for 12.7 mm bib tap and stop cock	Each	2
332	MAT-01886	BMW-F.121	Supplying & fixing leather washers for 19.05 mm bib tap and stop cock	Each	4
333	MAT-01887	BMW-F.122	Supplying & Fixing 12.7 mm fibre washers	Each	4
334	MAT-01888	BMW-F.123	Supplying & Fixing 19.05 mm fibre washers	Each	4
		G	PVC PIPES & FITTINGS(Materials shall be procured from the list of approved Brands/ Manufacturers/ Suppliers)		
335	MAT-01889	BMW-G.01	a) Providing & Placing on Terrace(at all floor levels) polyethylene water storage tank of Double layer Roto moulded confirming to IS:12701 approved brand & manufacture with suitable cover/cap and suitable locking arrangement & making necessary holes for inlet & outlets and over flow pipes but without fittings & base support for tanks	1 Lit	9
336	LAB-00258	BMW-G.02	b) - do - labour charges only	1 Lit	2

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
337	MAT-01890	BMW-G.03	Supply of Plastic storage tank lid with hinges	Each	71
338	MAT-01891	BMW-G.04	Supply & Fixing 76.2 mm dia PVC elbow 1st quality	Each	46
339	MAT-01892	BMW-G.05	Supply & fixing 31.75mm dia PVC flexible waste pipe of 914.4 mm length of 1st quality	Each	25
340	MAT-01893	BMW-G.06	Supply & Fixing 38.1 mm dia PVC solid waste pipe outlet	Each	87
341	MAT-01894	BMW-G.07	Supply & fixing Fancy PVC shelf including all fittings	Each	205
342	MAT-01895	BMW-G.08	Supply & fixing of PVC low level system with internal components & short bend:10 Litres capacity Single Flush	Each	1402
343	MAT-01896	BMW-G.09	Supply & fixing of PVC low level system with internal components & short bend:10 litres capacity Dual Flush	Each	1646
344	MAT-01897	BMW-G.10	Supply & fixing of PVC low level system with internal components & short bend:8 Litres capacity single Flush	Each	793
345	MAT-01898	BMW-G.11	75 mm dia 3 M Single Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	238
346	MAT-01899	BMW-G.12	90 mm dia 3 M single Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	378
347	MAT-01900	BMW-G.13	110 mm dia 3 M Single Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	451
348	MAT-01901	BMW-G.14	75 mm dia 3 M Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	270
349	MAT-01902	BMW-G.15	90 mm dia 3 M Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	429
350	MAT-01903	BMW-G.16	110 mm dia 3 M Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	525
351	MAT-01904	BMW-G.17	75 mm dia 1828.8 mm (6'-0") Single Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	168
352	MAT-01905	BMW-G.18	90 mm dia 1828.8 mm (6'-0") Single Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	258
353	MAT-01906	BMW-G.19	110 mm dia 1828.8 mm (6'-0") Single Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	321
354	MAT-01907	BMW-G.20	75 mm dia 1828.8 mm (6'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	178
355	MAT-01908	BMW-G.21	90 mm dia 1828.8 mm (6'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	275
356	MAT-01909	BMW-G.22	110 mm dia 1828.8 mm (6'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	332
357	MAT-01910	BMW-G.23	75 mm dia 1219. mm (4'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	122
358	MAT-01911	BMW-G.24	90 mm dia 1219. mm (4'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	189
359	MAT-01912	BMW-G.25	110 mm dia 1219. mm (4'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	227
360	MAT-01913	BMW-G.26	75 mm dia 914.4mm (3'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	104
361	MAT-01914	BMW-G.27	90 mm dia 914.4mm (3'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	153
362	MAT-01915	BMW-G.28	110 mm dia 914.4mm (3'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	196
363	MAT-01916	BMW-G.29	75 mm dia 609.6mm (2'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	63

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
364	MAT-01917	BMW-G.30	90 mm dia 609.6mm (2'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	105
365	MAT-01918	BMW-G.31	110 mm dia 609.6mm (2'-0") Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	132
366	MAT-01919	BMW-G.32	160 MM dia 3 M Double Socket PVC/SWR pipe - 4 Kg/sq.cm	Each	1075
367	MAT-01920	BMW-G.33	75 mm dia 3 M Single Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	404
368	MAT-01921	BMW-G.34	90 mm dia 3 M single Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	650
369	MAT-01922	BMW-G.35	110 mm dia 3 M Single Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	772
370	MAT-01923	BMW-G.36	75 mm dia 3 M Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	441
371	MAT-01924	BMW-G.37	90 mm dia 3 M Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	699
372	MAT-01925	BMW-G.38	110 mm dia 3 M Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	852
373	MAT-01926	BMW-G.39	75 mm dia 1828.8 mm (6'-0") Single Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	266
374	MAT-01927	BMW-G.40	90 mm dia 1828.8 mm (6'-0") Single Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	411
375	MAT-01928	BMW-G.41	110 mm dia 1828.8 mm (6'-0") Single Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	489
376	MAT-01929	BMW-G.42	75 mm dia 1828.8 mm (6'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	283
377	MAT-01930	BMW-G.43	90 mm dia 1828.8 mm (6'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	429
378	MAT-01931	BMW-G.44	110 mm dia 1828.8 mm (6'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	529
379	MAT-01932	BMW-G.45	75 mm dia 1219. mm (4'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	192
380	MAT-01933	BMW-G.46	90 mm dia 1219. mm (4'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	297
381	MAT-01934	BMW-G.47	110 mm dia 1219. mm (4'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	361
382	MAT-01935	BMW-G.48	75 mm dia 914.4mm (3'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	166
383	MAT-01936	BMW-G.49	90 mm dia 914.4mm (3'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	242
384	MAT-01937	BMW-G.50	110 mm dia 914.4mm (3'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	294
385	MAT-01938	BMW-G.51	75 mm dia 609.6mm (2'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	107
386	MAT-01939	BMW-G.52	90 mm dia 609.6mm (2'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	167
387	MAT-01940	BMW-G.53	110 mm dia 609.6mm (2'-0") Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	212
388	MAT-01941	BMW-G.54	160 mm dia 3 M Double Socket PVC/SWR pipe - 6 Kg/sq.cm	Each	1757

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
389	MAT-01942	BMW-G.55	75 mm dia - Plain Bend 87.5 Degree - UPVC/SWR Pipe fittings	Each	47
390	MAT-01943	BMW-G.56	90 mm dia - Plain Bend 87.5 Degree - UPVC/SWR Pipe fittings	Each	65
391	MAT-01944	BMW-G.57	110 mm dia - Plain Bend 87.5 Degree - UPVC/SWR Pipe fittings	Each	78
392	MAT-01945	BMW-G.58	75 mm dia - Door Bend 87.5 Degree - UPVC/SWR Pipe fittings	Each	63
393	MAT-01946	BMW-G.59	90 mm dia - Door Bend 87.5 Degree - UPVC/SWR Pipe fittings	Each	88
394	MAT-01947	BMW-G.60	110 mm dia - Door Bend 87.5 Degree - UPVC/SWR Pipe fittings	Each	101
395	MAT-01948	BMW-G.61	75 mm dia - 45 Degree Bend - UPVC/SWR Pipe fittings	Each	37
396	MAT-01949	BMW-G.62	90 mm dia - 45 Degree Bend - UPVC/SWR Pipe fittings	Each	51
397	MAT-01950	BMW-G.63	110 mm dia - 45 Degree Bend - UPVC/SWR Pipe fittings	Each	65
398	MAT-01951	BMW-G.64	75 mm dia - Cleaning Pipe - UPVC/SWR Pipe fittings	Each	63
399	MAT-01952	BMW-G.65	90 mm dia - Cleaning Pipe - UPVC/SWR Pipe fittings	Each	91
400	MAT-01953	BMW-G.66	110 mm dia - Cleaning Pipe - UPVC/SWR Pipe fittings	Each	110
401	MAT-01954	BMW-G.67	75 mm dia - Single Tee - UPVC/SWR Pipe fittings	Each	56
402	MAT-01955	BMW-G.68	90 mm dia - Single Tee - UPVC/SWR Pipe fittings	Each	83
403	MAT-01956	BMW-G.69	110 mm dia - Single Tee - UPVC/SWR Pipe fittings	Each	101
404	MAT-01957	BMW-G.70	75 mm dia - Single Tee with Door - UPVC/SWR Pipe fittings	Each	68
405	MAT-01958	BMW-G.71	90 mm dia - Single Tee with Door - UPVC/SWR Pipe fittings	Each	101
406	MAT-01959	BMW-G.72	110 mm dia - Single Tee with Door - UPVC/SWR Pipe fittings	Each	121
407	MAT-01960	BMW-G.73	75 mm dia - Double Tee - UPVC/SWR Pipe fittings	Each	106
408	MAT-01961	BMW-G.74	90 mm dia - Double Tee - UPVC/SWR Pipe fittings	Each	171
409	MAT-01962	BMW-G.75	110 mm dia - Double Tee - UPVC/SWR Pipe fittings	Each	202
410	MAT-01963	BMW-G.76	75 mm dia - Double Tee with Door - UPVC/SWR Pipe fittings	Each	142
411	MAT-01964	BMW-G.77	90 mm dia - Double Tee with Door - UPVC/SWR Pipe fittings	Each	268
412	MAT-01965	BMW-G.78	110 mm dia - Double Tee with Door - UPVC/SWR Pipe fittings	Each	261
413	MAT-01966	BMW-G.79	75 mm dia - Single 'Y' - UPVC/SWR Pipe fittings	Each	70
414	MAT-01967	BMW-G.80	90 mm dia - Single 'Y' - UPVC/SWR Pipe fittings	Each	110
415	MAT-01968	BMW-G.81	110 mm dia - Single 'Y' - UPVC/SWR Pipe fittings	Each	128
416	MAT-01969	BMW-G.82	75 mm dia - Single 'Y' with Door - UPVC/SWR Pipe fittings	Each	88
417	MAT-01970	BMW-G.83	90 mm dia - Single 'Y' with Door - UPVC/SWR Pipe fittings	Each	140
418	MAT-01971	BMW-G.84	110 mm dia - Single 'Y' with Door - UPVC/SWR Pipe fittings	Each	161
419	MAT-01972	BMW-G.85	75 mm dia - Double 'Y' - UPVC/SWR Pipe fittings	Each	94

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
420	MAT-01973	BMW-G.86	90 mm dia - Double 'Y' - UPVC/SWR Pipe fittings	Each	148
421	MAT-01974	BMW-G.87	110 mm dia - Double 'Y' - UPVC/SWR Pipe fittings	Each	168
422	MAT-01975	BMW-G.88	75 mm dia - Double 'Y' with Door - UPVC/SWR Pipe fittings	Each	123
423	MAT-01976	BMW-G.89	90 mm dia - Double 'Y' with Door - UPVC/SWR Pipe fittings	Each	192
424	MAT-01977	BMW-G.90	110 mm dia - Double 'Y' with Door - UPVC/SWR Pipe fittings	Each	216
425	MAT-01978	BMW-G.91	75 mm dia - Coupler - UPVC/SWR Pipe fittings	Each	34
426	MAT-01979	BMW-G.92	90 mm dia - Coupler - UPVC/SWR Pipe fittings	Each	48
427	MAT-01980	BMW-G.93	110 mm dia - Coupler - UPVC/SWR Pipe fittings	Each	54
428	MAT-01981	BMW-G.94	90 x 75 mm dia - Reducer - UPVC/SWR Pipe fittings	Each	56
429	MAT-01982	BMW-G.95	110 x 75 mm dia - Reducer - UPVC/SWR Pipe fittings	Each	54
430	MAT-01983	BMW-G.96	90 x 110mm dia - Reducer - UPVC/SWR Pipe fittings	Each	75
431	MAT-01984	BMW-G.97	63 mm dia - Vent Cowl - UPVC/SWR Pipe fittings	Each	9
432	MAT-01985	BMW-G.98	75 mm dia - Vent Cowl - UPVC/SWR Pipe fittings	Each	14
433	MAT-01986	BMW-G.99	90 mm dia - Vent Cowl - UPVC/SWR Pipe fittings	Each	17
434	MAT-01987	BMW-G.100	110 mm dia - Vent Cowl - UPVC/SWR Pipe fittings	Each	19
435	MAT-01988	BMW-G.101	40 mm dia - Pipe Clip - UPVC/SWR Pipe fittings - Pipe Clip - UPVC/SWR Pipe fittings	Each	10
436	MAT-01989	BMW-G.102	50 mm dia - Pipe Clip - UPVC/SWR Pipe fittings	Each	14
437	MAT-01990	BMW-G.103	63 mm dia - Pipe Clip - UPVC/SWR Pipe fittings	Each	14
438	MAT-01991	BMW-G.104	75 mm dia - Pipe Clip - UPVC/SWR Pipe fittings	Each	16
439	MAT-01992	BMW-G.105	90 mm dia - Pipe Clip - UPVC/SWR Pipe fittings	Each	17
440	MAT-01993	BMW-G.106	110 mm - Pipe Clip - UPVC/SWR Pipe fittings	Each	18
441	MAT-01994	BMW-G.107	160 mm dia - Pipe Clip - UPVC/SWR Pipe fittings	Each	34
442	MAT-01995	BMW-G.108	P' Trap (Small without Air vent) 110 mm - UPVC/SWR Pipe fittings	Each	175
443	MAT-01996	BMW-G.109	P' Trap (Small with Air vent) 110 mm - UPVC/SWR Pipe fittings	Each	194
444	MAT-01997	BMW-G.110	P' Trap (Big with Air vent) 110 mm - UPVC/SWR Pipe fittings	Each	221
445	MAT-01998	BMW-G.111	P' Trap (Big without Air vent) 110 mm - UPVC/SWR Pipe fittings	Each	204
446	MAT-01999	BMW-G.112	Floor Trap (Bell Mouth) 110 mm - UPVC/SWR Pipe fittings	Each	212
447	MAT-02000	BMW-G.113	Bell Mouth Trap 7 " (177.8 mm) - UPVC/SWR Pipe fittings	Each	308

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
448	MAT-02001	BMW-G.114	4" (101.6 mm) Nahany Trap (Without Jali with inlet)UPVC/SWR Pipe fittings	Each	91
449	MAT-02002	BMW-G.115	3" (76.2 mm) Nahany Trap (without Jali without inlet)UPVC/SWR Pipe fittings	Each	82
450	MAT-02003	BMW-G.116	4" (101.6 mm) Nahany Trap (without inlet with out Jali)UPVC/SWR Pipe fittings	Each	91
451	MAT-02004	BMW-G.117	Mini Trap - UPVC/SWR Pipe fittings	Each	50
452	MAT-02005	BMW-G.118	3" (76.2 mm) Nahany Trap with Jali - UPVC/SWR Pipe fittings	Each	94
453	MAT-02006	BMW-G.119	4" (101.6 mm) multi floor trap with Jali- UPVC/SWR Pipe fittings	Each	135
454	MAT-02007	BMW-G.120	4" (101.6) multi floor trap with out Jalli- UPVC/SWR Pipe fittings	Each	105
455	MAT-02008	BMW-G.121	Round Jali - UPVC/SWR Pipe fittings	Each	23
456	MAT-02009	BMW-G.122	Square tile & Jalli - UPVC/SWR Pipe fittings	Each	37
457	MAT-02010	BMW-G.123	Pipe connector(with LIP ring) - UPVC/SWR Pipe fittings	Each	135
458	MAT-02011	BMW-G.124	Pipe connector(with out LIP ring) - UPVC/SWR Pipe fittings	Each	109
459	MAT-02012	BMW-G.125	4" (101.6 mm) Floor Trap - UPVC/SWR Pipe fittings	Each	130
460	MAT-02013	BMW-G.126	5" (127.mm) floor Trap - UPVC/SWR Pipe fittings	Each	137
461	MAT-02014	BMW-G.127	75 mm dia - Door cap - UPVC/SWR Pipe fittings	Each	35
462	MAT-02015	BMW-G.128	90 mm dia - Door cap - UPVC/SWR Pipe fittings	Each	60
463	MAT-02016	BMW-G.129	110 mm dia - Door cap - UPVC/SWR Pipe fittings	Each	50
464	MAT-02017	BMW-G.130	75 mm dia - Socket plug - UPVC/SWR Pipe fittings	Each	34
465	MAT-02018	BMW-G.131	90 mm dia - Socket plug - UPVC/SWR Pipe fittings	Each	58
466	MAT-02019	BMW-G.132	110 mm dia - Socket plug - UPVC/SWR Pipe fittings	Each	60
467	MAT-02020	BMW-G.133	75 mm dia - Rubber ring for Socket - UPVC/SWR Pipe fittings	Each	8
468	MAT-02021	BMW-G.134	90 mm dia - Rubber ring for Socket - UPVC/SWR Pipe fittings	Each	9
469	MAT-02022	BMW-G.135	110 mm dia - Rubber ring for Socket - UPVC/SWR Pipe fittings	Each	10
470	MAT-02023	BMW-G.136	75 mm dia - Door Socket - UPVC/SWR Pipe fittings	Each	9

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
471	MAT-02024	BMW-G.137	90 mm dia - Door Socket - UPVC/SWR Pipe fittings	Each	10
472	MAT-02025	BMW-G.138	110 mm dia - Door Socket - UPVC/SWR Pipe fittings	Each	14
473	MAT-02026	BMW-G.139	LIP ring 110 mm - UPVC/SWR Pipe fittings	Each	64
474	MAT-02027	BMW-G.140	Rubber Lubricant - 100 Grams	Each	25
475	MAT-02028	BMW-G.141	Rubber Lubricant- 250Grams	Each	48
476	MAT-02029	BMW-G.142	Rubber Lubricant - 500 Grams	Each	86
477	MAT-02030	BMW-G.143	Rubber Lubricant - 1000 Grams	Each	204
478	MAT-02031	BMW-G.144	P' Trap with lip UPVC/SWR Pipe fittings	Each	278
479	MAT-02032	BMW-G.145	50 ml - Solvent Cement	Each	16
480	MAT-02033	BMW-G.146	100 ml - Solvent Cement	Each	24
481	MAT-02034	BMW-G.147	250 ml - Solvent Cement	Each	56
482	MAT-02035	BMW-G.148	500 ml - Solvent Cement	Each	108
483	MAT-02036	BMW-G.149	1000 ml - Solvent Cement	Each	212
484	MAT-02037	BMW-G.150	110mm x 90 mm - Internal Reducer - UPVC/SWR Pipe fittings	Each	84
485	MAT-02038	BMW-G.151	160 mm x 110 mm - Internal Reducer - UPVC/SWR Pipe fittings	Each	210
486	LAB-00259	BMW-G.152	Labour charges for laying, fixing and commissioning the PVC pipes including couplers/ bends/ tees etc any diameter including fixing necessary fittings like bends, plugs, couplers, junctions, tees, etc with solvent jointing as per standard practice	1 RM	85
		H	CENTRIFUGAL CAST IRON PIPES & FITTINGS AS PERIS: 3989 - 1984		
487	MAT-02039	BMW-H.01	75 mm dia CI (spun) soils Waste & Ventilating pipe (3 M)	Each	1399
488	MAT-02040	BMW-H.02	100 mm dia CI (spun) soils Waste & Ventilating pipe (3 M)	Each	1862
489	MAT-02041	BMW-H.03	150 mm dia CI (spun) soils Waste & Ventilating pipe (3 M)	Each	3412
490	MAT-02042	BMW-H.04	75 mm dia CI (spun) soils Waste & Ventilating pipe (3 M) Double socket	Each	1552
491	MAT-02043	BMW-H.05	100 mm dia CI (spun) soils Waste & Ventilating pipe (3 M) Double socket	Each	2094
492	MAT-02044	BMW-H.06	75 mm dia 9'-0" (2743.2 mm) CI (Spun) pipes	Each	1257

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
493	MAT-02045	BMW-H.07	100 mm dia 9'-0" (2743.2 mm) CI (Spun) pipes	Each	1680
494	MAT-02046	BMW-H.08	75 mm dia 8'-0" (2438.4 mm) CI (Spun) pipes	Each	1125
495	MAT-02047	BMW-H.09	100 mm dia 8'-0" (2438.4 mm) CI (Spun) pipes	Each	1495
496	MAT-02048	BMW-H.10	75 mm dia 6'-0" (1828.8 mm) CI (Spun) pipes	Each	915
497	MAT-02049	BMW-H.11	100 mm dia 6'-0" (1828.8 mm) CI (Spun) pipes	Each	1193
498	MAT-02050	BMW-H.12	75 mm dia 6'-0" (1828.8 mm) Double Socket CI (Spun) pipes	Each	962
499	MAT-02051	BMW-H.13	100 mm dia 6'-0" (1828.8 mm) Double Socket CI (Spun) pipes	Each	1193
500	MAT-02052	BMW-H.14	75 mm dia Cut pipes (pieces) 1 foot (304.8 mm) CI (Spun) fittings	Each	334
501	MAT-02053	BMW-H.15	100 mm dia Cut pipes (pieces) 1 foot (304.8 mm) CI (Spun) fittings	Each	384
502	MAT-02054	BMW-H.16	75 mm dia Cut pipes (pieces) 1'.6" (457.2 mm) CI (Spun) fittings	Each	478
503	MAT-02055	BMW-H.17	100 mm dia Cut pipes (pieces) 1'.6" (457.2 mm) CI (Spun) fittings	Each	550
504	MAT-02056	BMW-H.18	150 mm dia Cut pipes (pieces) 1'.6" (457.2 mm) CI (Spun) fittings	Each	1049
505	MAT-02057	BMW-H.19	75 mm dia Cut pipes (pieces) 2 feet (609.6 mm) CI (Spun) fittings	Each	660
506	MAT-02058	BMW-H.20	100 mm dia Cut pipes (pieces) 2 feet (609.6 mm) CI (Spun) fittings	Each	727
507	MAT-02059	BMW-H.21	150 mm dia Cut pipes (pieces) 2 feet (609.6 mm) CI (Spun) fittings	Each	1314
508	MAT-02060	BMW-H.22	75 mm dia Cut pipes (pieces) 3 feet (914.4 mm) CI (Spun) fittings	Each	1012
509	MAT-02061	BMW-H.23	100 mm dia Cut pipes (pieces) 3 feet (914.4 mm) CI (Spun) fittings	Each	1364
510	MAT-02062	BMW-H.24	75 mm dia Cut pipes (pieces) 4 feet (1219.2 mm) CI (Spun) fittings	Each	1112
511	MAT-02063	BMW-H.25	100 mm dia Cut pipes (pieces) 4 feet (1219.2 mm) CI (Spun) fittings	Each	1664
512	MAT-02064	BMW-H.26	75 mm dia Plain Bend - CI (Spun) fittings	Each	343
513	MAT-02065	BMW-H.27	100 mm dia Plain Bend - CI (Spun) fittings	Each	405
514	MAT-02066	BMW-H.28	150 mm dia Plain Bend - CI (Spun) fittings	Each	962
515	MAT-02067	BMW-H.29	75 mm dia Door Bend - CI (Spun) fittings	Each	356
516	MAT-02068	BMW-H.30	100 mm dia Door Bend - CI (Spun) fittings	Each	461
517	MAT-02069	BMW-H.31	150 mm dia Door Bend - CI (Spun) fittings	Each	1054
518	MAT-02070	BMW-H.32	75 mm dia Plain Bend 45 Degrees - CI (Spun) fittings	Each	343
519	MAT-02071	BMW-H.33	100 mm dia Plain Bend 45 Degrees - CI (Spun) fittings	Each	405
520	MAT-02072	BMW-H.34	150 mm dia Plain Bend 45 Degrees - CI (Spun) fittings	Each	962
521	MAT-02073	BMW-H.35	75 mm dia Door Bend 45 Degrees - CI (Spun) fittings	Each	356

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
522	MAT-02074	BMW-H.36	100 mm dia Door Bend 45 Degrees - CI (Spun) fittings	Each	461
523	MAT-02075	BMW-H.37	150 mm dia Door Bend 45 Degrees - CI (Spun) fittings	Each	1054
524	MAT-02076	BMW-H.38	Horn Bend Plain 101.6 x 50.8 mm (4" x 2") 100 mm dia - CI (Spun) fittings	Each	699
525	MAT-02077	BMW-H.39	Horn Bend door 101.6 x 50.8 mm (4" x 2") 100 mm dia - CI (Spun) fittings	Each	817
526	MAT-02078	BMW-H.40	75 mm dia Heel Rest Bend - CI (Spun) fittings	Each	365
527	MAT-02079	BMW-H.41	100 mm dia Heel Rest Bend - CI (Spun) fittings	Each	467
528	MAT-02080	BMW-H.42	150 mm dia Heel Rest Bend - CI (Spun) fittings	Each	993
529	MAT-02081	BMW-H.43	75 mm dia Single Branch Plain "T" - CI (Spun) fittings	Each	461
530	MAT-02082	BMW-H.44	100 mm dia Single Branch Plain "T" - CI (Spun) fittings	Each	621
531	MAT-02083	BMW-H.45	150 mm dia Single Branch Plain "T" - CI (Spun) fittings	Each	1283
532	MAT-02084	BMW-H.46	75 mm dia Single Branch Door "T" - CI (Spun) fittings	Each	544
533	MAT-02085	BMW-H.47	100 mm dia Single Branch Door "T" - CI (Spun) fittings	Each	720
534	MAT-02086	BMW-H.48	150 mm dia Single Branch Door "T" - CI (Spun) fittings	Each	1353
535	MAT-02087	BMW-H.49	75 mm dia Single Branch plain "Y" - CI (Spun) fittings	Each	544
536	MAT-02088	BMW-H.50	100 mm dia Single Branch plain "Y" - CI (Spun) fittings	Each	720
537	MAT-02089	BMW-H.51	150 mm dia Single Branch plain "Y" - CI (Spun) fittings	Each	1589
538	MAT-02090	BMW-H.52	75 mm dia Single Branch Door "Y" - CI (Spun) fittings	Each	595
539	MAT-02091	BMW-H.53	100 mm dia Single Branch Door "Y" - CI (Spun) fittings	Each	796
540	MAT-02092	BMW-H.54	150 mm dia Single Branch Door "Y" - CI (Spun) fittings	Each	1711
541	MAT-02093	BMW-H.55	75 mm dia Double Branch Plain "T" - CI (Spun) fittings	Each	628
542	MAT-02094	BMW-H.56	100 mm dia Double Branch Plain "T" - CI (Spun) fittings	Each	847
543	MAT-02095	BMW-H.57	75 mm dia Double Branch Door "T" - CI (Spun) fittings	Each	701
544	MAT-02096	BMW-H.58	100 mm dia Double Branch Door "T" - CI (Spun) fittings	Each	884
545	MAT-02097	BMW-H.59	75 mm dia Double Branch Plain "Y" - CI (Spun) fittings	Each	701
546	MAT-02098	BMW-H.60	100 mm dia Double Branch Plain "Y" - CI (Spun) fittings	Each	884
547	MAT-02099	BMW-H.61	75 mm dia Double Branch Door "Y" - CI (Spun) fittings	Each	739
548	MAT-02100	BMW-H.62	100 mm dia Double Branch Door "Y" - CI (Spun) fittings	Each	958
549	MAT-02101	BMW-H.63	75 mm dia Shoe Bend - CI (Spun) fittings	Each	435
550	MAT-02102	BMW-H.64	100 mm dia Shoe Bend - CI (Spun) fittings	Each	508
551	MAT-02103	BMW-H.65	150 mm dia Shoe Bend - CI (Spun) fittings	Each	1030
552	MAT-02104	BMW-H.66	75 mm dia Collar - CI (Spun) fittings	Each	297
553	MAT-02105	BMW-H.67	100 mm dia Collar - CI (Spun) fittings	Each	360
554	MAT-02106	BMW-H.68	150 mm dia Collar - CI (Spun) fittings	Each	739
555	MAT-02107	BMW-H.69	75 mm dia Cowl - CI (Spun) fittings	Each	263
556	MAT-02108	BMW-H.70	100 mm dia Cowl - CI (Spun) fittings	Each	297
557	MAT-02109	BMW-H.71	150 mm dia Cowl - CI (Spun) fittings	Each	665

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
558	MAT-02110	BMW-H.72	75 mm dia Offset 3" (76.2 mm) projection - CI (Spun) fittings	Each	340
559	MAT-02111	BMW-H.73	100 mm dia Offset 3" (76.2 mm) projection - CI (Spun) fittings	Each	461
560	MAT-02112	BMW-H.74	150 mm dia Offset 3" (76.2 mm) projection - CI (Spun) fittings	Each	930
561	MAT-02113	BMW-H.75	75 mm dia Offset 6" (152.4mm) projection - CI (Spun) fittings	Each	416
562	MAT-02114	BMW-H.76	100 mm dia Offset 6" (152.4mm) projection - CI (Spun) fittings	Each	544
563	MAT-02115	BMW-H.77	150 mm dia Offset 6" (152.4mm) projection - CI (Spun) fittings	Each	1082
564	MAT-02116	BMW-H.78	75 mm diaLong Door Bend - CI (Spun) fittings	Each	872
565	MAT-02117	BMW-H.79	100 mm diaLong Door Bend - CI (Spun) fittings	Each	938
566	MAT-02118	BMW-H.80	75 mm dia Hand Hole pipe (Inspection pipe)	Each	501
567	MAT-02119	BMW-H.81	100 mm dia Hand Hole pipe (Inspection pipe)	Each	683
568	MAT-02120	BMW-H.82	150 mm dia Hand Hole pipe (Inspection pipe)	Each	909
569	MAT-02121	BMW-H.83	75 mm dia P Traps - CI (Spun) fittings	Each	544
570	MAT-02122	BMW-H.84	100 mm dia P Traps - CI (Spun) fittings	Each	744
571	MAT-02123	BMW-H.85	4" x 3" (101.6 mm x 76.2mm) P. Traps 100 mm dia - CI (Spun) fittings	Each	853
572	MAT-02124	BMW-H.86	4" x 3" (101.6 mm x 76.2mm) Vent Traps 100 mm dia - CI (Spun) fittings	Each	853
573	MAT-02125	BMW-H.87	4" x 3" (101.6 mm x 76.2mm) Reducer 75 mm dia - CI (Spun) fittings	Each	530
574	MAT-02126	BMW-H.88	6" x 4" (152.4 mm x101.6 mm) Reducer 75 mm dia - CI (Spun) fittings	Each	725
575	MAT-02127	BMW-H.89	3" x 2" (76.2 mm x 50.8 mm) plain T 75 mm dia - CI (Spun) fittings	Each	452
576	MAT-02128	BMW-H.90	3" x 2" (76.2 mm x 50.8 mm) Door T 75 mm dia - CI (Spun) fittings	Each	707
577	MAT-02129	BMW-H.91	3" x 2" (76.2 mm x 50.8 mm) Plain Y 75 mm dia - CI (Spun) fittings	Each	707
578	MAT-02130	BMW-H.92	3" x 2" (76.2 mm x 50.8 mm) Door Y 75 mm dia - CI (Spun) fittings	Each	707
579	MAT-02131	BMW-H.93	4" x 3" (101.6 mm x 76.2mm) Plain T75 mm dia - CI (Spun) fittings	Each	707
580	MAT-02132	BMW-H.94	4" x 3" (101.6 mm x 76.2mm) Door T75 mm dia - CI (Spun) fittings	Each	748
581	MAT-02133	BMW-H.95	4" x 3" (101.6 mm x 76.2mm) Plain Y75 mm dia - CI (Spun) fittings	Each	748
582	MAT-02134	BMW-H.96	4" x 3" (101.6 mm x 76.2mm) DoorY75 mm dia - CI (Spun) fittings	Each	800
583	MAT-02135	BMW-H.97	6" x 4" (152.4 mm x101.6 mm) Plain T 75 mm dia - CI	Each	1046

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
			(Spun) fittings		
584	MAT-02136	BMW-H.98	6" x 4" (152.4 mm x101.6 mm)Door T 75 mm dia - CI (Spun) fittings	Each	1133
585	MAT-02137	BMW-H.99	6" x 4" (152.4 mm x101.6 mm) Plain Y 75 mm dia - CI (Spun) fittings	Each	1200
586	MAT-02138	BMW-H.100	6" x 4" (152.4 mm x101.6 mm)DoorY 75 mm dia - CI (Spun) fittings	Each	1465
587	MAT-02139	BMW-H.101	75 mm diaPlain " T" 27 " (685.8 mm) Special Types of Long Fittings	Each	1519
588	MAT-02140	BMW-H.102	100 mm dia - Plain " T" 27 " (685.8 mm) Special Types of Long CI (Spun) fittings	Each	2132
589	MAT-02141	BMW-H.103	75 mm dia Door "T" 27" (685.8 mm)Special Types of Long CI (Spun) fittings	Each	1696
590	MAT-02142	BMW-H.104	100mm dia Door "T" 27" (685.8 mm)Special Types of Long CI (Spun) fittings	Each	2343
591	MAT-02143	BMW-H.105	75 mm diaPlain " Y" 27" (685.8 mm) Special Types of Long CI (Spun) fittings	Each	1696
592	MAT-02144	BMW-H.106	100mm diaPlain " Y" 27" (685.8 mm) Special Types of Long CI (Spun) fittings	Each	2343
593	MAT-02145	BMW-H.107	75 mm dia Door " Y" 27" (685.8 mm)Special Types of Long CI (Spun) fittings	Each	1890
594	MAT-02146	BMW-H.108	100mm dia Door " Y" 27" (685.8 mm)Special Types of Long CI (Spun) fittings	Each	2573
		I	MISCELLANEOUS ITEMS		
595	MAT-02147	BMW-I.01	a) Supplying & Fixing solder joints up to 50.8 mm dia	Each	63
596	LAB-00260	BMW-I.02	b) - do - labour charges only	Each	23
597	MAT-02148	BMW-I.03	a) Supplying & Fixing solution joints up to 50.8 dia 1st quality.	Each	14
598	LAB-00261	BMW-I.04	b) - do - labour charges only	Each	3
599	MAT-02149	BMW-I.05	Chiselling the stone masonry wall for fixing of wooden blocks including finishing as directed by the department	Each	35
600	MAT-02150	BMW-I.06	Chiselling the stone masonry wall and repairs as directed by the department.	1 Rm	165
601	MAT-02151	BMW-I.07	Chiselling the brick masonry wall and repairs as directed by the department.	1 Rm	35
602	MAT-02152	BMW-I.08	a) S & F NP telephonic shower spray set & valve mixer with rest and all fittings complete (ARK/ESSCO or equivalent make)	Each	2119
603	LAB-00262	BMW-I.09	b) - do - labour charges only	Each	502
604	MAT-02153	BMW-I.10	a) S & F NP shower spray fancy with NP Flexible pipe	Each	568
605	LAB-00263	BMW-I.11	b) - do - labour charges only	Each	167
606	MAT-02154	BMW-I.12	a) S & F NP cover for Nahany trap	Each	33
607	LAB-00264	BMW-I.13	b) - do - labour charges only	Each	23
608	MAT-02155	BMW-I.14	a) Painting the flushing tank with white enamel paint	Each	120

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
609	LAB-00265	BMW-I.15	b) - do - labour charges only	Each	81
610	MAT-02156	BMW-I.16	S & F internal fittings for flush tank Parryplast wonder flush or equivalent	Each	776
611	MAT-02157	BMW-I.17	Repairing and over hauling flushing tank	Each	92
612	MAT-02158	BMW-I.18	a) Supplying & Fixing NP chain rubber and plug for basin	Each	42
613	LAB-00266	BMW-I.19	b) - do - labour charges only	Each	9
614	MAT-02159	BMW-I.20	a) S & F 25.4 mm dia& 609.6 mm long aluminium anodized towel rod with brackets and aluminium screws	Each	164
615	LAB-00267	BMW-I.21	b) - do - labour charges only	Each	56
616	MAT-02160	BMW-I.22	a) S & F 19.04 mm dia& 609.6 mm long aluminium anodized towel rod with brackets and aluminium screws	Each	146
617	LAB-00268	BMW-I.23	b) - do - labour charges only	Each	85
618	MAT-02161	BMW-I.24	a) S & F 609.6 mm long 127 mm wide plate glass shelf with superior quality aluminium railing complete with aluminium screws	Each	208
619	LAB-00269	BMW-I.25	b) - do - labour charges only	Each	70
620	MAT-02162	BMW-I.26	a) S & F 609.6 mm long 127 mm wide plate glass shelf only	Each	68
621	LAB-00270	BMW-I.27	b) - do - labour charges only	Each	15
622	MAT-02163	BMW-I.28	a) S & F NP soap dish heavy type with NP SCREWS	Each	233
623	LAB-00271	BMW-I.29	b) - do - labour charges only	Each	16
624	MAT-02164	BMW-I.30	a) S & F NP holder brackets with screws	Each	49
625	LAB-00272	BMW-I.31	b) - do - labour charges only	Each	18
626	MAT-02165	BMW-I.32	a) S & F liquid soap container NP metallic with NP brackets and screws.	Each	234
627	LAB-00273	BMW-I.33	b) - do - labour charges only	Each	29
628	MAT-02166	BMW-I.34	a) S & F 31.75 mm C.P TRAPS	Each	306
629	LAB-00274	BMW-I.35	b) - do - labour charges only	Each	56
630	MAT-02167	BMW-I.36	a) Supplying & fixing 88.9 mm A.C cowl	Each	70
631	LAB-00275	BMW-I.37	b) - do - labour charges only	Each	18
632	MAT-02168	BMW-I.38	a)Supplying & fixing A.CCowl 63.5 mm dia	Each	48
633	LAB-00276	BMW-I.39	b) - do - labour charges only	Each	15
634	MAT-02169	BMW-I.40	Removing and refixing W.C s	Each	219
635	MAT-02170	BMW-I.41	Removing and refixing wash hand basins of any size with fittings complete	Each	210
636	MAT-02171	BMW-I.42	a)S & F 76.2 x 101.6 mm teak wood block complete	Each	26
637	LAB-00277	BMW-I.43	b) - do - labour charges only	Each	13
638	LAB-00278	BMW-I.44	Cutting holes in C.C; basement & repairs Labour charges only	Each	130
639	LAB-00279	BMW-I.45	Cutting holes in stone masonry& basement and repairs Labour charges only	Each	87
640	LAB-00280	BMW-I.46	Cutting holes in Brick masonry& repairs Labour charges	Each	58

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
			only		
641	LAB-00281	BMW-I.47	Cutting holes in RCC slab floor & repairs Labour charges only	Each	87
642	MAT-02172	BMW-I.48	a)Supplying & Fixing 12.7 mm PVC connection with brass union nut C.P coated	Each	96
643	LAB-00282	BMW-I.49	b) - do - labour charges only	Each	21
644	MAT-02173	BMW-I.50	a) S & F 12.7 mm .M.P couplings	Each	35
645	LAB-00283	BMW-I.51	b) - do - labour charges only	Each	15
646	MAT-02174	BMW-I.52	a) S & F 19.05 mm M.P couplings	Each	42
647	LAB-00284	BMW-I.53	b) - do - labour charges only	Each	15
648	MAT-02175	BMW-I.54	a) S& F MP coupling 25.4 mm dia	Each	92
	LAB-00285		b) - do - labour charges only	Each	15
649	MAT-02176	BMW-I.55	a) S & FPVC Rubber adopter for LLC and bend	Each	20
650	LAB-00286	BMW-I.56	b) - do - labour charges only	Each	10
651	MAT-02177	BMW-I.57	a) S& F 31.75 mm Brass union nuts	Each	35
652	LAB-00287	BMW-I.58	b) - do - labour charges only	Each	9
653	MAT-02178	BMW-I.59	a) S& F 38.1 mm Brass union nuts	Each	38
654	LAB-00288	BMW-I.60	b) - do - labour charges only	Each	13
655	MAT-02179	BMW-I.61	a) Constructing Brick masonry chamber over the gully trap or peet valve and fitted with 304.8 x 228.6 m size CI frame and hinged cover.	Each	472
656	LAB-00289	BMW-I.62	b) - do - labour charges only	Each	125
657	MAT-02180	BMW-I.63	a) Constructing Brick masonry support for G.I pipe with C.M 304.8 x 228.6 x228.6 mm size includingplastering and finishing etc. complete.	Each	77
658	LAB-00290	BMW-I.64	b) - do - labour charges only	Each	28
659	MAT-02181	BMW-I.65	a) Supplying & fixing 304.8 x 228.6 mm CI frame & cover over gully taps	Each	123
660	LAB-00291	BMW-I.66	b) - do - labour charges only	Each	44
661	MAT-02182	BMW-I.67	a) Supplying & fixing CI Nahany trap grating	Each	22
662	LAB-00292	BMW-I.68	b) - do - labour charges only	Each	15
663	MAT-02183	BMW-I.69	a) Supplying & fixing CI gully trap grating	Each	50
664	LAB-00293	BMW-I.70	b) - do - labour charges only	Each	15
665	MAT-02184	BMW-I.71	a) Supplying & fixing valves for brass ball cocks 25.4 mm dia	Each	20
666	LAB-00294	BMW-I.72	b) - do - labour charges only	Each	13
667	MAT-02185	BMW-I.73	a) Supplying & fixing 12.7 m valve for bib tap or stop cocks	Each	19
668	LAB-00295	BMW-I.74	b) - do - labour charges only	Each	9
669	MAT-02186	BMW-I.75	a) Supplying & fixing 19.05 m valve for bib tap or stop cocks	Each	40
670	LAB-00296	BMW-I.76	b) - do - labour charges only	Each	15

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
671	MAT-02187	BMW-I.77	Removing 12.7 mm Glpipe and refixing the same	Mr.	66
672	MAT-02188	BMW-I.78	Removing 19.05 mm Glpipe and refixing the same	Mr.	73
673	MAT-02189	BMW-I.79	Removing 25.4 mm Glpipe and refixing the same	Mr.	109
674	MAT-02190	BMW-I.80	Removing 38.1 mm Glpipe and refixing the same	Rm	138
675	MAT-02191	BMW-I.81	Removing 50.8 mm Glpipe and refixing the same	Rm	161
676	MAT-02192	BMW-I.82	Cleaning the W.C with acid and Vim powder	Each	45
677	MAT-02193	BMW-I.83	Cleaning the Urinal with acid and Vim power	Each	45
678	MAT-02194	BMW-I.84	Cleaning the wash basin with acid and Vim powder	Each	45
679	MAT-02195	BMW-I.85	Cleaning theE.W.C with acid and Vim power	Each	45
680	MAT-02196	BMW-I.86	Supplying & fixing 914.4 x 457.2 mm CI man hole frame and cover (light weight) 30 Kgs	Each	1936
681	MAT-02197	BMW-I.87	Supplying & fixing 602 x 602 mm CI man hole frame and cover (light weight) 30 Kgs	Each	2866
682	LAB-00297	BMW-I.88	b) - do - labour charges only	Each	175
683	MAT-02198	BMW-I.89	a) Supplying & fixing CI steps for septic tank.	Each	64
684	LAB-00298	BMW-I.90	b) - do - labour charges only	Each	15
685	MAT-02199	BMW-I.91	a) Supplying & fixing 50.8cm dia C.I. Man hole frame & cover for 914.4 mm dia chamber (20 Kgs - Light weight)	Each	1253
686	LAB-00299	BMW-I.92	b) - do - labour charges only	Each	175
687	MAT-02200	BMW-I.93	a) Supplying & fixing 50.8cm dia C.I. Man hole frame & cover for 914.4 mm dia chamber(Medium weight) as per IS:1726 - 40 Kgs	Each	2600
688	LAB-00300	BMW-I.94	b) - do - labour charges only	Each	445
689	LAB-00301	BMW-I.95	Cost. 50.8 mm thick RCM baffle wall with 2.267 Kg steel & rabbit wire mesh in CM 1:3 with fine rendering in neat cement labour charges Only	1Sqm	237
690	MAT-02201	BMW-I.96	a) Cost. 50.8 mm RCC partition wall	1Sqm	266
691	LAB-00302	BMW-I.97	b) - do - labour charges only	1 Sqm	56
692	MAT-02202	BMW-I.98	a)S& F double layer of bamboo matting tarred on both sides.	10 Sqm	611
693	LAB-00303	BMW-I.99	b) - do - labour charges only	10 Sqm	153
694	MAT-02203	BMW-I.100	Removing of 101.6 m or 76.2 mm CI pipe	1 RM	35
695	MAT-02204	BMW-I.101	a) Supplying & fixing 76.2 mm W.I clamps	Each	26
696	LAB-00304	BMW-I.102	b) - do - labour charges only	Each	13
697	MAT-02205	BMW-I.103	a) Supplying & fixing NP coat hook	Each	46
698	LAB-00305	BMW-I.104	b) - do - labour charges only	Each	15
699	MAT-02206	BMW-I.105	a) Supplying and fixing TV shape mirror with plastic frame size 609.6 mm x 457 .2 mm	Each	507
700	LAB-00306	BMW-I.106	b) - do - labour charges only	Each	142
701	MAT-02207	BMW-I.107	a) Supplying & fixing GI pipe plug of size 12.7 mm dia	Each	11

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
702	LAB-00307	BMW-I.108	b) - do - labour charges only	Each	2
703	MAT-02208	BMW-I.109	a) Supplying & fixing 19.06 mm dia GI plug	Each	15
704	LAB-00308	BMW-I.110	b) - do - labour charges only	Each	2
705	MAT-02209	BMW-I.111	a) Supplying and fixing 38.1 mm dia of GI plug	Each	70
706	LAB-00309	BMW-I.112	b) - do - labour charges only	Each	13
707	MAT-02210	BMW-I.113	a) Supplying & fixing 50.8 mm dia of GI PLUG	Each	107
708	LAB-00310	BMW-I.114	b) - do - labour charges only	Each	15
709	MAT-02211	BMW-I.115	a) Supplying & fixing 76.2 mm dia of GI PLUG	Each	192
710	LAB-00311	BMW-I.116	b) - do - labour charges only	Each	23
711	MAT-02212	BMW-I.117	a) Supplying & fixing C.P flange.	Each	26
712	LAB-00312	BMW-I.118	b) - do - labour charges only	Each	11
713	MAT-02213	BMW-I.119	a) Supplying & fixing stainless steel sink size 36" x 18" (914.4x457.2mm) 1 mm thick with accessories	Each	7233
714	LAB-00313	BMW-I.120	b) - do - labour charges only	Each	633
715	MAT-02214	BMW-I.121	a) Supplying & fixing SINGLE BOWL stainless steel sink size 24"x18"x8 "(609.6 x 457.2 x 203.2mm) 1 mm thick with accessories	Each	5701
716	LAB-00314	BMW-I.122	b) - do - labour charges only	Each	613
717	MAT-02215	BMW-I.123	a) Supplying & fixing stainless steel sink size 20" x18" x 8 "(508x457.2x203.2mm) 1 mm thick with accessories	Each	5184
718	MAT-02216	BMW-I.124	b) - do - labour charges only	Each	562
719	MAT-02217	BMW-I.125	Supplying & fixing 4 " x 24 " (101.6x609.6mm) white glazed porcelain channel fixed in brick masonry white cement pointing.	Each	527
720	MAT-02218	BMW-I.126	Supply & Fixing of steel surgical long elbow action handle 12.7 mm dia bib cock Indian make heavy type including all materials	Each	954
721	MAT-02219	BMW-I.127	Supply & fixing 2 1/2" (63.5mm) dia Sluice valve ISI mark with 2 Nos. flanges, 8 nos, 3/4" dia nuts & bolts and all necessary washers and packing materials etc. complete	Each	5222
722	MAT-02220	BMW-I.128	Supply & fixing porcelain P' trap	Each	225
723	MAT-02221	BMW-I.129	Supplying & fixing oval shape basin white (520x410mm)parry or equivalent	Each	2390
724	MAT-02222	BMW-I.130	Supply & fixing RCC cover 22" dia with nominal reinforcement 3 " thick and hooks for lifting	Each	707
725	MAT-02223	BMW-I.131	Supply & fixing cp spl. Grating with frame and cover of 1st quality	Each	61
726	MAT-02224	BMW-I.132	Supply & fixing towel rod (CP) of 24" long and 3/4 " dia	Each	382
727	MAT-02225	BMW-I.133	Supply & fixing of LLC handle set 1stquality	Each	76
728	MAT-02226	BMW-I.134	Mechanical Cleaning of water sumps with pumps & UV disinfecting	1000 Lit	53
729	MAT-02227	BMW-I.135	Supply & fixing 4" dia CP thimble pipe: 150 mm long	Each	399
730	MAT-02228	BMW-I.136	Supply & fixing 4" dia CP thimble pipe:220 mm long	Each	595

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
731	MAT-02229	BMW-I.137	Supply & fixing 4" dia CP thimble pipe: 300 mm long	Each	794
732	MAT-02230	BMW-I.138	Supply & fixing CP long bend	Each	336
733	MAT-02231	BMW-I.139	Supply & fixing CP short bend	Each	169
734	MAT-02232	BMW-I.140	Supplying & fixing 15 mm bib tap with flange Chromeum plated	Each	1658
735	MAT-02233	BMW-I.141	Supply & fixing bib cock cum health faucet with 1 m long flexible tube and wall hook with 7 years warranty Chrome plated	Each	4200
736	MAT-02234	BMW-I.142	Supply & fixing 2 in 1 bib cock cum health faucet with 1 m long flexible tube and wall hook with 7 years warranty: Ivory gold	Each	7063
737	MAT-02235	BMW-I.143	Supply & fixing pillar cock with 7years warranty: Chrome plated	Each	1741
738	MAT-02236	BMW-I.144	Supply & fixing pillar cock with 7years warranty: Ivory gold	Each	2972
739	MAT-02237	BMW-I.145	Supply & fixing Angular stop cocks with wall flange with 7 years warranty: Chrome plated	Each	1718
740	MAT-02238	BMW-I.146	Supply & fixing Angular stop cocks with wall flange with 7 years warranty: Ivory gold	Each	3327
741	MAT-02239	BMW-I.147	Supply & fixing Waste coupling 32 mm size full thread with 80 mm heightJaquar make with 7 years warranty: Chrome plated	Each	387
742	MAT-02240	BMW-I.148	Supply & fixing of Bottle trap 225mm make with 7 years warranty: Chrome plated	Each	1643
743	MAT-02241	BMW-I.149	Supply & fixing of Bottle trap Jaquar make with 7 years warranty: Ivory gold	Each	2777
744	MAT-02242	BMW-I.150	Supply & Fixing copper pipe 450 mm long with nuts & washers Jaquar make with 7 years warranty: Chrome plated	Each	404
745	MAT-02243	BMW-I.151	Supply & Fixing copper pipe 450 mm long with nuts & washers Jaquar make with 7 years warranty:Ivory gold	Each	783
746	MAT-02244	BMW-I.152	Supply and fixing wall mirror with provision for over head shower and 115 mm long bend pipe with wall flange Jaquarmake queen series with 7 years warranty:Chrome plated	Each	5308
747	MAT-02245	BMW-I.153	Supply and fixing wall mirror with provision for over head shower and 115 mm long bend pipe with wall flange Jaquarmake queen series with 7 years warranty: Ivory gold	Each	8349
748	MAT-02246	BMW-I.154	Supply & fixing overhead shower rose with revolving joint and 150 mm long swivel shower arm with 7 years warranty:Chrome plated	Each	2463
749	MAT-02247	BMW-I.155	Supply & fixing overhead shower rose with revolving joint and 150 mm long swivel shower arm Jaquar make queen series. with 7 years warranty: Ivory Gold	Each	3608
750	MAT-02248	BMW-I.156	Supply and Fixing Wall Mixer with Telephonic shower arrangement with crutch and flexible pipe Jaquar series Ivory gold colour for bath tub. with 7 years warranty	Each	14065
751	MAT-02249	BMW-I.157	Supply & fixing Bath tub overflow set complete with over	Each	1713

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
			flow cap, 450 mm Ball chain with rubber plug & union bend with brass nut Jaquar make, Ivory gold colour. with 7 years warranty		
752	MAT-02250	BMW-I.158	Supply & fixing sink cock with regular swinging spout with wall flange chromeplated with 7 years warranty	Each	2461
753	MAT-02251	BMW-I.159	Supply & fixing soap dish: with 7 years warranty: Chrome plated	Each	1615
754	MAT-02252	BMW-I.160	Supply & fixing soap dish Jaquar make queen series: with 7 years warranty: Ivory Gold	Each	2370
755	MAT-02253	BMW-I.161	Supply & fixing of toilet paper holder. with 7 years warranty: Chrome plated	Each	1302
756	MAT-02254	BMW-I.162	Supply & fixing of toilet paper holder Jaquar make Queen series. with 7 years warranty: Ivory Gold	Each	2291
757	MAT-02255	BMW-I.163	Supply & Fixing of Towel ring with 7 years warranty: Chrome plated	Each	1224
758	MAT-02256	BMW-I.164	Supply & Fixing of Towel ring Jaquar make Queen series with 7 years warranty: Ivory Gold	Each	1998
759	MAT-02257	BMW-I.165	Supply & Fixing of Robe hook with 7 years warranty: Chrome plated	Each	910
760	MAT-02258	BMW-I.166	Supply & Fixing of towel coat hook Jaquar make Queen series with 7 years warranty: Ivory Gold	Each	1882
761	MAT-02259	BMW-I.167	Supply & Fixing of Towel rod 24 " Jaquar make Queen series Ivory gold colour with 7 years warranty	Each	3122
762	MAT-02260	BMW-I.168	Supply & Fixing of Tumbler holder Jaquar make Queen series, Ivory gold colour with 7 years warranty	Each	2188
763	MAT-02261	BMW-I.169	Supply & fixing of Glass shelf 22" Jaquar make Queen series, Ivory gold colour with 7 years warranty	Each	4266
764	MAT-02262	BMW-I.170	Supply & Fixing of 2 in 1 Bibcock cum Health Faucet with 1m long tube and wall hook , Chrome Finish with 7 years warranty	Each	3095
765	MAT-02263	BMW-I.171	Supply & Fixing of Bibcock, Chrome Finish with 7 years warranty	Each	910
766	MAT-02264	BMW-I.172	Supply & Fixing of Pillar cock Jaquar Continental series, Chrome Finish with 7 years warranty	Each	1130
767	MAT-02265	BMW-I.173	Supply & Fixing of Angular stopcock with wall flange Jaquar Continental series, Chrome finish with 7 years warranty	Each	841
768	MAT-02266	BMW-I.174	Supply fixing of Waste coupling Jaquar make, Chrome finish with 7 years warranty	Each	366
769	MAT-02267	BMW-I.175	Supply & Fixing of Bottle Trap Jaquar make, Chrome finish with 7 years warranty	Each	1643
770	MAT-02268	BMW-I.176	Supply & Fixing of copper pipe 450mm long with nuts & washers Jaquar make, Chrome Finish with 7 years warranty	Each	366
771	MAT-02269	BMW-I.177	Supply & Fixing of Wall Mixer with provision for overhead shower and 115mm long bend pipe with wall flange Jaquar make Continental series, Chrome finish with 7 years warranty	Each	3975

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
772	MAT-02270	BMW-I.178	Supply & Fixing of Exclusive overhead shower with 190mm long light body shower arm Jaquar make Continental series, Chrome finish with 7 years warranty	Each	1698
773	MAT-02271	BMW-I.179	Supply & Fixing wall mixer with telephonic shower arrangement with crutch and telephone shower with flexible tube Jaquar make Continental series Chrome colour for bath tub with 7 years warranty	Each	5550
774	MAT-02272	BMW-I.180	Supply & Fixing bath tub over flow set complete with over flow cap,450mm ball chain with rubber plug 7 Union bend with brass nuts Jaquar make, Chrome colour with 7 years warranty	Each	1296
775	MAT-02273	BMW-I.181	Supply & Fixing Sink cock with regular swinging spout with flange chrome plated Jaquar make Continental series with 7 years warranty	Each	1600
776	MAT-02274	BMW-I.182	Supply & Fixing soap dish Jaquar make Continental series, Chrome Finish with 7 years warranty	Each	1259
777	MAT-02275	BMW-I.183	Supply & Fixing of Toilet paper holder Jaquar make Continental series, Chrome finish with 7 years warranty	Each	841
778	MAT-02276	BMW-I.184	Supply & Fixing of Towel Ring Jaquar make Continental series, Chrome finish with 7 years warranty	Each	968
779	MAT-02277	BMW-I.185	Supply & Fixing Double coat hook Jaquar make Continental series, Chrome finish with 7 years warranty	Each	722
780	MAT-02278	BMW-I.186	Supply & Fixing of towel rail 24" Jaquar make Continental series, Chrome finish with 7 years warranty	Each	1562
781	MAT-02279	BMW-I.187	Supply & Fixing of Tumblerholder Jaquar make Continental series, Chrome finish with 7 years warranty	Each	1053
782	MAT-02280	BMW-I.188	Supply & Fixing of Glass shelf 22" Jaquar make Continental series, Chrome finish with 7 years warranty	Each	2071
783	MAT-02281	BMW-I.189	Supply & Fixing of Bibcock cum Health Faucet with 1m long tube and wall hook of Jaquar Florentine(Quarter turn) series, Chrome Finish with 7 years warranty	Each	3703
784	MAT-02282	BMW-I.190	Supply & Fixing of Bibcock Jaquar Florentine (Quarter turn)series, Chrome Finish with 7 years warranty	Each	1249
785	MAT-02283	BMW-I.191	Supply & Fixing of Pillar cock Jaquar Florentine(Quarter turn) series, Chrome Finish with 7 years warranty	Each	1249
786	MAT-02284	BMW-I.192	Supply & Fixing of Angular stopcock with wall flange Jaquar Florentine(Quarter turn)series, Chrome finish with 7 years warranty	Each	1229
787	MAT-02285	BMW-I.193	Supply & Fixing of Bottle Trap Jaquar make, Chrome finish with 7 years warranty	Each	1643
788	MAT-02286	BMW-I.194	Supply & Fixing of Wall Mixer with provision for overhead shower and 115mm long bend pipe with wall flange Jaquar make Florentine(Quarter turn) series, Chrome finish with 7 years warranty	Each	4797
789	MAT-02287	BMW-I.195	Supply & Fixing wall mixer with telephonic shower arrangement with crutch and telephone shower with flexible tube Jaquar make Florentine(Quarter turn) series Chrome colour for bath tub with 7 years warranty	Each	7228

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
790	MAT-02288	BMW-I.196	Supply & Fixing Sink cock with regular swinging spout with flange chrome plated make Florentine(Quarter turn) series with 7 years warranty	Each	1916
791	MAT-02289	BMW-I.197	Supply & Fixing of Rose shower with revolving ball joint & 115mm long shower arm with 7 years warranty	Each	2036
792	MAT-02290	BMW-I.198	Supply & Fixing of make chrome plated Metro pole flush valveconcealed type with cover plate 40mm size with 7 years warranty	Each	3565
793	MAT-02291	BMW-I.199	Supply & Fixing of make Sensotronic sensor faucetfor wash basin, Chrome plated with 7 years warranty	Each	13999
794	MAT-02292	BMW-I.200	Supply & fixing of Jaquar make Sensotronic concealed type flushing valve for urinal complete set with installation box with control cock, Chrome plated with 7 years warranty	Each	13999
795	MAT-02293	BMW-I.201	Supply & fixing of Jaquar make Auto closing system pillar cock for wash basin, Chrome plated with 7 years warranty	Each	2320
796	MAT-02294	BMW-I.202	Supply& Fixing of Jaquar make Auto Closing system Bibcock, Chrome plated with 7 years warranty	Each	2433
797	MAT-02295	BMW-I.203	ITEM DELETED		
798	MAT-02296	BMW-I.204	ITEM DELETED		
799	MAT-02297	BMW-I.205	ITEM DELETED		
800	MAT-02298	BMW-I.206	ITEM DELETED		
801	MAT-02299	BMW-I.207	ITEM DELETED		
802	MAT-02300	BMW-I.208	ITEM DELETED		
803	MAT-02301	BMW-I.209	ITEM DELETED		
804	MAT-02302	BMW-I.210	ITEM DELETED		
805	MAT-02303	BMW-I.211	ITEM DELETED		
806	MAT-02304	BMW-I.212	ITEM DELETED		
807	MAT-02305	BMW-I.213	ITEM DELETED		

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
808	MAT-02306	BMW-I.214	ITEM DELETED		
809	MAT-02307	BMW-I.215	S&F Polyethylene-Aluminium-Polyethylene (PE-AL-PE) composite pressure pipes conforming to IS-15450-2004 with UV stabilized, carbon black for hot & cold water supply, capable to withstand pressure up to 80 C including all special composite fittings, plastic & brass blend inserts for elbows, tees, reducers, couplers, connectors etc complete including excavating trenches up to 1.0 M deep laying pipes, fixing in position, testing, refilling excavated earth and commissioning etc16 mm OD pipe	1 RM	177
810	MAT-02308	BMW-I.216	S&F Polyethylene-Aluminium-Polyethylene (PE-AL-PE) composite pressure pipes conforming to IS-15450-2004 with UV stabilized, carbon black for hot & cold water supply, capable to withstand pressure up to 80 C including all special composite fittings, plastic & brass blend inserts for elbows, tees, reducers, couplers, connectors etc complete including excavating trenches up to 1.0 M deep laying pipes, fixing in position, testing, refilling excavated earth and commissioning etc 20 mm OD pipe	1 RM	208
811	MAT-02309	BMW-I.217	S&F Polyethylene-Aluminium-Polyethylene (PE-AL-PE) composite pressure pipes conforming to IS-15450-2004 with UV stabilized, carbon black for hot & cold water supply, capable to withstand pressure up to 80 C including all special composite fittings, plastic & brass blend inserts for elbows, tees, reducers, couplers, connectors etc complete including excavating trenches up to 1.0 M deep laying pipes, fixing in position, testing, refilling excavated earth and commissioning etc 25mm OD pipe	1 RM	254
812	MAT-02310	BMW-I.218	S&F Polyethylene-Aluminium-Polyethylene (PE-AL-PE) composite pressure pipes conforming to IS-15450-2004 with UV stabilized, carbon black for hot & cold water supply, capable to withstand pressure up to 80 C including all special composite fittings, plastic & brass blend inserts for elbows, tees, reducers, couplers, connectors etc complete including excavating trenches up to 1.0 M deep laying pipes, fixing in position, testing, refilling excavated earth and commissioning etc 32 mm OD pipe	1 RM	327
813	MAT-02311	BMW-I.219	S&F Polyethylene-Aluminium-Polyethylene (PE-AL-PE) composite pressure pipes conforming to IS-15450-2004 with UV stabilized, carbon black for hot & cold water supply, capable to withstand pressure up to 80 C including all special composite fittings, plastic & brass blend inserts for elbows, tees, reducers, couplers, connectors etc complete including excavating trenches up to 1.0 M deep laying pipes, fixing in position, testing, refilling excavated earth and commissioning etc 40 mm OD pipe	1 RM	419

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
			Supply and Fixing of Premium make CPVC Pipes and Fittings to meet the requirement of ASTM-D 2846 and are produced in CTS (Copper Tube Sizes 1/2" ton 2" SDR 11 and SDR 13.5 pipes are made from identical CPVC compounds having the same physical Properties for Hot and Cold Water (IS 15778:2007)		
814	MAT-02312	BMW-I.220	15.90mm OD Pipe - SDR 13.5	1 RM	159
815	MAT-02313	BMW-I.221	22.20mm OD Pipe - SDR 13.5	1 RM	186
816	MAT-02314	BMW-I.222	28.60mm OD Pipe - SDR 13.5	1 RM	224
817	MAT-02315	BMW-I.223	34.90mm OD Pipe - SDR 13.5	1 RM	291
818	MAT-02316	BMW-I.224	41.30mm OD Pipe - SDR 13.5	1 RM	394
819	MAT-02317	BMW-I.225	54mm OD Pipe - SDR 13.5	1 RM	527
820	MAT-02318	BMW-I.226	15.90mm OD Pipe - SDR 11	1 RM	170
821	MAT-02319	BMW-I.227	22.20mm OD Pipe - SDR 11	1 RM	200
822	MAT-02320	BMW-I.228	28.60mm OD Pipe - SDR 11	1 RM	247
823	MAT-02321	BMW-I.229	34.90mm OD Pipe - SDR 11	1 RM	324
824	MAT-02322	BMW-I.230	41.30mm OD Pipe - SDR 11	1 RM	442
825	MAT-02323	BMW-I.231	54mm OD Pipe - SDR 11	1 RM	605
826	MAT-02324	BMW-I.232	Supply of 20mm x 1.9mm PN 10/PPR Pipe conforming to DIN Standards 8077/8078 conforming to IS15801	1 RM	46
827	MAT-02325	BMW-I.233	Supply of 25mm x 2.3mm PN 10/PPR Pipe conforming to DIN Standards 8077/8078 conforming to IS15801	1 RM	68
828	MAT-02326	BMW-I.234	Supply of 32mm x 2.9mm PN 10/PPR Pipe conforming to DIN Standards 8077/8079 conforming to IS15801	1 RM	107
829	MAT-02327	BMW-I.235	Supply of 40mm x 3.7mm PN 10/PPR Pipe conforming to DIN Standards 8077/8079 conforming to IS15801	1 RM	168
830	MAT-02328	BMW-I.236	Supply of 50mm x 4.6mm PN 10/PPR Pipe conforming to DIN Standards 8077/8080 conforming to IS15801	1 RM	300
831	MAT-02329	BMW-I.237	Supply of 63mm x 5.8mm PN 10/PPR Pipe conforming to DIN Standards 8077/8081 conforming to IS15801	1 RM	470
832	MAT-02330	BMW-I.238	Supply of 75mm x 6.8mm PN 10/PPR Pipe conforming to DIN Standards 8077/8082 conforming to IS15801	1 RM	655
833	MAT-02331	BMW-I.239	Supply of 90mm x 8.2mm PN 10/PPR Pipe conforming to DIN Standards 8077/8083 conforming to IS15801	1 RM	898
834	MAT-02332	BMW-I.240	Supply of 110mm x 10mm PN 10/PPR Pipe conforming to DIN Standards 8077/8084 conforming to IS15801	1 RM	1330
835	MAT-02333	BMW-I.241	Supply of 20mm x 2.8mm PN 16/PPR Pipe conforming to DIN Standards 8077/8078 conforming to IS15801	1 RM	62
836	MAT-02334	BMW-I.242	Supply of 25mm x 3.5mm PN 16/PPR Pipe conforming to DIN Standards 8077/8078 conforming to IS15801	1 RM	94

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
837	MAT-02335	BMW-I.243	Supply of 32mm x 4.4mm PN 16/PPR Pipe conforming to DIN Standards 8077/8079 conforming to IS15801	1 RM	153
838	MAT-02336	BMW-I.244	Supply of 40mm x 5.5mm PN 16/PPR Pipe conforming to DIN Standards 8077/8079 conforming to IS15801	1 RM	233
839	MAT-02337	BMW-I.245	Supply of 50mm x 6.9mm PN 16/PPR Pipe conforming to DIN Standards 8077/8080 conforming to IS15801	1 RM	419
840	MAT-02338	BMW-I.246	Supply of 63mm x 8.6mm PN 16/PPR Pipe conforming to DIN Standards 8077/8081 conforming to IS15801	1 RM	660
841	MAT-02339	BMW-I.247	Supply of 75mm x 10.3mm PN 16/PPR Pipe conforming to DIN Standards 8077/8082 conforming to IS15801	1 RM	932
842	MAT-02340	BMW-I.248	Supply of 90mm x 12.3mm PN 16/PPR Pipe conforming to DIN Standards 8077/8083 conforming to IS15801	1 RM	1328
843	MAT-02341	BMW-I.249	Supply of 110mm x 15.1mm PN 16/PPR Pipe conforming to DIN Standards 8077/8084 conforming to IS15801	1 RM	1989
844	MAT-02342	BMW-I.250	Supply of 20mm x 3.4mm PN 20/PPR Pipe conforming to DIN Standards 8077/8078 conforming to IS15801	1 RM	72
845	MAT-02343	BMW-I.251	Supply of 25mm x 4.2mm PN 20/PPR Pipe conforming to DIN Standards 8077/8078 conforming to IS15801	1 RM	110
846	MAT-02344	BMW-I.252	Supply of 32mm x 5.4mm PN 20/PPR Pipe conforming to DIN Standards 8077/8079 conforming to IS15801	1 RM	177
847	MAT-02345	BMW-I.253	Supply of 40mm x 6.7mm PN 20/PPR Pipe conforming to DIN Standards 8077/8079 conforming to IS15801	1 RM	273
848	MAT-02346	BMW-I.254	Supply of 50mm x 8.3mm PN 20/PPR Pipe conforming to DIN Standards 8077/8080 conforming to IS15801	1 RM	484
849	MAT-02347	BMW-I.255	Supply of 63mm x 10.5mm PN 20/PPR Pipe conforming to DIN Standards 8077/8081 conforming to IS15801	1 RM	764
850	MAT-02348	BMW-I.256	Supply of 75mm x 12.5mm PN 20/PPR Pipe conforming to DIN Standards 8077/8082 conforming to IS15801	1 RM	1083
851	MAT-02349	BMW-I.257	Supply of 90mm x 15mm PN 20/PPR Pipe conforming to DIN Standards 8077/8083	1 RM	1472
852	MAT-02350	BMW-I.258	Supply of 110mm x 18.3mm PN 20/PPR Pipe conforming to DIN Standards 8077/8084 conforming to IS15801	1 RM	2317
853	MAT-02351	BMW-I.259	Supply of 20mm PPR Socket conforming to DIN Standards 8077/8084	1 RM	10
854	MAT-02352	BMW-I.260	Supply of 25mm PPR Socket conforming to DIN Standards 8077/8085	1 RM	16
855	MAT-02353	BMW-I.261	Supply of 32mm PPR Socket conforming to DIN Standards 8077/8086	1 RM	21
856	MAT-02354	BMW-I.262	Supply of 40mm PPR Socket conforming to DIN Standards 8077/8087	1 RM	34
857	MAT-02355	BMW-I.263	Supply of 50mm PPR Socket conforming to DIN Standards 8077/8088	1 RM	65
858	MAT-02356	BMW-I.264	Supply of 63mm PPR Socket conforming to DIN Standards 8077/8089	1 RM	125
859	MAT-02357	BMW-I.265	Supply of 75mm PPR Socket conforming to DIN Standards 8077/8090	1 RM	191

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
860	MAT-02358	BMW-I.266	Supply of 90mm PPR Socket conforming to DIN Standards 8077/8091	1 RM	364
861	MAT-02359	BMW-I.267	Supply of 110mm PPR Socket conforming to DIN Standards 8077/8092	1 RM	650
862	MAT-02360	BMW-I.268	Supply of 32mm PPR Core Flange conforming to DIN Standards 8077/8086	Each	40
863	MAT-02361	BMW-I.269	Supply of 40mm PPR Core Flange conforming to DIN Standards 8077/8087	Each	63
864	MAT-02362	BMW-I.270	Supply of 50mm PPR Core Flange conforming to DIN Standards 8077/8088	Each	82
865	MAT-02363	BMW-I.271	Supply of 63mm PPR Core Flange conforming to DIN Standards 8077/8089	Each	130
866	MAT-02364	BMW-I.272	Supply of 75mm PPR Core Flange conforming to DIN Standards 8077/8090	Each	150
867	MAT-02365	BMW-I.273	Supply of 90mm PPR Core Flange conforming to DIN Standards 8077/8091	Each	384
868	MAT-02366	BMW-I.274	Supply of 110mm PPR Core Flange conforming to DIN Standards 8077/8092	Each	495
869	MAT-02367	BMW-I.275	Supply of 20mm PPR Elbow conforming to DIN Standards 8077/8084	Each	18
870	MAT-02368	BMW-I.276	Supply of 25mm PPR Elbow conforming to DIN Standards 8077/8085	Each	22
871	MAT-02369	BMW-I.277	Supply of 32mm PPR Elbow conforming to DIN Standards 8077/8086	Each	40
872	MAT-02370	BMW-I.278	Supply of 40mm PPR Elbow conforming to DIN Standards 8077/8087	Each	70
873	MAT-02371	BMW-I.279	Supply of 50mm PPR Elbow conforming to DIN Standards 8077/8088	Each	132
874	MAT-02372	BMW-I.280	Supply of 63mm PPR Elbow conforming to DIN Standards 8077/8089	Each	256
875	MAT-02373	BMW-I.281	Supply of 75mm PPR Elbow conforming to DIN Standards 8077/8090	Each	414
876	MAT-02374	BMW-I.282	Supply of 90mm PPR Elbow conforming to DIN Standards 8077/8091	Each	769
877	MAT-02375	BMW-I.283	Supply of 110mm PPR Elbow conforming to DIN Standards 8077/8092	Each	1426
878	MAT-02376	BMW-I.284	Supply of 20mm PPR Tee conforming to DIN Standards 8077/8084	Each	17
879	MAT-02377	BMW-I.285	Supply of 25mm PPR Tee conforming to DIN Standards 8077/8085	Each	27
880	MAT-02378	BMW-I.286	Supply of 32mm PPR Tee conforming to DIN Standards 8077/8086	Each	48
881	MAT-02379	BMW-I.287	Supply of 40mm PPR Tee conforming to DIN Standards 8077/8087	Each	84
882	MAT-02380	BMW-I.288	Supply of 50mm PPR Tee conforming to DIN Standards 8077/8088	Each	149

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
883	MAT-02381	BMW-I.289	Supply of 63mm PPR Tee conforming to DIN Standards 8077/8089	Each	303
884	MAT-02382	BMW-I.290	Supply of 75mm PPR Tee conforming to DIN Standards 8077/8090	Each	593
885	MAT-02383	BMW-I.291	Supply of 90mm PPR Tee conforming to DIN Standards 8077/8091	Each	860
886	MAT-02384	BMW-I.292	Supply of 110mm PPR Tee conforming to DIN Standards 8077/8092	Each	1489
887	MAT-02385	BMW-I.293	Supply of 20mm PPR End Cap conforming to DIN Standards 8077/8084	Each	7
888	MAT-02386	BMW-I.294	Supply of 25mm PPR End Cap conforming to DIN Standards 8077/8085	Each	10
889	MAT-02387	BMW-I.295	Supply of 32mm PPR End Cap conforming to DIN Standards 8077/8086	Each	21
890	MAT-02388	BMW-I.296	Supply of 40mm PPR End Cap conforming to DIN Standards 8077/8087	Each	34
891	MAT-02389	BMW-I.297	Supply of 50mm PPR End Cap conforming to DIN Standards 8077/8088	Each	59
892	MAT-02390	BMW-I.298	Supply of 63mm PPR End Cap conforming to DIN Standards 8077/8089	Each	125
893	MAT-02391	BMW-I.299	Supply of 75mm PPR End Cap conforming to DIN Standards 8077/8090	Each	210
894	MAT-02392	BMW-I.300	Supply of 90mm PPR End Cap conforming to DIN Standards 8077/8091	Each	334
895	MAT-02393	BMW-I.301	Supply of 110mm PPR End Cap conforming to DIN Standards 8077/8092	Each	660
896	MAT-02394	BMW-I.302	Supply of 25mm x 20mm PPR Reducer conforming to DIN Standards 8077/8092	Each	13
897	MAT-02395	BMW-I.303	Supply of 32mm x 25mm PPR Reducer conforming to DIN Standards 8077/8092	Each	22
898	MAT-02396	BMW-I.304	Supply of 32mm x 20mm PPR Reducer conforming to DIN Standards 8077/8092	Each	21
899	MAT-02397	BMW-I.305	Supply of 40mm x 32mm PPR Reducer conforming to DIN Standards 8077/8092	Each	35
900	MAT-02398	BMW-I.306	Supply of 40mm x 25mm PPR Reducer conforming to DIN Standards 8077/8092	Each	34
901	MAT-02399	BMW-I.307	Supply of 40mm x 20mm PPR Reducer conforming to DIN Standards 8077/8092	Each	34
902	MAT-02400	BMW-I.308	Supply of 50mm x 20mm PPR Reducer conforming to DIN Standards 8077/8092	Each	51
903	MAT-02401	BMW-I.309	Supply of 50mm x 25mm PPR Reducer conforming to DIN Standards 8077/8092	Each	52
904	MAT-02402	BMW-I.310	Supply of 50mm x 32mm PPR Reducer conforming to DIN Standards 8077/8092	Each	52
905	MAT-02403	BMW-I.311	Supply of 50mm x 40mm PPR Reducer conforming to DIN Standards 8077/8092	Each	54

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
906	MAT-02404	BMW-I.312	Supply of 63mm x 20mm PPR Reducer conforming to DIN Standards 8077/8092	Each	115
907	MAT-02405	BMW-I.313	Supply of 63mm x 25mm PPR Reducer conforming to DIN Standards 8077/8092	Each	115
908	MAT-02406	BMW-I.314	Supply of 63mm x 32mm PPR Reducer conforming to DIN Standards 8077/8092	Each	117
909	MAT-02407	BMW-I.315	Supply of 63mm x 40mm PPR Reducer conforming to DIN Standards 8077/8092	Each	118
910	MAT-02408	BMW-I.316	Supply of 63mm x 50mm PPR Reducer conforming to DIN Standards 8077/8092	Each	119
911	MAT-02409	BMW-I.317	Supply of 75mm x 40mm PPR Reducer conforming to DIN Standards 8077/8092	Each	172
912	MAT-02410	BMW-I.318	Supply of 75mm x 50mm PPR Reducer conforming to DIN Standards 8077/8092	Each	173
913	MAT-02411	BMW-I.319	Supply of 75mm x 63mm PPR Reducer conforming to DIN Standards 8077/8092	Each	219
914	MAT-02412	BMW-I.320	Supply of 90mm x 63mm PPR Reducer conforming to DIN Standards 8077/8092	Each	419
915	MAT-02413	BMW-I.321	Supply of 90mm x 75mm PPR Reducer conforming to DIN Standards 8077/8092	Each	444
916	MAT-02414	BMW-I.322	Supply of 110mm x 63mm PPR Reducer conforming to DIN Standards 8077/8092	Each	559
917	MAT-02415	BMW-I.323	Supply of 110mm x 75mm PPR Reducer conforming to DIN Standards 8077/8092	Each	652
918	MAT-02416	BMW-I.324	Supply of 110mm x 90mm PPR Reducer conforming to DIN Standards 8077/8092	Each	701
919	MAT-02417	BMW-I.325	Supply of 25mm x 20mm x 25mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	34
920	MAT-02418	BMW-I.326	Supply of 32mm x 25mm x 32mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	58
921	MAT-02419	BMW-I.327	Supply of 32mm x 20mm x 32mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	58
922	MAT-02420	BMW-I.328	Supply of 40mm x 20mm x 40mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	94
923	MAT-02421	BMW-I.329	Supply of 40mm x 25mm x 40mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	96
924	MAT-02422	BMW-I.330	Supply of 40mm x 32mm x 40mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	99
925	MAT-02423	BMW-I.331	Supply of 50mm x 20mm x 50mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	137
926	MAT-02424	BMW-I.332	Supply of 50mm x 25mm x 50mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	139
927	MAT-02425	BMW-I.333	Supply of 50mm x 32mm x 50mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	143
928	MAT-02426	BMW-I.334	Supply of 50mm x 40mm x 50mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	144

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
929	MAT-02427	BMW-I.335	Supply of 63mm x 20mm x 63mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	395
930	MAT-02428	BMW-I.336	Supply of 63mm x 25mm x 63mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	397
931	MAT-02429	BMW-I.337	Supply of 63mm x 32mm x 63mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	403
932	MAT-02430	BMW-I.338	Supply of 63mm x 40mm x 63mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	409
933	MAT-02431	BMW-I.339	Supply of 63mm x 50mm x 63mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	416
934	MAT-02432	BMW-I.340	Supply of 75mm x 50mm x 75mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	557
935	MAT-02433	BMW-I.341	Supply of 75mm x 63mm x 75mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	567
936	MAT-02434	BMW-I.342	Supply of 90mm x 50mm x 90mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	749
937	MAT-02435	BMW-I.343	Supply of 90mm x 63mm x 90mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	798
938	MAT-02436	BMW-I.344	Supply of 110mm x 75mm x 110mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	1359
939	MAT-02437	BMW-I.345	Supply of 110mm x 90mm x 110mm PPR Reducer Tee conforming to DIN Standards 8077/8092	Each	1414
940	MAT-02438	BMW-I.346	Supply of 20mm x ½" PPR Female Threaded Adaptor conforming to DIN Standards 8077/8092	Each	105
941	MAT-02439	BMW-I.347	Supply of 25mm x ½" PPR Female Threaded Adaptor conforming to DIN Standards 8077/8092	Each	107
942	MAT-02440	BMW-I.348	Supply of 25mm x ¾" PPR Female Threaded Adaptor conforming to DIN Standards 8077/8092	Each	188
943	MAT-02441	BMW-I.349	Supply of 32mm x ½" PPR Female Threaded Adaptor conforming to DIN Standards 8077/8092	Each	192
944	MAT-02442	BMW-I.350	Supply of 32mm x ¾" PPR Female Threaded Adaptor conforming to DIN Standards 8077/8092	Each	197
945	MAT-02443	BMW-I.351	Supply of 32mm x 1" PPR Female Threaded Adaptor conforming to DIN Standards 8077/8092	Each	305
946	MAT-02444	BMW-I.352	Supply of 40mm x 1¼" PPR Female Threaded Adaptor conforming to DIN Standards 8077/8092	Each	451
947	MAT-02445	BMW-I.353	Supply of 50mm x 1½" PPR Female Threaded Adaptor conforming to DIN Standards 8077/8092	Each	630
948	MAT-02446	BMW-I.354	Supply of 63mm x 2" PPR Female Threaded Adaptor conforming to DIN Standards 8077/8092	Each	838
949	MAT-02447	BMW-I.355	Supply of 75mm x 2½" PPR Female Threaded Adaptor conforming to DIN Standards 8077/8092	Each	1615
950	MAT-02448	BMW-I.356	Supply of 20mm x ½" PPR Male Threaded Adaptor conforming to DIN Standards 8077/8092	Each	163
951	MAT-02449	BMW-I.357	Supply of 25mm x ½" PPR Male Threaded Adaptor conforming to DIN Standards 8077/8092	Each	168

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
952	MAT-02450	BMW-I.358	Supply of 25mm x ¾" PPR Male Threaded Adaptor conforming to DIN Standards 8077/8092	Each	245
953	MAT-02451	BMW-I.359	Supply of 32mm x ¾" PPR Male Threaded Adaptor conforming to DIN Standards 8077/8092	Each	256
954	MAT-02452	BMW-I.360	Supply of 32mm x 1" PPR Male Threaded Adaptor conforming to DIN Standards 8077/8092	Each	474
955	MAT-02453	BMW-I.361	Supply of 40mm x 1¼" PPR Male Threaded Adaptor conforming to DIN Standards 8077/8092	Each	556
956	MAT-02454	BMW-I.362	Supply of 50mm x 1½" PPR Male Threaded Adaptor conforming to DIN Standards 8077/8092	Each	778
957	MAT-02455	BMW-I.363	Supply of 63mm x 2" PPR Male Threaded Adaptor conforming to DIN Standards 8077/8092	Each	1195
958	MAT-02456	BMW-I.364	Supply of 75mm x 2½" PPR Male Threaded Adaptor conforming to DIN Standards 8077/8092	Each	1912
959	MAT-02457	BMW-I.365	Supply of 20mm x ½" PPR Female Threaded Elbow conforming to DIN Standards 8077/8092	Each	112
960	MAT-02458	BMW-I.366	Supply of 25mm x ½" PPR Female Threaded Elbow conforming to DIN Standards 8077/8092	Each	117
961	MAT-02459	BMW-I.367	Supply of 25mm x ¾" PPR Female Threaded Elbow conforming to DIN Standards 8077/8092	Each	181
962	MAT-02460	BMW-I.368	Supply of 32mm x ½" PPR Female Threaded Elbow conforming to DIN Standards 8077/8092	Each	173
963	MAT-02461	BMW-I.369	Supply of 32mm x ¾" PPR Female Threaded Elbow conforming to DIN Standards 8077/8092	Each	202
964	MAT-02462	BMW-I.370	Supply of 32mm x 1" PPR Female Threaded Elbow conforming to DIN Standards 8077/8092	Each	337
965	MAT-02463	BMW-I.371	Supply of 20mm x ½" PPR Male Threaded Elbow conforming to DIN Standards 8077/8092	Each	168
966	MAT-02464	BMW-I.372	Supply of 25mm x ½" PPR Male Threaded Elbow conforming to DIN Standards 8077/8092	Each	185
967	MAT-02465	BMW-I.373	Supply of 25mm x ¾" PPR Male Threaded Elbow conforming to DIN Standards 8077/8092	Each	244
968	MAT-02466	BMW-I.374	Supply of 32mm x ½" PPR Male Threaded Elbow conforming to DIN Standards 8077/8092	Each	233
969	MAT-02467	BMW-I.375	Supply of 32mm x 1" PPR Male Threaded Elbow conforming to DIN Standards 8077/8092	Each	504
970	MAT-02468	BMW-I.376	Supply of 20mm x ½" PPR Female Threaded Tee conforming to DIN Standards 8077/8092	Each	108
971	MAT-02469	BMW-I.377	Supply of 25mm x ½" PPR Female Threaded Tee conforming to DIN Standards 8077/8092	Each	119
972	MAT-02470	BMW-I.378	Supply of 25mm x ¾" PPR Female Threaded Tee conforming to DIN Standards 8077/8092	Each	197
973	MAT-02471	BMW-I.379	Supply of 32mm x ½" PPR Female Threaded Tee conforming to DIN Standards 8077/8092	Each	209
974	MAT-02472	BMW-I.380	Supply of 32mm x ¾" PPR Female Threaded Tee conforming to DIN Standards 8077/8092	Each	233

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
975	MAT-02473	BMW-I.381	Supply of 32mm x 1" PPR Female Threaded Tee conforming to DIN Standards 8077/8092	Each	329
976	MAT-02474	BMW-I.382	Supply of 20mm x ½" PPR Male Threaded Teeconforming to DIN Standards 8077/8092	Each	169
977	MAT-02475	BMW-I.383	Supply of 25mm x ½" PPR Male Threaded Tee conforming to DIN Standards 8077/8092	Each	181
978	MAT-02476	BMW-I.384	Supply of 25mm x ¾" PPR Male Threaded Tee conforming to DIN Standards 8077/8092	Each	258
979	MAT-02477	BMW-I.385	Supply of 32mm x ½" PPR Male Threaded Tee conforming to DIN Standards 8077/8092	Each	266
980	MAT-02478	BMW-I.386	Supply of 32mm x¾"PPR Male Threaded Tee conforming to DIN Standards 8077/8092	Each	279
981	MAT-02479	BMW-I.387	Supply of 32mm x 1" PPR Male Threaded Tee conforming to DIN Standards 8077/8092	Each	515
982	MAT-02480	BMW-I.388	Supply of 20mm x ½" PPR Female Threaded Union conforming to DIN Standards 8077/8092	Each	435
983	MAT-02481	BMW-I.389	Supply of 25mm x¾"PPR Female Threaded Union conforming to DIN Standards 8077/8092	Each	652
984	MAT-02482	BMW-I.390	Supply of 32mm x1"PPR Female Threaded Union conforming to DIN Standards 8077/8092	Each	869
985	MAT-02483	BMW-I.391	Supply of 40mm x1¼"PPR Female Threaded Union conforming to DIN Standards 8077/8092	Each	1218
986	MAT-02484	BMW-I.392	Supply of 50mm x 1½" PPR Female Threaded Union conforming to DIN Standards 8077/8092	Each	1956
987	MAT-02485	BMW-I.393	Supply of 63mm x 2" PPR Female Threaded Union conforming to DIN Standards 8077/8092	Each	3107
988	MAT-02486	BMW-I.394	Supply of 20mm x ½" PPR Male Threaded Union conforming to DIN Standards 8077/8092	Each	498
989	MAT-02487	BMW-I.395	Supply of 25mm x¾"PPR Male Threaded Union conforming to DIN Standards 8077/8092	Each	662
990	MAT-02488	BMW-I.396	Supply of 32mm x1"PPR Male Threaded Union conforming to DIN Standards 8077/8092	Each	869
991	MAT-02489	BMW-I.397	Supply of 40mm x1¼"PPR Male Threaded Union conforming to DIN Standards 8077/8092	Each	1085
992	MAT-02490	BMW-I.398	Supply of 50mm x 1½" PPR Male Threaded Union conforming to DIN Standards 8077/8092	Each	2065
993	MAT-02491	BMW-I.399	Supply of 63mm x 2" PPR Male Threaded Union conforming to DIN Standards 8077/8092	Each	3477
994	MAT-02492	BMW-I.400	Supply of 20mm PPR Union conforming to DIN Standards 8077/8092	Each	94
995	MAT-02493	BMW-I.401	Supply of 25mm PPR Union conforming to DIN Standards 8077/8092	Each	111
996	MAT-02494	BMW-I.402	Supply of 32mm PPR Union conforming to DIN Standards 8077/8092	Each	184
997	MAT-02495	BMW-I.403	Supply of 20mm PPR Ball Valve conforming to DIN Standards 8077/8092	Each	173

Sl. No	CFMS Code	Item Code	Description of item	Unit	Basic Rate for SoR 2025-26 (Rs.)
998	MAT-02496	BMW-I.404	Supply of 25mm PPR Ball Valve conforming to DIN Standards 8077/8092	Each	217
999	MAT-02497	BMW-I.405	Supply of 32mm PPR Ball Valve conforming to DIN Standards 8077/8092	Each	229
1000	MAT-02498	BMW-I.406	Supply of 40mm PPR Ball Valve conforming to DIN Standards 8077/8092	Each	467
1001	MAT-02499	BMW-I.407	Supply of 50mm PPR Ball Valve conforming to DIN Standards 8077/8092	Each	545
1002	MAT-02500	BMW-I.408	Supply of 63mm PPR Ball Valve conforming to DIN Standards 8077/8092	Each	881
1003	MAT-02501	BMW-I.409	Supply of 75mm PPR Ball Valve conforming to DIN Standards 8077/8092	Each	1449
1004	MAT-02502	BMW-I.410	Supply of 90mm PPR Ball Valve conforming to DIN Standards 8077/8092	Each	2071
1005	MAT-02503	BMW-I.411	Supply of 20mm PPR Clamp conforming to DIN Standards 8077/8092	Each	10
1006	MAT-02504	BMW-I.412	Supply of 25mm PPR Clamp conforming to DIN Standards 8077/8092	Each	13
1007	MAT-02505	BMW-I.413	Supply of 32mm PPR Clamp conforming to DIN Standards 8077/8092	Each	16
1008	MAT-02506	BMW-I.414	Supply of 40mm PPR Clamp conforming to DIN Standards 8077/8092	Each	17
1009	LAB-00315	BMW-I.415	Labour charges for laying, joining, welding, fixing and commissioning the PPR pipes including all specials such as couplers/ bends/ tees etc including fixing necessary fittings like bends, plugs, couplers, junctions, tees, etc with welding the joint as per standard practice - up to 40 mm dia	1 RM	37
1010	LAB-00316	BMW-I.416	Labour charges for laying, joining, welding, fixing and commissioning the PPR pipes including all specials such as couplers/ bends/ tees etc including fixing necessary fittings like bends, plugs, couplers, junctions, tees, etc with welding the joint as per standard practice - above 40 mm dia	1 RM	62
			Supply and fixing of UPVC Pipes and Fittings SCH-40 Grade to meet the requirement of ASTM-D 2846 for hot and cold water (IS 15778:2007) including cost and conveyance of all materials to site, labor charges for fixing, overheads & contractors profit complete for finished item of work at all floor levels.		
1011		BMW-I.417	65 mm OD Pipe	1 RM	814
1012		BMW-I.418	80 mm OD Pipe	1 RM	974
1013		BMW-I.419	100 mm OD Pipe	1 RM	1060

1014		BMW-I.420	125 mm OD Pipe	1 RM	1246
1015		BMW-I.421	150 mm OD Pipe	1 RM	1432



SCHEDULE OF RATES

ELECTRICAL AND ELECTRO-MECHANICAL WORKS

**PART III -BUILDINGS
FOR THE YEAR
2025-26**

PREAMBLE FOR ELECTRICAL WORKS

1. Overheads and Contractor Profit and over head charges as mentioned in the preamble for Buildings SoR 2025-26 (Civil and Electrical) is applicable to all original electrical works subject to the fulfilment of conditions mentioned in Para 4.0 of preamble.
2. Municipal Area Allowance, Agency or Tribal area allowance or any such allowance on the labour components is applicable to Electrical works as per the Preamble for Buildings SOR 2025-26.
3. The contractor is solely responsible for both quality and quantity.
4. Proposing specific make in the estimate from the SOR is within the scope of concerned field officers based on the necessity and availability of materials in such areas.
5. In case of 2way points i.e. stair case point etc where two way switch control is necessary, an extra at 50 % excess over each point shall be allowed
6. Where ever the light/fan point is provided at a height/length of 15 feet and above, then an extra of 50% over the point rates shall be allowed.
7. The rates for common civil items including labour rates have to be adopted from prevailing SOR.
8. The rates for all types of electrical items proposed in SOR are exclusive of GST (basic rates).
9. The rates for other items (Not covered in SoR) have to be invariably followed based on the prevailing market rates, since the rates and specification varies from manufacturer to manufacturer considerably. Hence, rates for certain items are not incorporated in the SOR. However, relevant data without rates is provided in the standard datas for electrical works.
10. In case of any addition/alteration/rectification to the proposed SOR, the approval has to be obtained from the Chief Engineer R&B Electrical. Temporary approvals for materials which are under relevant specifications of the BIS / IEC and BEE star ratings can be given by the Chief Engineer (R&B) Electrical.
11. The Superintending Engineer (R&B) Electrical will review the performance over the quality of the makes proposed in the SOR from time to time and in case any inferior quality is observed the same shall be brought to the notice of the Chief Engineer (R&B) Electrical to consider for deletion from the SOR.
12. The schedule of rates is only for guidance of officers for preparation of estimates as per the Para 113 of APPWD code. The authority that sanctioned the estimate is however responsible for adopting the proper rates in the estimates as envisaged in para 45 of APPWD code.
13. As per GO Ms No.51 Industries and commerce (MSME) Dept Dt:01.06.2010, all the indenting departments / Agents should give preference to local MSME which are manufacturing quality products having ISO 9001 – 2000, GEM, BIS certification

Chief Engineer(R&B) Electrical

Sl. No.	INDEX
	SECTION - 1
1.1	M.S. CONDUIT PIPES
1.2	PVC CONDUIT PIPES
1.3	METAL BOXES FOR SWITCH BOARDS
1.4	T.W. BOARDS
1.5	COPPER FLEXIBLE CABLES
1.6	SERVICE MAINS AND FLAT CABLES OF ISI FOR SUBMERSIBLE MOTORS.
1.7	FLUSH TYPE SWITCHES AND ACCESSORIES
1.8	MODULAR SWITCHES AND ACCESSORIES
	SECTION - 2
2.1	PANEL MOUNTING SWITCH DISCONNECTOR FUSE UNITS
2.2	ON LOAD CHANGE OVER SWITCHES (OPEN EXECUTION)
2.3	OFF LOAD CHANGEOVER SWITCHES IN SS ENCLOSURE
2.4	AUTO TRANSFER SWITCH
2.5	REWIRABLE/ DOUBLE BREAK SWITCHES IN SS ENCLOSURE
2.6	HRC FUSE LINKS (BOLTED TYPE)
2.7	PORCELAIN REWIRABLE FUSE UNITS.
2.8	VOLTAGE SURGE PROTECTORS
2.9	PANEL MOUNTING MCCBs/ ACBs/BUS DUCTs
2.10	MCBs
2.11	ISOLATORS
2.12	RCCBs
2.13	MCB DISTRIBUTION BOARDS
	SECTION - 3
3.1	STREET LIGHT LUMINAIRES
3.2	LED POST TOP LANTERN LUMINAIRES

SL. NO.	INDEX
3.3	ACCESSORIES FORMV / SV /MH LUMINAIRES i.e., COPPER BALLASTS, ENEGRY SAVING ELECTRONIC BALLAST FOR STREETLIGHT, CAPACITORS, IGNITORS
3.4	LAMPS
3.5	AUTOMATIC STREETLIGHT CONTROL SYSTEMS
3.6	INTERNAL LUMINAIRES
3.7	FLOURSCENT / CFL LAMPS/LED BULBS
3.8	LED LUMINAIRES
	SECTION - 4
4.1	U.G. CABLES
4.2	CABLETRAYS
4.3	DOUBLE WALL CORRUGATED HDPE PIPE
	SECTION - 5
5.1	FANS
5.2	WATER HEATERS (CONVENTIONAL & SOLAR)
5.3	ACCESSORIES FOR WATER HEATERS
5.4	PUMPSETS AND ITS CONTROL PANEL BOARDS
5.5	AIR CONDITIONERS(SPLIT/CASETTEE)
5.6	HVAC SYSTEMS(VRV/VRF)
5.7	EVAPORATIVE AIR-COOLING SYSTEM
5.8	STABILIZERS
5.9	REPAIRING OF FANS, COOLERS, PUMPS, MOTORS, FRIDGES AND AIR CONDITIONERS
	SECTION - 6
6.1	SWAGED, OCTOGANAL AND GRP POLES AND ACCESSORIES.
6.2	LT PANELAND ACCESSORIES

6.3	SUBSTATION EQUIPMENT AND TRANSFORMERS
6.4	MAINTENANCE AND REPAIRS OF TRANSFORMERS
6.5	OVER HEAD LINES AND LINE MATERIALS
6.6	LIGHNING PROTECTIVE SYSTEMS
6.7	EARTHINGS
	SECTION - 7
7.1	LOCAL AREA NETWORK
7.2	RACEWAYS AND JUNCTION BOXES
7.3	COMPUTERS, PRINTERS, SCANNERS
7.4	SMALL EPABX SYSTEM
7.5	LARGE EPABX SYSTEM
7.6	C.C.TV & SURVEILLANCE SYSTEM
7.7	PUBLIC ADDRESS SYSTEMS
7.8	AUDIO-VIDEO SYSTEMS
	SECTION - 8
8.1	MISCELLANIOUS ITEMS
8.2	LEGEND PLATES
8.3	COPPER/ALUMINIUM/GI ITEMS
8.4	SMC TYPE SUPPORTS FOR BUSBARS
8.5	LABOUR RATES
	SECTION - 9
9.1	WIRELESS FIRE ALARAM SYSTEM
9.2	ADDRESSABLE – FIRE ALARAM SYSTEM
9.3	CONVENTIONAL – FIRE ALARAM SYSTEM
9.4	POWDER BASED FIRE EXTINGUISHERS
9.5	FIRE HYDRANT AND SPRINKLER SYSTEM

	SECTION - 10
10.1	DIESEL GENERATORS
	SECTION - 11
11.1	INVERTERS AND ONLINE UPS SYSTEMS
	SECTION- 12
12.1	TEMPORARY ILLUMINATION
12.2	HIRING OF GENERATORS (TE-DG)
	SECTION- 13
13	13.1 ,13.2 & 13.3 LIFTS & Dismantling
	SECTION- 14 (Electrical items recommended by Chief Engineer (APMSIDC))
14.1	MEDICAL GAS PIPELINE SYSTEM
14.2.	STP & ETP WORKS (ELECTRO-MECHANICAL ITEMS)
14.3	BUILDING MANAGEMENT SYSTEMS
14.4	ACCESS CONTROL SYSTEMS
14.5	NURSE-CALL SYSTEM
A-I	List of recommended Brands / manufacturers
A-II	General Guidelines

SCHEDULED RATES FOR ELECTRICAL & ELECTRO MECHANICAL ITEMS SOR 2025-26

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			SECTION - 1		
		1.1	M.S. CONDUIT PIPES		
1		ELEC-1.1.1	Supply of ISI, ... outer dia,..... thickness MS conduit pipe as per IS-9537 Part II . Makes: As per list of recommended brands		
	MAT-02621	a	20 mm (1.6 mm thick)	1 RM	134
	MAT-02622	b	25 mm (1.6 mm thick)	1 RM	173
	MAT-02623	c	32 mm (1.6 mm thick)	1 RM	246
	MAT-02624	d	38 mm (2.0 mm thick)	1 RM	403
	MAT-02625	e	50 mm (2.0 mm thick)	1 RM	515
2		ELEC-1.1.2	Supply of MS Junction box normal range big size long neck.		
	MAT-02626	a	19/20 mm	1 No	38
	MAT-02627	b	25 mm	1 No	45
	MAT-02628	c	32 mm	1 No	104
	MAT-02629	d	40/38 mm	1 No	149
	MAT-02630	e	50 mm	1 No	284
3		ELEC-1.1.3	Supply of MS Junction deep box.		
	MAT-02631	a	20/25 mm	1 No	98
	MAT-02632	b	32 mm	1 No	173
	MAT-	c	40 mm	1 No	209

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	02633				
	MAT-02634	d	50 mm	1 No	254
4		ELEC-1.1.4	Supply of MS Inspection Bends.		
	MAT-02635	a	19/20 mm	1 No	33
	MAT-02636	b	25 mm	1 No	38
	MAT-02637	c	32 mm	1 No	83
	MAT-02638	d	40/38 mm	1 No	119
	MAT-02639	e	50 mm	1 No	254
5		ELEC-1.1.5	Supply of MS Inspection Tee.		
	MAT-02640	a	19/20 mm	1 No	38
	MAT-02641	b	25 mm	1 No	45
	MAT-02642	c	32 mm	1 No	104
	MAT-02643	d	40/38 mm	1 No	128
	MAT-02644	e	50 mm	1 No	261
6		ELEC-1.1.6	Supply of MS Inspection Elbow.		
	MAT-02645	a	19/20 mm	1 No	33
	MAT-02646	b	25 mm	1 No	45
	MAT-02647	c	32 mm	1 No	83

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02648	d	40/38 mm	1 No	104
	MAT-02649	e	50 mm	1 No	239
7		ELEC-1.1.7	Supply of MS Inspection 10 Gauge G.I. check nut of size		
	MAT-02650	a	19/20 mm	100 Nos	298
	MAT-02651	b	25 mm	100 Nos	373
	MAT-02652	c	32 mm	100 Nos	745
	MAT-02653	d	40/38 mm	100 Nos	1081
	MAT-02654	e	50 mm	100 Nos	1804
8		ELEC-1.1.8	Supply of Saddles with Base.		
	MAT-02655	a	19/20 mm	100 Nos	321
	MAT-02656	b	25 mm	100 Nos	336
	MAT-02657	c	32 mm	100 Nos	566
	MAT-02658	d	40/38 mm	100 Nos	933
	MAT-02659	e	50 mm	100 Nos	1178
9		ELEC-1.1.9	Supply of.....20 gauge Saddles.		
	MAT-02660	a	19/20 mm	100 Nos	164
	MAT-02661	b	25 mm	100 Nos	224
	MAT-02662	c	32 mm	100 Nos	358

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02663	d	40/38 mm	100 Nos	463
	MAT-02664	e	50 mm	100 Nos	566
10		ELEC-1.1.10	Supply of 16 Gauge socket coupler.		
	MAT-02665	a	19/20 mm	12 Nos	90
	MAT-02666	b	25 mm	12 Nos	119
	MAT-02667	c	32 mm	12 Nos	194
	MAT-02668	d	38 mm	12 Nos	254
	MAT-02669	e	40mm	12 Nos	284
	MAT-02670	f	50 mm	12 Nos	596
11		ELEC-1.1.11	Supply of 19mm Ball Socket.		
	MAT-02671	a	19 mm	12 Nos	343
	MAT-02672	b	25 mm	12 Nos	521
		1.2	PVC CONDUITS		
12		ELEC-1.2.1	Supply of ISI marked heavy grade with IS:9537-part 3 rigid PVC Conduit. Makes: As per list of recommended brands		
	MAT-02673	a	20 mm outer dia (1.95 - 2.10) mm thickness	1 RM	36
	MAT-02674	b	25 mm outer dia (2.00 - 2.20) mm thickness	1 RM	46
13		ELEC-1.2.2	Supply of ISI marked medium grade with IS:9537-part 3 rigid PVC Conduit. Makes: As per list of recommended brands		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02675	a	20mm outer dia (1.40 -1.55) mm thickness	1 RM	26
	MAT-02676	b	25mm outer dia (1.60 -1.80) mm thickness	1 RM	36
	MAT-02677	c	32mm outer dia (1.90 - 2.10) mm thickness	1 RM	56
	MAT-02678	d	40mm outer dia (2.10 - 2.30) mm thickness	1 RM	75
	MAT-02679	e	50mm outer dia (2.60 - 2.85) mm thickness	1 RM	107
		NOTE: Add 5% extra on above price for Red/Yellow/Blue/Black/Green Colour PVC pipes for specific purpose Usage			
14		ELEC-1.2.3	Supply of ISI marked width and 12mm height Casing and Caping. Makes: As per list of recommended brands		
	MAT-02680	a	19/20 mm	1 RM	28
	MAT-02681	b	25mm	1 RM	43
	MAT-02682	c	32mm	1 RM	50
	MAT-02683	d	38/40mm	1 RM	82
15		ELEC-1.2.4	Supply of dia FRPP corrugated Flexible conduit. Makes: As per list of recommended brands		
	MAT-02684	a	19/20 mm	1 RM	17
	MAT-02685	b	25mm	1 RM	21
	MAT-02686	c	32mm	1 RM	33
	MAT-02687	d	38/40mm	1 RM	46
	MAT-02688	e	50 mm	1 RM	76

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
16		ELEC-1.2.5	Supply of dia PVC Flexible Couplings for FRPP Corrugated conduit. Makes: As per list of recommended brands		
	MAT-02689	a	19/20 mm	1 No	14
	MAT-02690	b	25mm	1 No	21
	MAT-02691	c	32mm	1 No	36
	MAT-02692	d	40mm	1 No	43
	MAT-02693	e	50 mm	1 No	78
17		ELEC-1.2.6	Supply of dia PVC Junction Boxes confirms to IS : 3419 Makes: As per list of recommended brands		
	MAT-02694	a	19/20 mm	1 No	27
	MAT-02695	b	25mm	1 No	28
	MAT-02696	c	32mm	1 No	50
	MAT-02697	d	40mm	1 No	52
	MAT-02698	e	50 mm	1 No	71
18		ELEC-1.2.7	Supply of dia PVC deep Junction Boxes confirms to IS: 3419. Makes: As per list of recommended brands		
	MAT-02699	a	19/20 mm	1 No	32
	MAT-02700	b	25mm	1 No	36
	MAT-02701	c	32mm	1 No	57

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02702	d	40/38 mm	1 No	62
	MAT-02703	e	50 mm	1 No	90
19		ELEC-1.2.8	Supply of dia PVC Bends. Makes: As per list of recommended brands		
	MAT-02704	a	19/20 mm dia 1.5mm thick	1 No	9
	MAT-02705	b	25mm dia 1.5mm thick	1 No	12
	MAT-02706	c	32mm dia 2.0mm thick	1 No	26
	MAT-02707	d	40 mm dia 2.0mm thick	1 No	28
	MAT-02708	e	50 mm dia 2.0mm thick	1 No	41
20	MAT-02709	ELEC-1.2.9	Dummy Cover for PVC junction boxes	1 No	7
21		ELEC-1.2.10	Supply and fixing of DLP PVC Mini trunking with independent cover on wall/ ceiling size (width & height) including cost of all accessories like end caps, Internal/External angles, flat Angles, flat joints etc., with all labour charges, transportation etc., complete.		
		a	32mm x 20 mm	1 RM	123
		b	105/100 x 50 mm	1 RM	587
		c	150mm x 50mm	1 RM	880
		1.3	HOT DIP GALVANIZED METAL BOXES for switch boards		
22		ELEC-1.3.1	Supply of..... Hot Dip galvanized 18 SWG Module metal box with earthing terminal		
	MAT-02710	a	1 or 2	1 No	68

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02711	b	3	1 No	95
	MAT-02712	c	4	1 No	114
	MAT-02713	d	6	1 No	155
	MAT-02714	e	8 or 9	1 No	203
	MAT-02715	f	12	1 No	245
		g	16	1 No	327
		h	18	1 No	367
			METALLIC BOXES		
23		ELEC-1.3.2	Supply of size (length x width x depth)18 SWG sheet steel boxes duly finished with two coats of zinc chromate red oxide paint and enamel paint of matching colour to wall		
	MAT-02716	a	100mmx100x50mm	1 No	61
	MAT-02717	b	175mmx100x60mm	1 No	73
	MAT-02718	c	150mmx150x60mm	1 No	85
	MAT-02719	d	200mmx150x60mm	1 No	97
	MAT-02720	e	200mmx250x75mm	1 No	121
	MAT-02721	f	250mmx300x75mm	1 No	212
	MAT-02722	g	300mmx375x100mm	1 No	273
		1.4	T.W. BOARDS		
24		ELEC-1.4.1	Supply of T.W. Deep Box of Size		
	MAT-02723	a	4" x 4"	1 No	13

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02724	b	4" x 7	1 No	24
	MAT-02725	c	6" x 6"	1 No	26
	MAT-02726	d	6" x 8"	1 No	39
	MAT-02727	e	8" x 10"	1 No	65
	MAT-02728	f	10" x 12"	1 No	91
	MAT-02729	g	12" x 15"	1 No	142
25		ELEC-1.4.2	Supply of Decolam Board of size		
	MAT-02730	a	4" x 4"	1 No	20
	MAT-02731	b	4" x 7	1 No	33
	MAT-02732	c	6" x 6"	1 No	46
	MAT-02733	d	6" x 8"	1 No	51
	MAT-02734	e	8" x 10"	1 No	91
	MAT-02735	f	10" x 12"	1 No	142
	MAT-02736	g	12" x 15"	1 No	214
26		ELEC-1.4.3	Supply of Peeta Boards of size		
	MAT-02737	a	9" x 14"	1 No	65
	MAT-02738	b	12" x 10"	1 No	72
	MAT-02739	c	15" x 20"	1 No	246

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02740	d	18" x 24"	1 No	356
	MAT-02741	e	18" x 30"	1 No	440
27		ELEC-1.4.4	Supply of No.8 Screws of		
	MAT-02742	a	12mm.	100 Nos	78
	MAT-02743	b	25mm.	100 Nos	97
	MAT-02744	c	30mm.	100 Nos	117
	MAT-02745	d	35/38mm.	100 Nos	129
	MAT-02746	e	50mm	100 Nos	151
	MAT-02747	f	63/75mm.	100 Nos	181
		1.5	COPPER FLEXIBLE CABLES (AS PER IS:694)		
28		ELEC-1.5.1	Supply of..... ISI marked FRLS/ FRLS-H / HFFR / ZHFR PVC insulated flexible copper cables 1100V grade as per IS: 694/1990 & IS:17048/2018 specification for copper cable. Makes: As per list of recommended brands as category I		
	MAT-02748	a	1.0 Sq mm	100 RM	1424
	MAT-02749	b	1.5 Sq mm	100 RM	2046
	MAT-02750	c	2.5 Sq mm	100 RM	3305
	MAT-02751	d	4.0 Sq mm	100 RM	5046
	MAT-02752	e	6.0 Sq mm	100 RM	7721
	MAT-02753	f	10.0 Sq mm	100 RM	11920

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02754	g	16.0 Sq mm	100 RM	18828
29		ELEC-1.5.2	Supply of..... ISI marked FRLS/ FRLS-H / HFFR / ZHFR PVC insulated flexible copper cables 1100V grade as per IS: 694/1990 & IS:17048/2018 specification for copper cable. Makes: As per list of recommended brands as category II		
	MAT-02755	a	1.0 Sq mm	100 RM	1254
	MAT-02756	b	1.5 Sq mm	100 RM	1787
	MAT-02757	c	2.5 Sq mm	100 RM	2899
	MAT-02758	d	4.0 Sq mm	100 RM	4470
	MAT-02759	e	6.0 Sq mm	100 RM	6908
	MAT-02760	f	10.0 Sq mm	100 RM	10498
	MAT-02761	g	16.0 Sq mm	100 RM	17473
30		ELEC-1.5.3	Supply of..... ISI marked FRLS/ FRLS-H / HFFR / ZHFR PVC insulated flexible copper cables 1100V grade as per IS: 694/1990 & IS:17048/2018 specification for copper cable. Makes: As per list of recommended brands as category III		
	MAT-02762	a	1.0 Sq mm	100 RM	1083
	MAT-02763	b	1.5 Sq mm	100 RM	1517
	MAT-02764	c	2.5 Sq mm	100 RM	2438
	MAT-02765	d	4.0 Sq mm	100 RM	3657
	MAT-02766	e	6.0 Sq mm	100 RM	5689
	MAT-02767	f	10.0 Sq mm	100 RM	9008

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02768	g	16.0 Sq mm	100 RM	13816
			SHEATHED FLEXIBLE COPPER CABLES		
31		ELEC-1.5.4	Supply of ISI marked, PVC insulated and sheathed FRLS/FRLS-H round copper cable for voltage up to 1100V as per IS 694/1990. Makes: As per list of recommended brands as category I		
	MAT-05466	a	Single Core, 25 Sq mm	1 RM	298
	MAT-05467	b	Single Core, 35 Sq mm	1 RM	420
	MAT-05468	c	Single Core, 50 Sq mm	1 RM	596
	MAT-05469	d	Single Core, 70 Sq mm	1 RM	813
	MAT-02769	e	2 core, 1.5 Sq mm	1 RM	61
	MAT-02770	f	2 core, 2.5 Sq mm	1 RM	95
	MAT-02771	g	2 core, 4.0 Sq mm	1 RM	129
	MAT-05470	h	2 core, 6 Sq mm	1 RM	197
	MAT-05471	i	2 core, 10 Sq mm	1 RM	285
	MAT-05472	j	2 core, 16 Sq mm	1 RM	339
	MAT-02772	k	3 core, 1.5 Sq mm	1 RM	82
	MAT-02773	l	3 core, 2.5 Sq mm	1 RM	136
	MAT-02774	m	3 core, 4.0 Sq mm	1 RM	190
	MAT-05473	n	3 core, 6 Sq mm	1 RM	237

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-05474	o	3 core, 10 Sq mm	1 RM	313
	MAT-05475	p	3 core, 16 Sq mm	1 RM	503
	MAT-02775	q	4 core, 1.5 Sq mm	1 RM	109
	MAT-02776	r	4 core, 2.5 Sq mm	1 RM	170
	MAT-02777	s	4 core, 4.0 Sq mm	1 RM	258
	MAT-05476	t	4 core, 6 Sq mm	1 RM	378
	MAT-05477	u	4 core, 10 Sq mm	1 RM	583
	MAT-05478	v	4 core, 16 Sq mm	1 RM	739
		w	2 core, 1.0 Sq.mm	1 RM	31
		x	4 core, 0.5 sq.mm	1 RM	99
		z	12 core, 0.5 sq.mm	1 RM	202
32		ELEC-1.5.5	Supply of ISI marked PVC insulated and sheathed FRLS/FRLS-H round copper cable for voltage up to 1100V as per IS 694/1990. Makes: As per list of recommended brands as category II		
	MAT-05479	a	Single Core, 25 Sq mm	1 RM	265
	MAT-05480	b	Single Core, 35 Sq mm	1 RM	386
	MAT-05481	c	Single Core, 50 Sq mm	1 RM	522
	MAT-05482	d	Single Core, 70 Sq mm	1 RM	751
	MAT-02778	e	2 core, 1.5 Sq mm	1 RM	54
	MAT-02779	f	2 core, 2.5 Sq mm	1 RM	82
	MAT-	g	2 core, 4.0 Sq mm	1 RM	116

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	02780				
	MAT-05483	h	2 core, 6 Sq mm	1 RM	182
	MAT-05484	i	2 core, 10 Sq mm	1 RM	258
	MAT-05485	j	2 core, 16 Sq mm	1 RM	325
	MAT-02781	k	3 core, 1.5 Sq mm	1 RM	75
	MAT-02782	l	3 core, 2.5 Sq mm	1 RM	122
	MAT-02783	m	3 core, 4.0 Sq mm	1 RM	162
	MAT-05486	n	3 core, 6 Sq mm	1 RM	223
	MAT-05487	o	3 core, 10 Sq mm	1 RM	291
	MAT-05488	p	3 core, 16 Sq mm	1 RM	461
	MAT-02784	q	4 core, 1.5 Sq mm	1 RM	95
	MAT-02785	r	4 core, 2.5 Sq mm	1 RM	136
	MAT-02786	s	4 core, 4.0 Sq mm	1 RM	216
	MAT-05489	t	4 core, 6 Sq mm	1 RM	352
	MAT-05490	u	4 core, 10 Sq mm	1 RM	535
	MAT-05491	v	4 core, 16 Sq mm	1 RM	698
		w	2 core, 1.0 sq.mm	1 RM	26
		x	4 core, 0.5 sq.mm	1 RM	31

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		y	12 core, 0.5 sq.mm	1 RM	49
33	MAT-02787	ELEC-1.5.6 a	Supply of ISI marked 23 / 0060 twin core twisted / flat heavy Copper wire. Makes: As per list of recommended brands.	100 RM	1288
34		ELEC-1.5.6 b	Supply of ISI marked 23 / 0060 three core twisted / flat heavy Copper wire. Makes: As per list of recommended brands.	100 RM	1679
35		ELEC-1.5.7	Supply and Transportation of RG 6 co-axial cable for TVs. Makes: As per list of recommended brands as category I.	1 RM	30
36		ELEC-1.5.8	Supply and Transportation of RG 6 co-axial cable for TVs. Makes: As per list of recommended brands as category II.	1 RM	16
		1.6	SERVICE MAINS AND FLAT CABLE FOR SUBMERSIBLE MOTORS.		
37		ELEC-1.6.1	Supply of ISI marked WPSC (Weatherproof Single Core) ISI Aluminum Wire. Makes: As per list of recommended brands.		
	MAT-02788	a	2.5 Sq mm	100 RM	911
	MAT-02789	b	6 Sq mm	100 RM	1816
	MAT-02790	c	10 Sq mm	100 RM	1980
	MAT-02791	d	16 Sq mm	100 RM	3300
38		ELEC-1.6.2	Supply of ISI marked WPTC (Weatherproof Twin Core) ISI Aluminum Wire. Makes: As per list of recommended brands.		
	MAT-02792		6 Sq mm	100 RM	3696
	MAT-02793		10 Sq mm	100 RM	4469

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			16 Sq mm	100 RM	6900
39		ELEC-1.6.3	Supply of 3 Core.....ISI marked Flat Copper cable of ISI for Submersible Motors confirming to IS: 694:1990. Makes: As per list of recommended brands as category I		
	MAT-02794	a	1.5 Sq mm	1 RM	75
	MAT-02795	b	2.5 Sq mm	1 RM	109
	MAT-02796	c	4.0 Sq mm	1 RM	170
	MAT-02797	d	6.0 Sq mm	1 RM	244
	MAT-02798	e	10.0 Sq mm	1 RM	386
	MAT-02799	f	16.0 Sq mm	1 RM	507
40		ELEC-1.6.4	Supply of 3 Core..... ISI marked, Flat Copper cable of ISI for Submersible Motors confirming to IS:694:1990. Makes: As per list of recommended brands as category II		
	MAT-02800	a	1.5 Sq mm	1 RM	68
	MAT-02801	b	2.5 Sq mm	1 RM	98
	MAT-02802	c	4.0 Sq mm	1 RM	151
	MAT-02803	d	6.0 Sq mm	1 RM	216
	MAT-02804	e	10.0 Sq mm	1 RM	352
	MAT-02805	f	16.0 Sq mm	1 RM	461
		1.7	FLUSH TYPE SWITCHES AND ACCESSORIES		
41		ELEC-1.7.1	Supply of ISI marked. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02806	a	6A, 1 Way flush type Switch.	1 No	18
	MAT-02807	b	6A, 2 Way flush type Switch.	1 No	22
	MAT-02808	c	6A, 2 pin flush type Socket.	1 No	21
	MAT-02809	d	6A, 3 pin flush type Socket with shutter.	1 No	27
	MAT-02810	e	6A, flush type Neon Indicator.	1 No	21
	MAT-02811	f	6A, Triangle Plug Top of	1 No	35
	MAT-02812	g	1 Way, flush type Bed Switch / Bell Push.	1 No	22
	MAT-02813	h	16A, flush type Switch.	1 No	69
	MAT-02814	i	16A, flush type Socket with shutter.	1 No	69
	MAT-02815	j	16A, flush type Switch Socket combined (2 in one).	1 No	104
	MAT-02816	k	16A, Triangle Plug Top	1 No	53
	MAT-02817	l	Step type Electronic Regulator, Socket size of wattage 100/120W.	1 No	208
	MAT-02818	m	3 Plate Jumbo Ceiling Rose.	1 No	22
	MAT-02819	n	BH / SBH.	1 No	21
	MAT-02820	o	Pendent Holder / Adopter.	1 No	18
	MAT-02821	p	Telephone Jack with Connector.	1 No	53

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02822	q	TV Antenna Outlet.	1 No	29
	MAT-02823	r	15A/10A Flush type Fuse.	1 No	35
	MAT-02824	s	32A DP Flush type.	1 No	110
	MAT-02825	t	Calling Bell.	1 No	76
	MAT-02826	u	Buzzer.	1 No	64
	MAT-02827	v	Ding Dong Bell.	1 No	156
	MAT-02828	w	Electronic Musical Bell.	1 No	254
	MAT-02829	x	Remote Bell.	1 No	734
	MAT-02830	y	MC Holder.	1 No	23
	MAT-02831	z	Spike Guard with 1 No Switch and 4 Nos Sockets.	1 No	404
	MAT-02832	A	Spike Guard with 4 No Switches and 4 Nos Sockets.	1 No	578
		1.8	MODULAR SWITCHES AND ACCESSORIES		
42		ELEC-1.8.1	Supply of ISI marked Makes: As per list of recommended brands as category I.		
	MAT-02833	a	6A / 10A, 1 Way, 1 Module, Modular Switch.	1 No	72
	MAT-02834	b	6A / 10A, 2 Way, 1 Module, Modular Switch.	1 No	80
	MAT-02835	c	6A / 10A, 2 Pin, 2 Module, Modular Socket.	1 No	80
	MAT-02836	d	6A / 10A, 3-Pin, 2 Module, Modular Socket with shutter.	1 No	122
	MAT-02837	e	6A / 10A, 1 Module, Modular Switch with Neon Indicator.	1 No	99

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02838	f	6A / 10A, Modular Bell Push with Neon Indicator.	1 No	117
	MAT-02839	g	16A / 10A, Modular Flush Fuse with Neon Indicator.	1 No	124
	MAT-02840	h	16A / 20A, 1 Way, 1 Module, Modular Switch.	1 No	124
	MAT-02841	i	16A / 20A, 2 Way, 1 Module, Modular Switch.	1 No	135
	MAT-02842	j	20A, 1 Way, 1 Module, Modular Switch with Indicator.	1 No	135
	MAT-02843	k	20A, Modular Socket with shutter.	1 No	189
	MAT-02844	l	16A/6A, 1 way, Combi Socket Modular Socket with shutter	1 No	193
	MAT-02845	m	Deleted	1 No	
	MAT-02846	n	2 Module Modular type electronic step type Fan Regulator.	1 No	421
	MAT-02847	o	Modular socket type Telephone jack with Connector	1 No	84
	MAT-02848	p	Modular co-Axial socket type TV Antenna outlet.	1 No	84
	MAT-02849	q	Push type button motor starter for A.C Units	1 No	678
	MAT-08755	r	32A Modular type Double pole Switch with indicator	1 No	298
	MAT-08756	s	One Module PVC Blanking plate	1 No	21
	MAT-08757	t	Skirting Light with LED 230V 3 Module	1 No	149
43		ELEC-1.8.2	Supply of ISI marked. Makes: As per list of recommended brands as category II		
	MAT-02850	a	6A / 10A, 1 Way, 1 Module Modular Switch.	1 No	52
	MAT-02851	b	6A / 10A, 2 Way, 1 Module Modular Switch.	1 No	61

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02852	c	6A / 10A, 2 Pin, 2 Module Modular Socket.	1 No	61
	MAT-02853	d	6A / 10A, 3- Pin, 2 Module Modular Socket with shutter.	1 No	94
	MAT-02854	e	6A / 10A, 1 Module, Modular Switch with Neon Indicator.	1 No	65
	MAT-02855	f	6A / 10A, Modular Bell Push with Neon Indicator.	1 No	75
	MAT-02856	g	16A / 10A, Modular Flush Fuse with Neon Indicator.	1 No	82
	MAT-02857	h	16A / 20A, 1 Way, 1 Module Modular Switch.	1 No	82
	MAT-02858	i	16A / 20A, 2 Way, 1 Module Modular Switch.	1 No	92
	MAT-02859	j	20A, 1 Way, 1 Module, Modular Switch with Indicator.	1 No	86
	MAT-02860	k	20A Modular Socket with shutter.	1 No	159
	MAT-02861	l	16A/6A, 1 way, Combi Socket Modular Socket with shutter	1 No	159
	MAT-02862	m	Deleted	1 No	
	MAT-02863	n	2 Module, Modular type, electronic step type Fan Regulator.	1 No	342
	MAT-02864	o	Modular socket type Telephone jack with Connector	1 No	56
	MAT-02865	p	Modular co-Axial socket type TV Antenna outlet.	1 No	56
	MAT-02866	q	Push type button motor starter for A.C Units	1 No	632
	MAT-08758	r	32A Modular type Double pole Switch with indicator	1 No	255
	MAT-08759	s	One Module PVC Blanking plate	1 No	17
	MAT-08760	t	Skirting Light with LED 230V 3 Module	1 No	128

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			COVER FRAMES		
44		ELEC-1.8.3	Supply of Makes: As per list of recommended brands as category I.		
	MAT-02867	a	1 or 2 Modular Cover Frame.	1 No	76
	MAT-02868	b	3 Modular Cover Frame.	1 No	89
	MAT-02869	c	4 Modular Cover Frame.	1 No	101
	MAT-02870	d	6 Modular Cover Frame.	1 No	152
	MAT-02871	e	8 Modular Horizontal / Vertical Cover Frame.	1 No	197
	MAT-02872	f	12 Modular Vertical Cover Frame.	1 No	240
		g	16 Modular Cover Frame.	1 No	320
		h	18 Modular Cover Frame.	1 No	360
45		ELEC-1.8.4	Supply of Makes: As per list of recommended brands as category II		
	MAT-02873	a	1 or 2 Modular Cover Frame.	1 No	63
	MAT-02874	b	3 Modular Cover Frame.	1 No	76
	MAT-02875	c	4 Modular Cover Frame.	1 No	89
	MAT-02876	d	6 Modular Cover Frame.	1 No	127
	MAT-02877	e	8 Modular Horizontal / Vertical Cover Frame.	1 No	159
	MAT-02878	f	12 Modular Vertical Cover Frame.	1 No	190
		g	16 Modular Cover Frame.	1 No	253
		h	18 Modular Cover Frame.	1 No	285

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			SECTION - 2		
		2.1	PANEL MOUNTING SWITCH DISCONNECTOR FUSE UNITS (SDFU)		
46		ELEC-2.1.1	Supply of ISI marked TPN Switch Disconnecter Fuse Unit, Cubical type without fuses as per IS: 13947/IEC 60947-3 Makes: As per list of recommended brands as category I.		
	MAT-02879	a	32A	1 No	1543
	MAT-02880	b	63A	1 No	2635
	MAT-02881	c	125A	1 No	6291
	MAT-02882	d	200A	1 No	8249
	MAT-02883	e	250A	1 No	9851
	MAT-02884	f	400A	1 No	15192
	MAT-02885	g	630A	1 No	25756
47		ELEC-2.1.2	Supply of ISI marked TPN Switch Disconnecter Fuse Unit, Cubical type without fuses as per IS: 13947/IEC 60947-3 Makes: As per list of recommended brands as category II		
	MAT-02886	a	32A	1 No	1306
	MAT-02887	b	63A	1 No	1935
	MAT-02888	c	125A	1 No	4332
	MAT-02889	d	200A	1 No	6528
	MAT-02890	e	250A	1 No	7359
	MAT-02891	f	400A	1 No	11276

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02892	g	630A	1 No	18872
		2.2	ON LOAD CHANGEOVER SWITCHES (OPEN EXECUTION)		
48		ELEC-2.2.1	Supply of ISI marked 4 Pole Change Over Switch on Load with open Execution as per IS:13947 Makes: As per list of recommended brands as category I.		
	MAT-02893	a	63A	1 No	5839
	MAT-02894	b	125A	1 No	10967
	MAT-02895	c	200A	1 No	14670
	MAT-02896	d	250A	1 No	20936
	MAT-02897	e	400A	1 No	31619
	MAT-02898	f	630A	1 No	37744
49		ELEC-2.2.2	Supply of ISI marked 4 Pole Change Over Switch on Load with open Execution as per IS:13947 Makes: As per list of recommended brands as category II.		
	MAT-02899	a	32 A	1 No	2136
	MAT-02900	b	63A	1 No	5270
	MAT-02901	c	125A	1 No	10397
	MAT-02902	d	200A	1 No	13531
	MAT-02903	e	250A	1 No	19228
	MAT-02904	f	400A	1 No	29626
	MAT-	g	630A	1 No	34895

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	02905				
		2.3	OFF LOAD CHANGE OVER SWITCHES IN SS ENCLOSURE		
50		ELEC-2.3.1	Supply of Off load Changeover Switch in sheet steel enclosure as per IS:13947 Makes : As per list of recommended brands as category I		
		a	32A 240V DP	1 No	1632
		b	63A 415V FP	1 No	5614
		c	100A 415V FP	1 No	9857
51		ELEC-2.3.2	Supply of Off load Changeover Switch in sheet steel enclosure as per IS:13947 Makes : As per list of recommended brands as category I		
		a	32A 240V DP	1 No	947
		b	63A 415V FP	1 No	3264
		c	100A 415V FP	1 No	6136
			ON LOAD CHANGE OVER SWITCHES IN SS ENCLOSURE		
52		ELEC-2.3.3	Supply of ISI marked 4 pole On load Changeover Switch in sheet steel enclosure as per IS:13947 Makes: As per list of recommended brands as category I		
	MAT-02906	a	63A	1 No	7380
	MAT-02907	b	125A	1 No	13564
	MAT-02908	c	200A	1 No	17084
53		ELEC-2.3.4	Supply of ISI marked 4 pole On load Changeover Switch in sheet steel enclosure as per IS:13947 Makes: As per list of recommended brands as category II		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02909	a	63A	1 No	6642
	MAT-02910	b	125A	1 No	12208
	MAT-02911	c	200A	1 No	15376
		2.4	AUTO TRANSFER SWITCH		
54		ELEC-2.4.1	Supply of auto transfer switch for instantaneous switching between sources as per IEC 60947-6-1, Closed transition, (bare unit-without enclosure) with voltage surge suppressor, communication interface etc., complete. Makes: As per list of recommended brands.		
	MAT-02912	a	125A, 415VAC, FP	1 No	41542
	MAT-02913	b	160A, 415VAC FP	1 No	43322
	MAT-02914	c	200A 415VACFP	1 No	54005
	MAT-02915	d	250A, 415VAC FP	1 No	60571
	MAT-02916	e	315A, 415VAC FP	1 No	63318
	MAT-02917	f	400A, 415VAC FP	1 No	72485
55		ELEC-2.4.2	Supply of auto transfer switch for instantaneous switching between sources as per IEC 60947-6-1, Closed transition, (bare unit-without enclosure) with voltage surge suppressor, communication interface etc., complete. Makes: As per list of recommended brands.		
	MAT-02918	a	630A,415VAC FP	1 No	93012
	MAT-02919	b	800A, 415VAC FP	1 No	118690
	MAT-02920	c	1000A,415VAC FP	1 No	147176

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02921	d	1250A, 415VAC FP	1 No	182783
	MAT-02922	e	1600 A, 415VAC FP	1 No	226698
	MAT-02923	f	2000 A, 415VAC FP	1 No	331145
	MAT-02924	g	2500 A, 415VAC FP	1 No	365565
	MAT-02925	h	3200 A, 415VAC FP	1 No	470012
		2.5	REWIRABLE / DOUBLE BREAK SWITCHES IN SS ENCLOSURE		
56		ELEC-2.5.1	Supply of ISI marked Rewireable Fuse Switch in SS enclosure as per IS:13947 Makes: As per list of recommended brands as category I		
	MAT-02926	a	32A 240V SPN	1 No	1080
	MAT-02927	b	32A 415V TPN	1 No	2413
	MAT-02928	c	63A 415V TPN	1 No	4953
	MAT-02929	d	100A 415V TPN	1 No	9144
57		ELEC-2.5.2	Supply of Double Break Switch in SS enclosure without fuses as per IS:13947 Makes: As per list of recommended brands as category II		
	MAT-02930	a	100A 415V TPN	1 No	8226
	MAT-02931	b	200A 415V TPN	1 No	11834
58		ELEC-2.5.3	Supply of Rewireable Fuse Switch in SS enclosure as per IS:13947 Makes: As per list of recommended brands as category I		
	MAT-02932	a	32A 240V SPN	1 No	762

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02933	b	32A 415V TPN	1 No	1168
	MAT-02934	c	63A 415V TPN	1 No	2794
	MAT-02935	d	100A 415V TPN	1 No	5334
59		ELEC-2.5.4	Supply of Double Break Switch in SS enclosure without fuse as per IS:13947 Makes: As per list of recommended brands as category II		
	MAT-02936	a	100A 415V TPN	1 No	5461
	MAT-02937	b	200A 415V TPN	1 No	8890
		2.6	HRC FUSE LINKS (DIN/BOLTED TYPE)		
60		ELEC-2.6.1	Supply of.....ISI marked HRC Fuse Links as per IS 13703-Part 2/IEC 60269- Part 2 Makes: As per list of recommended brands as category I		
	MAT-02938	a	6A to 35 A	1 No	63
	MAT-02939	b	45A to 63A	1 No	96
	MAT-02940	c	100 A to 160 A	1 No	299
	MAT-02941	d	250A to 350A	1 No	444
	MAT-02942	e	400A	1 No	845
	MAT-05457	f	630A	1 No	1690
		2.7	PORCELAIN REWIRABLE FUSE UNITS.		
61		ELEC-2.7.1	Supply of Porcelain Rewireable Fuse Units. Makes: As per list of recommended brands.		
	MAT-	a	32A, 240V	1 No	161

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	02943				
	MAT-02944	B	32A, 415V	1 No	240
	MAT-02945	C	63A, 415V	1 No	403
	MAT-02946	D	100A, 415V	1 No	835
62		ELEC-2.7.2	Supply of..... Porcelain Rewireable Fuse Units with extension strip. Makes: As per list of recommended brands.		
	MAT-02947	A	200A, 415V	1 No	1366
	MAT-02948	B	300A, 415V	1 No	1678
		2.8	VOLTAGE SURGE PROTECTORS		
63		ELEC-2.8.1	Supply of Voltage Surge Protector, confirms to IEC/EN 61643-11. Makes: As per list of recommended brands.		
	MAT-02949	A	2 Pole 2 Module 40 KA, 1.4 KV	1 No	8308
	MAT-02950	B	4 Pole 4 Module 40 KA, 1.4 KV	1 No	15579
	MAT-02951	C	2 Pole 2 Module 15 KA, 1.2 KV	1 No	6647
	MAT-02952	D	4 Pole 4 Module 15 KA, 1.2 KV	1 No	12462
		2.9	PANEL MOUNTING MCCBs		
64		ELEC-2.9.1	Supply of, adjustable, confirms to IEC 60947-2 and IS 13947-Part 1 & 2, having Breaking Capacity with thermal magnetic release Panel Mounted. Makes: As per list of recommended brands as category I		
	MAT-02953	A	63-100A 3 Pole MCCB,16 KA	1 No	7744
	MAT-02954	B	63-100A 4 Pole MCCB,16 KA	1 No	8349

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02955	C	125A 3 Pole MCCB,25 KA	1 No	9075
	MAT-02956	D	125A 4 Pole MCCB,25 KA	1 No	10527
	MAT-02957	E	160A 3 Pole MCCB,25 KA	1 No	11495
	MAT-02958	F	160A 4 Pole MCCB,25 KA	1 No	14762
	MAT-02959	G	250A 3 Pole MCCB,36/35 KA	1 No	18755
	MAT-02960	H	250A 4 Pole MCCB,36/35 KA	1 No	24745
	MAT-02961	I	400A 3 Pole MCCB,36/35 KA	1 No	24613
	MAT-02962	J	400A 4 Pole MCCB,36/35 KA	1 No	30855
	MAT-02963	K	630A 3 Pole MCCB,50 KA	1 No	36905
	MAT-02964	L	630A 4 Pole MCCB,50 KA	1 No	45375
	MAT-02965	M	800A 3 Pole MCCB,50 KA	1 No	67760
	MAT-02966	N	800A 4 Pole MCCB,50 KA	1 No	72600
		O	16 - 50A 3 Pole MCCB, 16KA	1 No	6133
		P	16 - 50A 4 Pole MCCB, 16KA	1 No	7700
		Q	200A 3 Pole MCCB,25 KA	1 No	13484
		R	200A 4 Pole MCCB,25 KA	1 No	17150
		S	300/320A 3 Pole MCCB,36/35 KA	1 No	24915
		T	300/320A 4 Pole MCCB,36/35 KA	1 No	29260
		U	500A 3 Pole MCCB,50 KA	1 No	35182
		V	500A 4 Pole MCCB,50 KA	1 No	44543

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
64		ELEC-2.9.2	Supply of, adjustable, confirms to IEC 60947-2 and IS 13947-Part 1 & 2, having Breaking Capacity with thermal magnetic release Panel Mounted. Makes: As per list of recommended brands as category II		
	MAT-02967	A	63-100A 3 Pole MCCB,16 KA	1 No	5445
	MAT-02968	B	63-100A 4 Pole MCCB,16 KA	1 No	7079
	MAT-02969	C	125A 3 Pole MCCB,25 KA	1 No	6897
	MAT-02970	D	125A 4 Pole MCCB,25 KA	1 No	9015
	MAT-02971	E	160A 3 Pole MCCB,25 KA	1 No	9438
	MAT-02972	F	160A 4 Pole MCCB,25 KA	1 No	12463
	MAT-02973	G	250A 3 Pole MCCB,36/35 KA	1 No	18392
	MAT-02974	H	250A 4 Pole MCCB,36/35 KA	1 No	22264
	MAT-02975	I	400A 3 Pole MCCB,36/35 KA	1 No	23111
	MAT-02976	J	400A 4 Pole MCCB,36/35 KA	1 No	27709
	MAT-02977	K	630A 3 Pole MCCB,50 KA	1 No	32670
	MAT-02978	L	630A 4 Pole MCCB,50 KA	1 No	39446
	MAT-02979	M	800A 3 Pole MCCB,50 KA	1 No	56265
	MAT-02980	N	800A 4 Pole MCCB,50 KA	1 No	62920
		O	16 - 50A 3 Pole MCCB, 16KA	1 No	3662
		P	16 - 50A 4 Pole MCCB, 16KA	1 No	4322
		Q	200A 3 Pole MCCB,25 KA	1 No	12604

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		R	200A 4 Pole MCCB,25 KA	1 No	16189
		S	300/320A 3 Pole MCCB,36/35 KA	1 No	21991
		T	300/320A 4 Pole MCCB,36/35 KA	1 No	27019
		U	500A 3 Pole MCCB,50 KA	1 No	29295
		V	500A 4 Pole MCCB,50 KA	1 No	36288
			PANEL MOUNTING ACBs (Microprocessor Based)		
66		ELEC-2.9.3	Supply of Air Circuit Breaker confirms to IS 13947-2, IEC 60947-2 and BS-EN 60947 with Micro processor based having overload, shot circuit and earth fault protection with display and 20 faults History backup with BMS compatible communication ports. Makes: As per list of recommended brands as category I		
	MAT-02981	a	630A, 3 Pole, 50kA, electrically operated, fixed type	1 No	138220
	MAT-02982	b	630A, 3 Pole, 50kA, electrically operated, manually draw out type	1 No	158458
	MAT-02983	c	630A, 4 Pole, 50kA, electrically operated, fixed type	1 No	165297
	MAT-02984	d	630A, 4 Pole, 50kA electrically operated, manually draw out type	1 No	198847
	MAT-02985	e	800A, 3 Pole, 50kA electrically operated, manually draw out type	1 No	158458
	MAT-02986	f	800A, 4 Pole, 50kA electrically operated, manually draw out type	1 No	200542
	MAT-02987	g	1000A, 3 Pole, 50kA electrically operated, manually draw out type	1 No	164805
	MAT-02988	h	1000A, 4 Pole, 50kA electrically operated, manually draw out type	1 No	208263
	MAT-02989	i	1250A, 3 Pole, 50kA electrically operated, manually draw out type	1 No	181805
	MAT-02990	j	1250A, 4 Pole, 50kA electrically operated, manually draw out type	1 No	229424

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-02991	k	1600A, 3 Pole, 50kA electrically operated, manually draw out type	1 No	206771
	MAT-02992	l	1600A, 4 Pole, 50kA electrically operated, manually draw out type	1 No	254297
	MAT-02993	m	2000A, 3 Pole, 75kA electrically operated, manually draw out type	1 No	242873
	MAT-02994	n	2000A, 4 Pole, 75kA electrically operated, manually draw out type	1 No	298322
	MAT-02995	o	2500A, 3 Pole, 75kA electrically operated, manually draw out type	1 No	300246
	MAT-02996	p	2500A, 4 Pole, 75kA electrically operated, manually draw out type	1 No	361814
	MAT-02997	q	3200A, 3 Pole, 75kA electrically operated, manually draw out type	1 No	339653
	MAT-02998	r	3200A, 4 Pole, 75kA electrically operated, manually draw out type	1 No	401220
67		ELEC-2.9.4	Supply of Air Circuit Breaker conforms to IS 13947-2, IEC 60947-2 and BS-EN 60947 with Micro processor based having overload, short circuit and earth fault protection with display and 20 faults History backup with BMS compatible communication ports. Makes: As per list of recommended brands as category II		
	MAT-02999	a	630A, 3 Pole, 50kA, electrically operated, fixed type	1 No	124398
	MAT-03000	b	630A, 3 Pole, 50kA, electrically operated, manually draw out type	1 No	142612
	MAT-03001	c	630A, 4 Pole, 50kA, electrically operated, fixed type	1 No	148767
	MAT-03002	d	630A, 4 Pole, 50kA electrically operated, manually draw out type	1 No	178963
	MAT-03003	e	800A, 3 Pole, 50kA electrically operated, manually draw out type	1 No	142612
	MAT-03004	f	800A, 4 Pole, 50kA electrically operated, manually draw out type	1 No	180488
	MAT-03005	g	1000A, 3 Pole, 50kA electrically operated, manually draw out type	1 No	148325
	MAT-	h	1000A, 4 Pole, 50kA electrically operated, manually	1 No	187436

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03006		draw out type		
			AIR INSULATED BUS DUCT		
68		ELEC-2.9.5	Supply, installation, testing and commissioning of Amp, ...KA breaking capacity (100% Neutral busbar) air insulated compact Raising mains/Bus Duct system made of CRCA sheet/Hot Galvanized steel encloser of thickness not less than 0.8 mm having degree of protection of IP 55 as per IEC/EN 61439-6, PVC/Plastic insulated reinforced with glass fibre four strip ALUMINIUM busbar in convenient sections including necessary end cover units suitable for 415 volts 3 phase, 4 wire, 50 Hz A.C. System etc., with necessary joints Fire barrier at each floor Provision of tapping at each floor/every meter, continuous earthing with 2 no aluminum strip of suitable size (one on each side) including GI clamping brackets, angle iron brackets, steel fasteners, connecting to earth system as required . Makes: As per list of recommended brands.		
	MAT-03007	a	400Amp, 50 - 53KA	RM	13194
	MAT-03008	b	630Amp, 50 - 63KA	RM	15683
	MAT-03009	c	800 Amp, 50 - 76KA	RM	17191
	MAT-03010	d	1000 Amp, 50 - 76KA	RM	19754
	MAT-03011	e	1250 Amp, 50 - 76KA	RM	20660
	MAT-03012	f	1600 Amp, 50 - 76KA	RM	25938
69	MAT-03013	ELEC-2.9.6	Supply and Fixing of Spring Bracket with fixing kit for Air Insulated Busduct / Raising Mains. Makes: As per list of recommended brands.	1 No	7841
70		ELEC-2.9.7	Supply and fixing of Amps Horizontal / Vertical bends for Air Insulated Bus Duct. Makes: As per list of recommended brands.		
	MAT-03014	a	400 Amps	1 No	15080
	MAT-03015	b	630 Amps	1 No	17191

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03016	c	800 Amps	1 No	17945
	MAT-03017	d	1000Amps	1 No	21036
	MAT-03018	e	1250 Amps	1 No	22619
	MAT-03019	f	1600 Amps	1 No	25636
71		ELEC-2.9.8	Supply and fixing of Amps Tap off box for Air Insulated Busduct. Makes: As per list of recommended brands.		
	MAT-03020	a	125A	1 No	17945
	MAT-03021	b	250A	1 No	20810
	MAT-03022	c	400A	1 No	30762
	MAT-03023	d	630 A	1 No	33476
			SANDWICH BUSDUCT		
72		ELEC-2.9.9	Supply, installation, testing and commissioning of Amp, ...KA breaking capacity (100% Neutral busbar) sandwich busduct system made of CRCA sheet/Hot Galvanized steel encloser of thickness not less than 1.5mm having degree of protection of IP 55/IP 65 as per IEC/EN 61439-6, PVC/Plastic insulated reinforced with glass fibre four strip ALUMINIUM busbar in convenient sections including end cover units suitable for 415 volts 3 phase, 4 wire, 50 Hz A.C. system etc., with necessary joints, fire barrier at each floor, provision of tapping at each floor/every meter, continuous earthing with 2 no of aluminum strip of suitable size (one on each side) including GI clamping brackets, angle iron brackets, steel fasteners, connecting to earth system as required . Makes: As per list of recommended brands.		
	MAT-03024	a	630Amp, 36/40	RM	16135
	MAT-03025	b	800Amp, 42/50KA	RM	18096
	MAT-03026	c	1000Amp, 50KA	RM	19905

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03027	d	1250 Amp,75kA	RM	20810
	MAT-03028	e	1600 Amp,80 kA	RM	26087
	MAT-03029	f	2000 Amp ,80kA	RM	31968
	MAT-03030	g	2500 Amp ,150 kA	RM	45842
	MAT-03031	h	3200 Amp,160kA	RM	53081
	MAT-03032	i	4000 Amp,160kA	RM	71024
73		ELEC-2.9.10	Supply and fixing of Amps Horizontal / Vertical bends for sandwich Bus Duct. Makes: As per list of recommended brands.		
	MAT-03033	a	630A	1 No	16437
	MAT-03034	b	800A	1 No	17794
	MAT-03035	c	1000A	1 No	18548
	MAT-03036	d	1250 A	1 No	20057
	MAT-03037	e	1600 A	1 No	22922
	MAT-03038	f	2000 A	1 No	26691
	MAT-03039	g	2500 A	1 No	33628
	MAT-03040	h	3200 A	1 No	40866
	MAT-03041	i	4000 A	1 No	45842
74		ELEC-2.9.11	Supply and fixing of Amps Copper Flexibles for three phases and neutral for Air Insulated / sandwich Busduct. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03042	a	400A	1 No	35136
	MAT-03043	b	630A	1 No	37247
	MAT-03044	c	800A	1 No	40565
	MAT-03045	d	1000A	1 No	42675
	MAT-03046	e	1250 A	1 No	45239
	MAT-03047	f	1600 A	1 No	48707
	MAT-03048	g	2000 A	1 No	53081
	MAT-03049	h	2500 A	1 No	60318
	MAT-03050	i	3200 A	1 No	64540
	MAT-03051	j	4000 A	1 No	68914
75		ELEC-2.9.12	Supply and fixing of Flange end for Amps for Air insulated Bus ducts. Makes: As per list of recommended brands.		
	MAT-03052	a	400A	1 No	13571
	MAT-03053	b	630A	1 No	18548
	MAT-03054	c	800A	1 No	22922
76		ELEC-2.9.13	Supply and fixing of Flange end for Amps for sandwich bus ducts Makes: As per list of recommended brands.		
	MAT-03055	a	400A	1 No	16437
	MAT-03056	b	630A	1 No	23525
	MAT-	c	800A	1 No	27294

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03057				
	MAT-03058	d	1000 A	1 No	28803
	MAT-03059	e	1250 A	1 No	31455
	MAT-03060	f	1600 A	1 No	32969
	MAT-03061	g	2000 A	1 No	94985
	MAT-03062	h	2500 A	1 No	59263
	MAT-03063	i	3200 A	1 No	64843
	MAT-03064	j	4000 A	1 No	68160
77		ELEC-2.9.14	Supply and fixing of Amps Tap off box for Sandwich Busduct. Makes: As per list of recommended brands.		
	MAT-03065	a	160A	1 No	22619
	MAT-03066	b	250A	1 No	38001
	MAT-03067	c	400A	1 No	48104
	MAT-03068	d	630A	1 No	69818
	MAT-03069	e	800A	1 No	104804
		2.10	MCBs (AS PER IS:60898-1:2002)		
78		ELEC-2.10.1	Supply of 10KA C/D Curve ISI Mark. Makes: As per list of recommended brands as category I		
	MAT-03070	a	6-32A, SP MCB	1 No	228

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03071	b	40-63A, SP MCB	1 No	481
	MAT-03072	c	6-32A, DP MCB	1 No	692
	MAT-03073	d	40-63A, DP MCB	1 No	1100
	MAT-03074	e	6-32A, TP MCB	1 No	1100
	MAT-03075	f	40-63A, TP MCB	1 No	1767
	MAT-03076	g	6-32A, FP MCB	1 No	1514
	MAT-03077	h	40-63A, FP MCB	1 No	2206
79		ELEC-2.10.2	Supply of 10KA C/D Curve ISI Mark. Makes: As per list of recommended brands as category II		
	MAT-03078	a	6-32A, SP MCB	1 No	192
	MAT-03079	b	40-63A, SP MCB	1 No	415
	MAT-03080	c	6-32A, DP MCB	1 No	583
	MAT-03081	d	40-63A, DP MCB	1 No	842
	MAT-03082	e	6-32A, TP MCB	1 No	908
	MAT-03083	f	40-63A, TP MCB	1 No	1370
	MAT-03084	g	6-32A, FP MCB	1 No	1238
	MAT-03085	h	40-63A, FP MCB	1 No	1719
80		ELEC-2.10.3	Supply of 6-32A 10KA SP MCB, C/D Curve ISI Mark. Makes: As per list of recommended brands as category III		
	MAT-03086	a	6-32A, SP MCB	1 No	156

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03087	b	40-63A, SP MCB	1 No	264
	MAT-03088	c	6-32A, DP MCB	1 No	409
	MAT-03089	d	40-63A, DP MCB	1 No	601
	MAT-03090	e	6-32A, TP MCB	1 No	733
	MAT-03091	f	40-63A, TP MCB	1 No	1142
	MAT-03092	g	6-32A, FP MCB	1 No	961
	MAT-03093	h	40-63A, FP MCB	1 No	1226
		2.11	ISOLATORS CONFIRMS TO I E C 60947 PART-III		
81		ELEC-2.11.1	Supply of Isolator. Makes: As per list of recommended brands as category I.		
	MAT-03094	a	32A, DP	1 No	391
	MAT-03095	b	40A, DP	1 No	432
	MAT-03096	c	63A, DP	1 No	571
	MAT-03097	d	40A, TP	1 No	733
	MAT-03098	e	63A, TP	1 No	865
	MAT-03099	f	40A, FP	1 No	961
	MAT-03100	g	63A, FP	1 No	1082
	MAT-03101	h	100A, FP	1 No	1142
82		ELEC-2.11.2	Supply of Isolator. Makes: As per list of recommended brands as category II		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03102	a	32A, DP	1 No	379
	MAT-03103	b	40A, DP	1 No	396
	MAT-03104	c	63A, DP	1 No	481
	MAT-03105	d	40A, TP	1 No	685
	MAT-03106	e	63A, TP	1 No	697
	MAT-03107	f	40A, FP	1 No	793
	MAT-03108	g	63A, FP	1 No	853
	MAT-03109	h	100A, FP	1 No	1052
83		ELEC-2.11.3	Supply of..... Isolator. Makes: As per list of recommended brands as category III		
	MAT-03110	a	32A, DP	1 No	253
	MAT-03111	b	40A, DP	1 No	300
	MAT-03112	c	63A, DP	1 No	409
	MAT-03113	d	40A, TP	1 No	439
	MAT-03114	e	63A, TP	1 No	504
	MAT-03115	f	40A, FP	1 No	679
		2.12	RCCBs (ELCB/RCD) CONFIRMS TO IEC:61008 AND IS:12640-1		
84		ELEC-2.12.1	Supply of RCCB for earth leakage protection. Makes: As per list of recommended brands as category I.		
	MAT-03116	a	40A, 2 Pole,30mA	1 No	3209

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03117	b	40A, 2 Pole,100mA	1 No	3401
	MAT-03118	c	40A, 4 Pole30mA	1 No	3533
	MAT-03119	d	40A, 4 Pole ,100mA	1 No	3665
	MAT-03120	e	63A, 2 Pole,30mA,	1 No	3966
	MAT-03121	f	63A, 2 Pole,100mA	1 No	3905
	MAT-03122	g	63A, 4 Pole,30mA	1 No	4086
	MAT-03123	h	63A, 4 Pole,100mA	1 No	4543
85		ELEC-2.12.2	Supply of RCCB for earth leakage protection. Makes: As per list of recommended brands as category II		
	MAT-03124	a	40A, 2 Pole,30mA	1 No	2704
	MAT-03125	b	40A, 2 Pole,100mA	1 No	2765
	MAT-03126	c	40A, 4 Pole30mA	1 No	3005
	MAT-03127	d	40A, 4 Pole ,100mA	1 No	3125
	MAT-03128	e	63A, 2 Pole,30mA,	1 No	3377
	MAT-03129	f	63A, 2 Pole,100mA	1 No	3461
	MAT-03130	g	63A, 4 Pole,30mA	1 No	3593
	MAT-03131	h	63A, 4 Pole,100mA	1 No	3605
			RCBO CONFIRMS TO IEC:61009-1		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
86		ELEC-2.12.3	Supply of RCBO for overload, short-circuit and earth leakage protection. Makes: As per list of recommended brands.		
	MAT-03132	a	40A, 2 Pole, 30mA	1 No	5468
	MAT-03133	b	40A, 2 Pole,100mA	1 No	5973
	MAT-03134	c	40A, 4 Pole, 30mA	1 No	6213
	MAT-03135	d	40A, 4 Pole,100mA	1 No	6574
	MAT-03136	e	63A, 2 Pole,30mA,	1 No	6538
	MAT-03137	f	63A, 2 Pole,100mA	1 No	6922
	MAT-03138	g	63A, 4 Pole,30mA	1 No	7331
	MAT-03139	h	63A, 4 Pole,100mA	1 No	7475
	MAT-08761	i	Supply of MCB type Changeover Switch 20A, Double Pole, 2 Way 400V AC suitable to fix on Din Channel		2163
		2.13	MCB DISTRIBUTION BOARDS (AS PER IS 8623; IS 13032; IEC 61439-3)		
			SPN DBs		
87		ELEC-2.13.1	Supply of Protection suitable for S.P outgoing and for 1 No incomer etc., complete as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category I.		
	MAT-03140	a	4 Way SPN DB with IP 30, DP Incomer-1 No, SP MCBs - 2 Nos	1 No	1105
	MAT-03141	b	8 Way SPN DB with IP 30, DP Incomer-1 No, SP MCBs - 6 Nos	1 No	1199
	MAT-03142	c	12 Way SPN DB with IP 30, DP Incomer-1 No, SP MCBs -10 Nos	1 No	1451
	MAT-	d	4 Way SPN DB with IP 43, DP Incomer-1 No, SP	1 No	1514

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03143		MCBs - 2 Nos		
	MAT-03144	e	8 Way SPN DB with IP 43, DP Incomer-1 No, SP MCBs - 6 Nos	1 No	1641
	MAT-03145	f	12 Way SPN DB with IP 43, DP Incomer-1 No, SP MCBs -10 Nos	1 No	1988
88		ELEC-2.13.2	Supply of Protection suitable for S.P outgoing and for 1 No incomer etc., complete as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category II.		
	MAT-03146	a	4 Way SPN DB with IP 30, DP Incomer-1 No, SP MCBs - 2 Nos	1 No	947
	MAT-03147	b	8 Way SPN DB with IP 30, DP Incomer-1 No, SP MCBs - 6 Nos	1 No	1009
	MAT-03148	c	12 Way SPN DB with IP 30, DP Incomer-1 No, SP MCBs -10 Nos	1 No	1262
	MAT-03149	d	4 Way SPN DB with IP 43, DP Incomer-1 No, SP MCBs - 2 Nos	1 No	1325
	MAT-03150	e	8 Way SPN DB with IP 43, DP Incomer-1 No, SP MCBs - 6 Nos	1 No	1451
	MAT-03151	f	12 Way SPN DB with IP 43, DP Incomer-1 No, SP MCBs -10 Nos	1 No	1704
89		ELEC-2.13.3	Supply of Protection suitable for S.P outgoing and for 1 No incomer etc., complete as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category III.		
	MAT-03152	a	4 Way SPN DB with IP 30, DP Incomer-1 No, SP MCBs - 2 Nos	1 No	820
	MAT-03153	b	8 Way SPN DB with IP 30, DP Incomer-1 No, SP MCBs - 6 Nos	1 No	884
	MAT-03154	c	12 Way SPN DB with IP 30, DP Incomer-1 No, SP MCBs -10 Nos	1 No	1105
	MAT-03155	d	4 Way SPN DB with IP 43, DP Incomer-1 No, SP MCBs - 2 Nos	1 No	1187
	MAT-03156	e	8 Way SPN DB with IP 43, DP Incomer-1 No, SP MCBs - 6 Nos	1 No	1262
	MAT-03157	f	12 Way SPN DB with IP 43, DP Incomer-1 No, SP MCBs -10 Nos	1 No	1514
			TPN DBs		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
90		ELEC-2.13.4	Supply of protection suitable for installation of of SP outgoing MCBs and for 1 No 4 pole, MCB/Isolator incomer along with provision for 1 No of 4 Pole RCCB/ELCB etc., complete as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category I.		
	MAT-03158	a	(8 +12) 4 Way TPN DB Horizontal with IP 30, 12 Nos	1 No	2145
	MAT-03159	b	(8 +18) 6 Way TPN DB Horizontal with IP 30, 18 Nos	1 No	3028
	MAT-03160	c	(8 +12) 4 Way TPN DB Horizontal with IP 43, 12 Nos	1 No	3407
	MAT-03161	d	(8 +18) 6 Way TPN DB Horizontal with IP 43, 18 Nos	1 No	4795
	MAT-03162	e	(8 +24) 8 Way TPN DB Horizontal with IP 43, 24 Nos	1 No	5426
91		ELEC-2.13.5	Supply of protection suitable for installation of of SP outgoing MCBs and for 1 No 4 pole, MCB/Isolator incomer along with provision for 1 No of 4 Pole RCCB/ELCB etc., complete as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category II.		
	MAT-03163	a	(8 +12) 4 Way TPN DB Horizontal with IP 30, 12 Nos	1 No	1956
	MAT-03164	b	(8 +18) 6 Way TPN DB Horizontal with IP 30, 18 Nos	1 No	2713
	MAT-03165	c	(8 +12) 4 Way TPN DB Horizontal with IP 43, 12 Nos	1 No	3028
	MAT-03166	d	(8 +18) 6 Way TPN DB Horizontal with IP 43, 18 Nos	1 No	4164
	MAT-03167	e	(8 +24) 8 Way TPN DB Horizontal with IP 43, 24 Nos	1 No	4795
92		ELEC-2.13.6	Supply of protection suitable for installation of of SP outgoing MCBs and for 1 No 4 pole, MCB/Isolator incomer along with provision for 1 No of 4 Pole RCCB/ELCB etc., complete as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category III.		
	MAT-03168	a	(8 +12) 4 Way TPN DB Horizontal with IP 30, 12 Nos	1 No	1766

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03169	b	(8 +18) 6 Way TPN DB Horizontal with IP 30, 18 Nos	1 No	2398
	MAT-03170	c	(8 +12) 4 Way TPN DB Horizontal with IP 43, 12 Nos	1 No	2334
	MAT-03171	d	(8 +18) 6 Way TPN DB Horizontal with IP 43, 18 Nos	1 No	3028
	MAT-03172	e	(8 +24) 8 Way TPN DB Horizontal with IP 43, 24 Nos	1 No	3533
			VTPN DBs		
93		ELEC-2.13.7	Supply of Protection suitable for TP/SP out going MCBs and for 1 No of 4 pole MCB/Isolator incomer etc., complete as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category I .		
	MAT-03173	a	4 Way, VTPN DB with IP 43	1 No	8744
	MAT-03174	b	6 Way, VTPN DB with IP 43	1 No	10133
	MAT-03175	c	8 Way, VTPN DB with IP 43	1 No	11242
94		ELEC-2.13.8	Supply of 7 Segment with IP 42 Protection with provision for FPMCB / Isolator / RCCB / RCBO as incomer, 3Nos DPMCB / Isolator / RCCB / RCBO as sub incomer and Nos SPMCB's as outgoing MCBs as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category I		
	MAT-03176	a	4 Way TPN DB, 12 Nos	1 No	9023
	MAT-03177	b	8 Way TPN DB, 24 Nos	1 No	10285
95		ELEC-2.13.9	Supply of suitable for accommodating 125A / 160A 4 Pole MCCB as incomer and TP/SP MCBs as outgoings etc., as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category I.		
	MAT-03178	a	4 Way VTPN MCCB DB with IP 43 Protection.	1 No	11382
		b	6 Way VTPN MCCB DB with IP 43 Protection.	1 No	12838

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03179	c	8 Way VTPN MCCB DB with IP 43 Protection.	1 No	14296
96		ELEC-2.13.10	Supply of Protection suitable for TP/SP out going MCBs and for 1 No of 4 pole MCB/Isolator incomer etc., complete as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category II		
	MAT-03180	a	4 Way VTPN DB with IP 43	1 No	7698
	MAT-03181	b	6 Way VTPN DB with IP 43	1 No	8203
	MAT-03182	c	8 Way VTPN DB with IP 43	1 No	9590
97		ELEC-2.13.11	Supply of 7 Segment with IP 42 Protection with provision for FPMCB / Isolator / RCCB / RCBO as incomer, 3Nos DPMCB / Isolator / RCCB / RCBO as sub incomer and Nos SPMCB's as outgoing MCBs as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category II		
	MAT-03183	a	4 Way TPN DB,12 Nos	1 No	8076
	MAT-03184	b	8 Way TPN DB,24 Nos	1 No	9212
98		ELEC-2.13.12	Supply of suitable for accommodating 125A / 160A 4 Pole MCCB as incomer and TP/SP MCBs as outgoings etc., as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category II		
	MAT-03185	a	4 Way VTPN MCCB DB with IP 43 Protection.	1 No	9212
		b	6 Way VTPN MCCB DB with IP 43 Protection.	1 No	10411
	MAT-03186	c	8 Way VTPN MCCB DB with IP 43 Protection.	1 No	11609
99		ELEC-2.13.13	Supply of Metallic Plug and Socket with provision for 1 No of SP/TP MCB for control in SS enclosure as per IS 8623; IS 13032; IEC 61439-3 Makes: As per list of recommended brands as category I.		
	MAT-03187	a	20A SP	1 No	1244
	MAT-	b	20A TP	1 No	2354

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03188				
	MAT-03189	c	32A TP	1 No	2776
100		ELEC-2.13.14	Supply of Metallic Plug and Socket with provision for 1 No of SP/TP MCB for control in SS enclosure as per IS 8623; IS 13032; IEC 61439-3 Makes: As per list of recommended brands as category II.		
	MAT-03190	a	20A SP	1 No	884
	MAT-03191	b	20A TP	1 No	1577
	MAT-03192	c	32A TP	1 No	2082
101		ELEC-2.13.15	Supply of Metallic Plug and Socket with provision for 1 No of SP/TP MCB for control in SS enclosure as per IS 8623; IS 13032; IEC 61439-3 Makes: As per list of recommended brands as category III.		
	MAT-03193	a	20A SP	1 No	664
	MAT-03194	b	20A TP	1 No	1262
	MAT-03195	c	32A TP	1 No	1766
102		ELEC-2.13.16	Supply of 1-way Sheet Steel enclosure with IP 20 Protection etc., complete as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category I.		
	MAT-03196	a	SP	1 No	379
	MAT-03197	b	DP/TP/FP	1 No	505
103		ELEC-2.13.17	Supply of 1-way Sheet Steel enclosure with IP 20 Protection etc., complete as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category II.		
	MAT-03198	a	SP	1 No	290
	MAT-03199	b	DP/TP/FP	1 No	416

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
104		ELEC-2.13.18	Supply of 1-way Sheet Steel enclosure with IP 20 Protection etc., complete as per IS 8623; IS 13032; IEC 61439-3. Makes: As per list of recommended brands as category III.		
	MAT-03200	a	SP	1 No	266
	MAT-03201	b	DP/TP/FP	1 No	391
		2.14	Over voltage& Low voltage release		
105		ELEC-2.14.1	Supply of Over voltage + Low Voltage release, 230V AC, 60V AC< U <170V AC, U> 267V AC, 1 module. Makes: As per list of recommended brands	1 No	3017
		ELEC-2.14.2	Supply of Over voltage, 230V AC, U >275V AC, 3 phase in 1 module suitable for 3Ph+N. Makes: As per list of recommended brands	1 No	4390
		2.15	BUSBAR CHAMBERS(TPN)		
106		ELEC-2.15.1	Supply and fixing of 4 Way Busbar chamber made of ETP Copper. Makes: As per list of recommended brands		
		a	63A	1 No	7632
		b	100A	1 No	8455
		c	200A	1 No	10459
			SECTION - 3		
		3.1	STREET LIGHT LUMINAIRES		
	MAT-03202	ELEC-3.1.1	deleted	1 No	
	MAT-03203	ELEC-3.1.2	deleted	1 No	
	MAT-03204	ELEC-3.1.3 a	Deleted	1 No	
	MAT-03205	ELEC-3.1.3 b	Deleted	1 No	
	MAT-	ELEC-	Deleted	1 No	

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03206	3.1.3 c			
	MAT-03207	ELEC-3.1.4a	Deleted	1 No	
	MAT-03208	ELEC-3.1.4 b	Deleted	1 No	
	MAT-03209	ELEC-3.1.4 c	Deleted	1 No	
	MAT-03210	ELEC-3.1.5 a	Deleted	1 No	
	MAT-03212	ELEC-3.1.6 a	Deleted	1 No	
	MAT-03214	ELEC-3.1.7 a	Deleted	1 No	
	MAT-03215	ELEC-3.1.7 b	Deleted	1 No	
		3.2	LED POST TOP LANTERN LUMINAIRES		
107	MAT-03218	ELEC-3.2.1	Supply and Transportation of 40W LED Post top lantern made with cast Aluminum with decorative opal polycarbonate diffuser with IP 65 protection etc., complete with all accessories with not less than two years warranty. Makes: As per list of recommended brands.	1 No	7820
108	MAT-03219	ELEC-3.2.2	Supply and Transportation of 25 W Post Top lantern made with high Pressure die cast aluminum body with polycarbonate / high impact Poly carbonate protector for optimal luminous flux, IP66 suitable for vertical mounting of 76 mm dia, the luminaire shall have CCT 3000-4000K with internal surge protection of 4KV and External Surge Protection of 10 KV, p.f. >0.95 etc., with not less than two years warranty. Makes: As per list of recommended brands.	1 No	17480

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
109	MAT-03220	ELEC-3.2.3	Supply and Transportation of 35/40 W Post Top lantern made with high Pressure die cast aluminum body with polycarbonate / high impact PMMA protector for optimal luminous flux, IP66 suitable for vertical mounting of 76 mm dia. the luminaire shall have CCT 3000-4000K with internal surge protection of 4KV and External Surge Protection of 10 KV, p.f>0.95 etc., complete with not less than two years warranty. Makes: As per list of recommended brands.	1 No	21620
110	MAT-08762	ELEC-3.2.4	Supply and Transportation of 20 W LED Post top lantern made with cast Aluminum with decorative opal polycarbonate diffuser with IP 65 protection etc., complete with all accessories with not less than two years warranty. Makes: As per list of recommended brands.	1 No	4200
		3.3	ACCESSORIES FOR MV / SV / MH LUMINAIRES		
			COPPER BALLASTS		
	MAT-03221	ELEC-3.3.1 a	Deleted	1 No	
	MAT-03222	ELEC-3.3.1 b	Deleted	1 No	
	MAT-03223	ELEC-3.3.1 c	Deleted	1 No	
	MAT-03224	ELEC-3.3.1 d	Deleted	1 No	
	MAT-03225	ELEC-3.3.2 a	Deleted	1 No	
	MAT-03226	ELEC-3.3.2 b	Deleted	1 No	
	MAT-03227	ELEC-3.3.2 c	Deleted	1 No	
	MAT-03228	ELEC-3.3.2 d	Deleted	1 No	
			IGNITOR		
	MAT-03229	ELEC-3.3.3	Deleted	1 No	

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			HPF CAPACITORS		
	MAT-03230	ELEC-3.3.4 a	Deleted	1 No	
	MAT-03231	ELEC-3.3.4 b	Deleted	1 No	
	MAT-03232	ELEC-3.3.4 c	Deleted	1 No	
	MAT-03233	ELEC-3.3.4 d	Deleted	1 No	
	MAT-03234	ELEC-3.3.4 e	Deleted	1 No	
	MAT-03235	ELEC-3.3.4 f	Deleted	1 No	
		3.4	LAMPS		
	MAT-03236	ELEC-3.4.1 a	Deleted	1 No	
	MAT-03237	ELEC-3.4.1 b	Deleted	1 No	
	MAT-03238	ELEC-3.4.1 c	Deleted	1 No	
	MAT-03239	ELEC-3.4.1 d	Deleted	1 No	
	MAT-03240	ELEC-3.4.1 e	Deleted	1 No	
	MAT-03241	ELEC-3.4.1 f	Deleted	1 No	
	MAT-03242	ELEC-3.4.1 g	Deleted	1 No	
	MAT-03243	ELEC-3.4.1 h	Deleted	1 No	
	MAT-03244	ELEC-3.4.1 i	Deleted	1 No	
	MAT-	ELEC-	Deleted	1 No	

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03245	3.4.2 a			
	MAT-03246	ELEC-3.4.2 b	Deleted	1 No	
	MAT-03247	ELEC-3.4.2 c	Deleted	1 No	
	MAT-03248	ELEC-3.4.2 d	Deleted	1 No	
	MAT-03249	ELEC-3.4.2 e	Deleted	1 No	
	MAT-03250	ELEC-3.4.2 f	Deleted	1 No	
	MAT-03251	ELEC-3.4.2 g	Deleted	1 No	
	MAT-03252	ELEC-3.4.2 h	Deleted	1 No	
	MAT-03253	ELEC-3.4.2 i	Deleted	1 No	
		3.5	AUTOMATIC STREET LIGHT CONTROL SYSTEMS		
111		ELEC-3.5.1	Supply of Automatic Street Light Control System with Optical Micro Sensor, Low voltage / High voltage trip and reset, operating voltage 150 - 280V AC, 50 HZ with suitable SMC enclosure of IP 54 protection, MCBs and contactor suitable to control the load of of single-phase load with necessary clamping arrangements. Makes: As per list of recommended brands.		
	MAT-03254	a	1 KW	1 No	9900
	MAT-03255	b	3 KW	1 No	12430
	MAT-03256	c	5 KW	1 No	12980
	MAT-03257	d	8 KW	1 No	14850

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
112		ELEC-3.5.2	Supply of Automatic Street Light Control System with Optical Micro Sensor, Low voltage / High voltage trip and reset, operating voltage 150 - 280V AC per Phase, 50 HZ with suitable SMC enclosure of IP 54 protection, MCBs and contactor suitable to control the load of of Three phase load with necessary clamping arrangements. Makes: As per list of recommended brands.		
	MAT-03258	a	5 KW	1 No	16280
	MAT-03259	b	8 KW	1 No	16830
	MAT-03260	c	12 KW	1 No	20350
	MAT-03261	d	25KW	1 No	32340
	MAT-03262	e	50KW	1 No	46200
113		ELEC-3.5.3	Supply and fixing of Automatic Street Light Controller with optical micro sensor low voltage/ High Voltage trip and reset operating voltage 150 - 280V AC, withstands up to 440V, 50 HZ with suitable ABS enclosure of IP 54 protection, suitable to control the load of 10A of single phase with necessary arrangements etc complete. Makes: As per list of recommended brands.		
	MAT-08763	a	SLASM-01-10A /equivalent (Dusk to Dawn)	1 No	3500
	MAT-08764	b	SLASM-02-10A /equivalent (Time setting after 4hr)	1 No	4500
	MAT-08765	c	SLASM-03-10A /equivalent (Time setting 4hr,6Hr, 8Hr)	1 No	4200
		ELEC-3.5.4	Supply, installation testing and commissioning of single-phase Automatic Street Light Control system with smart energy meter/ CCMS to schedule the timing of lights (Reprogrammed based on astronomical clock or on field or through central control), ON / OFF switch (On field or centrally). CCMS system to capture the energy usage and other parameters at predetermined interval and store data for 30 days, download data in field via mobile app or mobile dash		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			board, system protection against surges, upgrade firmware on field using a communication device via WIFI / GSM and GPRS, MCB Reset mechanism for temporary fault rectification, inbuilt GPS for location identification, emergency on/off, with suitable rating of latching relay, door tamper sensing, instant load on/off functionality to support maintenance activity, low voltage/high voltage trip, overload cutoff and operating voltage 150-240 volts, 50Hz with CRCA power coated enclose of IP55 protection. Single pole C curve breaking capacity 10KA MCB and suitable to control the load KW of single phase with necessary clamping arrangements etc., Makes: As per list of recommended brands.		
		a	3 KW	1 No	14175
		b	5 KW	1 No	17010
		c	8 KW	1 No	20790
		d	12 KW	1 No	24570
		e	15 KW	1 No	27405
		f	18 KW	1 No	31185
		g	25 KW	1 No	39690
		ELEC-3.5.5	Supply, installation Testing and commissioning of Three Phase Automatic Street Light Control system with smart energy meter / CCMS to schedule the timing of lights (Reprogrammed based on astronomical clock or on field or through central control), ON / OFF switch (On field or centrally). CCMS system to capture the energy usage and other parameters at predetermined interval and store data for 30 days, download data in field via mobile app or mobile dash board, system protection against surges, upgrade firmware on field using a communication device via WIFI / GSM and GPRS, MCB Reset mechanism for temporary fault rectification, inbuilt GPS for location identification, emergency on/off, with suitable rating of latching relay, door tamper sensing, instant load on/off functionality to support maintenance activity,		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			low voltage/high voltage trip, overload cutoff and operating voltage 350-450 volts, 50Hz with CRCA power coated enclose of IP55 protection. Single pole C curve breaking capacity 10KA MCB and suitable to control the load KW of three phase with necessary clamping arrangements etc., Makes: As per list of recommended brands.		
		a	3 KW	1 No	23625
		b	5 KW	1 No	26460
		c	8 KW	1 No	30240
		d	12 KW	1 No	34020
		e	15 KW	1 No	36855
		f	18 KW	1 No	40365
		g	25 KW	1 No	49140
		3.6	INTERNAL LUMINAIRES		
	MAT-03263	ELEC-3.6.1 a	Deleted	1 No	
	MAT-03264	ELEC-3.6.1 b	Deleted	1 No	
	MAT-03265	ELEC-3.6.2 a	Deleted	1 No	
	MAT-03266	ELEC-3.6.2 b	Deleted	1 No	
	MAT-03267	ELEC-3.6.3	Deleted	1 No	
			ACCESSORIES		
	MAT-03268	ELEC-3.6.4	Deleted	1 No	
	MAT-03269	ELEC-3.6.5	Deleted	1 No	
	MAT-03270	ELEC-3.6.6	Deleted	1 No	

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03271	ELEC-3.6.7	Deleted	1 No	
	MAT-03272	ELEC-3.6.8	Deleted	1 No	
	MAT-03273	ELEC-3.6.9	Deleted	1 No	
	MAT-03274	ELEC-3.6.10	Deleted	1 No	
	MAT-03275	ELEC-3.6.11	Deleted	1 No	
		3.7	FLOURSCENT TUBES / CFL LAMPS / LED BULBS		
	MAT-03276	ELEC-3.7.1	Deleted	1 No	
	MAT-03277	ELEC-3.7.2	Deleted	1 No	
	MAT-03278	ELEC-3.7.3	Deleted	1 No	
114		ELEC-3.7.4	Supply of Pin type CFL Lamp. Makes: As per list of recommended brands.		
	MAT-03279	a	9W	1 No	66
	MAT-03280	b	11W	1 No	77
	MAT-03281	c	13W	1 No	99
	MAT-03282	d	18W	1 No	105
	MAT-03283	e	36W	1 No	138
			LED BULBS		
115		ELEC-3.7.5	Supply of Lamp with input voltage 90 to 300V, Color temperature 3000k - 6500k, Beam angle 170 - 220 degrees, B22 base. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03284	a	0.5W LED	1 No	46
	MAT-03285	b	3.0W LED	1 No	101
	MAT-03286	c	5.0W LED	1 No	110
	MAT-03287	d	(7 to 9)W LED	1 No	129
116	MAT-03292	ELEC-3.7.6	Supply of 3W to 5W 3000K, AC 160-260V, LED Candle Lamp for chandeliers. Makes: As per list of recommended brands.	1 No	184
117	MAT-08797	ELEC-3.7.7	Supply of 9W/10W LED Mirror Light fitting with decorative grey end caps, polycarbonate body and opal acrylic diffuser etc. Makes: As per list of recommended brands.	1 No	550
		3.8	LED LUMINAIRES INDOOR		
			DOWN LIGHTERS		
118		ELEC-3.8.1	Supply and fixing of..... heavy duty LED Down lighter, suitable for Recessed mounting made of pressure diecast aluminum body with powder coating, acrylic diffuser with driver as per IS: 15885 (Part 2/ Sec 13) : 2012 , operating voltage of 150 to 265 Volts AC, P.F > 0.9, Surge protection: 2KV, THD<10% with high power LEDs, having System Efficacy of >= 100 lumens / watt, CCT: 3000K - 5700K, minimum CRI > 70, Luminaire performance complies to IS 10322 (Part 5 / Sec-2) etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I.		
	MAT-03294	a	6W	1 No	610
	MAT-03295	b	9W	1 No	772
	MAT-03296	c	12W	1 No	1117
	MAT-03297	d	15W	1 No	1199
	MAT-03298	e	18W	1 No	1281

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
119		ELEC-3.8.2	Supply and fixing of heavy duty LED Down lighter, suitable for Recessed / Surface mounting made of pressure diecast aluminum body with powder coating, acrylic diffuser with driver as per IS: 15885 (Part 2/ Sec 13) : 2012 , operating voltage range of 150 to 265 Volts AC, P.F > 0.9, Surge protection: 2KV, THD<10% with high power LEDs, having System Efficacy of > =90 lumens / watt, CCT: 3000K - 5700K, minimum CRI > 70, Luminaire performance complies to IS 10322 (Part 5 / Sec-2) etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category II.		
	MAT-03299	a	6W	1 No	569
	MAT-03300	b	9W	1 No	724
	MAT-03301	c	12W	1 No	1049
	MAT-03302	d	15W	1 No	1126
	MAT-03303	e	18W	1 No	1204
120		ELEC-3.8.3	Supply and fixing of..... heavy duty LED Down lighter, suitable for Recessed / Surface mounting made of pressure diecast aluminum body with powder coating, acrylic diffuser with driver as per IS: 15885 (Part 2/ Sec 13) : 2012 , operating voltage range of 150 to 265 Volts AC, P.F > 0.9, Surge protection: 2KV, THD<10% with high power LEDs, having System Efficacy of >=80 lumens / watt, CCT: 3000K - 5700K, minimum CRI > 70, Luminaire performance complies to IS 10322 (Part 5 / Sec-2) etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category III.		
	MAT-03304	a	6W	1 No	496
	MAT-03305	b	9W	1 No	637
	MAT-03306	c	12W	1 No	903
	MAT-03307	d	15W	1 No	971
	MAT-03308	e	18W	1 No	1044

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			LED PANEL LIGHTS		
121		ELEC-3.8.4	Supply and fixing of..... LED Slim Panel Round /Square suitable for Recessed / Surface mounting made of diecast aluminum body with powder coating, acrylic diffuser with driver as per IS: 15885 (Part 2/ Sec 13) : 2012, operating voltage range of 150 to 265 Volts AC, P.F > 0.9, Surge protection: 2KV, THD<10%, with high power LEDs, having System Efficacy of >=100 lumens /watt, CCT: 3000K - 5700K, minimum CRI>70, Luminaire performance complies to IS 10322 (Part 5 / Sec-2) .etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I.		
	MAT-03309	a	3W	1 No	252
	MAT-03310	b	6W	1 No	435
	MAT-03311	c	12W	1 No	723
	MAT-03312	d	15W	1 No	913
	MAT-03313	e	18W	1 No	1000
	MAT-03314	f	24W	1 No	1262
	MAT-03315	g	40W (600mm x 600mm) square type	1 No	3088
		h	36W/40W (1200mm x 300mm) rectangle type	1 No	3214
122		ELEC-3.8.5	Supply and fixing of..... LED Slim Panel Round /Square suitable for Recessed / Surface mounting made of diecast aluminum body with powder coating, acrylic diffuser with driver as per IS: 15885 (Part 2/ Sec 13) : 2012, operating voltage range of 150 to 265 Volts AC, P.F > 0.9, Surge protection: 2KV, THD<10%, with high power LEDs, having System Efficacy of >=90 lumens /watt, CCT: 3000K - 5700K, minimum CRI>70, Luminaire performance complies to IS 10322 (Part 5 / Sec-2) etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category II.		
	MAT-03316	a	3W	1 No	244
	MAT-03317	b	6W	1 No	426

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03318	c	12W	1 No	695
	MAT-03319	d	15W	1 No	891
	MAT-03320	e	18W	1 No	957
	MAT-03321	f	24W	1 No	1174
	MAT-03322	g	40W (600mm x 600mm) square type	1 No	3001
		h	36W/40W (1200mm x 300mm) rectangle type	1 No	3127
123		ELEC-3.8.6	Supply and fixing of..... LED Slim Panel Round /Square suitable for Recessed / Surface mounting made of diecast aluminum body with powder coating, acrylic diffuser with driver as per IS: 15885 (Part 2/ Sec 13) : 2012, operating voltage range of 150 to 265 Volts AC, P.F > 0.9, Surge protection: 2KV, THD<10%, with high power LEDs, having System Efficacy of >=80 lumens /watt, CCT: 3000K - 5700K, minimum CRI>70, Luminaire performance complies to IS 10322 (Part 5 / Sec-2) etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category III.		
	MAT-03323	a	3W	1 No	231
	MAT-03324	b	6W	1 No	400
	MAT-03325	c	12W	1 No	653
	MAT-03326	d	15W	1 No	870
	MAT-03327	e	18W	1 No	900
	MAT-03328	f	24W	1 No	1131
			COB DOWN LIGHTS		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
124		ELEC-3.8.7	Supply and fixing of..... LED COB Down lighter, suitable for Recessed mounting made of pressure diecast aluminum housing with powder coating, with high efficiency reflector , operating voltage range of 150 to 265 Volts AC, P.F > 0.9, Surge protection: 2KV, THD<10% with high power LEDs, having System Efficacy of > =100 lumens/watt, CCT: 3000K - 5700K, minimum CRI>70, .etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I.		
	MAT-03329	a	9 / 10 W	1 No	1155
	MAT-03330	b	15 / 16 W	1 No	1497
	MAT-03331	c	18 / 20 W	1 No	1668
	MAT-03332	d	30 W	1 No	2652
	MAT-03333	f	45 W	1 No	2909
125		ELEC-3.8.8	Supply and fixing of LED COB Down lighter, suitable for Recessed mounting made of pressure diecast aluminum housing with powder coating, with high efficiency reflector , operating voltage range of 150 to 265 Volts AC, P.F > 0.9, Surge protection: 2KV, THD<10% with high power LEDs, having System Efficacy of >=90 lumens / watt, CCT: 3000K - 5700K, minimum CRI>70, etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category II.		
	MAT-03334	a	9 / 10 W	1 No	1112
	MAT-03335	b	15/ 16W	1 No	1412
	MAT-03336	c	18 / 20W	1 No	1583
	MAT-03337	d	30W	1 No	2567
			SPOTLIGHTS / WALL WASHERS		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
126		ELEC-3.8.9	Supply and Transportation of LED COB Spotlight suitable for Recessed mounting made of diecast aluminum body with powder coating, high efficiency reflector, with driver, operating voltage range of 150 to 265 Volts AC, P.F > 0.9, surge protection: 2KV, THD<10% with high power LEDs, having System Efficacy of > =100 lumens/watt, CCT: 3000K - 5700K, minimum CRI>70, etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I.		
	MAT-03338	a	2/3 W	1 No	385
	MAT-03339	b	5/6 W	1 No	471
	MAT-03340	c	7 W	1 No	898
127		ELEC-3.8.10	Supply and Transportation of LED COB Spotlight suitable for Recessed mounting made of diecast aluminum body with powder coating, high efficiency reflector, with driver, operating voltage range of 150 to 265 Volts AC, P.F > 0.9, Surge protection: 2KV, THD<10% with high power LEDs, having System Efficacy of > =90 lumens/watt, CCT: 3000K - 5700K, minimum CRI>70, etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category II.		
	MAT-03341	a	2/3 W	1 No	342
	MAT-03342	b	5/6 W	1 No	428
	MAT-03343	c	7 W	1 No	856
128		ELEC-3.8.11	Supply and fixing of..... LED single colour Wall washer, 1000mm length, IP65, made of diecast aluminum body with powder coating, with driver, operating voltage range of 150 to 265 Volts AC, with high power LEDs, having System Efficacy of >=100 lumens/watt, CCT: 3000-4000K , beam angle 25/45 degrees, minimum CRI>70, .etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I.		
	MAT-03344	a	18W	1 No	3508
	MAT-	b	24W	1 No	4107

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03345				
129		ELEC-3.8.12	Supply and fixing of..... LED single colour Wall washer, 1000mm length, IP65, made of diecast aluminum body with powder coating, with driver, operating voltage range of 150 to 265 Volts AC, with high power LEDs, having System Efficacy of ≥ 90 lumens/watt, CCT: 3000-4000K , beam angle 25/45 degrees, minimum CRI >70 , .etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category II.		
	MAT-03346	a	18W	1 No	3251
	MAT-03347	b	24W	1 No	3979
			LED BATTENS AND 2' x 2' LUMINARIES		
130	MAT-03348	ELEC-3.8.13	Supply and fixing of 20-24W, not less than 1100mm length LED batten light with extruded aluminum housing and polycarbonate cover, input voltage AC 220 - 260 Volts, with high power LEDs, having System Efficacy of ≥ 100 lumens/watt , PF >0.9 , Surge protection: 2KV, THD $<15\%$, with inbuilt driver and frosted cover CCT: 3000K - 5700K, minimum CRI >70 , etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I.	1 No	585
131	MAT-03349	ELEC-3.8.14	Supply and fixing of 20-24W, not less than 1100mm length LED batten light with extruded aluminum housing and polycarbonate cover, input voltage AC 220 - 260 Volts, with high power LEDs, having System Efficacy of ≥ 90 lumens/watt , PF >0.9 , Surge protection: 2KV, THD $<15\%$, with inbuilt driver and frosted cover CCT: 3000K - 5700K, minimum CRI >70 , etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category II.	1 No	526

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
132	MAT-03350	ELEC-3.8.15	Supply and fixing of 20-24W, not less than 1100mm length LED batten light with extruded aluminum housing and polycarbonate cover, input voltage AC 220 - 260 Volts, with high power LEDs, having System Efficacy of ≥ 80 lumens/watt, PF >0.9 , Surge protection: 2KV, THD $<15\%$, with inbuilt driver and frosted cover CCT: 3000K - 5700K, minimum CRI >70 , etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category III.	1 No	439
133	MAT-03351	ELEC-3.8.16	Supply and fixing of 20W, 2400 lumens, T8 not less than 1100 mm length LED retrofit tube light with aluminum anodized body, input voltage AC 220 - 260 Volts, having luminous efficacy ≥ 100 lumens/watt, with PF >0.9 , surge protection: 2KV, THD $<10\%$, with inbuilt driver and frosted cover CCT: 3000K-5700K, minimum CRI >70 , etc., as per IS 10322 (Part 5/ Sec 1), 2012, complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I.	1 No	520
134	MAT-03352	ELEC-3.8.17	Supply and fixing of 20W, 2400 lumens, T8 not less than 1100 mm length LED retrofit tube light with aluminum anodized body, input voltage AC 220 - 260 Volts, having luminous efficacy ≥ 90 lumens/watt, with PF >0.9 , surge protection: 2KV, THD $<10\%$, with inbuilt driver and frosted cover CCT: 3000K-5700K, minimum CRI >70 , etc., as per IS 10322 (Part 5/ Sec 1), 2012, complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category II.	1 No	475
135	MAT-03353	ELEC-3.8.18	Supply of not less than 1100mm length, Box type powder coated tube light luminaire with necessary wiring suitable for fixing 2 Nos retrofit T8 LED tubes but without tube and choke. Makes: As per list of recommended brands as Category-I.	1 No	248
136	MAT-03354	ELEC-3.8.19	Supply of not less than 1100mm length, Box type powder coated tube light luminaire with necessary wiring suitable for fixing 1 No retrofit T8 LED tube but without tube and choke. Makes: As per list of recommended brands as	1 No	214

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Category-II.		
137		ELEC-3.8.20	Supply, transportation and fixing of Recessed / Surface mounting 2' x 2' (600x600 mm) LED luminaire made of CRCA sheet housing with powder coated with acrylic diffuser, constant current driver as per IS: 15885 (Part 2/ Sec 13) : 2012 , with operating voltage range of 150 to 265 Volts AC, P.F > 0.9, Surge protection: 2KV, THD<10%, with high power LEDs, having System Efficacy of >=100 lumens / watt, CCT: 3000K - 5700K, minimum CRI>70, Luminaire performance complies to IS 10322 (Part 5 / Sec-2) etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I.		
	MAT-03355	a	36 W	1 No	2646
	MAT-03356	b	45 W	1 No	2948
138		ELEC-3.8.21	Supply, transportation and fixing of Recessed / Surface mounting 2' x 2' (600x600 mm) LED luminaire made of CRCA sheet housing with powder coated with acrylic diffuser, constant current driver as per IS: 15885 (Part 2/ Sec 13) : 2012 , with operating voltage range of 150 to 265 Volts AC, P.F > 0.9, Surge protection: 2KV, THD<10%, with high power LEDs, having System Efficacy of > =90 lumens / watt, CCT: 3000K - 5700K, minimum CRI>70, Luminaire performance complies to IS 10322 (Part 5 / Sec-2) etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category II.		
	MAT-03357	a	36 W	1 No	2494
	MAT-03358	b	45 W	1 No	2797
139	MAT-03359	ELEC-3.8.22	Supply of 10W LED Bulkhead fitting with Pressure die cast aluminum with opal diffuser with IP 65 protection etc., complete. Makes: As per list of recommended brands as category I.		
140		ELEC-3.8.22	Supply, Transportation and Fixing of, 1100mm length Linear Profile LED Luminaire recessed/surface mounted with Aluminum extrusion, powder coated cover, input voltage AC 90-270 volts with PF>0.95, with high power LEDs, having		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			system efficacy of ≥ 100 lumens / watt, surge protection: 2KV, THD $\leq 15\%$, with inbuilt driver and frosted cover CCT: 3000K - 5700K, minimum CRI ≥ 70 , .etc., complete including fixing of 23W Linear light duly recessed in the ceiling/surface mounted by hanging from ceiling with necessary mounting arrangements, jointing kit, connecting wire leads etc., and all accessories, giving connections and all labour charges etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands.		
	MAT-08766	a	20/25W	1 No	3222
	MAT-08767	b	40W	1 No	5524
			LED STREET LIGHTS		
141		ELEC-3.8.23	Supply and transportation of LED Street light Luminaire made of pressure diecast aluminum body with powder coated, having protective toughened glass/ temperature protective polycarbonate diffuser, supply input voltage 120 - 270V AC, P.F > 0.90 , high power LEDs having System Efficacy ≥ 120 lumens/watt and junction temperature $< 70^{\circ}\text{C}$, with Ingress protection IP66, Luminaire performance complies to IS 10322 (Part 5/Sec-3), driver surge protection 4KV, in-house additional Surge protection 10 KV with optics distribution, THD $\leq 10\%$ at 110 Volts AC, driver efficiency $> 90\%$, CCT: 3000K - 5700K, minimum CRI ≥ 70 , etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I.		
	MAT-03360	a	20W	1 No	1373
	MAT-03361	b	30W	1 No	2148
	MAT-03362	c	45W	1 No	3257
	MAT-03363	d	60W	1 No	4089

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
142		ELEC-3.8.24	Supply and transportation of LED Street light Luminaire made of pressure diecast aluminum body with powder coated, having protective toughened glass / temperature protective polycarbonate diffuser, supply input voltage 120 - 270V AC, P.F > 0.90, high power LEDs having System Efficacy >= 120 lumens/watt and junction temperature < 70°C, with Ingress protection IP66, Luminaire performance complies to IS 10322 (Part 5/Sec-3), driver surge protection 4KV, in-house additional Surge protection 10 KV with optics distribution, THD<10% at 110 Volts AC, driver efficiency >90%, CCT: 3000K - 5700K, minimum CRI>70, etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I		
	MAT-03364	a	90W	1 No	6377
	MAT-03365	b	120W	1 No	8248
	MAT-03366	c	150W	1 No	9530
	MAT-03367	d	180W	1 No	10742
	MAT-03368	e	210W	1 No	13861
143		ELEC-3.8.25	Supply and transportation of LED Street light Luminaire made of pressure diecast aluminum body with powder coated, having protective toughened glass / temperature protective polycarbonate diffuser, supply input voltage 120 - 270V AC, P.F > 0.90, high power LEDs having System Efficacy >= 100 lumens/watt and junction temperature < 70°C, with Ingress protection IP66, Luminaire performance complies to IS 10322 (Part 5/Sec-3), driver surge protection 4KV, in-house additional Surge protection 10 KV with optics distribution, THD<10% at 110 Volts AC, driver efficiency >90%, CCT: 3000K - 5700K, minimum CRI>70, etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category II		
	MAT-03369	a	20W	1 No	1283
	MAT-03370	b	30W	1 No	1997
	MAT-03371	c	45W	1 No	3119

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03372	d	60W	1 No	3881
	MAT-03373	e	90W	1 No	6030
	MAT-03374	f	120W	1 No	7277
	MAT-03375	g	150W	1 No	8733
	MAT-03376	h	180W	1 No	9980
	MAT-03377	i	210W	1 No	12163
144		ELEC-3.8.26	Supply and transportation of LED Street light Luminaire made of pressure diecast aluminum body with powder coated, having protective toughened glass / temperature protective polycarbonate diffuser, supply input voltage 120 - 270V AC, P.F > 0.90, high power LEDs having System Efficacy >= 90 lumens/watt and junction temperature < 70°C, with Ingress protection IP66, Luminaire performance complies to IS 10322 (Part 5/Sec-3), driver surge protection 4KV, in-house additional Surge protection 10 KV with optics distribution, THD<10% at 110 Volts AC, driver efficiency >90%, CCT: 3000K - 5700K, minimum CRI>70, etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category III		
	MAT-03378	a	20W	1 No	1217
	MAT-03379	b	30W	1 No	1768
	MAT-03380	c	45W	1 No	2912
	MAT-03381	d	60W	1 No	3604
	MAT-03382	e	90W	1 No	5613
	MAT-03383	f	120W	1 No	6584

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			FLOOD LIGHTS		
145		ELEC-3.8.27	Supply and transportation of LED Flood light Luminaire made of pressure diecast aluminum housing with powder coated, having protective toughened glass, supply Input voltage 120 - 270 V AC, P.F > 0.90, high power LEDs, with a System Efficacy >=120 lumens/watt and junction temperature < 70°C, with ingress protection IP66, Luminaire performance complies to IS 10322 (Part 5 / Sec-5), IK05, driver surge protection 4KV, In-house additional surge protection ≥ 10KV with wide/narrow beam optics, THD<10% at 110 Volts AC, driver efficiency >90%, , CCT: 3000K - 5700K, minimum CRI>70, etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I.		
	MAT-03384	a	50/60W	1 No	4055
	MAT-03385	b	90/100W	1 No	7173
	MAT-03386	c	120W	1 No	9293
	MAT-03387	d	150W	1 No	10915
	MAT-03388	e	200W	1 No	13099
	MAT-03389	f	250W	1 No	15281
	MAT-03390	g	300 W	1 No	18088
	MAT-03391	h	400W	1 No	20894
146		ELEC-3.8.28	Supply and transportation of LED Flood light Luminaire made of pressure diecast aluminum housing with powder coated, having protective toughened glass, supply Input voltage 120 - 270 V AC, P.F > 0.90, high power LEDs, with a System Efficacy >=100 lumens/watt and junction temperature < 70°C, with ingress protection IP66, Luminaire performance complies to IS 10322 (Part 5 / Sec-5), IK05, driver surge protection 4KV, In-house additional surge protection ≥ 10KV with wide/narrow beam optics, THD<10% at 110 Volts AC, driver efficiency >90%, , CCT: 3000K - 5700K, minimum CRI>70, etc., complete with earth connection and not less than two years warranty.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: As per list of recommended brands as category II.		
	MAT-03392	a	50/60W	1 No	3617
	MAT-03393	b	90/100W	1 No	6549
	MAT-03394	c	120W	1 No	8420
	MAT-03395	d	150W	1 No	9980
	MAT-03396	e	200W	1 No	11851
			HIGH BAY LIGHTS		
147		ELEC-3.8.29	Supply and transportation of LED High Bay Luminaire with high power COB LED made of pressure diecast aluminum housing with powder coated, supply input voltage 120 - 270 V AC, P.F > 0.90, high power LEDs, having system efficacy >=120 lumens/watt and junction temperature < 70°C, with ingress protection IP66, IK05, Driver surge protection 4KV, in-house additional surge protection ≥ 5KV with wide/narrow beam optics, THD<10% at 110 Volts AC, driver efficiency >90%, , CCT: 3000K - 5700K, minimum CRI>70, etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category I.		
	MAT-03400	a	60W	1 No	5891
	MAT-03401	b	90W	1 No	7624
	MAT-03402	c	120W	1 No	8663
	MAT-03403	d	150W	1 No	10049

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
148		ELEC-3.8.30	Supply and transportation of LED High Bay Luminaire with high power COB LED made of pressure diecast aluminum housing with powder coated, supply input voltage 120 - 270 V AC, P.F > 0.90, high power LEDs, having system efficacy >=100 lumens/watt and junction temperature < 70°C, with ingress protection IP66, IK05, Driver surge protection 4KV, in-house additional surge protection ≥ 5KV with wide/narrow beam optics, THD<10% at 110 Volts AC, driver efficiency >90%, , CCT: 3000K - 5700K, minimum CRI>70, etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands as category II.		
	MAT-03404	a	60W	1 No	5545
	MAT-03405	b	90W	1 No	6792
	MAT-03406	c	120W	1 No	7970
	MAT-03407	d	150W	1 No	9356
149		ELEC-3.8.31	Supply and transportation of LED Linear Wall washer of size mm with high power LEDs, made of pressure diecast aluminum housing with powder coated, supply Input voltage 120 - 270 V AC, leads to 24 V DC output voltage drives with beam angle of 15/25/45/60, P.F > 0.90, having system efficacy >=120 lumens/wat and junction temperature < 70°C, with ingress protection IP66, IK05, with multi colour (Red or Yellow or Green or blue or White) etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands.		
	MAT-05492	a	18 W, 1000 X 38 X 58 mm	1 No	8043
	MAT-05493	b	24 W, 1000 X 38 X 58 mm	1 No	8470
	MAT-05494	c	36 W, 1000 X 38 X 86 mm	1 No	9839
	MAT-05495	d	48 W, 1000 X 60 X 100 mm	1 No	11893
			RGB/RGBW LED Lighting		
150		ELEC-3.8.32	Supply and transportation of IP-66, RGBW LED Flood light Luminaries made of pressure die cast aluminum housing with powder coated, having protective toughened glass, with a system efficacy of		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			>=120 lumens/watt, supply input voltage 120 - 270 V AC, leads to 24 V DC output voltage drives RGB LEDs with light angle 60°, surge protection 6KV and junction temperature < 70°C, CRI>70, P.F>0.9, suitable for RGB DMX 512 controller etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands.		
	MAT-05496	a	90W	1 No	23460
	MAT-05497	b	120W	1 No	26680
151		ELEC-3.8.33	Supply and transportation of RGB LED Linear Wall washer of Size mm with high power LEDs, made of pressure diecast aluminum housing with powder coated, supply input voltage 120 - 270 V AC, leads to 24 V DC output voltage drives, with beam angle of 15/25/45/60, P.F > 0.90, having system efficacy >=100 lumens/watt and junction temperature < 70°C, with ingress protection IP66, IK05, suitable for RGB DMX 512 controller etc., complete with earth connection and not less than two years warranty. Makes: As per list of recommended brands.		
	MAT-05498	a	18 W, 1000 X 38 X 58 mm	1 No	10304
	MAT-05499	b	24 W, 1000 X 38 X 58 mm	1 No	10856
	MAT-05500	c	36 W, 1000 X 38 X 58 mm	1 No	12144
	MAT-05501	d	48 W, 1000 X 60 X 100 mm	1 No	15364
152	MAT-05502	ELEC-3.8.34	Supply, transportation and installation of stand-alone USB -DMX controller to control a wide variety of different DMX systems from RGB/RGBW, including 1024 DMX channels, input power 5-5.5 V DC 0.6 A with programmability on PC, MAC, tablet, smart phone with micro SD card etc complete Makes: As per list of recommended brands.	1 No	78000
153	MAT-05503	ELEC-3.8.35	Supply, Transportation and Installation of DMX splitter/booster in the existing junction box with necessary connections. Makes: As per list of recommended brands.	1 No	16000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
154	MAT-05504	ELEC-3.8.36	Supply, Transportation and Installation of DMX-DC-5A, decoder in the existing junction box with necessary connections. Makes: As per list of recommended brands.	1 No	5200
155	MAT-05505	ELEC-3.8.37	Supply, Transportation and Installation of DC 24V input DMX Data Repeater in the existing junction box with necessary connections. Makes: As per list of recommended brands.	1 No	3900
156	MAT-05506	ELEC-3.8.38	Supply, Transportation and Installation of 350W, non-waterproof, DC 24V, Constant Voltage Power Supply (driver) unit in the existing junction box with necessary connections. Makes: As per list of recommended brands.	1 No	4900
157	MAT-05507	ELEC-3.8.39	Supply, Transportation and Installation of 350W, non-water proof, DC 12V,1.25 A Constant Voltage Power Supply (driver) Unit in the existing junction box with necessary connections. Makes: As per list of recommended brands.	1 No	3200
			LED DRIVERS		
158		ELEC-3.8.40	Supply and transportation of LED Driver as per IS 15885 (Part 2 / Sec 13)..2012 with input line voltage 120V-270V AC, 50Hz with surge protection more than 2.5 KV, IP20, suitable for LED indoor luminaire, with 2 Years Warranty. Makes: As per list of recommended brands.		
	MAT-03408	a	6/9 W	1 No	259
	MAT-03409	b	12/15/18/20 W	1 No	374
	MAT-03410	c	36 W	1 No	700
	MAT-03411	d	40/45 W	1 No	800
159		ELEC-3.8.41	Supply and transportation of LED Driver as per IS 15885 (Part 2 / Sec 13)..2012 with input line voltage 120V-270V AC, 50Hz with surge protection of 4.0 KV, IP20, suitable for LED street light fitting with 2 Years Warranty. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03412	a	15-30 W	1 No	403
	MAT-03413	b	45-90 W	1 No	920
	MAT-03414	c	120-180 W	1 No	1610
			SECTION - 4		
		4.1	U.G. CABLES		
160		ELEC-4.1.1	Supply and transportation of following XLPE insulated, 1100V grade armoured aluminum cable as per specification confirming to IS:7098 (Part - I)/1554-I Makes: As per list of recommended brands as category I.		
	MAT-03415	a	4 Sq mm X 2 core	1 RM	90
	MAT-03416	b	6 Sq mm X 2 core	1 RM	110
	MAT-03417	c	10 Sq mm X 2 core	1 RM	133
	MAT-03418	d	6 Sq mm X 4 core	1 RM	146
	MAT-03419	e	10Sq mm X 4 core	1 RM	172
	MAT-03420	f	16 Sq mm X 4 core	1 RM	202
	MAT-03421	g	25 Sq mm X 3.5 core	1 RM	247
	MAT-03422	h	35Sq mm X 3.5 core	1 RM	306
	MAT-03423	i	50 Sq mm X 3.5 core	1 RM	405
	MAT-03424	j	70 Sq mm X 3.5 core	1 RM	545
	MAT-03425	k	95 Sq mm X 3.5 core	1 RM	680
	MAT-03426	l	120 Sq mm X 3.5 core	1 RM	846

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03427	m	150 Sq mm X 3.5 core	1 RM	985
	MAT-03428	n	185 Sq mmX 3.5 core	1 RM	1247
	MAT-03429	o	240 Sq mm X 3.5 core	1 RM	1587
	MAT-03430	p	300Sq mm X 3.5 core	1 RM	1931
	MAT-03431	q	400Sq mm X 3.5 core	1 RM	2485
161		ELEC - 4.1.2	Supply and transportation of following XLPE insulated, 1100V grade armoured aluminum cable as per specification confirming to IS:7098 (Part - I)/1554-I. Makes: As per list of recommended brands as category II.		
	MAT-03432	a	4 Sq mm X 2 core	1 RM	85
	MAT-03433	b	6 Sq mm X 2 core	1 RM	96
	MAT-03434	c	10 Sq mm X 2 core	1 RM	117
	MAT-03435	d	6 Sq mm X 4 core	1 RM	123
	MAT-03436	e	10Sq mm X 4 core	1 RM	134
	MAT-03437	f	16 Sq mm X 4 core	1 RM	150
	MAT-03438	g	25 Sq mm X 3.5 core	1 RM	191
	MAT-03439	h	35Sq mm X 3.5 core	1 RM	250
	MAT-03440	i	50 Sq mm X 3.5 core	1 RM	331
	MAT-03441	j	70 Sq mm X 3.5 core	1 RM	426
	MAT-03442	k	95 Sq mm X 3.5 core	1 RM	557

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03443	l	120 Sq mm X 3.5 core	1 RM	684
	MAT-03444	m	150 Sq mm X 3.5 core	1 RM	785
	MAT-03445	n	185 Sq mm X 3.5 core	1 RM	940
	MAT-03446	o	240 Sq mm X 3.5 core	1 RM	1189
	MAT-03447	p	300Sq mm X 3.5 core	1 RM	1439
	MAT-03448	q	400Sq mm X 3.5 core	1 RM	1867
			33 KV HT XLPE CABLES		
162		ELEC-4.1.3	Supply and Transportation of XLPE insulated IS:7098/II/85 H.T. cable for working voltage 33 KV Earthed with Stranded Compacted Circular Aluminum Conductor Screened with Extruded Semi-conducting compound, XLPE Insulated Screened with extruded semi-conducting compound in combination with Copper Tape, cores laid up, inner sheath of Thermoplastic tape, galvanized flat steel strip armoured and overall Extruded PVC Type ST- 2 Outer Sheathed cable etc., complete. Makes: As per list of recommended brands.		
	MAT-03449	a	3C X 95 Sq mm	1 RM	2070
	MAT-03450	b	3C X 120 Sq mm	1 RM	2272
	MAT-03451	c	3C X 150 Sq mm	1 RM	2509
	MAT-03452	d	3C X 185 Sq mm	1 RM	2780
	MAT-03453	e	3C X 240 Sq mm	1 RM	3168
	MAT-03454	f	3C X 300 Sq mm	1 RM	3578
	MAT-03455	g	3C X 400 Sq mm	1 RM	4162

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			11 KV HT XLPE CABLES		
163		ELEC-4.1.4	Supply and Transportation of XLPE insulated IS:7098/II/85 H.T. cable for working voltage 11 KV Earthed with Stranded Compacted Circular Aluminium Conductor Screened with Extruded Semi-conducting compound, XLPE Insulated Screened with extruded semi-conducting compound in combination with Copper Tape, cores laid up, inner sheath of Thermoplastic tape, galvanized flat steel strip armoured and overall Extruded PVC Type ST- 2 Outer Sheathed cable etc., complete. Makes: As per list of recommended brands.		
	MAT-03456	a	3C X 35 Sq mm	1 RM	685
	MAT-03457	b	3C X 50 Sq mm	1 RM	786
	MAT-03458	c	3C X 70 Sq mm	1 RM	935
	MAT-03459	d	3C X 95 Sq mm	1 RM	1119
	MAT-03460	e	3C X 120 Sq mm	1 RM	1291
	MAT-03461	f	3C X 150 Sq mm	1 RM	1447
	MAT-03462	g	3C X 185 Sq mm	1 RM	1691
	MAT-03463	h	3C X 240 Sq mm	1 RM	2035
	MAT-03464	i	3C X 300 Sq mm	1 RM	2413
	MAT-03465	j	3C X 400 Sq mm	1 RM	2947
			Unarmoured and Armoured Copper Control Cables		
164		ELEC-4.1.5	Supply and Transportation of XLPE/PVC insulated & PVC sheathed unarmoured control cables of 1.1 KV grade with copper conductor as per IS 7098 Part-I -1988 etc., complete. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03466	a	2C x 1.5 sq.mm	1 RM	117
	MAT-03467	b	3C x 1.5 sq.mm	1 RM	123
	MAT-03468	c	4C x 1.5 sq.mm	1 RM	144
	MAT-03469	d	5C x 1.5 sq.mm	1 RM	149
	MAT-03470	e	6C x 1.5 sq.mm	1 RM	169
	MAT-03471	f	8C x 1.5 sq.mm	1 RM	195
	MAT-03472	g	10C x 1.5 sq.mm	1 RM	246
	MAT-03473	h	12C x 1.5 sq.mm	1 RM	273
	MAT-03474	i	14C x 1.5 sq.mm	1 RM	304
	MAT-03475	j	19C x 1.5 sq.mm	1 RM	382
	MAT-03476	k	2C x 2.5 sq.mm	1 RM	130
	MAT-03477	l	3C x 2.5 sq.mm	1 RM	149
	MAT-03478	m	4C x 2.5 sq.mm	1 RM	174
	MAT-03479	n	5C x 2.5 sq.mm	1 RM	195
	MAT-03480	o	6C x 2.5 sq.mm	1 RM	273
	MAT-03481	p	8C x 2.5 sq.mm	1 RM	325
	MAT-03482	q	10C x 2.5 sq.mm	1 RM	376
	MAT-	r	12C x 2.5 sq.mm	1 RM	421

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03483				
	MAT-03484	s	14C x 2.5 sq.mm	1 RM	473
	MAT-03485	t	19C x 2.5 sq.mm	1 RM	550
165		ELEC-4.1.5 A	Supply and Transportation of stranded/solid copper conductor XLPE/PVC insulated & PVC sheathed, unarmoured and Overall Shielded instrumentation/control cables of 1.1 KV grade with copper conductor as per IS 7098 Part-I -1988 etc., complete. Makes: As per list of recommended brands.		
		a	2 Core, 1.5 Sq.mm	1 RM	70
		b	4 Core, 1.0 Sq.mm	1 RM	118
166		ELEC-4.1.5 B	Supply, Laying, Termination of ISI Certified (for Signal & Field devices, Third Party Integration etc....) ATSC, PVC insulated, armored, Tinned Copper, twisted, shielded, PE insulated, Cable with proper ferrules, lugs, and other necessary accessories. The spec shall meet the system manufacturer specifications including all charges complete etc., as directed by Engineer in Charge/ departmental authorities. Makes: As per list of recommended brands.		
		a	2 Core 1.5 sq.mm	1 RM	65
		b	4 Core 1.5 sq.mm	1 RM	94
167		ELEC-4.1.5 C	Supply of Shielded unarmoured Cable, as per the survey done, Rate shall include required accessories, tools and tackles, transportation, material, and labour etc., complete as instructed by Engineer In charge. The contractor should follow the safety measures inside the premises. Makes: As per list of recommended brands.		
		a	2 Core .75 Sq mm	1 RM	94
		b	4 Core .75 Sq mm	1 RM	126
		c	8 Core .75 Sq mm	1 RM	176
168		ELEC-4.1.6	Supply and Transportation of XLPE/PVC insulated & PVC sheathed armoured cables of 1.1 KV grade with copper conductor as per IS 7098 Part-I -1988 etc., complete. Makes: As per list of recommended brands.		
	MAT-03486	a	2Cx1.5 sq.mm	1 RM	123

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03487	b	2Cx2.5 sq.mm	1 RM	130
	MAT-03488	c	2C x 4 sq.mm	1 RM	163
	MAT-03489	d	2C x 6 sq.mm	1 RM	233
	MAT-03490	e	2C x 10 sq.mm	1 RM	325
	MAT-03491	f	2C x 16 sq.mm	1 RM	448
	MAT-03492	g	3C x 4 sq.mm	1 RM	205
	MAT-03493	h	3C x 6 sq.mm	1 RM	273
	MAT-03494	i	3C x 10 sq.mm	1 RM	340
	MAT-03495	j	3C x 16 sq.mm	1 RM	476
	MAT-03496	k	4C x 4 sq.mm	1 RM	285
	MAT-03497	l	4C x 6 sq.mm	1 RM	408
	MAT-03498	m	4C x 10 sq.mm	1 RM	612
	MAT-03499	n	4C x 16 sq.mm	1 RM	1018
	MAT-03500	o	4C x 25 sq.mm	1 RM	1632
	MAT-03501	p	4C x 35 sq.mm	1 RM	2177
	MAT-03502	q	4C x 50 sq.mm	1 RM	3128
	MAT-03503	r	4C x 70 sq.mm	1 RM	4761

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			CABLE TERMINATIONS AND ACCESSORIES		
169		ELEC-4.1.7	Supply and Making heat shrinkable type indoor/ outdoor/straight through terminations/joint kit of approved make suitable for XLPE insulated 33 KV cable, with required components, preparation of cable ends, testing etc. as required of following sizes. Makes: As per list of recommended brands.		
			INDOOR		
	MAT-03504	a	3 Core 95/120/150/185 sq mm	Set	14611
	MAT-03505	b	3 core 240/300/400 Sq mm	Set	20328
			OUTDOOR		
	MAT-03506	c	3 Core 95/120/150/185 sq mm	Set	20328
	MAT-03507	d	3 core 240/300/400 Sq mm	Set	28587
			STRAIGHT THROUGH		
	MAT-03508	e	3 Core 95/120/150/185 sq mm	Set	41292
	MAT-03509	f	3 core 240/300/400 Sq mm	Set	60349
170		ELEC-4.1.8	Supply and Making heat shrinkable type indoor /outdoor/straight through terminations/ joint kit of approved make suitable for XLPE insulated 11 KV cable, with required components, preparation of cable ends, testing etc. as required of following sizes. Makes: As per list of recommended brands.		
			INDOOR		
	MAT-03510	a	3 core 35/50 Sq mm	Set	6353.00
	MAT-03511	b	3 core 70/95 Sq mm	Set	9529.00
	MAT-03512	c	3 core120/150/185 Sq mm	Set	10800.00
	MAT-03513	d	3 core 240/300 Sq mm	Set	11308.00

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03514	e	3 core 400/500 Sq mm	Set	11943.00
			OUTDOOR		
	MAT-03515	f	3 core 35/50 Sq mm	Set	10800
	MAT-03516	g	3 core 70/95 Sq mm	Set	13341
	MAT-03517	h	3 core 120/150/185 Sq mm	Set	14611
	MAT-03518	i	3 core 240/300 Sq mm	Set	15882
	MAT-03519	j	3 core 400/500 Sq mm	Set	17787
			STRAIGHT THROUGH		
	MAT-03520	k	3 core 35/50 Sq mm	Set	17152
	MAT-03521	l	3 core 70/95 Sq mm	Set	20328
	MAT-03522	m	3 core 120/150/185 Sq mm	Set	23505
	MAT-03523	n	3 core 240/300 Sq mm	Set	25410
171		ELEC-4.1.9	Supply & Making heat shrinkable outdoor straight through joint for following size of PVC/ XLPE insulated aluminum conductor cable of 1.1 KV grade including cost of compound, sleeves etc. as required. Makes: As per list of recommended brands.		
	MAT-03524	a	3.5core x 25/35/50 sq.mm	Set	1906
	MAT-03525	b	3.5 core x 70/95/120 sq.mm	Set	3049
	MAT-03526	c	3.5 core x 150/185/240 sq.mm	Set	4447
	MAT-03527	d	3.5 core x 300/400 sq.mm	Set	6988
	MAT-03528	e	4 core x 6/10/16 sq.mm	Set	1016

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
172		ELEC-4.1.10	Supply and making one end termination with heavy duty double compression brass gland as per BS 6121:2005, IP 66 complete, SIBG type, heavy duty Aluminum lugs duly crimped with crimping tool, PVC tape etc., for following size of Armoured PVC insulated & PVC sheathed/ XLPE aluminum conductor cable of 1100 volt grade as required of size. Makes: As per list of recommended brands.		
	MAT-03529	a	3.5 core x 25 sq.mm	Set	273
	MAT-03530	b	3.5 core x 35 sq.mm	Set	363
	MAT-03531	c	3.5 core x 50 sq.mm	Set	424
	MAT-03532	d	3.5 core x 70 sq.mm	Set	629
	MAT-03533	e	3.5 core x 95 sq.mm	Set	721
	MAT-03534	f	3.5 core x 120 sq.mm	Set	908
	MAT-03535	g	3.5 core x 150 sq.mm	Set	1089
	MAT-03536	h	3.5 core x 185 sq.mm	Set	1210
	MAT-03537	i	3.5 core x 240sq.mm	Set	1815
	MAT-03538	j	3.5 core x 300 sq.mm	Set	2178
	MAT-03539	k	3.5 core x 400 sq.mm	Set	2904
	MAT-03540	l	4 core x 6/10/16 sq.mm	Set	278
173		ELEC-4.1.11	Supply and making one end termination with heavy duty single compression brass gland as per BS 6121:2005 ,IP 66 complete, SIBG type, heavy duty Aluminum lugs duly crimped with crimping tool, PVC tape etc., for following size of Armoured PVC insulated & PVC sheathed/ XLPE aluminum conductor cable of 1100 volt grade as required of size. Makes: As per list of recommended brands.		
	MAT-	a	2 core X 4/6/10 Sq mm	Set	79.00

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03541				
	MAT-03542	b	4 core X 6/10/16 Sq mm	Set	103.00
	MAT-03543	c	3.5 core X 25 Sq mm	Set	121.00
	MAT-03544	d	3.5 core X 35Sq mm	Set	182.00
	MAT-03545	e	3.5 core X 50 Sq mm	Set	194.00
	MAT-03546	f	3.5 core X 70 Sq mm	Set	212.00
	MAT-03547	g	3.5 core X 95 Sq mm	Set	254.00
	MAT-03548	h	3.5 core X 120 Sq mm	Set	303.00
	MAT-03549	i	3.5 coreX150 Sq mm	Set	545.00
	MAT-03550	j	3.5 coreX185 Sq mm	Set	666.00
	MAT-03551	k	3.5 coreX240 Sq mm	Set	787.00
	MAT-03552	l	3.5 coreX300Sq mm	Set	1089.00
	MAT-03553	m	3.5 coreX400Sq mm	Set	1452.00
174		ELEC-4.1.12	Supply and making end termination with heavy copper lugs (pin/ ring type) as per IS specification, duly crimped with crimping tool, PVC tape etc., of following size Makes: As per list of recommended brands.		
	MAT-03554	a	up to 16 Sq mm	each	25.00
	MAT-03555	b	25 Sq mm	each	34.00
	MAT-03556	c	35Sq mm	each	39.00
	MAT-	d	50 Sq mm	each	57.00

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03557				
	MAT-03558	e	70 Sq mm	each	86.00
	MAT-03559	f	95 Sq mm	each	111.00
175		ELEC-4.1.13	Supply and making end termination with heavy Aluminum lugs (pin/ ring type) as per IS specification duly crimped with crimping tool, PVC tape etc., of following size: Makes: As per list of recommended brands.		
	MAT-03560	a	up to 16 Sq mm	each	12.00
	MAT-03561	b	25 Sq mm	each	19.00
	MAT-03562	c	35Sq mm	each	24.00
	MAT-03563	d	50 Sq mm	each	31.00
	MAT-03564	e	70 Sq mm	each	36.00
	MAT-03565	f	95 Sq mm	each	43.00
	MAT-03566	g	120 Sq mm	each	48.00
	MAT-03567	h	150 Sq mm	each	55.00
	MAT-03568	i	185 Sq mm	each	67.00
	MAT-03569	j	240 Sq mm	each	97.00
	MAT-03570	k	300 Sq mm	each	121.00
	MAT-03571	l	400 Sq mm	each	206.00

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		4.2	CABLE TRAYS		
176		ELEC-4.2.1	Supply, transportation & installation of following sizes of Hot Dipped Galvanized Iron perforated cable trays without cover, including horizontal and vertical bends, reducers tees, cross members and other accessories as required and duly suspended from the ceiling/Wall with suspenders etc., complete. (NB: Add 30% Extra for perforated cable tray with cover)		
	MAT-03572	a	100mm x 50mm x 1.6mm	1 RM	373
	MAT-03573	b	150mm x 50mm x 1.6mm	1 RM	433
	MAT-03574	c	300mm x 50mm x 1.6mm	1 RM	799
	MAT-03575	d	450mm x 50mm x 2.0mm	1 RM	1158
	MAT-03576	e	600mm x 50mm x 2.0mm	1 RM	1326
	MAT-03577	f	300mm x 62.5mm x 2.0mm	1 RM	958
	MAT-03578	g	450mm x 62.5mm x 2.0mm	1 RM	1285
	MAT-03579	h	600mm x 62.5mm x 2.0mm	1 RM	1592
	MAT-03580	i	750mm x 62.5mm x 2.0mm	1 RM	1884
	MAT-03581	j	900mm x 62.5mm x 2.0mm	1 RM	2236
	MAT-03582	k	600mm x 75mm x 2.0mm	1 RM	1778
	MAT-03583	l	750mm x 75mm x 2.0mm	1 RM	1957
	MAT-03584	m	900mm x 75mm x 2.0mm	1 RM	2302

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
177		ELEC-4.2.2	Supply, transportation & installation of following sizes of Hot Dipped Galvanized Iron ladder type cable trays with rungs at span of 250 mm including horizontal and vertical bends, reducers tees, cross members and other accessories as required and duly suspended from the ceiling/wall with suspenders and etc., complete		
	MAT-03585	a	150mm x 50mm x 2.0mm	1 RM	546
	MAT-03586	b	300mm x 50mm x 2.0mm	1 RM	686
	MAT-03587	c	450mm x 50mm x 2.0mm	1 RM	905
	MAT-03588	d	600mm x 75mm x 2.0mm	1 RM	1118
	MAT-03589	e	750mm x 75mm x 2.0mm	1 RM	1185
	MAT-03590	f	900mm x 75mm x 2.0mm	1 RM	1258
		4.3	DOUBLE WALLED CORRUGATED HDPE PIPE		
178		ELEC-4.3.1	Supply and Transportation of double walled corrugated HDPE duct made as per specification BSEN - 500 86/IS 14930 Part-II. Makes: As per list of recommended brands.		
	MAT-03591	a	Outer dia 50mm and Inner dia 38mm	1 RM	120
	MAT-03592	b	Outer dia 63mm and Inner dia 51mm	1 RM	154
	MAT-03593	c	Outer dia 78mm and Inner dia 63mm	1 RM	186
	MAT-03594	d	Outer dia 90mm and Inner dia 76mm	1 RM	200
	MAT-03595	e	Outer dia 120mm and Inner dia 103.5mm	1 RM	314
	MAT-03596	f	Outer dia 160 mm and Inner dia 136 mm	1 RM	466
	MAT-03597	g	Outer dia 180 mm and Inner dia 152 mm	1 RM	613

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03598	h	Outer dia 200 mm and Inner dia 170 mm	1 RM	726
			SECTION - 5		
		5.1	FANS		
179	MAT-05508	ELEC-5.1.1	Supply of 48" (1200mm) Sweep 5 star rated BLDC (Brush less Direct Current) Ceiling Fan with double ball bearings, input voltage 230V AC converted to 24 V DC, power input not more than 30W, air delivery not less than 220 cubic meter/min and a minimum service value of 7.0, with remote and without Regulator. Makes: As per list of recommended brands.	1 No	3447
180	MAT-05509	ELEC-5.1.2	Supply of 56" (1400mm) Sweep 5 star rated BLDC (Brush less Direct Current) Ceiling Fan with double ball bearings, input voltage 230V AC converted to 24 V DC, power input not more than 32W, air delivery not less than 240 cubic meter/min and a minimum service value of 7.0, with remote and without Regulator. Makes: As per list of recommended brands.	1 No	4021
181	MAT-03599	ELEC-5.1.3	Supply of 48" (1200mm) Sweep star rated Ceiling Fan, with double ball bearings, air delivery more than 200 cubic meter/min, but without Regulator. Makes: As per list of recommended brands.	1 No	2405
182	MAT-03600	ELEC-5.1.4	Supply of 48" (1200mm) Sweep decorative Ceiling Fan, with double ball bearings with all accessories without Regulator. Makes: As per list of recommended brands.	1 No	2904
183	MAT-03602	ELEC-5.1.5	Supply of 56" (1400mm) Sweep Ceiling Fan, with double ball bearings, but without Regulator. Makes: As per list of recommended brands.	1 No	2887
184	MAT-03603	ELEC-5.1.6	Supply of 16" (400mm) Wall mounted Fan. Makes: As per list of recommended brands.	1 No	2766
185	MAT-03604	ELEC-5.1.7	Supply of 16" (400mm) Pedestal Fan. Makes: As per list of recommended brands.	1 No	3068
186	MAT-03605	ELEC-5.1.8	Supply of 18" (450mm) Wall mounting / Pedestal Air Circulators. Makes: As per list of recommended brands.	1 No	6950

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
187	MAT-03606	ELEC-5.1.9	Supply of 24" (600mm) Wall mounting / Pedestal Air Circulators. Makes: As per list of recommended brands.	1 No	8366
188	MAT-03607	ELEC-5.1.10	Supply of 12" (300mm) Cabin fan. Makes: As per list of recommended brands.	1 No	2044
189	MAT-03608	ELEC-5.1.11	Supply of 12" (300mm) Light duty exhaust fan with metallic blades and wire guard etc complete. Makes: As per list of recommended brands.	1 No	1744
190	MAT-03609	ELEC-5.1.12	Supply of 9" (225mm), Light duty exhaust fan with double ball bearing and wire guard etc complete. Makes: As per list of recommended brands.	1 No	1552
191	MAT-03610	ELEC-5.1.13	Supply of 12" (300mm) ISI, 900 RPM Heavy duty exhaust fan with metallic blades with mark. Makes: As per list of recommended brands.	1 No	3308
192	MAT-03611	ELEC-5.1.14	Supply of 15" (375mm) ISI, 900 RPM Heavy duty exhaust fan with metallic blades with ISI Mark. Makes: As per list of recommended brands.	1 No	3849
193	MAT-03612	ELEC-5.1.15	Supply of 18" (450mm) ISI, 900 RPM Heavy duty exhaust fan with metallic blades with ISI Mark. Makes: As per list of recommended brands.	1 No	4931
194		ELEC-5.1.16	Supply of 6" (150mm), Light duty exhaust fan with double ball bearing and wire guard etc complete. Makes: As per list of recommended brands.	1 No	1207
195		ELEC-5.1.17	Supply of 8" (200mm), Light duty exhaust fan with double ball bearing and wire guard etc complete. Makes: As per list of recommended brands.	1 No	1340
		ELEC-5.1.18	Supply of 48" (1200mm) Sweep 5 star rated BLDC (Brush less Direct Current) Ceiling Fan with double ball bearings, input voltage 230V AC converted to 24 V DC, power input not more than 30W, air delivery not less than 220 cubic meter/min and a minimum service value of 7.0, without Remote and without regulator.	1 No	3050

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: As per list of recommended brands.		
		5.2	WATER HEATERS (Conventional & Solar)		
196		ELEC-5.2.1	Supply, Transportation and fixing of storage / Pressure type Vertical / Horizontal 230/250V single phase 2000watts ISI mark 5 Star rated water heater with Glass/SS tank and ABS plastic body of capacity to withstand up to 6.5 bar of water pressure including all standard accessories and dead weight pressure reducing valve on outlet side, including cost of 2 Nos nylon / PVC / Metallic hose pipe, testing and all labour charges etc., complete. Makes: As per list of recommended brands.		
	MAT-03613	a	15 Ltrs	1 No	11600
	MAT-03614	b	25 Ltrs	1 No	13800
197		ELEC-5.2.2	Supply, Transportation, erection and Commissioning of MNRE approved and confirming to IS 12933 P-1,2,3&5..... Tube Collector type Solar Water heating System with temperature application of 60 degrees with Stain less steel - 304L grade inner tank with PUF Insulation and Aluminum Cladding for Outer Cover, suitable EPDM rubber pipe connection from Collector to Solar Tank with electrical Heating back up etc., with 3 years Guarantee for Solar system and additional 2 years warranty. Makes: As per list of recommended brands.		
	MAT-03615	a	250 LPD	1 No	55660
	MAT-03616	b	375LPD	1 No	77050
	MAT-03617	c	500 LPD	1 No	87400
	MAT-03618	d	1000 LPD	1 No	170200

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
198		ELEC-5.2.3	Supply, Transportation, erection and Commissioning of MNRE approved and confirming to IS 12933 P-1,2,3&5..... Flate plate Collector type Solar Water heating System with temperature application of 60 degrees with Stain less steel - 304L grade inner tank with PUF Insulation and Aluminum Cladding for Outer Cover, suitable EPDM rubber pipe connection from Collector to Solar Tank with electrical Heating back up etc., with 3 years Guarantee for Solar system and additional 2 years warranty. Makes: As per list of recommended brands.		
	MAT-03619	a	250 LPD	1 No	59800
	MAT-03620	b	375 LPD	1 No	82800
	MAT-03621	c	500 LPD	1 No	96025
	MAT-03622	d	1000 LPD	1 No	189750
			HEAT PUMP		
199		ELEC-5.2.4	Supply, Transportation and fixing of Energy Efficient Heat pump(Hybrid) water heater of Mono block storage / type Vertical / 230/250V single phase 50 Hz rated water heater with SS tank coated with Enamel and stain less body with IP X 4 water proof grade of capacity Mono Block unit to withstand up to 0.8 - 1.0 MPa bar of water pressure including 2 Kw Heating element and Auto Defrosting and with 50 MM puf insulation with all standard accessories and dead weight pressure reducing valve on out let side, including cost of CPVC Piping / Metallic hose pipe, testing and all labour charges etc., complete. Makes: As per list of recommended brands.		
	MAT-03623	a	200 Ltr	1 No	125580
	MAT-03624	b	300 Ltr	1 No	159390
200		ELEC-5.2.5	Supply, Transportation and fixing of Energy Efficient Heat pump(Hybrid) water heater of split type storage / type Vertical / 230/250V single phase 50 Hz rated water heater with SS tank coated with Enamel and preprinted steel body with IP X 4 water proof grade of capacity Mono Block unit to withstand up to 0.8 - 1.0 MPa bar of water pressure including 2 Kw Heating element and Auto Defrosting and with 50 MM Puf insulation with all standard accessories and dead weight pressure reducing valve on out let side, including cost of CPVC Piping / Metallic hose pipe, testing		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			and all labour charges etc., complete. Makes: As per list of recommended brands.		
	MAT-03625	a	400 Ltr	1 No	154675
	MAT-03626	b	500 Ltr	1 No	189336
		5.3	ACCESSORIES FOR WATER HEATERS		
201		ELEC-5.3.1	Supply and fixing of stem type ISI marked (IS 3017 / 85) snap action adjustable thermostat storage water heater including making connection testing etc. as required.		
	MAT-03627	a	11" stem thermostat	1 No	230
	MAT-03628	b	7" stem thermostat	1 No	206
202	MAT-03629	ELEC-5.3.2	Supply and fixing of stem type, ISI marked, push to reset type auto thermal cut off and rated at 20 A 250 V including testing etc. as required.	1 No	273
203		ELEC-5.3.3	Supply and fixing of ISI marked (IS:4159) marked copper sheathed, nickel plated, mineral filled heating element including making connection testing etc as required		
	MAT-03630	a	3.0 KW	1 No	787
	MAT-03631	b	2.0 KW	1 No	750
204		ELEC-5.3.4	Supply and fixing of twin ceramic cartridge, shock and hard waterproof heating element including making connection testing etc as required		
	MAT-03632	a	3.0 KW	1 No	908
	MAT-03633	b	2.0 KW	1 No	787
205		ELEC-5.3.5	Supply and fixing of base plate assembly with neoprene rubber gasket, inlet socket with inbuilt NRV/ PRV and drain out system and outlet socket pipe, fusible plug assembly, mounting hardware complete etc. as required.		
	MAT-03634	a	15 Ltr. To 50 Ltr. Capacity SWH	1 No	1694

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
206	MAT-03635	ELEC-5.3.5	Supply and fixing of heavy duty C.P. connection for storage water heater for inlet and outlet of length 300-600 mm including the cost of nuts, washers etc as required.	1 set	303
207	MAT-03636	ELEC-5.3.6	Charges for brass welding of inner copper tank for storage water heater including opening, refixing, testing etc. as required	job	484
208	MAT-03637	ELEC-5.3.7	Charges for descaling of storage water heater including required chemical, opening, refixing, testing as complete	job	363
209	MAT-03638	ELEC-5.3.8	Charges for Fixing of storage water heater including four nos. rag bolts of suitable size, supply & making heavy gauge inlet, outlet C.P. connection, testing, carrying from store to site, etc. as required	job	787
		5.4	PUMPSETS		
			SINGLE PHASE SUBMERSIBLE MOTOR PUMP SETS		
210		ELEC-5.4.1	Supply and Transportation of, 5star rated submersible motor pumpset, confirming to IS 8034 and motor confirming to IS 9283 with waterproof winding, pump shall be suitable for various delivery head and discharge with stainless steel shaft motor suitable for working on 240V $\pm$ 10%, single phase 50 Hz AC supply, etc complete for 4" Bore well. Makes: As per list of recommended brands as category I.		
	MAT-03639	a	0.75HP 8 Stage	1 No	18834
	MAT-03640	b	1.00HP 10 Stage	1 No	21562
	MAT-03641	c	1.00HP 15 Stage	1 No	22228
	MAT-03642	d	1.50HP 21 Stage	1 No	26953
	MAT-03643	e	2.00HP 25 Stage	1 No	32343
		f			

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
211		ELEC-5.4.2	Supply and Transportation of 5star rated submersible motor pumpset, confirming to IS 8034 and motor confirming to IS 9283 with water proof winding, pump shall be suitable for various delivery head and discharge with stainless steel shaft. Motor suitable for working on 240V $\pm$ 10% , Single Phase 50 Hz AC supply, etc complete for 4" Bore well. Makes: As per list of recommended brands as category II.		
	MAT-03644	a	0.75HP 8 Stage	1 No	16904
	MAT-03645	b	1.00HP 10 Stage	1 No	19300
	MAT-03646	c	1.00HP 15 Stage	1 No	19965
	MAT-03647	d	1.50HP 21 Stage	1 No	24224
	MAT-03648	e	2.00HP 25 Stage	1 No	29083
		f			
			THREE PHASE SUBMERSIBLE MOTOR PUMP SETS.		
212		ELEC-5.4.3	Supply and Transportation of 5star rated submersible motor pumpset, confirming to IS 8034 and motor confirming to IS 9283 with water proof winding, Pump shall be suitable for various delivery head and discharge with stainless steel shaft. Motor suitable for working on 415V $\pm$ 10% , Three Phase 50 Hz AC supply, etc complete for 4" Bore well. Makes: As per list of recommended brands as category I.		
	MAT-03649	a	3.00HP 15Stage	1 No	26221
	MAT-03650	b	4.00HP 20Stage	1 No	30613
	MAT-03651	c	5.00HP 25Stage	1 No	36203
213		ELEC-5.4.4	Supply and Transportation of 5star rated submersible motor pumpset, confirming to IS 8034 and motor confirming to IS 9283 with water proof winding, Pump shall be suitable for various delivery head and discharge with stainless steel shaft. Motor suitable for working on 415V $\pm$ 10%, Three Phase 50 Hz AC supply, etc complete for 4" Bore well. Makes: As per list of recommended brands as category II.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03652	a	3.00HP 15Stage	1 No	24624
	MAT-03653	b	4.00HP 20Stage	1 No	28750
	MAT-03654	c	5.00HP 25Stage	1 No	34074
214		ELEC-5.4.5	Supply and Transportation of,5star rated submersible motor pumpset, confirming to IS 8034 and motor confirming to IS 9283 with waterproof winding, Pump shall be suitable for various delivery head and discharge with stainless steel shaft. Motor suitable for working on 415V $\pm$ 10%, Three Phase 50 Hz AC supply etc complete for 6" Bore well. Makes: As per list of recommended brands as category I.		
	MAT-03655	a	3.00HP 5-10 Stage	1 No	39930
	MAT-03656	b	5.00HP, 5-10Stage	1 No	44922
	MAT-03657	c	5.00HP, 12-16 Stage	1 No	51244
	MAT-03658	d	7.50HP, 5-10 Stage	1 No	50445
	MAT-03659	e	7.50HP, 12-16 Stage	1 No	55902
	MAT-03660	f	7.50HP, 20-24 Stage	1 No	57233
	MAT-03661	g	10HP, 5-10 Stage	1 No	59230
	MAT-03662	h	10HP, 12-16 Stage	1 No	61226
	MAT-03663	i	10HP, 20-24 Stage	1 No	69212
	MAT-03664	j	12.5HP, 8-12 Stage	1 No	61226
	MAT-03665	k	12.5HP, 16-24 Stage	1 No	71874
	MAT-03666	l	15HP, 8-12 Stage	1 No	77065

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03667	m	15HP, 16-24 Stage	1 No	79594
	MAT-03668	n	20HP 10-20 Stage	1 No	92505
	MAT-03669	o	20HP 30-40 Stage	1 No	96498
	MAT-05510	p	25HP 20-25 Stage	1 No	105149
215		ELEC-5.4.6	Supply and Transportation of 5star rated submersible motor pumpset, confirming to IS 8034 and motor confirming to IS 9283 with water proof winding, Pump shall be suitable for various delivery head and discharge with stainless steel shaft. Motor suitable for working on 415V $\pm$ 10% , Three Phase 50 Hz AC supply, etc complete for 6" Bore well. Makes: As per list of recommended brands as category II.		
	MAT-03670	a	3.00HP 5-10 Stage	1 No	35937
	MAT-03671	b	5.00HP, 5-10Stage	1 No	40329
	MAT-03672	c	5.00HP, 12-16 Stage	1 No	46120
	MAT-03673	d	7.50HP, 5-10 Stage	1 No	45387
	MAT-03674	e	7.50HP, 12-16 Stage	1 No	50312
	MAT-03675	f	7.50HP, 20-24 Stage	1 No	51510
	MAT-03676	g	10HP, 5-10 Stage	1 No	53240
	MAT-03677	h	10HP, 12-16 Stage	1 No	55237
	MAT-03678	i	10HP, 20-24 Stage	1 No	62291
	MAT-03679	j	12.5HP, 8-12 Stage	1 No	55237
	MAT-03680	k	12.5HP, 16-24 Stage	1 No	64687

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03681	l	15HP, 8-12 Stage	1 No	69345
	MAT-03682	m	15HP, 16-24 Stage	1 No	71608
	MAT-03683	n	20HP 10-20 Stage	1 No	83188
	MAT-03684	o	20HP 30-40 Stage	1 No	86781
			SINGLE PHASE OPEN WELL SUBMERSIBLE MOTOR PUMP SETS		
216		ELEC-5.4.7	Supply and Transportation of Single phase open well submersible motor pump set confirms to IS 14220 : 1994. Makes: As per list of recommended brands as category I.		
	MAT-03685	a	1.00HP	1 No	16398
	MAT-03686	b	1.50HP	1 No	18448
	MAT-03687	c	3.00HP	1 No	25182
217		ELEC-5.4.8	Supply and Transportation of Single phase open well ISI submersible motor pumpset confirms to IS 14220 : 1994. Makes: As per list of recommended brands as category II.		
	MAT-03688	a	1.00HP	1 No	15374
	MAT-03689	b	1.50HP	1 No	17569
	MAT-03690	c	3.00HP	1 No	23938
			THREE PHASE OPEN WELL SUBMERSIBLE PUMP SETS		
218		ELEC-5.4.9	Supply and Transportation of Three phase open well ISI submersible motor pumpset confirms to IS 14220: 1994. . Makes: As per list of recommended brands as category I.		
	MAT-03691	a	3.00HP (65x50)	1 No	25182
	MAT-	b	5.00HP (75x65)	1 No	31479

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03692				
	MAT-03693	c	7.50HP (100x75)	1 No	37335
	MAT-03694	d	10.00HP (100x75)	1 No	47584
219		ELEC-5.4.10	Supply and Transportation of Three phase open well ISI submersible motor pumpset confirms to IS 14220 : 1994. Makes: As per list of recommended brands as category II. .		
	MAT-03695	a	3.00HP(65x50)	1 No	24158
	MAT-03696	b	5.00HP(75x65)	1 No	29575
	MAT-03697	c	7.50HP(100x75)	1 No	35138
	MAT-03698	d	10.00HP(100x75)	1 No	45387
			SINGLE PHASE MONO BLOCK MOTOR PUMP SETS.		
220		ELEC-5.4.11	Supply and Transportation of Single phase Mono block CI body motor pumpset confirms to IS 9079:2002 Makes: As per list of recommended brands as category I.		
	MAT-03699	a	0.5HP(25x25mm)	1 No	7321
	MAT-03700	b	1.0HP (25x25mm)	1 No	10469
	MAT-03701	c	1.5HP(32x25mm)	1 No	14056
221		ELEC-5.4.12	Supply and Transportation of Single phase Mono block CI body motor pumpset confirms to IS 9079:2002 Makes: As per list of recommended brands as category II.		
	MAT-03702	a	0.5HP(25x25mm)	1 No	6882
	MAT-03703	b	1.0HP (25x25mm)	1 No	9956

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03704	c	1.5HP(32x25mm)	1 No	13397
222		ELEC-5.4.13	Supply and Transportation of..... Three phase ISI self priming Mono block IP44 motor pumpset . Makes: As per list of recommended brands as category I.		
	MAT-03705	a	2.00HP(40x40mm)	1 No	20790
	MAT-03706	b	3.0HP (50x50mm)	1 No	28111
	MAT-03707	c	5.00HP(80x80mm)	1 No	33967
223		ELEC-5.4.14	Supply and Transportation of..... Three phase ISI self priming Mono block IP44 motor pumpset . Makes: As per list of recommended brands as category II.		
	MAT-03708	a	2.00HP(40x40mm)	1 No	19766
	MAT-03709	b	3.0HP (50x50mm)	1 No	26793
	MAT-03710	c	5.00HP(80x80mm)	1 No	32503
			CONTROL PANEL BOARD FOR MOTOR PUMPSETS		
224	MAT-03711	ELEC-5.4.15	Fabrication , transportation and supply of suitable size panel board for single phase submersible motor up to 1.5 HP consisting of relay, Contactor, starting and running capacitors, Voltmeter, Ammeter, indicator lamps, MCB , on/off switch including supply and fixing of DOL starter of complete., Makes: As per list of recommended brands.	1 No	5990
225	MAT-03712	ELEC-5.4.16	Fabrication , transportation and supply of suitable size panel board for single phase submersible motor 2 to 3HP consisting of relay, Contactor, starting and running capacitors, Voltmeter, Ammeter, indicator lamps, MCB , on/off switch including supply and fixing of DOL starter of complete., Makes: As per list of recommended brands.	1 No	7986

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
226		ELEC-5.4.17	Fabrication ,transportation and and supply of wall mounted control panel board of size 600x600x250mm made of 18 SWG CRCA sheet steel enclosure, 14 SWG mounting plate for cable entry fabricated , painted with two coats of Red oxide primer and two coats of Grey paint, lock and key arrangements two side louvres with weld mesh inside etc., complete consisting of the following equipment with all internal wiring using LAURITZ KNUDSEN (FORMERLY L&T) / Finolex copper FRLS cables of suitable size and capacity and cable clamp etc complete for 3 phase motor pump sets. Makes: As per list of recommended brands .		
			Voltmeter ; 0-500 V 96x96mm size.		
			0 to 20 Amps / 0 50 Amps Ammeter (96x96mm size)-1No.		
			Single phase preventor of suitable range - 1No.		
			32 A TP, 10KA MCB. - 1No		
			Indication lamps (R-Y-B) with switch control - 1set		
			Voltmeter & Ammeter selector switch - 2 Nos		
			Supply and fixing of ISI Mark suitable capacitor		
	MAT-03713	a	Upto 7.5 HP with DOL Starter of.	1 No	10648
	MAT-03714	b	above 7.5 HP to 12.5 HP with Star- Delta Starter	1 No	18634
	MAT-03715	c	From 15 HP up to 20 HP with Automatic Star Delta Starter	1 No	24624
227		ELEC-5.4.18	Supply & Fixing of D.O.L Starter 250V, Single phase, 50Hz. With SS enclosure comprising of contactor with bi-metalic relay with necessary push buttons, etc., complete suitable for..... Makes: As per list of recommended brands.		
	MAT-03716	a	up to 3 HP	1 No	1392
228		ELEC-5.4.19	Supply & Fixing of D.O.L Starter 415V, 3 phase, 50Hz..enclosed with no volt coil and overload protection with necessary materials, etc., complete suitable for..... Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03717	a	up to 3 HP	1 No	2489
	MAT-03718	b	5 to 7.5 HP	1 No	2782
	MAT-03719	c	10 HP	1 No	3075
229		ELEC-5.4.20	Supply & Fixing of Star-Delta Starter 415V, 3 phase, 50Hz.. enclosed with no volt coil, overload protection and single phase preventor , etc., complete suitable for Makes: As per list of recommended brands.		
	MAT-03720	a	12.50 to 15HP.	1 No	9051
	MAT-03721	b	25HP to 30HP	1 No	14934
			UPVC PIPES AND FITTINGS		
230		ELEC-5.4.21	Supply and delivery of for submersible motors with both ends square threaded, with rubber 'O' rings with smooth inner surface which can take the minimum load of 2100 to 4000 Kgs weights. Makes: As per list of recommended brands.		
	MAT-03722	a	42 / 32mm dia UPVC raising column pipe, with standing upto 20 Kgs / CM2 upto 200 Mts	1RM	157
	MAT-03723	b	48 / 40mm UPVC pipe with standing upto 20 Kgs / CM2 upto 200 Mts	1RM	194
	MAT-03724	c	60/50 mm UPVC pipe with standing upto 20 Kgs / CM2 upto 200 Mts	1RM	278
	MAT-03725	d	75/65 mm UPVC pipe with standing upto 20 Kgs / CM2 upto 200 Mts	1RM	375
	MAT-03726	e	88/80 mm UPVC pipe with standing upto 20 Kgs / CM2 upto 200 Mts	1RM	539
231	MAT-03727	ELEC-5.4.22	Supply and delivery of heavy duty couplings 42/32 mm UPVC pipe (27 Kgs / CM 2) capable of with standing up to 27 Kgs / CM2 above 200 mts and upto 300 mts	1NO	48
232	MAT-03728	ELEC-5.4.23	Supply and delivery of heavy duty couplings 48/40 mm UPVC pipe (27 Kgs / CM 2) capable of with standing up to 27 Kgs / CM2 above 200 mts and upto 300 mts	1NO	67

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
233	MAT-03729	ELEC-5.4.24	Supply and delivery of heavy duty couplings 60/50 mm UPVC pipe (27 Kgs / CM 2) capable of with standing up to 27 Kgs / CM2 above 200 mts and upto 300 mts	1NO	73
234	MAT-03730	ELEC-5.4.25	Supply and delivery off heavy duty couplings 75/65 mm UPVC pipe (27 Kgs / CM 2) capable of with standing up to 27 Kgs / CM2 above 200 mts and upto 300 mts	1NO	85
235	MAT-03731	ELEC-5.4.26	Supply and delivery of heavy duty couplings 88/80 mm UPVC pipe (27 Kgs / CM 2) capable of with standing up to 27 Kgs / CM2 above 200 mts and upto 300 mts	1NO	97
236		ELEC-5.4.27	Supply and Delivery of CI Adopter Assembly Makes: As per list of recommended brands.		
	MAT-03732	a	1/2" (48/40mm)	1NO	696
	MAT-03733	b	2" (60/50mm)	1NO	920
	MAT-03734	c	2 1/2" (75/65 mm)	1NO	1186
237		ELEC-5.4.28	Supply and Delivery of pump guard assembly with 2Nos SS Powder coated flange and 2Nos SS Rods with nut and colter pin. Makes: As per list of recommended brands.		
	MAT-03735	a	1 1/2" (48/40mm)	1NO	436
	MAT-03736	b	2" (60/50mm)	1NO	484
	MAT-03737	c	2 1/2" (75/65 mm)	1NO	666
	MAT-03738	d	3"(88/80 mm)	1NO	968
		5.5	AIR CONDITIONERS		
	MAT-03743	5.5.1 a	Deleted		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03744	5.5.1 b	Deleted		
	MAT-03747	5.5.1 c	Deleted		
	MAT-03748	5.5.1 d	Deleted		
			Inverter Split AC Units (Cooling Only)		
238		ELEC-5.5.1 A	Supply of INVERTER Model Cool type split AC unit with high wall mounted Single Split indoor unit and outdoor condensing unit Hermetically sealed compressor suitable for operation on 230V, 50Hz, 1Phase AC supply capable of performing Heat cool dehumidifying air circulating and filtering with cooling and condensing units with 3 mts of copper piping, insulation kit and 4 mts of 4 core copper flexible chord with cordless remote control etc., dual barrier coating in order to protect coil form oxidation with copper condenser.		
			1.5TR Split ACs		
		a	1.5 TR, 3 Star capable of delivering 18000 BTU/hr and above with operating on refrigerant R-32/ R-410A. Makes: As per list of recommended brands as category I.	1 No	53734
		b	1.5 TR, 3 Star capable of delivering 18000 BTU / hr and above with operating on refrigerant R-32 / R-410A. Makes: As per list of recommended brands as category II.	1 No	40805
			2.0 TR Split ACs		
		c	1.8/1.9/2.0TR, 3 Star capable of delivering not less than 21600 BTU/hr and above with operating on refrigerant R-410A / R-32 Makes: As per list of recommended brands as category I.	1 No	65148
		d	1.8/1.9/2.0TR, 3 Star capable of delivering not less than 21600 BTU/hr and above with operating on refrigerant R-410A / R-32 Makes: As per list of recommended brands as	1 No	53189

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			category II.		
239		ELEC-5.5.2	Supply of INVERTER Model Cool type split AC unit with high wall mounted Single Split indoor unit and outdoor condensing unit Hermetically sealed compressor suitable for operation on 230V, 50Hz, 1Phase AC supply capable of performing Heat cool dehumidifying air circulating and filtering with cooling and condensing units with 3 mts of copper piping, insulation kit and 4 mts of 4 core copper flexible chord with cordless remote control etc., dual barrier coating in order to protect coil form oxidation with copper condenser.		
			0.8/ 1.0TR Split ACs		
	MAT-05511	a	0.8 TR, 5 Star capable of delivering 9600 BTU/hr and above with operating on refrigerant R-32/ R-410A. Makes: As per list of recommended brands as category I.		43643
	MAT-05512	b	0.8 TR, 5 Star capable of delivering 9600 BTU/hr and above with operating on refrigerant R-32/ R-410A. Makes: As per list of recommended brands as category II.		35452
	MAT-05513	c	1.0 TR, 5 Star capable of delivering 12000 BTU/hr and above with operating on refrigerant R-32/ R-410A. Makes: As per list of recommended brands as category I.		48703
	MAT-05514	d	1.0 TR 5 Star capable of delivering 12000 BTU/hr and above with operating on refrigerant R-32/ R-410A. Makes: As per list of recommended brands as category II.		40259
			1.5, 1.8 & 2.0TR Split ACs		
	MAT-03753	e	1.5 TR, 5 star capable of delivering 18000 BTU/hr and above with operating on refrigerant R-32/ R-410A, COP not less than 4.5. Makes: As per list of recommended brands as category I.	1 No	64421
	MAT-03754	f	1.5 TR, 5 star capable of delivering 18000 BTU/hr and above with operating on refrigerant R-32/ R-410A, COP not less than 4.5. Makes: As per list of recommended brands as category II.	1 No	50294

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-05515	g	1.8/1.9/2.0TR, 5star capable of delivering not less than 21600 BTU/hr and above with operating on refrigerant R-410A / R-32 Makes: As per list of recommended brands as category I.	1 No	75710
	MAT-05516	h	1.8/1.9/2.0TR, 5 Star capable of delivering not less than 21600 BTU/hr and above with operating on refrigerant R-410A / R-32 Makes: As per list of recommended brands as category II.	1 No	61650
	MAT-03757	i	2.2 TR, 5 star capable of delivering 26400 BTU/hr and above with operating on refrigerant R-410A / R-32 Makes: As per list of recommended brands as category I.	1 No	84123
	MAT-03758	j	Deleted	1 No	
			INVERTER CASSETTE TYPE AC UNITS		
240		ELEC-5.5.35	Supply of inverter Cassette type AC unit with ceiling mounted indoor unit and outdoor condensing unit Hermetically sealed compressor suitable for operation on AC supply capable of performing cooling dehumidifying air circulating and filtering with cooling and condensing units etc. complete with Wireless remote controller, without refrigerant piping and cable with copper condenser.		
	MAT-03759	a	1.5 TR, 4-star Single Phase capable of delivering 18000 BTU / hr and above with operating on refrigerant R-32 / R-410A. Makes: As per list of recommended brands as category I.	1 No	92345
	MAT-03760	b	2.0TR, 4-star Single Phase capable of delivering 24000 BTU / hr and above with operating on refrigerant R-32 / R-410A, . Makes: As per list of recommended brands as category I.	1 No	103604
	MAT-03761	c	2.0TR 4-star Single Phase capable of delivering 24000 BTU / hr and above with operating on refrigerant R-32 / R-410A. Makes: As per list of recommended brands as category II.	1 No	94875

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03762	d	3.5 TR 4-star Three Phase capable of delivering 42000 BTU / hr and above with operating on refrigerant R-32 / R-410A. Makes: As per list of recommended brands as category I.	1 No	174570
	MAT-03763	e	3.5 TR 4-star Three Phase capable of delivering 42000 BTU / hr and above with operating on refrigerant R-32 / R-410A. Makes: As per list of recommended brands as category II.	1 No	171408
	MAT-03764	f	4.0 TR 4-star Three Phase capable of delivering 48000 BTU / hr and above with operating on refrigerant R-32 / R-410A. Makes: As per list of recommended brands as category I.	1 No	188612
	MAT-03765	g	4.0 TR 4-star Three Phase capable of delivering 48000 BTU / hr and above with operating on refrigerant R-32 / R-410A. Makes: As per list of recommended brands as category II.	1 No	163185
			TOWER MODEL (Vertical) TYPE AC UNITS		
241		ELEC-5.5.36	Supply of Slim line / Tower Model/Verticool type split AC unit with indoor unit and floor mounted outdoor condensing unit with 3.5 mtr of copper piping, insulation kit and 4 mtr of 4 core copper flexible card with refrigerant 410A/R32, Hermetically sealed Scroll compressor suitable for operation on AC supply capable of performing cooling dehumidifying air circulating and filtering with cooling and condensing units etc complete with cordless remote control		
	MAT-03766	a	3.0/ 3.3TR Three Phase capable of delivering 39600 BTU/hr and above with operating on refrigerant R-32/R-410. Makes: As per list of recommended brands.	1 No	120871
	MAT-03767	b	3.8 /4.0TR Three Phase capable of delivering 45600 BTU/hr and above with operating on refrigerant R-32/R-410. Makes: As per list of recommended brands.	1 No	128177
	MAT-03768	c	4.5/ 4.6TR Three Phase capable of delivering 55200 BTU/hr and above with operating on refrigerant R-32/R-410.	1 No	139466

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: As per list of recommended brands.		
			HVAC SYSTEMS(VRV/VRF)		
242		ELEC-5.6.1	Supply of Air cooled VRV / VRF Air Conditioning system of having high COP complete with indoor and outdoor units duly charged with refrigerant R-410A and oil (first charge) suitable for cooling with individual controller, (suitable for 415 +/- 10% for outdoor and 230 +/- 5% for indoor units) and complete with all accessories, fittings etc. The units shall be BMS Compatible. Outdoor Units shall be fully inverter system complete with 100% scroll/rotary compressor and drive arrangement, initial charge of refrigerant (R-410A),refrigerant piping, drier, sight glass, dual pressure cutout all housed and supported properly in cabinet, air cooled condenser & its controller for following capacities. The VRV system shall be cooling only system. Makes: As per list of recommended brands as category I.		
			Type of Compressor: Hermetic sealed Inverter Scroll/Twin Rotary		
			ODU should deliver the required capacity at the ambient conditions of the place as per ISHRAE Standards.		
			The System should be highly energy efficient, and COP shall not be less than 3.7. The outdoor units shall be suitable for operation between 5 and 53 deg C in cooling mode.		
			VRV/VRF OUTDOOR UNITS		
	MAT-03769	a	6 HP	1 No	200100
	MAT-03770	b	8 HP	1 No	218040
	MAT-03771	c	10 HP	1 No	270480
	MAT-03772	d	12 HP	1 No	303600
	MAT-03773	e	14 HP	1 No	343620
	MAT-03774	f	16 HP	1 No	391920
	MAT-03775	g	18 HP	1 No	430560

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03776	h	20 HP	1 No	473340
243		ELEC-5.6.2	Supply of Air cooled VRV / VRF Air Conditioning system of having high COP complete with indoor and outdoor units duly charged with refrigerant R-410A and oil (first charge) suitable for cooling with individual controller, (suitable for 415 +/- 10% for outdoor and 230 +/- 5% for indoor units) and complete with all accessories, fittings etc. The units shall be BMS Compatible. Outdoor Units shall be fully inverter system complete with 100% scroll/rotary compressor and drive arrangement, initial charge of refrigerant (R-410A),refrigerant piping, drier, sight glass, dual pressure cutout all housed and supported properly in cabinet, air cooled condenser & its controller for following capacities. The VRV system shall be cooling only system. Makes: As per list of recommended brands as category II.		
			Type of Compressor: Hermetic sealed Inverter Scroll/Twin Rotary		
			ODU should deliver the required capacity at the ambient conditions of the place as per ISHRAE Standards.		
			The System should be highly energy efficient, and COP shall not be less than 3.7. The outdoor units shall be suitable for operation between 5 and 53 deg C in cooling mode.		
	MAT-05517	a	6 HP	1 No	184230
	MAT-05518	b	8 HP	1 No	200100
	MAT-05519	c	10 HP	1 No	248814
	MAT-05520	d	12 HP	1 No	279312
	MAT-05521	e	14 HP	1 No	316020
	MAT-05522	f	16 HP	1 No	360180
	MAT-05523	g	18 HP	1 No	396060

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-05524	h	20 HP	1 No	434700
244	MAT-03777	ELEC-5.6.3	Supply and Installation of Ref Nets for Double ODU connections	1 No	6072
245	MAT-03778	ELEC-5.6.4	Supply and Installation of Ref Nets for Triple ODU connections	1 No	11638
246	MAT-03779	ELEC-5.6.5	Supply and Installation of Multi Connection Joint / Ref Nets for IDUs	1 No	5313
			VRV/VRF INDOOR UNITS		
247		ELEC-5.6.6	Supply of Indoor Units consisting of 2/3/4 row deep DX coil, filter, blower section and drive arrangement, initial charge of refrigerant & oil, integral refrigerant piping, electronic expansion valve, electrical panel with controls and duly wired, thermostatic control. Makes: As per list of recommended brands as category I.		
			Type Of Units : Hi Wall type units		
	MAT-03780	a	1.0 TR	1 No	34788
	MAT-03781	b	1.6 TR	1 No	37950
	MAT-03782	c	2.0 TR	1 No	39215
248		ELEC-5.6.7	Supply of Indoor Units consisting of 2/3/4 row deep DX coil, filter, blower section and drive arrangement, initial charge of refrigerant & oil, integral refrigerant piping, electronic expansion valve, electrical panel with controls and duly wired, thermostatic control. Makes: As per list of recommended brands as category II.		
			Type Of Units : Hi Wall type units	1 No	
	MAT-05525	a	1.0 TR	1 No	34914
	MAT-05526	b	1.6 TR	1 No	36053
	MAT-05527	c	2.0 TR	1 No	36053

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
249		ELEC-5.6.8	Supply of Indoor Units consisting of 2/3/4 row deep DX coil, filter, blower section and drive arrangement, initial charge of refrigerant & oil, integral refrigerant piping, electronic expansion valve, electrical panel with controls and duly wired, thermostatic control. Makes: As per list of recommended brands as category I.		
			Type Of Units : Round flow/4 way Cassette units		
	MAT-03783	a	1.0 TR	1 No	46299
	MAT-03784	b	1.5/1.6 TR	1 No	51865
	MAT-03785	c	2.0 TR	1 No	53130
	MAT-03786	d	2.6 TR	1 No	58190
	MAT-03787	e	3.2 TR	1 No	59455
	MAT-03788	f	4.0 TR	1 No	60720
	MAT-03789	g	4.5 TR	1 No	63630
250		ELEC-5.6.9	Supply of Indoor Units consisting of 2/3/4 row deep DX coil, filter, blower section and drive arrangement, initial charge of refrigerant & oil, integral refrigerant piping, electronic expansion valve, electrical panel with controls and duly wired, thermostatic control. Makes: As per list of recommended brands as category II.		
			Type Of Units : Round flow/4 way Cassette units		
	MAT-05528	a	1.0 TR	1 No	42504
	MAT-05529	b	1.5/1.6 TR	1 No	47691
	MAT-05530	c	2.0 TR	1 No	48829
	MAT-05531	d	2.6 TR	1 No	53510

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-05532	e	3.2 TR	1 No	54648
	MAT-05533	f	4.0 TR	1 No	55660
	MAT-05534	g	4.5 TR	1 No	58443
251		ELEC-5.6.10	Supply of Indoor Units consisting of 2/3/4 row deep DX coil, filter, blower section and drive arrangement, initial charge of refrigerant & oil, integral refrigerant piping, electronic expansion valve, electrical panel with controls and duly wired, thermostatic control. Makes: As per list of recommended brands as category I.		
			Type Of Units : High Static Duct Units		
	MAT-03790	a	3.2 TR	1 No	63630
	MAT-03791	b	4.0 TR	1 No	66792
	MAT-03792	c	4.5 TR	1 No	79063
	MAT-03793	d	5.5 TR	1 No	106513
	MAT-03794	e	6.3 TR	1 No	112206
	MAT-03795	f	8.0 TR	1 No	118278
252		ELEC-5.6.11	Supply of Indoor Units consisting of 2/3/4 row deep DX coil, filter, blower section and drive arrangement, initial charge of refrigerant & oil, integral refrigerant piping, electronic expansion valve, electrical panel with controls and duly wired, thermostatic control. Makes: As per list of recommended brands as category II.		
			Type Of Units : High Static Duct Units		
	MAT-05535	a	3.2 TR	1 No	58190
	MAT-05536	b	4.0 TR	1 No	60720
	MAT-05537	c	4.5 TR	1 No	72738

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-05538	d	5.5 TR	1 No	97405
	MAT-05539	e	6.3 TR	1 No	102465
	MAT-05540	f	8.0 TR	1 No	108790
253	MAT-03796	ELEC-5.6.12	Supply, Installation, Testing & Commissioning Simple wireless remote controller to control the IDUs with Machine coding, ON-OFF & Temp. setting of individual IDU and group of IDU.		1771
254		ELEC-5.6.13	Supply of Indoor Units consisting of 3/4 row deep DX coil, drain pan, filter, blower section and drive arrangement, initial charge of refrigerant & oil, integral refrigerant piping, electronic expansion valve, electrical panel with controls, duly wired, thermostatic control corded/cordless remote controller supports for indoor units etc. Makes: As per list of recommended brands as category I.		
			Type of Units: Ductable TFA Units		
	MAT-03797	a	4TR	1 No	104553
	MAT-03798	b	6TR	1 No	125994
	MAT-03799	c	8TR	1 No	132825
255		ELEC-5.6.14	Supply of Indoor Units consisting of 3/4 row deep DX coil, drain pan, filter, blower section and drive arrangement, initial charge of refrigerant & oil, integral refrigerant piping, electronic expansion valve, electrical panel with controls, duly wired, thermostatic control corded/cordless remote controller supports for indoor units etc. Makes: As per list of recommended brands as category II.		
			Type of Units: Ductable TFA Units		
	MAT-05541	a	4TR	1 No	96140
	MAT-05542	b	6TR	1 No	115115
	MAT-05543	c	8TR	1 No	122073

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			HVAC-LOW SIDE WORKS		
256		ELEC-5.6.15	Lifting, shifting, positioning, Installation and testing of the ODUs including all accessories with Vibration Isolators for ODUs etc., complete		
	MAT-03800	A	6 to 8 HP	1 No	8694
	MAT-03801	B	10 to 12 HP	1 No	12420
	MAT-03802	c	14 to 20 HP	1 No	14904
257		ELEC-5.6.16	Lifting Shifting, Positioning, Installation Testing and commissioning of the following indoor units with including all required accessories etc complete.,		
			Type Of Units : Hi Wall Units	1 No	
	MAT-03803	a	1.0 TR to 2.0 TR	1 No	1490
258		ELEC-5.6.17	Lifting Shifting, Positioning, Installation Testing and commissioning of the following indoor units with including all required accessories etc complete.,		
			Type Of Units : Round Flow /4 way Cassette units		
	MAT-03804	a	1.0 TR to 2.0 TR	1 No	1863
	MAT-03805	b	2.6 TR to 4.5 TR	1 No	3105
259		ELEC-5.6.18	Lifting Shifting, Positioning, Installation Testing and commissioning of the following indoor units with including all required accessories etc complete.,		
			Type Of Units : High Static Duct Units		
	MAT-03806	a	3.2 TR to 4.5 TR	1 No	3726
	MAT-03807	b	5.5 TR to 8.0 TR	1 No	5589

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
260		ELEC-5.6.19	Installation, testing & commissioning of Indoor Units consisting of 2/3/4 row deep DX coil, filter, blower section and drive arrangement, initial charge of refrigerant & oil, integral refrigerant piping, electronic expansion valve, electrical panel with controls duly wired, thermostatic control corded/cordless remote controller supports for indoor units etc.		
			Type of Units: Ductable TFA Units		
	MAT-03808	a	4 TR to 8 TR	1 No	5693
			Refrigerant Piping		
261		ELEC-5.6.20	Supply, installation and testing of Refrigerant Piping consisting of copper tubes of wall thickness 20G/22G inclusive of Suction Gas Piping & Fittings/Liquid Line Piping & Fittings , with class "O" nitrile rubber Insulation with finish as required. The piping to be mounted & supported properly with suitable size of clamp, M.S. hanger, tray etc., as required at site Makes: As per list of recommended brands.		
			The insulation shall be closed cell/cross linked elastomeric Nitrile rubber of thickness 13/19 mm. The insulation thickness upto 19.1 mm dia pipe shall be 13 mm and above 19.1 mm dia, the insulation thickness shall be 19 mm.		
			Testing of refrigerant piping and procedure shall be done as per Manufacturer's recommendations		
	MAT-03809	a	34.9 mm dia	Rmt	2020
	MAT-03810	b	28.6 mm dia	Rmt	1845
	MAT-03811	c	22.2 mm dia	Rmt	1668
	MAT-03812	d	19.1 mm dia	Rmt	1494
	MAT-03813	e	15.9 mm dia	Rmt	1318
	MAT-03814	f	12.7 mm dia	Rmt	1142
	MAT-03815	g	9.5 mm dia	Rmt	843

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03816	h	6.4 mm dia	Rmt	738
262		ELEC-5.6.21	Supply, installation, and testing of UPVC Drain Piping with 6mm Nitrile Rubber class "O" Insulation covered with interwoven glass cloth protection. Necessary pipe fittings (including enlarger, bends, T-Joints etc) has to be considered to connect the UPVC drain pipe to cast iron floor trap.		
	MAT-03817	a	25 mm dia	Rmt	188
	MAT-03818	b	32 mm dia	Rmt	224
	MAT-03819	c	40mm dia	Rmt	274
	MAT-03820	d	50 mm dia	Rmt	324
			Supply of PVC insulated 2 core 1.5 Sq mm sheathed flexible copper cable for voltage up to 1100V as per IS 694/1990. (Covered in Section -1)	Rmt	
263	MAT-03821	ELEC-5.6.22	Supply and transportation of R 410A Gas for the system.	kg	1309
264	MAT-03822	ELEC-5.6.23	Providing Pressure testing of entire system with Nitrogen and vacuuming nitrogen for all indoor and outdoor units. The pressure testing shall be done as per OEM recommendation.	HP	1582
265	MAT-03823	ELEC-5.6.24	Supply, installation, testing & commissioning of stand-alone, intelligent Touch controller with Display for controlling the indoor & outdoor units from a Remote place for all the circuits.	No	93610
266		ELEC-5.6.25	Supply, installation, testing& commissioning of GSS Ducting with required angle flanges & installation materials such as heavy duty supports by anchor fasteners etc as required asper IS 655 /SMACNA Standards. Makes: As per list of recommended brands.		
	MAT-03824	a	24 G	sqm	1044
	MAT-03825	b	22 G	sqm	1170

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03826	c	20 G	sqm	1392
	MAT-03827	d	18 G	sqm	1518
			Thermal Insulation		
267	MAT-03828	ELEC-5.6.26	Supply & Fixing of Duct Thermal Insulation applied outside of the duct work with All. backed Closed cell nitrile/ Cross linked foam duly fixed with adhesive and tapes. Makes: As per list of recommended brands.		
			13 mm Thick	sqm	734
			Acoustic Insulation		
268		ELEC-5.6.27	Supply & Fixing of Duct Acoustic Insulation applied inside of the duct work with All. backed Open cell nitrile duly fixed with adhesive and tapes Makes: As per list of recommended brands.		
	MAT-03829	a	10/15 mm Thick	sqm	1139
269	MAT-03830	ELEC-5.6.28	Supply, Installation, Testing and commissioning of extruded Aluminum powder coated grills/ diffusers for supply with removable core type with collar damper	sqm	10753
270	MAT-03831	ELEC-5.6.29	Supply, Installation, Testing and commissioning of extruded Aluminum powder coated grills/ diffusers for return with removable core type without collar damper	sqm	7843
271	MAT-03832	ELEC-5.6.30	Supply, Erection and Testing of GI Opposed blade Volume control dampers made out of 18G frame and 20G blades	sqm	6831
272	MAT-03833	ELEC-5.6.31	Supply, Erection of Fresh air louver with extruded aluminum grill with SS wire mesh and GI volume control damper with 20 micron filters	sqm	5440
273	MAT-03834	ELEC-5.6.32	Supply and Installation of Underdeck Insulation with 50 mm thick EPS, 48 Kg/Cum density, factory laminated faced aluminum foil covered with GI cross wiring.	sqm	823
274	MAT-03835	ELEC-5.6.33	Supply and Installation of GI Fusible link Fire dampers 500 mm long with sleeve as per UL 555 Standard, Minimum width of damper shall be 225	sqm	8223

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			mm.		
275	MAT-03836	ELEC-5.6.34	Supply and Installation of GI backdraft dampers as per UL 555 Standard,	sqm	6831
276	MAT-03837	ELEC-5.6.35	Supply, installation and testing of Canvas connection for the Treated Fresh Air units to the duct	each	2783
277		ELEC-5.6.36	Supply, erection, testing and commissioning of Fresh air intake GI louvers with bird screen as per standard specifications.	ONE Sqmtr	5500
278		ELEC-5.6.37	Supply, Installation, Testing and commissioning of extruded Aluminum powder coated grills/ diffusers for supply air with removable core type with collar damper	ONE Sqmtr	9657
279		ELEC-5.6.38	Supply, Installation, Testing and commissioning of extruded Aluminum powder coated grills/ diffusers for return air with removable core type without collar damper.	ONE Sq mtr	7044
		5.7	EVAPORATIVE AIR-COOLING SYSTEM		
280	MAT-03838	ELEC-5.7.1	Supply of single-phase evaporative air-cooling unit with a capacity of 9000 CFM consisting cabinet and water tank made of polypropylene material, blower water pump of 40W, single phase 1.20 KW motor axial type fan with variable speed, 20 micron filtration, noise level less than 78 dBA with auto cleaning, humidity control and water lack protection etc., complete. Makes: As per list of recommended brands.	1 No	132825
281	MAT-03839	ELEC-5.7.2	Supply of Three phase evaporative air-cooling unit with a capacity of 12000 - 15000 CFM consisting of cabinet and water tank made of polypropylene material, blower water pump of 40W, Three phase 3.0 KW motor axial type fan with 2 speed, 20 micron filtration, noise level less than 78 dBA with auto cleaning and water lack protection etc complete. Makes: As per list of recommended brands.	1 No	227700
282	MAT-03840	ELEC-5.7.3	Supply and fixing of 13mm thick Nitrile insulation for outdoor unit.	1 sft	69

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
283	MAT-03841	ELEC-5.7.4	Supply and fixing of 50mm thick glass wool of 24 kg density with aluminum foil insulation for indoor duct.	1 sft	74
284	MAT-03842	ELEC-5.7.5	Supply and fixing of angular iron frame with 2 coats of zinc chromate red oxide for installation of air-cooling unit	1 No	6325
285	MAT-03843	ELEC-5.7.6	Installation and commissioning charges for air cooling unit	1 No	4554
		5.8	STABILIZERS		
286		ELEC-5.8.1	Supply of 1-phase, automatic Electronic Voltage Stabilizer. Makes: As per list of recommended brands as category I.		
	MAT-03844	a	0.5 KVA	1 No	941
	MAT-03845	b	1.0 KVA	1 No	1663
	MAT-03846	c	3.0 KVA	1 No	2294
	MAT-03847	d	4.0 KVA	1 No	2787
	MAT-03848	e	5.0 KVA	1 No	3408
287		ELEC-5.8.2	Supply of 1-phase automatic Electronic Voltage Stabilizer. Makes: As per list of recommended brands as category II.		
	MAT-03849	a	0.5 KVA	1 No	774
	MAT-03850	b	1.0 KVA	1 No	1492
	MAT-03851	c	3.0 KVA	1 No	1950
	MAT-03852	d	4.0 KVA	1 No	2581
	MAT-03853	e	5.0 KVA	1 No	3201
		5.9	REPAIRING OF FANS, COOLERS, PUMPS, MOTORS, FRIDGES AND AIRCONDITIONERS		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
288		ELEC-5.9.1	Rewinding of ceiling fan motor (starting and running winding) including all necessary material. The motor is to be wound taking no. of coils, turns and pitch as it was originally wound with required size super enameled wire with 'E' class insulation material and making connections etc. as required. (New model ceiling fan)		
	MAT-03854	a	900/1200 mm sweep	1 No	583
	MAT-03855	b	1400 mm sweep	1 No	701
289	MAT-03856	ELEC-5.9.2	Charges for oiling, greasing, overhauling of ceiling fan, table fan, pedestal fan irrespective to the size of fan including removing, refixing of fan from site and testing etc. as required	1 No	190
290	MAT-03857	ELEC-5.9.3	Providing and Replacement of ball bearing of ceiling/ exhaust fan as required. (NBC/ SKF)	1 No	222
291	MAT-03858	ELEC-5.9.4	Providing and Replacement of Gun metal bush of ceiling/ exhaust/cooler fan/ as required	1 No	190
292	MAT-03859	ELEC-5.9.5	Servicing and overhauling of 20" sweep desert cooler including oiling, greasing, painting of tank from inside with rubber paint after properly dismantling each assembly and refixing the same as required.	1 No	316
293	MAT-03860	ELEC-5.9.6	Painting of desert cooler with two coats of rubber paint inside of water tank and two coat of synthetic enameled paint on both side of cooler body, fan body, grills etc. After cleaning with sandpaper, complete in all respect as required	1 No	569
294	MAT-03861	ELEC-5.9.7	Replacement of cooler pads (heavy) set of 3 no. of size 25" x 27"	1 No	190
295	MAT-03862	ELEC-5.9.8	Supply and fixing of Brass float valve of weighing approx. 250 gm, 8" long rod, PVC ball of 4" dia. For desert cooler as required.	1 No	253
296	MAT-03863	ELEC-5.9.9	Supply and fixing of adjustable M.S. grill 20/22 gauge of size approx. 24" x 26" including painting etc. as required	1 No	455
297	MAT-03864	ELEC-5.9.10	Spray painting of ceiling fan of size 900/1200/ 1400 mm with two coats of white/ brown enameled paint after cleaning with sandpaper. Filling etc. as required.	1 No	222

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
298		ELEC-5.9.11	Rewinding of Heavy-duty Exhaust fan motor including all necessary material, The motor is to be wound taking no. of coils, turns and pitch as it was originally wound with required size super enameled wire with 'E' class insulation material and making connections etc. as required.		
	MAT-03865	a	300/ 380 mm sweep	1 No	791
	MAT-03866	b	450 mm sweep	1 No	935
	MAT-03867	c	600 mm sweep	1 No	1581
299	MAT-03868	ELEC-5.9.12	Rewinding of 400 mm table fan/pedestal fan motor including all necessary material, the motor is to be wound taking no. of coils, turns and pitch as it was originally wound with required size super enameled wire with 'E' class insulation material and making connections etc. as required.	1 No	504
300		ELEC-5.9.13	Rewinding of single-phase motor of 1400 RPM including all necessary material and of the same characteristics as original with required size of super enameled wire 'E' class insulation material and testing etc. as required.	1 No	
	MAT-03869	a	0.5 H.P. To 1.00 H.P.	1 No	1050
	MAT-03870	b	2.0 H.P	1 No	1725
301		ELEC-5.9.14	Rewinding of three phase motor of 1400 to 2800 RPM including all necessary material and of the same characteristics as original with required size of super enameled wire 'E' class insulation material and testing etc. as required.		
	MAT-03871	a	3.0 H.P.	1 No	2550
	MAT-03872	b	5.0 H.P.	1 No	3600
	MAT-03873	c	7.5 H.P.	1 No	3900
	MAT-	d	10.0 H.P	1 No	5250

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	03874				
	MAT-03875	e	12.5 H.P	1 No	5550
	MAT-03876	f	15.0 H.P	1 No	6750
302		ELEC-5.9.15	Supply and charging of fresh refrigerant and testing of performance of air conditioner/ fridge/ water cooler of following capacity including capillary and strainer/ filter.		
	MAT-03877	a	1.0 TR Window/ Split A.C	1 No	2404
	MAT-03878	b	1.5 TR Window/ Split A.C	1 No	2657
	MAT-03879	c	2.0 TR Window/ Split A.C	1 No	3163
	MAT-03880	d	25/50 / 40/80 Ltr. Water cooler	1 No	2530
	MAT-03881	e	60/120 Ltr. Water cooler	1 No	2910
	MAT-03882	f	150/150 Ltr. Water cooler	1 No	3542
	MAT-03883	g	165 Ltr Refrigerator	1 No	1581
	MAT-03884	h	200/210 Ltr Refrigerator	1 No	2277
	MAT-03885	i	286/310 Ltr Refrigerator	1 No	2657
303		ELEC-5.9.16	Replacement of defective compressor by company repaired compressor of fridge/water cooler including testing etc. as required. Makes: As per list of recommended brands.		
	MAT-03886	a	25/50 / 40/80 Ltr. Water cooler	1 No	7590
	MAT-03887	b	60/120 Ltr. Water cooler	1 No	9614
	MAT-03888	c	150/150 Ltr. Water cooler	1 No	11385

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03889	d	165 Ltr Refrigerator)	1 No	3922
	MAT-03890	e	200/210 Ltr Refrigerator	1 No	4807
	MAT-03891	f	286/310 Ltr Refrigerator	1 No	5440
304		ELEC-5.9.17	Supply of brand new Rotary type sealed compressor for Air conditioner Makes: As per list of recommended brands.		
	MAT-03892	a	1.0/1.5 TR	1 No	11495
	MAT-03893	b	2 TR	1 No	12645
305		ELEC-5.9.18	Replacement of condensing/ cooling coil of copper fins for following capacity A.C./ Water cooler/ Fridge as required		
	MAT-03894	a	1.0 TR A.C.	1 No	4510
	MAT-03895	b	1.5 TR A.C.	1 No	5092
	MAT-03896	c	2.0 TR A.C.	1 No	5674
	MAT-03897	d	25/50 / 40/80 Ltr. Water cooler	1 No	3036
	MAT-03898	e	60/120 Ltr. Water cooler	1 No	4428
	MAT-03899	f	150/150 Ltr. Water cooler	1 No	4428
	MAT-03900	g	165 Ltr Refrigerator	1 No	1392
	MAT-03901	h	200/210 Ltr Refrigerator	1 No	1518
	MAT-03902	i	286/310 Ltr Refrigerator	1 No	1961
306	MAT-03903	ELEC-5.9.19	Replacement of overload protection of A.C./ Water cooler as required	1 No	633

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
307	MAT-03904	ELEC-5.9.20	Replacement of thermostat of A.C./ Water cooler/fridge as required.	1 No	569
308	MAT-03905	ELEC-5.9.21	Replacement of starting relay of A.C/water cooler/fridge compressor as required	1 No	620
309	MAT-03906	ELEC-5.9.22	Spray painting of complete fridge (inside and outside) of 165/ 200/286/310 Ltr. Capacity	1 No	2024
310		ELEC-5.9.23	Supply and fixing of 230V/ 275V, 50Hz rating		
			Starting capacitor		
	MAT-03907	a	20-60 micro farad	1 No	242
	MAT-03908	b	80-150 micro farad	1 No	484
			Running capacitor	1 No	
	MAT-03909	a	2.5/3.15/4.0/6.0 micro farad	1 No	91
	MAT-03910	b	8.0 micro farad	1 No	133
	MAT-03911	c	10.0 micro farad	1 No	182
	MAT-03912	d	15.0 to 36.0 micro farad	1 No	481
311	MAT-03913	ELEC-5.9.24	Supply, Fabrication of 1set MS bracket suitable for fixing outdoor unit of split AC unit.	1 Set	1452
312		ELEC-5.9.25	Providing 2 runs of Copper tubes for suction and liquid between indoor and outdoor unit for Split/Cassette Air- Conditioner including foaming etc., complete. Makes: As per list of recommended brands.		
	MAT-03914	a	1/2" x 1/4"	1 Mtr	1183
	MAT-03915	b	5/8" x 1/4"	1 Mtr	1301
	MAT-03916	c	3/4" x 3/8"	1 Mtr	1425

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03917	d	7/8" x 1/2"	1 Mtr	1608
	MAT-03918	e	1 1/8" x 5/8"	1 Mtr	1973
313	MAT-03919	ELEC-5.9.26	Multi speed Fan Motor suitable for 1.0 / 1.5 / 2.0 Ton Window A.C. Unit Makes: As per list of recommended brands.	1 No	1803
314	MAT-03920	ELEC-5.9.27	Air filter suitable for 1.50 Ton Window A.C. Unit P.V.C. / NYLON.	1 No	303
315	MAT-03921	ELEC-5.9.28	Air filter suitable for 1.50 Ton Split A.C. Unit P.V.C. / NYLON.	1 No	520
316	MAT-03922	ELEC-5.9.29	Fan blade for 1.0 / 1.5 Ton A.C. Machine.	1 No	605
317	MAT-03923	ELEC-5.9.30	Installation of Split Air Conditioners.	1 No	2200
318	MAT-03924	ELEC-5.9.31	Removing of existing Split Air Conditioners without damaging to copper pipe.	1 No	726
319	MAT-03925	ELEC-5.9.32	Installation of Cassette type Split Air Conditioners.	1 No	5500
320	MAT-03926	ELEC-5.9.33	Installation of Tower type Split Air Conditioners.	1 No	4125
321	MAT-03927	ELEC-5.9.34	Supply, Fabrication of 1set MS bracket suitable for fixing outdoor unit of 3.5 /4.50 TR Cassette AC unit.	1 Set	2057
322	LAB-01181	ELEC-5.9.35	Repairs and Installation of existing PCB in 1.0 / 1.5 / 2.0 Ton Split A.C. Unit	1 No	858
323	LAB-01182	ELEC-5.9.36	Overhauling and servicing the Split type 1.5/2.0 Ton A.C. Machine by Cleaning the condenser cooling Coil etc., by blower and oiling the Fan Motor and Cleaning all parts and putting the machine in working condition.	1 Job	950
324	LAB-01183	ELEC-5.9.37	Overhauling and servicing the Cassette type 1.5/2.0/3.5/4.0 Ton A.C. Machine by Cleaning the condenser cooling Coil etc., by blower and oiling the Fan Motor and Cleaning all parts and putting the machine in working condition.	1 Job	1300
325		ELEC-5.9.38	Supply, Transportation, Installation, Testing and Commissioning of the following actual capacity at		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			45°C ambient Outdoor Condensing Units-Inverter type suitable to operate upto 52°C ambient temperature with minimum one variable speed inverter scroll compressor. Matching air-cooled condenser with copper tubes and aluminum fins duly covered by anti-corrosion and hydrophilic resin film. Scroll compressors suitable for operation with R-410A. Unit with all necessary safety devices like high/low pressure cut-outs, fan motor thermal overload protector, over current/low current safety, fuses etc. Suitable for operation on 80V~415V, 3Ph~50Hz A.C. supply. Oil separator and accumulator to be provided for inverter compressors and with copper condensing units. Makes: As per list of recommended brands.		
		a	2.5 TR	1 No	55000
		b	3.5 TR	1 No	83000
		c	5.5 TR	1 No	85400
		d	8.5 TR	1 No	122000
		e	11 TR	1 No	146000
		f	17 TR	1 No	239000
			AIR HANDLING UNITS		
326		ELEC-5.10.1	Supply, Installation, Testing and Commissioning of double skin horizontal floor mounted air handling unit of recirculation type having mixing box with fresh air & return air manually operated AL dampers. Fresh air inlet should have back draft dampers along with AL manually operated fresh air dampers. Units shall be with a minimum of 80mm GI base channel. The panel thickness should be 46+/-2mm having thermal break AL profile. Outer skin of the unit should be 0.6mm pre-coated GI sheet & Inner skin should be 0.8mm AL. All internal blank off should be GI. Filter section with 90% efficiency down to 10-micron pre-		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			filter box type followed by 95% efficiency down to 5-micron Microvee filter in a separate filter frame. The cooling coil section should be 6 or 8 Row Deep Direct Expansion intertwining cooling coil compatible for Mitsubishi /DAIKIN/Toshiba/O General/ Blue star/Hitachi/Carrier outdoor unit. Fin thickness should be 0.15mm & fin spacing should be 12 FPI. Coil casing should be GI & fin shall be with standard fin material. Coil shall be 18G SS-304 drain pan with 13mm thick closed cell nitrile rubber insulations. Unit shall be ultraviolet lamp to kill germs/fungus. The heater section should be with 4kW electric strip heater in 2 banks. The fan section should be SISW direct driven plug fan with a minimum efficiency of 65%. Motors should be IE-2, TEFC squirrel cage induction type with IP-55 protection, 415V, 3Phase & 50Hz. The motor drive should be VFD. VFD drive should be included in AHU supply. Fan should be housed over the spring isolator. Units should be supplied with manually operated AL dampers. The AHU package should include Electronic expansion valves compatible to condensing units, Temperature sensor and controller compatible to inverter drive, communication cables from AHU to condensing unit etc., including cost of all accessories and all labour charges, transportation etc., complete. Makes: As per list of recommended brands.		
			1000 cfm 2.5" static	Each	74750
			1400 cfm 2.5" static	Each	86250
			2200 cfm 3.5" static	Each	132250
			3400 cfm 4.5" static	Each	212750
			4400 cfm 4.5" static	Each	258750
			6800 cfm 4.5" static	Each	385250
			8800 cfm 5.5" static	Each	442750

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
327		ELEC-5.10.2	Supply, installation, testing and commissioning of tube axial flow type Supply Air Fan of suitable capacity WC static pressure with powder coated MS/GSS casing and aluminum alloy impellers with high efficiency aero-foil sections, blades, the impeller directly driven by TEFC induction motor (IE-2) and 'F' class insulation suitable for 3 Phase, 50 Hz, 415±10% Volt, ac supply (and as per manufacturer specification) for a static pressure as indicated below. Fan section shall be suitable for Floor Mounted outdoor application as well as ceiling suspended indoor applications with suitable capacity of starter with Four Pole MCB etc., and other protective devices of approved brands within MS enclosure box complete as required and as per specifications. The fan shall be equipped with mounting bracket Inlet & outlet cone required at discharge. The sound pressure should not exceed 80 db(A) at a distance of 3 Mts. The Fan should be complete with all accessories including fire rated canvas connection with metallic flange, vibration isolators, gravity louvers, bird screen etc., as per specification including transportation to site, all mounting arrangements like brackets etc., and cost of all accessories and all labour charges complete. Fan total efficiency should not be less than 60%. Makes: As per list of recommended brands.		
		a	1500 CFM/ 20mm	Each	17419
		b	2500 CFM/ 20mm	Each	19441
		c	3000 CFM/ 20mm	Each	19441
		d	3500 CFM/ 20mm	Each	21656
		e	4000 CFM/ 20mm	Each	24411
		f	5000 CFM/ 20mm	Each	27910
		g	5500 CFM/ 20mm	Each	25997

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		h	6500 CFM/ 35mm	Each	30995
		i	9500 CFM/ 20mm	Each	36103
		j	11500 CFM/ 35mm	Each	41593
		k	12000 CFM/ 35mm	Each	41593
		l	16000 CFM/ 35mm	Each	56406
328		ELEC-5.10.3	Supply, installation, testing and commissioning of tube axial flow type Fire rated Exhaust Air Fan of suitable capacity WC static pressure with powder coated MS/ GSS casing and aluminum alloy impellers with high efficiency aero-foil sections, blades, the impeller directly driven by TEFC induction motor (IE-2) and 'H' class insulation suitable for 3 Phase, 50 Hz, 415±10% Volt, ac supply, (and as per manufacturer specification) for a static pressure as indicated below. Fan section shall be suitable for Floor Mounted outdoor application as well as ceiling suspended indoor applications with suitable capacity of starter with Four Pole MCB etc., and other protective devices of approved brands within MS enclosure box complete as required and as per specifications. The fan shall be equipped with mounting bracket Inlet & outlet cone required at discharge. Fans should be AMCA certified. The sound pressure should not exceed 80 db(A) at a distance of 3 Mts. Fan and Motor for Fire exhaust fans shall be suitable for operation at minimum 250 deg C for 2 hrs. The Fan should be complete with all accessories including fire rated canvas connection with metallic flange, vibration isolators, gravity louvers, bird screen etc., as per specification including transportation to site, all mounting arrangements like brackets etc., and cost of all accessories and all labour charges complete. Fan total efficiency should not be less than 60%. Makes: As per list of recommended brands.		
		a	2500 CFM/ 20mm	Each	22736

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		b	3000 CFM/ 20mm	Each	21990
		c	3500 CFM/ 20mm	Each	24759
		d	4000 CFM/ 20mm	Each	24759
		e	5000 CFM/ 20mm	Each	29858
		f	5500 CFM/ 20mm	Each	29858
		g	16000 CFM/ 35mm	Each	64949
		h	19000 CFM/ 25mm	Each	65799
329		ELEC-5.10.4	Supplying, installing, testing and commissioning of low noise silent type ESP Inline Fan. The motor shall be suitable for 220-volt single phase 50 cycles AC supply, 6/15 Amp plug and wiring between the fan and the socket and low sound level exceeding not more than 50dBA. Fan should be complete with all accessories including canvas connection, gravity louver/ shutter as required etc., as per manufacturer specification including transportation to site, all mounting arrangements like brackets etc., as per specification including transportation to site, all mounting arrangements like brackets etc., and cost of all accessories and all labour charges complete. Makes: As per list of recommended brands.		
		a	100 CFM / 3-5 mm	Each	4386
		b	150 CFM / 3-5 mm	Each	4627
		c	200 CFM / 5 mm	Each	4723
		d	300 CFM / 5 mm	Each	5639
		e	400 CFM / 5 mm	Each	7046

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		f	450 CFM / 5 mm	Each	5976
		g	500 CFM / 5 mm	Each	7229
		h	600 CFM / 8 mm	Each	8868
		l	800 CFM / 8 mm	Each	10121
		J	1000 CFM / 8 mm	Each	11133
		K	1300 CFM / 10 mm	Each	12483
330		ELEC-5.10.5	Supplying, installing, testing and commissioning of SP-For Fresh Air Cabinet FAN SECTION - DIDW of double skin construction as per specifications, each complete with squirrel cage induction motor (mounted internally), centrifugal fan belt drive and vibrations isolators, base, drive arrangement, flexible canvass connection inside and for duct connection and all other accessories as required and as called for in the drawings. Motors shall be suitable for $415 \pm 10\%$ volts, 50 cycles, 3 phase or 220-volt single phase 50 cycles AC supply (as per manufacturer specification) for a static pressure as indicated. In addition, all supply fans (SF) shall be provided with 50mm thick prefilter. Fan section shall be suitable for Floor Mounted outdoor application as well as ceiling suspended indoor applications with suitable capacity of starter with Four Pole MCB etc., and other protective devices of approved brands within MS enclosure etc., as per specification including transportation to site, all mounting arrangements like brackets etc., and cost of all accessories and all labour charges complete. Makes: As per list of recommended brands.		
		a	15000 CFM / 30mm	Each	87233
		b	25000 CFM / 30mm	Each	304882

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
331		ELEC-5.10.6	Supply, Installation, Testing and Commissioning of Electrostatic Type Kitchen Exhaust Air Cleaner (Dry Scrubber) complete with the following accessories, components etc. Making it a completely functional dry scrubber suitable for Kitchen Hood Exhaust. The component to be included are:- Fan Section:-Double skin floor mounted cabinet fan section for exhaust air made of 25 ± 2 mm thick panel consisting of pre painted GSS sheet of thickness 0.8mm outside layer and 0.63 mm inside layer with polyurethane foam (PUF) insulation of density 40 kg/m³ factory injected between them by injection moulding machine, complete with SISW backward curved centrifugal fan suitable for static pressure as required with TEFC induction motor (IP 55 protection) should be of high efficiency class IE3 suitable for 3 Phase 50 Hz 415V ± 10 %, of Class F insulation, internal fire rated flexible connection with flanges, fire rated connection for duct/ dry scrubber, gravity louver, vibration isolator etc. including all accessories complete as required and as per specifications. Motor and drive shall be out of hot air stream and shall be protected with GI covering/weatherproof canopy. Pre Filter-Section with Wire Mesh SS Filters for Coarse Particle. Electrostatic Precipitator Section - Electrostatic section shall be made of 16 SWG galvanised sheet, high bake epoxy powder coated, SS Spiked ionizers to create high voltage DC field, aluminum collector plates which should be alternatively charged positive and negative with large collecting area with deep cell, to work as magnet for charged smoke and oil particles. Average efficiency of 90-95% in single pass as per ASHRAE/DOP test method. Electrostatic Precipitator should be able to charge particles from 0.01 micron to 10 microns through solid state power supply. Collector cell should be of permanent type and incorporate slide out facility for easy removal for cleaning. Power supplies shall be 100% solid state. Suitable capacity of starter with Four Pole MCB etc., and other protective devices of approved brands and other protective devices within M.S enclosure box with suitable length of cable for connection with fan from isolator complete as required and as per specifications. Fan should be		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			complete with all accessories including canvas connection, vibration isolators etc., as per specification including transportation to site, all mounting arrangements like brackets etc., and cost of all accessories and all labour charges complete. Makes: As per list of recommended brands.		
		a	18000 CFM / 65mm	Each	373016
		b	30000 CFM / 65mm	Each	679370
332		ELEC-5.10.7	Supplying, installing, testing, and commissioning of 150 mm dia low noise direct driven wall mounted PROPELLER FAN. Each fan shall be complete with permanent split capacitor or shaded pole motor, mounting plate with light weight type PVC /aluminum impellers with aero foil contours for high efficiency & finished with decorative frames & gravity shutter/ bird screen at discharge as required. The motor shall be suitable for 220 volt single phase 50 cycles AC supply, 6/15 Amp plug and wiring between the fan and the socket etc., as per specification including transportation to site, all mounting arrangements like brackets etc., and cost of all accessories and all labour charges complete. Makes: As per list of recommended brands.		
		a	150 mm dia	Each	1957
		b	300 mm dia	Each	2699
333		ELEC-5.10.8	Supply, Transportation, Installation, Testing and Commissioning of Ceiling suspended laminar flow (Planair Ceiling system) with unidirectional airflow work space / discharge plenum for operation rooms comprising as standard feature with HEPA filter efficiency not less than 99.97% down to 0.3 Microns (Factory DOP tested), per operation room shall not be less than 3.1 sqm area with appropriate depth to accommodate absolute filters, with air flow at approx. 90-100 Fpm velocity. Size 8ft X 6ft. The laminar flow system shall have such design that it provides "H13/14" class Hepa filter. Material of construction Shall be 1.2mm thick S S 304 Plenum	Each	275000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			with S S Perforated sheet at the bottom. Each air inlet should be supplied with Aluminum opposed blade damper. Diffuser: 2 layer monofilament precision woven polyester of uniform porosity with an open area of sufficient resistance to create laminar from diffusers face and integral lighting provides an illumination level in excess of 1500 Lux in operating area and 1000 Lux other electronic stepless dimming down to 5% without flicker. The entire plenum should be insulated with 19mm thick Al faced nitrile rubber. Bottom discharge should be perforated SS Sheet of 1.6mm with reinforcement to avoid waviness.		
			SECTION 6		
		6.1	SWAGED / OCTAGONAL POLES AND GARDEN POSTS		
334	MAT-03928	ELEC-6.1.1	Fabrication, supply and transportation of all sizes swaged poles up to site confirming to IS 2713 / 1980 specifications. The pole should be painted with primary coat of red oxide and black bituminous paint up to ground level with base plate, including cost of all materials etc., complete. (Rate per K. G)	1 Kg	88
335	MAT-03929	ELEC-6.1.2	Fabrication and Supply of M.S. Poles for garden posts with 'B' class 60.25mm outer dia with base plate and suitable pole cap including cost and conveyance of all material including fixing of luminaire and labour charges etc., complete. (Rate per K. G)	1 Kg	79
336	MAT-03930	ELEC-6.1.3	Supply of different sizes of M. S. Pipe brackets (Rate per K.G)	1 Kg	79
			OCTOGONAL POLES		
337	MAT-03931	ELEC-6.1.4	Fabrication, Transportation and supply of hot-dip galvanized Octagonal Pole with BSEN - 10025 grade S 355 JO steel plate for shaft, IS 2062 for base plate with hinged door opening arrangement, including the supply of suitable boards with bakelite sheet as per IS specification suitable to withstand the wind speed of 180 KMPH for 7.5 Mtrs height Pole having dimensions Bottom 130 mm,. Top 70mm with 3mm thick, base plate 220 x 220 x 12mm and 4 Nos of M20 x 700 long 'J' bolts along with template. Makes: As per list of recommended brands.	1 No	13842

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
338	MAT-03932	ELEC-6.1.5	Fabrication, Transportation and supply of hot-dip galvanized Octagonal Pole with BSEN - 10025 grade S 355 JO steel plate for shaft, IS 2062 for base plate with Hinged door opening arrangement, including the supply of suitable boards with bakelite sheet as per IS specification suitable to withstand the wind speed of 180 KMPH for 9 Mtrs height Pole having dimensions Bottom 155 mm,. Top 70mm with 3mm thick, base plate 260 x 260 x 16mm and 4 Nos of M24 x 750 long 'J' bolts along with template. Makes: As per list of recommended brands.	1 No	20009
339	MAT-03933	ELEC-6.1.6	Fabrication, Transportation and supply of hot-dip galvanized Octagonal Pole with BSEN - 10025 grade S 355 JO steel plate for shaft, IS 2062 for base plate with hinged door opening arrangement, including the supply of suitable boards with bakelite sheet as per IS specification suitable to withstand the wind speed of 180 KMPH for 10 Mtrs height Pole having dimensions Bottom 175 mm,. Top 70mm with 3mm thick, base plate 275 x 275 x16mm and 4 Nos of M24 x 750 long 'J' bolts along with template. Makes: As per list of recommended brands.	1 No	21998
340	MAT-03934	ELEC-6.1.7	Fabrication, Transportation and supply of hot-dip galvanized Octagonal Pole with BSEN - 10025 grade S 355 JO steel plate for shaft, IS 2062 for base plate with door opening arrangement, including the supply of suitable boards with bakelite sheet as per IS specification suitable to withstand the wind speed of 180 KMPH for 12 mtrs height Pole having dimensions Bottom 240mm, Top 100mm with 4mm thick, base plate 320 x320 x20mm and 4 Nos of M24 x 850 long 'J' bolts along with template. Makes: As per list of recommended brands.	1 No	31779

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			DECORATIVE DRAGON TYPE BRACKET WITH POLE		
341		ELEC-6.1.8	Fabrication, Transportation and supply of hot-dip galvanized Octagonal Pole with BSEN - 10025 grade S 355 JO steel plate for shaft, IS 2062 for base plate with door opening arrangement, including the supply of suitable boards with bakelite sheet and MCB's as per IS specification suitable to withstand the wind speed of 180KMPH for 9 Mtrs mounting height Pole having dimensions bottom 185 mm,. Top 70mm with 3mm thick, base plate 275 x 275 x 20mm and 4 Nos of M24 x 1000 long 'J' bolts along with templates. Including Supply of 1.5M Dragon type decorative. Makes: As per list of recommended brands.		
	MAT-03935	a	galvanized double arm with PU Painted bracket.	1 No	31308
	MAT-03936	b	galvanized Single arm with PU Painted bracket.	1 No	26836
	MAT-05544	c	Double arm Galvanize finished bracket	1 No	26483
	MAT-05545	d	Single arm Galvanize finished bracket	1 No	24011
342		ELEC-6.1.9	Fabrication, Transportation and supply of hot-dip galvanized Octagonal Pole with BSEN - 10025 grade S 355 JO steel plate for shaft, IS 2062 for base plate with door opening arrangement, including the supply of suitable boards with bakelite sheet and MCB's as per IS specification suitable to withstand the wind speed of 180 KMPH for 9 Mtrs Mounting height Pole having dimensions Bottom 185 mm,. Top 70mm with 3mm thick, base plate 275 x 275 x 20mm and 4 Nos of M24 x 1000long 'J' bolts along with templates. Including Supply of 1.5M Dragon type decorative		
343		ELEC-6.1.10	Fabrication, Transportation and supply of hot-dip PU Paint finish curved Octagonal Pole with BSEN - 10025 grade S 355 JO steel plate for shaft, IS 2062 for base plate with door opening arrangement, including the supply of suitable boards with bakelite sheet and MCB's as per IS specification suitable to withstand the wind speed of 180 KMPH for 9 Mtrs mounting height Curved Pole having dimensions Bottom 180 mm,. Top 85mm with 3mm thick, base plate 400 x 400 x 20mm and 4 Nos of M24 x 750 long 'J' bolts along with templates. Including Supply of 0.2M long Single arm bracket.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: As per list of recommended brands.		
	MAT-03937	a	Galvanized	1 No	26247
	MAT-05546	b	Galvanized PU paint finished	1 No	35545
			POLE BRACKETS		
344	MAT-03938	ELEC-6.1.11	Fabrication, Transportation and supply of 1.0 Mtr Length Single Arm Bracket made with MS galvanized 40mm / 50mm dia Pipe. (The design should be approved from field Engineers)	1 No	1530
345	MAT-03939	ELEC-6.1.12	Fabrication, Transportation and supply of 1.50 Mtr Length Single Arm Bracket made with MS galvanized 40mm / 50mm dia Pipe. (The design should be approved from field Engineers).	1 No	2024
346	MAT-03940	ELEC-6.1.13	Fabrication, Transportation and supply of 1 Mtr length Double Arm Bracket made with MS galvanized 40mm / 50mm dia Pipe. (The design should be approved from field Engineers).	1 No	1895
347		ELEC-6.1.14	Fabrication, Transportation and supply of 1.5 Mtr length Double Arm Bracket made with MS galvanized 40mm / 50mm dia Pipe. (The design should be approved from field Engineers)	1 No	3413
348	MAT-03942	ELEC-6.1.15	Fabrication, Transportation and supply of 1.5 Mtr Length Single Arm suitable size decorative galvanized bracket with PU paint colour finish etc complete. (The design should be approved from field Engineers)	1 No	5650
349	MAT-03943	ELEC-6.1.16	Fabrication, Transportation and supply of 1.5 Mtr length double arm suitable size decorative galvanized bracket with PU paint colour finish etc complete. (The design should be approved from field Engineers)	1 No	10711

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
350	MAT-03944	ELEC-6.1.17	Fabrication, Transportation and supply of 1.5mtrs sword type or any decorative double arm bracket with dooms either side complete with all accessories with MS galvanized 40mm / 50mm dia Pipe. (The design should be approved from field Engineers)	1 No	6238
351	MAT-03945	ELEC-6.1.18	Fabrication, Transportation and supply of 1.5mtrs sword type or any decorative Single arm bracket with dooms either side complete with all accessories with MS galvanized 40mm / 50mm dia Pipe. (The design should be approved from field Engineers)	1 No	4826
352	MAT-03946	ELEC-6.1.19	Fabrication, Transportation and supply of 1.0mtrs sword type or any decorative double arm bracket with dooms either side complete with all accessories with MS galvanized 40mm / 50mm dia Pipe. (The design should be approved from field Engineers)	1 No	5061
353	MAT-03947	ELEC-6.1.20	Fabrication, Transportation and supply of 1.0 mtrs sword type or any decorative Single arm bracket with dooms either side complete with all accessories with MS galvanized 40mm / 50mm dia Pipe. (The design should be approved from field Engineers)	1 No	4237
			HIGH MAST POLES		
354	MAT-03948	ELEC-6.1.21	Fabrication, transportation and supply of 12 Mtrs Polygon High Mast with single section of 3mm thick of bottom 360mm and top 150mm dia with BSEN - 10025 grade S 355 JO steel plate for shaft, IS 2062 for base plate, having a base plate of size 520mm dia 16mm thick with its accessories. Mast shall be in single section for 12 Mtrs and 2 sections for 16 and 20 Mtrs. Mast shall be hot dip galvanized and suitable for wind velocity of 180 KMPH as per IS 875 part 3 including head frame, 2 point suspension system with steel rope 6mm dia (7/19) construction double drum winch / power tool operating speed of 900 RPM, and necessary cable trailer connections and single speed motor with M24 x 800 mm foundation bolts of required quantity, and GI Pipe ring suitable for fixing luminaires with LED type aviation twin lamp.	1 No	123585

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: As per list of recommended brands.		
355	MAT-03949	ELEC-6.1.22	Fabrication, transportation and supply of 16 Mtrs Polygon High Mast with two sections of bottom 4mm thick and top section with 3mm thick with GLS type aviation lamp of Bottom 360mm and Top 150mm dia with BSEN - 10025 grade S 355 JO steel plate for shaft, IS 2062 for base plate, having a base plate of size 560mm dia 25mm thick with its accessories. Mast shall be in single section for 12 Mtrs and 2 sections for 16 and 20 Mtrs. Mast shall be hot dip galvanized and suitable for wind velocity of 180 KMPH as per IS 875 part 3 including head frame, 2 point suspension system with steel rope 6mm dia (7/19) construction double drum winch / power tool operating speed of 900 RPM, and necessary cable trailer connections and single speed motor with M24 x 800 mm foundation bolts of required quantity and GI Pipe ring suitable for fixing luminaires with LED type aviation twin lamp. Makes: As per list of recommended brands.	1 No	162426
356	MAT-03950	ELEC-6.1.23	Fabrication, transportation and supply of 20 Mtrs Polygon High Mast with two sections of bottom 4mm thick and top section with 3mm thick of bottom 460mm and top 150mm dia with BSEN - 10025 grade S 355 JO steel plate for shaft, IS 2062 for base plate, having a base plate of size 670mm dia 25mm thick with its accessories. Mast shall be in single section for 12 Mtrs and 2 sections for 16 and 20 Mtrs. Mast shall be hot dip galvanized and suitable for wind velocity of 180 KMPH as per IS 875 part 3 including head frame, 2 point suspension system with steel rope 6mm dia (7/19) construction double drum winch / power tool operating speed of 900 RPM, and necessary cable trailer connections and single speed motor with M30 x 750 mm foundation bolts of required quantity and GI Pipe ring suitable for fixing luminaires with LED type aviation twin lamp. Makes: As per list of recommended brands.	1 No	210095

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			FEEDER PILLAR BOXES		
357	MAT-03951	ELEC-6.1.24	Supply and fixing of suitable outdoor type feeder pillar box made with 14 SWG CRCA sheet after 7 tank process including S & F 40-63A FP MCB, 6 Nos SP MCB's, din channel, bus bars, 6 Sq mm 3 core copper cable for internal wiring, contactor, connectors and provision for energy meter etc., complete for finished item of work. Makes: As per list of recommended brands.	1 No	21539
358	MAT-03952	ELEC-6.1.25	Supply and fixing of suitable outdoor type feeder pillar box made with 14 SWG CRCA sheet after 7 tank process including S & F 40-63A FP MCB, 9 Nos SP MCB's, din channel, bus bars, 6 Sq mm 3 core copper cable for internal wiring, contactor, connectors and provision for energy meter etc., complete for finished item of work. Makes: As per list of recommended brands.	1 No	22245
			ERRECTION- HIGH MAST POLES		
359	MAT-03953	ELEC-6.1.26	Earth work excavation with an approximate quantity of 4.0 Cum for erection of 12 Mtrs high mast and refilling with a quantity of 0.53 Cum of PCC 1:4:8, 1.50 Cum M 20 grade concrete and (80 Kgs) reinforced steel of 12mm / 10mm / 8mm, Soil bearing capacity of 10 T/Sqm, Anchor plate with cost and conveyance of all above materials including labour charges for erection of High Mast and carriage etc complete.	1 No	33739
360	MAT-03954	ELEC-6.1.27	Earth work excavation with an approximate quantity of 6.0 Cum for erection of 16 Mtrs high mast and refilling with a quantity of 0.65 Cum of PCC 1:4:8, 2.60 Cum M 20 grade concrete and (110 Kgs) reinforced steel of 12mm / 10mm / 8mm, Soil bearing capacity of 10 T/Sqm, Anchor plate with cost and conveyance of all above materials including labour charges for erection of High Mast and carriage etc complete.	1 No	42174

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
361	MAT-03955	ELEC-6.1.28	Earth work excavation with an approximate quantity of 7.0 Cum for erection of 20 Mtrs high mast and refilling with a quantity of 0.75 Cum of PCC 1:4:8, 3.60 Cum M20 grade concrete and (140 Kgs) reinforced steel of 12mm / 10mm / 8mm, Soil bearing capacity of 10 T/Sqm, Anchor plate with cost and conveyance of all above materials including labour charges for erection of High Mast and carriage etc complete.	1 No	54173
362		ELEC-6.1.29	Supply of Sizes thermo-plastic cable junction boxes with IP66/67 weatherproof, for outdoor installation with knockouts for cable entry including terminals etc., complete (sizes in mm). Makes: As per list of recommended brands.		
	MAT-03956	a	155 X 210 X 92	1 No	1893
	MAT-03957	b	205 X 255 X112	1 No	2754
	MAT-03958	c	225 X 295 X 122	1 No	9695
	MAT-03959	d	255 X 600 X 170	1 No	10670
			FOUNDATION AND ERRECTION CHARGES OF POLES		
363	MAT-03960	ELEC-6.1.30	Erection charges for 7.50 Mts long Octagonal pole on bridge kerb portion with 4 Nos, 8" Anchor bolts with chemical treatment with suitable "J" type bolts etc duly drilling holes to RCC slab with V.C.C. M.15 concrete for suitable base concreting with necessary steel reinforcement work and curing for 7 days etc. including cost and conveyance of all material and all labour charges etc., complete as directed by the department officers.	1 Job	5339
364	MAT-03961	ELEC-6.1.31	Foundation and erection charges with special T&P, for 7.50 Mtrs long Octagonal /Conical pole duly erecting on base plate duly providing 4 Nos foundation bolts with nuts with providing of 0.45Mtr x 0.45Mtrs x1.20 Mtr size M20 cc work vibrated concreting mixing with necessary steel (10kgs) reinforcement and curing for 7 days as directed by the field engineers during execution including	1 Job	6228

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			excavation of Earth/BT all labour charges and cost and conveyance of materials etc., complete.		
365	MAT-03962	ELEC-6.1.32	Foundation and erection charges with special T&P, for 9.00Mtrs / 10Mtrs long Octagonal / Conical pole duly erecting on base plate duly providing 4 Nos foundation bolts with nuts with providing of 0.60Mtr x 0.60Mtrs x 1.40 Mtr size M20 cc work vibrated concreting mixing with necessary steel (15kgs) reinforcement and curing for 7 days as directed by the field engineers during execution including excavation of Earth/BT all labour charges and cost and conveyance of materials etc., complete.	1 Job	8390
366	MAT-03963	ELEC-6.1.33	Foundation and erection charges with special T&P, for 12Mtrs long Octagonal /Conical pole duly erecting on base plate duly providing 4 Nos foundation bolts with nuts with providing of 0.67Mtr x 0.67Mtrs x 1.50 Mtr size M20 cc work vibrated concreting mixing with necessary steel (20kgs) reinforcement and curing for 7 days as directed by the field engineers during execution including excavation of Earth/BT all labour charges and cost and conveyance of materials etc., complete.	1 Job	10297
			GRP POLES		
367		ELEC-6.1.34	Supply and transportation of following glass reinforced polymer (GRP) composite type Conical pole with single arm bracket of length 1Mtr and internal junction box including labour charges etc., complete. Makes: As per list of recommended brands.		
	MAT-03964	a	...do.... 3.00 Mtrs height, Bottom dia 143mm, Top 76mm, AV thickness 6mm and to withstand maximum wind velocity 180Km/Hr	1 No	10005
	MAT-03965	b	...do.... 4.00 Mtrs height, Bottom dia 143mm, Top 76mm, AV thickness 6mm and to withstand maximum wind velocity 180Km/Hr	1 No	12712
	MAT-03966	c	...do.... 6.00 Mtrs height, Bottom dia 143mm, Top 76mm, AV thickness 6mm and to withstand maximum wind velocity 180Km/Hr	1 No	15890
	MAT-03967	d	...do.... 8.00 Mtrs height, Bottom dia 193mm, Top 76mm, AV thickness 6mm and to withstand maximum wind velocity 180Km/Hr	1 No	20480

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03968	e	...do.... 9.00 Mtrs height, Bottom dia 210mm, Top 76mm, AV thickness 6mm and to withstand maximum wind velocity 180Km/Hr	1 No	22363
	MAT-03969	f	...do.... 10.00 Mtrs height, Bottom dia 227mm, Top 76mm, AV thickness 6mm and to withstand maximum wind velocity 180Km/Hr	1 No	32368
368		ELEC-6.1.35	Supply and transportation of base bracket suitable for glass reinforced polymer (GRP) composite type pole including labour charges etc., complete. Makes: As per list of recommended brands.		
	MAT-03970	a	...do.... For 3.00 Mtrs Pole	1 No	1824
	MAT-03971	b	...do.... For 4.00 Mtrs Pole	1 No	1824
	MAT-03972	c	...do.... For 6.00 Mtrs Pole	1 No	2177
	MAT-03973	d	...do.... For 8.00 Mtrs Pole	1 No	2531
	MAT-03974	e	...do.... For 9.00 Mtrs Pole	1 No	4826
	MAT-03975	f	...do.... For 10.00 Mtrs Pole	1 No	6003
		6.2	LT PANEL AND ACCESSORIES		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
369	MAT-03976	ELEC-6.2.1	Supply Installation Testing and commissioning of free-standing floor mounted dust and vermin proof compartmentalized cubical panel made out of CRCA sheet, required hardware, cleaning with 7 tank process duly painted by two coats of zinc/red oxide primer followed by Powder coated / epoxy / PU painted with phosphatisation in grey or required shade after rinsing. The panel having PU/ Neoprene rubber gasket of not less than 3mm thickness, separate detachable, gland plate M.S. base channel, hinged door with locking arrangement for equipment/switchgear. The thickness of sheet shall not be less than 1.6mm up to 600mm length/ width of any compartment and be 2.0mm above 600mm. The load bearing structure shall be of 2.0mm thick sheet supported by base M.S. channel if required. Side walls and cable alley compartments having bolted type doors with detachable extension type structure (only outer area on all sides shall be measured and panel to be fabricated from CPRI approved fabricator).	1 sqm	5586
370		ELEC-6.2.2	Supply and fixing of..... bus bar by means of SMC / DMC type insulator, high tensile nuts and bolts spring washers in existing panel including bending , cutting in required shape and size and colour coding with heat shrinkable PVC sleeves		
	MAT-03977	a	Electrolytic grade aluminum bus bar	kg	469
	MAT-03978	b	Electrolytic grade copper bus bar	kg	990
371		ELEC-6.2.3	Supply and fixing of (0-500) V range Voltmeter on existing panel, making connection by PVC insulated copper conductor with PVC sleeves / channel etc. as required. Makes: As per list of recommended brands.		
	MAT-03979	a	Analog type (96 mm x 96 mm)	1 No	935
	MAT-03980	b	Digital type	1 No	2090
372		ELEC-6.2.4	Supply and fixing of CT operated direct reading type Ammeter on existing panel, making connection by PVC insulated copper conductor with PVC sleeves / channel etc. as required.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: As per list of recommended brands.		
			Analog type (96 mm x 96 mm)		
	MAT-03981	a	Below 500 A	1 No	935
	MAT-03982	b	Above 500A	1 No	935
			Digital type		
	MAT-03983	c	Below 500 A	1 No	2090
	MAT-03984	d	Above 500 A	1 No	2090
373		ELEC-6.2.5	Supply and Fixing of Current Transformer, with all necessary support in existing panel including connection etc. as required: Makes: As per list of recommended brands.		
	MAT-03985	a	up to 150 / 5 Ratio, 5 VA, class 1 accuracy	1 No	523
	MAT-03986	b	from 200 / 5 to 400/5 Ratio, 10 VA, class 1 accuracy	1 No	770
	MAT-03987	c	from 500 / 5 to 1600/5 Ratio, 15 VA, class 1 accuracy	1 No	1045
	MAT-03988	d	from 2000 / 5 to 3200 /5 Ratio, 15 VA, class 1 accuracy	1 No	1650
374	MAT-03989	ELEC-6.2.6	Supply and fixing of selector switch for voltmeter (4 position) including making connection etc. as required Makes: As per list of recommended brands.	1 No	374
375	MAT-03990	ELEC-6.2.7	Supply and fixing of CT linked selector switch of 10 A for Ampere meter (4 position) including making connection etc. as required. Makes: As per list of recommended brands.	1 No	413
376		ELEC-6.2.8	Supply and fixing of single phase Electronic energy Meter,.....AC,50 HZ as per IS13010 up to 40A range with 200% over load capacity complete with connections etc., complete on the existing board. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-03991	a	Single Phase	1 No	1100
	MAT-03992	b	Three Phase	1 No	3080
377		ELEC-6.2.9	Supply and Fixing of 240/220 V, LED (22.5 mm dia) Pilot lamp with integral circuit, terminal block, including connection etc. as required		
	MAT-03993	a	Red/yellow/Green colour	1 No	132
	MAT-03994	b	Blue colour	1 No	220
378		ELEC-6.2.10	Supply and Fixing of Tap-off boxes suitable for following size of approved design		
	MAT-03995	a	up to 95 sq. mm (3.5/4 core)	1 No	440
	MAT-03996	b	from 120 sq. mm. to 185 sq. mm (3.5/4 core)	1 No	770
379	MAT-03997	ELEC-6.2.11	Supply and fixing of energy analyzer (multi-function energy meter) with LCD/LED display capable of minimum 20 numbers electrical parameters display with 1A/5A CT input for LV/ HV network, RS 485 communication port etc. complete in all respect.	1 No	11550
380		ELEC-6.2.12	Supply Installation Testing and commissioning of self-healing MPP/MP type shunt capacitor (banks) conforming to IS:13340-41 / IEC :831-1&2 in existing panel or parallel with load terminals , the capacitor shall be fitted with discharge resistors, pressure sensitive disconnecter (PSD) and shall have dissipation factor less than 0.0025 at 50 Hz and total wattage loss less than 0.5 Watt per KVAR. including making connections with suitable capacity conductors/cables testing as required. Makes: As per list of recommended brands.		
	MAT-03998	a	Standard duty Single phase 250 V / Three phase 440 V, 50 Hz capacitor (Bank)	1 KVAR	237
	MAT-03999	b	Heavy duty Three phase 440 V, 50 Hz capacitor (Bank)	1 KVAR	356

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
381	MAT-04000	ELEC-6.2.13	Supply Installation Testing and commissioning of microprocessor based intelligent power factor correction relay having sensitivity up to 50 milli Amp secondary current and following way, self-analyzing auto c/k setting according to targeted power factor setting, the relay shall have minimum three digit display unit for display of real power factor, targeted power factor, lag/lead capacitor switching status, alarm output for under current, over current, insufficient compensation, indication of switching on units, auto/manual status, and shall have over load protection, no volt release etc. as required. Makes: As per list of recommended brands.		
			6 to 14 stage - sensitivity upto 50 milli Amp	1 No	21958
382		ELEC-6.2.14	Supply and Fixing of Cam operated rotary switches on existing panel with 2 way and off position. Makes: As per list of recommended brands.		
			one pole		
	MAT-04001	a	16 A	1 No	415
	MAT-04002	b	32 A	1 No	534
	MAT-04003	c	63 A	1 No	771
			Two pole		
	MAT-04004	d	16 A	1 No	475
	MAT-04005	e	32 A	1 No	629
	MAT-04006	f	63 A	1 No	1039
			Three pole		
	MAT-04007	g	16 A	1 No	593
	MAT-04008	h	32 A	1 No	831
	MAT-04009	i	63 A	1 No	1484
			Four pole		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04010	j	16 A	1 No	593
	MAT-04011	k	32 A	1 No	890
	MAT-04012	l	63 A	1 No	1662
383		ELEC-6.2.15	Supply and fixing of ac operated heavy duty 230 /440 Volt power contactor conforming to IS:13947-4-1/IEC:947-4-1 having provision of mechanical interlocking, Din rail mounting type including making connections, testing etc. as required. Makes: As per list of recommended brands.		
			3 pole AC3 Rating contactors		
	MAT-04013	a	Up to 12 Amp	1 No	950
	MAT-04014	b	13 to 32 Amp	1 No	1573
	MAT-04015	c	35 to 40 Amp	1 No	1899
	MAT-04016	d	41 to 50 Amp	1 No	4154
			4 pole AC 1 Rating contactors		
	MAT-04017	e	Up to 25 Amp	1 No	1187
	MAT-04018	f	26 to 32 Amp	1 No	1424
	MAT-04019	g	33 to 45 Amp	1 No	2374
	MAT-04020	h	46 to 60 Amp	1 No	4985
384		ELEC-6.2.16	Supply and fixing of 440 Volt 3 pole capacitor (AC 6 B) duty contactor with 3 no. early make and post break auxiliary contacts in series with quick discharge damping resistors/ reactors to limit the inrush current, conforming to IS:13947-4-1/IEC:947-4-1, Din rail mounting type including making connections, testing etc. as required. suitable for following capacity capacitor bank. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04021	a	Up to 6 KVAR	1 No	1899
	MAT-04022	b	7 to 10 KVAR	1 No	2136
	MAT-04023	c	11 to 20 KVAR	1 No	3205
	MAT-04024	d	21 to 25 KVAR	1 No	4273
	MAT-04025	e	30 KVAR	1 No	6172
	MAT-04026	f	40 KVAR	1 No	9851
	MAT-04027	g	50 KVAR	1 No	11394
385		ELEC-6.2.17	Supply and fixing of thermal overload relay with built in single phase protection and having at least 1NO & 1NC contacts, manual /auto reset facility including making connection testing etc. as required. Makes: As per list of recommended brands.		
	MAT-04028	a	Up to 14 A	1 No	1424
	MAT-04029	b	15 to 20 A	1 No	1899
	MAT-04030	c	21 to 30 A	1 No	2730
	MAT-04031	d	31 to 40 A	1 No	3086
386		ELEC-6.2.18	Supply and fixing of push button actuators and integral contact block of dia. 22.5 mm including making connection etc. as required. Makes: As per list of recommended brands.		
	MAT-04032	a	Non-luminous type	1 No	113
	MAT-04033	b	Luminous type	1 No	154

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		6.3	SUB STATION EQUIPMENT AND TRANSFORMERS		
387	MAT-04034	ELEC-6.3.1	Supply, Installation, Testing & Commissioning of HT metering cubical panel as approved By DISCOMs fabricated out of 14 SWG CRCA sheet steel in two compartment & MS angle of size 60mmX6mm having provision for Following: Makes: As per list of recommended brands.	1 No	28486
			(i) Provision for fixing Tri-vector Meter (To be supplied by DISCOMs)		
			(ii) Provision for fixing of combined CT PT Set (To be supplied by DISCOMs)		
			(iii) TT Block		
			(iv) 6mm Bakelite sheet on all sides.		
388	MAT-05547	ELEC-6.3.1a	Supply, Transportation, Installation and Commissioning of 11 KV, 630A, 25 KA Outdoor type Load Break Switch as detailed below with suitable CC foundation and 2 Nos GI pipe earthing with brick masonry chambers etc., complete for finished item of work. Makes: As per list of recommended brands. a) Load break switch: 11KV, 630A, 25 KA with fuse trip, earth switch, manually operated spring charged mechanism with 2 no + 2 NC. b) HT HRC fuse upto 63A - 3 nos. c) Bus bar connection. d) Indication lamps. e) Manual trip Push button.		142428
			33 KV HT Panel (draw out type)		
389		ELEC-6.3.2	Supply, Installation, Testing and Commissioning of indoor type floor mounted metal clad, Switchgear Panel enclosure of sheet steel preferably Aluzinc, dust tight, vermin proof, totally enclosed cubicle floor mounting, free standing type with single break, horizontally draw out type breaker with trip free mechanism as per latest standard i.e. IS/IEC 62271-200 as amended up to date and as per Technical specifications, IP4X for VCB Panel enclosure. Switchgear Panel shall be electrically & mechanically interlocked as per IEC 62271-1, full voltage insulated copper Busbar with heat shrinkable sleeving, complete with suitable metering & protection		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			devices, breaker featured with mechanical ON-OFF indicator with hand trip device and all accessories such as shunt trip coil, motorized & manually operated spring charging mechanism, emergency trip push buttons, auxiliary switch of 2NO + 2NC, interconnections, space heaters, panel earthing etc. and equipped with following switchgear and accessories including connection suitable for 3x185 to 3x 400 Sq mm XLPE 33 kV cable (cable entry from bottom) to be connected through heat shrinkable jointing material etc., as required. (Note - Cost of end termination not included in this item.) Makes: As per list of recommended brands.		
			<u>INCOMER/OUTGOINGS 1 No. each comprising the following</u>		
			1 No. 800 Amp. VCB. 31.5KA		
			1 No. Integral Earth switch for line side earthing		
			3 No. dual core CTs 600A/1/1A of 7.5VA burden max and accuracy Class 0.5 for metering and class 5P10 for protection		
			3 No. Cast Resin 33000V/v3/110V/v3/110V/v3 PT Class 0.5/3P accuracy and 30VA burden max with and protection fuses / MCB.		
			1 No. Digital voltmeter with selector switch.		
			1 No. Digital Ammeter with selector switch.		
			1 No. Microprocessor based numerical relays with O/L, E/F and S/C protection with Integrated Arc sensing feature along with trip/lockout / anti-pumping / aux. relays.		
			1 No. Multi-function meter.		
			Set of MCBs for Panel AC/DC		
			Set of MCBs for Main AC/DC		
			Set of Indication lamps LED types		
			TNC Switch, L-R Switch, Pushbuttons for ON-OFF		
	MAT-04035	a	33 KV 800A VCB Panel with 3 Nos. VCBs suitable for 50Hz 3-phase system, suitable for 31.5kA/3sec	1 No	3151220

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			short circuit withstand capacity & 31.5kA/1sec Internal Arc capacity		
		b	33 KV 800A VCB Panel with 1 Nos. VCBs suitable for 50Hz 3-phase system, suitable for 31.5kA/3sec short circuit withstand capacity & 31.5kA/1sec Internal Arc capacity	1 No	1050400
			11KV HT Panel (draw out type)		
390		ELEC-6.3.3	Supply, Installation, Testing and Commissioning of indoor type floor mounted metal clad, Switchgear Panel enclosure of sheet steel preferably Aluzinc, dust tight, vermin proof, totally enclosed cubicle floor mounting, free standing type with single break, horizontally draw out type breaker with trip free mechanism as per latest standard i.e. IS/IEC 62271-200 as amended up to date and as per Technical specifications, IP4X for VCB Panel enclosure. Switchgear Panel shall be electrically & mechanically interlocked as per IEC 62271-1, full voltage insulated copper Busbar with heat shrinkable sleeving, complete with suitable metering & protection devices, breaker featured with mechanical ON-OFF indicator with hand trip device and all accessories such as shunt trip coil, motorized & manually operated spring charging mechanism, emergency trip push buttons, auxiliary switch of 2NO + 2NC, interconnections, space heaters, panel earthing etc. and equipped with following switchgear and accessories including connection suitable for 3x185 to 3x 400 Sq mm XLPE 11kV cable (cable entry from bottom) to be connected through heat shrinkable jointing material etc., as required. (Note - Cost of end termination not included in this item.) Makes: As per list of recommended brands.		
			<u>INCOMER /OUTGOINGS 1 No. each comprising the following</u>		
			1 No. 800 Amp. VCB. 26.3KA		
			1 No. Integral Earth switch for line side earthing		
			3 No. dual core CTs 600A/1/1A of 7.5VA burden max and accuracy Class 0.5 for metering and class 5P10 for protection		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			3 No. Cast Resin 11000V/v3/110V/v3/110V/v3 PT Class 0.5/3P accuracy and 30VA burden max with and protection fuses / MCB.		
			1 No. Digital voltmeter with selector switch.		
			1 No. Digital Ammeter with selector switch.		
			1 No. Microprocessor based numerical relays with O/L, E/F and S/C protection with Integrated Arc sensing feature along with trip/lockout / anti-pumping / aux. relays.		
			1 No. Multi-function meter.		
			Set of MCBs for Panel AC/DC		
			Set of MCBs for Main AC/DC		
			Set of Indication lamps LED types		
			TNC Switch, L-R Switch, Pushbuttons for ON-OFF		
	MAT-04036	a	11 KV 800A VCB Panel with 3 Nos. VCBs suitable for 50Hz 3-phase system, suitable for 26.3kA/3sec short circuit withstand capacity & 26.3kA/1sec Internal Arc capacity	1 No	1596381
		b	11 KV 800A VCB Panel with 1 Nos. VCBs suitable for 50Hz 3-phase system, suitable for 26.3kA/3sec short circuit withstand capacity & 26.3kA/1sec Internal Arc capacity	1 No	540000
			Oil Immersed TRANSFORMERS		
391		ELEC-6.3.4	Supply, Transportation, Installation, Testing and Commissioning of copper wound Transformers 33/0.433 KV, Three Phase, 50 Hz, DYN 11, ONAN type , Standard accessories, winding temperature rise of 45°C/40°C first fill oil, having permissible total loss values as per the latest amendment no.4 of BIS in march 2021 for 33 KV as per energy efficiency level - 2 at basic Insulation level conforming to ISS 2026 (Part- I to Part - II), latest amended and IS 1180 Part-I : 2014 described as above with Cable box on HV side and Bus duct on LV Side , ON load Tap changer(OLTC) with RTCC etc., with initial filling of oil as per IS 335-1993 complete and as per the following continuous rating. Makes: As per list of recommended brands as category I.		
	MAT-04037	a	deleted	1 No	

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04038	b	deleted	1 No	
	MAT-04039	c	1250 KVA	1 No	2768625
	MAT-04040	d	1600 KVA	1 No	3433095
	MAT-04041	e	2000 KVA	1 No	4245225
		f	2500 KVA	1 No	4669480
392		ELEC-6.3.5	Supply, Transportation, Installation, Testing and Commissioning of 11/0.433 KV TRANSFORMER with all test reports. The Transformer shall be designed and manufactured as per Energy Efficiency Level - 2 at basic Insulation level conforming to ISS 2026 (Part-I to Part - II) with latest ammended and as per IS 1180 Part-I : 2014 latest ammended, OCTC with initial filling of oil as per IS 335-1993. The basic details of the Transformer are as under. Makes : As per list of recommended brands as category I.		
			1. Quantity : 1 2. Rated KVA: KVA 3. Service & Location: Continuous Outdoor Distribution Transformer 4. Mounting: Plinth. 5. Wound: Copper Double wound 6. Type: Core type oil immersed 7. Cooling: ONAN 8. Temp Rise: 40°C in oil, 45°C by resistance 9. Vector Group: Dyn 11 10. Primary Connection: Delta 11. Nominal Voltage / Current: — 12. Highest system Voltage: 12000V 13. Primary Frequency :50 HZ +/- 3% 14. Number of Phases: 3 15. Primary wires: 3 16. Secondary connection: Star 17. Secondary Volts / Current : 433V 18. Secondary phases: 3 19. Secondary wires: 4 20. Taps on primary winding for primary voltage variation: +5% to - 10% in steps of 2.5% of 7 position (6 Steps)		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			21. Terminal arrangement. a. HV: HT terminal box as per the site condition. b. LV: Cable box suitable to receive ----- --Sq.mm XLPE cable 22. LV: One separate terminal for earthing. 23. Total Losses at 50% Loading [Watts] [Max] --- as per IS 24. Total Losses at 100% Loading [Watts] [Max]--- as per IS 25. Percentage Impedance at 75 deg. C at -----as per IS 26. No Load current: Less than 2% of full load current. 27. Standard Fittings & Accessories. a. Rating and terminal marking plate: One b. Lifting Lugs: Two c. Off-circuit tap switch: One. d. Earthing Terminals : Two e. Radiators (Attachable): Adequate f. Explosion vent with Diaphragm : One g. Conservator with Drain plug: one h. Oil filling hole with cap :One i. Oil level indicator: One j. Dehydrating Silica gel Breather: One k. Terminal Arrangement: HV With Terminal Box l. Terminal Arrangement: LV Cable Box m. Separate Neutral Bushing : One n. Drain cum filter valve with blanking plate: One o. Air release device: One p. Thermometer Pocket: One q. Four: Unidirectional flat rollers r. One :10Cm dial thermometer (Rigid stem type)		
	MAT-04042	a	100 KVA Copper Wound Transformer	1 No	478170
	MAT-04043	b	160 KVA Copper Wound Transformer	1 No	788981
	MAT-04044	c	250 KVA Copper Wound Transformer	1 No	947043
	MAT-04045	d	315 KVA Copper Wound Transformer	1 No	1261838
	MAT-04046	e	500 KVA Copper Wound Transformer	1 No	1656327

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04047	f	Deleted	1 No	
	MAT-04048	g	Deleted	1 No	
393		ELEC-6.3.5 A	Supply, Transportation, Installation, Testing and Commissioning of 11/0.433 KV TRANSFORMER with all test reports. The Transformer shall be designed and manufactured as per Energy Efficiency Level – 1 at basic Insulation level conforming to ISS 2026 (Part- I to Part - II) with latest amended, and as per IS 1180 Part-I : 2014 latest amended, OCTC type with initial filling of oil as per IS 335-1993. The basic details of the Transformer are as under. Makes: As per list of recommended brands as category I.		
		a	1. Quantity : 1 2. Rated KVA: KVA 3. Service & Location: Continuous Outdoor Distribution Transformer 4. Mounting: Plinth. 5. Wound: Copper Double wound 6. Type: Core type oil immersed 7. Cooling: ONAN 8. Temp Rise: 40°C in oil, 45°C by resistance 9. Vector Group: Dyn 11 10. Primary Connection: Delta 11. Nominal Voltage / Current: — 12. Highest system Voltage: 12000V 13. Primary Frequency :50 HZ +/- 3% 14. Number of Phases: 3 15. Primary wires: 3 16. Secondary connection: Star 17. Secondary Volts / Current : 433V 18. Secondary phases: 3 19. Secondary wires: 4 20. Taps on primary winding for primary voltage variation: +5% to - 10% in steps of 2.5% of 7 position (6 Steps) 21. Terminal arrangement. a. HV: HT terminal box as per the site condition. b. LV: Cable box suitable to receive ----- --Sq.mm XLPE cable 22. LV: One separate terminal for earthing. 23. Total Losses at 50% Loading [Watts] [Max] --- as per IS 24. Total Losses at 100% Loading [Watts] [Max]---	1 No	

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			as per IS 25. Percentage Impedance at 75 deg. C at -----as per IS 26. No Load current: Less than 2% of full load current. 27. Standard Fittings & Accessories. a. Rating and terminal marking plate: One b. Lifting Lugs: Two c. Off-circuit tap switch: One. d. Earthing Terminals : Two e. Radiators (Attachable): Adequate f. Explosion vent with Diaphragm : One g. Conservator with Drain plug: one h. Oil filling hole with cap :One i. Oil level indicator: One j. Dehydrating Silica gel Breather: One k. Terminal Arrangement: HV With Terminal Box l. Terminal Arrangement: LV Cable Box m. Separate Neutral Bushing : One n. Drain cum filter valve with blanking plate: One o. Air release device: One p. Thermometer Pocket: One q. Four: Unidirectional flat rollers r. One :10Cm dial thermometer (Rigid stem type)		
			100 KVA Copper Wound Transformer	1 No	409860
			160 KVA Copper Wound Transformer	1 No	676269
			250 KVA Copper Wound Transformer	1 No	811751
			315 KVA Copper Wound Transformer	1 No	1081575
			500 KVA Copper Wound Transformer	1 No	1419710
394		ELEC-6.3.5 B	Supply and Transportation of ISI marked copper wound Transformers 11/0.433 KV, Three Phase, 50 Hz, DYN 11, ONAN type , Standard accessories, winding temperature rise of 45°C/40°C first fill oil, having permissible total loss values not exceeding 7.5%of the maximum total loss values for 11 KV as per Energy Efficiency Level - 2 at basic Insulation level conforming to ISS 2026 (Part- I to Part - II), latest ammended and IS 1180 Part-I : 2014 described as above with Cable box on HV side and Bus duct on LV Side , ON load Tap changer(OLTC)+10% to -10%, with RTCC etc., with initial filling of oil as per IS 335-1993 complete and as per the following continuous rating. Makes : As per list of recommended brands as category I.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-08780	a	630 KVA	1 No	2237170
	MAT-08781	b	1000 KVA	1 No	2819985
			Dry Type transformers		
395		ELEC-6.3.6	Supply ,Transportation of cast Resin (Dry Type) indoor type copper double wound 33KV/0.433 KV, Three Phase 50 Hz Transformers designed and manufactured as per IS 11171/IEC 60726 , ANSI and NEMA Standards with all standard fittings, connected Delta on Primary side and Star on Secondary side with additional neutral brought out on load side 33000/433V with HV off load tap changing +5% to -15% temperature rise by the resistance 90 degrees with terminal arrangement Cable box on HV side and Bus duct on LV Side with off circuit Tap links etc.,, complete Makes: As per list of recommended brands.		
	MAT-04049	a	1000 KVA	1 No	3657000
	MAT-04050	b	1250 KVA	1 No	4554000
	MAT-04051	c	1600 KVA	1 No	5506200
	MAT-04052	d	2000 KVA	1 No	6624000
	MAT-04053	e	2500 KVA	1 No	7452000
396		ELEC-6.3.7	Supply, Transportation, Installation, Testing and Commissioning of 3 Phase, 50 Hz, Dry type, Indoor type copper wound Transformer designed and manufactured as per IS 2026-1977 and IS 11171-1985, connected delta on primary side and Star on secondary side with additional neutral brought out on load side, 11000V / (433V /415V) with HV off load tap changing + 5% to -5% in steps of 2.5%, temperature rise by the resistance 90°C complete with test reports with the following standard mountings. Makes: As per list of recommended brands.		
			1. Rated KVA : KVA (Cast Resin)		
			2. Service: Indoor		
			3. Mounting : Floor.		
			4. Copper wound : Double.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			5. Type of cooling : ANAN.		
			6. Insulation Class : Class F		
			7. Temperature rise by resistance : 90°C		
			8. Vector Group: Dyn 11		
			9. Primary Connection : Delta		
			10. Primary Volts : 11000		
			11. Primary Frequency : 50		
			12. Primary Phases : 3		
			13. Primary wires: 3		
			14. Secondary connection : Star		
			15. Secondary Volts : 433V / 415V		
			16. Secondary phases : 3		
			17. Secondary wires: 4		
			18. Taps on primary winding for primary voltage variation : +5.0% to - 10.0% in steps of 2.5% through links.		
			19. Terminal arrangement.		
			a. HV: Cable end box b. LV : Cable end box		
			20. No load losses (Watts): As per IS specifications		
			21. Load losses (Watts): As per IS specifications		
			22. Impedance(Z%) : As per IS specifications		
			23. Fittings & Accessories.		
			a. Rating and terminal marking plate b. Earthing terminals		
			c. Lifting Lugs		
			d. Winding temperature Indicator		
			e. Separate neutral bushing		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			f. Uni directional flat rollers.		
	MAT-04054	a	250 KVA Copper Wound Cast Resin Transformer		1006940
	MAT-04055	b	315 KVA Copper Wound Cast Resin Transformer		1157475
	MAT-04056	c	500 KVA Copper Wound Cast Resin Transformer		1577455
	MAT-04057	d	630 KVA Copper Wound Cast Resin Transformer		1727990
	MAT-04058	e	750 KVA Copper Wound Cast Resin Transformer		2029060
	MAT-04059	f	1000 KVA Copper Wound Cast Resin Transformer		2555300
		6.4	MAINTENANCE AND REPAIRS OF TRANSFORMERS		
397	MAT-04060	ELEC-6.4.1	Carryout routine maintenance, servicing and testing of 630A to 1000A L.T.ACB by cleaning fixed contacts, moving contacts and arc chutes including servicing and putting the ACB in perfect working condition after setting all relay and ON, OFF mechanism etc., done with only manufacturing companies	1 No	5940
398	MAT-04061	ELEC-6.4.2	Carryout routine maintenance and servicing of LT. Cubical panel board having approximately 15 to 22 Nos of switches cleaning with power blower and servicing the contacts, tightening the connection of incoming and outgoing cables, and checking the operating mechanism for smooth functioning of switches and putting them in smooth working condition.	1 No	3564
399	MAT-04062	ELEC-6.4.3	Routine maintenance of transformer, including testing of insulation resistance, oil breakdown strength. Reconditioning / replacement of silica zel, cleaning of transformer and topping upto oil level if required (extra cost will be paid for oil).	1 No	5346
400	MAT-04063	ELEC-6.4.4	Testing of Transformer oil for dielectric breakdown strength.	1 No	713

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
401		ELEC-6.4.5	Removing the existing transformer from the plinth / Pole and refixing the standby transformer of following capacity including connections etc., complete.....		
	MAT-04064	a	up to 315 KVA	1 No	4158
	MAT-04065	b	500 / 1000 KVA	1 No	5346
402		ELEC-6.4.6	Replacing old and unserviceable gasket of top cover plate of transformer having following capacity. -.....		
	MAT-04066	a	up to 315 KVA	1 No	891
	MAT-04067	b	500 / 1000 KVA	1 No	1188
403		ELEC-6.4.7	Replacing old and unserviceable gasket of bushing for the following Transformer capacity. -.....		
	MAT-04068	a	up to 315 KVA HT,	1 No	416
	MAT-04069	b	500 / 1000 KVA HT,	1 No	891
	MAT-04070	c	up to 315 KVA LT,	1 No	1069
	MAT-04071	d	500 / 1000 KVA LT,	1 No	1782
404		ELEC-6.4.8	Replacement the H T / L. T burnt out winding coils of distribution transformer including rewinding, varnishing and vacuuming etc., duly retaining the removed burnt winding coils by the Contractor / Firm-		
	MAT-04072	a	For copper coils	1 Kg	713
	MAT-04073	b	For aluminum coils	1 Kg	475
405	MAT-04074	ELEC-6.4.9	Insulating HT / LT copper / aluminum coils for Transformers.	1 Kg	387

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
406		ELEC-6.4.10	Painting to transformer with 2 coats Zinc chromate red oxide duly scraping existing paint followed by 2 coats of hammer ton grey paint etc., complete. -.....		
	MAT-04075	a	Upto 500 KVA	1 No	4158
	MAT-04076	b	630 / 1000 KVA	1 No	5346
407		ELEC-6.4.11	Replacing for distribution Transformer by new one.		
	MAT-04077	a	H.T bushing	1 No	416
	MAT-04078	b	H.T bushing with metal parts	1 No	475
	MAT-04079	c	L.T bushing Upto 315 KVA	1 No	238
	MAT-04080	d	L.T bushing 500 / 1000 KVA	1 No	297
	MAT-04081	e	L.T bushing rod with metal parts up to 315 KVA	1 No	594
	MAT-04082	f	L.T bushing rod with metal parts 500/1000 KVA	1 No	2198
408		ELEC-6.4.12	Drying the repaired transformer with appropriate heat / air of following capacity of transformers.-		
	MAT-04083	a	Upto 315 KVA	1 No	5227
	MAT-04084	b	500 / 1000KVA	1 No	6534
409		ELEC-6.4.13	Loading, transportation and unloading of transformer from site to Workshop or vice versa.		
	MAT-04085	a	Upto 500 KVA	1 No	5346
	MAT-04086	b	630 / 1000 KVA	1 No	8316
410	MAT-04087	ELEC-6.4.14	Supply of new and tested transformer oil as per IS-335 - 1972 (per Ltr)	1 Ltr	143

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
411		ELEC-6.4.15	Filtration of transformer oil as per ISS specifications filters to dielectric strength above 40KV		
	MAT-04088	a	at site. (Per Ltr) excluding transportation	1 Ltr	12
	MAT-04089	b	at workshop (per Ltr)	1 Ltr	9
		6.5	OVERHEAD LINES& LINE MATERIALS		
412		ELEC-6.5.1	Supply and transportation of PSCC Poles		
	MAT-04090	a	8.0 Mtr , Working load-140 Kgs	1No	2415
	MAT-04091	b	8.0 Mtr , Working load-200 Kgs	1No	3450
	MAT-04092	c	9.1 Mtr , Working load-280 Kgs	1No	4910
413		ELEC-6.5.2	Supply and transportation of 9 mtr length RS Joist Poles		
	MAT-04093	a	150 x 75 mm (Wt of the pole-140 Kgs)	1No	10500
	MAT-04094	b	175 x 85 mm (Wt of the pole-215Kgs)	1No	16125
	MAT-04095	c	150 x 150 mm (Wt of the pole-333 Kgs)	1No	24975
414		ELEC-6.5.3	Supply and erection of GI stay set of dia..... including stay clamps, turn buckle and GI stay wire tight end through strain insulator including excavation of pit and cc work etc., complete		
	MAT-04096	a	20mm,2.4 mtr long stay rod and anchor plate 380mmx380mmx6.4mm	1 set	2245
	MAT-04097	b	16mm,1.8 mtr long stay rod and anchor plate 380mmx380mmx6.4mm	1 set	1699
415		ELEC-6.5.4	Supply and fixing of 11KV -V- cross arms with duly welded with necessary clamping arrangements etc., complete		
	MAT-04098	a	75x40 mm MS channel including 4 nos 50 x 50 x6 mm packing plates (9 Kgs)	1 No	1494
	MAT-	b	65 x65 x6 MS angle (8.2 Kgs)	1 No	1058

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	04099				
416		ELEC-6.5.5	Supply and fixing of LT 3 phase 4 wire cross arm of length 3' 8" with..... and necessary clamping arrangements, cutting, drilling and welding etc., complete		
	MAT-04100	a	50 x 50 x6 mm MS angle (wt 5.75 Kgs)	1 No	517
	MAT-04101	b	65 x65 x6 MS angle (wt 7 Kgs)	1 No	610
417		ELEC-6.5.6	Supply and fixing of LT 3 phase 5 wire cross arm of length 4' 5" with..... and necessary clamping arrangements, cutting, drilling and welding etc., complete		
	MAT-04102	a	50 x 50 x6 mm MS angle (wt 7.30Kgs)	1 No	667
	MAT-04103	b	65 x65 x6 MS angle (wt 9.60 Kgs)	1 No	841
418	MAT-04104	ELEC-6.5.7	Supply and fixing of LT single phase 3 wire cross arm with 50 x 50 x6 mm MS angle of 2' 5" (wt 4.20 Kgs) and necessary clamping arrangements ,cutting ,drilling and welding etc., complete		411
419	MAT-04105	ELEC-6.5.8	Supply and fixing of 11 KV pin Insulator (IS 731/ 1971) with minimum creepage distance of 300 mm on existing cross arm including all accessories like Hot dip GI spindle and nuts etc.,	220	220
420		ELEC-6.5.9	Supply and fixing of LT porcelain pin insulator as per IS 1447-1997 suitable for working voltage 1100 V including all accessories like Hot dip GI spindle and nuts etc.,		
	MAT-04106	a	100 x 65 mm	each	97
	MAT-04107	b	100 x 85 mm	each	109
421		ELEC-6.5.10	Supply and fixing of LT porcelain shackle insulator as per IS 1443-1979 suitable for working voltage 1100 V including all accessories like Hot dip GI spindle and nuts etc.,		
	MAT-	a	75 x 90 mm	each	169

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	04108				
	MAT-04109	b	100 x 110 mm	each	206
422	MAT-04110	ELEC-6.5.11	Supply and fixing of distribution type lightning arrester 11 KV 5 kA as per IS 3070 with mounting base on the existing DP structure	each	3025
423	MAT-04111	ELEC-6.5.12	Supply and fixing of 100 A 11 KV Horn Gap fuse set as per IS 9385 on existing DP structure with 6 no of 24 KV /22 KV post Insulators (IS 5350, Hot dipped Hardware, fuse wire of required size etc., complete	each	6655
424	MAT-04112	ELEC-6.5.13	Supply and fixing of 11 KV danger plates on the existing poles	each	121
425	MAT-04113	ELEC-6.5.14	Supply and fixing of 11 KV ,400 A 3 phase central post rotating double break type AB switch(isolator) as per IS 9921) without earth blade, gang operated, Horizontal type, operating mechanism with GI spring loaded reverse loop type fixed contact, solid HD electrolytic copper tubular moving contact with silver/Nickel plated at end points,9 Nos post insulators of 12 KV (IS 2594 and IS 5350) ,Hot Dip galvanizing hardware, GI pipe, Nuts and bolts etc., complete.,	each	21780
426		ELEC-6.5.15	Supply and Transportation of Over Head Conductor as per IS 398 (PART - II): 1996		
		a	7/3.55 ACSR Rabbit (214 Kg/KM)	1KM	
		b	7/2.59 ACSR weasel (128 Kg/KM)	1KM	
		c	7/2.11 ACSR squirrel (85 Kg/KM)	1KM	
	MAT-04114	d	100 Sq mm AAA	1KM	102248
	MAT-04115	e	55 Sq mm AAA	1KM	67000
	MAT-04116	f	34 Sq mm AAA	1KM	36000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
427		ELEC-6.5.16	Supply and erecting fencing section having size 2045 mt height from ground level and 1.2 mt width by using angle iron size 50 x50 x6 mm erected in cc foundation 15 x15x40 cm deep. The section of the frame shall be fitted with flat iron support of size 25 x 6 mm on top, bottom and mid-way and chain link Jolley of 3.26 mm dia /10 SWG GI hard wire mesh of 50 x50 mm to the angle iron at every distance of 30 cm , by iron studs complete duly painted with one coat of red oxide and 2 coats of aluminum paint,	1 No	As per DATA
428		ELEC-6.5.17	Supply and erecting double leaf hinged door each 150 cm in width and 180 cm in height using 40 mm dia B grade ISI mark GI pipe from all 4 sides with necessary bends and cross supports of angle iron 45 X45 X5 mm with the door leaf covered with chain links Jolley 50 X 50 mm made from 3.26 mm dia/10 SWG Gi wire with necessary flat iron covering all round with necessary no of spikes of size 10 mm dia at top and bottom at 150 mm apart to match the height of fencing. The door shall have latches and side channel of 100 X50 X5 mm rigidly welded for providing locking arrangement Godrej/ Navtal make medium size lock with duplicate keys, fencing completely erected and painted with anti-corrosive red oxide paint and 2 coats of prescribed enamel paint/silver paint. The Channel iron of size 150X75 mm by 2.5 mtr long shall be provided and erected at both sides of gate.	1 No	As per DATA
429		ELEC-6.5.18	Supply and erecting 50 X50X6 mm angle iron corner support 0.5 mt way from the fence supports fixed at the middle fencing frame and other side in cc foundation 15 X15X 40 cm complete duly painted with 1 coat of red oxide and 2 coats of aluminum paint.	1 No	As per DATA
430		ELEC-6.5.19	Providing and spreading HBG metal of size 40 mm size for 100 mm depth above the ground level.		As per DATA
431	MAT-05548	ELEC-6.5.20	Providing transformer plinth 1.2 x 1.2 x 1.5 mtr in size with necessary excavation in ground at the bottom with 150mm thick 1:2:4 cement concrete raft at the bottom and top and 225mm thick wall constructed in stone masonry and remaking hallow portion shall be filled with stone chips duly plastered	1 No	12100

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			20mm thick outsides including watering etc., complete.		
432	MAT-05549	ELEC-6.5.21	Providing CTPT plinth 600mm x 600mm x 2.1 mtr in size with necessary excavation in ground at the bottom with 150mm thick 1:2:4 cement concrete raft at the bottom and top duly plastered 20mm thick outsides including watering etc., complete.	1 No	7260
		6.6	LIGHTENING PROTECTIVE SYSTEM		
			Advanced LPS		
433	MAT-05550	ELEC-6.6.1 a	Supply of ESE Air Terminal of external wide area of protection system based on proactive Early Steamer Emission (ESE) Technology manufactured in accordance with NFC 17-102:2011 , is made of high-quality, non-corrosive and weather resistant XL-304 Stainless Steel Having triggering advance $t = 30\mu s$, Protection Radius ranging from 48 Meters in Level-I to 71 Meters in Level-IV when installed on a 5 Meters Mast. ESE terminal is capable to withstand Current Impulses of 40kA (5 Shots of 8/20 μs wave shape) and having capturing rod dia of 25mm. Makes: As per list of recommended brands.	1 No	114950
434	MAT-05551	ELEC-6.6.1 b	Supply of ESE Air Terminal of external wide area of protection system based on proactive Early Steamer Emission (ESE) Technology manufactured in accordance with NFC 17-102:2011 , is made of high-quality, non-corrosive and weather resistant XL-304 Stainless Steel Having triggering advance $t = 50\mu s$, Protection Radius ranging from 68 Meters in Level-I to 95 Meters in Level-IV when installed on a 5 Meters Mast. ESE terminal is capable to withstand Current Impulses of 40kA (5 Shots of 8/20 μs wave shape) and having capturing rod dia of 25mm. Makes: As per list of recommended brands.	1 No	121000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
435	MAT-04117	ELEC-6.6.1 c	Supply of ESE Air Terminal of external wide area of protection system based on proactive Early Steamer Emission (ESE) Technology manufactured in accordance with NFC 17-102:2011 , is made of high-quality, non-corrosive and weather resistant XL-304 Stainless Steel Having triggering advance $t = 60\mu s$, Protection Radius ranging from 79 Meters in Level-I to 107 Meters in Level-IV when installed on a 5 Meters Mast. ESE terminal is capable to withstand Current Impulses of 40kA (5 Shots of 8/20 μs wave shape) and having capturing rod dia of 25mm. Makes: As per list of recommended brands.	1 No	137940
436	MAT-04118	ELEC-6.6.2	Installation and commissioning of advanced lighting protection systems which includes: 1. Laying of CC Bed 2. Installation of Lighting Rod 3. Laying of Down conductor 4. Installation of Counter 5. Installation of GI Mast with stay wire. 6. Termination of down conductor to earth bus etc complete.	1 No	35090
437	MAT-04119	ELEC-6.6.3	Supply of 6 Digit Electronic/Mechanical counter Makes: As per list of recommended brands.	1 No	18150
438	MAT-04120	ELEC-6.6.4	Supply of G.I mast of 5 Meters length, 50 mm Dia, with FRP Collar (Insulating Bush) Base Plate & Complete Fitting Accessories with Supporting Guy Wire (Stay Wires) and all fitting accessories	1 Set	7260
439	MAT-04122	ELEC-6.6.5	Supply and Installation of IEC 62561-7 compliant Eco-friendly, Maintenance free, anti-corrosive, lead-free, super conductive, mineral based high-grade earthing compound, to enhance soil conductivity. With resistance <0.12 ohms-meter, Sulphur Free, should be tested as per IEC-62561-7 for resistance Toxic Elements, Leachable elements etc. 25 Kg Bag Makes: As per list of recommended brands.	1 No	2662
440	MAT-04123	ELEC-6.6.6	Supply of Bentonite Moisture Retaining Powder 30 Kg Bag	1 No	206

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
441	MAT-04124	ELEC-6.6.7	Supply of Concrete Earth Pit of Dimensions: Width: 320 mm, Length: 320 mm, Height: 192mm, Weight 30 Kgs, Load bearing Capacity: 5000 Kgs	1 No	1815
			CONVENTIONAL LPS AS PER IS/IEC 62305		
			Air Terminal		
442	MAT-04125	ELEC-6.6.8	Supply, installation, testing and commissioning of 8 mm Aluminum Round Conductor complete as per requirements of DIN EN 50164-2 (VDE 0185 part 202) & VDE 0185-305 (IS/IEC 62305)	1 RM	109
443	MAT-04126	ELEC-6.6.9	Supply, installation, testing and commissioning of Roof conductor holder for parapet- Polyamide Conductor holder: With M8 female thread or diameter 7mm, M8 Screw to connect the conductor holder. Weather and temperature resistant from -35 to +90 degree Celsius tested. Conductor holder @ 1 meter distance	each	61
444	MAT-04127	ELEC-6.6.10	Supply, installation, testing and commissioning of Polyamide roof cable holder for flat roof: DIN 48829 Form B1. Closed form with bottom. Filling weight 1Kg (frost-resistant concrete). Sleeve from polyethylene, black @ 1 meter distance.	each	157
445	MAT-04128	ELEC-6.6.11	Supply, installation, testing and commissioning of Fang Fix Junior system - Inclusive of Al interception rod of 1Mtr length (10mm dia), Quick mounting of the interception rod in the base using plug technology	each	1997
446	MAT-04129	ELEC-6.6.12	Supply, installation, testing and commissioning of cross universal connector: For T and cross connection, to route vertical down conductor /mesh formation made of hot dipped galvanized iron with necessary screws etc as required. Installed with 4 hexagonal bolts M8*25 with M8 hexagonal nuts	each	160
447	MAT-04130	ELEC-6.6.13	Supply, installation, testing and commissioning of expansion piece with connector: For equalizing temperature related length changes. Necessary on conductors of length over 20 meters. For round conductor Rd 8/ALU connector: For T cross and parallel connectors. Quick installation using hexagonal bolt M10X30 high-grade hot dip galvanized. Confirms to the requirements according to DIN VDE 0185-305 (IS-IEC 2305)(2nos/expansion piece).	each	479

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			DOWN CONDUCTOR		
448	MAT-04131	ELEC-6.6.14	Supply, installation, testing and commissioning of 8 mm Aluminum Round Conductor complete as specified in drawing & meets the requirements of DIN EN 50164-2 (VDE 0185 part 202) & VDE 0185-305 (IS/IEC 62305)	1 RM	109
449	MAT-04132	ELEC-6.6.15	Supply, installation, testing and commissioning of Roof conductor holder for parapet- Polyamide Conductor holder: With M8 female thread or diameter 7mm, M8 Screw to connect the conductor holder. Weather and temperature resistant from -35 to +90 degree Celsius tested. Conductor holder @ 1 meter distance	each	61
450	MAT-04133	ELEC-6.6.16	Supply, installation, testing and commissioning of Test Joint (Folding Clamp) suitable to connect 8mm round conductor and max by 30x3 mm GI strip as specified in drawing and directed by Engineer	each	375
451	MAT-04134	ELEC-6.6.17	Supply, installation, testing and commissioning of Lightning counter - To count no of lightning strike & it can record the date and time of the lightning incident also tested as per IEC 62561-6.	each	19965
		6.7	EARTHING		
452	MAT-04135	ELEC-6.7.1	Providing earth electrode of low carbon steel rod, UL listed of 17.2 mm dia, 3 Mtr long, coated with copper of 254 microns thickness, CPRI tested for short time current withstand test of 25 kA, coating thickness, environmental test (Salt Mist Test), Bend test, Tensile strength, Yield / tensile ratio, Electrical Resistivity test, complete with clamps and 2 bags of (Earth plus ULTRA /TIRUMALA) high grade earthing compound IEC 62561-7 complaint Eco-friendly, Maintenance free, anti-corrosive, lead-free, super conductive, mineral based high-grade earthing compound, to enhance soil conductivity. With resistance <0.20 ohms-meter, should be leach proof & Sulphur free complete with earth inspection chamber of dimensions: width: 320 mm x 320 mm, Height : 192 mm, weight : 30 Kgs, Load bearing capacity : 5000 Kgs	1 No	11495

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
453	MAT-04136	ELEC-6.7.2	Providing earthing as per IS 3043 with perforated 3 mtr long 40 mm dia B class GI pipe including all accessories like nuts bolts reducer, nipple, wire meshed funnel and CC finished chamber covered with hinged type with CI cover, CI frame of size 300 X 300 mm and embodying the pipe complete with alternate layers of salt and coke /charcoal/bentonite powder testing earth resistance as required etc., complete	1 No	As per DATA
454	MAT-04137	ELEC-6.7.3	Providing earthing as per IS 3043 with GI earth plate of size 600 x600 x 6 mm by embodying 3 to 4 mtr below the ground level with 40 mm dia GI B class perforated pipe including all including all accessories like nuts bolts reducer, nipple, wire meshed funnel and CC finished chamber covered with hinged type with CI cover ,CI frame of size 300 X 300 mm and embodying the pipe complete with alternate layers of salt and coke /charcoal/bentonite powder testing earth resistance as required etc., complete	1 No	As per DATA
455	MAT-04138	ELEC-6.7.4	Providing earthing as per IS 3043 with copper earth plate of size 600 x 600 x 3.15 mm by embodying 3 to 4 mtr below the ground level with 40mm dia 'B' Class G.I Pipe by excavating a pit to a depth of 3 to 4 Mtr in all soils for Sophisticated Electronic equipment as per National Electric Code and earth connection from electrode Copper strip of 25mm x 5mm x 200mm length to be bolted with nut bolts to G.I. pipe including 25mm x 3mm copper strip of 6Mtrs length connected from plate to Copper strip including filling with 20Kg Salt and 40Kg Charcoal or 40Kg bentonite powder including all accessories like nuts bolts reducer, nipple, wire meshed funnel and CC finished chamber covered with hinged type with CI cover ,CI frame of size 300 X 300 mm ,testing earth resistance as required etc., complete	1 No	As per DATA

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
456	MAT-04139	ELEC-6.7.5	Providing independent earthing for Important equipment with 100mm dia Heavy gauge C.I (Cast iron) pipe with Flange 2.5m long enclosed in C.C/ brick masonry chamber of 450m x 450m x 400mm with R.C.C. Slab cover duly providing staggered holes filling with salt and charcoal from the bottom of the pipe giving earth connection from electrode through G.I strip of 40 x 6mm x 200mm length with all accessories and labour charges complete, as per IS specifications 732/1982 (Part II)	1 No	9075
457		ELEC-6.7.6	PROVIDING OF INDEPENDENT CHEMICAL EARTHING AFTER EXCAVATING AN EARTH PIT. THE EARTH ELECTRODES, 50MM DIA, WALL THICKNESS, 3.25MM, 3 MTR LONG GALVANIZED GI PIPE, STRIP IN PIPE SYSTEM FITTED WITH 40X6X3100MM GI STRIP FROM TOP TO BOTTOM, TERMINAL HOLE OF 12MM, PIPE FILLED WITH CONDUCTIVE CRYSTALLINE COMPOUND ,INCLUDING 2 BAG OF EARTH LIFE COMPOUND (25 KGS EACH) AS PER IS 3043. with earth inspection chamber of dimensions: Width :320 mm x 320 mm, Height: 192 mm, Weight: 30 Kgs, Load bearing capacity: 5000 Kgs including drilling of bore in any kind of soil.	1 No	8955
458		ELEC-6.7.7	PROVIDING OF INDEPENDENT CHEMICAL EARTHING AFTER EXCAVATING AN EARTH PIT. THE EARTH ELECTRODES, 50MM DIA, WALL THICKNESS, 3.25MM, 3 MTR LONG COPPER BONDED (250 MICRONS) MS PIPE, STRIP IN PIPE SYSTEM FITTED WITH 40X6X3100MM COPPER BONDED STRIP FROM TOP TO BOTTOM, TERMINAL HOLE OF 12MM, PIPE FILLED WITH CONDUCTIVE CRYSTALLINE COMPOUND, INCLUDING 2 BAG OF EARTH LIFE COMPOUND (25 KGS EACH) AS PER IS 3043. with earth inspection chamber of dimensions: Width: 320 mm x 320 mm, Height: 192 mm, Weight: 30 Kgs, Load bearing capacity: 5000 Kgs including drilling of bore in any kind of soil.	1 No	9675

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
459		ELEC-6.7.8	PROVIDING OF INDEPENDENT CHEMICAL EARTHING AFTER EXCAVATING AN EARTH PIT. THE EARTH ELECTRODES, 50MM DIA, WALL THICKNESS, 1.8MM, 3 MTR LONG PURE COPPER PIPE, STRIP IN PIPE SYSTEM FITTED WITH 40X6X3100MM PURE COPPER STRIP FROM TOP TO BOTTOM, TERMINAL HOLE OF 12MM, PIPE FILLED WITH CONDUCTIVE CRYSTALLINE COMPOUND, INCLUDING 2 BAGS OF EARTH LIFE COMPOUND (25 KGS EACH) AS PER IS 3043. with earth inspection chamber of dimensions: Width: 320 mm x 320 mm, Height: 192 mm, Weight: 30 Kgs, Load bearing capacity: 5000 Kgs including drilling of bore in any kind of soil.	1 No	17865
			EARTH CONDUCTORS		
460		ELEC-6.7.6	Supply and laying of following sizes Earth wire/Strip in horizontal /Vertical run in Ground/surface/Recess including, riveting, soldering, saddles, making connection etc as required		
	MAT-04140	a	6 SWG Copper wire (0.16 Kgs/1 Mtr)	1 Mtr	146
	MAT-04141	b	8 SWG Copper wire(0.1155Kgs/1Mtr)	1 Mtr	106
	MAT-04142	c	10 SWG Copper wire(0.075Kgs/1Mtr)	1 Mtr	69
	MAT-04143	d	6 SWG GI wire (0.192 Kgs/Mtr)	1 Mtr	16
	MAT-04144	e	8 SWG GI wire(0.104Kgs/1Mtr)	1 Mtr	10
	MAT-04145	f	10 SWG GI wire(0.067Kgs/1Mtr)	1 Mtr	4
	MAT-04146	g	20mm x 3mm Copper Flat(0.529Kgs/1Mtr)	1 Mtr	486
	MAT-04147	h	25mm x 3mm Copper Flat (0.663Kgs/1Mtr)	1 Mtr	608
	MAT-04148	i	32 mm x 6mm Copper Flat (1.9 Kgs/Mtr)	1 Mtr	1743
	MAT-	j	50 mm x 6mm Copper Flat (2.680Kgs/1Mtr)	1 Mtr	2460

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	04149				
	MAT-04150	k	25mm x 3mm GI Flat (0.656 Kgs/Mtr)	1 Mtr	55
	MAT-04151	l	25mm x 6mm GI Flat (1.18Kgs/1Mtr)	1 Mtr	97
	MAT-04152	m	32 mm x 6mm GI Flat (1.6 kgs/Mtr)	1 Mtr	137
	MAT-04153	n	50 mm x 6mm GI Flat (2.5 Kgs/mtr)	1 Mtr	208
			SECTION 7		
		7.0	LOCAL AREA NETWORK		
461		ELEC-7.1.1	Supply, laying ,testing and commissioning of 4-pair, Cat6 Solid (Third party ETL Intertek tested up to 600 MHZ) to support 1Gbps with Cross (+) filler pair separator & PVC sheath 23 AWG, STP/UTP Cable , Meets or exceeds ANSI/TIA-568-C.2 and UL Listed &RoHS Compliant in the existing raceways /PVC conduits including making connections to information outlets and patch panels with ferruling at both ends for identification with necessary tools for punching stripping crimping and testing required etc., complete. Makes: As per list of recommended brands as Category I.		
	MAT-04154	a	6 UTP cable	RM	45
	MAT-05553	b	6 STP cable	RM	70
462	MAT-04155	ELEC-7.1.2	Supply installation testing and commissioning of 2nos of Cat6 Tool less built-in crimping mechanism Information Outlet with Dust Cover Exceed ANSI/ TIA-568-C.2 and ISO/IEC 11801 standards with 2module face plate for Category 6 component performance & Compatible to T568A,T568B wiring pattern and UL-940V0 Rated Plastic &RoHS Compliant Makes: As per list of recommended brands as Category I.		
				each	1050

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
463	MAT-04156	ELEC-7.1.3	Supply installation testing and commissioning of 1 no of Cat6 Tool less built-in crimping mechanism Information Outlet with Dust Cover Exceed ANSI/ TIA-568-C.2 and ISO/IEC 11801 standards with 1 module face plate for Category 6 component performance & Compatible to T568A, T568B wiring pattern and UL-940V0 Rated Plastic & RoHS Compliant Makes: As per list of recommended brands as Category I.	each	520
464		ELEC-7.1.4	Supply installation testing and commissioning of 4 pair 23AWG Cat-6 UTP, flexible, double ended LSZH patch cords along with 2 nos of RJ 45 connectors with strain relief boots Compatible to T568A, T568B specifications including making connections to information outlets. Makes: As per list of recommended brands as Category I.		
	MAT-04157	a	1 mtr / 3 ft	each	253
	MAT-04158	b	2 mtr / 7 ft	each	298
	MAT-04159	c	3 mtr / 10 ft	each	343
465	MAT-04160	ELEC-7.1.5	Supply installation testing and commissioning of LC Pigtails LSZH 1mtr for fiber core connectivity Makes: As per list of recommended brands as Category I.		
		a	Single Mode	each	290
		b	Multi Mode	each	360
466	MAT-04161	ELEC-7.1.6	Supply installation testing and commissioning of SC Pigtails LSZH 1mtr for fiber core connectivity. Makes: As per list of recommended brands as Category I.		
		a	Single Mode	each	405
		b	Multi Mode	each	494
467	MAT-04162	ELEC-7.1.7	Supply installation testing and commissioning of LC Pigtails LSZH 2mtr for fiber core connectivity. Makes: As per list of recommended brands as Category I.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		a	Single Mode	each	315
		b	Multi Mode	each	373
468	MAT-04163	ELEC-7.1.8	Supply installation testing and commissioning of SC Pigtails LSZH 2mtr for fiber core connectivity. Makes: As per list of recommended brands as Category I.		
		a	Single Mode	each	420
		b	Multi Mode	each	520
469		ELEC-7.1.9	Supply installation testing and commissioning of Indoor Multimode [62.5/125um] glass Fiber Optic Cable as per latest amendments of TIA /EIA 568 B.3, GR 409 CORE / UL listed NEC 770 Standards in existing raceways/ PVC Conduits/ slotted channels including making Terminations to active passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required. Makes: As per list of recommended brands as Category I.		
	MAT-04164	a	4 fiber		95
	MAT-04165	b	6 fiber		120
	MAT-04166	c	12 fiber		210
470		ELEC-7.1.9A	Supply installation testing and commissioning of Indoor Single mode [9/125um] glass Fiber Optic Cable as per latest amendments of TIA /EIA 568B.3 , GR 409 CORE / UL listed NEC 770 Standards in existing Raceways/PVC Conduits/ slotted channels including making Terminations to active passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required Makes: As per list of recommended brands as Category I.		
			4 fiber		90
			6 fiber		110
			12 fiber		150

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
471		ELEC-7.1.10	Supply installation testing and commissioning Outdoor, steel tape armoured multimode [62.5/125um] glass Fiber Optic Cable as per latest amendments of TIA /EIA 568B.3 , GR 20 CORE/ UEC 794-1/ EN 187000 Standards in existing MSPVC Conduits/ hume pipe including making terminations to active passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required. Makes: As per list of recommended brands as Category I.		
	MAT-04167	a	4 fiber		108
	MAT-04168	b	6 fiber		133
	MAT-04169	c	12 fiber		220
472		ELEC-7.1.10 A	Supply installation testing and commissioning Outdoor, steel tape armoured Single mode [9/125um] glass Fiber Optic Cable as per latest amendments of TIA /EIA 568B.3 , GR 20 CORE/ UEC 794-1/ EN 187000 Standards in existing MSPVC Conduits/ hume pipe including making terminations to active passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required. Makes: As per list of recommended brands as Category I.		
			4 fiber		92
			6 fiber		115
			12 fiber		155
473	MAT-04170	ELEC-7.1.11	Supply, Installation and Testing and commissioning of indoor 1 pair multimode [62.5/125um] glass Fiber Optic Patch Cords of One mtr length as per latest amendments of TIA /EIA 568B.3 and IEC 794 Standard Specifications including ST II / SC/FC/MT/ PC connectors at both ends as per requirements. Makes: As per list of recommended brands as Category I.	mtr	1800
474		ELEC-7.1.11A	Supply, Installation and Testing and commissioning of indoor 1 pair Singlemode [9/125um] glass Fiber Optic Patch Cords of One mtr length as per latest ammendments of TIA/EIA 568B.3 and IEC 794 Standard Specifications including ST II / SC/FC/MT/PC connectors at both ends as per requirements. Makes: As per list of recommended brands as	mtr	1790

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Category I.		
475		ELEC-7.1.12	Supply, Installation Testing and commissioning of 19 " Rack mounted/surface mounted aluminum / CRS powder coated multimode glass Fiber Optic Cable Patch panel/ LIU along with cable tray/ fiber management system , adapters for ST II/ SC/FC/MT/PC/LC connections including making connections to active / passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required. Makes: As per list of recommended brands as Category I.		
	MAT-04171	a	8 Ports	1 No	7334
	MAT-04172	b	12 Ports	1 No	9601
	MAT-04173	c	24 Ports	1 No	18169
	MAT-04174	d	36 Ports	1 No	20535
476		ELEC-7.1.12 A	Supply, Installation Testing and commissioning of 19 " Rack mounted/surface mounted aluminum / CRS powder coated Single mode glass Fiber Optic Cable Patch panel/ LIU along with cable tray/ fiber management system , adapters for ST II/ SC/FC/MT/PC/LC connections including making connections to active / passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required. Makes: As per list of recommended brands as Category I.		
		a	8 Ports	1 No	7334
		b	12 Ports	1 No	9601
		c	24 Ports	1 No	18169
		d	36 Ports	1 No	20535
477		ELEC-7.1.13	Supply, Installation, Testing and Commissioning of Rack mounted 19", Cat 6 UTP,1.5-1.6 MM CRS chasis, powder coated Modular Patch Panels with collapsible shutters on jacks to support latest amendments of TIA / EIA Cat 6 Specifications in Existing Communication Rack along with necessary connections of Cat 6 UTP Cables, With Rear Cable management trays and clamps. Makes: As per list of recommended brands as Category I..		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04175	a	6 Ports	1 No	4138
	MAT-04176	b	12 Ports	1 No	5136
	MAT-04177	c	18 Ports	1 No	6420
	MAT-04178	d	24 Ports	1 No	7847
478		ELEC-7.1.14	Supply, Installation, Testing and Commissioning of Wall mounted Communication rack in one section with glass doors, swing handles, lock, Top and Bottom Cable entries, supports for mounting rack on wall, Cable managers, Fan tray with 2 x 230 Volt fans, Equipment mounting hardware, wire managers, power supply box for supplying power to hubs, fans etc., along with earth continuity kit, MCB, indicator, moulded power supply cable, Blank panels, sliding shelves etc. Makes: As per list of recommended brands as Category I.		
	MAT-04179	a	6 U(44 mm) wall mounted	1 No	8299
	MAT-04180	b	9 U(44 mm) wall mounted	1 No	9819
	MAT-04181	c	12 U(44 mm) wall mounted	1 No	9945
	MAT-04182	d	15 U(44 mm) wall mounted	1 No	10988
479		ELEC-7.1.15	Supply, Installation, Testing and Commissioning of Floor mounted communication rack in on Section with glass doors, swing handles, lock on both doors, Top and Bottom Cable entries with gland plates, Castor with brakes , 7 no Cable managers, 1 no Fan tray with 2 x 230 Volt fans, Equipment mounting hardware, wire managers, power supply box for supplying power to hubs, fans etc., along with earth continuity kit, MCB, indicator, moulded power supply cable, Blank panels of 1u / 2 u, sliding shelves. Frame of communication rack should be made of heavy grade Aluminum profile PS grey painted and panels should be made from CRCA steel 18 SWG RS Beige painted. Makes: As per list of recommended brands as Category I.		
	MAT-	a	22 U (44 mm) Floor Standing Rack	1 No	35989

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	04183				
	MAT-04184	b	27 U (44 mm) Floor Standing Rack	1 No	42228
	MAT-04185	c	36 U (44 mm) Floor Standing Rack	1 No	58095
	MAT-04186	d	42 U (44 mm) Floor Standing Rack 800WX1000D	1 No	60970
			MANAGEBLE NET WORK SWITCHES		
480	MAT-04187	ELEC-7.1.16	Supply, Installation, Testing and Commissioning of Small Business 24 port Gigabit Managed Switch. Makes: As per list of recommended brands as Category I.	1 No	30600
481	MAT-04188	ELEC-7.1.17	Supply, Installation, Testing and Commissioning of Small Business 48 port Gigabit Managed Switch. Makes: As per list of recommended brands as Category I.	1 No	76000
482	MAT-04189	ELEC-7.1.18	Supply & Fixing of small business 8 port Gigabit POE Managed Switch. Makes: As per list of recommended brands as Category I..	1 No	25200
483	MAT-04190	ELEC-7.1.19	Supply & Fixing of small business 24 port Gigabit POE Managed Switch. Makes: As per list of recommended brands as Category I.	1 No	45900
484	MAT-04191	ELEC-7.1.20	Supply, Installation, Testing and Commissioning of Small Business 24 port Gigabit Managed Switch Makes: As per list of recommended brands as Category I..	1 No	deleted
485	MAT-04192	ELEC-7.1.21	Supply, Installation, Testing and Commissioning of Layer2 , Catalyst 1000 24T-4G-L 24GE port, 10/100/1000 4X 1G SFP Uplink Ports, LAN base Manageable Network switch. Makes: As per list of recommended brands as Category I..	1 No	68773
486	MAT-04193	ELEC-7.1.22	Supply, Installation, Testing and Commissioning of Layer2 , Catalyst 1000 48T-4G-L 48GE port, 10/100/1000 4 X1 G SFP Uplink Ports LAN base Manageable Network switch. Makes: As per list of recommended brands as	1 No	113400

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Category I..		
487	MAT-04194	ELEC-7.1.23	Supply, Installation, Testing and Commissioning of Layer2 , Catalyst 1000 24P-4G-L 24 GE port, POE 10/100/1000 4 X 1G SFP Uplink LAN base Manageable Network switch. Makes: As per list of recommended brands as Category I.	1 No	114300
488	MAT-04195	ELEC-7.1.24	Supply, Installation, Testing and Commissioning of Layer2 , Catalyst 1000 48P-4G-L 48 GE port, POE 10/100/1000 4 X 1G SFP Uplink LAN base Manageable Network switch. Makes: As per list of recommended brands as Category I.	1 No	1,82,700
489	MAT-04196	ELEC-7.1.25	Supply, Installation, Testing and Commissioning of Layer2 , Catalyst 1000 Plus 24 port, GigE LAN base Manageable Network switch. Makes: As per list of recommended brands as Category I.	1 No	Deleted
490	MAT-04197	ELEC-7.1.26	Supply, Installation, Testing and Commissioning of Layer2 , Catalyst 1000 Plus 48 port, GigE LAN base Manageable Network switch. Makes: As per list of recommended brands as Category I.	1 No	Deleted
491	MAT-04198	ELEC-7.1.27	Supply & Fixing of WIFI Access point with mounting accessories etc., complete. Makes: As per list of recommended brands as Category I.	1 No	32175
492		ELEC-7.1.28	Supply, Installation, Testing and Commissioning of Layer3 , Catalyst 9300L-24T-4G-E 24 GE port, 10/100/1000 4 X 1G SFP Uplink ports LAN base Manageable Network switch. Makes: As per list of recommended brands as Category I.	1 No	6,10,900
493		ELEC-7.1.29	Supply, Installation, Testing and Commissioning of 1G SFP Long Range (Single) Module up to 10KM - Makes: As per list of recommended brands as Category I.	1 No	23000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Category II		
494		ELEC-7.1.30	Supply, laying ,testing and commissioning of 4-pair, Cat6 Solid Performance verified up to 450 MHZ. support 1Gbps with Cross (+) filler pair separator & FRPVC sheath 23 AWG, STP/UTP Cable , Meets or exceeds ANSI/TIA-568-C.2 and ISO/IEC 11801-1 UL Listed &RoHS Compliant in the existing raceways /PVC conduits including making connections to information outlets and patch panels with ferruling at both ends for identification with necessary tools for punching stripping crimping and testing required etc., complete. Makes: As per list of recommended brands as category II.		
			6 UTP cable	RM	34
			6 STP cable	RM	54
495		ELEC-7.1.31	Supply installation testing and commissioning of 2nos of Cat6 Unshielded RJ45 Keystones Jack Punchdown Type with Collapsible Door Exceed ANSI/ TIA-568-C.2 and ISO/IEC 11801 standards with 2module face plate for Category 6 component performance & Compatible to T568A,T568B wiring pattern and UL-940V0 Rated Plastic &RoHS Compliant Makes: As per list of recommended brands as category II.	Each	630
496		ELEC-7.1.32	Supply installation testing and commissioning of 1no of Cat6 Unshielded RJ45 Keystones Jack Punchdown Type with Collapsible Door Exceed ANSI/ TIA-568-C.2 and ISO/IEC 11801 standards with 1module face plate for Category 6 component performance & Compatible to T568A, T568B wiring pattern and UL-940V0 Rated Plastic &RoHS Compliant Makes: As per list of recommended brands as category II.	Each	360
497		ELEC-7.1.33	Supply installation testing and commissioning of 4 pair 24AWG Cat-6 UTP, flexible, double ended patch cords LSZH along with 2 nos of RJ 45 connectors with strain relief boots Compatible to T568A, T568B specifications including making connections to information outlets Makes: As per list of recommended brands as category II.		
			1 mtr / 3 ft patch cord	Each	189
			2 mtr /7 ft patch cord	Each	223

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			3 mtr /10 ft patch cord	Each	258
498		ELEC-7.1.34	Supply installation testing and commissioning of LC Pigtails LSZH 1mtr for fiber core connectivity Makes: As per list of recommended brands as category II.		
			Single Mode	Each	217
			Multi Mode	Each	270
499		ELEC-7.1.35	Supply installation testing and commissioning of SC Pigtails LSZH 1mtr for fiber core connectivity. Makes: As per list of recommended brands as category II.		
			Single Mode	Each	303
			Multi Mode	Each	370
500		ELEC-7.1.36	Supply installation testing and commissioning of LC Pigtails LSZH 2mtr for fiber core connectivity. Makes: As per list of recommended brands as category II.		
			Single Mode	Each	236
			Multi Mode	Each	280
501		ELEC-7.1.37	Supply installation testing and commissioning of SC Pigtails LSZH 2mtr for fiber core connectivity. Makes: As per list of recommended brands as category II.		
			Single Mode	Each	315
			Multi Mode	Each	390
502		ELEC-7.1.38	Supply installation testing and commissioning of Indoor Multimode [62.5/125um] glass Fiber Optic Cable HDPE as per latest amendments of TIA /ANSI/ 568 B.3, GR 20 CORE / UL listed NEC 770 Standards in existing raceways/ PVC Conduits/ slotted channels including making Terminations to active passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required. Makes: As per list of recommended brands as category II.		
			4 fiber	Each	72

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			6 fiber	Each	86
			12 fiber	Each	120
503		ELEC-7.1.39	Supply installation testing and commissioning of Indoor Single mode [9/125um] glass Fiber Optic Cable HDPE as per latest amendments of TIA /ANSI/ 568 B.3, GR 20 CORE / UL listed NEC 770 Standards in existing raceways/ PVC Conduits/ slotted channels including making Terminations to active passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required. Makes: As per list of recommended brands as category II.		
			4 fiber	Each	65
			6 fiber	Each	80
			12 fiber	Each	110
504		ELEC-7.1.40	Supply installation testing and commissioning Outdoor, steel tape armoured multimode[62.5/125um] glass Fiber Optic Cable HDPE as per latest amendments of TIA /EIA 568B.3 , GR 20 CORE/ UEC 794-1/ EN 187000 Standards in existing MSPVC Conduits/ hume pipe including making terminations to active passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required. Makes: As per list of recommended brands as category II.		
			4 fiber	Each	80
			6 fiber	Each	90
			12 fiber	Each	160
505		ELEC-7.1.41	Supply installation testing and commissioning Outdoor, steel tape armoured Single mode[9/125um] glass Fiber Optic Cable HDPE as per latest amendments of TIA /EIA 568B.3, GR 20 CORE/ UEC 794-1/ EN 187000 Standards in existing MSPVC Conduits/ hume pipe including making terminations to active passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required. Makes: As per list of recommended brands as category II.		
			4 fiber	Each	68
			6 fiber	Each	83
			12 fiber	Each	115
506		ELEC-	Supply, Installation and Testing and commissioning	Each	1300

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		7.1.42	of indoor 1 pair multimode [62.5/125um] glass Fiber Optic Patch Cords of three mtr length as per latest amendments of TIA /EIA 568B.3 and IEC 794 Standard Specifications including ST II / SC/FC/MT/ PC connectors at both ends as per requirements. Makes: As per list of recommended brands as category II.		
507		ELEC-7.1.43	Supply, Installation and Testing and commissioning of indoor 1 pair Single mode [9/125um] glass Fiber Optic Patch Cords of three mtr length as per latest amendments of TIA /EIA 568B.3 and IEC 794 Standard Specifications including ST II / SC/FC/MT/ PC connectors at both ends as per requirements. Makes: As per list of recommended brands as category II.	Each	1250
508		ELEC-7.1.44	Supply, Installation Testing and commissioning of 19 " Rack mounted/surface mounted aluminum / Black matt powder coated multimode glass Fiber Optic Cable Patch panel/ along with cable tray/ fiber management system , adapters for ST II/ SC/LC /MT/PC /LC connections including making connections Cable management rings are used to ensure flexibility of pigtailed and excess fibers to active / passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required. Makes: As per list of recommended brands as category II.		
			8 Ports	Each	5500
			12 Ports	Each	7200
			24 Ports	Each	8260
			36 Ports	Each	10400
509		ELEC-7.1.45	Supply, Installation Testing and commissioning of 19 " Rack mounted/surface mounted aluminum / Black matt powder coated Single mode glass Fiber Optic Cable Patch panel/ along with cable tray/ fiber management system , adapters for ST II/ SC/LC /MT/PC connections including making connections Cable management rings are used to ensure flexibility of pigtailed and excess fibers to active / passive equipment with ferruling at both ends for identification with necessary tools for Terminations and testing required. Makes: As per list of recommended brands as		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			category II.		
			8 Ports	Each	5500
			12 Ports	Each	7200
			24 Ports	Each	8260
			36 Ports	Each	10400
510		ELEC-7.1.46	Supply, Installation, Testing and Commissioning of Rack mounted 19", UTP Patch Panel is a elegant design patch panel. The panel has two-piece structure design combined with both 24-port panel and cable management. The panel has 180-degree punch down design for convenient network terminations. The panels cable management shelf ensures proper routing of cables with proper bend radius compliance to avoid strain relief. Exceeds ANSI/TIA-568-C.2 Standard and supports 1000-Base-T. and clamps. Makes: As per list of recommended brands as category II.		
			6 Ports	Each	3100
			12 Ports	Each	3850
			18 Ports	Each	4500
			24 Ports	Each	4800
511		ELEC-7.1.47	Supply, Installation, Testing and Commissioning of Wall mounted Communication rack in one section with glass doors, swing handles, lock, Top and Bottom Cable entries, supports for mounting rack on wall, Cable managers, Fan tray with 2 x 230 Volt fans, Equipment mounting hardware, wire managers, power supply box for supplying power to hubs, fans etc., along with earth continuity kit, MCB, indicator, moulded power supply cable, Blank panels, sliding shelves etc. Makes: As per list of recommended brands as category II.		
			6 U(44 mm) wall mounted	Each	7470
			9 U(44 mm) wall mounted	Each	8830
			12 U(44 mm) wall mounted	Each	8950
			15 U(44 mm) wall mounted	Each	9890

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
512		ELEC-7.1.48	Supply, Installation, Testing and Commissioning of Floor mounted communication rack in one section with glass doors, swing handles, lock on both doors, Top and Bottom Cable entries with gland plates, Castor with brakes , 7 no Cable managers, 1 no Fan tray with 2 x 230 Volt fans, Equipment mounting hardware, wire managers, power supply box for supplying power to hubs, fans etc., along with earth continuity kit, MCB, indicator, moulded power supply cable, Blank panels of 1u / 2 u, sliding shelves. Frame of communication rack should be made of heavy grade Aluminum profile PS grey painted and panels should be made from CRCA steel 18 SWG RS Beige painted Makes: As per list of recommended brands as category II.		
			22 U (44 mm) Floor Standing Rack	Each	32000
			27 U (44 mm) Floor Standing Rack	Each	38000
			36 U (44 mm) Floor Standing Rack	Each	52000
			42 U (44 mm) Floor Standing Rack	Each	54873
			MANAGEBLE NET WORK SWITCHES		
513		ELEC-7.1.49	Supply, Installation, Testing and Commissioning of Small Business 24 port Gigabit Managed Switch. Makes: As per list of recommended brands as category II.	1 No	20360
514		ELEC-7.1.50	Supply, Installation, Testing and Commissioning of Small Business 48 port Gigabit Managed Switch. Makes: As per list of recommended brands as category II.	1 No	41000
515		ELEC-7.1.51	Supply & Fixing of small business 8 port Gigabit POE Managed Switch. Makes: As per list of recommended brands as category II.	1 No	18599
516		ELEC-7.1.52	Supply & Fixing of small business 24 port Gigabit POE Managed Switch. Makes: As per list of recommended brands as category II.	1 No	27000
517		ELEC-7.1.53	Supply, Installation, Testing and Commissioning of Layer2, 24GE port 10/100 /1000 + 4 1/10G SFP Uplink Ports, LAN base Manageable Network switch.	1 No	34000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: As per list of recommended brands as category II.		
518		ELEC-7.1.54	Supply, Installation, Testing and Commissioning of Layer2, 48GE port 10/100 /1000 + 4 1/10G SFP Uplink Ports, LAN base Manageable Network switch.. Makes: As per list of recommended brands as category II.	1 No	54300
519		ELEC-7.1.55	Supply, Installation, Testing and Commissioning of Layer2, 24GE port POE 10/100 /1000 + 4 1/10G SFP Uplink Ports, LAN base Manageable Network switch. Makes: As per list of recommended brands as category II.	1 No	48340
520		ELEC-7.1.56	Supply, Installation, Testing and Commissioning of Layer2, 48GE port POE 10/100 /1000 + 4 1/10G SFP Uplink Ports, LAN base Manageable Network switch.. Makes: As per list of recommended brands as category II.	1 No	94580
521		ELEC-7.1.57	Supply, Installation, Testing and Commissioning of Layer3 , 24 GE port, 10/100/1000 4 X 1G SFP Uplink ports LAN base Manageable Network switch. Makes: As per list of recommended brands.	1 No	208978
522		ELEC-7.1.58	Supply & Fixing of WIFI Access point with mounting accessories etc., complete. Makes: As per list of recommended brands as category II.	1 No	22500
523		ELEC-7.1.59	Supply, Installation, Testing and Commissioning of 1G SFP Long Range (Single) Module up to 10KM - Makes: As per list of recommended brands as category II..	1 No	8320
524		ELEC-7.1.60	Supply, Installation, Testing and Commissioning of Small Business 8 port Gigabit Un managed Switch. Makes: As per list of recommended brands as category II.	1 No	9800
525		ELEC-7.1.61	Supply, Installation, Testing and Commissioning of Small Business 16 port Gigabit Un managed Switch. Makes: As per list of recommended brands as category II.	1 No	12700

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
526		ELEC-7.1.62	Supply, Installation, Testing and Commissioning of Small Business 24 port Gigabit Un managed Switch. Makes: As per list of recommended brands as category II.	1 No	13900
527		ELEC-7.1.63	Supply and fixing of 8 PoE 10/100/1000 ports + 2 Gigabit SFP ports with 175W Web Smart Switch. Makes: As per list of recommended brands.	1 No	20520
528		ELEC-7.1.64	Supply and fixing of 24 PoE 10/100/1000 ports + 2 Gigabit SFP ports up to 250W Web Smart Switch. Makes: As per list of recommended brands	1 No	31050
529		ELEC-7.1.65	Supply Installation Testing and commissioning of High-Speed HDMI male to male cable of length. Makes: As per list of recommended brands	Each	4500
			5 Mtr	Each	3250
			10 Mtr	Each	6500
			25 Mtr	Each	16250
530		ELEC-7.1.66	Supply, installation, testing and commissioning of Wi-fi router. Makes: As per list of recommended brands.	Nos	5500
531		ELEC-7.1.67	Supply and laying of 2 mtr. HDMI- HDMI Patch Cords. Makes: As per list of recommended brands.	Nos	3800
532		ELEC-7.1.68	Supply and laying of USB Cable Makes: As per list of recommended brands.		
			2 Mtr	Nos	570
			10 Mtr	Nos	1520
533		ELEC-7.1.69	Supply and laying of 2 mtr. VGA-VGA Patch Cords. Makes: As per list of recommended brands.	Nos	4180
			8 Ports SC Type		
			12 Ports SC Type		
			24 Ports SC Type		
		7.2	RACEWAYS AND JUNCTION BOXES		
534		ELEC-7.2.1	Supply of G I Raceways of 2mm thick with top cover and required hardware etc complete.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04199	a	100mm x 38mm	1 Mtr	549
	MAT-04200	b	150mm x 38mm	1 Mtr	722
	MAT-04201	c	300mm x 38mm	1 Mtr	1225
	MAT-04202	d	100mm x 25mm	1 Mtr	510
	MAT-04203	e	150mm x 25mm	1 Mtr	667
	MAT-04204	f	300mm x 25mm	1 Mtr	1201
535		ELEC-7.2.2	Supply of G.I. Junction box of 2mm thick for direct acces to cables at the inter section of Raceways.		
	MAT-04205	a	172mm x 52mm	1 No	407
	MAT-04206	b	222mm x 52mm	1 No	516
	MAT-04207	c	372mm x 52mm	1 No	959
		7.3	COMPUTERS, PRINTERS AND SCANNERS		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
536	MAT-04208	ELEC-7.3.1	Supply, Transportation and installation of Desktop with fully loaded software as desired, with the following configuration. 1. Processor: Intel® Core™ i7-12th Generation or Higher version Processor with Intel® HD Graphics 770 (2.9 GHz base frequency, up to 4.9 GHz with Intel® Turbo Boost Technology, 25 MB L3 cache, 12 cores 20 threads) Intel Q670 Chipset 2. Memory: 8 GB DDR4-3200 MHz SDRAM (1 x 8 GB) memory slots 2 DIMM 3. Hard drive 512GB SSD (Hard Drive 2 nd 1 TB 7200 SATA HDD) 4. 1 audio line in; 1 audio line out; 1 HDMI; 1 RJ-45; 1 VGA; 4 USB 3.0; 4 USB 2.0 5. Operating Systems: Windows 11 Pro professional 64 bit with product key License. 6. communications (intel Wi-Fi & Blue tooth) 7. Preloaded with latest version of Antivirus Symantec/ McAfee / NOD32 / e-Trust / Avast Internet Security / Kaspersky / Quick heal / eScan / Msecure with following features: Antivirus, Antispyware, intrusion Prevention Browser protection with single management console with 3 year subscription with support updates and patches. 8. Accessories: With required connecting cables and driver media should be supplied. 9. Warranty: 3 Year Standard On-Site Comprehensive Hardware Warranty (including O.S support, Spares- Parts/Service/Labour/On-site) Makes: As per list of recommended brands.	1 No	76500

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
537	MAT-04209	ELEC-7.3.2	Supply, Transportation and installation of Desktop with fully loaded software as desired, with the following configuration. 1. Processor: Intel® Core™ i5-12th Generation or Higher version processor with Intel® HD Graphics 770 (2.9 GHz base frequency with Intel® Turbo Boost Technology, 18 MB cache 6 core 12 threads) Intel Chipset 2. Memory: 8 GB DDR4-3200 MHz SDRAM (1 x 8 GB) 3. Hard drive 512GB SSD (Hard Drive 2 nd 1 TB 7200 SATA HDD) 4. 1 audio line in; 1 audio line out; 1 HDMI; 1 RJ-45; 1 VGA; 4 USB 3.0; 4 USB 2.0 5. Operating Systems: Windows 11 Pro professional 64 bit with product key License. However, the product key should be mentioned in the installation report at the time of installation. 6. communications (intel Wi-Fi & Blue tooth) 7. Preloaded with latest version of Antivirus Symantec/ McAfee / NOD32 / eTrust / Avast Internet Security / Kaspersky / Quickheal / eScan / Msecure with following features: Antivirus, Antispyware, intrusion prevention Browser protection with single management console with 3 year subscription with support updates and patches. 8. Accessories: With required connecting cables and driver media should be supplied. 9. Warranty: 3 Year Standard On-Site Comprehensive Hardware Warranty (including O.S support, Spares- Parts/Service/Labour/On-site) Makes: As per list of recommended brands.	1 No	65800
538	MAT-04210	ELEC-7.3.3	Supply, Transportation and installation of Printer Features: Print technology Laser Duty cycle (monthly, letter) Up to 5000 pages Recommended monthly page volume 250 to 2000. Duty cycle (monthly, A4) Up to 5000 pages print Print speed black (normal, letter) Up to 15 ppm Print speed black (normal, A4) Up to 14 ppm Duplex printing Manual (driver support provided) PROCESSOR : processor speed 234 MHz PAPER HANDLING Envelope feeder No Paper trays, maximum 1 (plus single-sheet priority	1 No	13165

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			input slot) Makes: As per list of recommended brands.		
539	MAT-04211	ELEC-7.3.4	Supply, Transportation and installation of All-in-One (Print, Copy, Scan) with duplex, auto document feeder features: -Print Resolution 600 x 600dpi -Print Speed (A4) 27ppm -Auto Duplex Printing Standard -Available Paper Size for Auto Duplex Print A4, Letter, Legal (*1), Indian Legal, Fullscape -COPY Copy Speed (A4) 27ppm Maximum Number of Copies Up to 999 copies Scan Type Colour Contact Image Sensor Scan Resolution Optical Up to 600 x 600dpi Pull Scan Yes, USB and Network Makes: As per list of recommended brands.	1 No	24805
540	MAT-04212	ELEC-7.3.5	Supply, Transportation and installation of Document Scanner Features: upto 30ppm/60ipm at 300dpi paper size A8 to A4/Legal 256MB memory upto 1200X1200 dpi resolution 50pages ADF input capacity upto 3000 pgs daily duty cycle USB 2.0 Host & Gigabit Lan Port Makes: As per list of recommended brands.	1 No	42338
541	MAT-04213	ELEC-7.3.6	Supply of 5 Pair telephone copper wire. Makes: As per list of recommended brands.	100 Mtrs	3479
542	MAT-04214	ELEC-7.3.7	Supply of 100 pair MDF loaded with 2/10 Modular. Makes: As per list of recommended brands.	1 No	4029
543	MAT-04215	ELEC-7.3.8	Supply of 100 Pair raiser cable for telephone. Makes: As per list of recommended brands.	1 Mtr	424
544	MAT-04216	ELEC-7.3.9	Supply of 10 Pair telephone Copper wire. Makes: As per list of recommended brands.	1 Mtr	49
545	MAT-04217	ELEC-7.3.10	Supply of 20 Pair telephone Copper wire. Makes: As per list of recommended brands.	1 Mtr	98
546	MAT-04218	ELEC-7.3.11	Supply of 50 Pair telephone Copper wire. Makes: As per list of recommended brands.	1 Mtr	244

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
547	MAT-04219	ELEC-7.3.12	Supply of 10 pair Telephone distribution box with back mount frame, krone connector, powder coated metal body with lock and key arrangement.	1 No	714
548	MAT-04220	ELEC-7.3.13	Supply of 20 pair Telephone distribution box with back mount frame, krone connector, powder coated metal body with lock and key arrangement.	1 No	1089
549	MAT-04221	ELEC-7.3.14	Supply of 50 pair Telephone distribution box with back mount frame, krone connector, powder coated metal body with lock and key arrangement.	1 No	2269
550	MAT-04222	ELEC-7.3.15	Supply of 200 pair Telephone distribution box with back mount frame, krone connector, powder coated metal body with lock and key arrangement.	1 No	8664
551		ELEC-7.3.16	Supply, Installation, Testing and commissioning of Non caller ID push button Telephone instruments etc., complete with connectors. Makes: As per list of recommended brands	Each	495
552		ELEC-7.3.16	Supply, Installation, Testing and commissioning of 60.45cm (23.8") FHD (1920X1080) monitor with adjustable stand/ vesa mountable with IPS panel 1VGA1USB with HD CP support. Makes: As per list of recommended brands	Each	19700
			EPABX SYSTEM		
		7.4	SMALL SYSTEM		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
553	MAT-05554	ELEC-7.4.1	Supply, Installation, testing and Commissioning of IP Based digital Telephone (EPABX) system ----- complied with following specifications: > IP @ Core, PCM/TDM, Non-blocking, > Must Support PRI, E1, Analog Junctions > Must Support PC Console, > Must support Mobile SIP (Android and Ios) > Must support Voice Mail > Must support Card based GSM > Inbuilt 8 Channel Auto Attendant > Inbuilt Call Details Software with search engine software > 4 Analog Trunks > 6 Digital Extensions > 32 Analog Extensions > 1 Digital Key Phone with minimum 16 Keys (Must work only on 2 wires) > Expandable to 64 Analog Extensions or more / Makes: As per list of recommended brands.	1 No	104665
554	MAT-05555	ELEC-7.4.2	Supply, Installation, testing and Commissioning of IP Based digital Telephone (EPABX) system ----- complied with following specifications: > IP @ Core, PCM/TDM, Non-blocking, > Must Support PRI, E1, Analog Junctions > Must Support PC Console, > Must support Mobile SIP (Android and Ios) > Must support Voice Mail > Must support Card based GSM > Inbuilt 8 Channel Auto Attendant > Inbuilt Call Details Software with search engine software > 4 Analog Trunks > 6 Digital Extensions > 48 Analog Extensions > 1 Digital Key Phone with minimum 16 Keys (Must work only on 2 wires) > Expandable to 64 Analog Extensions or more Makes: As per list of recommended brands.	1 No	114950

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
555	MAT-05556	ELEC-7.4.3	Supply, Installation, testing and Commissioning of IP Based digital Telephone (EPABX) system ----- complied with following specifications: > IP @ Core, PCM/TDM, Non-blocking, > Must Support PRI, E1, Analog Junctions > Must Support PC Console, > Must support Mobile SIP (Android and Ios) > Must support Voice Mail > Must support Card based GSM > Inbuilt 8 Channel Auto Attendant > Inbuilt Call Details Software with search engine software > 4 Analog Trunks > 1 ISDN PRI Module > 6 Digital Extensions > 48 Analog Extensions > 1 Digital Key Phone with minimum 16 Keys (Must work only on 2 wires) > Expandable to 64 Analog Extensions or more Makes: As per list of recommended brands.	1 No	128018
556	MAT-05557	ELEC-7.4.4	Supply, Installation, testing and Commissioning of IP Based digital Telephone (EPABX) system ----- complied with following specifications: > IP @ Core, PCM/TDM, Non-blocking, > Must Support PRI, E1, Analog Junctions > Must Support PC Console, > Must support Mobile SIP (Android and Ios) > Must support Voice Mail > Must support Card based GSM > Inbuilt 8 Channel Auto Attendant > Inbuilt Call Details Software with search engine software > 4 Analog Trunks > 6 Digital Extensions > 64 Analog Extensions > 1 Digital Key Phone with minimum 16 Keys (Must work only on 2 wires) > Expandable to 64 Analog Extensions or more Makes: As per list of recommended brands.	1 No	131890

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
557	MAT-05558	ELEC-7.4.5	Supply, Installation, testing and Commissioning of IP Based digital Telephone (EPABX) system ----- complied with following specifications: > IP @ Core, PCM/TDM, Non-blocking, > Must Support PRI, E1, Analog Junctions > Must Support PC Console, > Must support Mobile SIP (Android and Ios) > Must support Voice Mail > Must support Card based GSM > Inbuilt 8 Channel Auto Attendant > Inbuilt Call Details Software with search engine software > 4 Analog Trunks > 1 ISDN PRI Module > 6 Digital Extensions > 64 Analog Extensions > 1 Digital Key Phone with minimum 16 Keys (Must work only on 2 wires) > Expandable to 64 Analog Extensions or more Makes: As per list of recommended brands.	1 No	143990
558	MAT-05559	ELEC-7.4.6	Supply and installation of Analog Extension Card (with Caller ID) 8 extensions.	1 No	17545
559	MAT-05560	ELEC-7.4.7	Supply and installation of Analog Extension Card (with Caller ID) 16 extensions.	1 No	22990
560	MAT-05561	ELEC-7.4.8	Supply and installation of Analog Trunk Card (with Caller ID) 4 trunks.	1 No	19481
561	MAT-05562	ELEC-7.4.9	Supply and installation of Analog Trunk Card (with Caller ID) 8 trunks.	1 No	24200
562	MAT-05563	ELEC-7.4.10	Supply and installation of Digital Extension Card for 8 digital extensions:	1 No	22627
563	MAT-05564	ELEC-7.4.11	Supply and installation of Digital Extension Card for 16 digital extensions:	1 No	38115
564	MAT-05565	ELEC-7.4.12	Supply and installation of E1 Trunk Card or PRI Card 30 ISDN PRI or R2 trunk channels.	1 No	57173
		7.5	LARGE SYSTEM	1 No	

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
565	MAT-05566	ELEC-7.5.1	Supply, Installation, Testing and Commissioning of IP Based digital Telephone (EPABX) system-- complied with following specifications: > IP @ Core, PCM/TDM switching, non-blocking, > Must Support PRI, E1, Analog Junctions > Must Support PC Console, > Must support Mobile SIP (Android and IOs) > Must support Voice Mail > Must support Card based GSM > Inbuilt Call Details Software with search engine software > 8 Analog Trunks > 8 Digital Extensions > 96 Analog Extensions > 1 Digital Key Phone with minimum 16 Keys (Must work only on 2 wires) > Expandable to 220 Ports wired or more at extra cost Makes: As per list of recommended brands.	1 No	288706
566	MAT-05567	ELEC-7.5.2	Supply, Installation, Testing and Commissioning of IP Based digital Telephone (EPABX) system-- complied with following specifications: > IP @ Core, PCM/TDM switching, non-blocking, > Must Support PRI, E1, Analog Junctions > Must Support PC Console, > Must support Mobile SIP (Android and IOs) > Must support Voice Mail > Must support Card based GSM > Inbuilt Call Details Software with search engine software > 8 Analog Trunks > 1 PRI Trunk module > 8 Digital Extensions > 128 Analog Extensions > 1 Digital Key Phone with minimum 16 Keys (Must work only on 2 wires) > Expandable to 220 Ports wired or more at extra cost Makes: As per list of recommended brands.	1 No	436810

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
567	MAT-05568	ELEC-7.5.3	Supply, Installation, Testing and Commissioning of IP Based digital Telephone (EPABX) system-- complied with following specifications: > IP @ Core, PCM/TDM switching, non-blocking, > Must Support PRI, E1, Analog Junctions > Must Support PC Console, > Must support Mobile SIP (Android and IOs) > Must support Voice Mail > Must support Card based GSM > Inbuilt Call Details Software with search engine software > 8 Analog Trunks > 1 PRI Trunk module > 8 Digital Extensions > 160 Analog Extensions > 1 Digital Key Phone with minimum 16 Keys (Must work only on 2 wires) > Inbuilt hot standby for CPU and PSU. > Compatibility to run on DC -48v source. > Expandable to 220 Ports wired or more at extra cost. Makes: As per list of recommended brands.	1 No	526350
568	MAT-05569	ELEC-7.5.4	Supply, Installation, Testing and Commissioning of IP Based digital Telephone (EPABX) system-- complied with following specifications: > IP @ Core, PCM/TDM switching, non-blocking, > Must Support PRI, E1, Analog Junctions > Must Support PC Console, > Must support Mobile SIP (Android and IOs) > Must support Voice Mail > Must support Card based GSM > Inbuilt Call Details Software with search engine software > 8 Analog Trunks > 1 PRI Trunk module > 16 Digital Extensions > 224 Analog Extensions > 1 Digital Key Phone with minimum 16 Keys (Must work only on 2 wires) > Inbuilt hot standby for CPU and PSU. > Compatibility to run on DC -48v source. > Expandable to 400 Ports wired or more at extra cost.	1 No	733260

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: As per list of recommended brands.		
569	MAT-05570	ELEC-7.5.5	Supply, Installation, Testing and Commissioning of IP Based digital Telephone (EPABX) system-- complied with following specifications: > IP @ Core, PCM/TDM switching, non-blocking, > Must Support PRI, E1, Analog Junctions > Must Support PC Console, > Must support Mobile SIP (Android and IOs) > Must support Voice Mail > Must support Card based GSM > Inbuilt Call Details Software with search engine software > 8 Analog Trunks > 1 PRI Trunk module > 16 Digital Extensions > 304 Analog Extensions > 1 Digital Key Phone with minimum 16 Keys (Must work only on 2 wires) > Inbuilt hot standby for CPU and PSU. > Compatibility to run on DC -48v source. > Expandable to 400 Ports wired or more at extra cost. Makes: As per list of recommended brands.	1 No	849420
570	MAT-05571	ELEC-7.5.6	Supply and Installation of Analog Extension Card (with Caller ID) 16 extensions.	1 No	24079
571	MAT-05572	ELEC-7.5.7	Supply and Installation of Analog Trunk Card (with Caller ID) 8 trunks.	1 No	24079
572	MAT-05573	ELEC-7.5.8	Supply and Installation of Digital Extension Card for 8 digital extensions:	1 No	24079
573	MAT-05574	ELEC-7.5.9	Supply and Installation of Digital Extension Card for 16 digital extensions:	1 No	39567
574	MAT-05575	ELEC-7.5.10	Supply and Installation of E1 Trunk Card or PRI Card 30 ISDN PRI or R2 trunk channels.	1 No	59411
575	MAT-05576	ELEC-7.5.11	Supply and Installation of IP CPU card for redundancy purpose	1 No	43318
576	MAT-05577	ELEC-7.5.12	Supply and Installation of PSU card for redundancy purpose	1 No	26378
577	MAT-05578	ELEC-7.5.13	Supply and Installation of Digital Key Telephone with 2-line display, 10 programmable keys, handsfree	1 No	10164

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			dialing.		
578	MAT-05579	ELEC-7.5.14	Supply and Installation of Digital Key Telephone with 2-line display, 16 programmable keys, fully handsfree talk back.	1 No	17787
579	MAT-05580	ELEC-7.5.15	Supply and Installation of IP Gateway card for 8 channels	1 No	50215
580	MAT-05581	ELEC-7.5.16	Supply and Installation of IP Gateway card for 16 channels	1 No	72600
581	MAT-05582	ELEC-7.5.17	Supply and Installation of SIP extensions licenses pack (5 SIP extensions)	1 No	5143
582	MAT-05583	ELEC-7.5.18	Supply and Installation of SIP extensions licenses pack (10 SIP extensions)	1 No	9015
583	MAT-05584	ELEC-7.5.19	Supply and Installation of IP phone with POE.	1 No	20328
584	MAT-05585	ELEC-7.5.20	Supply and Installation of 4 port GSM card	1 No	52998
585	MAT-05586	ELEC-7.5.21	Supply and Installation of Expansion cabinet for 220 more extensions	1 No	100430
586	MAT-05587	ELEC-7.5.22	Supply and Installation of 100 Pair MDF along with IPM	1 No	16214
			C.C.TV & SURVEILLANCE SYSTEM		
		ELEC-7.6.1A	Supply, Installation, Testing and Commissioning of 64CH Embedded 4K NVR 8 SATA expandable up to 144 TB, audio input & Output, Two way communication supported, G7.11 audio format support, 512 Mb recording throughput, 2 alarm inputs & 1 Outputs, with maximum 128 users, Op. temp 0 to 50 deg. C, NDAA compliant, UL/CE/FCC, certified. Makes: As per list of recommended brands as Category I.	Each	110951
587		ELEC-7.6.1B	Supply, Installation, Testing and Commissioning of 32CH Embedded 4K NVR 4SATA expandable up to 40TB, audio input & Output, Two way communication supported, G7.11 audio format support, 512 Mb recording throughput, 2 alarm inputs & 1 Outputs, with maximum 16 users, Op. temp 0 to 50 deg. C, NDAA compliant, UL/CE/FCC, certified. Makes: As per list of recommended brands	Each	86521

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			as Category I.		
588		ELEC-7.6.2	Supply, Installation, Testing and Commissioning of 16CH Embedded 4K NVR 2SATA expandable up to 20TB, audio input & Output, Two way communication supported, G7.11 audio format support, 512 Mb recording throughput, 2 alarm inputs & 1 Output, RS485, HDMI, to be supported with maximum 16 users, Op. temp 0 to 50 deg. C, NDAA compliant, UL/CE/FCC certified. Makes: As per list of recommended brands as Category I	Each	42763
589		ELEC-7.6.3	Supply, Installation, Testing and Commissioning of 8CH Embedded 4K NVR 1SATA expandable up to 10TB, audio input & Output, Two way communication supported, G7.11 audio format support, 180 Mb recording throughput, 2 alarm inputs & 1 Output, RS485, HDMI, VGA ports to be supported with maximum 16 users, Op. temp 0 to 50 deg. C, NDAA compliant, UL/CE/FCC, certified. Makes: As per list of recommended brands as Category I..	Each	28036
590		ELEC-7.6.4	Supply, Installation, Testing and Commissioning of 4 MP or higher IR Dome, Fixed lens min 2.8mm" ½.8 progressive CMOS image sensor, Min. Illumination 0.01 (color), S/N Ratio: 70 dB, Electronics Shutter: 1/15 ~ 1/100000s IR Distance: 50M, with built in video analytics,WDR~120dB/BLC/HLC/3D DNR, Gain Control: 0~100%; SD card up to 512GB, PAN: 0-330, Tilt: 0- 75, Rotation: 0- 180; Video Compression: H.265 /H.264/MJPEG, Smart Codec; Quad Stream; Protocols: H.265 /H.264/MJPEG, Smart Codec; ONVIF: S/G/T; Op. Temp: -30 to 60 Deg; power consumption max. 7W; IP67,IK10,UL,NDAA,BIS Compliance, Makes: As per list of recommended brands as Category I.	Each	13800
591		ELEC-7.6.5	Supply, Installation, Testing and Commissioning of 4 MP or higher IR Bullet, Fixed lens min 2.8mm ½.8 progressive CMOS image sensor, Min. Illumination 0.01 (color), S/N Ratio: 70 dB, Electronics Shutter: 1/15 ~ 1/100000s IR Distance: 50M, with built in video analytics	Each	14200

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			,WDR~120dB/BLC/HLC/3D DNR, Gain Control: 0~100%; SD card up to 512 GB, PAN: 0- 330, Tilt: 0- 75, Rotation: 0- 180; Video Compression: H.265 H.264/MJPEG, Smart Codec; Quad Stream; Protocols: H.265 /H.264/MJPEG, Smart Codec; ONVIF: S/G/T; Op. Temp: -30 to 60 Deg; power consumption max. 7W; IP67,IK10,UL,NDAA,BIS Compliance accessories mounts to be considered. Makes: As per list of recommended brands as Category I. 1/2.8"		
592		ELEC-7.6.6	Supply, installation, Testing and Commissioning of IP IR PTZ Camera- 2MP 38x Network PTZ Dome Camera Max. 2megapixel (1920 x 1080) resolution,4.44 ~ 169.4 mm (Optical 38x) lens, Max. IR viewable length : 300m Day & Night (ICR), WDR (120dB),1/ 2.8" Progressive Scan CMOS, Intelligent Video / Audio Analytics, Intrusion Detection and Motion Detection, Shock detection, Azimuth display (Cardinal & intermediate directions),Multiple streaming, Wise Stream II support H.265, H.264, MJPEG codec support MicroSD / SDHC / SDXC memory (Up to 512 GB) IP67, IK10 UL Certified, PTZ Camera along with pole/wall mount L-bracket for Mounting, Power Adapter, IP 67,with lighting protection, surge protection and voltage transient protection etc., Makes: As per list of recommended brands as Category I.	Each	1,18,000
		ELEC-7.6.4 A	Supply, Installation, Testing and Commissioning of 4 MP or higher IR Bullet, Motorized Varifocal Lens 2.8mm to 12mm ½.8 progressive CMOS image sensor, Min. Illumination 0.01 (color), S/N Ratio: 70 dB, Electronics Shutter: 1/15 ~ 1/100000s IR Distance: 50M, with built in video analytics,WDR~120dB/BLC/HLC/3D DNR, Gain Control: 0~100%; SD card up to 512GB, PAN: 0- 360, Tilt: 0- 90, Rotation: 0-360; Video Compression: H.265 /H.264/MJPEG, Smart Codec; Quad Stream; Protocols: H.265 /H.264/MJPEG, Smart Codec; ONVIF: S/G/T; Op. Temp: -30 to 60 Deg; power consumption max. 7W; IP67,IK10,UL,NDAA,BIS Compliance Makes: As per list of recommended brands as Category I.	Each	21735

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		ELEC-7.6.5 A	Supply, Installation, Testing and Commissioning of 5 MP or higher IR Dome, Motorized Varifocal Lens 2.8mm to 12mm 1/2.8 progressive CMOS image sensor, Min. Illumination 0.01 (color), S/N Ratio: 70 dB, Electronics Shutter: 1/15 ~ 1/100000s IR Distance: 50M, with built in video analytics,WDR~120dB/BLC/HLC/3D DNR, Gain Control: 0~100%; SD card up to 512GB, PAN: 0-330, Tilt: 0- 75, Rotation: 0-180; Video Compression: H.265 /H.264/MJPEG, Smart Codec; Quad Stream; Protocols: H.265 /H.264/MJPEG, Smart Codec; ONVIF: S/G/T; Op. Temp: -30 to 60 Deg; power consumption max. 6W; IP67,IK10,UL,NDAA,BIS Compliance, Makes: As per list of recommended brands as Category I.	Each	22365
593		ELEC-7.6.7	Supply and fixing of Surveillance HDD-4 TB. Makes: As per list of recommended brands.	Each	17442
594		ELEC-7.6.8	Supply and installation of 4K UHD, 55" LED Display complete with following Specifications: a) Diagonal Size 55" b) Type Edge LED BLU. c) Resolution 3840*2160 (4K UHD) d) Pixel Pitch(mm)0.105 x 0.315. e) Active Display Area(mm)1209.6(H) x 680.4(V) f) Brightness (Typ.) 350 nit. g) Contrast Ratio 4000:1. Makes: As per list of recommended brands	Each	85707
595		ELEC-7.6.9	Supply and installation of 24 inch (60.96cm) Full HD LED Monitor with Wall Mountable Stand, Height Adjustable, HDMI and VGA Ports with all accessories. Makes: As per list of recommended brands	Each	16950
596		ELEC-7.6.10	Installation, testing, Commissioning & Integration of CCTV system in Control room including mobile configuration and communication of entire system as per the directions of Engineer-in-Charge.	Each Job	12000
			Note: The above charges for Installation, testing, Commissioning & Integration of CCTV system in Control room may be given on job work basis for every 10 cameras or part there of depending upon		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			size of the building/premises.		
			Category II		
597		ELEC-7.6.11	Supply, Installation, Testing and Commissioning of 32CH Embedded 4K NVR 4SATA expandable up to 40TB, audio input & Output, Two way communication supported, G7.11 audio output support, 512 Mb recording throughput, Op. temp 0 to 50 deg. C, NDAA compliant, UL/CE/FCC certified. /BIS Makes:- As per list of recommended brands as Category II	Each	47790
598		ELEC-7.6.12	Supply, Installation, Testing and Commissioning of 16CH Embedded 4K NVR 2SATA expandable up to 20TB, audio input & Output, Audio out put communication supported, G7.11 audio format support, 180 Mb recording throughput, HDMI, ports to be supported with maximum 16 users, Op. temp 0 to 50 deg. C, UL/CE,FCC, certified. Makes:- As per list of recommended brands as Category II	Each	15156
599		ELEC-7.6.13	Supply, Installation, Testing and Commissioning of 8CH Embedded 4K NVR 1SATA expandable up to 10TB, audio Output, Two way communication supported, G7.11 audio format support, 180 Mb recording throughput, HDMI, ports to be supported with maximum 16 users, Op. temp 0 to 50 deg. C, NDAA compliant, UL/CE/FCC certified. Makes:- As per list of recommended brands as Category II	Each	7866
600		ELEC-7.6.14	Supply, Installation, Testing and Commissioning of 4 MP or higher IR Dome, fixed lens min 2.8mm ½.8 progressive CMOS image sensor, Min. Illumination 0.01 (color), S/N Ratio: 70 dB, Electronics Shutter: 1/15 ~ 1/100000 IR Distance: 30M, with built in video analytics ,WDR~120dB/BLC/HLC/3D DNR, Gain Control: 0~100%; SD card up to 256GB, Video Compression:H.265 /H.264/MJPEG, Smart Codec; Triple Stream; Protocols: H.265 /H.264/MJPEG, Smart Codec; ONVIF: S/G/T; Op. Temp: -30 to 60 Deg; power consumption max. 7W; IP67,IK10,BIS Compliance,	Each	7000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: - As per list of recommended brands as Category II		
601		ELEC-7.6.15	Supply, Installation, Testing and Commissioning of 4MP or higher IR Bullet, fixed lens min 2.8mm 1.2/8 progressive CMOS image sensor, Min. Illumination 0.01(color), S/N Ratio: 50dB, Electronics Shutter: 1/15 ~ 1/100000, IR Distance: 30M, with built in video analytics ,WDR~120dB/BLC/HLC/3D DNR, Gain Control: 0~100%; SD card up to 256GB, Video Compression:H.265 /H.264/MJPEG, Smart Codec; Triple Stream; Protocols: H.265 /H.264/MJPEG, Smart Codec; ONVIF: S/G/T; Op. Temp: -30 to 60 Deg; power consumption max. 6W; IP67,IK10,BIS Compliance accessories mounts to be considered. Makes:- As per list of recommended brands as Category II.	Each	7200
602		ELEC-7.6.16	Supply, installation, Testing and Commissioning of IP IR 2MP PTZ Camera- 32x Network PTZ Dome Camera Max. 2megapixel (1920 x 1080) resolution, 4.44 ~ 142.6mm (Optical 32x) lens, Max. IR viewable length : 200m (656ft), Day & Night (ICR), WDR (150dB), DIS (Built-in gyro sensor), 1/2.8" Progressive Scan CMOS, Intelligent Video / Audio Analytics, Intrusion Detection and Motion Detection, Shock detection, Azimuth display (Cardinal & intermediate directions),Multiple streaming, Wise Stream II support H.265, H.264, MJPEG codec support MicroSD / SDHC / SDXC memory 2 slots (Up to 512 GB) IP66, IK10 UL Certified PTZ Camera along with pole/wall mount L-bracket for Mounting, Power Adapter, IP66, TVS 4,000V Lightning Protection, Surge Protection and Voltage Transient Protection etc. Makes: As per list of recommended brands as Category II.	Each	94400
			PUBLIC ADDRESS SYSTEMS		
603		ELEC-7.7.1	Supply and Installation of 120Watt Booster Amplifier, the amplifier is protected against overload and short circuits. A temperature-controlled fan ensures high reliability at high output levels and low acoustic noise at lower output levels. An overheat protection circuit switches off the power stage and activates an LED	Each	19500

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			on the front panel, if the internal temperature reaches acritical limit due to poor ventilation or overload. Makes: As per list of recommended brands		
604		ELEC-7.7.2	Supply and installation testing and commissioning of Tabletop mounted gooseneck type Conference Delegate unit Loudspeaker volume is set centrally at the Control Unit for all delegate units. To prevent acoustic feedback, the built-in loudspeaker is automatically muted when the microphone is on, the headphone volume level can be adjusted by means of a thumbwheel on the unit for maximum comfort, Nominal Acoustic Input 85dB SPL, Frequency Response 400Hz to 10kHz, Length of the microphone from the base of the stem 488mm. Makes: As per list of recommended brands.	Each	14200
605		ELEC-7.7.3	Supply, Fixing and Installation of Tabletop/Podium mounted gooseneck type Conference Chairman unit Loudspeaker volume is set centrally at the Control Unit for all delegate units. To prevent acoustic feedback, the built-in loudspeaker is automatically muted when the microphone is on, the headphone volume level can be adjusted by means of a thumbwheel on the unit for maximum comfort. Makes: As per list of recommended brands.	Each	16800
606		ELEC-7.7.4	Supply, Fixing and Installation of Rack mounted Conference Control unit, having digital acoustic feedback suppression facility that automatically eliminates acoustic feedback, giving better speech intelligibility by allowing the speaker volume to be turned up as loud as required without any risk of feedback. Makes: As per list of recommended brands.	Each	29050
607		ELEC-7.7.5	Supply and Installation of Wall mounted 30W Cabinet Loudspeaker, High-fidelity music and speech reproduction, Selectable 8 ohm, 70 V and 100 V inputs, Compact yet robust ABS enclosure, Supplied with adjustable mounting bracket, Complies with international installation and safety regulations. Makes: As per list of recommended brands.	Each	5910
608		ELEC-7.7.6	Supply, Fixing and Installation of 4 Channel Mixer, High-fidelity music and speech reproduction,	Each	37200

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			selectable 8-ohm, 70 V and 100 V inputs, Compact yet robust ABS enclosure, Supplied with adjustable mounting bracket, Complies with international installation and safety regulations. Makes: As per list of recommended brands.		
609		ELEC-7.7.7	Supply and Installation of Wireless Handheld microphone, With the touch of a single button, ClearScan™ scans through all 32 preset channels and selects the clearest channel, which ensures noise-free operation over the longest operating range. In the increasingly cluttered world of RF, ClearScan™ gives you confidence that you can easily find an open frequency. Makes: As per list of recommended brands.	Each	29470
610		ELEC-7.7.8	Supply and fixing of wireless hand held microphone Having Frequency Response of 40Hz-13kHz etc., complete. Makes: As per list of recommended brands.	Each	4650
611		ELEC-7.7.9	Supply and Installation of Wireless Collar Microphone with Frequency Response of 40Hz-13kHz etc., complete. Makes: As per list of recommended brands.	Each	4800
612		ELEC-7.7.10	Supply and Fixing of High fidelity 2-Way wall mountable Speakers with 16W impedance with power taps of 4W/8W/16W etc., complete. Makes: As per list of recommended brands.	Each	4635
613		ELEC-7.7.11	Supply, Installation, Testing and Commissioning of speakers with following specifications:12W Wall mount box Speaker, rated power: 12W, Tapings 100 volt line : 12/6/9WTransformer Impedance, Ohms , 100V : 1.67k/3.33k/6.66k, Frequency Response : 55-15,000 Hz SPL at 1kHz (1W/1M) : min 85dB, Color / Finish : White RAL9016 / Black. Makes: As per list of recommended brands.	Each	1740
614		ELEC-7.7.12	Supplying, installing, testing and commissioning of 25 zone selector P.A. console and with CRCA sheet housing and control desk also included with rack arrangement as required. The console shall have all call / call back type complete with battery backup and it should also work on AC single phase power. (Considered each floor one Zone).	Each	27030

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: As per list of recommended brands.		
615		ELEC-7.7.13	Supply and Fixing of High fidelity 2-Way wall mountable with 10W impedance with power taps of 1.5W/3W/6W etc., complete. Makes: As per list of recommended brands.	Each	3980
616		ELEC-7.7.14	Supply and Fixing of Ceiling mount Speakers with 6W impedance with power taps of 1.5W/3W/6W etc., complete. Makes: As per list of recommended brands.	Each	3228
617		ELEC-7.7.15	Supply and Laying of Microphone Cables and connectors etc., complete. Makes: As per list of recommended brands.	1 RM	48
618		ELEC-7.7.16	Testing and commissioning of the above Public Address systems as required at site.	Each Job	2000
			Note: The above charges for Testing and commissioning of the above Public Address systems may be given on job work basis for each amplifier with mixer/each conference hall etc., depending upon size of the building/premises.		
			AUDIO-VIDEO SYSTEMS		
619		ELEC-7.8.1	Supply and Fixing of Projector for front end Audience, As 4200lm, 5000:1 contrast ratio, 1080p@50/60Hz and HDMI & VGA interface etc. complete. Makes: As per list of recommended brands.	Each	70060
620		ELEC-7.8.2	Supply, installation, testing & commissioning of 3LCD / 1DLP laser projector with 4200 ANSI Lumens brightness, Ultra short throw (0.3 : 1) lens, Resolution: WXGA (1280 x 800), Colors: 16.7 million colors, Contrast Ratio: 500,000 : 1, Speaker Output: 16W, Input Ports: 1 x HDMI, 1 x MHL, 2 x VGA, 1 x composite video, 1 x component video, 1 x 3.5 mm stereo mini jack, Output: 1 x 3.5 mm stereo mini jack, 1 x VGA, Wired and wireless network LAN, 1 x RS-232 control port. Makes: As per list of recommended brands.	Each	247000
621		ELEC-7.8.3	Supply, installation, testing & commissioning of 3LCD/1DLP laser projector with 3500 ANSI Lumens brightness, Resolution: WXGA (1280 x 800), Colors: 16.7 million colors, Contrast Ratio: 2,000,000 : 1,	Each	129200

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Life: 40,000 hours, Speaker Output: 16W, Input Ports: 2 x HDMI, 2 x VGA, 1 x composite video, 1 x component video, 1 x RCA jack, Output: 1 x 3.5 mm stereo mini jack, 1 x VGA, Wired and wireless network LAN, 1 x RS-232 control port. Makes: As per list of recommended brands.		
622		ELEC-7.8.4	Supply and Fixing of Ceiling Mount Kits for Projector etc. complete. Makes: As per list of recommended brands.	Each	10305
623		ELEC-7.8.5	Supply and fixing of 120" Motorized projection screen with remote control etc. complete. Makes: As per list of recommended brands.	Each	20610
624		ELEC-7.8.6	Supply and fixing of 55" Full HD LED Large format Display (LFD) Commercial model for 24x7 operations, as 1920 x 1080 (16:9) resolution & 170°/160°(H/V) viewing angle, with HDMI & VGA Interface etc., complete. Makes: As per list of recommended brands.	Each	80060
625		ELEC-7.8.7	Supply and Fixing of Ceiling Mount Kits for front LED etc. complete. Makes: As per list of recommended brands.	Each	11221
626		ELEC-7.8.8	Supply and fixing of 4-input and 8-output HDMI (High-Definition Multimedia Interface) matrix Switcher Board with EDID Minder (Interface switching unit for LFD & Projectors to provide Audio and Video) etc. complete. Makes: As per list of recommended brands.	Each	270300
627		ELEC-7.8.9	Supply and fixing of long distance HDMI (High-Definition Multimedia Interface) twisted Pair Transmitter/Receiver for LED cable for long distance which contains OFC and converting accessories etc. complete. Makes: As per list of recommended brands.	Each Pair	49440
628		ELEC-7.8.10	Supply and fixing of VGA to HDMI Convertor etc. complete. Makes: As per list of recommended brands.	Each	16946
629		ELEC-7.8.11	Supply and laying of twisted pair type High-Definition Multimedia Interface cable for long distance which contains OFC and converting accessories for multiple connectivity like connectors for Tx & Rx etc.	Each	4809

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			complete. Makes: As per list of recommended brands.		
630		ELEC-7.8.12	Supply and Fixing of Wireless remote control Laser point Presenter and Slider etc. complete. Makes: As per list of recommended brands.	Each	6320
631		ELEC-7.8.13	Supply, installation, testing & commissioning of 2.4 GHz Digital Wireless Handheld Microphone with 256 bit, AES Encryption, Frequency Response: 70 Hz–20 KHz, Dynamic Range: 116 dB @ 1 KHz, Signal-to-noise: >90 dBA, Latency<=2.9ms along with Up to 12 Hours battery life. Makes: As per list of recommended brands.	Each	38000
632		ELEC-7.8.14	Supply, installation, testing & commissioning of 2.4 GHz Digital Wireless Lapel Microphone with 256 bit AES Encryption, Frequency Response: 20 Hz–20 KHz, Dynamic Range: 116 dB @ 1 KHz, Signal-to-noise: >90 dBA, Latency<=2.9ms along with Up to 12 Hours battery life. Makes: As per list of recommended brands.	Each	38000
633		ELEC-7.8.15	Supply, installation, testing & commissioning of Gooseneck Microphone with on/off button with Polar pattern: Cardioid, Frequency range: 70 to 18,000 Hz , Max. SPL 125 dB, Equivalent noise level: <21 dB-A , Signal/noise ratio: >73 dB, Impedance: <=600 ohms, load impedance >=2,000 ohms, Connector 3-pin male XLR. Makes: As per list of recommended brands.	Each	38000
634		ELEC-7.8.16	Supply, installation, testing & commissioning of Modular Digital Signal Processor with AEC and current configuration of minimum 6mic/line inputs and 4-line outputs, 2 x 2 USB in/out for PC audio, Dante connectivity and Processor: 40-bit floating point, Sampling rate: 48kHz, standard Dante digital audio networking. Makes: As per list of recommended brands.	Nos	173793
635		ELEC-7.8.17	Supply, installation, testing & commissioning of Column Line array Speaker with 8 nos. vertically aligned array of full range speakers with Frequency Range: 80 Hz – 20 kHz, Sensitivity: 93 dB, Power Capacity: 100 Watt (400 W Peak), Nominal Impedance: 8 ohms, Max SPL: 121 dB, Transformer	Nos	44290

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Tap: 60W, 30W @ 100V, Fiberglass reinforced ABS cabinet, painted aluminum grille along with Swivel (pan)/tilt wall bracket. Makes: As per list of recommended brands.		
636		ELEC-7.8.18	Supply, installation, testing & commissioning of Class D Dual channel Power Amplifier with Power output: 2 x 240 Watt @ 100v, Frequency response : 50Hz-22kHz, Total harmonic distortion (THD) : < 0.3%, Signal to noise ratio : > 100 dB, Crosstalk (@ 1 kHz) < 80 dB along with Dc short circuit, overheating, over load, signal limiting, temperature control fan protection. Makes: As per list of recommended brands.	Nos	83030
637		ELEC-7.8.19	Supply, installation, testing & commissioning of 250-Watt Mixing Amplifier with frequency response 50Hz to 15kHz +/-3 dB, THD <10%, Inputs: 6 x Mic, 2 x Aux, 1 x Line inputs, Outputs: 1 x Preamp out & 1 x Line out, Signal to Noise ratio:70db, with Bass and treble control. Makes: As per list of recommended brands.	Nos	23750
638		ELEC-7.8.20	Supply, Installation, Testing and Commissioning of Two way ceiling speaker 4" LF Driver, 0.75" Tweeter, Power Handling Capacity : 60 Watt continuous program power, Sensitivity (SPL 1W/1m) : 87 dB, Peak SPL: 108 dB, Frequency Range: 75 Hz – 20 kHz, Coverage : 120° Conical, impedance: 8 ohms, UL / EN certified, along with integrated steel back can complete as required. Makes: As per list of recommended brands.	Nos	9207
639		ELEC-7.8.21	Supply and fixing of 1600 W, 132 dB peak SPL utilizing high-sensitivity transducers 15" Two-Way Passive Loudspeaker etc. complete. Makes: As per list of recommended brands.	Each	8879
640		ELEC-7.8.22	Supply and fixing of 1000 W, 126 dB 12" Two-Way Powered Loudspeaker etc. complete. Makes: As per list of recommended brands.	Each	7948
641		ELEC-7.8.23	Supply and Fixing of Ultra compact two-way with single 8-inch woofer etc. complete. Makes: As per list of recommended brands.	Each	28033
642		ELEC-7.8.24	Supply and fixing of 650 W per channel Class-H power amplifier With 2x 450W @ 4 Ohms etc.	Each	4358

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			complete. Makes: As per list of recommended brands.		
643		ELEC-7.8.25	Supply and Fixing of Pop-up box etc. complete. Makes: As per list of recommended brands.	Each	3570
644		ELEC-7.8.26	Supply and Fixing of XLR connector etc. complete. Makes: As per list of recommended brands.	Each	675
645		ELEC-7.8.27	Supply, Installation, Testing and Commissioning of Multiformat 3 x 1 automatic transmitter and receiver with scaler solution, Should support HDCP 2.2 and auto scaling at output, 4K30 Support for source devices and displays, Inputs (TX) – Transmitter includes 2x HDMI and 1x VGA inputs, Outputs(RX) – Receiver includes 1x HDMI input and scaled HDMI output , control port: RS-232, 2 x Relay and de-embedded audio out. Makes: As per list of recommended brands.	Nos	64980
646		ELEC-7.8.28	Supply, Installation, Testing and Commissioning of 4x1 4K60 Presentation Switcher with Inputs: 1 x VGA with audio, 3 x HDMI, Outputs: 1 x HDBT and 1 x HDMI output, 1 x de-embedded audio out along with control port: 1 x RS-232, 1 x IR, 1 x contact-in, 1 x tally out and ethernet port. Makes: As per list of recommended brands.	Nos	77976
647		ELEC-7.8.29	Supply, Installation, Testing and Commissioning of Multi-Format Wall plate Transmitters, Inputs: 1x HDMI, 1 x VGA, 1 x audio, Output: HdbaseT/ Dxlink RJ-45, Resolution: 480p up to 1920x1200 @ 60 Hz , HDCP Compliant, 3D Support, Analog to Digital Conversion: 48 kHz Sample Rate, 24-bit. Makes: As per list of recommended brands.	Nos	71535
648		ELEC-7.8.30	Supply, Installation, Testing and Commissioning of Receiver compatible to the above transmitter, input: HbaseT/Dxlink RJ-45, output: HDMI, Analog Stereo Output : 3.5mm Mini-Stereo Jack, HDCP Compliant, Control: Rs232, IR. Makes: As per list of recommended brands.	Nos	81863
649		ELEC-7.8.31	Supply, installation, testing and commissioning of Wireless Presentation System with 4K resolution, enables iOS, Android, Chromebook, PC, and Mac device users to instantly connect to a main display without a dongle, 2.4GHz/5GHz Wi-Fi and MIMO	Nos	66500

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			antennas, Two participants can simultaneously present content on main display along with in-built processor of Intel, Main Memory: 4GB, Storage: 32 GB, Networking: 802.11 ac/b/g/n dual band Wireless LAN and Bluetooth 4.1, Operating System: Linux. Makes: As per list of recommended brands.		
650		ELEC-7.8.32	Supply, installation, testing and commissioning of 8 Button control Pad with 2 x RS-232, 2x IR/Serial, 2 x I/O channel, 1 x Relay, 1 x USB Mini-B, USB, with Flash: 4 GB, Memory Card: 4 GB SD, DDRAM: 256 MB along with Display Monitoring. Makes: As per list of recommended brands.	Nos	55423
651		ELEC-7.8.33	Supply, Installation, testing and commissioning of Mobile Signal Jammer for 8 Band with all standard accessories. Model: GST-JAMM-009HI (High Cooling Mechanism+ Industrial Model) ☐ 08 Antennas ☐ Power Supply Adopter Unit (Note: This Model will Jamm mobile Signal approximately 40- 50 meters Depending on the Input Signal Strength. Makes: As per list of recommended brands.	Each	48000
			SECTION 8		
		8.1	MISCELLANEOUS ITEMS		
652	MAT-04223	ELEC-8.1.1	TW Separators / Gutties	100 Nos	233
653	MAT-04224	ELEC-8.1.2	PVC Rawl Plugs	100 Nos	39
654	MAT-04225	ELEC-8.1.3	PVC Grips	100 Nos	39
655	MAT-04226	ELEC-8.1.4	U Nails	100 Nos	39
656	MAT-04227	ELEC-8.1.5	Aluminum Link Clips	100 Nos	43
657	MAT-04228	ELEC-8.1.6	50 mm G.I. Nut and Bolts.	1 Set	20
658	MAT-04229	ELEC-8.1.7	63 to 100 mm G.I. Nut and Bolts.	1 Set	33

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
659	MAT-04230	ELEC-8.1.8	50 mm 0 Gauge Nails	1 Doz	59
660	MAT-04231	ELEC-8.1.9	63 to 100 mm 0 Gauge Nails	1 Doz	93
661	MAT-04232	ELEC-8.1.10	Hard Coke	1 Kg	26
662	MAT-04233	ELEC-8.1.11	Salt	1 Kg	20
663	MAT-04234	ELEC-8.1.12	PVC Cleats 2 Way	100 Nos	422
664	MAT-04235	ELEC-8.1.13	PVC Cleats 4 Way	100 Nos	556
665	MAT-04236	ELEC-8.1.14	Binding Wire	1 Kg	78
666	MAT-04237	ELEC-8.1.15	PVC /cotton tape Role (8 Mtrs)	1 No	24
667	MAT-04238	ELEC-8.1.16	C.I. Knob	1 No	33
668	MAT-04239	ELEC-8.1.17	Stay tight set (Jam bracket 300 mm)	1 Pair	394
669	MAT-04240	ELEC-8.1.18	Stay clamp with bolts and Nuts)	1 Set	262
670	MAT-04241	ELEC-8.1.19	L.T. Guy insulator	1 No	97
671	MAT-04242	ELEC-8.1.20	12 / 15 MS plain rod fan hook	1 No	42
672	MAT-04243	ELEC-8.1.21	19 / 20 mm Steel tube fan down rod	1 Mtr	119
673	MAT-04244	ELEC-8.1.22	Concealed box PVC / MS with hook for fan	1 No	139
674	MAT-04245	ELEC-8.1.23	Supply and fixing of Anchor fastener with fan hook / Providing MS Fan hook with grouting and cement plastering.	1 No	130
675	MAT-	ELEC-	Coil Earthing	1 No	97

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	04246	8.1.24			
676	MAT-04247	ELEC-8.1.25	Cable root Indicators of size 152mm round / 102mm x 102mm / 152mm x 152mm	1 No	110
677	MAT-04248	ELEC-8.1.26	40 mm x 40 mm x 6 mm angle iron with I bolt.	1 Set	327
678	MAT-04249	ELEC-8.1.27	Mild Steel Items	1 Kg	83
679	MAT-04250	ELEC-8.1.28	Acrylic Cover of size 4" x 7" for night lamps.	1 No	26
680	MAT-04251	ELEC-8.1.29	TW / PVC Round Blocks	1 No	11
681	MAT-04252	ELEC-8.1.30	G.I. Funnel with Mesh 1/2" x 4"	1 No	104
682	MAT-04253	ELEC-8.1.31	Asbestos Sheet	1 Sq Mt	33
683	MAT-04254	ELEC-8.1.32	First Aid box 18" x 12" x 8"	1 No	1392
684	MAT-04255	ELEC-8.1.33	11 KV/ 22 KV Hand gloves	1 No	259
685	MAT-04256	ELEC-8.1.34	100mm CI pipe	1 mtr	As per civil SOR
		8.2	LEGEND PLATES		
686		ELEC-8.2.1	Danger Notice Plates of size -----, shall comply with IS:2551-1982		
	MAT-04257	a	250x200mm,	1 No	292
	MAT-04258	b	200x150mm,	1 No	259
	MAT-04259	c	150x100mm,	1 No	129
687	MAT-04260	ELEC-8.2.2	Bus bar chamber 100mm x 40mm	1 No	70
688	MAT-04261	ELEC-8.2.3	Cable Alley 100mm x 40mm	1 No	70

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
689	MAT-04262	ELEC-8.2.4	Earth 40mm x 20mm	1 No	65
690	MAT-04263	ELEC-8.2.5	Auto / Manual	1 No	65
691	MAT-04264	ELEC-8.2.6	Semi oval type aluminum anodized legend plates ON / OFF / Forward / Reverse / Start / Stop / UP / DOWN / R Phase / Y Phase / B Phase / Trip / Open / Close / Left / Right / Motor on / Motor off / Accept / Retract / Reset / Emergency / Running / Pump off / Emergency Stop / Emergency on / Slow.	1 No	33
692	MAT-04265	ELEC-8.2.7	Shock instruction chart in English / Hindi / Telugu duly framed with front glass	1 No	583
		8.3	COPPER / ALLUMINIUM / G.I. ITEMS (PER KG)		
693	MAT-04266	ELEC-8.3.1	Copper Plate / Strip / SWG wire No.8 / 10 / 14	1 kg	1037
694	MAT-04267	ELEC-8.3.2	Copper winding wire	1 kg	1149
695	MAT-04268	ELEC-8.3.3	Copper winding wire with PVC Insulated of fine quality	1 kg	1182
696	MAT-04269	ELEC-8.3.4	Aluminum Bus bars / Strips / Accessories	1 kg	338
697	MAT-04270	ELEC-8.3.5	Aluminum winding wire	1 kg	441
698	MAT-04271	ELEC-8.3.6	G.I. Strip / Plate / Wire	1 kg	94
		8.4	SMC TYPE SUPPORTS FOR THE BUSBARS		
699		ELEC-8.4.1	Supply of type supports for the bus bars-----		
	MAT-04272	a	50 x 70 x 14 mm	1 No	43
	MAT-04273	b	60 x 70 x 14 mm	1 No	50
	MAT-04274	c	70 x 70 x 14 mm	1 No	93
	MAT-	d	300 x 50 x 10 mm	1 No	29

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	04275				
	MAT-04276	e	350 x 52 x 10 mm	1 No	229
	MAT-04277	f	420 x 60 x 12 mm	1 No	328
700	MAT-04278	ELEC-8.4.2	DMC Earth Flat Supports 20 x3 mm / 20x 6mm / 25 x 6mm / 25 x 3mm / 32 x 3 mm / 32 x 6mm / 40 x 3 mm / 40 x 6mm	1 No	65
701	MAT-04279	ELEC-8.4.3	Heat shrinkable sleeves for the Bus bars up to 70 Sq mm	1 Mtr	20
702	MAT-04280	ELEC-8.4.4	Heat shrinkable sleeves for the Bus bars above 70 Sq mm	1 Mtr	33
703	MAT-04281	ELEC-8.4.5	8 mm LED series bulb (54 Nos.)	Set	340
704	MAT-04282	ELEC-8.4.6	8 mm LED series bulb with Navar Patti (250/300 Nos.) with necessary control gear	Set	2833
705	MAT-05588	ELEC-8.4.7	LED RGB pixel series bulbs(50 Nos)	Set	623
706	MAT-05589	ELEC-8.4.8	LED RGB pixel series bulbs with Navvar Patti (150 Nos) with necessary control gear	Set	5099
707	MAT-05590	ELEC-8.4.9	Supply of 3W X54 LED RGB PAR cans with IP 67 protection	1 No	9149
708	MAT-04284	ELEC-8.4.10	Supply and fixing of 6mm thick MS Chequered plate.	1 Kg	97
709	MAT-04285	ELEC-8.4.11	Supply and fixing of 6mm thick Aluminum Chequered plate	1 Kg	357
710	MAT-04286	ELEC-8.4.12	Copper old winding Wire scrap for 1 Kg	1 Kg	211
711	MAT-04287	ELEC-8.4.13	Cement	1 Kg	11
712		ELEC-8.4.14	Cost of Sand	1 Cum	777
713		ELEC-8.4.15	Cost of Bricks	1000 Nos	5179
714	MAT-04288	ELEC-8.4.16	Hylam Sheet	1 Sq inch	1

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
715		ELEC-8.4.17	Supply of Nominal-Bore ----- G.I. Pipe		
	MAT-04289	a	25mm Heavy grade	1 mtr	364
	MAT-04290	b	25mm Medium grade	1 mtr	319
	MAT-04291	c	40mm Heavy grade	1 mtr	546
	MAT-04292	d	40mm Medium grade	1 mtr	455
		e	50mm Medium grade	1 mtr	585
		f	65mm Medium grade	1 mtr	742
		g	80mm Medium grade	1 mtr	945
716	MAT-04293	ELEC-8.4.18	80mm Nominal Bore C.I. Earth Pipe of 3 Mtrs Length	1 no	4530
717	MAT-04294	ELEC-8.4.19	Earth work excavation including all soils for trench, Pole Pit and Earth Pit	1 cum	348
718	MAT-04295	ELEC-8.4.20	Drilling of 16 Nos through holes of 12mm dia to G.I pipe	1 No	9
719	MAT-04296	ELEC-8.4.21	G.I Nuts, Bolts and Washers each set	1 set	15
720	MAT-04297	ELEC-8.4.22	18" dia 2" thick hume pipe ring	1 No	390
721	MAT-04298	ELEC-8.4.23	18" dia 3" hume pipe ring	1 No	450
722	MAT-04299	ELEC-8.4.24	2" thick CC cover for hume pipe ring with handle.	1 No	250
723		ELEC-8.4.25	Supply of Saddle / Clamps suitable for fixing -----		
	MAT-04300	a	4 to 10 Sq mm 2 Core Cable	100 Nos	297

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04301	b	4 & 6 Sq mm 4 Core Cable	100 Nos	297
	MAT-04302	c	10 & 16 Sq mm 4 Core Cable	100 Nos	388
	MAT-04303	d	25 & 35 Sq mm 3.5 Core Cable.	100 Nos	454
	MAT-04304	e	50 Sq mm 3.5 Core Cable.	100 Nos	647
	MAT-04305	f	70 & 95 Sq mm 3.5 Core Cable	100 Nos	713
	MAT-04306	g	120 to 185 Sq mm 3.5 Core Cable	100 Nos	906
	MAT-04307	h	240 & 300 Sq mm 3.5 Core Cable	100 Nos	1101
	MAT-04308	i	400 Sq mm 3.5 Core Cable	100 Nos	1424
724		ELEC-8.4.26	Supply and fixing of PVC synthetic elastomer electrically insulated at conforming to IS: 15652-2006 with-----		
	MAT-04309	a	Class A insulation having 2mm thickness upto 3.3KV	1 sq mt	4598
	MAT-04310	b	Class B insulation having 2.5mm thickness upto 11KV	1 sq mt	4719
	MAT-04311	c	Class C insulation having 3mm thickness upto 33KV	1 sq mt	4840
725	MAT-04312	ELEC-8.4.27	Supply of round bottom G.I sheet bucket of 9 Ltrs. Capacity as per IS:2546 made out of 24-gauge GI sheet with extra handle at bottom duly painted inside and red outside with printed with FIRE Mark for stand and hook and filled with sand and arranged to existing stand or hook.	1 no	327
726	MAT-04313	ELEC-8.4.28	Providing floor mounting stand for keeping 4No of fire bucket 1500mm length, 900mm height made out of 40x40x6mm angle iron welded with 4 hooks and duly painted with one coat of red lead and two coats of enamel paint.	1 no	1331

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
727		ELEC-8.4.29	Supply of GI Louver shutter for exhaust fan		
	MAT-04314	a	9 to 12"	1 no	182
	MAT-04315	b	15 to 18"	1 no	218
728	MAT-04316	ELEC-8.4.30	EICHER model 11:10 with 100 H.P. direct injection 4 stroke engine with one spare wheel 3800 mm cabin high deck with jangla (full body) (4 wheeler) for generator	1 No	750200
			LABOUR RATES		
			NB : The labour rates may be adopted based on the common Civil SoR for the year 2023-24		
		9.1	WIRELESS FIRE ALARAM SYSTEM		
729	MAT-04336	ELEC-9.1.1	Supply and fixing of wireless smoke detection control panel of 28 wireless zones, 2 Hard wired Zones, Tamper Alert, Pass code protected, RF jamming recognition, diagnostic feature for RF signal strength between panel and each detector, vent reporting using PSTN telephone line, dialing upto 4 telephone numbers, event reporting as per users choice, LCD screen display, two way voice interaction, battery backup stand by time up to 12 hrs. Including transportation, all taxes and all labour charges etc complete. Makes: As per list of recommended brands.	1 No	48300
730	MAT-04337	ELEC-9.1.2	Supply and fixing of wireless repeater. The wireless repeater extends the communication range of detection by relaying data between receiver and remote wireless transmitter including transportation, all taxes and all labour charges etc complete. Makes: As per list of recommended brands.	1 No	9775

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
731	MAT-04338	ELEC-9.1.3	Supply and fixing of Wireless Siren Strobe external wireless siren - a fully supervised power code outdoor (IP55) wireless Siren and strobe light. Designed for external installation. Wire - Free connection between control panel and siren. Convenient rapid no- mess installation. Separate fire alarm signals, 98db Piezo siren and high-power strobe light. Weather resistant, IP55, 2-way communication for local and remote diagnostics. Plug-in power supply, NIMH rechargeable back-up power battery, transmits status, tamper, low- battery, supervisory and AC loss messages to the control panel, Tri- State tamper switch identifies screw manipulation removal of cover or playing from the wall including transportation, all taxes and all labour charges etc complete. Makes: As per list of recommended brands.	1 No	13225
732	MAT-04339	ELEC-9.1.4	Supply and fixing of wireless Fully Supervised Smoke Detector, Photoelectric detection technology for superior detection sensitivity, sound and transmitted for smoke, tamper and low battery, works on power code protocol, easy programming and enrolling to the control panel, long life 9 volt alkaline or lithium battery including transportation, all taxes and all labour charges etc complete. Makes: As per list of recommended brands.	1 No	7936
		9.2	ADDRESSABLE - FIRE ALARM SYSTEM		
733		ELEC-9.2.1	Supply, install, test and commissioning of addressable peer to peer Networkable analogue addressable type fire alarm control panel with minimum 1500 Character / 240X64 Pixel / 7inch Touchscreen graphic LCD display. The panel should be equipped with sufficient numbers of loop with 20% spare capacity, with each networkable intelligent fire alarm Control Panel having SLC with capacity of min 250 detectors/ devices in any combination (Min 120 Detector) with key pad, dual flash-based microprocessor technology, inbuilt USB Port for upload and down load the configuration tools, RS232 serial port for direct PC or modem connection, inbuilt NAC's, min 20 programmable Zonal LEDs and operates on 240V AC + 10% with 50 Hz with built in charger. The panel shall have fire, fault relays, option of BMS integration MODBUS/ BACKNET, graphical software for provision of TCP/ IP modules, Remote Access, Class 'X' wiring with provision of both class 'A' and class 'B' wiring in the SLC circuit, user friendly with communication facility to monitor & control the FACP's from a single window. The panel shall be		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			suitable for minimum of 5000 event record facility, event fetch from FACP facility and the single panel shall be suitable for min 2000 fire zones and 200 Panels/ Nodes in one network with all other accessories required to successfully run the system. The panel shall be completed as per UL and FM/EN54 & VDS standards (The System cost shall be included of all necessary cards, modules, Panel enclosure, CPU and associated accessories to complete the system design) Makes: As per list of recommended brands as category I.		
	MAT-04340	a	1 loop	1 No	221375
	MAT-04341	b	2 loop	1 No	253000
	MAT-04342	c	4 loop	1 No	309925
	MAT-04343	d	6 loop	1 No	415553
	MAT-04344	e	8 loop	1 No	455400
	MAT-04345	f	10 loop	1 No	626175
734		ELEC-9.2.2	Supply, install, test and commissioning of addressable peer to peer Networkable analogue addressable type fire alarm control panel with minimum 1500 Character / 240X64 Pixel / 7inch Touchscreen graphic LCD display. The panel should be equipped with sufficient numbers of loop with 20% spare capacity, with each networkable intelligent fire alarm Control Panel having SLC with capacity of min 250 detectors/ devices in any combination (Min 120 Detector) with key pad, dual flash-based microprocessor technology, inbuilt USB Port for upload and down load the configuration tools, RS232 serial port for direct PC or modem connection, inbuilt NAC's, min 20 programmable Zonal LEDs and operates on 240V AC + 10% with 50 Hz with built in charger. The panel shall have fire, fault relays, option of BMS integration MODBUS/ BACKNET, graphical software for provision of TCP/ IP modules, Remote Access, Class 'X' wiring with provision of both class 'A' and class 'B' wiring in the SLC circuit, user friendly with communication facility to monitor & control the FACP's from a single window. The panel shall be suitable for minimum of 5000 event record facility, event fetch from FACP facility and the single panel shall be suitable for min 2000 fire zones and 200 Panels/ Nodes in one network with all other accessories required to successfully run the system. (The System cost shall be included of all necessary cards, modules, Panel enclosure, CPU and associated		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			accessories to complete the system design). Makes: As per list of recommended brands as category II.		
	MAT-04346	a	1 loop	1 No	198605
	MAT-04347	b	2 loop	1 No	222640
	MAT-04348	c	4 loop	1 No	258060
	MAT-04349	d	6 loop	1 No	335858
	MAT-04350	e	8 loop	1 No	389367
	MAT-04351	f	10 loop	1 No	619850
735	MAT-04352	ELEC-9.2.3	Supply, Installation, Testing & Commissioning of Network Active Repeater Panel with 1500 Character / 240X64 Pixel / 7inch Touchscreen. The LCD shall Display all events / detectors, devices status of complete systems in the networked. Makes: As per list of recommended brands as category I.	1 No	132825
736	MAT-04353	ELEC-9.2.4	Supply, Installation, Testing & Commissioning of Network Active Repeater Panel with 1500 Character / 240X64 Pixel / 7inch Touchscreen. The LCD shall Display all events / detectors, devices status of complete systems in the networked. Makes: As per list of recommended brands as category II.	1 No	108158
737	MAT-04354	ELEC-9.2.5	Supply, Installation, Testing & Commissioning of Analogue Addressable loop powered Sounder & Beacon with inbuilt isolator and having Min 15 distinct sound patterns/ multitone to indicate Exit doors and direct occupants for safe and fast evacuation and 100dB output with minimum 1Hz Frequency flash rate designed for IP65 requirements and approved to operate in -10°C to +55°C temperature, complies with the essential requirement of the EMC Directive to be supplied with Junction Box, Glands and other mounting accessories for proper	1 No	5819

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			installation. Makes: As per list of recommended brands as category I.		
738	MAT-04355	ELEC-9.2.6	Supply, Installation, Testing & Commissioning of Analogue Addressable loop powered Sounder & Beacon with inbuilt isolator and having Min 15 distinct sound patterns/ multitone to indicate Exit doors and direct occupants for safe and fast evacuation and 100dB output with minimum 1Hz Frequency flash rate designed for IP65 requirements and approved to operate in -10°C to +55°C temperature, complies with the essential requirement of the EMC Directive to be supplied with Junction Box, Glands and other mounting accessories for proper installation Makes: As per list of recommended brands as category II.	1 No	4681
739	MAT-04356	ELEC-9.2.7	Supply, Installation, Testing & Commissioning of Dust and Vermin proof (Resettable) addressable analogue Manual call boxes along with Isolators inbuilt having front reset mechanism with 170° viewable LED and can be viewed from the distance of 7 M. also have inbuilt isolator having operating temperature from -40°C-70°C to initiate audio visual alarm in case of Human detection of fire. The manual call point must be indoor type with IP 44 rating. The call point must be resettable type without break glass. Makes: As per list of recommended brands as category I.	1 No	5693
740	MAT-04357	ELEC-9.2.8	Supply, Installation, Testing & Commissioning of Dust and Vermin proof (Resettable) addressable analogue Manual call boxes along with Isolators inbuilt having front reset mechanism with 170° viewable LED and can be viewed from the distance of 7 M. also have inbuilt isolator having operating temperature from -40°C-70°C to initiate audio visual alarm in case of Human detection of fire. The manual call point must be indoor type with IP 44 rating. The call point must be resettable type without break glass. Makes: As per list of recommended brands as category II.	1 No	5060

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
741	MAT-04358	ELEC-9.2.9	Optical smoke detector with LED with standard base having capacity of min 126 address combination. Operating temperature -40°C to 70°C & Humidity 0-95%. The detector should have polling 360-degree viewable LED with 5 class approved response modes all approved with the relevant standards, drift compensation and transient rejection. The detector shall have facility to mount in different comprehensive environment like Hostile environment, precious storage, Warehouse and normal working environments. The detector should have a self-locking mechanism and requires a special tool to remove this detector. The detector should have a hard address inside the base. The detector must have nonvolatile memory to write the installation date & site codes. The detector should be made of fire-retardant material & should be melt above 100-degree C. The detectors must be openable for the cleaning of dust whenever required. All the other specs should be as per the specification attached. Makes: As per list of recommended brands as category I.	1 No	4086
742	MAT-04359	ELEC-9.2.10	Optical smoke detector with LED with standard base having capacity of min 126 address combination. Operating temperature -40°C to 70°C & Humidity 0-95%. The detector should have polling 360 degree viewable LED with 5 class approved response modes all approved with the relevant standards, drift compensation and transient rejection. The detector shall have facility to mount in different comprehensive environment like Hostile environment, precious storage, warehouse and normal working environments. The detector should have a self-locking mechanism and requires a special tool to remove this detector. The detector should have a hard address inside the base. The detector must have nonvolatile memory to write the installation date & site codes. The detector should be made of fire retardant material & should be melt above 100 degree C. The detectors must be openable for the cleaning of dust whenever required. All the other specs should be as per the specifications. Makes: As per list of recommended brands as category II.	1 No	3602

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
743	MAT-04360	ELEC-9.2.11	Analogue Addressable Heat detector and LED with standard base having capacity of min 126 address combination. Storage temperature -40°C to 80°C & Humidity 0-95%. The detector shall have facility to mount in different comprehensive environment like Hostile environment, Precious storage, Ware house and normal working environments. The heat detector must trigger the alarm as per the A1R/A2R/A2S/CR/CS requirement. The detector should have self-locking mechanism and requires special tool to remove this detector. The detector must have nonvolatile memory to write the installation date & site codes. Makes: As per list of recommended brands as category I.	1 No	4409
744	MAT-04361	ELEC-9.2.12	Analogue Addressable Heat detector and LED with standard base having capacity of min 126 address combination. Storage temperature -40°C to 80°C & Humidity 0-95%. The detector shall have facility to mount in different comprehensive environment like Hostile environment, Precious storage, Ware house and normal working environments. The heat detector must trigger the alarm as per the A1R/A2R/A2S/CR/CS requirement. The detector should have self-locking mechanism and requires special tool to remove this detector. The detector must have nonvolatile memory to write the installation date & site codes. Makes: As per list of recommended brands as category II.	1 No	3871
745	MAT-04362	ELEC-9.2.13	Analogue Addressable Multi-sensor (Smoke & Heat) detector with LED with standard base having capacity of min 126 address combination. Operating temperature -40°C to 70°C & Humidity 0-95%. The detector should have polling 360-degree viewable LED with 5 class approved response modes all approved with the relevant standards, drift compensation and transient rejection. The detector should trigger heat alarm as per the A1R class requirement. The detector shall have facility to mount in different comprehensive environment like Hostile environment, Parking Garage, Precious storage, Ware house and normal working environments. The detector should have a self-locking mechanism and	1 No	4516

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			requires a special tool to remove this detector. The detector should have a hard address inside the base. The detector should be made of fire-retardant material & should be melt above 100-degree C. The detectors must be open for the cleaning of dust whenever required. The detector must have 4 nonvolatile memories to write the installation date & site codes Makes: As per list of recommended brands as category I.		
746	MAT-04363	ELEC-9.2.14	Analogue Addressable Multi-sensor (Smoke & Heat) detector with LED with standard base having capacity of min 126 address combination. Operating temperature -40°C to 70°C & Humidity 0-95%. The detector should have polling 360 degree viewable LED with 5 class approved response modes all approved with the relevant standards, drift compensation and transient rejection. The detector should trigger heat alarm as per the A1R class requirement. The detector shall have facility to mount in different comprehensive environment like Hostile environment, Parking Garage, Precious storage, Ware house and normal working environments. The detector should have a self-locking mechanism and requires special tool to remove this detector. The detector should have a hard address inside the base. The detector should be made of fire-retardant material & should be melt above 100-degree C. The detectors must be open for the cleaning of dust whenever required. The detector must have 4 nonvolatile memories to write the installation date & site codes Makes: As per list of recommended brands as category II.	1 No	3871
747	MAT-04364	ELEC-9.2.15	Supply, install, test and commissioning of Analogue addressable Control (Input/Output) module with inbuilt relay and isolator with LED indicator, approved to operate in -10°C to +55°C temperature, complies with the essential requirement of the EMC Directive to be supplied with Junction Box and other mounting accessories for proper installation. In case of Manufacturer with single Input or Output module need to supply One quantity of each for line item. Makes: As per list of recommended brands as category I.	1 No	4782

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
748	MAT-04365	ELEC-9.2.16	Supply, install, test and commissioning of Analogue addressable Control (Input/Output) module with inbuilt relay and isolator with LED indicator, approved to operate in –10°C to +55°C temperature, complies with the essential requirement of the EMC Directive to be supplied with Junction Box and other mounting accessories for proper installation. In the case of Manufacturer with single Input or Output module need to supply One quantity of each for line item. Makes: As per list of recommended brands as category II.	1 No	4213
	MAT-04366	ELEC-9.2.17	Deleted	1 No	
	MAT-04367	ELEC-9.2.18	Deleted	1 No	
749	MAT-04368	ELEC-9.2.19	Supply, Installation, Testing & Commissioning of Loop isolation module which consists of LED. This LED shall be mounted with in a round polycarbonate enclosure. Isolator Base for Isolators. Makes: As per list of recommended brands as category I.	1 No	4326
750	MAT-04369	ELEC-9.2.20	Supply, Installation, Testing & Commissioning of Loop isolation module which consists of LED. This LED shall be mounted with in a round polycarbonate enclosure. Isolator Base for Isolators. Makes: As per list of recommended brands as category II.	1 No	3416
		9.3	CONVENTIONAL - FIRE ALARM SYSTEM		
751		ELEC-9.3.1	Supply, Installation, testing and commissioning of conventional Micro-processor based Fire Alarm panel with, 12V SMF batteries etc., complete with all standard accessories. Makes: As per list of recommended brands.		
	MAT-04370	a	2 Zone	1 No	14516
	MAT-04371	b	4 Zone	1 No	17059
	MAT-04372	c	6 Zone	1 No	18975

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04373	d	8 Zone	1 No	19608
	MAT-04374	e	10 Zone	1 No	24668
	MAT-04375	f	12 Zone	1 No	28463
	MAT-04376	g	14 Zone	1 No	30645
752	MAT-04377	ELEC-9.3.2	Supply and installation of Repeater panel including the cost of mounting accessories complete as per specifications and as required. Makes: As per list of recommended brands.	1 No	14117
753	MAT-04378	ELEC-9.3.3	Supply and installation of dual tone electronic hooter of 85dB including the cost of mounting accessories complete as per specifications and as required. Makes: As per list of recommended brands.	1 No	949
754	MAT-04379	ELEC-9.3.4	Supply and installation of dust and vermin proof manual call point to initiate audio-visual alarm including the cost of mounting accessories complete as per specifications and as required. Makes: As per list of recommended brands.	1 No	759
755	MAT-04380	ELEC-9.3.5	Supply and installation of response indicators for above false ceiling detectors. Makes: As per list of recommended brands.	1 No	190
756	MAT-04381	ELEC-9.3.6	Supply and installation of plug - in-type multi-criterion detectors including the cost of base plate. 75mm dia M.S. outlet box for fixing of the detector base. Mounting accessories etc., complete as per specifications as required. Makes: As per list of recommended brands.	1 No	2024
757	MAT-04382	ELEC-9.3.7	Supply and installation of plug -in type photo electric smoke detectors including the cost of base plate. 75mm dia MS outlet box for fixing the detector base. Mounting accessories etc complete and as per specifications and as required. Makes: As per list of recommended brands.	1 No	1771

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
758	MAT-04383	ELEC-9.3.8	Supply and installation of plug -in type rate of rise cum fixed temperature heat detectors including the cost of base plate. 75mm dia MS outlet box for fixing of the detector base, mounting accessories etc., complete as per specifications and as required. Makes: As per list of recommended brands.	1 No	1645
		9.4	POWDER BASED FIRE EXTINGUISHERS		
759			Supply and fixing of ABC stored pressure squeeze grip type fire extinguishers, 9 kg capacity, IS:15683 : 2006, filled with ABC Mono Ammonium Phosphate base powder-90 complete with discharge hose and wall mounting bracket, 2mm Mild Steel, EPDM Rubbers, Pressure Gauge, which work effectively on all class of fires (A, B, C & Electrical fires) with 5 years warranty Including transportation, all taxes and all labour charges etc complete.		
	MAT-04384	ELEC-9.4.1	Makes: As per list of recommended brands as category I.	1 No	9891
	MAT-04385	ELEC-9.4.2	Makes: As per list of recommended brands as category II.	1 No	6100
760			Supply and fixing of ISI mark (IS:15683) Mono ammonium phosphate powder 90 (MAP) 2 Kg Fire extinguisher, stored pressure type, pressure gauge, gross wt. 3.6 kg, empty wt.1.6 kg, Discharge time minimum 8 sec, controllable discharge mechanism, range min. 2 mts applicable on classes A,B, C & electrically started fire, A rating -2 A, B rating -21 B, can construction: Deep drawn and Co2 MIG welding, Valve construction: Forging & Machining, internal coating of can: Epoxy powder coating, External coating of Can: Epoxy polyester powder coating, sheet metal thickness:1.60mm, Helium leak detection tested with 5 years warranty Including transportation, all taxes and all labour charges etc complete.		
	MAT-04386	ELEC-9.4.3	Makes: As per list of recommended brands as category I.	1 No	4820
	MAT-04387	ELEC-9.4.4	Makes: As per list of recommended brands as category II.	1 No	4187

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
761			Supply and fixing of ISI mark (IS:15683) Mono ammonium phosphate powder 90 (MAP) 4 Kg Fire extinguisher, stored pressure type, pressure gauge, gross wt. 6.9 kg, empty wt.2.9 kg, Discharge time minimum 13 sec, controllable discharge mechanism, range min. 4 mts applicable on classes A,B, C & electrically started fire, A rating -3 A, B rating -34 B, can construction: Deep drawn and Co2 MIG welding, Valve construction: Forging & Machining, internal coating of can: Epoxy powder coating, External coating of Can: Epoxy polyester powder coating, sheet metal thickness:1.60mm, Helium leak detection tested with 5 years warranty Including transportation, all taxes and all labour charges etc complete.		
	MAT-04388	ELEC-9.4.5	Makes: As per list of recommended brands as category I.	1 No	6633
	MAT-04389	ELEC-9.4.6	Makes: As per list of recommended brands as category II.	1 No	5200
762			Supply and fixing of ISI mark (IS:15683) Mono ammonium phosphate powder 90 (MAP) 6 Kg Fire extinguisher, stored pressure type, pressure gauge, gross wt. 9.4 kg, empty wt.3.4 kg, Discharge time minimum 13 sec, controllable discharge mechanism, range min. 4 mts applicable on classes A,B, C & electrically started fire, A rating -4 A, B rating -34 B, can construction: Deep drawn and Co2 MIG welding, Valve construction: Forging & Machining, internal coating of can: Epoxy powder coating, External coating of Can: Epoxy polyester powder coating, sheet metal thickness:1.60mm, Helium leak detection tested with 5 years warranty Including transportation, all taxes and all labour charges etc complete.		
	MAT-04390	ELEC-9.4.7	Makes: As per list of recommended brands as category I.	1 No	7711
	MAT-04391	ELEC-9.4.8	Makes: As per list of recommended brands as category II.	1 No	7116
			CLEAN AGENT FIRE EXTINGUISHERS		
763			Supply and fixing of ISI mark (IS:15683) Clean Agent HCFC 123, 2 Kg Fire extinguisher , Stored pressure type, pressure gauge, gross weight 3.7Kg , empty weight 1.7 Kg, discharge time minimum 8 secs, controllable discharge mechanism, range minimum 2 meters, applicable on class A,B,C and electrically started Fire, A rating- 1A, B rating-21B, can construction: Deep drawn & CO2 MIG welded, Valve construction: Forging & Machining, Internal coating of Can: Epoxy powder coating, External coating of can: Epoxy polyester powder coating, sheet metal thickness: 1.60 mm, Helium leak detection tested, 5 Years warranty		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04392	ELEC-9.4.9	Makes: As per list of recommended brands as category I.	1 No	16808
	MAT-04393	ELEC-9.4.10	Makes: As per list of recommended brands as category II.	1 No	13910
764			Supply and fixing of ISI mark (IS:15683) Clean Agent HCFC 123, 4 Kg Fire extinguisher , Stored pressure type, pressure gauge, gross weight 6.9Kg , empty weight 2.9 Kg, discharge time minimum 8 secs, controllable discharge mechanism, range minimum 2 meters, applicable on class A,B,C and electrically started Fire, A rating- 1A, B rating-21B, can construction: Deep drawn & CO2 MIG welded, Valve construction: Forging & Machining, Internal coating of Can: Epoxy powder coating, External coating of can: Epoxy polyester powder coating, sheet metal thickness: 1.60 mm, Helium leak detection tested, 5 Years warranty.		
	MAT-04394	ELEC-9.4.11	Makes: As per list of recommended brands as category I.	1 No	28256
	MAT-04395	ELEC-9.4.12	Makes: As per list of recommended brands as category II.	1 No	25358
765			Supply and fixing of Co2 type Fire Extinguishers 4.5 Kg capacity confirming to IS 2878 made from ISI marked steam less cylinder confirming to IS:7285 & CE certified and fitted with ISI marked controlled valve confirming to IS:3224, high pressure 1 Mtr discharge hose & horn complete with initial gas charged with carrying handle with wheels and wall mounting bracket. Squeeze lever discharge, used un-used indicator, epoxy coated paint (Red) with 93% gloss with 2 years warranty including transportation, all taxes and all labour charges etc complete.		
	MAT-04396	ELEC-9.4.13	Makes: As per list of recommended brands as category I.	1 No	12180
	MAT-04397	ELEC-9.4.14	Makes: As per list of recommended brands as category II.	1 No	9169
766	MAT-04398	ELEC-9.4.15	Supply and fixing of Escape signage boards in Rigid Photo luminescent based glow in Dark rigid sheet with high intensity luminous properties with specification. Makes: As per list of recommended brands.	1 No	1518
767	MAT-04399	ELEC-9.4.16	Supply and fixing of Cease fire or its equivalent Escape gear Mild Steel box size 425mmx360mmx140mm Epoxy powder coated to protect it from Weathering , smoke hood tested to	1 No	17078

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			European Standard EN 403 1993-S known to reduce Carbon Monoxide, propend (acrolein), hydrogen chloride, hydrogen Cyanide and Solid and liquid toxic particles to manageable level for at least 15 minutes shall with stand temperatures upto 80 degrees single use only Fire Blanket size 1.2m x1.8m used to cover any vessel containing used to Extinguish a clothing fire wrap blanket around the victim.		
768	MAT-04400	ELEC-9.4.17	Supply and fixing of 4Nos of 9 Ltrs capacity round bottom sand buckets along with bucket sand, Fire buckets with round bottom type enamel painted, white inside & red outside and letter FIRE in black outside & Handle with mounting bracket.	1 Set	1518
769	MAT-04401	ELEC-9.4.18	Supply and fixing of Fire bucket stand fabricated by M.S. angles to install for Four numbers of buckets as per local fire officers' standards.	1 Set	1898
			AEROSOL GENERATION SYSTEM (An alternative to water based sprinkler system)		
770	MAT-05591	ELEC-9.4.19	Supply, Installation and commissioning of Auto Detection and Suppression System using Non Pressurized Aerosol Generator System with detection of thermocord to make the system standalone. It can be used for all classes of fire. The product Min. Life shall be 15 years and no Maintenance. The Discharge time shall be 8 sec. The Generator has a net weight of 0.5 kg. Active Substance of 50gms. The Generator has a capacity to cover 1 m ³ . Makes: As per list of recommended brands.	1 No	5175
771	MAT-05592	ELEC-9.4.20	Supply, Installation and commissioning of Auto Detection and Suppression System using Non-Pressurized Aerosol Generator System with detection of thermocord and Inbuilt Aerosol Sprinkler flexibility of adjusting it for a temperature of 57/68/93/141 degree centigrade as per the site environment to make the system standalone. It can be used for all classes of fire. The product Min. Life shall be 15 years and no	1 No	40250

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Maintenance. The Discharge time shall be 18 sec. The Generator has a net weight of 2 kg. Active Substance of 300gms. The Generator has a capacity to cover 6 m ³ . Makes: As per list of recommended brands.		
772	MAT-05593	ELEC-9.4.21	Supply, Installation and commissioning of Auto Detection and Suppression System using Non-Pressurized Aerosol Generator System with detection of thermocord and Inbuilt Aerosol Sprinkler flexibility of adjusting it for a temperature of 57/68/93/141 degree centigrade as per the site environment to make the system standalone. It can be used for all classes of fire. The product Min. Life shall be 15 years and no Maintenance. The Discharge time shall be 22 sec. The Generator has a net weight of 3 kg. Active Substance of 0.5 kg. The Generator has a capacity to cover 10 m ³ . Makes: As per list of recommended brands.	1 No	51750
773	MAT-05594	ELEC-9.4.22	Supply, Installation and commissioning of Auto Detection and Suppression System using Non-Pressurized Aerosol Generator System with detection of thermocord and Inbuilt Aerosol Sprinkler flexibility of adjusting it for a temperature of 57/68/93/141 degree centigrade as per the site environment to make the system standalone to make the system standalone. It can be used for all classes of fire. The product Min. Life shall be 15 years and no Maintenance. The Discharge time shall be 45 sec. The Generator has a net weight of 4.6 kg. Active Substance of 1 kg. The Generator has a capacity to cover 20 m ³ . Makes: As per list of recommended brands.	1 No	74750

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
774	MAT-05595	ELEC-9.4.23	Supply, Installation and commissioning of Auto Detection and Suppression System using Non-Pressurized Aerosol Generator System with detection of thermocord and Inbuilt Aerosol Sprinkler flexibility of adjusting it for a temperature of 57/68/93/141 degree centigrade as per the site environment to make the system standalone to make the system standalone. It can be used for all classes of fire. The product Min. Life shall be 15 years and no Maintenance. The Discharge time shall be 56 sec. The Generator has a net weight of 5.6 kg. Active Substance of 2 kg. The Generator has a capacity to cover 40 m³. Makes: As per list of recommended brands.	1 No	94300
775	MAT-05596	ELEC-9.4.24	Supply, Installation and commissioning of Auto Detection and Aerosol Suppression System using Non-Pressurized Aerosol Generator System with detection of thermocord and Inbuilt Aerosol Sprinkler flexibility of adjusting it for a temperature of 57/68/93/141 degree centigrade as per the site environment to make the system standalone. It can be used for all classes of fire. The product Min. Life shall be 15 years and no Maintenance. The Discharge time should be 80 sec. The Generator has a net weight of 8 kg. Active Substance of 4 kg. The Generator has a capacity to cover 80 m³. Makes: As per list of recommended brands.	1 No	106950
776	MAT-05597	ELEC-9.4.25	Supply, Installation and commissioning of Aerosol Fire suppression control Panel is basically a 10 Zone conventional panel with LED indications for sensors is open or fire. When the fire is detected by Sprinkler, Aerosol gets activated. 10 Aerosol Sprinkler input and 10 Aerosol Generator outputs provided. The Panel consists of 10 individual manual operation switch and one master switch to activate 10 Aerosol Generator outputs simultaneously	1 No	80500
777	MAT-05598	ELEC-9.4.26	Supply, Installation and commissioning of Aerosol control Switch is a Controller for Activation of Each Aerosol Generator Makes: As per list of recommended brands.	1 No	22425

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
778	MAT-05599	ELEC-9.4.27	Providing 'Fire Retardant Paint 1 hr Fire Resistance can be used to 'flame retard only 100 % cotton fabric, is normally used 'to treat coarse fabric e.g. tents etc. and gives coverage of 'approx. 120 to 130 sq.ft. to a fabric of 275-325 gsm. 'Can be applied 'Meant only for 100% cotton and coarse fabric like canvas ' / tents, natural wood etc. Makes: As per list of recommended brands.	1 No	2185
779	MAT-05600	ELEC-9.4.28	Providing 'Flame retard any kind of fabric, be it 100% polyester or '100% cotton. It is normally used to flame 'retard upholstery, curtains, carpets etc., gives a coverage 'of approx. 120 to 130 sq.ft. to a fabric of 275-325 gsm.	1 No	2990
780	MAT-05601	ELEC-9.4.29	Providing 'Fire Retardant coat towards passive protection to sustain 'up to 1000 Deg.C. for 1 hour. This product can be used for 'all the materials such as cable, steel, wood, cloth & 'concrete surface etc.	1 No	4830
781		ELEC-9.4.30	AUTO ABC 150KG FIRE EXTINGUISHING SYSTEM WITH AUTO FIRE DETECTION TUBE TECHNOLOGY SKIT MOUNTED ABC powder firefighting unit 150 kg capacity. Vessels are made of boiler quality steel plate 8 mm thick radiography welding as per ASME code. Skit mounted having an Auto Fire Detection tube 25mtr. long fitted. The discharge line can be fixed with open type nozzle, expelling agent of Co2 cylinder agent which is fitted with Auto Fire Detection specially designed imported Ceodeux valve and specially designed DIFFUSER SYSTEM to achieve minimum 98% discharge. Used for all classes of fire. This system consists of the following: Expelling cylinder and Skit mounted ABC container with discharge output nozzle Expelling container connected through with manifold & diffuser nozzle to main cylinder. It is also fitted with Ceodex Valve, one end connected with Auto Fire Detection Tube to detect and another end fitted with pressure switch and hooter. Auto Fire Detection Tube will be installed with pressure of 12kg/cm2. In case of fire the tube gets rupture in the temperature 115 degree C .	1 NO	588525

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Whereby the pressure in tube comes down to 0 level sudden falling in pressure opens the valve and releases the expelling gas to main cylinder. through manifold and diffuser systems. Discharge from main cylinder at fixed pressure through rapture disc to flood and quench fire instantly. Rapture disc can also be designed depending upon hazardous area. This is the only latest technology which is used for all kinds of inflammable hazards at open area. The fire fighting unit shall be made strictly as per the specifications to the satisfaction of State Disaster Response and Fire Serivces Vijayawada. Makes: As per list of recommended brands.		
		ELEC-9.4.31	Supply of manually operated Aerosol suppression System using Non-Pressurized Aerosol Generator system and also with detection of termocord. It can be used for all classes of fire, the product Minimum Life shall be 15 years and no maintenance. The Discharge time should be 26 sec. The Generator has a net weight of 6 kg. Active substance of 3 Kg. The generator has a capacity to cover 60 m3. ETDC-Govt of India Approved. Makes: - As per list of recommended brands.	1 No	93750
		ELEC-9.4.32	Supply of manually operated Aerosol suppression System using Non-Pressurized Aerosol Generator system and also with detection of termocord. It can be used for all classes of fire, the product Minimum Life shall be 15 years and no maintenance. The Discharge time should be 20 sec. The Generator has a net weight of 5 kg. Active substance of 2 Kg. The generator has a capacity to cover 40 m3. ETDC-Govt of India Approved. Makes: - As per list of recommended brands.	1 No	78500
		ELEC-9.4.33	Providing/ Conducting third-party audit of fire safety including submission of audit report for the whole premises.	1 Sq.mtr	8
		9.5	FIRE HYDRANT AND SPRINKLER SYSTEM		
			ELECTRIC DRIVEN MAIN FIRE PUMPS (SPLIT CASE)		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
782	MAT-04402	ELEC-9.5.1	Supplying, installation, testing and commissioning of electric driven main fire pump suitable for automatic operation and consisting of following complete in all respect as required	1 Set	401856
			a) Horizontal type, multistage, centrifugal, split casing pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal to ensure a minimum pressure of 3.5 Kg / sq.cm. at the highest and farthest outlet at specified flow of 1620 lpm at 56 Mtr. head conforming to IS 1520		
			b) Suitable HP SQ cage induction motor, TEFC, synchronous speed 1500 RPM, suitable for operation on 415Volts, 3 phase 50 Hz. AC with IP 55 protection for enclosure, horizontal foot mounted type with Class-'F' insulation, conforming to IS-325		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
783	MAT-04403	ELEC-9.5.2	Supplying, installation , testing and commissioning of electric driven main fire pump suitable for automatic operation and consisting of following : complete in all respect as required	1 Set	452088
			a) Horizontal type, multistage, centrifugal, split casing pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal to ensure a minimum pressure of 3.5 Kg / sq.cm. at highest and farthest outlet at specified flow of 2280 lpm at 70 Mtr. head conforming to IS 1520		
			b) Suitable HP SQ cage induction motor, TEFC, synchronous speed 1500 RPM, suitable for operation on 415Volts, 3 phase 50 Hz. AC with IP 55 protection for enclosure, horizontal foot mounted type with Class-'F' insulation, conforming to IS-325		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
784	MAT-04404	ELEC-9.5.3	Supplying Installation, testing and commissioning of electric driven main fire pump suitable for automatic operation and consisting of following Complete in all respect as required.		703248

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			a) Horizontal type, multistage, centrifugal, split casing pump of cast iron body and bronze impeller with stainless steel shaft, mechanical seal to ensure a minimum pressure of 3.5 kg/sq.cm. at highest and farthest outlet at specified flow of 2280 LPM and 120 Metres head conforming to IS 1520.		
			b) Suitable HP SQ cage induction motor, TEFC, synchronous speed 1500 RPM, suitable for operation on 415 volts, 3 phase 50 Hz. AC with IP 55 protection for enclosure, horizontal foot mounted type with Class-'F' insulation, conforming to IS-325		
			c)M.S. fabricated Common base plate, coupling, coupling guard, foundation bolts etc. as required.		
			d)Suitable CC foundation of 1:2:4 ratio (1 Cement: 2 coarse sand : 4 graded stone aggregate 40 mm nominal size) duly plastered and with anti-vibration pads. Makes: As per list of recommended brands.		
785	MAT-04405	ELEC-9.5.4	Supplying, installation, testing and commissioning of electric driven main fire pump suitable for automatic operation and consisting of following complete in all respect as required.	1 Set	521157
			a) Horizontal type, multistage, centrifugal, split casing pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal to ensure a minimum pressure of 3.5 Kg / sq.cm. at highest and farthest outlet at specified flow of 2850 lpm at 70 Mtr. head conforming to IS 1520		
			b) Suitable HP SQ cage induction motor, TEFC, synchronous speed 1500 RPM, suitable for operation on 415Volts, 3 phase 50 Hz. AC with IP 55 protection for enclosure, horizontal foot mounted type with Class-'F' insulation, conforming to IS-325		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
786	MAT-04406	ELEC-9.5.5	Supplying Installation, testing and commissioning of electric driven main fire pump suitable for automatic operation and consisting of following Complete in all respect as required.	1 Set	728364

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			a) Horizontal type, multistage, centrifugal, split casing pump of cast iron body and bronze impeller with stainless steel shaft, mechanical seal to ensure a minimum pressure of 3.5 kg/sq.cm. at highest and farthest outlet at specified flow of 2850 LPM and 120 Metres head conforming to IS 1520.		
			b) Suitable HP SQ cage induction motor, TEFC, synchronous speed 1470 RPM, suitable for operation on 415 volts, 3 phase 50 Hz. AC with IP 55 protection for enclosure, horizontal foot mounted type with Class-'F' insulation, conforming to IS-325		
			c)M.S. fabricated Common base plate, coupling, coupling guard, foundation bolts etc. as required.		
			d)Suitable CC foundation of 1:2:4 ratio (1 Cement: 2 coarse sand : 4 graded stone aggregate 40 mm nominal size) duly plastered and with anti-vibration pads Makes: As per list of recommended brands.		
			DIESEL ENGINE DRIVEN FIRE PUMPS		
787	MAT-04407	ELEC-9.5.6	Supplying, installation, Testing and commissioning of diesel engine driven main fire pump suitable for automatic operation and consisting of following : complete in all respect as required	1 Set	522413
			a) Horizontal type, multistage, centrifugal pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal to ensure a minimum pressure of 3.5 Kg / sq.cm. at highest and farthest outlet at specified flow of 1620 lpm at 56 Mtr head conforming to IS 1520		
			b) Suitable HP, 1500 RPM water cooled with radiator, diesel engine conforming to relevant BS & IS standard complete with auto starting mechanism, 12 Volts / 24 Volts electric starting equipment, Diesel Tank, exhaust pipe extended upto 1 m. outside pump house duly insulated with 50mm thick glass wool with 1.0mm thick aluminum sheet cladding, residential silencer, instruments and protection as per specification, stop solenoid for auto stop in the event of fault with audio indications, painted with post office red color etc as required.		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
788	MAT-04408	ELEC-9.5.7	Supplying, installation, Testing and commissioning of diesel engine driven main fire pump suitable for automatic operation and consisting of following : complete in all respect as required	1 Set	753480
			a) Horizontal type, multistage, centrifugal pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal to ensure a minimum pressure of 3.5 Kg / sq.cm. at highest and farthest outlet at specified flow of 2280 lpm at 70 Mtr head conforming to IS 1520		
			b) Suitable HP, 1500 RPM water cooled with radiator, diesel engine conforming to relevant BS & IS standard complete with auto starting mechanism, 12 Volts / 24 Volts electric starting equipment, Diesel Tank, exhaust pipe extended upto 1 m. outside pump house duly insulated with 50mm thick glass wool with 1.0mm thick aluminum sheet cladding, residential silencer, instruments and protection as per specification, stop solenoid for auto stop in the event of fault with audio indications, painted with post office red colour etc as required.		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
789	MAT-04409	ELEC-9.5.8	Supplying, installation, Testing and commissioning of diesel engine driven main fire pump suitable for automatic operation and consisting of following : complete in all respect as required		910455
			a) Horizontal type, multistage, centrifugal pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal to ensure a minimum pressure of 3.5 Kg / sq.cm. at highest and farthest outlet at specified flow of 2280 lpm at 120 Mtr head conforming to IS 1520		
			b) Suitable HP, 1500 RPM water cooled with radiator, diesel engine conforming to relevant BS & IS standard complete with auto starting mechanism, 12 Volts / 24 Volts electric starting equipment, Diesel Tank, exhaust pipe extended upto 1 m. outside pump house duly insulated with 50mm thick glass wool with 1.0mm thick aluminum sheet cladding, residential silencer, instruments and protection as per specification, stop solenoid for auto stop in the event of fault with audio indications, painted with post office red colour etc as required.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
790	MAT-04410	ELEC-9.5.9	Supplying, installation, Testing and commissioning of diesel engine driven main fire pump suitable for automatic operation and consisting of following: complete in all respect as required	1 Set	853944
			a) Horizontal type, multistage, centrifugal pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal to ensure a minimum pressure of 3.5 Kg / sq.cm. at highest and farthest outlet at specified flow of 2850 lpm at 70 Mtr head conforming to IS 1520		
			b) Suitable HP, 1500 RPM water cooled with radiator, diesel engine conforming to relevant BS & IS standard complete with auto starting mechanism, 12 Volts / 24 Volts electric starting equipment, Diesel Tank, exhaust pipe extended upto 1 m. outside pump house duly insulated with 50mm thick glass wool with 1.0mm thick aluminum sheet cladding, residential silencer, instruments and protection as per specification, stop solenoid for auto stop in the event of fault with audio indications, painted with post office red colour etc as required.		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
791	MAT-04411	ELEC-9.5.10	Supplying, installation, Testing and commissioning of diesel engine driven main fire pump suitable for automatic operation and consisting of following: complete in all respect as required	1 Set	973245
			a) Horizontal type, multistage, centrifugal pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal to ensure a minimum pressure of 3.5 Kg / sq.cm. at highest and farthest outlet at specified flow of 2850 lpm at 120 Mtr head conforming to IS 1520		
			b) Suitable HP, 1500 RPM water cooled with radiator, diesel engine conforming to relevant BS & IS standard complete with auto starting mechanism, 12 Volts / 24 Volts electric starting equipment, Diesel Tank, exhaust pipe extended upto 1 m. outside pump house duly insulated with 50mm thick glass wool with 1.0mm thick aluminum sheet cladding, residential silencer, instruments and protection as per specification, stop		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			solenoid for auto stop in the event of fault with audio indications, painted with post office red colour etc as required.		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
			ELECTRIC DRIVEN MAIN FIRE PUMPS (END SUCTION)		
792	MAT-04412	ELEC-9.5.11	Supplying, installation, testing and commissioning of electric driven main fire pump suitable for automatic operation and consisting of following : complete in all respect as required	1 Set	301392
			a) End suction back pull-out centrifugal pump, Std fitted with BRONZE IMPELLER & gland packing, capacity 171 Cum/hr (2850 LPM) at total head 70 M at operating speed 2900 rpm. Pump duty as per TAC		
			b) 55 KW / 75 HP, 3000 rpm, TEFC (IP55) horizontal foot mounted, squirrel cage induction motor, suitable for 415 volts +/- 10%, 3 Ph, 50 Hz +/-5%, a.c. supply. Class 'F' insulated and suitable for ambient temperature up to 50 deg C. Motor in frame SC 250 M frame for driving above pump.		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
793	MAT-04413	ELEC 9.5.12	Supplying, installation , testing and commissioning of electric driven main fire pump suitable for automatic operation and consisting of following : complete in all respect as required	1 Set	246137

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			a) End suction back pull out centrifugal pump, Std fitted with BRONZE IMPELLER & gland packing ,capacity 137 Cum/hr (2280 LPM) at total head 70 mwc at operating speed 2900 rpm. Pump duty as per TAC		
			b) 45 KW / 60 HP, 3000 rpm, TEFC (IP55) Horizontal foot mounted, squirrel cage induction motor, suitable for 415 volts +/- 10%, 3 Ph, 50 Hz +/-5%, a.c. supply. Class 'F' insulated and suitable for ambient temperature up to 50 deg C. Motor in frame SC 225 M frame		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
794	MAT-04414	ELEC 9.5.13	Supplying, installation, Testing and commissioning of Electric engine driven main fire pump suitable for automatic operation and consisting of following: complete in all respect as required		180835
			a) End suction back pull out centrifugal pump, Std fitted with BRONZE IMPELLER & gland packing, capacity 97 Cum/hr (1620 LPM) at total head 56 mwc at operating speed 2900 rpm. Pump duty as per TAC		
			b) 30 KW / 40 HP, 3000 srpm, TEFC (IP55) horizontal foot mounted, squirrel cage induction motor, suitable for 415 volts +/- 10%, 3 Ph, 50 Hz +/-5%, a.c.supply. Class 'F' insulated and suitable for ambient temperature up to 50 deg C. Motor in frame SC 250 M frame for driving above pump.		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
			DIESEL ENGINE DRIVEN MAIN FIRE PUMPS (END SUCTION)		
795	MAT-04415	ELEC-9.5.14	Supplying, installation, Testing and commissioning of diesel engine driven main fire pump suitable for automatic operation and consisting of following: complete in all respect as required	1 Set	626644

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			a) End suction back pull out pump, Std fitted with BRONZE Impeller & gland packing, capable of delivering 171 Cum/hr(2850 LPM) at a total head of 70 M when operated at 1800 rpm and pump duty as per TAC		
			b) Liquid cooled, 85 BHP at 1800 rpm, diesel engine (Radiator cooled) 12 Volts starting system with standard accessories		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
796	MAT-04416	ELEC-9.5.15	Supplying, installation, Testing and commissioning of diesel engine driven main fire pump suitable for automatic operation and consisting of following: complete in all respect as required	1 Set	499808
			a) End suction back pull out pump, Std fitted with BRONZE Impeller & gland packing, capable of delivering 137 Cum/hr(2280 LPM) at a total head of 70 M when operated at 2150 rpm and pump duty as per TAC		
			b) Liquid cooled, 68 BHP at 1800 rpm, Diesel engine (Radiator cooled) 12 Volts starting system with standard accessories		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
797	MAT-04417	ELEC-9.5.16	Supplying, installation, Testing and commissioning of Diesel engine driven main fire pump suitable for automatic operation and consisting of following : complete in all respect as required	1 Set	437018
			a) End suction back pull out pump, Std fitted with BRONZE Impeller & gland packing, capable of delivering 97 Cum/hr(1620 LPM) at a total head of 56 M when operated at 2150 rpm and pump duty as per TAC		
			b) Liquid cooled, 50 BHP at 1800 rpm, Diesel engine (Radiator cooled) 12 Volts starting system with standard accessories		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
			JOCKEY PUMPS		
798	MAT-04418	ELEC-9.5.17	Supplying, installation , testing and commissioning of electric driven pressurization / Jockey pump suitable for automatic operation and consisting of following : complete in all respect as required	1 Set	61534
			a) Horizontal type, multistage, centrifugal pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal and flow of 180 lpm at 56 Mtr head conforming to IS 1520		
			b) Suitable HP SQ cage induction motor TEFC type suitable for operation on 415Volts, 3 phase 50 Hz. AC with IP 55 class of protection for enclosure, horizontal foot mounted type with Class-'F' insulation, conforming to IS-325		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
799	MAT-04419	ELEC-9.5.18	Supplying, installation, testing and commissioning of electric driven pressurization / Jockey pump suitable for automatic operation and consisting of following: complete in all respect as required	1 Set	90418
			a) Horizontal type, multistage, centrifugal pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal and flow of 180 lpm at 70 Mtr head conforming to IS 1520		
			b) Suitable HP SQ cage induction motor TEFC type suitable for operation on 415Volts, 3 phase 50 Hz. AC with IP 55 class of protection for enclosure, horizontal foot mounted type with Class-'F' insulation, conforming to IS-325		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
800	MAT-04420	ELEC-9.5.19	Supplying, installation, testing and commissioning of electric driven pressurization / Jockey pump suitable for automatic operation and consisting of following: complete in all respect as required	1set	138138
			a) Horizontal type, multistage, centrifugal pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal and flow of 180 lpm at 120 Mtr head conforming to IS 1520		
			b) Suitable HP SQ cage induction motor TEFC type suitable for operation on 415Volts, 3 phase 50 Hz. AC with IP 55 class of protection for enclosure, horizontal foot mounted type with Class-'F' insulation, conforming to IS-325		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
			BOOSTER PUMPS		
801	MAT-04421	ELEC-9.5.20	Supplying, installation, testing and commissioning of electric driven Terrace / Booster pump suitable for automatic operation and consisting of following: complete in all respect as required.	1 Set	70325
			a) Horizontal type, multistage, centrifugal pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal and flow of 900 lpm at 45 Mtr head conforming to IS 1520		
			b) Suitable HP SQ cage induction motor TEFC type suitable for operation on 415Volts, 3 phase 50 Hz. AC with IP 55 class of protection for enclosure, horizontal foot mounted type with Class-'F' insulation, conforming to IS-325		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
802	MAT-04422	ELEC-9.5.21	Supplying, installation , testing and commissioning of electric driven Terrace / Mono Bloc Booster pump suitable for automatic operation and consisting of following : complete in all respect as required.	1 Set	54627

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			a) Horizontal type, centrifugal End Suction pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal and flow of 900 lpm at 45 Mtr head conforming to IS 1520		
			b) Three Phase High Speed Centrifugal Pump. Pump with CI Impeller and Gland Packing with 9.3 KW / 12.5HP, 2 pole, TEFC, 415 V, 3ph motor		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
803	MAT-04423	ELEC-9.5.22	Supplying, installation, testing and commissioning of electric driven Terrace / Mono Bloc Booster pump suitable for automatic operation and consisting of following: complete in all respect as required.	1 Set	52116
			a) Horizontal type, centrifugal End Suction pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal and flow of 750 lpm at 35 Mtr head conforming to IS 1520		
			b) Three Phase High Speed Centrifugal Pump. Pump with CI Impeller and Gland Packing with 7.5 KW / 10 HP, 2 pole, TEFC, 415 V, 3ph motor		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
804	MAT-04424	ELEC-9.5.23	Supplying, installation, testing and commissioning of electric driven Terrace / Mono Bloc Booster pump suitable for automatic operation and consisting of following: complete in all respect as required.	1 Set	47972
			a) Horizontal type, centrifugal End Suction pump of cast iron body & bronze impeller with stainless steel shaft, mechanical seal and flow of 450 lpm at 35 Mtr head conforming to IS 1520		
			b) Three Phase High Speed Centrifugal Pump. Pump with CI Impeller and Gland Packing with 5 KW / 7.5 HP, 2 pole, TEFC, 415 V, 3ph motor		
			c) M.S. Fabricated common base plate, coupling, coupling guard, foundation bolts etc as required.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			d) Suitable cement concrete foundation duly plastered with anti-vibration pads. Makes: As per list of recommended brands.		
			CONTROL PANELS		
805	MAT-05602	ELEC-9.5.24	Fabrication, supply, transportation, Installation testing & commissioning of Electrical control panel of cubical construction, floor mounted type, fabricated out of 2mm thick CRCA sheet, compartmentalized with hinged lockable doors, dust and vermin proof, powder coated of approved shade after 7 tank treatment process, cable alley, interconnection with suitable size copper conductor cable/solid copper strip, having switchgears and accessories, mountings and internal wiring, earth terminals, numbering etc. complete in all respect, suitable for main fire pump, pressurization pump & diesel pump set complete with following in coming and Outgoings, suitable for operation on 415V, 3 phase, 50Hz Ac Supply. Makes: As per list of recommended brands.	1 No	266783
			<u>INCOMING :</u>		
			250A, 50kA 4 Pole MCCB, Ics = 100%, Icu rating		
			Digital Voltmeter 0-500V with selector switch		
			Digital Ammeter (0-250 A) with selector switch & CTs etc.		
			LED type RYB phase indicating lamps, ON, OFF, trip indicating lamps		
			Set of Copper Bus Bar 300A		
			<u>OUTGOING :</u>		
			(Note : All outgoing feeders for pumps should have digital Ammeter with selector switches, and LED type ON, OFF, trip indicating lamps)		
			<u>MAIN FIRE PUMP</u>		
			125 A, 50kA TPN MCCB, Ics=100% Icu, with fully automatic Star/Delta starter suitable for 60 HP pump with overload protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation selector switch for local/remote, auto/manual/OFF operation.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			<u>JOCKEY PUMP</u>		
			63 A, 50kA TPN MCCB, Ics=100% Icu, with suitable protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation, selector switch for local/remote, auto/manual/OFF operation.		
			<u>DIESEL ENGINE CONTROL</u>		
			Control for diesel engine comprising - Automatic/Manual selector switch & 3 attempts starting device, timers and relays as required, push buttons, start/stop in manual mode Indicating lamp for high/ low lube oil pressure, High Water Temp and Engine on indication Water Temp and Engine on indication. Battery charger suitable for 12V/24 V DC with boost and trickle selector switch, 0-30 V DC voltmeter, and 0- 20 A DC Ammeter All standard relays and accessories for automatic operation of diesel engine System Controller.		
806	MAT-05603	ELEC-9.5.25	Designing, Supply, Transportation, Installation, Testing and commissioning of system controller to control operation of main electric fire pump, diesel pump, Pressurization pump, Terrace pump in sequence as per specification consisting of relays, timers. Sensors, annunciation window for fault indication, complete as per specification Makes: As per list of recommended brands.	1 No	313935
			<u>INCOMING :</u>		
			400A, 50kA 4 Pole MCCB, Ics=100% Icu rating		
			Digital Voltmeter 0-500V with selector switch		
			Ammeter (0-400 A) with selector switch & CTs etc.		
			LED type RYB phase indicating lamps, ON, OFF, trip		
			indicating lamps		
			Set of Copper Bus Bar 500A		
			<u>OUTGOING :</u>		
			(Note : All outgoing feeders for pumps should have		
			digital Ammeter with selector switches, and LED type		
			ON, OFF, trip indicating lamps)		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			MAIN FIRE PUMP		
			200 A, 50kA TPN MCCB, Ics=100% Icu, with fully automatic Star/Delta starter suitable for 75 hp pump with overload protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation, selector switch for local/remote, auto/manual/OFF operation.		
			JOCKEY PUMP		
			100 A, 50kA TPN MCCB, Ics=100% Icu, with suitable HP fully automatic Star/Delta starter with overload protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation, selector switch for local/remote, auto/manual/OFF operation.		
			DIESEL ENGINE CONTROL		
			Control for diesel engine comprising - Automatic/Manual selector switch & 3 attempt starting device, timers and relays as required, push buttons, start/stop in manual mode Indicating lamp for high/ low lube oil pressure, High Water Temp and Engine on indication Battery charger suitable for 12V/24 V DC with boost and trickle selector switch, 0-30 V DC volt meter, and 0-20 A DC Ammeter All standard relays and accessories for automatic operation of diesel engine System Controller		
807	MAT-05604	ELEC-9.5.26	Designing, Supply, Transportation, Installation, Testing and commissioning of system controller to control operation of main electric fire pump, diesel pump, Pressurization pump, Terrace pump in sequence as per specification consisting of relays, timers. Sensors, annunciation window for fault indication, complete as per specifications. Makes: As per list of recommended brands.	1 No	347438
			<u>INCOMING :</u>		
			630A, 50kA 4 Pole MCCB, Ics=100% Icu rating		
			Digital Voltmeter 0-500V with selector switch		
			Ammeter (0-630 A) with selector switch & CTs etc.		
			LED type RYB phase indicating lamps, ON, OFF, trip		
			indicating lamps		
			Set of Copper Bus Bar 800Amps		
			<u>OUT GOING :</u>		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			(Note : All outgoing feeders for pumps should have		
			digital Ammeter with selector switches, and LED type		
			ON, OFF, trip indicating lamps)		
			<u>MAIN FIRE PUMP</u>		
			250 A, 50kA TPN MCCB, Ics=100% Icu, with fully automatic Star/Delta starter suitable for 100 hp pump with overload protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation, selector switch for local/remote, auto/manual/OFF operation.		
			<u>JOCKEY PUMP</u>		
			125 A, 50kA TPN MCCB, Ics=100% Icu, with Suitable HP fully automatic Star/Delta starter with over load protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation, selector switch for local/remote, auto/manual/OFF operation.		
			<u>DIESEL ENGINE CONTROL</u>		
			Control for diesel engine comprising - Automatic/Manual selector switch & 3 attempts starting device, timers and relays as required, push buttons, start/stop in manual mode Indicating lamp for high/ Low Lub. Oil pressure, High Water Temp and Engine on indication Battery charger suitable for 12V/24 V DC with boost and trickle selector switch, 0-30 V DC volt meter, and 0-20 A DC Ammeter All standard relays and accessories for automatic operation of diesel engine System Controller.		
808	MAT-05605	ELEC-9.5.27	Designing, Supply, Transportation, Installation, Testing and commissioning of system controller to control operation of main electric fire pump, diesel pump, Pressurization pump, Terrace pump in sequence as per specification consisting of relays, timers. Sensors, annunciation window for fault indication, complete as per specification Makes: As per list of recommended brands.	1 No	406999
			<u>INCOMING :</u>		
			400A, 50kA 4 Pole MCCB, Ics=100% Icu Rating		
			Digital Voltmeter 0-500V with selector switch		
			Ammeter (0-400 A) with selector switch & CTs etc.		
			LED type RYB phase indicating lamps, ON, OFF, trip		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			indicating lamps		
			Set of Copper Bus Bar 500Amps		
			<u>OUT GOING :</u>		
			(Note : All outgoing feeders for pumps should have		
			digital Ammeter with selector switches, and LED type		
			ON, OFF, trip indicating lamps)		
			MAIN FIRE PUMPS		
			125 Amp, 50kA TPN MCCB, Ics=100% Icu, with fully automatic Star/Delta starter suitable for 60 hp pump with overload protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation, selector switch for local/remote, auto/manual/OFF operation. - 2 sets		
			JOCKEY PUMP		
			63 Amp, 50kA TPN MCCB, Ics=100% Icu, with Suitable HP fully automatic Star/Delta starter with overload protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation, selector switch for local/remote, auto/manual/OFF operation. - 2 sets		
			DIESEL ENGINE CONTROL		
			Control for diesel engine comprising - Automatic/Manual selector switch & 3 attempts starting device, timers and relays as required, push buttons, start/stop in manual mode Indicating lamp for high/ Low Lub. Oil pressure, High Water Temp and Engine on indi Battery charger suitable for 12V/24 V DC with boost and trickle selector switch, 0-30 V DC volt meter, and 0-20 A DC Ammeter All standard relays and accessories for automatic operation of diesel engine System Controller		
809	MAT-05606	ELEC-9.5.28	Designing, Supply, Transportation, Installation, Testing and commissioning of system controller to control operation of main electric fire pump, diesel pump, Pressurization pump, Terrace pump in sequence as per specification consisting of relays, timers. Sensors, annunciation window for fault indication, complete as per specification Makes: As per list of recommended brands.	1 No	486413
			<u>INCOMING :</u>		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			630A, 50kA 4 Pole MCCB, Ics=100% Icu Rating		
			Digital Voltmeter 0-500V with selector switch		
			Ammeter (0-630 A) with selector switch & CTs etc.		
			LED type RYB phase indicating lamps, ON, OFF, trip		
			indicating lamps		
			Set of Copper Bus Bar 800Amps		
			<u>OUT GOING :</u>		
			(Note : All outgoing feeders for pumps should have		
			digital Ammeter with selector switches, and LED type		
			ON, OFF, trip indicating lamps)		
			MAIN FIRE PUMP		
			200 Amp, 50kA TPN MCCB, Ics=100% Icu, with fully automatic Star/Delta starter suitable for 75 hp pump with overload protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation, selector switch for local/remote, auto/manual/OFF operation. - 2 sets		
			JOCKEY PUMP		
			100 Amp, 50kA TPN MCCB, Ics=100% Icu, with Suitable HP fully automatic Star/Delta starter with overload protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation, selector switch for local/remote, auto/manual/OFF operation. - 2 sets		
			DIESEL ENGINE CONTROL		
			Control for diesel engine comprising - Automatic/Manual selector switch & 3 attempts starting device, timers and relays as required, push buttons, start/stop in manual mode Indicating lamp for high/ Low Lub. Oil pressure, High Water Temp and Engine on indication Battery charger suitable for 12V/24 V DC with boost and trickle selector switch, 0-30 V DC volt meter, and 0-20 A DC Ammeter All standard relays and accessories for automatic operation of diesel engine System Controller.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
810	MAT-05607	ELEC-9.5.29	Designing, Supply, Transportation, Installation, Testing and commissioning of system controller to control operation of main electric fire pump, diesel pump, Pressurization pump, Terrace pump in sequence as per specification consisting of relays, timers. Sensors, annunciation window for fault indication, complete as per specification Makes: As per list of recommended brands.	1 No	620425
			<u>INCOMING :</u>		
			800A, 50kA 4 Pole MCCB, Ics=100% Icu Rating		
			Digital Voltmeter 0-500V with selector switch		
			Ammeter (0-800 A) with selector switch & CTs etc.		
			LED type RYB phase indicating lamps, ON, OFF, trip		
			indicating lamps		
			Set of Copper Bus Bar 1000Amps		
			<u>OUT GOING:</u>		
			(Note : All outgoing feeders for pumps should have		
			digital Ammeter with selector switches, and LED type		
			ON, OFF, trip indicating lamps)		
			Main Fire Pump		
			250 Amp, 50kA TPN MCCB, Ics=100% Icu, with fully automatic Star/Delta starter suitable for 100 hp pump with overload protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation, selector switch for local/remote, auto/manual/OFF operation. - 2 sets		
			JOCKEY PUMP		
			125 Amp, 50kA TPN MCCB, Ics=100% Icu, with Suitable HP fully automatic Star/Delta starter with overload protection, current sensing type single phase preventor complete with all accessories and internal wiring required for automatic operation, selector switch for local/remote, auto/manual/OFF operation. - 2 sets		
			DIESEL ENGINE CONTROL		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Control for diesel engine comprising - Automatic/Manual selector switch & 3 attempts starting device, timers and relays as required, push buttons, start/stop in manual mode Indicating lamp for high/ low Lube Oil pressure, High Water Temp and Engine on indication Battery charger suitable for 12V/24 V DC with boost and trickle selector switch, 0-30 V DC volt meter, and 0-20 A DC Ammeter All standard relays and accessories for automatic operation of diesel engine System Controller		
			MS PIPES		
811		ELEC-9.5.30	Providing, laying, testing & Commissioning of following classes MS pipes conforming to IS 3589 and 1239 including fittings like elbows, tees, flanges, tapers, nuts, bolts, gaskets including transportaiton and painting with two coats of red oxide paint and one coat of post office red enamel paint and all labour charges and cost of all accessories etc., complete. Makes: As per list of recommended brands.		
			C-CLASS MS PIPES		
	MAT-04425	a	250 mm dia	1 Mtr	5169
	MAT-04426	b	200 mm dia	1 Mtr	4484
	MAT-04427	c	150 mm dia	1 Mtr	3421
	MAT-04428	d	100 mm dia	1 Mtr	2128
	MAT-04429	e	80 mm dia	1 Mtr	1413
	MAT-04430	f	65 mm dia	1 Mtr	1065
	MAT-04431	g	50 mm dia	1 Mtr	852
	MAT-04432	h	40 mm dia	1 Mtr	722
	MAT-04433	i	32 mm dia	1 Mtr	570
	MAT-04434	j	25 mm dia	1 Mtr	426
			B- CLASS MS PIPES		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04435	a	250 mm dia	1 Mtr	4560
	MAT-04436	b	200 mm dia	1 Mtr	3953
	MAT-04437	c	150 mm dia	1 Mtr	2736
	MAT-04438	d	100 mm dia	1 Mtr	1824
	MAT-04439	e	80 mm dia	1 Mtr	1293
	MAT-04440	f	65 mm dia	1 Mtr	958
	MAT-04441	g	50 mm dia	1 Mtr	745
	MAT-04442	h	40 mm dia	1 Mtr	563
	MAT-04443	i	32 mm dia	1 Mtr	456
	MAT-04444	j	25 mm dia	1 Mtr	380
812		ELEC-9.5.31	Supplying and fixing single headed Internal / External hydrant valve with instantaneous Gun metal/Stainless steel couplings of 63mm dia with Cast iron wheel ISI marked conforming to IS 5290 (Type -A) with blank Gun Metal cap and chain as required. Makes: As per list of recommended brands.		
	MAT-04445	a	Single Headed Gun Metal	1 No	9503
	MAT-05608	b	Single Headed Stainless Steel	1 No	8462
813		ELEC-9.5.32	Supplying, fixing, testing and commissioning of butterfly valve PN 1.6, with Bronze / Gun metal seat duly ISI marked complete with Nuts, Bolts, Washers, gaskets, conforming to IS 13095 of following sizes as required. Makes: As per list of recommended brands.		
	MAT-04446	a	(a) 250 mm . dia	1 No	14971

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04447	b	(b) 200 mm . dia	1 No	6379
	MAT-04448	c	(c) 150 mm dia	1 No	5337
	MAT-04449	d	(d) 100 mm dia	1 No	4101
	MAT-04450	e	(e) 80 mm dia	1 No	3775
814		ELEC-9.5.33	Providing, installation, testing and commissioning of dual Plate non - return valve of following sizes confirming to IS: 5312 complete with rubber gasket, GI bolts, nuts, washers etc as required. Makes: As per list of recommended brands.		
	MAT-04451	a	a) 250mm dia	1 No	23432
	MAT-04452	b	(b) 200 mm dia	1 No	11977
	MAT-04453	c	(c) 150 mm dia	1 No	8592
	MAT-04454	d	(d) 100 mm dia	1 No	4556
	MAT-04455	e	(e) 80 mm dia	1 No	4426
	MAT-04456	f	(f) 50 mm dia	1 No	2343
815		ELEC-9.5.34	Manufacture, Supply and delivery of CI Wafer Lug type Butterfly Valves conforming to IS 13095/1991 (Reaffirmed 1998) excluding transportation, CED and taxes etc., complete. Operation done with worm actuator ISI marked . Makes: As per list of recommended brands.		
	MAT-04457	a	250 mm . dia	1 No	19918
	MAT-04458	b	200 mm . dia	1 No	14320
	MAT-04459	c	150 mm dia	1 No	9113
	MAT-04460	d	100 mm dia	1 No	6118

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04461	e	80 mm dia	1 No	4556
	MAT-04462	f	(50 mm dia	1 No	3645
816		ELEC-9.5.35	Providing, installation, testing and commissioning of gun metal valves of following sizes as required. Makes: As per list of recommended brands.		
	MAT-04463	a	50 mm dia	1 No	2083
	MAT-04464	b	40 mm dia	1 No	1692
	MAT-04465	c	32 mm dia	1 No	1529
817		ELEC-9.5.36	Supplying and fixing 63mm dia, 15 mtr long RRL hose pipe with 63mm dia Male and Female Gun metal / SS couplings duly binded with GI wire, rivets etc conforming to IS 636 (Type -A) as required. Makes: As per list of recommended brands.		
	MAT-04466	a	Gun metal	1 No	7330
	MAT-05609	b	SS couplings	1 No	5468
818		ELEC-9.5.37	Supplying and fixing 63mm dia, 15 mtr long CP hose pipe with 63mm dia Male and Female Gun metal / SS couplings duly binded with GI wire, rivets etc conforming to IS 636 (Type -A) as required. Makes: As per list of recommended brands.		
	MAT-04467	a	Gun metal	1 No	6249
	MAT-05610	b	SS couplings	1 No	5207
819		ELEC-9.5.38	Supply, installation, testing and commissioning of stainless steel Y–strainer fabricated out of 1.6 mm thick SS 304 with following sizes confirming to IS specifications complete with rubber gasket, GI bolts , nuts, washers etc as required. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04468	a	250mm dia	1 No	23953
	MAT-04469	b	200 mm . dia	1 No	22131
	MAT-04470	c	150 mm dia	1 No	10414
	MAT-04471	d	100 mm dia	1 No	5598
	MAT-04472	e	80 mm dia	1 No	5077
820	MAT-04473	ELEC-9.5.39	Supplying and fixing First -Aid Hose Reel with MS construction spray painted in Post office Red, Conforming to Is 884 with upto date amendments, complete with the following as required. Makes: As per list of recommended brands.	1 No	8722
			a) 36.6 Mtr Long 20mm (Nominal internal) dia water hose Thermoplastic / Textile reinforced / Rubber braided / Polypropylene Type - 2 as per IS:12585		
			b) 20mm (Nominal internal) dia gun metal ball/gate valve and nozzle.		
			c) Drum and brackets for fixing the equipment on wall.		
			d) Connections from riser with 25mm dia stop valve (gun metal) & MS pipe.		
821	MAT-04474	ELEC-9.5.40	Supplying and fixing of hose cabinet of size 750mm X 600mm x 250mm made of No 16 gauge SWG CRCA sheet with 6mm thick glazed glass door including necessary locking arrangement suitable to accommodate 2 Nos 15 mtr long Hose pipe, 1 No branch pipe, mounted on wall OR raised brick platform and duly painted with Post office red externally and white internally with synthetic enamel paint complete in all respect, for external hydrant as required. Makes: As per list of recommended brands.	1 No	3775
822		ELEC-9.5.41	Supply and fixing 63mm dia Gun metal branch pipe with 20mm (Nominal internal diameter) size Gun metal / SS nozzle conforming to IS 903, suitable for instantaneous connection to interconnect hose pipe coupling as required. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04475	a	Gun metal	1 No	2864
	MAT-05611	b	SS couplings	1 No	2083
823	MAT-04476	ELEC-9.5.42	Supply and fixing 4 way fire brigade connection of cast iron body with 4 Nos Gun metal Male instantaneous inlet couplings complete with cap and chain as required for 150mm dia MS pipe connection, conforming to IS 904 as required. Makes: As per list of recommended brands.	1 No	10414
824	MAT-04477	ELEC-9.5.43	Supply and fixing 2 way fire brigade connection of cast iron body with 2 Nos Gun metal Male instantaneous inlet couplings complete with cap and chain as required for 100mm dia MS pipe connection, conforming to IS 904 as required. Makes: As per list of recommended brands.	1 No	7811
825	MAT-04478	ELEC-9.5.44	Supply and fixing air vessel made of 250 mm dia, 8 mm thick MS sheet, 1200mm in height with air release valve on top and flanged connection to riser, drain arrangement with 25mm dia Gun metal wheel valve, with required accessories, pressure gauge and painting with synthetic enamel paint of approved shade as required.	1 No	19471
826	MAT-04479	ELEC-9.5.45	Providing fixing, testing and commissioning of 15mm size quartzoid bulb type sprinklers of rating 68° C. pendent / side wall with required accessories. Makes: As per list of recommended brands.	1 No	557
827	MAT-04480	ELEC-9.5.46	Supply fixing, testing and commissioning of UL approved flexible dropper of 1.5 mtr length with required accessories Makes: As per list of recommended brands.	1 No	1329
828	MAT-04481	ELEC-9.5.47	Providing and fixing of Pressure Switch in the MS pipeline including connection etc as required. Makes: As per list of recommended brands.	1 No	2847
829	MAT-04482	ELEC-9.5.48	Providing and fixing Flow Switches in 100mm dia MS pipe. Makes: As per list of recommended brands.	1 No	6072

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
830	MAT-04483	ELEC-9.5.49	Providing and fixing Flow Switches in 150 mm dia MS pipe. Makes: As per list of recommended brands.	1 No	8476
831	MAT-04484	ELEC-9.5.50	Supply, installation, testing and commissioning of Bourdon type, stainless steel dial type pressure gauge with isolation valve and pipe having calibration of 0-16 kg/cm2. Makes: As per list of recommended brands.	1 No	759
832	MAT-04485	ELEC-9.5.51	Supply, installation, testing and commissioning of 25mm dia Gate valve. Makes: As per list of recommended brands.	1 No	1367
833	MAT-04486	ELEC-9.5.52	Supply, installation, testing and commissioning of 25mm dia Ball valve. Makes: As per list of recommended brands.	1 No	755
834	MAT-04487	ELEC-9.5.53	Supply, installation, testing and commissioning of 25 / 20mm dia Air Release Valve Makes: As per list of recommended brands.	1 No	1432
835		ELEC-9.5.54	Supply, installation, testing & commissioning of sprinkler flexible pipe (UL Listed) of stainless steel complete with 15 NPT on reducer thread with maximum working pressure of 175 PSI test pressure of 875 PSI (Burst) with branch line (Inlet) 25mm NPT male thread to sprinkler head (Outlet) 15mm NPT female thread with reducer, nipple, 2 side brackets, center bracket, stock bar of following sizes complete as required. Makes: As per list of recommended brands.		
	MAT-04488	a	750mm to 800 mm	1 No	1139
	MAT-04489	b	1000 mm to 1200 mm	1 No	1329
	MAT-04490	c	1500 mm	1 No	1582
836		ELEC-9.5.55	Providing, fixing, testing & commissioning of installation control valve of cast iron body, brass/bronze working parts comprising of water motor alarm, bronze seat clapper, clapper arm and hydraulically driven mechanical gong bell to sound continuous alarm when the wet riser/sprinkler system activates, pressure gauges, emergency releases, strainer, pressure switch, cock valve complete with drain valve and bypass, test control box, ball valves, MS pipe of required size, flanges, orifice plate, gasket etc of following sizes as required :		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: As per list of recommended brands.		
	MAT-05612	a	80mm dia	1 No	46865
	MAT-05613	b	100mm dia	1 No	49468
	MAT-04491	c	150mm dia	1 No	52072
837		ELEC-9.5.56	Supplying, installing, testing and commissioning of CI body Foot Valve with brass strainer with necessary flanges, nuts and bolts etc., complete on to the suction line. Makes: As per list of recommended brands.		
	MAT-04492	a	a) 200mm nominal dia	1 Ea	29030
	MAT-04493	b	b) 150mm nominal dia	1 Ea	15622
	MAT-04494	c	c) 100mm nominal dia	1 Ea	8722
	MAT-04495	d	d) 80mm nominal dia	1 Ea	5988
838		ELEC-9.5.57	Supply and laying of 300mm dia NP2 RCC Hume pipe with Collars for Road crossings -As per Civil SoR		
839		ELEC-9.5.58	Supplying and wrapping the anticorrosive material for buried pipes with coating of Primer and wrapping with 4 mm thick polymer corrosion resistant tape as per IS: 10221 with 15 mm overlap as per specifications. Makes: As per list of recommended brands.		
	MAT-04496	a	a) 200mm nominal dia	1 Mtr	521
	MAT-04497	b	b) 150mm nominal dia	1 Mtr	391
	MAT-04498	c	c) 100mm nominal dia	1 Mtr	352
	MAT-04499	d	d) 80mm nominal dia	1 Mtr	300

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
840	MAT-04500	ELEC-9.5.59	Supply, fabricating, installing structural steel supports for fixing all sizes of MS pipes from ceiling / wall with MS Channels, Angles, Flats, Rods, as required at site with anchor fasteners, Clamps, threaded rods, nuts, bolts, washers etc complete with painting.	1 Kg	82
841	MAT-08784	ELEC-9.5.60	Fabrication ,transportation and supply of fully outdoor type wall mounted/floor mounted automatic control panel board with IP-66 protection for 3 phase 7.5 H.P. Motor of Booster Pump set of size 600x 600 x 250mm made of 18 SWG CRCA sheet steel enclosure, 14 SWG mounting plate for cable entry fabricated , painted with two coats of Red oxide primer and two coats of Grey paint, lock and key arrangements two side louvers with weld mesh inside and mounted on suitable angle frame work of 450mm height on a PCC pedestal over the terrace consisting of the following equipment/ components with all internal wiring for power and control circuits and control wiring from sensors like pressure switches etc., using copper FRLS cables of suitable size and capacity and cable clamp etc complete with DOL Starter of including cost of all materials and all labour charges, transportation etc., complete for finished item of work. (Panel shall be fabricated from reputed and branded manufacturers approved by dept and having CPRI approval with CPRI test certificates). Makes: As per list of recommended brands.	1 No	24817
			1) Supply & Fixing of DOL Starter suitable for 7.5 HP Pump Motor - 1 No 2) Supply and fixing of (0-500) V range Voltmeter on existing panel, making connection by PVC insulated copper conductor with PVC sleeves/channel etc., as required. -1 No 3) Supply and fixing of CT operated direct reading type Ammeter, below 500A, on existing panel, making connection by PVC insulated copper conductor with PVC sleeves/channel etc. as required - 1 No 4) Supply and fixing of selector switch for Voltmeter & Ammeter (4 position) including making connection etc. as required - 2 No 5) Supply and fixing of 240/220 V, LED (22.5 mm		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			dia) Pilot indication lamps Red, Yellow & Blue Colour with integral circuit, terminal block, including connection etc. as required - 3 No 6) Supply and Fixing of Single Phase Preventor of suitable range - 1No. 7) Supply and fixing of ISI Mark suitable capacitor 8) Supply and Fixing of MPCB (Motor Protection Circuit Breaker) suitable for 7.5 HP Motor, Icu=50 KA with adjustable thermal and magnetic release Panel Mounted 9) Supply and Fixing of Non-Luminous type, ON/OFF/TRIP push button actuators and integral contact block of dia. 22.5 mm including making connections etc. as required. 10) Supply and Fixing of AC operated heavy duty 230 /440 Volt power contactor conforming to IS:13947-4-1/IEC:947-4-1 having provision of mechanical interlocking, Din rail mounting type including making connections, testing etc. as required. - 3 pole, 35-40A, AC3 Rating, Contactor - 1 No 11) Supply and fixing of 24 V DC, Aux Contactor with 2 NO + 2NC Contacts with suitable NO+NC ADD on Block 12) Supply and fixing of thermal over load relay with built in single phase protection and having at least 1NO & 1NC contacts, manual /auto reset facility including making connection testing etc. as required - 1 No 13) Supply and Fixing of Current Transformer, upto 150 / 5 ratio, 10 VA , class 1 accuracy with all necessary support in existing panel including connection etc. as required - 3 No		
			Control & Power wiring with suitable size of approved make FRLS PVC flexible copper wires and from pressure sensors etc., Earth Bus Bar, Door Loop earthing, Ferrules, danger plate, door locks, mounting arrangements with 40x40x6mm MS angle iron frame, PCC and masonry work, painting for MS angle frame with red oxide and enamel paint etc., and all other accessories including all labour charges etc with connections for finished item of work including transportation charges		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
842	MAT-08785	ELEC-9.5.61	Providing and fixing of gun metal fire Brigade suction Hose coupling (Draw-out Connection) with nut for female coupling as per IS:902- 1974 complete with 100 mm dia. G.I. Suction pipe and 100 mm dia. 1No. C.I. Foot valve flanged (to be connected to static water tank). Makes: As per list of recommended brands.		7854
843	MAT-08786	ELEC-9.5.62	Providing, installation, testing & commissioning of water curtain nozzle 15mm dia nickel chrome plated brass, BSPT, K-factor as per design consideration complete as required. Makes: As per list of recommended brands.		556
844	MAT-08787	ELEC-9.5.63	Supplying and fixing orifice plate made out of 6 mm thick stainless steel (Grade 304) with orifice of required size to be fitted between flange& landing valve of external and internal hydrants to reduce pressure at the outlet to the level of 3.5 kg/cm2 complete as required. Makes: As per list of recommended brands.		1086
845		ELEC-9.5.64	Supply, Installation, testing and commissioning of stainless steel puddle flange fabricated out of 1.6mm thick SS 304 confirming to IS specifications including nuts, bolts and rubber insertions etc. Makes: As per list of recommended brands.		
	MAT-08788	a	150 mm dia	1 No	7315
	MAT-08789	b	100mm dia	1 No	6380
	MAT-08790	c	80 mm dia	1 No	4950
	MAT-08791	d	65 mm dia	1 No	3300
	MAT-08792	e	50 mm dia	1 No	3080
846	MAT-08793	ELEC-9.5.65	Supply, Erection, Testing and commissioning of Sluice valves as per IS:14846 (PN 10 Rating, for suction side of the pumps) and rising spindle type with flanges, bolts, nuts, washers, gaskets etc. The valve shall be fitted with Supervisory switch for monitoring. Makes: As per list of recommended brands.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			100mm dia		12100
847	MAT-08794	ELEC-9.5.66	Supplying, installation, testing & commissioning of deluge valve (to be used for water curtains) UL listed with wet pilot basic trim assembly for DVA with test and alarm, drip and drain valve with water motor gong complete as required. Makes: As per list of recommended brands.		
			150mm dia		102198
848	MAT-08795	ELEC-9.5.67	Providing, installation, testing & commissioning of electric release trim assembly for deluge wall with two way solenoid valve, weather proof operation on 24 volts DC supply complete as required. Makes: As per list of recommended brands.		6204
849	MAT-08796	ELEC-9.5.68	Providing, installation, testing & commissioning of adjustable rosette plate for 15mm dia in white finish as per specifications complete as required.		171
850		ELEC-9.5.69	Supply & Installation, Testing and commissioning of trolley mounted, electrically operated triplex plunger pumps with 2-H.P, 1-Phase 1450 rpm, 1-phase motor with high pressure triplex pump of 5-0 kg/cm ² with nylon hydraulic hose pipe of 3/4" dia, 5mt height for suction and 3/8" dia 30mt length for delivery with all required nozzles has valves, high pressure gun, fittings etc with come of 3-core, 2.5 Sq mm flexible copper cable with 3-pin 16A top and all required accessories and labour charges for erection, testing including transportation etc. complete, Make of motor: crompton, kiroken, texmo, suguna with ISI mark, Pump: Green tech, Kisan, Ultrajet, Pressurejet, Ambica tools, searaa or any ISI	Each	41625
851		ELEC-9.5.70	Supply and installation, testing and commissioning of trolley mounted 6.50HP high pressure petrol driven triplex pump with hydraulic nylon pipes 3/4" dia, 5mt length for suction 3/8" dia 30mt length for delivery, nozzles, valves high pressure gun, fitting etc complete with all required accessories and labour charges for erection testing and transportation etc complete.	Each	35000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
852		ELEC-9.5.71	Supply & Installation, Testing and commissioning of trolley mounted, electrically operated triplex plunger pumps with 5-H.P, 1-Phase 1450 rpm, 1-phase motor with high pressure triplex pump of 5-0 kg/cm ² with nylon hydraulic hose pipe of 3/4" dia, 5mt height for suction and 3/8" dia 30mt length for delivery with all required nozzles has valves, high pressure gun, fittings etc with come of 3-core, 2.5 Sq mm flexible copper cable with 3-pin 16A top and all required accessories and labour charges for erection, testing including transportation etc. complete, Make of motor: crompton, kiroken, texmo, suguna with ISI	Each	46725
			SECTION 10		
		10.1	GENERATORS SPECIFICATION		
853		ELEC-10.1.1	Supply Installation Testing And commissioning of DG Set complete with 1500 RPM Diesel Engine of suitable BHP & AC Brush less SPDP Alternator mounted on a common base Frame & coupled through a flexible coupling or close coupled. Alternator: It shall be self-regulated, self-excited and confirms to IS: 13364/1992 or latest version with regulation of +5% from No load to full load, IP23, with standard Alternator Protection (over voltage, over speed & under voltage). Diesel Engine: It shall have residential silencer, up to 10 M exhaust piping, electronic / Mechanical governor, Manual & electric Start, Batteries, Fuel tank & piping, control panel (16 G) with SPN(For 5 KVA)/TPN MCCB of required rating (25/36/50 KA) with PLC based Engine controller supplied by OEM, Ammeter, Voltmeter, Frequency Meter or Multi-function meter, Energy Meter & Hour Meter, Engine instruments panel, AVM and Automatic Voltage Regulator. The diesel engine shall be capable of providing 10% overload for 1 Hr for every 11 Hrs of continuous running at full load. The DG set shall be supplied with initial filling of fuel, lube oil, coolant oil as per OEM specifications and shall be tested at site. Acoustic Enclosure: Weatherproof, powder coated Acoustic enclosure for DG set for sound attenuation fabricated from 1.6 mm CRCA sheet steel (structure) with side wall fabricated from 1.6 mm CRCA sheet and filled with foam as per CPCB norms latest amendments & IS 8183. The doors are fabricated from 1.6 mm CRCA sheet packed with acoustic material, floor of MS chequered plate 5.0 mm thick, all doors/ opening are sealed with neoprene/ EPDM gaskets. The DG Set shall be maintained for two years after commissioning by the supplier including regular servicing, cost of consumables etc complete as specified by the OEM along with warranty for two years.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			The enclosure has built in fuel tank, residential silencer (isolated from main DG chamber) with protection and tripping of DG set against temperature of more than 50 °C. All controls for operation of DG set are from outside the enclosure with DG control panel having processor based genset monitoring and control system MCCB/ACB Ammeter, voltmeter, PF meter, frequency meter, KWH meter, Ind. Lamps etc. mounted inside enclosure, visible and accessible from outside. The enclosure should be suitable for following capacity DG sets and alternator. Noise level is less than 75 db (A) at a distance of 1 Mtrs as per CPCB-II norms, complete in all respect of following capacity:		
			Radiator Cooled and Turbocharged		
		a	5 kVA at 0.8 pf 230V 50Hz 1-Ø	1 No	150000
		b	10 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	235000
	MAT-04501	c	15 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	340000
		d	20 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	357000
		e	25 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	399000
	MAT-04502	f	30 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	440000
	MAT-04503	g	40 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	548000
	MAT-04504	h	62.5kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	630000
	MAT-04505	i	125 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	825000
		(a to i)	Makes: As per list of recommended brands.		
	MAT-04506	j	160 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	1080000
		k	200 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	1296000
	MAT-04508	l	250 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	1550000
	MAT-04509	m	320 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	2250000
	MAT-	n	380 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	2870000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	04510				
		(j to n)	Makes: As per list of recommended brands.		
	MAT-04511	o	500kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	3150000
	MAT-04512	p	625 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	3800000
	MAT-04513	q	750 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	4730000
	MAT-04514	r	1000 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	5700000
	MAT-04515	s	1250 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	7700000
	MAT-04516	t	1500 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	8740000
		(o to t)	Makes: As per list of recommended brands.		
854		ELEC-10.1.2	Supply Installation Testing and Commissioning of AUTO MAINS FAILURE (AMF) Panel with IP 52 protection, fabricated from CRCA sheet steel 2mmThick , Powder coated finish , Engine START & STOP commands, control RELAYS, selector switches for Ammeter & Voltmeter, Ammeter & Voltmeter ,4pole MCCBs for EB Supply and DG Supply of required rating and breaking capacity, automatic battery charger(External charger for DG) Control & Power Contactors, Timers, Electronic Hooter ,Visual & Alarm indication for faults, UPS, operator interface panel complete in all respect suitable for following capacity DG sets:		
	MAT-04517	a	25 to 40 KVA	1 No	86625
	MAT-04518	b	50 to 63.5 KVA	1 No	127050
	MAT-04519	c	80 to 160 KVA	1 No	179025
	MAT-04520	d	180 to 250 KVA	1 No	242550
	MAT-04521	e	320 to 500 KVA	1 No	300300

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04522	f	deleted	1 No	
	MAT-04523	g	Deleted	1 No	
	MAT-04524	h	deleted	1 No	
855	MAT-04525	ELEC-10.1.3	Supply and fixing of Thermal Insulation with asbestos Rope for Exhaust pipe	Mtr	251
856	MAT-04526	ELEC-10.1.4	Supply and fixing of Thermal Insulation with Rock/Glass Wool with Aluminum cladding (Density - 96 Kg/m3 thickness -50mm) for Exhaust pipe	Mtr	1247
			CPCB IV		
857		10.1.5	Supply Installation Testing And commissioning of CPCB IV+ DG Set complete with 1500 RPM Diesel Engine of suitable BHP & AC Brush less Alternator mounted on a common base Frame & coupled through a flexible coupling or close coupled. Alternator 1. 1500 RPM, 1P or 3P, Brushless type, screen protected, revolving field, Self-excited alternator conforming to IS/IEC 60034-1 IP23, with standard Alternator Protection (over voltage, over speed & Under voltage) 2. A reliable long life with superior class 'H' insulation with temperature rise to Class H Diesel Engine: Engine: Engine should comprise of Silencer, Electronic governor from >25 KVA & above, suitable rating battery , Battery charging alternator, battery charger , Inbuilt Fuel tank with fuel pipe, AVM pads , Control panel with 3P MCCB of suitable rating with short circuit protections (25kA,36kA, 50kA) with microprocessor based controller indicating genset parameters (i.e. volt, amps, KWH, KVAR, Hrs etc.), The diesel engine shall be capable of providing 10% overload for 1 Hr for every 11 Hrs of continuous running at full load. The DG set shall be supplied as per OEM specifications and shall be tested at site along with below. 1. CRDI Engine >25 KVA DG set		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			2. Water cooled Radiator coupled to engine 3. Dry type air cleaner with service indicator 4. First fill of lube oil, Coolant & first fill of Diesel 5. Electrical starter motor with soft start System 6. Battery charging alternator 7. Remote Monitor system >58.5 KVA & Above 8. 2 years / 5000 Hrs Warranty from commissioning or 30-month form supply. 9. Emission control system - EGR & (DOC, SCR for >75 KVA DG set) 10.10 Mtrs Exhaust pipe from Silencer Genset Controller: 1. Microprocessor based genset monitoring, metering and control system with full graphics LCD display for easy front panel access. 2. AMF relay, manual and remote start / stop modes for 1-ph & 3-ph gensets 3. Backlit and full graphics display with power saving feature 4. Engine parameter monitoring -Lube oil pressure, Engine coolant temperature, Fuel level, Battery voltage, Engine running hours 5. AC Alternator parameter monitoring -Voltage L-N & L_L, Current, kW, kVA (Phase & Total), Frequency, kWH, PF 6. Genset Protection: Engine: Low lube oil pressure, High coolant temperature, Battery High/Low Volts, Fail to Start, Sensor failure, Low fuel level, Overspeed AC Alternator: Over/Under Voltage, Over/Under, Frequency, Loss of AC sensing, Over frequency, Over Current, kW Overload, Unbalancing load 7. Maintenance notification based on Engine Run Hour & due date 8.Communication: USB port, RS485, CAN 9.30-50 Event logs		
			Acoustic Enclosure: 1. Specially designed to meet stringent MOEF/CPCB IV+ norms 2. Weatherproof, powder coated Acoustic enclosure for DG set for sound attenuation fabricated from 1.2 mm / 1.6 mm CRCA sheet steel (structure) with side wall fabricated from 1.2mm /1.6 mm CRCA sheet and filled with PU Foam/Rockwood for Fire retardant acoustic and for better safety 3. Designed to operate in extreme climatic conditions		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			in temperatures ranging from -10 deg to 55 deg without any external aid 4. Fabricated base frame with AVM pads. 5. Noise level is less than 75 db (A) at a distance of 1 Mtrs as per CPCB norms, complete in all respect. following capacity:		
			Radiator Cooled and Turbocharged		
		a	5 kVA at 0.8 pf 230V 50Hz 1-Ø	1 No	277200
		b	10 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	369735
		c	15 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	387784
		d	20 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	429495
		e	25 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	567321
		f	30 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	605617
		g	40 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	684583
		h	58.5kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	801376
		i	125 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	1342246
		(a to i)	Makes: As per list of recommended brands.		
		j	160 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	1796054
		k	200 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	2269705
		l	250 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	2483965
		m	320 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	3219482
		n	380 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	4281860
		(j to n)	Makes: As per list of recommended brands.		
		o	500kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	5264424
		p	625 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	6528148
		q	750 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	6947600
		r	1000 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	8162000
		s	1250 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	11058062

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		t	1500 kVA at 0.8 pf 415V 50Hz 3-Ø	1 No	12826704
		(o to t)	Makes: As per list of recommended brands.		
			SECTION 11		
		11.1	INVERTERS and ONLINE UPS SYSTEMS		
858		ELEC-11.1.1	Supply and installation of inverter (home UPS system) pure sine wave output, single phase input / Single phase output. Makes: As per list of recommended brands.		
	MAT-04527	a	800 VA, 12 V DC	1 No	9350
	MAT-04528	b	1400 VA, 24 V DC	1No	13200
	MAT-04529	c	2000 VA, 36 V DC	1No	18700
859		ELEC-11.1.2	Supply installation Testing and commissioning of KVA on line UPS system confirms to IS 16242(Part-I):2014 and IEC 60240-1: 2008 with IGBT technology pure sine wave output, double conversion with auto and manual static by pass switch single phase input / Single phase output. Makes: As per list of recommended brands.		
	MAT-04530	a	2.0 KVA, 72/96VDC	1 No	31126
	MAT-04531	b	3.0 KVA, 72/96 VDC	1 No	42798
	MAT-04532	c	3.0 KVA, 72/96 VDC with Isolation Transformer	1 No	56376
	MAT-04533	d	6.0 KVA, 192/240 VDC with Isolation Transformer	1 No	96944
	MAT-04534	e	7.0 KVA, 192/240 VDC with Isolation Transformer	1 No	117078
	MAT-04535	f	10.0 KVA, 192-240 VDC with Isolation Transformer	1 No	140941

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
860		ELEC-11.1.3	Supply installation Testing and commissioning of KVA on line UPS system as per IEC 62040-I (Safety), IEC 62040-3 (Performance) for critical IT solutions, fully digital IGBT Converter and Inverter, SCR rectifier with Internal /External isolation transformer from DC to AC, PWM, pure sine wave output, double conversion, output pf 0.8, with paralleling facility, standard communication features/options auto and manual static by pass switch three phase input / Three phase output. acoustic level shall be less than 58dB at 1 mtr distance. Makes: As per list of recommended brands.		
	MAT-04536	a	10.0 KVA 312/360 V DC	1 No	270250
	MAT-04537	b	15.0 KVA 312/360 V DC	1 No	316250
	MAT-04538	c	20.0 KVA 312/360 V DC	1 No	327750
	MAT-04539	d	30.0 KVA 360/384/480 V DC	1 No	408250
	MAT-04540	e	40.0 KVA 360/384/480/504 V DC	1 No	494500
861		ELEC-11.1.4	Supply installation Testing and commissioning of KVA on line UPS system as per IEC 62040-I(Safety), IEC 62040-3 (Performance) for critical IT solutions, fully digital IGBT Converter and Inverter,SCR rectifier with Internal /External isolation transformer from DC to AC, PWM, pure sine wave output, double conversion ,output pf 0.8, with paralleling facility , standard communication features/options auto and manual static by pass switch three phase input / Three phase output. Acoustic level shall be less than 58dB at 1 mtr distance. Makes: As per list of recommended brands.		
	MAT-04541	a	60 KVA 480/504/528/600/720 V DC	1 No	735000
	MAT-04542	b	80.0 KVA 480/504/528/600/720 V DC	1 No	845000
	MAT-04543	c	100.0 KVA 480/504/528/600/720 V DC	1 No	1085000
	MAT-04544	d	120.0 KVA 480/504/528/600/720 V DC	1 No	1210000
	MAT-04545	e	160.0 KVA 480/504/528/600/720 V DC	1 No	1410000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-04546	f	200.0 KVA 480/504/528/600/720 V DC	1 No	1725000
862	MAT-04547	ELEC-11.1.5	Supply and providing of UPS cum battery rack up to 4 batteries	1 No	1650
863	MAT-04548	ELEC-11.1.6	Supply and providing of battery rack for 5 to 10 batteries (42 AH)	1 No	3300
864	MAT-04549	ELEC-11.1.7	Supply and providing of battery rack upto 11 to 20 batteries (42 AH)	1 No	5500
865	MAT-04550	ELEC-11.1.8	Supply and providing of battery rack upto 20 to 30 batteries (65 & 100 AH)	1 No	9900
866	MAT-04551	ELEC-11.1.9	Supply and fixing of 12V 26 AH SMF battery with 3 years warranty, including wire leads, connections etc complete. Makes: As per list of recommended brands.	1 No	3520
867	MAT-04552	ELEC-11.1.10	Supply and fixing of 12V 42 AH SMF battery with 3 years warranty including wire leads, connections etc complete. Makes: As per list of recommended brands.	1 No	6270
868	MAT-04553	ELEC-11.1.11	Supply and fixing of 12V 65 AH SMF battery with 3 years warranty including wire leads, connections etc complete. Makes: As per list of recommended brands.	1 No	7128
869	MAT-04554	ELEC-11.1.12	Supply and fixing of 12V 100 AH SMF battery with 3 years warranty including wire leads, connections etc complete. Makes: As per list of recommended brands.	1 No	11484
870	MAT-04555	ELEC-11.1.13	Supply and fixing of 12V 120/130 AH SMF battery with 3 years warranty including wire leads, connections etc complete. Makes: As per list of recommended brands.	1 No	12276
871	MAT-04556	ELEC-11.1.14	Supply and fixing of 12V, 150 AH SMF battery with 3 years warranty including wire leads, connections etc complete. Makes: As per list of recommended brands.	1 No	17160
872	MAT-04557	ELEC-11.1.15	Supply and fixing of 12V, 200 AH SMF battery with 3 years warranty including wire leads, connections etc complete., Makes: As per list of recommended brands.	1 No	23760

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
873		ELEC-11.1.16	Supply and fixing of 12V, 100 AH Tubular/MF battery including wire leads Makes: As per list of recommended brands.	1 No	11766
874	MAT-04559	ELEC-11.1.17	Supply and fixing of 12V, 150 AH Tubular/MF battery including wire leads. Makes: As per list of recommended brands.	1 No	15610
875		ELEC-11.1.18	Supply and fixing of 12V, 200 AH Tubular/MF battery including wire leads. Makes: As per list of recommended brands.	1 No	18627
			SERVO CONTROLLED VOLTAGE STABILISERS		
876		ELEC-11.2.1	Supply, Installation, Testing & Commissioning of Micro controller based confirming to IS:9815 IP 20 Servo Controlled 3 phase voltage stabilizer with Input Voltage Range: 340-480 V, Output Voltage : 415V $\pm$ 1% (230V Phase) Rated supply frequency : 47 - 53 Hz Ambient Temperature : 45° C Continuous Duty cycle with low voltage/High Voltage/Over load/Short Circuit/single phase prevention protections,3 Nos sensing Transformers, Correction rate :30 V/sec, Input on, Input Low, Input High, Output On, Output Cutoff, Auto / Manual Selector switch, Increase / Decrease Selector switch, Volts adj. Potentiometer, Voltmeter to read input and Output Voltage with Selector switch, Ammeter to read the Output current 3 phase SCVS, Input MCCB, Bypass, Output Contactor, Type Air Cooled etc., complete with all labour charges and with connections.		
		a	10 KVA	1 No	52470
		b	15 KVA	1 No	56870
		C	20 KVA	1 No	66770
		D	30 KVA	1 No	92840
		E	40 KVA	1 No	89100

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		F	50 KVA	1 No	115445
		G	60 KVA	1 No	134860
		H	75/80 KVA	1 No	172590
		i	100 KVA	1 No	210760
			SECTION – 12		
		12.1	TEMPORARY ILLUMINATION		
877	HIR-00241	ELEC-12.1.1	Hire charges for Temporary illumination, consisting of 20W LED tube light complete with required switchgears with continuous earth wire duly erected and dismantled with required scaffolding including cost and conveyance of all materials and labour charges etc., complete for one day.	1 No	43
878	HIR-00242	ELEC-12.1.2	Hire charges for Temporary illumination, consisting of flood light fitting 1000/500W complete halogen fitting with lamp, holders, mains and required switchgears with continuous earth wire erected and dismantled with required scaffolding for one day.	1 No	354
879	HIR-00243	ELEC-12.1.3	Hire charges for Temporary illumination, consisting of 400W Metal halide flood light fitting with lamp, holders, mains and required switchgears with continuous earth wire erected and dismantled with required scaffolding for one day.	1 No	416
880	HIR-00244	ELEC-12.1.4	Hire charges for Temporary illumination, consisting of 400W Metal Halide flood light fitting with Coloured lamp (Blue / Pink / Yellow / Red etc.,) holders, mains and required switchgears with continuous earth wire erected and dismantled with required scaffolding for one day.	1 No	456

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
881	HIR-00245	ELEC-12.1.5	Hire charges for Temporary illumination, consisting of 54 W LED RGB Parcan light fitting non integral, weather proof die cast aluminum housing with IP66 protection with control gear box, control gear with required cables, holder, mains duly erected with required scaffolding and dismantled on existing poles including cost and conveyance of all materials and labour charges etc., complete for one day.	1 No	440
882	HIR-00246	ELEC-12.1.6	Hire charges for providing temporary illumination consisting of flood light fitting 150/200 W complete LED fitting with lamp, complete required switchgear erected and dismantled with using scaffolding for one day.	1 No	507
883	HIR-00247	ELEC-12.1.7	Hire charges for temporary illumination consisting of strip lights 8mm LED lights of various colors (Navar Patta) complete with holders, required wire leads erected and dismantled including required scaffolding and T&P including cost and conveyance of all materials and all labour charges etc., complete for one day.	1000 Nos	1589
884	HIR-00248	ELEC-12.1.8	Hire charges for temporary illumination consisting of white color series lights with miniature lamps of 8mm LED lights with required wire leads erected and dismantled including required scaffolding and T&P including cost and conveyance of all materials and all labour charges etc., complete for one day.	1000 Nos	1092
885	HIR-00249	ELEC-12.1.9	Hire charges for temporary illumination consisting of LED RGB pixel series strip lights 8mm LED lights of various colors (Navar Patta) complete with holders, required wire leads erected and dismantled including required scaffolding and T&P including cost and conveyance of all materials and all labour charges etc., complete for one day.	1000 Nos	1352
886	HIR-00250	ELEC-12.1.10	Hire charges for temporary illumination consisting LED, RGB pixel series lights with miniature lamps of 8mm LED lights with required wire leads erected and dismantled including required scaffolding and T&P including cost and conveyance of all materials and all labour charges etc., complete for one day.	1000 Nos	867

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
887	HIR-00251	ELEC-12.1.11	Hire Charges for National Flag of size 8"x4"Comprising LEDs with required wire leads and switch gear etc., complete for one day.	1 No	6064
889	HIR-00252	ELEC-12.1.12	Hire charges for supply and maintaining of oscillating type pedestal air circulators 600/900 mm connected with necessary mains, required switchgears with continuous earthing maintaining the same during the function and including dismantling for one day.	1 No	194
890	HIR-00253	ELEC-12.1.13	Hire charges for supply and maintaining of oscillating type pedestal fan 16" (400 mm) or ceiling fan connected with necessary mains, required switchgears with continuous earthing maintaining the same during the function and including dismantling for one day.	1 No	179
891	HIR-00254	ELEC-12.1.14	Hire charges for providing 1.1KW , 24500 m3/Hr Air cooler and required materials with necessary mains switch gear with continues earth lead during function duly removing including cost and conveyance of all materials and labour charges etc., complete for one day.	1 No	1504
892	HIR-00255	ELEC-12.1.15	Hire charges for supply and maintaining of heavy duty exhaust fan 18" or 24" connected with necessary mains, required switchgears with continuous earthing maintaining the same during the function and including dismantling for one day.	1 No	179
893	HIR-00256	ELEC-12.1.16	Hire charges for supply and maintaining of plug points with 16A/6A 5 Pin socket and switch with necessary mains, required switchgears and continuous earth connection for one day.	1 No	75
894	HIR-00257	ELEC-12.1.17	Hire charges for supply and maintaining 280 liters capacity refrigerator complete with M.S. stand if necessary, connected with mains, switchgear and continuous earthing maintaining the same during the function and including dismantling for one day.	1 No	607
895	HIR-00258	ELEC-12.1.18	Hire charges for supply and maintaining 120/150 liter capacity water cooler with water filter (candle type or UV tube) with M.S. stand complete with minor plumbing work if necessary connected with	1 No	1335

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			mains, required switchgears and continuous earthing maintaining the same during the function and including dismantling for one day.		
896	HIR-00259	ELEC-12.1.19	Hire charges for supply and maintaining 20"/24" colour television with multi channel tuner, connected with necessary mains, required switchgears with continuous earthing maintaining the same during the function and including dismantling for one day.	1 No	437
897	HIR-00260	ELEC-12.1.20	Providing and maintaining temporary LCD/LED colour T.V. (32"to 42" size) and positioning at site with required cabling as per direction of authority, duly connecting and testing for one day.	1 No	909
898	HIR-00261	ELEC-12.1.21	Hire charges for supply and maintaining 6V/10V with 20/40 Watt fluorescent emergency lamp connected with necessary mains, required switchgears and continuous earthing maintaining the same during the function and including dismantling for one day.	1 No	122
899	HIR-00262	ELEC-12.1.22	Hire charges for supply and maintaining digital projector with spring loaded white screen connected with necessary mains, required switchgears and maintaining the same during the function including dismantling for one day.	1 No	6186
900	HIR-00263	ELEC-12.1.23	Hire charges for providing 1.5/2.0 Ton capacity split type air conditioning unit complete with temporary stand and fabrication work and required material to achieve cooling temperature connected along with necessary mains, required switchgears and continuous earthing maintaining the same during the function and including dismantling for one day.	1 No	5326
901	HIR-00264	ELEC-12.1.24	Hire charges for providing 3.5 Ton capacity tower type air conditioning unit complete with temporary stand and fabrication work and required material to achieve cooling temperature connected along with necessary mains, required switchgears and continuous earthing maintaining the same during the function and including dismantling for one day.	1 No	6086

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
902	HIR-00265	ELEC-12.1.25	Hire charges for providing 4.5 Ton capacity tower type air conditioning unit complete with temporary stand and fabrication work and required material to achieve cooling temperature connected along with necessary mains, required switchgears and continuous earthing, maintaining the same during the function and including dismantling for one day.	1 No	6973
903	HIR-00266	ELEC-12.1.26	Hire charges for providing 6.5Ton/7.5Ton capacity tower type air conditioning unit complete with temporary stand and fabrication work and required material to achieve cooling temperature connected along with necessary mains, required switchgears and continuous earthing, maintaining the same during the function and including dismantling for one day.	1 No	8241
904	HIR-00267	ELEC-12.1.27	Hire charges for providing, maintaining and operating temporary public address system on hire consisting 02 Nos. solid state heavy wattage amplifier 250 watts (one for working and another for stand by emergency) working on AC / generator and 24 volt car battery supply, 06 Nos. of matching of 100 volt line (200 watts) box type speakers/sound column, 02 Nos super sensitive microphone with suitable size of microphone holding stand. The system shall be in a fully automatic changeover operation in case of failure of supply for one day.	1 No	9096
905	HIR-00268	ELEC-12.1.28	Hire charges for providing and maintaining temporary additional box type speaker of 100 Volt line (100 watts) for one day.	1 No	424
906	HIR-00269	ELEC-12.1.29	Hire charges for providing and maintaining temporary cordless (Hand type or lap type) super sensitive HUF microphone (1 no stand by) for one day.	1 No	2947
907	HIR-00270	ELEC-12.1.30	Providing temporary line matching transformer (40-XT) for speakers having distance more than 60 Mtrs from Amplifiers and maintaining the same for one day.	1 No	243

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
908	HIR-00271	ELEC-12.1.31	Hire charges for providing, maintaining and operating fingertip switcher of 8 ways to operate the public address system between dias and participants in the hall with necessary cabling, wiring etc for one day.	1 No	3032
909	HIR-00272	ELEC-12.1.32	Hire charges providing and maintaining all in one desktop PC with following configuration Intel TM second generation core i3 G630, 2GB DDR3 RAM, 1TB HARD DISK, DVD RW optical drive 20" LED screen, web camera, wifi, Bluetooth, keyboard and mouse, media card reader etc for one day.	1 No	1213
910	HIR-00273	ELEC-12.1.33	Hire charges providing and maintaining Laser Printer, resolution (in dpi) mono 600, paper size A4, print speed in PPM (A4 size) 25, Port: 1 USB, memory (in MB): NA network card 10/100: YES, Duplexing: YES etc for one day.	1 No	364
911	HIR-00274	ELEC-12.1.34	Hire charges for providing and maintaining 1 KVA online UPS pure sine wave suitable for 30 minutes battery backup to provided computer with necessary interconnecting cabling, wiring etc for one day.	1 No	2001
912	HIR-00275	ELEC-12.1.35	Hire charges for providing and maintaining temporary 1400 VA to 1600 VA digital pure sine wave Inverter based on IGBT technology suitable for 120 minutes battery backup to electrical installation with necessary interconnecting cabling, wiring etc for one day.	1 No	1213
913	HIR-00276	ELEC-12.1.36	Hire charges for supply and fixing distribution main board consisting of 400A/250A 4pole MCCB with bus bar arrangement 12 Nos 63A fuse units as outgoing including conveyance of all materials and all labour charges etc., complete for one day.	1 No	1633
914	HIR-00277	ELEC-12.1.37	Hire charges for Supply & Fixing of Distribution board of load main board consisting of 400A MCCB 4 pole with Busbar arrangement and 12 Nos 63A fuse units as outgoing including conveyance of all materials and all labour charges etc., complete for one day.	1 No	1666

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
915	HIR-00278	ELEC-12.1.38	Hire charges for Supply & Fixing of Distribution board of load main board consisting of 250A MCCB 4 pole with Busbar arrangement and 12 Nos 63A fuse units as outgoing including conveyance of all materials and all labour charges etc., complete for one day.	1 No	1599
916	HIR-00279	ELEC-12.1.39	Hire charges for supply and maintaining towards supply and fixing of 200A 4 pole Changeover / TPN switches including erection and dismantling and cost and conveyance of all materials and labour charges complete for one day.	1 No	371
917	HIR-00280	ELEC-12.1.40	Hire charges for supply and fixing distribution main board consisting of 400A/250A 4pole change over switch with bus bar arrangement 12 Nos 63A fuse units as outgoing including conveyance of all materials and all labour charges etc., complete for one day.	1 No	1579
918	HIR-00281	ELEC-12.1.41	Hire charges for supply and fixing distribution main board consisting of 250A 4pole change over switch with bus bar arrangement 12 Nos 63A fuse units as outgoing including conveyance of all materials and all labour charges etc., complete for one day.	1 No	1525
919	HIR-00282	ELEC-12.1.42	Hire charges for Supply and maintaining towards supply and fixing of 4 way TPN DB with 1 No 125 TP MCCB and 12Nos 6-32A 10kA SP MCBs including erection and dismantling and cost and conveyance of all materials and labour charges complete for one day.	1 No	1407
920	HIR-00283	ELEC-12.1.43	Hire charges for Supply and maintaining towards supply and fixing of 6 way TPN DB with IP-43 Protection with 1 No 125 FP MCCB and 18Nos 6-32A 10kA SP MCBs including erection and dismantling and cost and conveyance of all materials and labour charges complete for one day.	1 No	1456
921	HIR-00284	ELEC-12.1.44	Hire charges for providing industrial type panel board consisting of bus bar chamber with 200/250 amps incoming TP/MCCB as incomers switch, 12 no's 63 amps fuse unit, earth wire erected and dismantled all accessories etc., complete for one day.	1 No	563

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
922	HIR-00285	ELEC-12.1.45	Hire charges for supply and installing and maintaining towards supply and run of 1 of 6/10 Sq.mm WPTC / 2 of WPSC / VIR cable with necessary terminations etc. complete for one day.	1 Mtr	6
923	HIR-00286	ELEC-12.1.46	Hire charges for supply and installing and maintaining towards supply and run of 16 Sq.mm to 35 Sq mm x 3 1/2 core cable / 4 of single core 16 Sq mm to 35 Sq mm cable with necessary terminations etc. complete for one day.	1 Mtr	30
924	HIR-00287	ELEC-12.1.47	Hire charges for supply and installing and maintaining towards supply and run of 50Sq mm to 95 Sq.mm x 3 1/2 core cable / 4 of single core 50Sq mm to 95Sq mm cable with necessary terminations etc. complete for one day.	1 Mtr	34
925	HIR-00288	ELEC-12.1.48	Hire charges for supply and installing and maintaining towards supply and run of 50 Sq mm x 3 1/2 core cable / 4 of single core 50 Sq mm cable with necessary terminations etc. complete for one day.	1 Mtr	32
926	HIR-00289	ELEC-12.1.49	Hire charges for supply and installing and maintaining towards supply and run of 95 Sq.mm x 3 1/2 core cable / 4 of single core 95Sq mm cable with necessary terminations etc. complete for one day.	1 Mtr	35
927	HIR-00290	ELEC-12.1.50	Hire charges for supply and installing and maintaining towards supply and run of 120 Sq.mm x 3 1/2 core cable / 4 of single core 120 Sq.mm cable with necessary terminations etc. complete for one day.	1 Mtr	36
928	HIR-00291	ELEC-12.1.51	Hire charges for supply and installing and maintaining towards supply and run of 185 Sq.mm x 3 1/2 core cable / 4 of single core 185 Sq.mm cable with necessary terminations etc. complete for one day.	1 Mtr	39
929	HIR-00292	ELEC-12.1.52	Hire charges for Supply and erection of MS Single pole structure of 20' (6.00 Mtrs.) with necessary cross arms and hardware materials for fixing halogen / Metal halide fittings etc., and dismantling and cost and conveyance of all materials and all labour charges complete for one day.	1 No	1905

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
930	HIR-00293	ELEC-12.1.53	Hire charges for Supply and erection of 4 pole structure of 4 of 25' (7.50 Mtrs.) GI pipe of 63/80mm dia with necessary cross arms and hardware materials for fixing halogen / Metal halide fittings with suitable earthing arrangements and dismantling and cost and conveyance of all materials and all labour charges complete for one day.	1 No	2527
931	HIR-00294	ELEC-12.1.54	Hire charges for Supply and erection of 6 pole structure of 6 of 25' (7.50 Mtrs.) GI pipe of 63/80mm dia with necessary cross arms and hardware materials for fixing halogen / Metal halide fittings with suitable earthing arrangements and dismantling and cost and conveyance of all materials and all labour charges complete for one day.	1 No	3800
932	HIR-00295	ELEC-12.1.55	Hire charges for providing, commissioning and maintaining CCTV system with 8 channel NVR, IP video/audio input - 1 no, IP based 2.0 MP, Full HD, IR IP dome camera - 2 nos, IP based 2.0 MP, Full HD, IR IP PTZ camera - 2 nos, 2TB Hard Disk - 2 no, 32" Full H D professional Display - 1 no, 8 port PoE Switch - 1 no, Power supply unit to camera - 1 no, On Line UPS - 1 no with necessary mains, switchgears for one day	1 Job	8659
933	HIR-00296	ELEC-12.1.56	Hire charges for providing, commissioning and maintaining IP based 2.0 MP, full HD, IR IP dome / bullet camera with necessary Cat 6 cables etc., for one day.	1 No	1074
934	HIR-00297	ELEC-12.1.57	Hire charges for providing, commissioning and maintaining IP based 2.0 MP, Full HD, IR IP PTZ camera with necessary Cat 6 cables etc., for one day.	1 No	2983
		Note:-	1) The Rates for all the items are for one glowing / working day		
			2) Allow 50% of the rate for each day upto 3 days (i.e, 2nd and 3rd day) (Except items 12.1.23 to 12.1.26).		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			3) For each additional day after 3 days, but not exceeding 15 days, allow 25% rate.		
			4) For more than 15 days allow 10% per day but total rental charges shall not exceed 80% of the capital cost of the item.		
			5) For item no. 12.1.22 the rate of projector is for 1 function or for max. period of 1 day whichever is more, including transportation, connections with projector, operator till completion of function.		
			6) For item No 12.1.23 to 12.1.26, the rate is for one day, For subsequent days (i.e, 2nd to 8th day) allow 75% of the above rate, after 8th day allow 50% the rate.		
			12.2 Hiring of Generators		
935	HIR-00298	ELEC-12.2.1	Hire charges for supplying and maintaining 62.5KVA, 415V, 50 cycles A.C. Generating set with acoustic enclosure as per IS Specification with DCM 4 Wheeler Vehicle with all standard accessories such as control panel, batteries etc. complete excluding cost of fuel, for one day.	1 No	8653
936	HIR-00299	ELEC-12.2.2	Hire charges for supplying and maintaining 125KVA 415V 50 cycles A.C. Generating set with acoustic enclosure as per IS Specification with DCM 4- Wheeler Vehicle with all standard accessories such as control panel, batteries etc. complete excluding cost of fuel, for one day.	1 No	9890
937	HIR-00300	ELEC-12.2.3	Hire charges for supplying and maintaining 250KVA 415V 50 cycles A.C. Generating set with acoustic enclosure as per IS Specification with DCM 4 Wheeler Vehicle with all standard accessories such as control panel, batteries etc. complete excluding cost of fuel, for one day.	1 No	13852
		Note:-	1) Above rates are applicable for per one day only.		
			2) For subsequent days the above rate shall be reduced by 25% after 8th day reduce the rate by 50%		
			3) Diesel cost will be paid extra for running hours at the prevailing rates.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			4) For test run, The minimum requirement of the fuel shall be borne by the contractor.		
			5) The D.G set should be in good condition and the life of set shall not be beyond 10 years.		
		13.1	LIFTS (New Installation)		
938	MAT-08534	ELEC-13.1.1	Supply, Installation, Testing and Commissioning of Electric Traction Passenger Lift of Makes: As per list of recommended brands. with - Rated capacity :- 8 Passenger/544Kg - Floors :- G+1 floor (2Stops/2 Landings) - Travel :- 3 to 4.2 mtrs - Location of Lift Machine:- MRL - Rated speed :- 1.0/1.25mps VS - Doors type :- COPO/TOPO Doors with frame having clear opening of 800 mm wide x 2000 mm high made from SS 304 grade sheet of 1.5mm, thick in hairline finish for car and all landing doors with SS door architraves/frames - Lift car enclosure made from SS 304 grade sheet of 1.5mm, thick with hairline finish with frame made from MS girders, bracing of adequate size with minimum safety factor of 5, with Toe Guard Apron, with necessary false ceiling with adequate LED lights, blower/fan for ventilation & SS chequered plate flooring, handrails, mirror, emergency light etc. COP with SS face plate having metallic push buttons with Braille Code & luminous indicator around button with FPI, scrolling UP/DN LED indicator & with/without attendant key switch, OWD with audio-visual alarm, VAS in Telugu & English with intercom system with telephone instrument in Lift car, LMR & FCC/ground floor Clear Car size of mm wide x mm deep x mm high	1Job	1303592
			LOP with SS face plate having recess/surface push button box for all landings with scrolling UP/DN LED indicator having metallic push buttons with Braille Code & luminous indicator around button with CPI, Lift car arrival & next travel direction audio-visual indication at all landings Lift controller based on microprocessor/ PLC with VVVF Drive having closed loop control system, with		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			IBMS compatible having necessary port, control panel duly wired with proper size & strength copper wire for power & control circuit, with provision for addition of floor/control card & allied accessories control panel having enclosure of 1.5mm CRCA sheet with powder coating with IP54 Protection class • ARD complete with necessary SMF VRLA batteries • Fireman controller having fireman switch at fire Landing, Lift Machine of Gearless PMSM of suitable kW with Traction pulley, OSG, electromagnetic brakes, entire assembly mounted on adequate size girders duly fixed on LMR floor/ shaft walls complete with main/diverter traction sheaves, suspension wire ropes/belts of adequate size & strength • Other mechanical parts such as 'T' section adequate size guide rails for car & counter weight with brackets fasteners, counter weight frame with necessary blocks, buffers with necessary support arrangement, MS pit ladder etc. erected with necessary steel work		
			Minor civil work for alteration if any and erection of door frames and accessories, erection buffers, erection of lift machinery, adequate size core cuts if required & scaffolding for erecting guide rails fixing of girders for mounting lift machine etc. complete as per specification no. LFT. •Lift shaft available having clear size of mm wide x mm deep. mm Pit depth, ...mm Overhead.		
939	MAT-08535	ELEC-13.1.2	Supply, Installation, Testing and Commissioning of Electric Traction Passenger Lift of Makes: As per list of recommended brands. with • Rated capacity :- 10 Passenger/680Kg • Floors :- G+1 floor (2Stops/2 Landings) • Travel :- 3 to 4.2 mtrs • Location of Lift Machine:- MRL • Rated speed :- 1.0/1.25mps VS • Doors type :- COPO/TOPO Doors with frame having clear opening of 800 mm wide x 2000 mm high made from SS 304 grade sheet of 1.5mm, thick	1Job	1559413

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			in hairline finish for car and all landing doors with SS door architraves/frames • Lift car enclosure made from SS 304 grade sheet of 1.5mm, thick with hairline finish with frame made from MS girders, bracing of adequate size with minimum safety factor of 5, with Toe Guard Apron, with necessary false ceiling with adequate LED lights, blower/fan for ventilation & SS chequered plate flooring, handrails, mirror, emergency light etc. • COP with SS face plate having metallic push buttons with Braille Code & luminous indicator around button with FPI, scrolling UP/DN LED indicator & with/without attendant key switch, OWD with audio-visual alarm, VAS in Telugu & English with intercom system with telephone instrument in Lift car, LMR & FCC/ground floor. Clear Car size of mm wide x mm deep x mm high		
			• LOP with SS face plate having recess/surface push button box for all landings with scrolling UP/DN LED indicator having metallic push buttons with Braille Code & luminous indicator around button with CPI, Lift car arrival & next travel direction audio-visual indication at all landings • Lift controller based on microprocessor/ PLC with VVVF Drive having closed loop control system, with IBMS compatible having necessary port, control panel duly wired with proper size & strength copper wire for power & control circuit, with provision for addition of floor/ control card & allied accessories control panel having enclosure of 1.5mm CRCA sheet with powder coating with IP54 Protection class • ARD complete with necessary SMF VRLA batteries • Fireman controller having fireman switch at fire Landing. • Lift Machine of Gearless PMSM of suitable kW with Traction pulley, OSG, electromagnetic brakes, entire assembly mounted on adequate size girders duly fixed on LMR floor/ shaft walls complete with main/diverter traction sheaves, suspension wire ropes/belts of adequate size & strength. • Other mechanical parts such as 'T' section adequate size guiderails for car & counter weight		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			with brackets fasteners, counter weight frame with necessary blocks, buffers with necessary support arrangement, MS pit ladder etc. erected with necessary steel work		
			- Minor civil work for alteration if any and erection of door frames and accessories, erection buffers, erection of lift machinery, adequate size core cuts if required & scaffolding for erecting guide rails fixing of girders for mounting lift machine etc. complete as per specification no. LFT. - Lift shaft available having clear size of mm wide x mm deep , ...mm Pit depth, , ...mm Overhead.		
940	MAT-08536	ELEC-13.1.3	Supply, Installation, Testing and Commissioning of Electric Traction Passenger Lift of Makes: As per list of recommended brands. with - Rated capacity :- 13 Passenger/884Kg - Floors :- G+1 floor (2Stops/2 Landings) - Travel :- 3 to 4.2 mtrs. - Location of Lift Machine:- MRL - Rated speed :- 1.0/1.25mps VS - Doors type :- COPO/TOPO Doors with frame having clear opening of 900/1000 mm wide x 2000 mm high made from SS 304 grade sheet of 1.5mm, thick in hairline finish for car and all landing doors with SS door architraves/ frames - Lift car enclosure made from SS 304 grade sheet of 1.5mm, thick with hairline finish with frame made from MS girders, bracing of adequate size with minimum safety factor of 5, with Toe Guard Apron, with necessary false ceiling with adequate LED lights, blower/fan for ventilation & SS chequered plate flooring, handrails, mirror, emergency light etc. COP with SS face plate having metallic push buttons with Braille Code & luminous indicator around button with FPI, scrolling UP/DN LED indicator & with/without attendant key switch, OWD with audio-visual alarm, VAS in Telugu & English with intercom system with telephone instrument in Lift car, LMR & FCC/ground floor - Clear Car size of mm wide x mm deep x mm high	1Job	1664867

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			• LOP with SS face plate having recess/surface push button box for all landings with scrolling UP/DN LED indicator having metallic push buttons with Braille Code & luminous indicator around button with CPI, Lift car arrival & next travel direction audio-visual indication at all landings • Lift controller based on microprocessor/ PLC with VVVF Drive having closed loop control system, with IBMS compatible having necessary port, control panel duly wired with proper size & strength copper wire for power & control circuit, with provision for addition of floor /control card & allied accessories control panel having enclosure of 1.5mm CRCA sheet with powder coating with IP54 Protection class ARD complete with necessary SMF VRLA batteries • Fireman controller having fireman switch at fire Landing, • Lift Machine of Gearless PMSM of suitable kW with Traction pulley, OSG, electromagnetic brakes, entire assembly mounted on adequate size girders duly fixed on LMR floor/ shaft walls complete with main/diverter traction sheaves, suspension wire ropes/belts of adequate size & strength - Other mechanical parts such as 'T' section adequate size guide rails for car & counter weight with brackets fasteners, counter weight frame with necessary blocks, buffers with necessary support arrangement, MS pit ladder etc. erected with necessary steel work		
			• Minor civil work for alteration if any and erection of door frames and accessories, erection buffers, erection of lift machinery, adequate size core cuts if required & scaffolding for erecting guide rails fixing of girders for mounting lift machine etc. complete as per specification no. LFT. • Lift shaft available having clear size of mm wide x mm deep, ...mm Pit depth, ...mm Overhead		
941	MAT-08537	ELEC-13.1.4	Supply, Installation, Testing and Commissioning of Electric Traction Passenger cum Stretcher/Hospital Lift of Makes: As per list of recommended brands. with	1Job	1951573

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			- Rated capacity :- 15 Passenger/1020Kg - Floors :- G+1 floor (2Stops/2 Landings) - Travel :- 3 to 4.2 mtrs - Location of Lift Machine:- MRL - Rated speed :- 1.0/1.25mps VS - Doors type :- COPO/TOPO Doors with frame having clear opening of 800/900/1000 mm wide x 2000mm high made from SS 304 grade sheet of 1.5mm, thick in hairline finish for car and all landing doors with SS door architraves /frames - Lift car enclosure made from SS 304 grade sheet of 1.5mm, thick with hairline finish with frame made from MS girders, bracing of adequate size with minimum safety factor of 5, with Toe Guard Apron, with necessary false ceiling with adequate LED lights, blower/fan for ventilation & SS chequered plate flooring, handrails, mirror, emergency light etc. COP with SS face plate having metallic push buttons with Braille Code & luminous indicator around button with FPI, scrolling UP/DN LED indicator & with/without attendant key switch, OWD with audio-visual alarm, VAS in Telugu & English with intercom system with telephone instrument in Lift car, LMR & FCC/ground floor - Clear Car size of mm wide x mm deep x mm high		
			LOP with SS face plate having recess/surface push button box for all landings with scrolling UP/DN LED indicator having metallic push buttons with Braille Code & luminous indicator around button with CPI, Lift car arrival & next travel direction audio-visual indication at all landings		
			- Lift controller based on microprocessor/ PLC with VVVF Drive having closed loop control system, with IBMS compatible having necessary port, control panel duly wired with proper size & strength copper wire for power & control circuit, with provision for addition of floor/ control card & allied accessories - control panel having enclosure of 1.5mm CRCA sheet with powder coating with IP54 Protection class - ARD complete with necessary SMF VRLA batteries - Fireman controller having fireman switch at fire Landing, - CCTV surveillance system comprises of 2nos		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			minimum 2.0MP FHD IP based vandal proof Dome camera in lift car & in LMR/inside lift shaft top aimed on Lift machinery & controller with NVR kept in LMR/FCC with HDR data backup for 60 days with 18" FHD TV monitor, to be kept in FCC/LMR as directed by Engineer In Charge • Lift Machine of Gearless PMSM of suitable kW with Traction pulley, OSG, electromagnetic brakes, entire assembly mounted on adequate size girders duly fixed on LMR floor/ shaft walls complete with main/diverter traction sheaves, suspension wire ropes/belts of adequate size & strength - Other mechanical parts such as 'T' section adequate size guide rails for car & counter weight with brackets fasteners, counter weight frame with necessary blocks, buffers with necessary support arrangement, MS pit ladder etc. erected with necessary steel work • Minor civil work for alteration if any and erection of door frames and accessories, erection buffers, erection of lift machinery		
			, adequate size core cuts if required & scaffolding for erecting guide rails fixing of girders for mounting lift machine etc. complete as per specification no. LFT. • Lift shaft available having clear size of mm wide x mm deep , ...mm Pit depth, , ...mm Overhead		
942	MAT-08538	ELEC-13.1.5	Supply, Installation, Testing and Commissioning of Electric Traction Passenger cum Stretcher/Hospital Lift of Makes: As per list of recommended brands. with • Rated capacity :- 20 Passenger/1360Kg • Floors :- G+1 floor (2Stops/2 Landings) • Travel :- 3 to 4.2 mtrs • Location of Lift Machine:- MRL • Rated speed :- 1.0/1.25mps VS • Doors type :- COPO/TOPO Doors with frame having clear opening of 1100/1200 mm wide x 2000 mm high made from SS 304 grade sheet of 1.5mm, thick in hairline finish for car and all landing doors with SS door architraves/frames • Lift car enclosure made from SS 304 grade sheet of 1.5mm, thick with hairline finish with frame made	1Job	2327245

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			from MS girders, bracing of adequate size with minimum safety factor of 5, with Toe Guard Apron, with necessary false ceiling with adequate LED lights, blower/fan for ventilation & SS chequered plate flooring, handrails, mirror, emergency light etc. • COP with SS face plate having metallic push buttons with Braille Code & luminous indicator around button with FPI, scrolling UP/DN LED indicator & with/without attendant key switch, OWD with audio-visual alarm, VAS in Telugu & English with intercom system with telephone instrument in Lift car, LMR & FCC/ground floor • Clear Car size of mm wide x mm deep x mm high		
			LOP with SS face plate having recess/surface push button box for all landings with scrolling UP/DN LED indicator having metallic push buttons with Braille Code & luminous indicator around button with CPI, Lift car arrival & next travel direction audio-visual indication at all landings • Lift controller based on microprocessor/ PLC with VVVF Drive having closed loop control system, with IBMS compatible having necessary port, control panel duly wired with proper size & strength copper wire for power & control circuit, with provision for addition of floor/control card & allied accessories control panel having enclosure of 1.5mm CRCA sheet with powder coating with IP54 Protection class - ARD complete with necessary SMF VRLA batteries • Fireman controller having fireman switch at fire Landing, • CCTV surveillance system comprises of 2nos minimum 2.0MP FHD IP based vandal proof Dome camera in lift car & in LMR/inside lift shaft top aimed on Lift machinery & controller with NVR kept in LMR/FCC with HDR data backup for 60 days with 18" FHD TV monitor, to be kept in FCC/LMR as directed by Engineer In Charge. • Lift Machine of Gearless PMSM of suitable kW with Traction pulley, OSG, electromagnetic brakes, entire assembly mounted on adequate size girders duly fixed on LMR floor/ shaft walls complete with main/diverter traction sheaves, suspension wire		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			ropes/belts of adequate size & strength.		
			Other mechanical parts such as 'T' section adequate size guide rails for car & counter weight with brackets fasteners, counter weight frame with necessary blocks, buffers with necessary support arrangement, MS pit ladder etc. erected with necessary steel work • Minor civil work for alteration if any and erection of door frames and accessories, erection buffers, erection of lift machinery, adequate size core cuts if required & scaffolding for erecting guide rails fixing of girders for mounting lift machine etc. complete as per specification no. LFT. • Lift shaft available having clear size of mm wide x.....mm deep, ...mm Pit depth, ...mm Overhead.		
943	MAT-08539	ELEC-13.1.6	Supply, Installation, Testing and Commissioning of Electric Traction Passenger Lift of Makes: As per list of recommended brands. with • Rated capacity :- 22 Passenger/1496Kg • Floors :- G+1 floor (2Stops/2 Landings) • Travel :- 3 to 4.2 mtrs • Location of Lift Machine:- MRL • Rated speed :- 1.0/1.25mps VS • Doors type :- COPO/TOPO Doors with frame having clear opening of 1100 mm wide x 2000 mm high made from SS 304 grade sheet of 1.5mm, thick in hairline finish for car and all landing doors with SS door architraves/frames • Lift car enclosure made from SS 304 grade sheet of 1.5mm, thick with hairline finish with frame made from MS girders, bracing of adequate size with minimum safety factor of 5, with Toe Guard Apron, with necessary false ceiling with adequate LED lights, blower/fan for ventilation & SS chequered plate flooring, handrails, mirror, emergency light etc. COP with SS face plate having metallic push buttons with Braille Code & luminous indicator around button with FPI, scrolling UP/DN LED indicator & with/without attendant key switch, OWD with audio-visual alarm, VAS in Telugu & English with intercom	1Job	2387416

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			system with telephone instrument in Lift car, LMR & FCC/ground floor • Clear Car size of mm wide x mm deep x mm high • LOP with SS face plate having recess/surface push button box for all landings with scrolling UP/DN LED indicator having metallic push buttons with Braille Code & luminous indicator around button with CPI, Lift car arrival & next travel direction audio-visual		
			indication at all landings Lift controller based on microprocessor/ PLC with VVVF Drive having closed loop control system, with IBMS compatible having necessary port, control panel duly wired with proper size & strength copper wire for power & control circuit, with provision for addition of floor/control card & allied accessories control panel having enclosure of 1.5mm CRCA sheet with powder coating with IP54 Protection class • ARD complete with necessary SMF VRLA batteries • Fireman controller having fireman switch at fire Landing, Lift Machine of Gearless PMSM of suitable kW with Traction pulley, OSG, electromagnetic brakes, entire assembly mounted on adequate size girders duly fixed on LMR floor/ shaft walls complete with main/diverter traction sheaves, suspension wire ropes/belts of adequate size & strength • Other mechanical parts such as 'T' section adequate size guide rails for car & counter weight with brackets fasteners, counter weight frame with necessary blocks, buffers with necessary		
			support arrangement, MS pit ladder etc. erected with necessary steel work Minor civil work for alteration if any and erection of door frames and accessories, erection buffers, erection of lift machinery, adequate size core cuts if required & scaffolding for erecting guide rails fixing of girders for mounting lift machine etc. complete as per specification no. LFT. • Lift shaft available having clear size of mm wide x mm deep, ...mm Pit depth, ...mm		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Overhead.		
944	MAT-08540	ELEC-13.1.7	Supply, Installation, Testing and Commissioning of Electric Traction Passenger cum Stretcher/Hospital Lift of Makes: As per list of recommended brands. with • Rated capacity :- 26 Passenger/1768Kg • Floors :- G+1 floor (2Stops/2 Landings) • Travel :- 3 to 4.2 mtrs • Location of Lift Machine:- MR • Rated speed :- 1.0/1.25mps VS • Doors type :- COPO/TOPO Doors with frame having clear opening of 1100/1200 mm wide x 2000 mm high made from SS 304 grade sheet of 1.5mm, thick in hairline finish for car and all landing doors with SS door architraves/frames • Lift car enclosure made from SS 304 grade sheet of 1.5mm, thick with hairline finish with frame made from MS girders, bracing of adequate size with minimum safety factor of 5, with Toe Guard Apron, with necessary false ceiling with adequate LED lights, blower/fan for ventilation & SS chequered plate flooring, handrails, mirror, emergency light etc. COP with SS face plate having metallic push buttons with Braille Code & luminous indicator around button with FPI, scrolling UP/DN LED indicator & with/without attendant key switch, OWD with audio-visual alarm, VAS in Telugu & English with intercom system with telephone instrument in Lift car, LMR & FCC/ground floor • Clear Car size of mm wide x mm deep x mm high	1Job	2546889
			•LOP with SS face plate having recess/surface push button box for all landings with scrolling UP/DN LED indicator having metallic push buttons with Braille Code & luminous indicator around button with CPI, Lift car arrival & next travel direction audio-visual indication at all landings Lift controller based on microprocessor/ PLC with VVVF Drive having closed loop control system, with IBMS compatible having necessary port, control panel duly wired with proper size & strength copper wire for power & control circuit, with provision for		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			addition of floor/control card & allied accessories control panel having enclosure of 1.5mm CRCA sheet with powder coating with IP54 Protection class • ARD complete with necessary SMF VRLA batteries • Fireman controller having fireman switch at fire Landing, • CCTV surveillance system comprises of 2nos minimum 2.0MP FHD IP based vandal proof Dome camera in lift car & in LMR/inside lift shaft top aimed on Lift machinery & controller with NVR kept in LMR/FCC with HDR data backup for 60 days with 18" FHD TV monitor, to be kept in FCC/LMR as directed by Engineer In Charge. Lift Machine of Gearless PMSM of suitable kW with Traction pulley, OSG, electromagnetic brakes, entire assembly mounted on adequate size girders duly fixed on LMR floor/ shaft walls complete with main/diverter traction sheaves, suspension wire ropes/belts		
			of adequate size & strength • Other mechanical parts such as 'T' section adequate size guide rails for car & counter weight with brackets fasteners, counter weight frame with necessary blocks, buffers with necessary support arrangement, MS pit ladder etc. erected with necessary steel work • Minor civil work for alteration if any and erection of door frames and accessories, erection buffers, erection of lift machinery, adequate size core cuts if required & scaffolding for erecting guide rails fixing of girders for mounting lift machine etc. complete as per specification no. LFT. • Lift shaft available having clear size of mm wide x.....mm deep, ...mm Pit depth, ...mm Overhead.		
945	MAT-08541	ELEC-13.1.8	Supply, Installation, Testing and Commissioning of Electric Traction Goods Lift of Makes: As per list of recommended brands. with • Rated capacity :- 3000Kg Goods/44 Passengers • Floors :- G+1 floor (2Stops/2 Landings)	1Job	3091754

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			• Travel :- 3 to 4.2 mtrs • Location of Lift Machine:- MR • Rated speed :- 0.6 to 1.0mps VS • Doors type :- COPO/TOPO Doors with frame having clear opening of 1700 mm wide x 2000 mm high made from SS 304 grade sheet of 1.5mm, thick in hairline finish for car and all landing doors with SS door architraves/frames • Lift car enclosure made from SS 304 grade sheet of 1.5mm, thick with hairline finish with frame made from MS girders, bracing of adequate size with minimum safety factor of 5, with Toe Guard Apron, with necessary false ceiling with adequate LED lights, blower/fan for ventilation & SS chequered plate flooring, handrails, mirror, emergency light etc. • COP with SS face plate having metallic push buttons with Braille Code & luminous indicator around button with FPI, scrolling UP/DN LED indicator & with/without attendant key switch, OWD with audio-visual alarm, VAS in Telugu & English with intercom system with telephone instrument in Lift car, LMR & FCC/ground floor • Clear Car size of mm wide x mm deep x mm high • LOP with SS face plate having recess/surface push button box for all landings with scrolling UP/DN LED indicator having metallic push buttons with Braille Code & luminous indicator around button with		
			CPI, Lift car arrival & next travel direction audio-visual indication at all landings • Lift controller based on microprocessor/ PLC with VVVF Drive having closed loop control system, with IBMS compatible having necessary port, control panel duly wired with proper size & strength copper wire for power & control circuit, with provision for addition of floor/control card & allied accessories • control panel having enclosure of 1.5mm CRCA sheet with powder coating with IP54 Protection class • ARD complete with necessary SMF VRLA batteries • Fireman controller having fireman switch at fire Landing, • Lift Machine of Gearless PMSM of suitable kW		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			with Traction pulley, OSG, electromagnetic brakes, entire assembly mounted on adequate size girders duly fixed on LMR floor/ shaft walls complete with main/diverter traction sheaves, suspension wire ropes/belts of adequate size & strength Other mechanical parts such as 'T' section adequate size guide rails for car & counter weight with brackets fasteners, counter		
			weight frame with necessary blocks, buffers with necessary support arrangement, MS pit ladder etc. erected with necessary steel work • Minor civil work for alteration if any and erection of door frames and accessories, erection buffers, erection of lift machinery, adequate size core cuts if required & scaffolding for erecting guide rails fixing of girders for mounting lift machine etc. complete as per specification no. LFT. • Lift shaft available having clear size of mm wide x.....mm deep, ...mm Pit depth, ...mm Overhead.		
946	MAT-08542	ELEC-13.1.9	Supply, Installation, Testing and Commissioning of Electric Traction Goods Lift of Makes: As per list of recommended brands. with - Rated capacity :- 4000Kg Goods /59 Passengers - Floors :- G+1 floor (2Stops/2 Landings) - Travel :- 3 to 4.2 mtrs - Location of Lift Machine:- MR - Rated speed :- 0.6 to 1.0mps VS - Doors type :- COPO/TOPO Doors with frame having clear opening of 2100 mm wide x 2000 mm high made from SS 304 grade sheet of 1.5mm, thick in hairline finish for car and all landing doors with SS door architraves/frames - Lift car enclosure made from SS 304 grade sheet of 1.5mm, thick with hairline finish with frame made from MS girders, bracing of adequate size with minimum safety factor of 5, with Toe Guard Apron, with necessary false ceiling with adequate LED lights, blower/fan for ventilation & SS chequered plate flooring, handrails, mirror, emergency light etc. - COP with SS face plate having metallic push buttons with Braille Code & luminous indicator	1Job	3423866

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			around button with FPI, scrolling UP/DN LED indicator & with/without attendant key switch, OWD with audio-visual alarm, VAS in Telugu & English with intercom system with telephone instrument in Lift car, LMR & FCC/ground floor Clear Car size of mm wide x mm deep x mm high • LOP with SS face plate having recess/surface push button box for all landings with scrolling UP/DN LED indicator having metallic push buttons with Braille Code & luminous indicator around button with CPI, Lift car arrival & next travel direction audio-visual		
			indication at all landings • Lift controller based on microprocessor/ PLC with VVVF Drive having closed loop control system, with IBMS compatible having necessary port, control panel duly wired with proper size & strength copper wire for power & control circuit, with provision for addition of floor/control card & allied accessories control panel having enclosure of 1.5mm CRCA sheet with powder coating with IP54 Protection class ARD complete with necessary SMF VRLA batteries • Fireman controller having fireman switch at fire Landing, • Lift Machine of Gearless PMSM of suitable kW with Traction pulley, OSG, electromagnetic brakes, entire assembly mounted on adequate size girders duly fixed on LMR floor/ shaft walls complete with main/diverter traction sheaves, suspension wire ropes/belts of adequate size & strength. Other mechanical parts such as 'T' section adequate size guide rails for car & counter weight with brackets fasteners, counter weight frame with necessary blocks, buffers with necessary support arrangement, MS pit ladder etc. erected with necessary steel work • Minor civil work for alteration if any and erection of door frames		
			and accessories, erection buffers, erection of lift machinery, adequate size core cuts if required & scaffolding for erecting guide rails fixing of girders for mounting lift machine etc. complete as per specification no. LFT.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Lift shaft available having clear size of mm wide x.....mm deep, ...mm Pit depth, ...mm Overhead.		
		NOTE:	1. The above rates are applicable only for the makes: KONE/OTIS/SCHINDLER/MITSUBISHI/JOHNSON.		
			2. If the local reputed brands preferred by the Departments or Corporations, the makes Suryodaya Elevators/ESCO Lifts/Sunrise Lifts/BECO LIFTS/ or any other make approved by the competent authority subject to the condition that the Specifications remains unchanged can be adopted in the estimate by reducing the price @15% less than the above rates.		
			Add On		
		A	For Lift travelling up to six floors or at a speed of 1.0 mps, add as below,		
947	MAT-08543	1	For Lift having 700mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	160765
948	MAT-08544	2	For Lift having 800mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, traveling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	165625
949	MAT-08545	3	For Lift having 900mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with	1Floor	171409

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete		
950	MAT-08546	4	For Lift having 1000mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	176577
951	MAT-08547	5	For Lift having 1100mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	181868
952	MAT-08548	6	For Lift having 1200mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	188143
953	MAT-08549	7	For Lift having 1300mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two/four panel], this includes all necessary accessories like LOP's with UP/DN buttons- arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	193927
954	MAT-08550	8	For Lift having 1400mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door	1Floor	199833

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			[Two/four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete		
955	MAT-08551	9	For Lift having 1500mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	209923
956	MAT-08552	10	For Lift having 1700mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	220136
957	MAT-08553	11	For Lift having 1800mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	231334
958	MAT-08554	12	For Lift having 2100mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Six panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift	1Floor	252006

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			installation complete		
959	MAT-08555	13	For Lift having 2200mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Six panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	260743
		A1	For Lift travelling above six floors & up to fifteen floors or at a speed of 1.5 mps, add as below,		
960	MAT-08556	1	For Lift having 700mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	167963
961	MAT-08557	2	For Lift having 800mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	173131
962	MAT-08558	3	For Lift having 900mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	179161

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
963	MAT-08559	4	For Lift having 1000mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	184452
964	MAT-08560	5	For Lift having 1100mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	189989
965	MAT-08561	6	For Lift having 1200mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	196634
966	MAT-08562	7	For Lift having 1300mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two/four panel], this includes all necessary accessories like LOP's with UP/DN buttons- arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	202540
967	MAT-08563	8	For Lift having 1400mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two/four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting	1Floor	208693

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete		
968	MAT-08564	9	For Lift having 1500mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	219152
969	MAT-08565	10	For Lift having 1700mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	229980
970	MAT-08566	11	For Lift having 1800mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	241547
971	MAT-08567	12	For Lift having 2100mm wide x 2000mm high clear entrance 1.5mm thick SS 304 grade landing door [Six panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete	1Floor	263204
972	MAT-08568	13	For Lift having 2200mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Six panel], this includes all necessary accessories	1Floor	272433

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope landing doors with all accessories etc. necessary for the normal safe functioning of lift installation complete		
		A2	For Lift travelling above fifteen floors & up to twenty floors or at a speed of 1.75 mps, add as below,		
973	MAT-08569	1	For Lift having 800mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.	1Floor	178176
974	MAT-08570	2	For Lift having 900mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.	1Floor	184452
975	MAT-08571	3	For Lift having 1000mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.	1Floor	189866
976	MAT-08572	4	For Lift having 1100mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.	1Floor	195650

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
977	MAT-08573	5	For Lift having 1200mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.	1Floor	202417
978	MAT-08574	6	For Lift having 1300mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two/four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.	1Floor	208570
979	MAT-08575	7	For Lift having 1400mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Two/four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.	1Floor	214845
980	MAT-08576	8	For Lift having 1500mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.	1Floor	225551
981	MAT-08577	9	For Lift having 1700mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows-indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.	1Floor	236871
982	MAT-08578	10	For Lift having 1800mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door	1Floor	201433

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			[Four panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.		
983	MAT-08579	11	For Lift having 2100mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Six panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.	1Floor	271202
984	MAT-08580	12	For Lift having 2200mm wide x 2000mm high clear entrance in 1.5mm thick SS 304 grade landing door [Six panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring 1.5mm thick SS 304 grade landing door [Six panel], this includes all necessary accessories like LOP's with UP/DN buttons-arrows- indicators, extension of guide rails, shaft wiring with trunking, travelling cables, main hoisting ropes/belts, & OSG rope, landing doors with all accessories etc. complete for the safe functioning of lift installation.	1Floor	280308
		B	If there is additional automatic car door, add as below.		
985	MAT-08581	1	For Lift car having 700mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [Two panel] complete with required accessories like door operator mechanism with drive, required aluminium sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete.	1Set	133140
986	MAT-08582	2	For Lift car having 800mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [Two panel] complete with required accessories like door operator mechanism with drive, required Aluminium sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete.	1Set	137201

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
987	MAT-08583	3	For Lift car having 900mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [Two panel] complete with required accessories like door operator mechanism with drive, required aluminum sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete.	1Set	142000
988	MAT-08584	4	For Lift car having 1000mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [Two panel]complete with required accessories like door operator mechanism with drive, required aluminum sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete.	1Set	146676
989	MAT-08585	5	For Lift car having 1100mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [Two panel]complete with required accessories like door operator mechanism with drive, required aluminum sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete	1Set	151105
990	MAT-08586	6	For Lift car having 1200mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [Two panel]complete with required accessories like door operator mechanism with drive, required aluminum sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete.	1Set	156520
991	MAT-08587	7	For Lift car having 1300mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [Two/four panel] complete with required accessories like door operator mechanism with drive, required aluminum sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete.	1Set	161565
992	MAT-08588	8	For Lift car having 1400mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [Two/four panel] complete with required accessories like door operator mechanism with drive, required aluminum sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete.	1Set	166364

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
993	MAT-08589	9	For Lift car having 1500mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [four panel] complete with required accessories like door operator mechanism with drive, required aluminum sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete.	1Set	174608
994	MAT-08590	10	For Lift car having 1700mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [four panel] complete with required accessories like door operator mechanism with drive, required aluminum sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete.	1Set	184329
995	MAT-08591	11	For Lift car having 1800mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [four panel] complete with required accessories like door operator mechanism with drive, required aluminum sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete.	1Set	193435
996	MAT-08592	12	For Lift car having 2100mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [six panel] complete with required accessories like door operator mechanism with drive, required aluminum sill, infrared curtain & necessary wiring with interlocking arrangement etc. complete.	1Set	211400
997	MAT-08593	13	For Lift car having 2200mm wide x 2000mm high clear entrance having 1.5mm thick SS 304 grade sheet car door [six panel] complete required aluminum sill, infrared curtain & necessary wiring interlocking arrangement etc. complete.	1Set	219521
		C	For Full Collective control system, add as below.		
998	MAT-08594	1	For Lift travelling above First floor & up to Sixth floor	1No	31661
999	MAT-08595	2	For Lift travelling above Sixth floor & up to Fifteenth floor	1No	72503

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
1000	MAT-08596	3	For Lift travelling above Fifteenth floor & up to Twentieth floor	1No	95102
1001	MAT-08597	D	For additional 2MP Camera along with necessary accessories at Home Landing, add as given.	1No	15654
		E	For Group control system of number of lifts, add as below.		
1002	MAT-08598	1	For Duplex Lift control system	1Job	40253
1003	MAT-08599	2	For Triplex Lift control system	1Job	60145
1004	MAT-08600	3	For Quadruplex Lift control system	1Job	81095
1005	MAT-08601	F	For vision panel having Size 100mm wide x 200mm high covered with fire rated laminated glass, having punched Jali as a part of the door panel SS sheet itself.	1No	3178
		G	The above rates are for landing & car door height of 2000mm and Lift car ceiling height of 2250mm. If the requirements for landing & car doors height above 2000mm & Lift car height above 2250mm, add overall Rs. per 100mm rise per Lift per landing.		
		a	For Lift car enclosure & car door per 100mm Step rise		
1006	MAT-08602	1	for Lift car door, having clear entrance of 700/800/900mm wide	1 per Landing	52141
1007	MAT-08603	2	for Lift car door, having clear entrance 1000/1100/1200/1300mm wide	1 per Landing	71444

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
1008	MAT-08604	3	for Lift car door, having clear entrance 1400/1500/1700mm wide	1 per Landing	125233
1009	MAT-08605	4	for Lift car door, having clear entrance 1800/2100/2200mm wide	1 per Landing	212802
		b	For Lift Landings per 100mm Step rise		
1010	MAT-08606	1	for Lift Landing door having clear entrance of 700/800/900mm wide	1 per Landing	13065
1011	MAT-08607	2	for Lift Landing door, having clear entrance of 1000/1100/1200/1300mm wide	1 per Landing	17773
1012	MAT-08608	3	for Lift Landing door, having clear entrance of 1400/1500/1700mm wide	1 per Landing	28130
1013	MAT-08609	4	for Lift Landing door, having clear entrance of 1800/2100/2200mm wide	1 per Landing	42137
		Notes:			
		1	General: - Job includes entire procedure of obtaining all necessary erection permissions & "License to Work the Lift" from Electrical Inspector(Lifts) with submission to the Engineer In Charge.		
		2	Warrantee: - Job covers two years onsite warrantee for all the Lift parts with FCAMC as per the maintenance schedule.		
			Note 1 and 2 above shall be included in item description.		
		3	If the lift shaft is greater than the required size of the lift as mentioned in relevant Indian Standard [with Amendments up to date], the provision of extra steel required for erecting supports of guide rails shall be made by the department as a separate item		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		4	The Electric power supply of 415 volts, 3 phase 4 wire,50Hz shall be made available up to Lift controller, and as per the provisions laid down in relevant The Electricity Safety Regulations 2010[with Amendments up to date], Indian Standard, relevant Rules, the separate cables for lighting and power & shall be erected through lift shaft only with 2nos distinct earth connections from lift machine & controller		
		5	The technical specification of Lift duty motor, control panel, brakes, guide rails, and guide shoes, lift car frame, car, counter weight and suspension, lift safety gear and governor, buffer, lift doors, locking device and contacts, lift wire rope of lifts shall be as per actual requirement of the job.		
		6	For nonstandard lift shafts the Lift capacity shall be selected so that all the safety clearances to be maintained as per the provisions laid down in relevant Indian Standard, & relevant Rules and work shall be carried out accordingly		
		7	For building having height of 15 mtr or more, lift shall meet the requirement of fireman lift as per the statutory requirements laid in relevant Indian Standard		
		8	Vision Panel shall not be provided on power operated doors and Fireman lifts. However manually operated vertically sliding, horizontally sliding or swing type doors may be provided with a vision panel if required		
		9	While framing estimates of lifts for handicapped persons/ Hospital/Goods Lifts, the relevant Indian standard shall be referred for dimensions.		
		10	The sizes in mm for Lift car, entrance, available lift Shaft etc. with travel shall be mentioned in the Detailed Estimate		
		11	The above rates are for mostly installed Electric Traction Lifts, for Lift requirements with different purposes/ specifications, the items should be got approved from the competent authority		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		12	The Traffic Analysis [TA] shall be done as per the provisions laid down in relevant Indian standards for finalizing the capacity and number of Lifts in different types of buildings.		
			13.2: LIFT REPAIR/MODERNIZATION		
			LIFT MACHINE		
1014	MAT-08610	ELEC-13.2.1	Overhauling of Gearbox by opening the gear box, cleaning the oil path with oil adjusting the Thrust bearing, & bush with packings etc. and refilling with the fresh oil of requisite viscosity and sufficient quantity, complete with re-erection as original with necessary alignment & testing.	1Job	7062
1015	MAT-08611	ELEC-13.2.2	Providing dismantling the existing worn-out/damaged Thrust bearing & bush with allied accessories complete supplying & installing new Thrust bearing & Bush with allied accessories like packings etc. and refilling with the fresh gear oil of requisite viscosity and sufficient quantity, complete suitable up to 10 passenger lift car with re-erection as original with necessary alignment & testing	1Job	17655
1016	MAT-08612	ELEC-13.2.3	Providing dismantling the existing lift duty electric motor from lift gearbox coupling to carryout necessary repairs and re-erection the same as original with necessary alignment & testing complete after repairing	1Job	3531
1017	MAT-08613	ELEC-13.2.4	Providing rewinding of the electromagnetic type brake coil suitable to operate on 110V DC supply by superior quality enameled copper wire of require size complete with testing	1Job	5297
1018	MAT-08614	ELEC-13.2.5	Providing and fixing new set brake liner of good quality complete with alignment & testing with removal of old worn-out brake liners	1Job	2943
1019	MAT-08615	ELEC-13.2.6	Providing dismantling the existing main driving sheave complete by hanging the lift car and providing and fixing a new main driving sheave made from superior quality cast iron completely finished having diameter up to 600mm suitable up to 4nos rope grooves the size for the same will be specified in the estimate	1Job	17067

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
1020	MAT-08616	ELEC-13.2.7	Providing dismantling the existing main driving sheave complete by hanging the lift car and providing and fixing a new main driving sheave made from superior quality cast iron completely finished having diameter 601 to 800mm suitable up to 4nos rope grooves .	1Job	21775
1021	MAT-08617	ELEC-13.2.8	Providing dismantling the existing diverter sheave complete by hanging the lift car and providing and fixing a new diverter sheave made from superior quality cast iron completely finished having diameter up to 250mm suitable up to 4nos rope grooves.	1Job	12241
1022	MAT-08618	ELEC-13.2.9	Providing dismantling the existing diverter sheave complete by hanging the lift car and providing and fixing a new diverter sheave made from superior quality cast iron completely finished having diameter 251 to 500mm suitable up to 4nos rope grooves.	1Job	13889
1023	MAT-08619	ELEC-13.2.10	Providing dismantling the existing OSG pulley set (top & bottom) complete and providing and fixing overspeed governor pulley set (top& bottom) made from superior quality cast iron completely finished suitable for Lift car rated speed.	1Job	12005
1024	MAT-08620	ELEC-13.2.11	Providing dismantling the existing OSG rubber roller complete, providing and fixing new nylon roller of superior quality.	1Job	471
			LIFT CAR		
1025	MAT-08621	ELEC-13.2.12	Providing dismantling the existing lift car/counter weight guide shoe liner and providing and fixing new superior quality non-metallic car/counter weight guide shoe Liner complete with re-erection, alignment & adjustment complete with lubrication	1Job	3413
1026	MAT-08622	ELEC-13.2.13	Providing dismantling the existing unserviceable retiring cam (Door)by supplying & erecting new one of superior quality with necessary spare complete with re-erection and testing etc. with copper wound magnetic coil of 110V DC supply.	1Job	5414
1027	MAT-08623	ELEC-13.2.14	Providing dismantling the existing deteriorated lift car flooring/floor tiles by supplying & erecting SS chequered plate of required thickness and of	1Kg	589

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			superior quality with necessary material		
1028	MAT-08624	ELEC-13.2.15	Providing dismantling the existing deteriorated lift car enclosure by supplying & erecting new enclosure made from 1.5mm thick stainless steel sheet SS304 grade of superior quality with necessary material complete with handrail, mirror, required thickness stainless steel chequered plate flooring and min. 2.5mm thick GI sheet car top & stainless steel 304grade 1.2mm thick false ceiling & required LED light fitting & cabin fan/blower, emergency light with necessary grill along with required accessories suitable for 4 to 8 passenger lift car	1Job	179022
1029	MAT-08625	ELEC-13.2.16	Providing dismantling the existing deteriorated lift car enclosure by supplying & erecting new enclosure made from 1.5mm thick stainless steel sheet SS304 grade of superior quality with necessary material complete with handrail, mirror, required thickness stainless steel chequered plate flooring and min. 2.5mm thick GI sheet car top & stainless steel 304grade 1.2mm thick false ceiling & required LED light fitting & cabin fan/blower, emergency light with necessary grill along with required accessories suitable for 10 to 13 passenger lift	1Job	215626
1030	MAT-08626	ELEC-13.2.17	Providing dismantling the existing deteriorated lift car enclosure by supplying & erecting new enclosure made from 1.5mm thick stainless steel sheet SS304 grade of superior quality with necessary material complete with handrail, mirror, required thickness stainless steel chequered plate flooring and min. 2.5mm thick GI sheet car top & stainless steel 304grade 1.2mm thick false ceiling & required LED light fitting & cabin fan/blower, emergency light with necessary grill along with required accessories suitable for 14 to 16 passenger lift car	1Job	251290
1031	MAT-08627	ELEC-13.2.18	Providing dismantling the existing deteriorated lift car enclosure by supplying & erecting new enclosure made from 1.5mm thick stainless steel sheet SS304 grade of superior quality with necessary material complete with handrail, mirror, required thickness stainless steel chequered plate flooring and min. 2.5mm thick GI sheet car top & stainless	1Job	291308

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			steel 304grade 1.2mm thick false ceiling & required LED light fitting & cabin fan/blower, emergency light with necessary grill along with required accessories suitable for 18 to 23 Passenger Lift Car		
1032	MAT-08628	ELEC-13.2.19	Providing dismantling the existing deteriorated Lift car enclosure by supplying & erecting new enclosure made from 1.5mm thick stainless steel sheet SS304 grade of superior quality with necessary material complete with handrail, mirror, required thickness stainless steel chequered plate flooring and min. 2.5mm thick GI sheet car top & stainless steel 304grade 1.2mm thick false ceiling & required LED light fitting & cabin fan/blower, emergency light with necessary grill along with required accessories suitable for 26 to 36 Passenger Lift Car	1Job	371814
1033	MAT-08629	ELEC-13.2.20	Supplying erecting & testing & commissioning minimum 2000mm high Infra-Red/IR curtain with minimum 80beams, suitable to attach automatic Lift car door complete with electronic driver suitable to work on 230V AC supply with required wiring & accessories complete connected to the lift controller safety circuit. including dismantling of existing accessories as applicable	1No	58497
1034	MAT-08630	ELEC-13.2.21	Supplying & erecting laminated type with minimum 6mm thick mirror confirming to relevant standard in the lift car complete pasting with necessary adhesives if required and fixing with SS frame & accessories complete, this job includes dismantling of existing accessories as applicable	1Sqft	589
			LIFT SHAFT		
1035	MAT-08631	ELEC-13.2.22	Providing Emergency Stop Switch as per IS [push to stop & pull/rotate clockwise to open] erected on GI box in pit/LMR /car top for maintenance work complete with necessary wires	1No	824
1036	MAT-08632	ELEC-13.2.23	Supplying & erecting over travel final/Terminal limit switch complete with nylon roller for up & down direction along with cams etc as required.	1No	2354
1037	MAT-08633	ELEC-13.2.24	Providing and fixing new magnetic reed switch with M.S. Flag for levelling the lift. Providing and fixing	1No	1177

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			necessary magnet for the floor position indicator, providing and fixing electronics card with digital indicator, complete with re-erection including dismantling of existing accessories as applicable		
1038	MAT-08634	ELEC-13.2.25	Supplying & erecting lift car door lock with electrical contact[spring loaded NO/NC of 5A/250V rating] complete unit with Bakelite roller attached to bracket on car top with M.S. "T" bracket attached to car gate complete with Testing including dismantling of existing accessories as applicable	1No	1177
1039	MAT-08635	ELEC-13.2.26	Supplying & erecting main suspension wire rope of 13mm dia having 8/19 construction as per IS complete with termination in provided eye bolts including dismantling of existing accessories as applicable	1Mt	235
1040	MAT-08636	ELEC-13.2.27	Supplying & erecting main suspension wire rope of 10mm dia. having 8/19 construction as per IS complete with termination in provided eye bolts including dismantling of existing accessories as applicable	1Mt	235
1041	MAT-08637	ELEC-13.2.28	Supplying & erecting main suspension wire rope of 8mm dia .having 8/19 construction as per IS complete with termination in provided eye bolts including dismantling of existing accessories as applicable	1Mt	177
1042	MAT-08638	ELEC-13.2.29	Supplying & erecting wire rope of 3/4/6mm dia. having 6/19 construction as per IS complete with termination in provided eye bolts including dismantling of existing accessories as applicable	1Mt	118
1043	MAT-08639	ELEC-13.2.30	Supplying & erecting GI eye bolt suitable for tie up of min. 13mm dia. lift wire ropes with 4nos bull dog clips 8/19 construction as per IS Complete with termination in provided eye bolts including dismantling of existing accessories as applicable	1No	1766
1044	MAT-08640	ELEC-13.2.31	Supplying & erecting GI eye bolt suitable for tie up of 8/10mm dia. lift wire ropes with 4nos bull dog clips 8/19 construction as per IS Complete with termination in provided eye bolts including dismantling of existing accessories as applicable.	1No	1412

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			CAR & LANDING DOORS:		
1045	MAT-08641	ELEC-13.2.32	Repairing of M.S. collapsible landing/lift car door for broken rivets, pickets gibes, roller bearings complete with oiling etc. complete with re-erection, and alignment for smooth operation	1Job	1059
1046	MAT-08642	ELEC-13.2.33	Supplying & erecting MS collapsible type perforate Car/ Landing door with 50mm high 8mm thick MS pata at top with roller bearings & nylon gibes complete having adequate strength as per requirements with necessary alignment complete with having clear opening of 700/800mm in width and clear height not less than 2000mm including dismantling of existing door as applicable	1Job	10593
1047	MAT-08643	ELEC-13.2.34	Supplying & erecting MS collapsible type perforate Car/Landing door with 50mm high 8mm thick MS pata at top with roller bearings & nylon gibes complete having adequate strength as per requirements with necessary alignment complete with having clear opening of 1000/1200mm in width and clear height not less than 2000mm including dismantling of existing door as applicable	1Job	12594
1048	MAT-08644	ELEC-13.2.35	Supplying & erecting MS Collapsible type imperforate Car/Landing door with 50mm high 8mm thick MS pata at top with roller bearings & Nylon gibes complete having adequate strength as per requirements with necessary alignment complete with grassing Note for Imperforate door the thickness of CRCA sheet not less than 1.mm having clear opening of 700/800mm in width and clear height not less than 2000mm, including dismantling of existing door as applicable	1Job	16478
1049	MAT-08645	ELEC-13.2.36	Supplying & erecting COPO car/landing door panels with frame made from 1.5mm thick SS 304grade sheet complete with necessary coupler arrangements, nylon bearings at hanger with header assembly with all required accessories with electromechanical lock & nylon coated guide shoes complete having adequate strength as per requirements with necessary alignment complete with greasing having clear opening of 700mm in width and clear height not less than 2000mm,	1Job	73798

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			including dismantling of existing door as applicable.		
1050	MAT-08646	ELEC-13.2.37	Supplying & erecting COPO car/landing door panels with frame made from 1.5mm thick SS 304grade sheet complete with necessary coupler arrangements, nylon bearings at hanger with header assembly with all required accessories with electromechanical lock & nylon coated guide shoes complete having adequate strength as per requirements with necessary alignment complete with greasing having clear opening of 800mm in width and clear height not less than 2000mm, including dismantling of existing door as applicable	1Job	79094
1051	MAT-08647	ELEC-13.2.38	Supplying & erecting COPO car/landing door panels with frame made from 1.5mm thick SS 304grade sheet complete with necessary coupler arrangements, nylon bearings at hanger with header assembly with all required accessories with electromechanical lock & nylon coated guide shoes complete having adequate strength as per requirements with necessary alignment complete with greasing having clear opening of 900mm in width and clear height not less than 2000mm, including dismantling of existing door as applicable	1Job	89687
1052	MAT-08648	ELEC-13.2.39	Supplying & erecting COPO car/landing door panels with frame made from 1.5mm thick SS 304grade sheet complete with necessary coupler arrangements, nylon bearings at hanger with header assembly with all required accessories with electromechanical lock & nylon coated guide shoes complete having adequate strength as per requirements with necessary alignment complete with greasing having clear opening of 1000mm in width and clear height not less than 2000mm, including dismantling of existing door as applicable	1Job	102164
1053	MAT-08649	ELEC-13.2.40	Supplying & erecting COPO car/landing door panels with frame made from 1.5mm thick SS 304grade sheet complete with necessary coupler arrangements, nylon bearings at hanger with header assembly with all required accessories with electromechanical lock & nylon coated guide shoes complete having adequate strength as per	1Job	116523

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			requirements with necessary alignment complete with greasing having clear opening of 1200mm in width and clear height not less than 2000mm, including dismantling of existing door as applicable		
1054	MAT-08650	ELEC-13.2.41	Providing & fixing aluminum sill with 1 track suitable for fixing of car/ landing door with necessary material like MS brackets, fasteners complete with alignment, including dismantling of existing door as applicable	1Mt	1236
1055	MAT-08651	ELEC-13.2.42	Providing & fixing aluminum Sill with 2 track suitable for fixing of car/ landing door with necessary material like MS brackets, fasteners complete with alignment, including dismantling of existing door as applicable	1Mt	1648
1056	MAT-08652	ELEC-13.2.43	Providing & fixing landing door gate lock of superior quality with necessary adjustable operating lever complies with the relevant IS suitable for swing or collapsible type landing doors	1No	4708
1057	MAT-08653	ELEC-13.2.44	Providing & fixing landing/Car gate movable contact electrical switch of superior quality complies with the relevant IS suitable for all type of landing/car doors	1No	177
1058	MAT-08654	ELEC-13.2.45	Providing & fixing LOP with single push button with metallic top& Braille Coded suitable for UP/DN having luminous glow indicator around button with MS box & 3mm thick SS face plate with screws with UP & DN button & digital CPI (suitable for 1digits) complete with necessary connections, including dismantling of existing door as applicable	1No	5179
1059	MAT-08655	ELEC-13.2.46	Providing & fixing LOP with two push button with metallic top & Braille coded suitable for UP/DN having luminous glow indicator around button with MS box & 3mm thick SS face plate with screws with UP & DN button & digital CPI (suitable for 2digits) complete with necessary connections, including dismantling of existing door as applicable	1No	6238
1060	MAT-08656	ELEC-13.2.47	Providing & fixing COP with push buttons having luminous glow indicator around button suitable for G+7 floors with push buttons with metallic top & Braille coded suitable for door close, door open, alarm bell, stop, light, fan, intercom etc, FPI, with MS box & 3mm thick SS face Plate with UP & DN arrows & digital FPI (suitable for 2digits) complete with necessary connections, including dismantling of	1No	19185

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			existing COP as applicable		
1061	MAT-08657	ELEC-13.2.48	Providing & fixing push button suitable with micro switch with push button on existing COP/LOP with necessary connections and testing complete including dismantling of existing button accessories as applicable	1No	1118
1062	MAT-08658	ELEC-13.2.49	Providing & fixing 40mm high fixing digital indicator module of gives indication of required shade with connections and testing complete including dismantling of existing accessories as applicable	1No	1412
1063	MAT-08659	ELEC-13.2.50	Providing & fixing car door operator motor with assembly of suitable capacity & speed with necessary pulleys & required accessories complete including dismantling of existing accessories as applicable	1No	28248
1064	MAT-08660	ELEC-13.2.51	Providing & fixing hydraulic type landing door closer suitable for swing door with necessary material complete, including dismantling of existing accessories as applicable	1No	1471
1065	MAT-08661	ELEC-13.2.52	Providing & fixing car/landing door guide shoe liner/ gibes complete with necessary material like nylon coating complete including dismantling of existing accessories as applicable	1 door	706
			CONTROLLER		
1066	MAT-08662	ELEC-13.2.53	Supplying erecting, testing & commissioning of electronic microprocessor/ PLC based collective-selective lift controller with closed loop logic suitable up to 5.5kW capacity lift duty motor without VVVF Drive and lift car travelling Gr+7 floors having manual operated doors complete erected on wall or floor made from 1.5mm thick CRCA sheet with powder coated enclosure having IP54 protection grade, including dismantling of existing accessories as applicable.	1Job	123350
1067	MAT-08663	ELEC-13.2.54	Supplying erecting, testing & commissioning of electronic microprocessor/PLC based collective-selective lift controller with closed loop logic suitable up to 5.5kW capacity lift duty motor without VVVF Drive & lift car travelling Gr+7	1Job	146772

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			floors having power operated doors complete erected on wall or floor made from 1.5mm thick CRCA sheet with powder coated enclosure having IP54 protection grade. including dismantling of existing accessories as applicable		
1068	MAT-08664	ELEC-13.2.55	Supplying erecting, testing & commissioning of VVVF drive having provision for closed loop logic with necessary card, suitable to drive lift duty electric motor up to 5.5kW capacity to be erected in position with necessary wiring in existing control panel including dismantling of existing accessories as applicable	1Job	71679
1069	MAT-08665	ELEC-13.2.56	Supplying erecting, testing & commissioning of VVVF drive having provision for closed loop logic with necessary card, suitable to drive lift duty electric motor up to 7.5kW capacity to be erected in position with necessary wiring in existing control panel including dismantling of existing accessories as applicable	1Job	83979
1070	MAT-08666	ELEC-13.2.57	Supplying erecting, testing & commissioning of VVVF drive having provision for closed loop logic with necessary card, suitable to drive lift duty electric motor up to 10/11kW capacity to be erected in position with necessary wiring in existing control panel including dismantling of existing accessories as applicable	1Job	107342
1071	MAT-08667	ELEC-13.2.58	Supplying erecting, testing & commissioning of VVVF drive having provision for closed loop logic with necessary card, suitable to drive lift duty electric motor up to 15kW capacity to be erected in position with necessary wiring in existing control panel including dismantling of existing accessories as applicable	1Job	135708
1072	MAT-08668	ELEC-13.2.59	Supplying erecting, testing & commissioning of VVVF drive having provision for closed loop logic suitable to drive lift door operator motor up to 0.5/0.75kW capacity to be erected in position with necessary wiring in existing control panel including dismantling of existing accessories as applicable	1Job	28130
1073	MAT-08669	ELEC-13.2.60	Supplying erecting, testing & commissioning of rotary encoder mounted on the lift motor shaft for	1Job	26129

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			correct & control the positioning & direction of the lift car & providing closed loop feedback to the lift controller complete with necessary shielded data cable up to controller with necessary connectors, this job includes dismantling of existing encoder if any.		
1074	MAT-08670	ELEC-13.2.61	Providing & fixing inspection/maintenance box with cover of suitable size with UP/DN push buttons (with mechanical protection), stop button as per IS, mechanically protected, toggle switch for normal/inspection/maintenance mode, 6A/250V 3Pin socket & 6A piano type switch protected cover with bulb & switch having IP54 grade protection class, this job includes dismantling of existing Inspection/maintenance box if any.	1Job	1766
1075	MAT-08671	ELEC-13.2.62	Providing & fixing junction box having size of 300x300mm & height of 80mm complete with Bakelite terminal strip of 16A/500V rating with cover having IP54 grade protection class includes dismantling of existing Junction box if any. This job includes dismantling of existing inspection/maintenance box if any.	1Job	1295
1076	MAT-08672	ELEC-13.2.63	Supplying erecting, testing & commissioning of ARD panel having audio-visual indication in lift car complete with necessary SMF VRLA batteries suitable for up to 8 passenger capacity lift car including dismantling of existing accessories as applicable	1Job	92512
1077	MAT-08673	ELEC-13.2.64	Supplying erecting, testing & commissioning of ARD panel having audio-visual indication in lift car complete with necessary SMF VRLA batteries suitable for 9 to 12 passenger capacity lift car. Including dismantling of existing accessories as applicable	1Job	104871
1078	MAT-08674	ELEC-13.2.65	Supplying erecting, testing & commissioning of ARD panel having audio-visual indication in lift car complete with necessary SMF VRLA batteries suitable for 13 to 16 passenger capacity lift car. Including dismantling of existing accessories as applicable	1Job	119819
1079	MAT-08675	ELEC-13.2.66	Supplying erecting, testing & commissioning of ARD panel having audio-visual indication in lift car	1Job	136532

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			complete with necessary SMF VRLA batteries suitable for 17 to 22 passenger capacity lift car. Including dismantling of existing accessories as applicable		
1080	MAT-08676	ELEC-13.2.67	Supplying erecting, testing & commissioning of ARD panel having audio-visual indication in lift car complete with necessary SMF VRLA batteries suitable for 23 to 29 passenger capacity lift car. Including dismantling of existing accessories as applicable	1Job	156894
1081	MAT-08677	ELEC-13.2.68	Providing complete lift shaft wiring in copper wire/cable from main controller to car top with COP & to all landing push button panel to all landing gate locks to all floor levelling switch to main motor to brake unit & final limit switch indicator system using ISI mark single pvc insulated flexible copper wire having minimum 1.0 sq. mm size from controller to safety devices & 0.75 Sq mm size for indication system complete in PVC/GI trunking with cover for lift with manually/power operated doors travelling up to G+1 floors /2stops& 2landings for floor height up to 4.2mtrs including dismantling of existing accessories as applicable	1Job	23540
1082	MAT-08678	ELEC-13.2.69	Supplying, erecting & terminating flat flexible PVC insulated cable 4core 1.0 sq. mm copper conductor used for railing cables complete erected with PVC/wooden fastening arrangement & lugs, on wall / trunking as per specification including dismantling of existing accessories as applicable	1Mt	177
1083	MAT-08679	ELEC-13.2.70	Supplying, erecting & terminating flat flexible PVC insulated cable 12core 1.0 sq. mm copper conductor used for trailing cables complete erected with pvc/wooden fastening arrangement & lugs, on wall/ trunking as per specification including dismantling of existing accessories as applicable	1Mt	471
1084	MAT-08680	ELEC-13.2.71	Supplying, erecting, testing & commissioning programmable rope mounted Overload Warning Device (OWD) within built digital indicator complete with required wiring & accessories with audio visual indication in lift car including dismantling of existing accessories as applicable.	1Job	75093

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		Note:	1.For item no 13-2-2....for 11 to 20 passenger capacity lift, add 15% to the basic cost		
			2.For item no 13-2-2....for 21 to 29 passenger capacity lift, add 25% to the basic cost		
			3.For item nos. 13-2-6 to 13-2-9 main/diverter sheave for additional groove exceeding 4nos, add 10% in the basic cost per additional groove		
			4.For item no's 13-2-33 to 13-2-35 for Stainless Steel Collapsible doors, basic cost of MS collapsible shall be doubled, Note:- This item shall be operated with prior permission in writing from the concern Superintending Engineer (Electrical).		
			5.For item no's 13-2-33 to 13-2-35, If the requirements for landing/car doors clear height above 2000mm , for Manual operated MS door panels add Rs.1,000/- per 100mm rise per landing.		
			6. For item nos. 13-2-36 to 13-2-40 the rates are for automatic landing/car door with clear height of 2000mm If the Requirements for landing/car doors clear height above 2000mm, refer add on item no. 13-1/G (b)		
			7.For item no 13-2-47- Providing & fixing additional Floor button with allied hardware components on COP, add Rs. 2500/- per additional button.		
			8.For item no 13-2-53 & 13-2-54... Lift Controller for Lift car travelling 9 stops to 15 stops, add Rs. 27300/-.		
			9.For item no 13-2-53 & 13-2-54... Lift Controller for Lift car travelling 16 stops to 21 stops, Rs. 46000/-.		
			10.For item no 13-2-53 & 13-2-54....Lift Controller for Power Circuit suitable for above 5.5kW & up to 10kW motor, add Rs.7500/-.		
			11.For item no 13-2-53 & 13-2-54... Lift Controller for Power Circuit suitable for above 10kW & up to 15kW motor, add Rs.10900/-		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			12.For item no 13-2-68 ... For Lift Shaft Wiring in copper wire/cable, above 1st floor for lifts with manually/power operated doors, add Rs. 2500/- per floor.		
			13.The cost of dismantled material of lift parts, shall be calculated on the rate analysis based on weight density calculations of actual dismantled material e.g. mild steel/MS/GI/SS sheets, motors, copper wire, wooden parts etc.		
			14.The lift dismantled retrieved material will be handed over to agency and the calculated amount will be deducted in the bill.		
			13.3: DISMANTLING		
1085	MAT-08681	ELEC-13.3.1	Dismantling the existing 4 to 7 Passenger lift of all types travelling G+1 floors (2 Landings/2Stops) having with auto/manual operated doors for lift car & all landings with door frames, guide rails, controller, wiring buffers, Lift Machine, ropes complete with all allied accessories of Lift and making the site clear in all respect complete with refilling the holes with cement mortar & making the site as original this job includes transportation of the dismantled material upto division/section store and handing over to the section engineer/store keeper in charge complete.	1Job	35310
1086	MAT-08682	ELEC-13.3.2	Dismantling the existing 8 to 12 Passenger lift of all types travelling G+1 floors (2 Landings/2Stops) having with auto/manual operated doors for lift car & all landings with door frames, guide rails, controller, wiring buffers, Lift Machine, ropes complete with all allied accessories of Lift and making the site clear in all respect complete with refilling the holes with cement mortar & making the site as original this job includes transportation of the dismantled material upto division/section store and handing over to the section engineer/store keeper in charge complete.	1Job	41195

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
1087	MAT-08683	ELEC-13.3.3	Dismantling the existing 13 to 17 passenger/Stretcher/Goods lift of all types travelling G+1 floors (2 Landings/2Stops) having with auto/manual operated doors for lift car & all landings with door frames, guide rails, controller, wiring buffers, Lift Machine, ropes complete with all allied accessories of Lift and making the site clear in all respect complete with refilling the holes with cement mortar & making the site as original this job includes transportation of the dismantled material up to division/section store and handing over to the section engineer/store keeper in charge complete	1Job	47080
1088	MAT-08684	ELEC-13.3.4	Dismantling the existing 18 to 22 Passenger/Stretcher/Goods lift of all types travelling G+1 floors (2 Landings/2Stops) having with auto/manual operated doors for lift car & all landings with door frames, guide rails, controller, wiring buffers, Lift Machine, ropes complete with all allied accessories of Lift and making the site clear in all respect complete with refilling the holes with cement mortar & making the site as original this job includes transportation of the dismantled material up to division/section store and handing over to the section engineer/store keeper in charge complete	1Job	49434
1089	MAT-08685	ELEC-13.3.5	Dismantling the existing 23 to 26 Passenger/Stretcher/Goods lift of all types travelling G+1 floors (2 Landings/2Stops) having with auto/manual operated doors for lift car & all landings with door frames, guide rails, controller, wiring buffers, Lift Machine, ropes complete with all allied accessories of Lift and making the site clear in all respect complete with refilling the holes with cement mortar & making the site as original this job includes transportation of the dismantled material up to division/section store and handing over to the section engineer/store keeper in charge complete	1Job	56496
1090	MAT-08686	ELEC-13.3.6	Dismantling the existing 27 to 36 Passenger/Stretcher/Goods lift of all types travelling G+1 floors (2 Landings/2Stops) having with auto/manual operated doors for lift car & all landings with door frames, guide rails, controller, wiring buffers, Lift Machine, ropes complete with all allied accessories of Lift and making the site clear in all	1Job	61204

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			respect complete with refilling the holes with cement mortar & making the site as original this job includes transportation of the dismantled material up to division/section store and handing over to the section engineer/store keeper in charge complete		
1091	MAT-08687	ELEC-13.3.7	Dismantling the 3000 to 5000KG Goods lift of all types travelling G+1Upper Floors (2 Landings/2Stops) having with auto/manual operated doors for lift car & all landings with door frames, guide rails, controller, wiring buffers, Lift Machine, ropes complete with all allied accessories of Lift and making the site clear in all respect complete with refilling the holes with cement mortar & making the site as original this job includes transportation of the dismantled material up to division/section store and handing over to the section engineer/store keeper in charge complete	1Job	63558
			Add On		
		A	If there are addition of floors for lift travelling up to six floors, add as given below		
	MAT-08688	1	For 4 to 7 passenger lift of all types	1Floor	2943
	MAT-08689	2	For 8 to 12 passenger lift of all types	1Floor	3178
	MAT-08690	3	For 13 to 17 passenger/stretchers/goods lift of all types	1Floor	3413
	MAT-08691	4	For 18 to 23 passenger/stretchers/goods lift of all types	1Floor	3884
	MAT-08692	5	For 23 to 26 passenger/stretchers/goods lift of all types	1Floor	4002
	MAT-08693	6	For 27 to 36 passenger/stretchers/goods lift of all types	1Floor	4237
	MAT-08694	7	For 3000 to 5000Kg goods lift of all types	1Floor	4590

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		A1	If there are additional floors for Lift travelling above Six floors and up to Fifteen floors Add as given below		
	MAT-08695	1	For 4 to 7 passenger lift of all types	1Floor	3178
	MAT-08696	2	For 8 to 12 passenger lift of all types	1Floor	3413
	MAT-08697	3	For 13 to 17 passenger/stretchers/goods lift of all types	1Floor	3884
	MAT-08698	4	For 18 to 23 passenger/stretchers/goods lift of all types	1Floor	4002
	MAT-08699	5	For 23 to 26 passenger/stretchers/goods lift of all types	1Floor	4237
	MAT-08700	6	For 27 to 36 passenger/stretchers/goods lift of all types	1Floor	4590
	MAT-08701	7	For 3000 to 5000Kg goods lift of all types	1Floor	4826
		A2	If there are additional floors for Lift travelling above fifteen floors and up to Twenty floors , add as given below		
	MAT-08702	1	For 4 to 7 passenger lift of all types	1Floor	3413
	MAT-08703	2	For 8 to 12 passenger lift of all types	1Floor	3884
	MAT-08704	3	For 13 to 17 passenger/stretchers/goods lift of all types	1Floor	4002
	MAT-08705	4	For 18 to 23 passenger/stretchers/goods lift of all types	1Floor	4237
	MAT-08706	5	For 23 to 26 passenger/stretchers/goods lift of all types	1Floor	4590
	MAT-08707	6	For 27 to 36 passenger/stretchers/goods lift of all types	1Floor	4826

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
	MAT-08708	7	For 3000 to 5000Kg goods lift of all types	1Floor	5297
		B	If there are additional set of lift car door and landing door, add		
			as given below		
	MAT-08709	1	For 4 to 7 passenger lift of all types	1Set	2119
	MAT-08710	2	For 8 to 12 passenger lift of all types	1Set	2354
	MAT-08711	3	For 13 to 17 passenger/stretchers/goods lift of all types	1Set	2472
	MAT-08712	4	For 18 to 23 passenger/stretchers/goods lift of all types	1Set	2825
	MAT-08713	5	For 23 to 26 passenger/stretchers/goods lift of all types	1Set	2472
	MAT-08714	6	For 27 to 36 passenger/stretchers/goods lift of all types	1Set	2943
	MAT-08715	7	For 3000 to 5000Kg goods lift of all types	1Set	3531

			MEDICAL GAS PIPELINE SYSTEM		
1092		ELEC-14.1.1	Supply and Fixing of 2 x 20 Oxygen Main Manifold with 19 mm O.D x12 mm ID Copper Pipe mounted on Top Frame, Middle Frame and Bottom Frame, along with brass blocks, NRVs/Cylinder Valves and Pigtail Pipes of 1 mtr long of size 8 mm O.D x 3 mm I.D, duly tested at 250 Kg/Cm ² pressure, with Automatic Control Panel including cost and conveyance of all material, taxes, transportation charges and labour charges erection and	Set	258750

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			commissioning charges etc.complete for finished item of work Makes: As per list of recommended brands.		
1093		ELEC-14.1.2	Supply and Fixing of 2 x 4 Oxygen Emergency Manifold with 19 mm O.D x12 mm ID Copper Pipe mounted on Top Frame, Middle Frame and Bottom Frame, along with brass blocks, NRVs/Cylinder Valves and Pigtail Pipes of 1 mtr long of size 8 mm O.D x 3 mm I.D,duly tested at 250 Kg/Cm2 pressure and manifold fixed with High Pressure Valve System fixed on the Manifold both the Sides. Makes: As per list of recommended brands.	Set	85000
1094		ELEC-14.1.3	Supply and Fixing of 2 x 4 Main Nitrous Oxide Manifold with 19 mm O.D x12 mm ID Copper Pipe mounted on Top Frame, Middle Frame and Bottom Frame, along with brass blocks, NRVs/Cylinder Valves and Pigtail Pipes of 1 mtr long of size 8 mm O.D x 3 mm I.D,duly tested at 250 Kg/Cm2 pressure. & Semi Automatic Control Panel for Nitrous Oxide. Makes: As per list of recommended brands.	Set	85000
1095		ELEC-14.1.4	Supply and Fixing of 2 x 2 Nitrous Oxide Emergency Manifold with Heavy Duty with 19 mm O.D x12 mm ID Copper Pipe mounted on Top Frame, Middle Frame and Bottom Frame, along with brass blocks, NRVs/Cylinder Valves and Pigtail Pipes of 1 mtr long of size 8 mm O.D x 3 mm I.D,duly tested at 250 Kg/Cm2 pressure with Regulator kit and 1 no. service point, including cost and conveyance of all materials, taxes, transportation charges and labour charges erection and commissioning charges etc. complete for finished item of work.Makes: As per list of recommended brands.	Set	27600
1096		ELEC-14.1.5	Supply and Fixing of 15 V x 10 Model Ingersoll Rand model Twin Vacuum pump system with 2000 Ltrs Capacity Vacuum Receiver, 10 HP Motors, Starters, Filters, Vacuum Switches and other standard accessories, Twin System. Makes: As per list of recommended brands.	Set	1055700
1097		ELEC-14.1.6	Supply and Fixing of Aneste Iwata Make TFS 150 C9 Model, Compresso Two stage, Motor 15 HP & 57.18 CFM, 60 CFM Air Dryer with2000 Ltrs	Set	1140000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Receiver Twin System. Makes: As per list of recommended brands.		
1098		ELEC-14.1.7	Supply and fixing of mm thick copper pipe thick for distribution, pipes shall be half drawn, tempered, seamless, phosphorous deoxidized, non arsenic and decreased confirming to BS 2871-1971 Part-1 (Table-X) and the chemical compositions shall be as per BS 6017 of 1981 table-2 with Lloyd Test Certification, including cost and conveyance of pipes, cost of necessary specials made of copper and suitable for a steam working pressure of 17 bar and should confirm to BS 864 with specially made for brazed socket type connections, including taxes, transportation charges including laying and jointing, testing, commissioning and all other labour charges etc. complete for finished item of work. Makes: As per list of recommended brands.		
		a	12mm O.D x 0.7 mm	Rmt	348
		b	15mm O.D x0.9mm	Rmt	555
		c	22mm O.D x0.9mm	Rmt	764
		d	28mm O.D x0.9mm	Rmt	917
		e	42mm O.Dx1.2mm	Rmt	2234
		f	54mm O.Dx1.5mm	Rmt	3273
1099		ELEC-14.1.8	Supply and fixing of..... Isolation Valves with necessary brass end fittings designed for a working pressure of 300 psi / 27 inc. Hg. Vacuum, Non Ferrous, Non Lubricated with 90 degrees turn, Hand lever operated of standard make of valves including cost and conveyance of all materials, taxes, transportation charges, fixing charges and testing charges and all labour charges etc. complete for finished item of work. Makes: As per list of recommended brands.		
		a	15 mm Valves (1/2")	Each	1150
		b	22 mm Valves (3/4")	Each	633
		c	28 mm Valves (1")	Each	759
		d	42 mm Valves (1")	Each	2128
		e	54 mm Valves (2")	Each	3117
1100		ELEC-14.1.9	Deleted	Each	Deleted
1101		ELEC-	Supply and fixing of consisting of all necessary accessories ie		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
		14.1.10	pressure sensors, regulators, pressure SWGs etc. complete including cost and conveyance of all materials, taxes, transportation charges etc. complete for finished item of work. Makes: As per list of recommended brands.		
		a	3 Gas Digital Alarm Panel	Each	28000
		b	4 Gas Digital Alarm Panel	Each	28750
1102		ELEC-14.1.11	Supply and Fixing of Oxygen Flow meters with Humidifier Bottles. Makes: As per list of recommended brands	Each	1400
1103		ELEC-14.1.12	Supply and Fixing of Ward Vacuum Units with 600 ml Jar. Makes: As per list of recommended brands.	Each	1725
1104		ELEC-14.1.13	Deleted	Each	Deleted
1105		ELEC-14.1.14	Deleted	Each	Deleted
1106		ELEC-14.1.15	Deleted	Each	Deleted
1107		ELEC-14.1.16	Deleted	Each	Deleted
1108		ELEC-14.1.17	Deleted	Each	Deleted
1109		ELEC-14.1.18	Supply and Fixing of Vacuum Tube. Makes: As per list of recommended brands.	Rmt	45
1110		ELEC-14.1.19	Supply and Fixing of HP (High pressure) Tube. Makes: As per list of recommended brands.	Rmt	52
1111		ELEC-14.1.20	Deleted	Each	Deleted
1112		ELEC-14.1.21	Deleted	Each	Deleted
			STP & ETP WORKS (ELECTRO-MECHANICAL ITEMS)		
1113		ELEC-14.2.1	Supply and fixing, testing and commissioning of Manual Coarse Bar Screen Size: To Suit 400mm Wide x 200mm Liquid Height Clear Opening of Screen: 25mm Size of Flat: 50mm	Each	36000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			x 6mm Angle of Inclination: 60 Degree Shape of Screen: Curved Top Accessories: Rake & 2 Nos. Side Plate MOC: SS 304 including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1114		ELEC-14.2.2	Supply and fixing, testing and commissioning of Manual Coarse Bar Screen Size: To Suit 600mm Wide x 200mm Liquid Height Clear Opening of Screen: 25mm Size of Flat: 50mm x 6mm Angle of Inclination: 60 Degree Shape of Screen: Curved Top Accessories: Rake & 2 Nos. Side Plate MOC: SS 304 including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	40000
1115		ELEC-14.2.3	Supply and fixing, testing and commissioning of Manual Fine Bar Screen Size: To Suit 300mm Wide x 200mm Liquid Height Clear Opening of Screen: 10mm Size of Flat: 50mm x 6mm Angle of Inclination: 45 Degree Shape of Screen: Curved Top Accessories: Rake MOC: SS 304 including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	44000
1116		ELEC-14.2.4	Supply and fixing, testing and commissioning of Manual Fine Bar Screen Size: To Suit 500mm Wide x 200mm Liquid Height Clear Opening of Screen: 10mm Size of Flat: 50mm x 6mm Angle of Inclination: 45 Degree Shape of Screen: Curved Top Accessories: Rake	Each	40000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			MOC: SS 304 including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1117		ELEC-14.2.5	Supply and fixing, testing and commissioning of Mechanical Fine Bar Screen Size: To Suit 500mm Wide x 200mm Liquid Height (700mm Total Height) Clear Opening of Screen: 6mm Size of Flat: 50mm x 3mm Angle of Inclination: 75 Degree Type of Screen: Fixed Bar, Mechanically Raked Screen Accessories: Discharge Chute MOC of All Wetted Parts : SS 304 including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	130000
1118		ELEC-14.2.6	Supply and fixing, testing and commissioning of Slotted Pipe Oil Skimmer Size: To Suit 750mm Wide Oil & Grease Trap Size of Slotted Pipe: 200mm Dia Type of Operation: Manual Hand Wheel MOC of All Wetted Parts : SS 304 including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	85000
1119		ELEC-14.2.7	Supply and fixing, testing and commissioning of Slotted Pipe Oil Skimmer Size: To Suit 750mm Wide Oil & Grease Trap Size of Slotted Pipe: 200mm Dia Type of Operation: Manual Hand Wheel MOC of All Wetted Parts : SS 304 including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	85000
1120		ELEC-14.2.8	Supply and fixing, testing and commissioning of Slotted Pipe Oil Skimmer	Each	130000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Size: To Suit 2000mm Wide Oil & Grease Trap Size of Slotted Pipe: 200mm Dia Type of Operation: Manual Hand Wheel MOC of All Wetted Parts : SS 304 including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1121		ELEC-14.2.9	Supply and fixing, testing and commissioning of Equalisation Tank Blower Capacity of Blower: 50m ³ /Hr @ 5.5 MWC Type of Blower: Twin Lobe MOC of Blower: CI Speed of Blower : Less than 1000 RPM Speed of Blower Motor: 1440 RPM The Blower shall be complete with Blower & Motor mounted on a common base frame, belt drive, belt guard, Suction & Discharge Silencer, Air Filter, Safety Valve, NRV, etc., complete. including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	75000
1122		ELEC-14.2.10	Supply and fixing, testing and commissioning of Equalisation Tank Blower Capacity of Blower: 180m ³ /Hr @ 5.5 MWC Type of Blower: Twin Lobe MOC of Blower: CI Speed of Blower : Less than 1000 RPM Speed of Blower Motor: 1440 RPM The Blower shall be complete with Blower & Motor mounted on a common base frame, belt drive, belt guard, Suction & Discharge Silencer, Air Filter, Safety Valve, NRV, etc., complete. including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	170000
1123		ELEC-14.2.11	PH METER :- supply and Fixing of PH meter PO 650 ph/ orp with push button type for physical dimensions 105x105x130mm cut out size 92x92mm enclosure ABS weather proof IP-65 calibration /set point ,Sensor dimension 140mmx32mm ,Flow throw	Each	19000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			. It including cost and conveyance , all taxes specification Provided at the outlet of Sewerage treated water sump it including all taxes as directed by Engineer-in-charge . Makes: As per list of recommended brands.		
1124		ELEC-14.2.12	Supply and fixing, testing and commissioning of Coarse Bubble Diffusers Type: Disc Diffuser Size: 80mm Dia MOC: EPDM including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	750
1125		ELEC-14.2.13	Supply and fixing, testing and commissioning of Fine Bubble Diffusers Type: Tubular Size: 1.0m Long x 90 Dia MOC: EPDM including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	2000
1126		ELEC-14.2.14	Supply and fixing, testing and commissioning of Equivalisation Effluent/ Sewage Pump Capacity of Pump: 4.00 Cu.m/Hr @ 6m Head Type of Pump: Non Clog Vertical Submersible Solid Handling Size: 10mm Impeller Type: Non Clog MOC of Casing: CI MOC of Impeller: CI Accessories: Auto Coupling, SS304 Lifting Chain, SS Guide Pipe, Control Panel with Level Switches for auto Start & Stop including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	57000
1127		ELEC-14.2.15	Supply and fixing, testing and commissioning of Equalisation Effluent/Sewage Pump Capacity of Pump: 15 Cu.m/Hr @ 6m Head Type of Pump: Non Clog Vertical Submersible	Each	70132

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Solid Handling Size: 80mm Impeller Type: Non Clog MOC of Casing: CI MOC of Impeller: CI Accessories: Auto Coupling, SS304 Lifting Chain, SS Guide Pipe, Control Panel with Level Switches for auto Start & Stop including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1128		ELEC-14.2.16	Supply and fixing, testing and commissioning of Equalisation Effluent/ Sewage Pump Capacity of Pump: 25 Cu.m/Hr @ 6m Head Type of Pump: Non Clog Vertical Submersible Solid Handling Size: 80mm Impeller Type: Non Clog MOC of Casing: CI MOC of Impeller: CI Accessories: Auto Coupling, SS304 Lifting Chain, SS Guide Pipe, Control Panel with Level Switches for auto Start & Stop including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	85000
1129		ELEC-14.2.17	Supply and fixing, testing and commissioning of Equalisation Effluent/ Sewage Pump Capacity of Pump: 32.5 Cu.m/Hr @ 6m Head Type of Pump: Non Clog Vertical Submersible Solid Handling Size: 40mm Impeller Type: Non Clog MOC of Casing: CI MOC of Impeller: CI Accessories: Auto Coupling, SS304 Lifting Chain, SS Guide Pipe, Control Panel with Level Switches for auto Start & Stop including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	100000
1130		ELEC-14.2.18	Supply and fixing, testing and commissioning of Mixer for Anoxic Tank	Nos	75000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Type: Turbine Type RPM of Mixer: 50 MOC of Shaft & Blades: SS 304 Motor KW: 1.1 including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1131		ELEC-14.2.19	Supply and fixing, testing and commissioning of Mixer for Anoxic Tank Size: To Suit 2.275 x 2.0 x 4.5m LD (5.0m TD) Type: Turbine Type RPM of Mixer: 100 MOC of Shaft & Blades: SS 304 Motor KW: 1.1 including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	95000
1132		ELEC-14.2.20	Supply and fixing, testing and commissioning of Aeration Blower Capacity of Blower: 120Nm3/Hr @ 5.5 MWC Type of Blower: Twin Lobe MOC of Blower: CI Speed of Blower : Less than 1000 RPM Speed of Blower Motor: 1440 RPM The Blower shall be complete with Blower & Motor mounted on a common base frame, belt drive, belt guard, Suction & Discharge Silencer, Air Filter, Safety Valve, NRV, etc., complete. including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	160000
1133		ELEC-14.2.21	Supply and fixing, testing and commissioning of Aeration Blower Capacity of Blower: 504Nm3/Hr @ 5.5 MWC Type of Blower: Twin Lobe MOC of Blower: CI Speed of Blower : Less than 1000 RPM Speed of Blower Motor: 1440 RPM The Blower shall be complete with Blower & Motor mounted on a common base frame, belt drive, belt	Each	285000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			guard, Suction & Discharge Silencer, Air Filter, Safety Valve, NRV, etc., complete. including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1134		ELEC-14.2.22	Supply and fixing, testing and commissioning of Air Piping from Blower upto Diffusers for Equalisation Tank Blower & Aeration Blower MOC of Exposed Pipes: SS 304 MOC of Vertical Drops: SS 304 MOC of Under Water pipes: SS 304 MOC of Guide Pipe & Lifting Chain: SS 304 The Air Piping shall be complete with Individual blower delivery piping with NRV, Diaphragm Valve, Main Header Piping from the Blower delivery up to equ tank/aeration tank including drop/vertical piping, header along the tank, vertical drop pipes with control valve & dismantling type joint, diffuser header pipe & laterals with nozzles for diffuser, end cap, vertical guide pipe at the other end of diffuser header, lifting chain, etc., complete. The design of piping shall be such that it should be possible to remove diffusers from the tanks without emptying tank & shutting off the system. The arrangement shall be that the we should be able to take out the Vertical drop pipe & the diffuser header just by dismantling the joint in the vertical drop pipe and should be able to refix the same in position. Pipe Sizes: As per Diffuser Manufacturer recommendations. The Contractor has to provide detailed air piping calc for the air pipes from the diffuser supplier to match the specified blower. Battery Limit: Form Flange of Blowers till diffuser The Piping cost is inclusive all necessary materials required for the piping like pipes, fittings, adopters, flanges, fasteners, pipe supports, clamps, valves, labour charges for fabrication, erection, pressure testing, etc., complete. including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	ONE KG	450

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
1135		ELEC-14.2.23	Supply and fixing, testing and commissioning of Air Piping from Blower upto Diffusers for Equalisation Tank Blower & Aeration Blower MOC of Exposed Pipes: SS 304 MOC of Vertical Drops: SS 304 MOC of Under Water pipes: SS 304 MOC of Guide Pipe & Lifting Chain: SS 304 The Air Piping shall be complete with Individual blower delivery piping with NRV, Diaphragm Valve, Main Header Piping from the Blower delivery up to equ tank/aeration tank including drop/vertical piping, header along the tank, vertical drop pipes with control valve & dismantling type joint, diffuser header pipe & laterals with nozzles for diffuser, end cap, vertical guide pipe at the other end of diffuser header, lifting chain, etc., complete. The design of piping shall be such that it should be possible to remove diffusers from the tanks without emptying tank & shutting off the system. The arrangement shall be that the we should be able to take out the Vertical drop pipe & the diffuser header just by dismantling the joint in the vertical drop pipe and should be able to refix the same in position. Pipe Sizes: As per Diffuser Manufacturer recommendations. The Contractor has to provide detailed air piping calc for the air pipes from the diffuser supplier to match the specified blower. Battery Limit: Form Flange of Blowers till diffuser The Piping cost is inclusive all necessary materials required for the piping like pipes, fittings, adopters, flanges, fasteners, pipe supports, clamps, valves, labour charges for fabrication, erection, pressure testing, etc., complete. including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	ONE KG	340
1136		ELEC-14.2.24	Supply, Transportation and fixing, testing and commissioning of Media for MBBR (Moving Bed Bio-Reactor) Tank Volume of Media: Cu.m Shape of Media: Conical Frustum Surface Area:300-400 m2/m3 of media	CUM	8352

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Structure: Cylindrical with Fins Sp Gravity: 0.9 to 0.95 MOC: P P UV Stabilised No.of Pieces 50,000-70000 No/Cu.Mt Weight per Cum 95 to 100 Kgs including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1137		ELEC-14.2.25	Supply and fixing, testing and commissioning of Internal Recirculation Pump Capacity of Pump: 1 Cu.m/Hr @ 5m Head Type of Pump: Non Clog Vertical Submersible Solid Handling Size: 10mm Impeller Type: Non Clog MOC of Casing: CI MOC of Impeller: CI Accessories: Auto Coupling, SS304 Lifting Chain, SS Guide Pipe, Control Panel with Level Switches for auto Start & Stop including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Final payment after Lab Testing treated water satisfying the following parameters BOD less than 20, COD less than 50. Makes: As per list of recommended brands.	Nos	57000
1138		ELEC-14.2.26	Supply and fixing, testing and commissioning of Internal Recirculation Pump Capacity of Pump: 15 Cu.m/Hr @ 3m Head Type of Pump: Non Clog Vertical Submersible Solid Handling Size: 80mm Impeller Type: Non Clog MOC of Casing: CI MOC of Impeller: CI Accessories: Auto Coupling, SS304 Lifting Chain, SS Guide Pipe, Control Panel with Level Switches for auto Start & Stop including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Final payment after Lab Testing treated water	Each	74750

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			satisfying the following parameters BOD less than 5, COD less than 10. Makes: As per list of recommended brands.		
1139		ELEC-14.2.27	Supply and fixing, testing and commissioning of Internal Recirculation Pump Capacity of Pump: 50.00 Cu.m/Hr @ 3m Head Type of Pump: Non Clog Vertical Submersible Solid Handling Size: 80mm Impeller Type: Non Clog MOC of Casing: CI MOC of Impeller: CI Accessories: Auto Coupling, SS304 Lifting Chain, SS Guide Pipe, Control Panel with Level Switches for auto Start & Stop including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Final payment after Lab Testing treated water satisfying the following parameters BOD less than 5, COD less than 10. Makes: As per list of recommended brands.	Each	90000
1140		ELEC-14.2.28	Supply and fixing, testing and commissioning of Internal Recirculation Pump Capacity of Pump: 62.5 Cu.m/Hr @ 3m Head Type of Pump: Non Clog Vertical Submersible Solid Handling Size: 80mm Impeller Type: Non Clog MOC of Casing: CI MOC of Impeller: CI Accessories: Auto Coupling, SS304 Lifting Chain, SS Guide Pipe, Control Panel with Level Switches for auto Start & Stop including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Final payment after Lab Testing treated water satisfying the following parameters BOD less than 5, COD less than 10. Makes: As per list of recommended brands.	Each	95000
1141		ELEC-14.2.29	Supply and fixing, testing and commissioning of Secondary Clarifier To Suit: 3.0 m x 3.0 m x2.50m SWD (0.5m FB) Sq	Each	225000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Clarifier. Floor Slope: 1 in 12 Free Board: 0.5m The Clarifier shall be to suit the Civil Tank (As per the attached GA Drg). The Launder top will be finished to true level to ensure uniform overflow to avoid overflow weirs. The clarifier shall be complete with Mechanical Bridge/Platform spanning across the tank with GI Grating & Handrails for the entire length, Feed Well, Central Drive mechanism, Centre shaft, scrapper arm with neoprene squeezes, sludge pit cone scrapper, etc., complete. MOC: MSEP + GI Gratings + GI Handrails including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1142		ELEC-14.2.30	Supply and fixing, testing and commissioning of Secondary Clarifier To Suit: 5.0 m x 5.0 m x 3.50m SWD (0.5m FB) Sq Clarifier. Floor Slope: 1 in 12 Free Board: 0.5m The Clarifier shall be to suit the Civil Tank (As per the attached GA Drg). The Launder top will be finished to true level to ensure uniform overflow to avoid overflow weirs. The clarifier shall be complete with Mechanical Bridge/Platform spanning across the tank with GI Grating & Handrails for the entire length, Feed Well, Central Drive mechanism, Centre shaft, scrapper arm with neoprene squeezes, sludge pit cone scrapper, etc., complete. MOC: MSEP + GI Gratings + GI Handrails including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	350000
1143		ELEC-14.2.31	Supply and fixing, testing and commissioning of Secondary Clarifier To Suit: 9.1m x 9.1m x 3.0m SWD (0.5m FB) Sq Clarifier. Floor Slope: 1 in 12 Free Board: 0.5m	Each	400000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			The Clarifier shall be to suit the Civil Tank (As per the attached GA Drg). The Launder top will be finished to true level to ensure uniform overflow to avoid overflow weirs. Mechanical Bridge/Platform spanning across the tank with GI Grating & Handrails for the entire length, Feed Well, Central Drive mechanism, Centre shaft, scrapper arm with neoprene squeezes, sludge pit cone scrapper, etc., complete. MOC: MSEP + GI Gratings + GI Handrails including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1144		ELEC - 14.2.32	Supply and fixing, testing and commissioning of Sludge Pump Capacity of Pump : 1 Cu.m/Hr @ 5m Head Type of Pump: Horizontal Centrifugal Impeller Type: Non Clog MOC of Impeller: CI including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item. Makes: As per list of recommended brands.	Nos	35000
1145		ELEC- 14.2.33	Supply and fixing, testing and commissioning of Sludge Pump Capacity of Pump: 25 Cu.m/Hr @ 3m Head Type of Pump: Horizontal Centrifugal Impeller Type: Non Clog MOC of Casing: CI MOC of Impeller: CI including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	72240
1146		ELEC- 14.2.34	Supply and fixing, testing and commissioning of Sludge Pump Capacity of Pump: 32 Cu.m/Hr @ 3m Head Type of Pump: Horizontal Centrifugal Impeller Type: Non Clog MOC of Casing: CI MOC of Impeller: CI including all incidental and operational charges etc,	Each	100000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1147		ELEC-14.2.35	Supply and fixing, testing and commissioning of UV Disinfection System Flow: 25 Cu.m/Hr. Type of Flow: Gravity Type: UV Lamp covered with Quartz Glass MOC of Enclosure: SS 304 Accessories: Control Panel including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	215000
1148		ELEC-14.2.36	Supply and fixing, testing and commissioning of UV Disinfection System Flow: 32 Cu.m/Hr. Type of Flow: Gravity Type: UV Lamp covered with Quartz Glass MOC of Enclosure: SS 304 Accessories: Control Panel including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	235000
1149		ELEC - 14.2.37	Supply and fixing, testing and commissioning of Filter Feed Pump Capacity of Pump: 5 Cu.m/Hr @ 20m Head Type of Pump: Horizontal Centrifugal Impeller Type: Closed MOC of Casing: CI MOC of Impeller: CI including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Nos.	34500
1150		ELEC-14.2.38	Supply and fixing, testing and commissioning of Filter Feed Pump Capacity of Pump: 25 Cu.m/Hr @ 30m Head Type of Pump: Horizontal Centrifugal Impeller Type: Semi Open MOC of Casing: CI MOC of Impeller: CI	Each	94000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1151		ELEC-14.2.39	Supply and fixing, testing and commissioning of Filter Feed Pump Capacity of Pump: 33.5 Cu.m/Hr @ 30m Head Type of Pump: Horizontal Centrifugal Impeller Type: Semi Open MOC of Casing: CI MOC of Impeller: CI including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	118000
1152		ELEC-14.2.40	Supply and fixing, testing and commissioning of Pressure Sand Filter Capacity of Filter: 7.50 Cu.m/Hr. Minimum Dia of Filter: 0.90m Minimum HOS of Filter: 1.8m Minimum Height of Filter Sand: 0.30m Minimum Plate Thickness for Shell & Dish: 6mm Type of Underdrain: Nozzle Plate with Plastic Nozzles Type of Inlet: Inlet Distribution Box/ Bell Mouth. Specification for Filter Media: As per CPHEEO Manual Accessories: Frontal Piping & Valves. including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	115000
1153		ELEC-14.2.41	Supply and fixing, testing and commissioning of Pressure Sand Filter Capacity of Filter: 32.50 Cu.m/Hr. Minimum Dia of Filter: 1.8m Minimum HOS of Filter: 1.5m Minimum Height of Filter Sand: 0.75m Minimum Plate Thickness for Shell & Dish: 6mm Type of Underdrain: Nozzle Plate with Plastic Nozzles Type of Inlet: Inlet Distribution Box/ Bell Mouth. Specification for Filter Media: As per CPHEEO	Each	207000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Manual MOC of Filter: MSEP Accessories: Frontal Piping & Valves. including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1154		ELEC-14.2.42	Supply and fixing, testing and commissioning of Activated Carbon Filter Capacity of Filter: 7.50 Cu.m/Hr. Minimum Dia of Filter: 0.70m Minimum HOS of Filter: 1.8m Minimum Height of Activated Carbon: 0.30m Minimum Plate Thickness for Shell & Dish: 6mm Type of Underdrain: Nozzle Plate with Plastic Nozzles Type of Inlet: Inlet Distribution Box. Type of Activated Carbon: Coal Based/Coconut shell Minimum Iodine Value for Activated Carbon: 1000 MOC of Filter: MSEP Accessories: Frontal Piping & Valves. including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	160000
1155		ELEC-14.2.43	Supply and fixing, testing and commissioning of Activated Carbon Filter Capacity of Filter: 32.50 Cu.m/Hr. Minimum Dia of Filter: 1.90m Minimum HOS of Filter: 1.5m Minimum Height of Activated Carbon: 0.75m Minimum Plate Thickness for Shell & Dish: 6mm Type of Underdrain: Nozzle Plate with Plastic Nozzles Type of Inlet: Inlet Distribution Box. Type of Activated Carbon: Coal Based/Coconut shell Minimum Iodine Value for Activated Carbon: 1000 MOC of Filter: MSEP Accessories: Frontal Piping & Valves. including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	265000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
1156		ELEC-14.2.44	Supply and fixing, testing and commissioning of Hypochlorite solution dosing System Dosing System shall be complete with 1 No. - 100 Lit Capacity HDPE Tank with Inlet & Outlet Connections, Level Indicator Dosing Pump, 0 - 5 LPH Capacity, 2 Nos. Complete Flexible Tubing with Valves, NRV's, Strainers, etc., from Dosing Tank to dosing Point including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	System	40000
1157		ELEC-14.2.45	Supply and fixing, testing and commissioning of FeCl3 solution dosing System Dosing System shall be complete with 1 No. - 50 Lit Capacity HDPE Tank with Inlet & Outlet Connections, Level Indicator 1 No. - Agitator to suit 50 Lit HDPE tank of SS 304 MOC, 100 RPM speed. Dosing Pump, 0 - 6 LPH Capacity, 2 Nos. Complete Flexible Tubing with Valves, NRV's, Strainers, etc., from Dosing Tank to dosing Point including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	System	28750
1158		ELEC - 14.2.46	Supply and fixing, testing and commissioning of Treated Water Pump Capacity of Pump: 5 Cu.m/Hr @ 20m Head Type of Pump: Horizontal Centrifugal Impeller Type: Closed MOC of Casing: CI MOC of Impeller: CI including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Nos	39000
1159		ELEC-14.2.47	Supply and fixing, testing and commissioning of Treated Water Pump Capacity of Pump: 15 Cu.m/Hr @ 20m Head Type of Pump: Horizontal Centrifugal Impeller Type: Semi Open MOC of Casing: CI MOC of Impeller: CI including all incidental and operational charges etc, as per approved drawings and as directed by	Each	75000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1160		ELEC-14.2.48	Supply and fixing, testing and commissioning of Treated Water Pump Capacity of Pump: 32 Cu.m/Hr @ 30m Head Type of Pump: Horizontal Centrifugal Impeller Type: Semi Open MOC of Casing: CI MOC of Impeller: CI including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	80000
1161		ELEC-14.2.49	Supply and fixing, testing and commissioning of Filter Press Feed Pump Capacity of Pump: 1 Cu.m/Hr @ 20m Head Type of Pump: Screw Pump Impeller Type: Screw MOC of Casing: CI MOC of stator : Nitrile MOC of rotor : SS 304 including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	52000
1162		ELEC-14.2.50	Supply and fixing, testing and commissioning of Manual Plate Filter Press Size of Plate: 610 x 610mm No. of Chambers: 8 Chamber Operation: Hydraulic Pump Capacity: For Dewatering of 2 Cu.m/Day, 3% Sludge in 10Hour including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	132000
1163		ELEC-14.2.51	Supply and fixing, testing and commissioning of Manual Plate Filter Press Size of Plate: 610 x 610mm No. of Chambers: 16 Chamber Operation: Hydraulic Pump Capacity: For Dewatering of 5 Cu.m/Day, 3% Sludge	Each	250000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			in 12 Hour including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1164		ELEC-14.2.52	Supply and fixing, testing and commissioning of Dewatering PE solution dosing System Dosing System shall be complete with 2 Nos. - 50 Lit Capacity HDPE Tank with Inlet & Outlet Connections, Level Indicator. 2 Nos. - Agitator to suit 100 Lit HDPE tank of SS 304 MOC, 100 RPM speed. Complete Flexible Tubing with Valves, NRV's, Strainers, etc., from Dosing Tank to dosing Point including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	System	65000
1165		ELEC-14.2.53	Supply and fixing, testing and commissioning of Jib Crane for Lifting of Submersible Pumps Capacity : 0.5 Ton Min Clear Height: 2.50m to the Bottom of the Hook (From Base plate). Degree of Rotation: 360 Degrees. Length of Boom: 2.0m to the Centre of Lifting Hook from the centre of mast. Rotating Operation: Manual Accessories Req'd: 0.5 Ton Capacity Chain Pulley Block with Lifting Chain of 9.0m + Trolley of reputed make. Mast section: Circular Mast of required Height Method of Installation: By Welding to Fish Plate embedded in concrete. including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.	Each	120000
1166		ELEC-14.2.54	Supply and fixing, testing and commissioning of Tube Settler Media for Settling tank Volume of Media: 48 Cu.m Shape of Media: Vertical Plate Structure: Sheet with locking arrangement MOC: PVC	CUM	8500

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			No.of Pieces 150 per Cum (Size 1 Mtr x 0.5) including all incidental and operational charges etc, as per approved drawings and as directed by Engineer-in-charge complete for finished item of work. Makes: As per list of recommended brands.		
1167		ELEC-14.2.55	Supplying, Laying, Testing & Commissioning of Piping from Last Manhole to Coarse Screen Chamber.....complete piping for the MLD E&STP to match the P & ID and to match the layout, using suitable material pipes of approved makes conforming to IS, including pipe specials like bends of suitable degree, elbow, tee, union/flanges, valves, fasteners, Cutting the pipes to requirement, making joints with pipe specials, earth work excavation, laying, refilling as required, or in pipe supports including its foundation, pipe supports, clamping system, etc., Conducting wet run, rectifying the leaks if any in laid pipe work, etc, complete with valves as applicable. Battery Limits: From Head Manhole near the STP-I (Approx. 15m), piping for Treated Water Pump for a length of 100m from the STP boundary. The complete piping within the E&STP area shall be contractor's scope. Makes: As per list of recommended brands.		
		a	100 Dia PVC 10 KSC Pipe	1 RM	650
		b	300 Dia PVC 10 KSC Pipe	1 RM	1050
1168		ELEC-14.2.56	Supplying, Laying, Testing & Commissioning of Delivery Piping with Valves & NRV for Raw Effluent/Sewage Pump up to Inlet Chamber.....complete piping for the MLD E&STP to match the P & ID and to match the layout, using suitable material pipes of approved makes conforming to IS, including pipe specials like bends of suitable degree, elbow, tee, union/flanges, valves, fasteners, Cutting the pipes to requirement, making joints with pipe specials, earth work excavation, laying, refilling as required, or in pipe supports including its foundation, pipe supports, clamping system, etc., Conducting wet run, rectifying the leaks if any in laid pipe work, etc, complete with valves as applicable. Battery Limits: From Head Manhole near the STP-I (Approx. 15m), piping for Treated Water Pump for a length of 100m from the STP boundary. The complete piping within the E&STP area shall be contractor's scope. Makes: As per list of recommended brands.		
		a	80 NB - DI Pipe	1 RM	750
		b	100 NB - DI Pipe	1 RM	900
1169		ELEC-14.2.57	Supplying, Laying, Testing & Commissioning of Delivery Piping with Valves & NRV for Equ Effluent/ Sewage Pump up to Anoxic Tank - 80 NB - uPVC	1 RM	750

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Sch 40 Pipe complete piping for the MLD E&STP to match the P & ID and to match the layout, using suitable material pipes of approved makes conforming to IS, including pipe specials like bends of suitable degree, elbow, tee, union/flanges, valves, fasteners, Cutting the pipes to requirement, making joints with pipe specials, earth work excavation, laying, refilling as required, or in pipe supports including its foundation, pipe supports, clamping system, etc., Conducting wet run, rectifying the leaks if any in laid pipe work, etc, complete with valves as applicable. Battery Limits: From Head Manhole near the STP-I (Approx. 15m), piping for Treated Water Pump for a length of 100m from the STP boundary. The complete piping within the E&STP area shall be contractor's scope. Makes: As per list of recommended brands.		
1170		ELEC-14.2.58	Supplying, Laying, Testing & Commissioning of Delivery Piping with Valves & NRV for Internal Recirculation Pump up to Inlet of Anoxic Tank.....complete piping for the MLD E&STP to match the P & ID and to match the layout, using suitable material pipes of approved makes conforming to IS, including pipe specials like bends of suitable degree, elbow, tee, union/flanges, valves, fasteners, Cutting the pipes to requirement, making joints with pipe specials, earth work excavation, laying, refilling as required, or in pipe supports including its foundation, pipe supports, clamping system, etc., Conducting wet run, rectifying the leaks if any in laid pipe work, etc, complete with valves as applicable. Battery Limits: From Head Manhole near the STP-I (Approx. 15m), piping for Treated Water Pump for a length of 100m from the STP boundary. The complete piping within the E&STP area shall be contractor's scope. Makes: As per list of recommended brands.		
		a	80 NB - uPVC Sch 40 Pipe	1 RM	750
		b	100 NB - uPVC Sch 40 Pipe	1 RM	950
1171		ELEC-14.2.59	Supplying, Laying, Testing & Commissioning of Piping from Sec Clarifier Launder Outlet to Filter Feed Tank through UV disinfection module.....complete piping for the MLD E&STP to match the P & ID and to match the layout, using suitable material pipes of approved makes conforming to IS, including pipe specials like bends of suitable degree, elbow, tee, union/flanges, valves, fasteners, Cutting the pipes to requirement, making joints with pipe specials, earth work excavation, laying, refilling as required, or in pipe supports including its foundation, pipe supports, clamping system, etc., Conducting wet run, rectifying the		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			leaks if any in laid pipe work, etc, complete with valves as applicable. Battery Limits: From Head Manhole near the STP-I (Approx. 15m), piping for Treated Water Pump for a length of 100m from the STP boundary. The complete piping within the E&STP area shall be contractor's scope. Makes: As per list of recommended brands.		
		a	80 NB uPVC Sch 40 Pipe	1 RM	750
		b	125 NB uPVC Sch 40 Pipe	1 RM	1150
1172		ELEC-14.2.60	Supplying, Laying, Testing & Commissioning of Filter Feed Pump Suction (Dual Suction, one from Filter Feed Tank & second from UF Feed Tank) and Delivery Piping with valves, NRV, up to frontal piping of PSF &ACF - 80 NB uPVC Sch 40 Pipe complete piping for the MLD E&STP to match the P & ID and to match the layout, using suitable material pipes of approved makes conforming to IS, including pipe specials like bends of suitable degree, elbow, tee, union/flanges, values, fasteners, Cutting the pipes to requirement, making joints with pipe specials, earth work excavation, laying, refilling as required, or in pipe supports including its foundation, pipe supports, clamping system, etc., Conducting wet run, rectifying the leaks if any in laid pipe work, etc, complete with valves as applicable. Battery Limits: From Head Manhole near the STP-I (Approx. 15m), piping for Treated Water Pump for a length of 100m from the STP boundary. The complete piping within the E&STP area shall be contractor's scope. Makes: As per list of recommended brands.	1 RM	750
1173		ELEC-14.2.61	Supplying, Laying, Testing & Commissioning of Filter Feed Pump Suction (Dual Suction, one from Filter Feed Tank & second from UF Feed Tank) and Delivery Piping with valves, NRV, up to frontal piping of PSF &ACF.....complete piping for the MLD E&STP to match the P & ID and to match the layout, using suitable material pipes of approved makes conforming to IS, including pipe specials like bends of suitable degree, elbow, tee, union/flanges, values, fasteners, Cutting the pipes to requirement, making joints with pipe specials, earth work excavation, laying, refilling as required, or in pipe supports including its foundation, pipe supports, clamping system, etc., Conducting wet run, rectifying the leaks if any in laid pipe work, etc, complete with valves as applicable. Battery Limits: From Head Manhole near the STP-I (Approx. 15m), piping for Treated Water Pump for a length of 100m from the STP boundary. The complete piping within the E&STP area shall be contractor's scope.		

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Makes: As per list of recommended brands.		
		a	65 NB - uPVC Sch 40 Pipe	1 RM	650
		b	80 NB - uPVC Sch 40 Pipe	1 RM	750
1174		ELEC-14.2.62	SITC of DO Meter of approved make with interconnection wiring for auto switching on and off of Blowers, based on the DO Levels of the aeration tank. Makes: As per list of recommended brands.	Each	50000
1175		ELEC-14.2.63	SITC of 50 Dia Electro Magnetic Flow Meter with local & remote indication panel with totaliser, including wiring between instrument & remote indicator, power supply wiring, etc., complete. Makes: As per list of recommended brands.	Each	50000
1175		ELEC-14.2.64	Supply, installation, testing and commissioning of Bourden type, stainless steel dial type pressure gauge with isolation valve and pipe having calibration of 0-16 kg/cm2. Makes: As per list of recommended brands.	Each	700
			BUILDING MANAGEMENT SYSTEMS		
1177		ELEC-14.3.1	Supply, Installation, Testing & Commissioning of BMS server with following latest Intel microprocessor Xeon or higher processor, 2.7 to 3.0Ghz or above clock speed, 16 GB expandable up to 32GB DDR 4 RAM,HDD - 1TB SATA, R/W CD / DVD drive, Flat Monitor - 32" LED, Serial Ports - 2 Nos, USB Ports - 4 Nos, Network Card 10/100/1000MB, Graphics card 1GB, Windows Operating System-Higher version, MS office suite Anti virus, Optical mouse & key board etc.as per detailed technical specifications and approved make including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.	Set	434500
1178		ELEC-14.3.2	Supply, Installation, Testing & Commissioning of BMS Client Workstation with following Latest Intel microprocessor i7 / higher , 2.7 to 3.0Ghz or above clock speed, 8GB expandable up to 32GB DDR 4 RAM, HDD - 1TB SATA ,R/W CD / DVD drive, Flat Monitor - 32" LED, Serial Ports - 2 Nos. USB Ports - 4 Nos with at least 2 NOs USB 3.0 Ports, Network Card 10/100/1000MB - 2 Nosography card	Set	104500

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			1GB,Windows 10 Operating System / Higher, MS office suite Anti virus, Optical mouse & key board etc.as per detailed technical specifications and approved. Makes: As per list of recommended brands.		
1179		ELEC-14.3.3	Supply, Installation, Testing & Commissioning of Building Control System Software - MAIN BMS SERVER SOFTWARE, of the following windows based graphical software for IBMS system with 1No Client for Operator workstation, 1No Client for Engineer workstation. The Software shall have 3D & HD vector dynamic graphics with Autocad import of plan with Zoom In & Zoom Out facility, Native 64 Bit System , BTL,UL,EN Certified System, BACnet Profile B-AWS (Advanced workstation) as per the BTL Listing, dot net platform, Certified OPC DA Server by OPC Foundation, Web-Based Server software shall permit use of Standard Web-Browsers such as Microsoft Internet Explorer, Chrome, Firefox, Netscape Navigator, etc. The Software shall comply to international standards and strive to deliver products that meet security standards such as ISA/IEC 62443, UL2900, ISO/IEC 27001, ISO/IEC62443 and OWASP. Cybersecurity audit trail , 4-eye principle , Seamless integration of certificates within customer IT infrastructure, Microsoft's active directory-based authentication, Use of network infrastructure that supports physical network or VLAN segmentation, Placing the web server in a "demilitarized zone" (DMZ), End-to-end encryption, from client to server, End-to-end encryption between servers, Certificate-based data exchange, Encrypted backups. The software shall have the capability to integrate with BIM Modelling. The software shall be Energy Conservation Calculation Software, Energy Management & Engineering Software and Software license shall be for 100% spare license. The software shall be Server based with all other accessories complete as required including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.	Set	715000
1180		ELEC-14.3.4	DDC for Air Handling Unit -(2 AHU per DDC)- Supply, Installation, Testing & Commissioning of 32	Set	68200

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			Bit Microprocessor true IP Based DDC supporting and I/O's designed as per the IO Summary with all other mounting accessories, The controller shall have inbuilt 2-port Ethernet switch . The controller shall have 16 inputs/outputs inbuilt and can be expandable upto max 40 points by Input/Output Modules, The DDC shall have 300 Mhz processor with 128 MByte SDRAM (DDR3) and 512 MByte NAND Flash. Each DDC should contain 20% spare IO for each type of below mentioned IO's. DDC Internal Cabling shall be BMS vendor scope. For more Details, Please refer IO Summary and as per detailed technical specifications and approved make including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.		
1181		ELEC-14.3.5	DDC for OT - Air Handling Unit - (1 AHU per DDC)- SITC of True IP Based DDC Standalone 32 Bit Intelligent, peer to peer communication, interoperable DDC as per the specification. The compact controller shall have inbuilt 2-port Ethernet switch with WLAN interface. The controller shall have 16 inputs/outputs inbuilt and can be expandable upto max 40 points by Input/Output Modules. The DDC shall have 300 Mhz processor with 128 MByte SDRAM (DDR3) and 512 MByte NAND Flash. The controller shall be freely programmable and have System functions (alarming, scheduling, trending, access protection with individually definable user profiles and categories). It should have Cloud connectivity for remote access and inbuilt port for POT for local interface. Makes: As per list of recommended brands.	Set	62091
1182		ELEC-14.3.6	DDC for Ventilation and Lift Lobby Pressurization Fans- (4 Fans per DDC)- SITC of True IP Based DDC Standalone 32 Bit Intelligent, peer to peer communication, interoperable DDC as per the specification. The compact controller shall have inbuilt 2-port Ethernet switch with WLAN interface. The controller shall have 16 inputs/outputs inbuilt and can be expandable upto max 40 points by Input/Output Modules. The DDC shall have 300 Mhz processor with 128 MByte SDRAM (DDR3) and 512 MByte NAND Flash. The controller shall be freely	Set	60716

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			programmable and have System functions (alarming, scheduling, trending, access protection with individually definable user profiles and categories). It should have Cloud connectivity for remote access and inbuilt port for POT for local interface. Makes: As per list of recommended brands.		
1183		ELEC-14.3.7	DG - SITC of True IP Based DDC Standalone 32 Bit Intelligent, peer to peer communication, interoperable DDC as per the specification. The compact controller shall have inbuilt 2-port Ethernet switch with WLAN interface. The controller shall have 16 inputs/outputs inbuilt and can be expandable upto max 40 points by Input/Output Modules. The DDC shall have 300 Mhz processor with 128 MByte SDRAM (DDR3) and 512 MByte NAND Flash. The controller shall be freely programmable and have System functions (alarming, scheduling, trending, access protection with individually definable user profiles and categories). It should have Cloud connectivity for remote access and inbuilt port for PO. Makes: As per list of recommended brands.	Set	66550
1184		ELEC-14.3.8	DDC for Transformer/HT/LT- Supply, Installation, Testing & Commissioning of 32 Bit Microprocessor true IP Based DDC supporting and I/O's designed as per the IO Summary with all other mounting accessories, The controller shall have inbuilt 2-port Ethernet switch . The controller shall have 16 inputs/outputs inbuilt and can be expandable upto max 40 points by Input/Output Modules, The DDC shall have 300 Mhz processor with 128 MByte SDRAM (DDR3) and 512 MByte NAND Flash. Each DDC should contain 20% spare IO for each type of below mentioned IO's. DDC Internal Cabling shall be BMS vendor scope. For more Details, Please refer IO Summary. As per detailed technical specifications and approved make including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.	Each	198520
1185		ELEC-14.3.9	DDC for Lifts- Supply, Installation, Testing & Commissioning of 32 Bit Microprocessor true IP Based DDC supporting and I/O's designed as per	Each	66550

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			the IO Summary with all other mounting accessories, The controller shall have inbuilt 2-port Ethernet switch . The controller shall have 16 inputs/outputs inbuilt and can be expandable upto max 40 points by Input/Output Modules, The DDC shall have 300 Mhz processor with 128 MByte SDRAM (DDR3) and 512 MByte NAND Flash. Each DDC should contain 20% spare IO for each type of below mentioned IO's. DDC Internal Cabling shall be BMS vendor scope. For more Details, Please refer IO Summary.as per detailed technical specifications and approved make including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.		
1186		ELEC-14.3.10	DDC for Plumbing System & Fire Fighting - Supply, Installation, Testing & Commissioning of 32 Bit Microprocessor true IP Based DDC supporting and I/O's designed as per the IO Summary with all other mounting accessories, The controller shall have inbuilt 2-port Ethernet switch . The controller shall have 16 inputs/outputs inbuilt and can be expandable upto max 40 points by Input/Output Modules, The DDC shall have 300 Mhz processor with 128 MByte SDRAM (DDR3) and 512 MByte NAND Flash. Each DDC should contain 20% spare IO for each type of below mentioned IO's. DDC Internal Cabling shall be BMS vendor scope. For more Details, Please refer IO Summary,. As per detailed technical specifications and approved make including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.	Each	63800
1187		ELEC-14.3.11	Software Integration- SITC of True IP Based BTL & UL Listed for third party integration for AHU VFD's, VRV System, Thermostats, DG/UPS/LT/HT Panel and Fire Alarm Systems. The controller shall have 2-port Ethernet switch and WLAN interface. It should have BTL label (BACnet communications passed the BTL test) and consisting of Dual microprocessor with Storage capacity of 1 GB RAM. It should support Real Time clock upto 7 Days. It should Support of the major communication protocols: BACnet,/IP, BACnet MS/TP, Modbus IP and Modbus RTU upto	Job	275000

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			500 points. Integrator shall be of same make only. Makes: As per list of recommended brands.		
1188		ELEC-14.3.12	Supply, Installation, Testing & Commissioning of Ambient Temperature + RH Sensor with all the mounting accessories included. Temp sensor shall be Pt 1000 RTD type with 4 to 20mA transmitter or thermistor type and RH sensor shall be capacitive type with 4 to 20mA transmitter. The temperature measurement range shall be 0 to 50oC and humidity range shall be 0 to 95% RH as technical specification with all other mounting accessories complete as required including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.	Each	20684
1189		ELEC-14.3.13	Supply, fixing, Testing & Commissioning of Room Type Temperature + Humidity Sensor including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.	Nos	15048
1190		ELEC-14.3.14	Supply, Installation, Testing & Commissioning of Differential Pressure Switch (DPS) with all the mounting accessories included. The maximum pressure limit shall be 0-1000Pa as technical specification with all other mounting accessories complete as required. Field Devices & internal cabling of AHU shall be BMS vendor scope including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.	Each	2696
1191		ELEC-14.3.15	Supply, Installation, Testing & Commissioning of Duct Static Pressure Sensor with all the mounting accessories included. The maximum pr limit shall be 0-500Pa all other mounting accessories complete as required. Field Devices & internal cabling of AHU shall be BMS vendor scope including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.	Each	7534
1192		ELEC-14.3.16	Supply, fixing, Testing & Commissioning of Duct Temperature Sensors including all charges complete etc as directed by Engineer In charge/	Nos	3733

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			departmental authorities. Makes: As per list of recommended brands.		
1193		ELEC-14.3.17	Supply, installation, testing and commissioning of Return air CO2 Sensor including all charges complete etc as directed by Engineer In Charge/ departmental authorities. Makes: As per list of recommended brands.	Each	17365
1194		ELEC-14.3.18	Supply, fixing, Testing & Commissioning of Current Relay including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.	Nos	2255
1195		ELEC-14.3.19	Supply, fixing, Testing & Commissioning of Voltage Transducer including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.	Each	7150
1196		ELEC-14.3.20	Supply, fixing, Testing & Commissioning of Ultrasonic Water Level Sensor (Note: Level should indicate as Litre basis in BMS Screen) for Water tank as technical specification with all other mounting accessories including all charges complete etc as directed by Engineer In Charge/ departmental authorities. Makes: As per list of recommended brands.	Each	21437
1197		ELEC-14.3.21	Supply, fixing, Testing & Commissioning of Flame Proof Diesel Level Sensor for Diesel Day Tank Monitoring. Tank Height 1 Mtr including all charges complete etc as directed by Engineer In charge/ departmental authorities. Makes: As per list of recommended brands.	Each	13594
			ACCESS CONTROL SYSTEMS		
1198		ELEC-14.4.1	Supply and installation of Biometric Thumb reader with Proximity card readers based on RFID technology with Keypad, with Back Plate including all fixing accessories. Rate shall include required accessories, tools and tackles, transportation, material and labour etc., complete as instructed by Engineer In charge. The contractor should follow the safety measures inside the premises. Makes: As per list of recommended brands.	Each	20592

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
1199		ELEC-14.4.2	Supply and installation of Proximity card readers based on RFID technology, along with Back Plate including all fixing accessories. Rate shall include required accessories, tools and tackles, transportation, material and labour etc., complete as instructed by Engineer In charge. The contractor should follow the safety measures inside the premises. Makes: As per list of recommended brands.	Each	11960
1200		ELEC-14.4.3	Supply and installation of Proximity Access Card (16k bit with 2 application areas) with print as per client requirement. Makes: As per list of recommended brands.	Each	291
1201		ELEC-14.4.4	Supply and installation of Exit Push Button (Egress Switch), Rate shall include required accessories, tools and tackles, transportation, material and labour etc., complete as instructed by Engineer In charge. The contractor should follow the safety measures inside the premises. Makes: As per list of recommended brands.	Each	635
1202		ELEC-14.4.5	Supply and installation of Single Leaf 600 Lbs Magnetic Lock with required mounting accessories, Rate shall include required accessories, tools and tackles, transportation, material and labour etc., complete as instructed by Engineer In charge. The contractor should follow the safety measures inside the premises. Makes: As per list of recommended brands.	Each	2964
1203		ELEC-14.4.6	Supply and installation of Double Leaf Magnetic Lock with required mounting accessories, Rate shall include required accessories, tools and tackles, transportation, material and labour etc., complete as instructed by Engineer In charge. The contractor should follow the safety measures inside the premises. Makes: As per list of recommended brands.	Each	5876
1204		ELEC-14.4.7	Supply and installation of UL, CE approved Access Controller - Smart card reader interfaces for 2 door, supports up to 4 smart card reader interfaces, Network connection to the host system and Compact Flash, RS485, RS232 or Ethernet connectivity, 20,000 cardholders	Each	36400

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
			data & up to 100,000 transaction detail storage. Makes: As per list of recommended brands.		
1205		ELEC-14.4.8	Supply and installation of ACCESS DOOR CONTROLLER housing shall be in accordance with UL guidelines and is used for securely mounting and housing the Access Controller, extensions and the power supplies. Makes: As per list of recommended brands.	Each	6760
1206		ELEC-14.4.9	Supply and installation of Power supply with battery charger for ACCESS DOOR CONTROLLER Shall be with Selectable 12 VDC or 24 VDC voltage output Overvoltage protection Regulates battery charging voltage The product is classified in accordance with the following standards: • EN 55022 Class B • EN 55024 • IEC / UL / EN 60950 & CSA (product safety) • CE The Power supply can be mounted on rails and installed in the housing. Makes: As per list of recommended brands.	Each	8528
1207		ELEC-14.4.10	Supply and installation of Door Buzzer, Rate shall include required accessories, tools and tackles, transportation, material and labour etc., complete as instructed by Engineer In charge. The contractor should follow the safety measures inside the premises. Makes: As per list of recommended brands.	Each	676
1208		ELEC-14.4.11	Supply of MS Junction boxes for mounting readers/exit switch/break glass in wall / partitions. Makes: As per list of recommended brands.	Each	350
			NURSE-CALL SYSTEM		
1209		ELEC-14.5.1	Deleted	Each	Deleted

SL. NO.	CFMS CODE (2018-19)	ITEM CODE	DESCRIPTION OF ITEM	Unit	Basic Rate for SOR 2025-26 (Rs.)
1		2	3	4	5
1210		ELEC-14.5.2	Deleted	Each	Deleted
1211		ELEC-14.5.3	Deleted	Each	Deleted
1212		ELEC-14.5.4	Deleted	Each	Deleted
1213		ELEC-14.5.5	Deleted	Each	Deleted
1214		ELEC-14.5.6	Deleted	Each	Deleted
1215		ELEC-14.5.7	Deleted	Each	Deleted
1216		ELEC-14.5.8	Deleted	Each	Deleted
1217		ELEC-14.5.9	Deleted	Each	Deleted
1218		ELEC-14.5.10	Deleted	Each	Deleted
1219		ELEC-14.5.11	Deleted	Each	Deleted
1220		ELEC-14.5.12	Deleted	Each	Deleted

Electrical & Electro Mechanical items

(List of Recommended brands/Manufacturers for guidance of field engineers)

S.No	Item Code	Category	Makes
			SECTION – 1
	1.1		M.S. CONDUIT PIPES
1	ELEC-1.1.1		Makes: NAI / Bharath / GB / AKG/Precision.
	1.2		PVC CONDUIT PIPES
2	ELEC1.2.1/ 1.2.2/1.2.6/1.2.7/1.2.8		Makes: Precision/Universal& Marudhar/VIP/ GoldMedal / Million plast / GM / Sudhakar/Polycab /Anchor/ Polyline/ Orbit /AKG /Beljin /Vasavi /DEC/MODI'S.
3	ELEC-1.2.3		Makes: Precision/VIP / Modi/ GoldMedal / Million plast / GM / Sudhakar / Polyline/Orbit/Anchor/Beljin
4	ELEC-1.2.4 /1.2.5		Make:Precision/ VIP / GoldMedal / Million plast / Sudhakar / Polyline/Anchor/Beljin
5	ELEC-1.2.10		Make: Legrand/ Modi's/ Honeywell
	1.5		COPPER FLEXIBLE CABLES (AS PER IS:694)
6	ELEC-1.5.1	CATEGOR Y- I	Makes: Finolex / RR kabel / Havells/Finecab/ KEI/Polycab/Gloster/Goldmedal/GM/ Fortune Arrt/Anchor/Million/ APAR(Anushakthi) /Sudhakar /Orbit/Batra Henlay
7	ELEC-1.5.2	CATEGOR Y- II	Makes: V-Guard/Bonton / HPL / Tamra/ /Plaza/ Vihan/Ollvin/Laser/Beljin/Rhino/ Standard / Vimal /DEC /Unistar/LS cable/ AKG /Nakoda /Vijaya /South king / Millicab/Salzar/Avocab/Gemscab/AJUSS
8	ELEC-1.5.3	CATEGOR Y- III	Makes: Star / Airson/ Benlo / Rajnigandha/ CRI /Spykaar /Unicab/Fybros/A-Flex /Foursun /Vimcab /Vasura/Vasavi
			SHEATHED FLEXIBLE COPPER CABLES
9	ELEC-1.5.4	CATEGOR Y- I	Makes: Finolex / RR kabel / Havells/ Finecab /KEI/Polycab/ Gloster/ Goldmedal/GM// Fortune Arrt/Anchor /Million/Sudhakar/Orbit/Batra Henlay.
10	ELEC-1.5.5	CATEGOR Y- II	Makes: V-Guard/Bonton/ HPL / Tamra/ /Plaza/ Vihan/Spykaar/ Ollvin /Laser /Beljin /Rhino/ Standard/ Vimal/DEC/Unistar/Fybros/A-Flex//LS cable/ Foursun/Vimcab/Nakoda/Salzar/Vijaya /South king/Millicab/Vasura/Vasavi/AJUSS
11	ELEC-1.5.6		Makes: Finolex / Polycab / Havells / V-Guard / Gold Medal / GM / Million / Vimal /Airson/CRI/ Tamra/ ollvin/Avocab
12	ELEC-1.5.7	CATEGOR Y- I	Makes: Finolex / RR kabel / Havells KEI/Polycab/Gloster/Goldmedal/GM/Million/Sudhakar/Or bit
13	ELEC-1.5.8	CATEGOR Y- II	Makes: V-Guard/Bonton /Finecab/ HPL /Fortune Arrt / Tamra/ Anchor/Plaza/ Vihan /Ollvin /Laser /Beljin/Rhino/

			Standard / Vimal
	1.6		SERVICE MAINS AND FLAT CABLE FOR SUBMERSIBLE MOTORS.
14	ELEC-1.6.1/1.6.2		Makes: Gold Medal / Million / GM / Vimal / Finecab / Nakoda / Plaza/ Payal / Sudhakar/ Rajnigandha/ Airson/Orbit/ollvin/Beljin
15	ELEC-1.6.3	CATEGOR Y- I	Makes: Finolex / RR Kabel/ Polycab / Havells / KEI/ Gloster/ Goldmedal / GM/ Finecab/ Million/ APAR(Anushakthi)/Sudhakar/ Lauritz Knudsen (formerly L&T)
16	ELEC-1.6.4	CATEGOR Y- II	Makes: V-Guard / Vihan/Vimal / CRI/ Lubi /Unicab /Hitech/ Spykaar/ Airson/Ollvin/ Laser/ Beljin /Rhino /Fortune Arrt/Unistar/DEC//LS cable/ A-Flex/ Fybros/ Foursun/Vimcab/Nakoda/Salzar/Vijaya /South king/Millicab/Vasura/Vasavi/AJUSS
	1.7		FLUSH TYPE SWITCHES AND ACCESSORIES
17	ELEC-1.7.1		Makes: GM G Home / Gold Medal Olive / Million Zoom / Great white Omega/Koncept/Vimal opel/ Anchor/Vihan/CPL/ Havells Reo/Elleys
	1.8		MODULAR SWITCHES AND ACCESSORIES
18	ELEC-1.8.1/1.8.3	CATEGOR Y- I	Makes: Legrand (Myrius/Lyncus) / Schneider (Clipsal X/ Livia AB)/ Crabtree (Murano/Athena)/Lauritz Knudsen-englaze (formerly L&T)/ GM-(Four-Five)/ Goldmedal(GIFA)/North-West(Artisa)/Million (M-VEE)/Anchor Roma (PLUS)/Precision(Series 7)/Honeywell(Blenze pro)/Indoasian(Shynora)
19	ELEC-1.8.2/1.8.4	CATEGOR Y- II	Makes: Legrand(Ally)/Crabtree Verona / Lauritz Knudsen (formerly L&T)) / HPL/ Schneider Livia/ GM-(G NINE/ GX) C&S/ Goldmedal (Curve/Air) / North-West(Nowa)/Million Mway / Logus Platina/ Panasonic Vision / Salzer (S90series/Gravitas) / Precision(Series 5)/Koncept (Samrat/ Qura)/ /Polycab(Levana / IndoAsian(Elvira)/ Pointer/ CPL/Kolors/ Vihan/Hosper/ Vimal/DEC(Unicus)/Fybros/Infinity/ Elleys(e-soft)/Orbit(German)
			SECTION - 2
	2.1		PANEL MOUNTING SWITCH DISCONNECTOR FUSE UNITS (SDFU)
20	ELEC-2.1.1	CATEGOR Y- I	Makes: Lauritz Knudsen (Formerly LAURITZ KNUDSEN (FORMERLY L&T))/ Schneider / C&S / ABB / SIEMENS
21	ELEC-2.1.2	CATEGOR Y- II	Makes: Standard / Havells / HPL / Indo Asian / Benlo/Anchor/BCH
	2.2		ON LOAD CHANGEOVER SWITCHES (OPEN EXECUTION)
22	ELEC-2.2.1	CATEGOR Y- I	Makes: Socomec / Lauritz Knudsen (formerly L&T) /HPL / Havells/ C&S/Legrand/ABB
23	ELEC-2.2.2	CATEGOR Y- II	Makes: ABB / GE / Siemens / Indo Asian / Benlo/Standard
	2.3		OFF LOAD CHANGE OVER SWITCHES IN SS ENCLOSURE
24	ELEC-2.3.1	CATEGOR	Makes: HPL / Havells / Standard / Indo Asian /

		Y- I	C&S/Legrand/ABB
25	ELEC-2.3.2	CATEGOR Y- II	Makes: Benlo / Million / GoldMedal /GM/ Vimal
			ON LOAD CHANGE OVER SWITCHES IN SS ENCLOSURE
	ELEC-2.3.3	CATEGOR Y- I	Makes: HPL / Havells / Standard / Indo Asian / C&S/ABB
	ELEC-2.3.4	CATEGOR Y- II	Makes: Benlo / Million / GoldMedal /GM/ Vimal
	2.4		AUTO TRANSFER SWITCH
26	ELEC-2.4.1		Makes: Socomec /Hager /ABB/ HPL/ Lauritz Knudsen (formerly L&T) /Havells
27	ELEC-2.4.2		Makes: Socomec ATysP/ ABB/ Lauritz Knudsen (formerly L&T)
	2.5		REWIRABLE / DOUBLE BREAK SWITCHES IN SS ENCLOSURE
28	ELEC-2.5.1	CATEGOR Y- I	Makes: HPL / Havells / Standard / Indo Asian/Benlo
29	ELEC-2.5.2	CATEGOR Y- I	Makes: HPL / Havells / Standard / Indo Asian /Benlo
30	ELEC-2.5.3	CATEGOR Y- II	Makes:Anchor / GM / Million / Sputnik / Sigma / Gold Medal / Star/Kundan cab/Anchor.
31	ELEC-2.5.4	CATEGOR Y- II	Makes: Anchor / GM / Million / Sputnik / Sigma / Gold Medal / Star/Kundan cab/Anchor.
	2.6		HRC FUSE LINKS (DIN/BOLTED TYPE)
32	ELEC-2.6.1		Makes: Lauritz Knudsen (formerly L&T) / G E / C & S / Standard / HPL / Havells / Siemens / Indo Asian
	2.7		PORCELAIN REWIRABLE FUSE UNITS.
33	ELEC-2.7.1		Makes: C&S/Standard/HPL/ Sputnik / Million / Gold Medal /GM/ Benlo/Anchor
34	ELEC-2.7.2		Makes: C&S/Standard/HPL/ Sputnik / Million / Gold Medal / GM/Benlo/Anchor
	2.8		VOLTAGE SURGE PROTECTORS
35	ELEC-2.8.1		Makes: Legrand / Siemens / G.E / Lauritz Knudsen (formerly L&T) /Hager/Havells
	2.9		PANEL MOUNTING MCCBs
36	ELEC-2.9.1	CATEGOR Y- I	Makes: Lauritz Knudsen (formerly L&T) - D shine / Schneider-CVS/Legrand –(DP X3/DRX)/ Siemens- 3VL / Hager-h3/C&S -Winbreak/HPL-Techno /ABB (Formula DSP)
37	ELEC-2.9.2	CATEGOR Y- II	Makes: GE / ABB / Havells / Standard / Indo Asian/BCH/Eaton
			PANEL MOUNTING ACBs (Microprocessor Based)
38	ELEC-2.9.3	CATEGOR Y- I	Makes: Siemens/ Lauritz Knudsen (formerly L&T) / Schneider /Legrand /C&S /HPL/ABB
39	ELEC-2.9.4	CATEGOR Y- II	Makes: GE / Indo Asian / Havells/BCH/Eaton
			AIR INSULATED BUS DUCT
40	ELEC-2.9.5		Makes: Legrand (Zucchini) / C&S/Advance-Anant
41	ELEC-2.9.6		Makes: Legrand (Zucchini) / C&S/Advance- Anant
42	ELEC-2.9.7		Makes: Legrand (Zucchini) / C&S /Advance-Anant
43	ELEC-2.9.8		Makes: Legrand (Zucchini) / C&S/Advance-Anant

			SANDWITCH BUSDUCT
44	ELEC-2.9.9		Makes: Legrand (Zucchini) / Lauritz Knudsen (formerly L&T) / Schneider/C&S/Advance-Anant
45	ELEC-2.9.10		Makes: Legrand (Zucchini) / Lauritz Knudsen (formerly L&T) / Schiender / C&S /Advance-Anant
46	ELEC-2.9.11		Makes: Legrand (Zucchini) / Lauritz Knudsen (formerly L&T) / Schiender /C&S/Advance-Anant
47	ELEC-2.9.12		Makes: Legrand (Zucchini) / Schiender /C&S/Advance-Anant
48	ELEC-2.9.13		Makes: Legrand (Zucchini) / Lauritz Knudsen (formerly L&T) / Schiender /C&S/Advance- Anant
49	ELEC-2.9.14		Makes: Legrand (Zucchini) / Lauritz Knudsen (formerly L&T) / Schiender /C&S/Advance-Anant
	2.1		MCBs (AS PER IS:60898-1:2002)
50	ELEC-2.10.1	CATEGOR Y- I	Makes: Legrand-DX3 / Schneider-A9/Hager-h3/ Siemens-5SX4/ Havells STADx / Lauritz Knudsen (formerly L&T)-AU/Indo Asian-Opti pro/ HPL (Techno) /Anchor (Uno Plus)/ABB-SB200
51	ELEC-2.10.2	CATEGOR Y- II	Makes: ABB- S200/Standard / Havells-euro II / C&S / Lauritz Knudsen (formerly L&T) -Exora/ GM/Gold Medal/ Salzer /Polycab/Million/Benlo/BCH/Eaton
52	ELEC-2.10.3	CATEGOR Y- III	Makes: Legrand RX3/Milltec/ Sputnik / Vimal /Precision/Amron.
	2.11		ISOLATORS CONFIRMS TO I E C 60947 PART-III
53	ELEC-2.11.1	CATEGOR Y- I	Makes: Legrand-DX3 / Schneider-A9/Hager-h3/ Siemens-5SX4/ Havells STADx/ Lauritz Knudsen (formerly L&T) -AU/Indo Asian-Opti pro/HPL(Techno)/ Anchor (Uno Plus)/ABB-SDB200
54	ELEC-2.11.2	CATEGOR Y- II	Makes: ABB- S200/Standard / Havells-euro II / C&S / Lauritz Knudsen (formerly L&T) -Exora/ GM/Gold Medal/ Salzer /Polycab/ Million/Benlo/BCH/Eaton
55	ELEC-2.11.3	CATEGOR Y- III	Makes: Legrand RX3/ Milltec / Sputnik / Vimal/ Precision/Amron.
	2.12		RCCBs(ELCB/RCD) CONFIRMS TO IEC:61008 AND IS:12640-1
56	ELEC-2.12.1	CATEGOR Y- I	Makes: Legrand-DX3 / Schneider-A9/Hager-h3/ Siemens-5SX4/ Havells STADx/ Lauritz Knudsen (formerly L&T) -AU/Indo Asian-Opti pro/HPL(Techno)/ Anchor (Uno Plus)/ABB-FB200
57	ELEC-2.12.2	CATEGOR Y- II	Makes: ABB- S200/Standard / Havells-euro II / C&S / Lauritz Knudsen (formerly L&T) -Exora/ GM/Gold Medal/Salzer /Polycab/Benlo/BCH/Eaton
			RCBO CONFIRMS TO IEC:61009-1
58	ELEC-2.12.3		Makes: ABB- S200/Standard / Havells-euro II / HPL (Techno) / C&S/ Lauritz Knudsen (formerly L&T) - Exora/ GM /Gold Medal/ Anchor/Salzer /Polycab /Benlo/ABB-DSB-201
	2.13		MCB DISTRIBUTION BOARDS (AS PER IS 8623; IS 13032; IEC 61439-3)
59	ELEC-2.13.1	CATEGOR Y- I	Makes: Legrand(Ekinox 3) / Schneider-A9/Hager - Novello+/ Seimens/Havells STADx/ Lauritz Knudsen (formerly L&T) -Newrange/Indo Asian-Opti Pro/ HPL

			(Techno)/ Anchor (Uno Plus)/ABB-ITUS
60	ELEC-2.13.2	CATEGOR Y- II	Makes: Standard / Havells-euro II / C&S/ Lauritz Knudsen (formerly L&T) /GM /Gold Medal/ Salzer/Polycab/ Million/Benlo/BCH/Eaton
61	ELEC-2.13.3	CATEGOR Y- III	Makes: Milltec / Sputnik / Vimal/Precision/ Amron/.
			TPN DBs
62	ELEC-2.13.4	CATEGOR Y- I	Makes: Legrand (Ekinox 3) / Schneider-A9/Hager - Novello+/ Seimens/Havells STADx/ Lauritz Knudsen (formerly L&T) -Newrange/Indo Asian-Opti Pro/ HPL (Techno)/ Anchor (Uno Plus)/ABB-ITUS
63	ELEC-2.13.5	CATEGOR Y- II	Makes: Standard / Havells-euro II / C&S/ Lauritz Knudsen (formerly L&T) /GM /Gold Medal/ Salzer /Polycab /Million/Benlo/BCH/Eaton.
64	ELEC-2.13.6	CATEGOR Y- III	Makes: Milltec / Vimal /Precision/Amron.
			VTPN DBs
65	ELEC-2.13.7	CATEGOR Y- I	Makes: Legrand(Ekinox 3) / Schneider-A9/Hager - Novello+/ Seimens/Havells STADx/ Lauritz Knudsen (formerly L&T) -Newrange/Indo Asian-Opti Pro/ HPL (Techno)/ Anchor (Uno Plus)/ABB-ITUS
66	ELEC-2.13.8	CATEGOR Y- I	Makes: Legrand(Ekinox 3) / Schneider-A9/Hager - Novello+/ Seimens/Havells STADx/ Lauritz Knudsen (formerly L&T) -Newrange/Indo Asian-Opti Pro/ HPL (Techno)/ Anchor (Uno Plus)/ABB-ITUS.
67	ELEC-2.13.9	CATEGOR Y- I	Makes: Legrand(Ekinox 3) / Schneider-A9/Hager - Novello+/ Seimens/Havells STADx/ Lauritz Knudsen (formerly L&T) -Newrange/Indo Asian-Opti Pro/ HPL (Techno)/ Anchor (Uno Plus)/ABB-ITUS
68	ELEC-2.13.10	CATEGOR Y- II	Makes: Standard / Havells-euro II / C&S / Lauritz Knudsen (formerly L&T) /GM /Gold Medal/Salzer/Benlo/BCH/Eaton
69	ELEC-2.13.11	CATEGOR Y- II	Makes: Siemens / Standard / Havells /Hager/ C&S/ Lauritz Knudsen (formerly L&T) / Benlo/BCH/Eaton.
70	ELEC-2.13.12	CATEGOR Y- II	Makes: Standard / Havells-euro II / C&S / Lauritz Knudsen (formerly L&T) /GM /Gold Medal/Salzer/ Benlo/BCH/Eaton.
71	ELEC-2.13.13	CATEGOR Y- I	Makes: Legrand(Ekinox 3) / Schneider-A9/Hager - Novello+/ Seimens/Crabtree Xpro classique-II/ Lauritz Knudsen (formerly L&T) -Newrange/Indo Asian-Opti Pro/ HPL (Techno)/ Anchor (Uno Plus)/ABB-ITUS
72	ELEC-2.13.14	CATEGOR Y- II	Makes: Standard / Havells-euro II / C&S / Lauritz Knudsen (formerly L&T) /GM /Gold Medal/ Salzer /Polycab /Million /Benlo/BCH/Eaton.
73	ELEC-2.13.15	CATEGOR Y- III	Makes: Milltec / Sputnik / Vimal/Amron
74	ELEC-2.13.16	CATEGOR Y- I	Makes: Legrand(Ekinox 3) / Schneider-A9/Hager - Novello+/ Seimens/Havells STADx/ Lauritz Knudsen (formerly L&T) -Newrange/Indo Asian-Opti Pro/ HPL (Techno)/ Anchor (Uno Plus)/ABB-ITUS
75	ELEC-2.13.17	CATEGOR Y- II	Makes: Siemens / ABB / Standard / Havells / Hager/ C&S / Lauritz Knudsen (formerly L&T) / GM / Gold

			Medal /Polycab/Million/Benlo/BCH/Eaton.
76	ELEC-2.13.18	CATEGOR Y- III	Makes: Milltec / Sputnik / Vimal/Amron.
	ELEC-2.14.1& ELEC-2.14.2		Makes : Havells/Legrand/Hager /Schenider/ABB
	ELEC-2.15.1		Makes : Havells//Hager/Indo Asian /HPL /Million
			SECTION - 3
	3.1		STREET LIGHT LUMINAIRES
77	ELEC-3.1.1	CATEGOR Y- I	Deleted
78	ELEC-3.1.2	CATEGOR Y-II	Deleted
79	ELEC-3.1.3	CATEGOR Y- I	Deleted
80	ELEC-3.1.4	CATEGOR Y- II	Deleted
81	ELEC-3.1.5	CATEGOR Y- I	Deleted
82	ELEC-3.1.6	CATEGOR Y- II	Deleted
83	ELEC-3.1.7		Deleted
	3.2		LED POST TOP LANTERN LUMINAIRES
84	ELEC-3.2.1		Makes: Crompton LPTO-40-CDL-M/ Bajaj Celesta BGCL 40 W LED Wh/Wipro LP 02 or equivalent in Phillips/Keselec/Havells Endura Spring / Rhino(GPLP14)/Lightman-Derby
85	ELEC-3.2.2		Make: Keselec MIRI or equivalent in Philips/Wipro/Lightman-blimp
86	ELEC-3.2.3		Make: Keselec CAMBRIDGE/ or equivalent in Philips/Wipro/Lightman-Amaira
87	ELEC-3.2.4		Makes: Crompton / Bajaj/ Wipro /Phillips /Keselec /Havells /Lightman-panama
	3.3		ACCESSORIES FOR MV / SV / MH LUMINAIRES
			COPPER BALLASTS
88	ELEC-3.3.1		Deleted
89	ELEC-3.3.2		Deleted
90	ELEC-3.3.3		Deleted
91	ELEC-3.3.4		Deleted
	3.4		LAMPS
92	ELEC-3.4.1	CATEGOR Y- I	Deleted.
93	ELEC-3.4.2	CATEGOR Y- II	Deleted
	3.5		AUTOMATIC STREET LIGHT CONTROL SYSTEMS
94	ELEC-3.5.1		Make: Nature Switch / Lightmate/ GL/Bajaj/Schnell
95	ELEC-3.5.2 a - e		Make: Nature Switch / LightMate /GL/Bajaj/Schnell
96	ELEC-3.5.3 a - c		Makes :Super tech (Light Mate)/ Lauritz Knudsen (formerly L&T) / Siemens / Bajaj/Schnell
	ELEC-3.5.4 a - g		Makes :- Lauritz Knudsen (formerly L&T) / Siemens / Bajaj/KSP/Schnell

	ELEC-3.5.5 a-g		Makes : Lauritz Knudsen (formerly L&T) / Siemens / Bajaj/KSP/Schnell
	3.6		INTERNAL LUMINAIRES
97	ELEC-3.6.1		Deleted
98	ELEC-3.6.2		Deleted
99	ELEC-3.6.3		Deleted
100	ELEC-3.6.4		Deleted
101	ELEC-3.6.5		Deleted
102	ELEC-3.6.6		Deleted
103	ELEC-3.6.7		Deleted
104	ELEC-3.6.8		Deleted
105	ELEC-3.6.9		Deleted
106	ELEC-3.6.10		Deleted
107	ELEC-3.6.11		Deleted
	3.7		FLOURSCENT TUBES / CFL LAMPS / LED BULBS
108	ELEC-3.7.1		Deleted
109	ELEC-3.7.2		Deleted
110	ELEC-3.7.3		Deleted
111	ELEC-3.7.4		Deleted
			LED BULBS
112	ELEC-3.7.5		. Makes: Phillips /Crompton / Bajaj / Havells / Halonix /GM/HPLSyska / Green Lites / Fortune Arrt / GoldMedal / Luker/Leo/Orbit /Rhino / GLO LED /Million /Victoria/Benlo/Goldwyn/Sturlite/AJUSS/Orient
113	ELEC-3.7.6		Makes: Phillips /Crompton / Bajaj / Havells / Halonix/GM/HPL/Syska / Green Lites / Fortune Arrt / GoldMedal/ Luker/Leo/Orbit/Rhino /GLO LED
114	ELEC-3.7.7		Makes: Philips/Bajaj / Crompton / Havells/ HPL.
	3.8		LED LUMINAIRES INDOOR
			DOWN LIGHTERS
115	ELEC-3.8.1	CATEGOR Y- I	a) LUMINAIRE MAKE : Phillips / GE-Venture / Crompton / Wipro / Bajaj / Havells / Halonix /Jaquar /HPL/GM / GreenLites / Gold Medal/Eveready/ FortuneArrt/ Rhino/Panasonic/Ecolink/Capart b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG/Everlight
116	ELEC-3.8.2	CATEGOR Y- II	Makes: Surya /C&S / Syska / Enrich / Stanjo / Polycab / Ib LED/ Opple/R LED/Luker/ Orbit/Trinic / GLO LED /Vimal /Benlo /Goldwyn /Lumirise /Sturlite /AJUSS/Orient. b) LED MAKE : CREE / NICHIA / OSRAM / SAMSUNG / EVERLIGHT
117	ELEC-3.8.3	CATEGOR Y- III	a) LUMINAIRE MAKE : Pasolite / Cosmo / Siger/ Konzept/Kiran/Vibrant/Leo/Lumens/Ilite/Akarui/Million/Fy bros /Victoria/RK b) LED MAKE : CREE / NICHIA / OSRAM / SAMSUNG / EVERLIGHT
			LED PANEL LIGHTS
118	ELEC-3.8.4	CATEGOR Y- I	a) LUMINAIRE MAKE : Phillips / GE- Venture / Crompton / Wipro / Bajaj / Havells / Halonix /Jaquar /HPL/GM / GreenLites / Gold Medal/Eveready/

			FortuneArrt/ Rhino/Panasonic/Ecolink/Bee-lite/Capart b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG/Everlight.
119	ELEC-3.8.5	CATEGOR Y- II	Makes: Surya /C&S / Syska / Enrich / Stanjo / Polycab/ Ib LED/ Oppl/ Luker/ Orbit/Trinic/Lumens/ GLO LED/ Vimal/Benlo/Goldwyn/ Lumirise/Sturlite/AJUSS/Orient. b) LED MAKE : CREE / NICHIA / OSRAM / SAMSUNG / EVERLIGHT
120	ELEC-3.8.6 a to f	CATEGOR Y- III	a) LUMINAIRE MAKE : Pasolite / Cosmo / Siger/ Koncept/ Kiran/Vibrant/Leo/Ilite/Akarui/Million/Fybros /Victoria/RK b) LED MAKE : CREE / NICHIA / OSRAM / SAMSUNG / EVERLIGHT/ San'an
			COB DOWN LIGHTS
121	ELEC-3.8.7	CATEGOR Y- I	a) LUMINAIRE MAKE : Phillips / GE-Venture / Crompton / Wipro / Bajaj / Havells / Halonix/Jaquar/HPL/GM / GreenLites / Gold Medal /Eveready/ FortuneArrt/ Rhino /Panasonic /Ecolink/Capart b) LED MAKE : Bridge Lux / LUMILEDS / CREE / NICHIA / Epistar/ Sunpo/Samsung
122	ELEC-3.8.8	CATEGOR Y- II	Makes: Surya /C&S / Syska / Enrich / Stanjo / Polycab/ Ib LED/ Oppl/Luker/ Orbit/ Trinic/Lumens /GLO LED /Vimal/Akarui /Million /Fybros /Victoria /Benlo /Goldwyn/ Lumirise/Sturlite/AJUSS/Orient. b) LED MAKE : Bridge Lux / LUMILEDS / CREE / NICHIA / Epistar/ Sunpo/Samsung
			SPOT LIGHTS / WALL WASHERS
123	ELEC-3.8.9	CATEGOR Y- I	a) LUMINAIRE MAKE : Phillips / GE-Venture / Crompton / Wipro / Bajaj/ Havells / Halonix/Jaquar/HPL/GM / GreenLites / Gold Medal/Eveready/ FortuneArrt/Panasonic b) LED MAKE : Bridge Lux / LUMILEDS / CREE / NICHIA / Epistar/ Sunpo
124	ELEC-3.8.10	CATEGOR Y- II	Makes: Surya /C&S / Syska / Enrich / Stanjo / Polycab/ Ib LED/ Oppl/R LED/Luker/ Orbit/Trinic /Akarui/Lumirise b) LED MAKE : Bridge Lux / LUMILEDS / CREE / NICHIA / SAMSUNG/ Sunpo
125	ELEC-3.8.11	CATEGOR Y- I	a) LUMINAIRE MAKE : Phillips / GE- Venture / Crompton / Wipro / Bajaj / Havells / Halonix/ GreenLites /HPL /Eveready/ FortuneArrt b) LED MAKE :Bridge Lux / LUMILEDS / CREE / NICHIA / Epistar.
126	ELEC-3.8.12	CATEGOR Y- II	Makes: Surya / Polycab/ Oppl /Luker/ Orbit/Akarui b) LED MAKE : Bridge Lux/ CREE / NICHIA / Epistar
			LED BATTENS AND 2' x 2' LUMINARIES

127	ELEC-3.8.13	CATEGOR Y- I	a) LUMINAIRE MAKE : Phillips / GE- Venture / Crompton / Wipro / Bajaj / Havells / Halonix /Jaquar /HPL/GM / GreenLites / Gold Medal/Eveready// Rhino/Panasonic/Ecolink/Capart. b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG/ Everlight.
128	ELEC-3.8.14	CATEGOR Y- II	Makes: Surya /C&S/ Fortune Arrt / Syska / Enrich / Stanjo / Polycab/ Ib LED/ Oppl/ Luker/ Orbit/ Trinic/Lumens/ GLO LED / Vimal /Benlo /Goldwyn /Sturlite /AJUSS/Orient b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG / EVERLIGHT
129	ELEC-3.8.15	CATEGOR Y- III	a) LUMINAIRE MAKE : Pasolite / Cosmo / Siger/ Koncept/ Kiran /Vibrant /Leo /ilite /Akarui /Million /Fybros /Victoria/RK b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG / EVERLIGHT
130	ELEC-3.8.16	CATEGOR Y- I	a) LUMINAIRE MAKE : Phillips / GE- Venture / Crompton / Wipro / Bajaj / Havells / Halonix /Jaquar /HPL/GM / GreenLites / Gold Medal/Eveready// Rhino/Panasonic/Ecolink/Capart. b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG.
131	ELEC-3.8.17	CATEGOR Y- II	Makes: Surya /C&S/ Fortune Arrt / Syska / Enrich / Stanjo / Polycab/ Ib LED/ Oppl/ Luker/ Orbit/ Trinic/Lumens/ilite/ GLO LED/ Vimal /Akarui /Million /Fybros/Victoria/Benlo/Goldwyn/Sturlite/AJUSS/Orient. b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG / EVERLIGHT
132	ELEC-3.8.18		Makes: Phillips / Crompton / Bajaj/Surya/Havells/HPL
133	ELEC-3.8.19		Makes: Greenlites / Fortune Arrt / Capart / GM / Goldmedal /Trinic/Kiran.
134	ELEC-3.8.20	CATEGOR Y- I	a) LUMINAIRE MAKE : Phillips / GE-Venture / Crompton / Wipro / Bajaj/ Havells / Halonix /Jaquar /HPL/GM / GreenLites / Gold Medal/Eveready / FortuneArrt// Rhino/Panasonic/Ecolink/Bee-lite/Capart. b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG/Everlight.
135	ELEC-3.8.21	CATEGOR Y- II	Makes: Surya /C&S / Syska / Enrich / Stanjo / Polycab/ Ib LED/ Oppl/ Luker/ Orbit/Trinic/ilite/GLO LED/ Vimal/Akarui/ Million /Fybros /Victoria /Benlo /Goldwyn/Sturlite/AJUSS/Orient. b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG / EVERLIGHT.
136	ELEC-3.8.22		Makes: Philips/Bajaj/ Crompton / Surya / Havells / Greenlites/ Insta Power/HPL /Halonix/ Panasonic. / FortuneArrt
137	ELEC-3.8.22		a) LUMINAIRE MAKE : Phillips (Pureline Slim) / GE- Venture / Crompton / Wipro / Bajaj / Havells (Dustello) b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG/LG
138	ELEC-3.8.23	CATEGOR Y- I	a) LUMINAIRE MAKE : Wipro(Skyline) / Philips (Green line) / GE-Venture / Crompton(Neo Series) / Bajaj

			(Edge) / Halonix(Lumos - Super) / Havells (Endura Series)/Valmont(Supernova) /Capart(Premium) /Greenlites(Hi-Lux) /Polycab /Keselec/ HPL(City Vision)/ Jaquar(Premium) /Eveready/ Surya (Lexon) / FortuneArrt (Leaf) / Rhino(GPSL04)/Orient(Fiest Plus) /Bee-lite(Gritty)/Ecolink(Durastreet Gen II) b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG / LG
139	ELEC-3.8.24	CATEGOR Y- I	a) Luminaire Make : Wipro(Skyline) / Philips (Greenline Extra) / GE- Venture / Crompton(Nexus / Hawk series) / Bajaj (Edge) / Halonix (Modular/ Lumos-Super) / Havells (Endura Series)/Valmont (Supernova) Greenlites(HI-Lux) / Capart(Premium) /Polycab/Keselec / HPL(City Vision)/Jaquar (Premium) /Eveready /Surya (Pollux) / Fortune Arrt (Leaf) / Rhino(GPSL06)/Orient (Fiesta Plus) /Bee-lite(Gritty) /Ecolink(Durastreet Gen-II) /Pro-Lite(GLM) b) LED MAKE :PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG / LG.
140	ELEC-3.8.25	CATEGOR Y- II	a) LUMINAIRE Makes: Syska / GM / C&S/ VIN/Gold Medal /Pharox / Cosmo / Enrich// Renesola / Stanjo / Goldwyn/ Ib LED/ Orbit/ Luker/Trinic/ GLO LED/ Vimal/Transrail/Valmont/Benlo/Goldwyn/ Lumirise/Sturlite. b) LED MAKE : CREE / NICHIA / OSRAM / SAMSUNG / LG.
141	ELEC-3.8.26	CATEGOR Y- III	a) LUMINAIRE Makes: Trinic / Pasolite / Sieger/Koncept/Vibrant/Leo/Lumens/Ilite/Akarui/Million/Fybro/SNKS-NLight/Victoria/Foursun/RK/SIRIMAYI LIGHTS. b) LED MAKE: CREE / NICHIA / OSRAM / SAMSUNG / LG.
			FLOOD LIGHTS
142	ELEC-3.8.27	CATEGOR Y- I	a) LUMINAIRE MAKE : Wipro / Philips/ GE-Venture / Crompton/ Bajaj/Greenlites / Havells /Valmont(Hypernova)/ Capart(Premium) /Halonix/ Polycab/Keselec/HPL/Jaquar/Eveready / Surya (Livia Pro) / FortuneArrt (Fin)/ Rhino(GPFL02 Series)/Orient (Sigma Plus) /Bee-lite(Endura)/Ecolink(Dura floodlight)/ Pro-Lite(BGL) b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG.
143	ELEC-3.8.28	CATEGOR Y- II	a) LUMINAIRE Makes: Pharox / GM / Goldmedal / Syska / C&S/Cosmo/ Ib LED/ Vibrant/ Stanjo/Enrich/ Orbit/Luker/Trinic/Ilite/GLO LED /Vimal /Akarui /Million /Fybro/Transrail/Valmont/Victoria/Benlo/Goldwyn/ Lumirise/Sturlite/RK. b) LED MAKE : CREE / NICHIA / OSRAM / SAMSUNG / LG
			HIGH BAY LIGHTS

144	ELEC-3.8.29	CATEGOR Y- I	a) LUMINAIRE MAKE : Wipro / Philips/ GE-Venture / Crompton/ Bajaj /Greenlites / Havells/ Capart(Premium) /Halonix/ Polycab/Keselec/ HPL/ Jaquar/Eveready / Surya (ORION-II)/ FortuneArrt (UFO-S) /Rhino(GPHB02 Series)/Ecolink(Megalux)/Bee-Lite b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG .
145	ELEC-3.8.30	CATEGOR Y- II	a) LUMINAIRE Makes: Pharox / GM / Goldmedal / Syska / C&S/Cosmo/ Ib LED/ Vibrant/ Stanjo /Enrich /Orbit /Luker/Trinic/Ilite/GLO LED /Akarui /Victoria /Benlo/Goldwyn/Sturlite. b) LED MAKE : CREE / NICHIA / OSRAM / SAMSUNG.
146	ELEC-3.8.31		UMINAIRE MAKE : Wipro / Philips/ GE / Crompton/ Bajaj / Greenlites/ Havells/ FortuneArrt b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG/Seoul .
			RGB/RGBW LED Lighting
147	ELEC-3.8.32		LUMINAIRE MAKE : Wipro / Philips/ Crompton/ Bajaj / Greenlites/ Havells/ FortuneArrt b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG/Seoul .
148	ELEC-3.8.33		a) LUMINAIRE MAKE : Wipro / Philips/ GE / Crompton/ Bajaj / Greenlites/ Havells/ FortuneArrt b) LED MAKE : PHILIPS LUMILEDS / CREE / NICHIA / OSRAM / SAMSUNG /SEOUL.
149	ELEC-3.8.34		Make: Sunlite Suit2/Artnet or its equivalent
150	ELEC-3.8.35		Makes:colourdreamer/ AURA/Greenlites
151	ELEC-3.8.36		Makes:colourdreamer/ AURA/Greenlites
152	ELEC-3.8.37		Makes:colourdreamer/ AURA/Greenlites
153	ELEC-3.8.38		Makes:Mean Well or its equivalent
154	ELEC-3.8.39		Makes:Mean Well or its equivalent
			LED DRIVERS
155	ELEC-3.8.40		Makes: Philips /Crompton / Bajaj/ Havells/Surya/Greenlites/HPL/Halonix/Jaquar/Ib LED/Promtec/Eveready.
156	ELEC-3.8.41		Makes: Philips /Crompton / Bajaj/ Havells/Surya/Greenlites/HPL/Halonix/Jaquar/Ib LED/Promtec/Eveready/Stanjo/ Pro-Lite.
			SECTION - 4
	4.1		U.G. CABLES
157	ELEC-4.1.1	CATEGOR Y- I	Makes: Torent / Universal / Unicab / Havells / Finecab / KEI / Gloster/ Polycab /RR Kabel/ Fortune Arrt /KEC Asian Cables/Orbit/Avocab /Gemscab /Batra Henlay.
158	ELEC - 4.1.2	CATEGOR Y- II	Makes: Finolex / Paragon / V-Guard / Suncab / Delton / Payal / Laser /Rhino /Pawancab/AKG/LS cable/Polywires/Nakoda/South king.
			33 KV HT XLPE CABLES
159	ELEC-4.1.3		Make: Torrent / Universal / Unicab / Havells / KEI /Polycab/Gloster/RR Kabel/KEC Asian cables /Avocab/Gemscab
			11 KV HT XLPE CABLES

160	ELEC- 4.1.4		Make: Torrent / Universal / Unicab / Havells / KEI / Polycab/Gloster/RR Kabel/KEC Asian Cables /Avocab/Gemscab
			Un Armoured and Armoured Copper Control Cables
161	ELEC-4.1.5		Make: Torrent / Universal / Unicab / Havells / KEI / Polycab/Gloster /orbit/ Paragon / RR Kabel/ KEC Asian cables/Pawancab /AKG/LS cable /Polywires/South king/Avocab/Gemscab/Batra Henlay
162	ELEC-4.1.5 A		Makes: Torent / Universal / Unicab / Havells / KEI / Gloster/Finecab / Polycab /RR Kabel/ Polywires
163	ELEC-4.1.5 B		Makes: KEC Asian cables / Finolex / Paragon / V-Guard / Fortune Arrt / Suncab / Delton / Payal / Gemscab/ Orbit/Avocab/Laser/Rhino.
164	ELEC-4.1.5C		Makes:- Finolex/RR kabel/ Havells/ KEI/ Polycab/ Gloster/V-Guard/HPL/GM/ Million/Goldmedal/Anchor.
165	ELEC-4.1.6		Make: Torrent / Universal / Unicab / Havells / KEI / Polycab/Gloster/Orbit/ Paragon/RR Kabel / KEC Asian Cables /Rhino /Pawancab/AKG/LS cable/ Polywires/South king/Avocab/Gemscab/Batra Henlay
			CABLE TERMINATIONS AND ACCESSORIES
166	ELEC-4.1.7		Makes: Raychem /M seal/ Denson/ Multy/ Transeal-Hongshang
167	ELEC-4.1.8		Makes: Raychem /M seal/ Denson/ Multy/ Transeal-Hongshang
168	ELEC-4.1.9		Makes: Raychem /M seal/ Denson/ Multy/ Transeal-Hongshang
169	ELEC-4.1.10		Makes:Dowels/Comet/SMI
170	ELEC-4.1.11		.Makes:Dowels/Comet/SMI
171	ELEC-4.1.12		Makes:Dowels/Jainson/Comet
172	ELEC-4.1.13		Makes:Dowels/Jainson/Comet
	4.3		DOUBLE WALLED CORRUGATED HDPE PIPE
173	ELEC-4.3.1 a-h		Makes: DURA LINE (Dura Guard)/Precision/CPE/Million(AJUSS) or any ISI make approved by CE Electrical..
			SECTION - 5
	5.1		FANS
174	ELEC-5.1.1		Makes: Atomberg(GV2)/ Halonix(Plasma) /Havells(Efficiencia Neo)/ Crompton(EN Groove)/Superfan(E281)/RJP(Ecowise)/GM (Excel 25 Pro)/ Goldmedal(OPUS)
175	ELEC-5.1.2		Makes: Atomberg(GV2)/ Halonix(Plasma) /Havells(Efficiencia Neo)
176	ELEC-5.1.3		Makes: Crompton (HS Plus/HS) / Havells (ES PLUS/SS390ES) /Orient Energy Star/ Halonix(Zephyr) /Polycab(Zoomer-HS) / G.M.(G AIR) /Bajaj-Edge/Arcline (Glacier) /Million (Enerzio50) /Goldmedal(Legacy 390).
177	ELEC-5.1.4		Makes: Crompton (HS Decora/Aura) / Bajaj Regal Star / Havells Festiva / Orient Ornamental Shine /Halonix(Halo) /Polycab(Aerobliss)/G.M. (Air Wave Premium) /Goldmedal(Flora)/RJP(Aroma Super)/ Million (Max400Deco).

178	ELEC-5.1.5		Makes: Crompton HS / Havells Velocity ES 50/Orient Summer Breeze Pro/Halonix(Zephyr) /Polycab(Aerobliss)/Arcline (Glacier)/GM(Air Breeze 56).
179	ELEC-5.1.6		Makes: Crompton Wind Flo / Bajaj Elite / Havells Swing / Orient Wall 50/Halonix Krypton/G.M. (Bolt)/ Goldmedal(Nora-16)/Million(Swing wall fan)
180	ELEC-5.1.7		Makes: Crompton Wind Flo / Bajaj Spectrum / Havells Swing / Orient Stand 37/Halonix Krypton/Polycab / G.M. (Bolt)/Goldmedal(Nora)
181	ELEC-5.1.8		Makes: Crompton / Havells Turbo Force / Orient Tornado II / Almounard/Halonix Turbon/Polycab./ G.M. (Air-Burst)/Goldmedal(Ultra Air)
182	ELEC-5.1.9		Makes: Crompton / Havells Turbo Force / Almounard/Halonix
183	ELEC-5.1.10		Makes: Crompton / Havells ciera / Orient Wall 11/Halonix
184	ELEC-5.1.11		Makes: Crompton / Bajaj Bahar WG / Havells Ventil Air-DSP / Orient hill air/Halonix /Polycab/G.M. (Xenix)/Goldmedal (Havoc Plus)/Million (300mm-LX)
185	ELEC-5.1.12		Makes: Crompton / Bajaj Bahar WG / Havells Ventil Air-DSP / Orient hill air/Halonix /Polycab/ G.M. (Xenix)/Goldmedal (Havoc)/Million (225mm-LX)
186	ELEC-5.1.13		Makes: Crompton / Almounard / Havells Ventil Air-DB
187	ELEC-5.1.14		Makes: Crompton / Almounard / Havells Turbo Force/Halonix Krypton
188	ELEC-5.1.15		Makes: Crompton / Almounard / Havells Turbo Force/Halonix Krypton
	ELEC-5.1.16		Makes: Crompton / Bajaj Bahar / Havells Ventil Air-LX / Orient hill air/Halonix /Polycab/G.M. (Eco Air)/Goldmedal (Rapido)
	ELEC-5.1.17		Makes: Crompton / Bajaj Bahar WG / Havells Ventil Air LX/ Orient hill air/Halonix /Polycab/G.M. (Eco Air)/Goldmedal (Rapido)
	ELEC-5.1.18		Makes: Atomberg/ Halonix/Havells/ Crompton
	5.2		WATER HEATERS (Conventional & Solar)
189	ELEC-5.2.1		Makes: Prevailing models of Crompton/ Jaquar / Venus / Racold / AO Smith /Havells /Warmex/ GM/ Goldmedal makes and shall be confirming to SOR specifications
190	ELEC-5.2.2		Make:TATA / BHEL/ BOSCH/ ETC/V-GUARD /RACOLD
191	ELEC-5.2.3		Make:TATA / BHEL/ BOSCH/ ETC/V-GUARD /RACOLD
192	ELEC-5.2.4		Make:Jaquar/AO Smith/Voltex/Racold /Rheem
193	ELEC-5.2.5		Make:Jaquar/AO Smith/Voltex/Racold /Rheem
	5.4		PUMPSETS
			SINGLE PHASE SUBMERSIBLE MOTOR PUMP SETS
194	ELEC-5.4.1	CATEGOR Y- I	Makes: Kirloskar / Crompton / Texmo / CRI / KSB/Lubi/ PSG/ARYEN VARSHA/ Falcon/Prithvi.
195	ELEC-5.4.2	CATEGOR Y- II	Makes: Pluga / Sterling / Kumar / Unnati zen/Duke/Lada/Ellen/ Suguna /UNIttek /KSP(Karunya) /Anco/Sabar/Fitwell/Deccan/Karvel / SILVER/Samudra/ Acube(SS-Deluxe)/ JEROME PUMPS

			THREE PHASE SUBMERSIBLE MOTOR PUMP SETS.
196	ELEC-5.4.3	CATEGOR Y- I	Makes: Kirloskar / Crompton / Texmo / CRI / KSB/Lubi/ PSG/ ARYEN VARSHA /Falcon/Prithvi
197	ELEC-5.4.4	CATEGOR Y- II	Makes: Pluga / U-Neel / Sterling / Kumar / Unnati zen/Duke/Lada/Ellen/ Suguna/ UNIttek/KSP(Karunya)/ Anco/ Sabar/ Fitwell/Deccan/Karvel/ SILVER/Samudra/ JEROME PUMPS
198	ELEC-5.4.5	CATEGOR Y- I	Makes: Kirloskar / Crompton / Texmo / CRI / KSB/Lubi/ PSG/ ARYEN VARSHA /Falcon/Prithvi
199	ELEC-5.4.6	CATEGOR Y- II	Makes: Pluga / U-Neel / Sterling /Kumar / Unnati zen/Duke/Lada/Ellen/ Suguna/UNIttek /KSP (Karunya) /Anco/ Sabar/Fitwell/Polycab/Deccan/Karvel/ SILVER/Samudra/JEROME PUMPS
			SINGLE PHASE OPEN WELL SUBMERSIBLE MOTOR PUMP SETS
200	ELEC-5.4.7	CATEGOR Y- I	Makes: Kirloskar / Crompton / Texmo / CRI / KSB/Lubi/PSG/ ARYEN VARSHA /Falcon/Prithvi
201	ELEC-5.4.8	CATEGOR Y- II	Makes: Pluga / U-Neel / Sterling / Kumar / Unnati zen/Duke/LDK/Ellen/ Suguna/UNIttek /KSP (Karunya) / Anco/ Sabar/Fitwell/Deccan/Karvel/ SILVER/ Samudra /Acube
			THREE PHASE OPEN WELL SUBMERSIBLE PUMP SETS
202	ELEC-5.4.9	CATEGOR Y- I	Makes: Kirloskar / Crompton / Texmo / CRI / KSB/Lubi /PSG/ ARYEN VARSHA /Falcon/Prithvi
203	ELEC-5.4.10	CATEGOR Y- II	Makes: Pluga / U-Neel / Sterling / Kumar / Unnati zen/Duke/LDK/Ellen/ Suguna/UNIttek/ KSP(Karunya) /Polycab/ Anco/ Sabar /Fitwell/Deccan/Karvel/ SILVER/Samudra/Acube.
			SINGLE PHASE MONO BLOCK MOTOR PUMP SETS.
204	ELEC-5.4.11	CATEGOR Y- I	Makes: Kirloskar / Crompton / Texmo / CRI / KSB/Lubi / Havells Hi-flow V2 / PSG/ ARYEN VARSHA /Falcon
205	ELEC-5.4.12	CATEGOR Y- II	Makes: Pluga / U-Neel / Sterling /Kumar / Unnati zen/Ellen/LDK/Suguna/ UNIttek/Polycab/Anco/ Sabar/Fitwell/Deccan/Karvel / SILVER
206	ELEC-5.4.13	CATEGOR Y- I	Makes: Kirloskar / Crompton / Texmo / CRI / KSB /Lubi/ ARYEN VARSHA /Falcon
207	ELEC-5.4.14	CATEGOR Y- II	Makes: Pluga / U-Neel / Sterling /Kumar / Unnati zen/Ellen/LDK/Suguna/ UNIttek/Polycab/Anco/ Sabar/Fitwell/Deccan/Karvel/ SILVER
			CONTROL PANEL BOARD FOR MOTOR PUMPSETS
208	ELEC-5.4.15		make C&S/LTLK/ Seimens/ BCH/KSP(Karunya)/ Crompton. complete.,
209	ELEC-5.4.16		make C&S/ Lauritz Knudsen (formerly L&T) /Seimens/BCH /KSP(Karunya) /Crompton. complete.,
210	ELEC-5.4.17		Voltmeter ;. Makes: Lauritz Knudsen (formerly L&T) / C&S / SALZAR / HPL/ AEI / Mecor / Rishab Ammeter Makes: Lauritz Knudsen (formerly L&T)/ C&S / SALZAR / HPL/ AEI / Mecor / Rishab Single phase preventor Makes: Lauritz Knudsen (formerly L&T) / Minilec / Powertec.

			32 A TP, 10KA MCB. Makes: Legrand / Schneider capacitor Makes: Lauritz Knudsen (formerly L&T) / Siemens / Schneider / Epcos/Havells.
	a		Make C&S.Crompton / Lauritz Knudsen (formerly L&T) /KSP/ Siemens/BCH.
	b		Make C&S/Crompton / Lauritz Knudsen (formerly L&T) / Siemens/BCH.
	c		Make C&S/Crompton / Lauritz Knudsen (formerly L&T) / Siemens/BCH.
211	ELEC-5.4.18		Makes: Siemens / Crompton / Lauritz Knudsen (formerly L&T) (MF1)
212	ELEC-5.4.19		Makes: Siemens / Crompton / Lauritz Knudsen (formerly L&T) (MK2 DOL).
213	ELEC-5.4.20		Makes: Siemens / Crompton / Lauritz Knudsen (formerly L&T) (MU1 DOL)
			UPVC PIPES AND FITTINGS
214	ELEC-5.4.21		Makes: Ashirvad / Finolex / Waterflo /Sudhakar/Precision.
215	ELEC-5.4.27		Makes: Ashirvad / Finolex / Waterflo
216	ELEC-5.4.28		Makes: Ashirvad / Finolex / Waterflo / Apollo
	5.1		AIR CONDITIONERS
	ELEC-5.5.1		1.5TR Split ACs
	a	CATEGOR Y- I	Deleted
	b	CATEGOR Y- II	Deleted
			2.0 TR Split Acs
	c	CATEGOR Y- I	Deleted
	d	CATEGOR Y- II	Deleted
			Inverter Split AC Unts (Cooling Only)
217	ELEC-5.5.1 A		1.5TR Split ACs
	a	CATEGOR Y- I	Makes: Mitsubishi / O General /Toshiba (prevailing models in the market)
	b	CATEGOR Y- II	Makes: Blue Star / Daikin / Hitachi / Voltas / Carrier /LG/Lloyd (prevailing models in the market)
			2.0 TR Split Acs
	c	CATEGOR Y- I	Makes: Mitsubishi / O General / Toshiba (prevailing models in the market)
	d	CATEGOR Y- II	Makes: / Hitachi / Blue Star / Daikin / Voltas /Carrier/ LG/Lloyd (prevailing models in the market)
218	ELEC-5.5.2		0.8/ 1.0TR Split Acs
	a	CATEGOR Y- I	Makes: Mitsubishi / O General / Toshiba (prevailing models in the market)
	b	CATEGOR Y- II	Makes: Blue star /Carrier /Hitachi/Daikin/ LG /Lloyd (prevailing models in the market)
	c	CATEGOR Y- I	Makes: Mitsubishi / O General / Toshiba (prevailing models in the market)
	d	CATEGOR	Makes: Blue Star / Carrier / Hitachi / Daikin/ LG /Lloyd

		Y- II	(prevailing models in the market)
			1.5, 1.8 & 2.0TR Split Acs
	e	CATEGOR Y- I	Makes: Mitsubishi / O General /Toshiba (prevailing models in the market)
	f	CATEGOR Y- II	Makes: / Blue Star / Daikin / Hitachi/Carrier / LG/Lloyd (prevailing models in the market)
	g	CATEGOR Y- I	Makes: Mitsubishi / O General /Toshiba (prevailing models in the market)
	h	CATEGOR Y- II	Makes: Blue star / Hitachi / Daikin/Lloyd (prevailing models in the market)
	i	CATEGOR Y- I	Makes: Mitsubishi /O General /Toshiba (prevailing models in the market)
	j	CATEGOR Y- II	Deleted
			INVERTER CASSETTE TYPE AC UNITS
219	ELEC-5.5.35		
	a	CATEGOR Y- I	Makes: Mitsubishi PLY- SP18EA / Toshiba RAV- SE561UP / O General.
	b	CATEGOR Y- I	Makes: Mitsubishi PLY- SP24EA / O General AUGA25FRTA-B / Toshiba RAV-SE801UP
	c	CATEGOR Y- II	Makes: Blue Star3HNCS24YAF/ Daikin / Carrier/ LG
	d	CATEGOR Y- I	Makes: Mitsubishi PLY- SP42EA / O General /Toshiba
	e	CATEGOR Y- II	Makes: Daikin / Bluestar / Carrier
	f	CATEGOR Y- I	Makes: Mitsubishi PLY-SP48EA / O General / Toshiba RAV- SE1251UP
	g	CATEGOR Y- II	Makes: Blue Star / Carrier / Daikin/LG
			TOWER MODEL (Vertical) TYPE AC UNITS
220	ELEC-5.5.36		
	a		Makes: Carrier /Daikin / Blue Star
	b		Makes: Carrier /Daikin / Blue Star
	c		Makes: Carrier /Daikin / Blue Star
			HVAC SYSTEMS(VRV/VRF)
221	ELEC-5.6.1	CATEGOR Y- I	Makes: Mitsubishi /DAIKIN/Toshiba/O General
222	ELEC-5.6.2	CATEGOR Y- II	Makes: LG/Voltas/Blue star/Hitachi/Carrier/Samsung
223	ELEC-5.6.6	CATEGOR Y- I	Makes: Mitsubishi /DAIKIN/Toshiba/ O General
224	ELEC-5.6.7	CATEGOR Y- II	Makes: LG/Voltas/Blue star/Hitachi/Carrier/Samsung
225	ELEC-5.6.8	CATEGOR Y- I	Makes: Mitsubishi /DAIKIN/Toshiba /O General
226	ELEC-5.6.9	CATEGOR Y- II	Makes: LG/Voltas/Blue star/Hitachi/Carrier/Samsung
227	ELEC-5.6.10	CATEGOR Y- I	Makes: Mitsubishi /DAIKIN/Toshiba/ O General
228	ELEC-5.6.11	CATEGOR Y- II	Makes: LG/Voltas/Blue star/Hitachi/Carrier/Samsung

229	ELEC-5.6.13	CATEGOR Y- I	Makes: Mitsubishi /DAIKIN/Toshiba/ O General
230	ELEC-5.6.14	CATEGOR Y- II	Makes: LG/Voltas/Blue star/Hitachi/Carrier/Samsung
			Refrigerant Piping
231	ELEC-5.6.20		Makes: Totaline/Mandav/Mexico Insulation: Kflex/ Totaline /Armaflex/Aerofoam/Cani
232	ELEC-5.6.25		Makes: TATA/Jindal
	ELEC-5.6.26 & ELEC-5.6.27		Insulation: Kflex/ Totaline /Armaflex/Aerfoam/Cani
	5.7		EVAPORATIVE AIR COOLING SYSTEM
233	ELEC-5.7.1		Makes: Cool Breeze / Breeze Air
234	ELEC-5.7.2		Makes: Cool Breeze/Breeze Air
			STABILIZERS
235	ELEC-5.8.1	CATEGOR Y- I	Makes: V-Guard / Real Guard / Uni Stab / ITL.
236	ELEC-5.8.2	CATEGOR Y- II	Makes: Keeline / Soft Line
	5.9		REPAIRING OF FANS, COOLERS, PUMPS, MOTORS, FRIDGES AND AIRCONDITIONERS
237	ELEC-5.9.16		Makes: Carrier/ Kirlosker/ Techam-Shah/ Shriram/ Voltas
238	ELEC-5.9.17		Makes: DAIKIN/LG/Carrier/Kirloskar/Techam-shah
239	ELEC-5.9.25		Make: Copper: Totaline /Nippon /Mandev/Nitrile Insulation: Kflex/ Totaline /Armaflex/Aerofoam/Cani
240	ELEC-5.9.26		Makes: Crompton / AU.
241	ELEC-5.9.38		Makes: Mitsubishi /DAIKIN/Toshiba/O General/ LG/Voltas/Blue star/Hitachi/Carrier/Samsung
242	ELEC-5.10.1		Makes:- 1. FAN – KRUGER / ZIEHL- ABEGG /MAICO-DYNAIR 2. MOTORS – ABB/SIEMENS/BBL 3. FILTERS – CAMFIL/THERMADYNE 4. VFD DRIVE - DANFOSS / ABB 5. AHU - EDGE TECH / ZRCO/ CITIZEN/ BOOPATHY
243	ELEC-5.10.2- 5.10.7		Makes:- Crystal Air/Kruger/ System Air/ Carry Air/ Edgetech/ Greenheck/ Aerotech/Maico-Dynair.
244	ELEC-5.10.8		Make : Dyna / American Air Filter / M.K Precesion
			SECTION 6
	6.1		SWAGED / OCTAGONAL POLES AND GARDEN POSTS
			OCTOGONAL POLES
245	ELEC-6.1.4		Makes: Bajaj / Valmont/Laasma/Transrail /Utkarsh/ Skipper /Consoul /Surya /Vakrangee/Lysaght Pole /Hakke
246	ELEC-6.1.5		Makes: Bajaj / Valmont/Laasma/Transrail/Utkarsh/ Skipper/Consoul/Surya/Vakrangee/Lysaght Pole /Hakke
247	ELEC-6.1.6		Makes: Bajaj / Valmont/Laasma/Transrail/Utkarsh/ Skipper/Consoul/Surya/Vakrangee/Lysaght Pole/ Hakke
248	ELEC-6.1.7		Makes: Bajaj / Valmont/Laasma/Transrail/Utkarsh/ Skipper/Consoul/Surya/Vakrangee/Lysaght Pole /Hakke
			DECORATIVE DRAGON TYPE BRACKET WITH

			POLE
249	ELEC-6.1.8		Makes: Bajaj / Valmont/Laasma /Transrail/Utkarsh/ Skipper/Consoul/Surya/Vakrangee/Lysaght Pole/ Hakke
250	ELEC-6.1.10		Makes: Bajaj / Valmont/Laasma /Transrail/Utkarsh/ Skipper/Consoul/Surya/Vakrangee/Lysaght Pole/ Hakke
			POLE BRACKETS
251	ELEC-6.1.11		Deleted
252	ELEC-6.1.12		Deleted
253	ELEC-6.1.13		Deleted
254	ELEC-6.1.14		Deleted
255	ELEC-6.1.15		Deleted
256	ELEC-6.1.16		Deleted
257	ELEC-6.1.17		Deleted
258	ELEC-6.1.18		Deleted
259	ELEC-6.1.19		Deleted
260	ELEC-6.1.20		Deleted
			HIGH MAST POLES
261	ELEC-6.1.21		Makes: Bajaj / Valmont/Laasma/Transrail/Utkarsh/ Skipper/Consoul/Surya/Vakrangee/Lysaght Mast /Hakke
262	ELEC-6.1.22		Makes: Bajaj / Valmont/Laasma/Transrail/Utkarsh/ Skipper/Consoul/Surya/Vakrangee/Lysaght Mast /Hakke
263	ELEC-6.1.23		Makes: Bajaj / Valmont/Laasma /Transrail/Utkarsh/ Skipper/Consoul/Surya/Vakrangee/Lysaght Mast /Hakke
			FEEDER PILLAR BOXES
264	ELEC-6.1.24		FP MCBmake :Legrand / Schnieder / Lauritz Knudsen (formerly L&T)
265	ELEC-6.1.25		FP MCBmake :Legrand / Schnieder Lauritz Knudsen (formerly L&T)
			ERRECTION- HIGH MAST POLES
266	ELEC-6.1.29		Make : Hensel/Sadhrish
			GRP POLES
267	ELEC-6.1.34		Makes: Bajaj / Kemrock / Valmont/Sumip/Helipole
268	ELEC-6.1.35		Makes: Bajaj / Kemrock / Valmont/Sumip / Helipole
	6.2		LT PANEL AND ACCESSORIES
269	ELEC-6.2.3		.Make: Conzerve/Elmeasure/Meco/HPL/ Lauritz Knudsen (formerly L&T) /socomec/ Legrand/ABB
270	ELEC-6.2.4		Make: Conzerve/Elmeasure/ Meco/HPL/ Lauritz Knudsen (formerly L&T) /Schneider /AE /Socomec/ABB
271	ELEC-6.2.5		Make: Kappa/ Lauritz Knudsen (formerly L&T) /Seimens/C&S/Schneider/ABB
272	ELEC-6.2.6		Make: Lauritz Knudsen (formerly L&T) /C&S/SALZER/HPL/ABB
273	ELEC-6.2.7		Make: Lauritz Knudsen (formerly L&T) /C&S/SALZER/HPL/ABB
274	ELEC-6.2.8		Makes: CONZERVE / ELMEASURE / MECO / HPL / HAVELLS/ Lauritz Knudsen (formerly L&T) /ABB.
275	ELEC-6.2.12		Makes: Lauritz Knudsen (formerly L&T) /Seimens/Epcos/Schneider/Havells /Legrand/ABB
276	ELEC-6.2.13		Makes Lauritz Knudsen (formerly L&T) /Seimens/Epcos /Schneider/ ABB/Neptune

277	ELEC-6.2.14		makes: Lauritz Knudsen (formerly L&T) (SALZER)/ABB/Schneider/Seimens/C&S/HPL
278	ELEC-6.2.15		Make:Seimens/ABB/Schneider/ Lauritz Knudsen (formerly L&T) /C&S/HPL/Havells
279	ELEC-6.2.16		Make:Seimens/ABB/Schneider/ Lauritz Knudsen (formerly L&T) /C&S/HPL/Havells
280	ELEC-6.2.17		Make:Seimens/ABB/Schneider/ Lauritz Knudsen (formerly L&T) /C&S/HPL/Havells
281	ELEC-6.2.18		Make:Seimens/ ABB/ Schneider/ Lauritz Knudsen (formerly L&T) /C&S/HPL
	6.3		SUB STATION EQUIPMENT AND TRANSFORMERS
282	ELEC-6.3.1		make:as approved By DISCOMs
283	ELEC-6.3.1a		Make:ABB/ Megawin/Amara Raja/ Lauritz Knudsen (formerly L&T)
284	ELEC-6.3.2		Makes:ABB/Schneider/Seimens/Kirlos kar/Amara Raja/Megawin/ Lauritz Knudsen (formerly L&T)
285	ELEC-6.3.3		Makes:ABB/Schneider/Seimens/Kirlos kar/Amara Raja/Megawin/ Lauritz Knudsen (formerly L&T)
			Oil Immersed TRANSFORMERS
286	ELEC-6.3.4		Make:ABB/ALSTOM/SEIMENS/Kirloskar/Voltamp/ Esennar/KPEL/SSE/THOTA / Vajra/SriJesta(SJTE)
288	ELEC-6.3.5		Makes:Schneider/Kirloskar/Voltamp/ Esennar/ Toshiba/ KPEL/ Powertech /SSE / THOTA / Vajra /SriJesta(SJTE)/Haritha/VVE/ Voltek.
289	ELEC-6.3.5 A		Makes:Schneider/Kirloskar/Voltamp/ Esennar/ Toshiba/ KPEL/ Powertech /SSE / THOTA / Vajra/ SriJesta(SJTE) /Haritha/VVE /Voltek/Star Gazer.
290	ELEC-6.3.5 B		Make: Schneider/Kirloskar/Voltamp/ Esennar/ Toshiba/ KPEL/ Powertech /SSE/ THOTA / Vajra/ SriJesta(SJTE).
292	ELEC-6.3.6		Make:ABB/ALSTOM/SEIMENS/Crompton/Kirloskar/Volt amp/ Esennar
293	ELEC-6.3.7		Make:ABB/ALSTOM/SEIMENS/Crompton/Kirloskar/Volt amp/ Esennar
	6.6		LIGHTENING PROTECTIVE SYSTEM
			Advanced LPS
294	ELEC-6.6.1 a		Make : THUNDERGUARD(EARTHPLUS)/ KALRE/ NIMBUS / FOREND
295	ELEC-6.6.1 b		Make : THUNDERGUARD(EARTHPLUS)/ KALRE/ NIMBUS / FOREND
296	ELEC-6.6.1 c		Make : THUNDERGUARD(EARTHPLUS)/ KALRE/ NIMBUS / FOREND
297	ELEC-6.6.3		Make: EARTHPLUS (THUNDER GUARD) / NIMBUS / KALRE / FOREND
298	ELEC-6.6.5		Make: EARTHPLUS /CIRPROTEC /INDALAC / INGESCO
			SECTION 7
	7.0		LOCAL AREA NETWORK
299	ELEC-7.1.1		Makes: Systimax /Panduit/ Siemond/ Legrand /R&M /Digisol
300	ELEC-7.1.2		Makes: Systimax /Panduit/ Siemond/ Legrand /R&M /Digisol
301	ELEC-7.1.3		Makes: Systimax /Panduit/ Siemond/ Legrand /R&M

			/Digisol
302	ELEC-7.1.4		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M /Digisol
303	ELEC-7.1.5		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M /Digisol
304	ELEC-7.1.6		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M /Digisol
305	ELEC-7.1.7		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M /Digisol
306	ELEC-7.1.8		Makes: Systimax /Panduit/ Siemon/ Legrand/ R&M /Digisol
307	ELEC-7.1.9		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M/ Digisol
	ELEC-7.1.9A		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M /Digisol
308	ELEC-7.1.10		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M /Digisol
	ELEC-7.1.10A		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M /Digisol
309	ELEC-7.1.11		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M /Digisol
	ELEC-7.1.11A		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M/Digisol
310	ELEC-7.1.12		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M /Digisol
	ELEC-7.1.12A		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M/ Digisol
311	ELEC-7.1.13		Makes: Systimax /Panduit/ Siemon/ Legrand /R&M /Digisol
312	ELEC-7.1.14		Make: APW/HCL/Valrack/Netrack/R&M
313	ELEC-7.1.15		Make: APW/HCL/Valrack/Netrack/R&M
			MANAGEBLE NET WORK SWITCHES
314	ELEC-7.1.16		Makes: Cisco/Juniper/Extreme/ Digisol DG-GS4628E2
315	ELEC-7.1.17		Makes:Cisco/Juniper/Extreme/ Digisol DG-GS4652E
316	ELEC-7.1.18		Makes:Cisco /Juniper/Extreme/Digisol DG-GS4610HPE
317	ELEC-7.1.19		Make:Cisco/Juniper/Extreme/Digisol DG-GS4628HPE-P
318	ELEC-7.1.20		Deleted
319	ELEC-7.1.21		Makes:Cisco/Juniper/Extreme/ Digisol DG-GS4628E-XS
320	ELEC-7.1.22		Makes:Cisco/Juniper/Extreme/ Digisol DG-GS4652E-XS
321	ELEC-7.1.23		Mak:Cisco/Juniper/Extreme/Digisol DG-GS4628HPE-XS
322	ELEC-7.1.24		Make:Cisco/Juniper/Extreme/Digisol DG-GS4652HP-XS
323	ELEC-7.1.25		deleted
324	ELEC-7.1.26		deleted
325	ELEC-7.1.27		Make : Cisco / Ruckus/Aruba
326	ELEC-7.1.28		Make: Cisco/Juniper/Extreme
327	ELEC-7.1.29		Makes:- Cisco/Juniper/Extreme
			LOCAL AREA NETWORK CATEGORY-II
	ELEC-7.1.30		Makes: D-Link/Msys connect/Finolex/Derwiser
	ELEC-7.1.31		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.32		Makes: D-Link/Msys connect/Derwiser
	ELEC-7.1.33		Makes: D-Link/Msys connect/Derwiser
	ELEC-7.1.34		Makes: D-Link/Msys connect /Derwiser

	ELEC-7.1.35		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.36		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.37		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.38		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.39		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.40		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.41		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.42		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.43		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.44		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.45		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.46		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.47		Makes: D-Link/Msys connect /Derwiser
	ELEC-7.1.48		Makes: D-Link/Msys connect /Derwiser
			MANAGEBLE NET WORK SWITCHES CATEGORY II
	ELEC-7.1.49		Makes: D-Link-DGS-1210-28/Netgear
	ELEC-7.1.50		Makes: D-Link-DGS-1210-52/Netgear
	ELEC-7.1.51		Makes: D-Link-DGS-1210-10P/Netgear
	ELEC-7.1.52		Makes: D-Link-DGS-1210-28P/Netgear
	ELEC-7.1.53		Makes: D-Link-DGS-1510-28X/Netgear
	ELEC-7.1.54		Makes: D-Link-DGS-1510-52X/Netgear
	ELEC-7.1.55		Makes: D-Link-DGS-1510-28P/Netgear
	ELEC-7.1.56		Makes: D-Link-DGS-3130-54PS/Netgear
	ELEC-7.1.57		Makes: D-Link-DGS-3630-28TC/Netgear
	ELEC-7.1.58		Makes: D-Link /Netgear/TP Link /Netgear
	ELEC-7.1.59		Makes: D-Link /Netgear/TP Link
	ELEC-7.1.60		Makes: D-Link /Netgear/TP Link
	ELEC-7.1.61		Makes: D-Link /Netgear/TP Link
	ELEC-7.1.62		Makes: D-Link /Netgear/TP Link
	ELEC-7.1.63		Make-D-Link /Cisco/Netgear/HP
	ELEC-7.1.64		Make-D-Link / Cisco/Netgear/HP
	ELEC-7.1.65		Make : BELKIN or any reputed approved make
	ELEC-7.1.66		Makes: D-Link / TP-Link/ Netgear/Cisco
	ELEC-7.1.67		Makes: D-Link / TP-Link/ Netgear/Cisco
	ELEC-7.1.68		Makes: D-Link / TP-Link/ Netgear/Cisco
	ELEC-7.1.69		Makes: D-Link / TP-Link/ Netgear/Cisco
	7.3		COMPUTERS,PRINTERS AND SCANNERS
333	ELEC-7.3.1		Model : HP ProDesk or its equivalent in Dell
334	ELEC-7.3.2		Model : HP ProDesk or its equivalent in Dell
335	ELEC-7.3.3		Make : HP LaserJet 1020 Plus Printer (OR) It's Equivalent in Canon /Epson
336	ELEC-7.3.4		makes: Canon imageCLASS MF244dw /HP/Brother DCPB7535DW or its equivalent
337	ELEC-7.3.5		Make : Brother ADS-2400N document scanner (OR) It's Equivalent in Canon/HP
338	ELEC-7.3.6		Makes: Finolex / Delton / Surabi / Polycab
339	ELEC-7.3.7		Makes: Krone or its equivalent.
340	ELEC-7.3.8		Makes: Finolex / Delton / Surabi / Polycab.
341	ELEC-7.3.9		Makes: Finolex / Delton / Surabi / Polycab
342	ELEC-7.3.10		Makes: Finolex / Delton / Surabi / Polycab

343	ELEC-7.3.11		Makes: Finolex / Delton / Surabi / Polycab.
	ELEC-7.3.16		Makes: Beetel / NEC/ Alcatel /Avaya/Seimens.
	ELEC-7.3.16		Makes: HP/Dell/Lenovo
			EPABX SYSTEM
	7.4		SMALL SYSTEM
344	ELEC-7.4.1		Makes: NEC/ Alcatel /Avaya/Siemens/Matrix
345	ELEC-7.4.2		Makes: NEC/ Alcatel /Avaya/Siemens/Matrix
346	ELEC-7.4.3		Makes: NEC/ Alcatel /Avaya/Seimens/Matrix
347	ELEC-7.4.4		Makes: NEC/ Alcatel /Avaya/Siemens/Matrix
348	ELEC-7.4.5		Makes: NEC/ Alcatel /Avaya/Siemens/Matrix
	7.5		LARGE SYSTEM
349	ELEC-7.5.1		Makes: NEC/ Alcatel /Avaya/Siemens/Matrix
350	ELEC-7.5.2		Makes: NEC/ Alcatel /Avaya/Siemens/Matrix
351	ELEC-7.5.3		Makes: NEC/ Alcatel /Avaya/Siemens/Matrix
352	ELEC-7.5.4		Makes: NEC/ Alcatel /Avaya/Siemens/Matrix
353	ELEC-7.5.5		Makes: NEC/ Alcatel /Avaya/Siemens/Matrix
			CCTV & SURVEILLANCE SYSTEM CATEGORY-I
354	ELEC-7.6.1A, ELEC-7.6.1B,		Makes:- Honeywell /Panasonic/Matrix
355	ELEC-7.6.2/ 7.6.3		Make: Honeywell /Panasonic//Matrix
356	ELEC-7.6.4/ 7.6.5/7.5.6		Makes Honeywell /Panasonic//Matrix
	ELEC-7.6.4 A/ 7.6.5A		Makes Honeywell /Panasonic//Matrix
357	ELEC-7.6.7		Make: Seagate/Hitachi/TOSHIBA/ED
358	ELEC-7.6.8		Make- Samsung QB55R or its equivalent make in Dell / LG / Samsung / Lenovo / HP
359	ELEC-7.6.9		Make: Dell / LG / Samsung / HP
			CCTV & SURVEILLANCE SYSTEM CATEGORY-II
	ELEC-7.6.11 to ELEC- 7.6.13		Makes:- D-Link/CP-Plus/PRAMA.
	ELEC-7.6.14		Make:- D-Link/CP-Plus/PRAMA.
	ELEC-7.6.15		Makes:- D-Link/CP-Plus/PRAMA.
	ELEC-7.6.16		Makes:- D-Link/CP-Plus/PRAMA.
			PUBLIC ADDRESSING SYSTEM
360	ELEC-7.7.1 - ELEC-7.7.7		Make: Bosch/ Honeywell.
361	ELEC-7.7.8/ 7.7.9/7.7.10		Make: Ahuja/Mega/Studio Master
362	ELEC- 7.7.11/7.7.12		Makes - Bosch/Honeywell
363	ELEC- 7.7.13/7.7.14		Make: Ahuja/Mega/Studio Master.
364	ELEC-7.7.15		Make: Prevailing models in Market.
			AUDIO-VIDEO SYSTEM
365	ELEC-7.8.1		Make: - Hitachi/ BenQ/ Sony/ Panasonic/LG
366	ELEC- 7.8.2/7.8.3		Makes: Sony / NEC/Panasonic/Christie / Hitachi/Epson
367	ELEC-7.8.4		Make: OEM Make or Custom make.

368	ELEC-7.8.5		Make: Liberty/Suvira /Prolite.
369	ELEC-7.8.6		Make: Samsung/LG/Sony
370	ELEC-7.8.7		Make: OEM Make or Custom make.
371	ELEC-7.8.8/7.8.9		Make: Extron/Kramer
372	ELEC-7.8.10		Make: Custom make
373	ELEC-7.8.11		Make: NT/Customs.
374	ELEC-7.8.12		Make: Logitech
375	ELEC-7.8.13/7.8.14/7.8.15		Makes: Sennheiser / AKG / Electrovoice/JBL/Bose
376	ELEC-7.8.16		Makes: BSS / Xilica / Bose/JBL/Sennheiser
377	ELEC-7.8.17		Makes: Bose / JBL / Electrovoice
378	ELEC-7.8.18		Makes: Bose / Crown / Dynacord / Audac
379	ELEC-7.8.19		Makes: Bose / JBL / Dynacord / Audac
380	ELEC-7.8.20		Makes: Bose / JBL / Electrovoice
381	ELEC-7.8.21		Makes: Bose / JBL / Electrovoice
382	ELEC-7.8.22/7.8.23/7.8.24		Make: Electro-Voice/Bose/ JBL/Signature
383	ELEC-7.8.25		Make: Prevailing models in Market.
384	ELEC-7.8.26		Make: Prevailing models in Market.
385	ELEC-7.8.27 to ELEC-7.8.32		Makes: Extron / AMX / Lightware
386	ELEC-7.8.33		Amrutha Technologies/Dolphin Automation & Technology/Mangal Security Systems
	8.1	MISCELLANEOUS ITEMS	
		NIL	
	9.1		WIRELESS FIRE ALARM SYSTEM
387	ELEC-9.1.1		Makes: Cease Fire / Visonic / Honeywell
388	ELEC-9.1.2		Makes: Cease Fire / Visonic /Honeywell.
389	ELEC-9.1.3		Makes: Cease Fire / Visonic / Honeywell.
390	ELEC-9.1.4		Makes: Cease Fire / Visonic / Honeywell.
	9.2		ADDRESSABLE - FIRE ALARM SYSTEM
391	ELEC-9.2.1 a - f	CATEGOR Y- I	Makes: Notifier / Edwards/Bosch
392	ELEC-9.2.2 a - f	CATEGOR Y- II	Makes: Siemens / Morley / Honeywell/ Ravel/Seaara/Apollo/Cooper
393	ELEC-9.2.3	CATEGOR Y- I	Makes: Notifier / Edwards/Bosch
394	ELEC-9.2.4	CATEGOR Y- II	Makes: Siemens / Morley / Honeywell/ Ravel/Seaara/Apollo/Cooper
395	ELEC-9.2.5	CATEGOR Y- I	Makes: Notifier / Edwards/Bosch
396	ELEC-9.2.6	CATEGOR Y- II	Makes: Siemens / Morley / Honeywell/ Ravel/Seaara/Apollo/Cooper
397	ELEC-9.2.7	CATEGOR Y- I	Makes: Notifier / Edwards/Bosch
398	ELEC-9.2.8	CATEGOR Y- II	Makes:Siemens / Morley / Honeywell/ Ravel/Seaara/Apollo/Cooper
399	ELEC-9.2.9	CATEGOR Y- I	Makes: Notifier / Edwards/Bosch
400	ELEC-9.2.10	CATEGOR	Makes: Siemens / Morley / Honeywell/

		Y- II	Ravel/Seaara/Apollo/Cooper.
401	ELEC-9.2.11	CATEGOR Y- I	Makes: Notifier / Edwards/Bosch
402	ELEC-9.2.12	CATEGOR Y- II	Makes:Siemens / Morley / Honeywell/ Ravel/Seaara/Apollo/Cooper.
403	ELEC-9.2.13	CATEGOR Y- I	Makes: Notifier / Edwards/Bosch
404	ELEC-9.2.14	CATEGOR Y- II	Makes: Siemens / Morley / Honeywell/ Ravel/Seaara/Apollo/Cooper.
405	ELEC-9.2.15	CATEGOR Y- I	Makes: Notifier / Edwards/Bosch
406	ELEC-9.2.16	CATEGOR Y- II	Makes:Siemens / Morley / Honeywell/ Ravel/Seaara/Apollo/Cooper.
407	ELEC-9.2.17	CATEGOR Y- I	Makes: Notifier / Edwards/Bosch
408	ELEC-9.2.18	CATEGOR Y- II	Makes:Siemens / Morley / Honeywell/ Ravel/Seaara/Apollo/Cooper .
409	ELEC-9.2.19	CATEGOR Y- I	Makes: Notifier / Edwards/Bosch
410	ELEC-9.2.20	CATEGOR Y- II	Makes:Siemens / Morley / Honeywell/ Ravel/Seaara/Apollo/Cooper.
	9.3		CONVENTIONAL - FIRE ALARM SYSTEM
411	ELEC-9.3.1		Makes: System Censor / Ravel/Vertex
412	ELEC-9.3.2		Makes: Makes: System Censor / Ravel/Vertex
413	ELEC-9.3.3		Makes: System Censor / Ravel/Vertex
414	ELEC-9.3.4		Makes: System Censor / Ravel/Vertex
415	ELEC-9.3.5		Makes: System Censor / Ravel/Vertex/Apollo.
416	ELEC-9.3.6		Makes: Makes: System Censor / Ravel/Vertex
417	ELEC-9.3.7		Makes: System Censor / Ravel/Vertex
418	ELEC-9.3.8		Makes: System Censor / Ravel/Vertex
	9.4		POWDER BASED FIRE EXTINGUISHERS
419	ELEC-9.4.1	CATEGOR Y- I	Makes: Cease Fire / Minimax
420	ELEC-9.4.2	CATEGOR Y- II	Makes: Safex / Kenex / Bharat / Reliance/NewTech/Kartar/Armorfire/Securezone
421	ELEC-9.4.3	CATEGOR Y- I	Makes: Cease Fire / Minimax
422	ELEC-9.4.4	CATEGOR Y- II	Makes: Safex / Kenex / Bharat / Reliance/NewTech/Kartar/Armorfire/Securezone
423	ELEC-9.4.5	CATEGOR Y- I	Makes: Cease Fire / Minimax
424	ELEC-9.4.6	CATEGOR Y- II	Makes: Safex / Kenex / Bharat / Reliance/NewTech/Kartar/Armorfire/Securezone
425	ELEC-9.4.7	CATEGOR Y- I	Makes: Cease Fire / Minimax
426	ELEC-9.4.8	CATEGOR Y- II	Makes: Safex / Kenex / Bharat / Reliance/NewTech/Kartar/Armorfire/Securezone
			CLEAN AGENT FIRE EXTINGUISHERS
427	ELEC-9.4.9	CATEGOR Y- I	Makes: Cease Fire / Minimax
428	ELEC-9.4.10	CATEGOR Y- II	Makes: Safex / Kenex / Bharat / Reliance/NewTech

429	ELEC-9.4.11	CATEGOR Y- I	Makes: Cease Fire / Minimax
430	ELEC-9.4.12	CATEGOR Y- II	Makes: Safex / Kenex / Bharat / Reliance/NewTech
431	ELEC-9.4.13	CATEGOR Y- I	Makes: Cease Fire / Minimax
432	ELEC-9.4.14	CATEGOR Y- II	Makes: Safex / Kenex / Bharat / Reliance/NewTech/Kartar
433	ELEC-9.4.15		Makes: Cease Fire or its equivalent make Model-1ES01
			AEROSOL GENERATION SYSTEM (An alternative to water based sprinkler system)
434	ELEC-9.4.19		Makes: SEAARA/AGS/SALAMANDRA
435	ELEC-9.4.20		Makes: SEAARA/AGS/SALAMANDRA
436	ELEC-9.4.21		Makes: SEAARA/AGS/SALAMANDRA
437	ELEC-9.4.22		Makes: SEAARA/AGS/SALAMANDRA
438	ELEC-9.4.23		Makes: SEAARA/AGS/SALAMANDRA
439	ELEC-9.4.24		Makes: SEAARA/AGS/SALAMANDRA
440	ELEC-9.4.26		Makes: SEAARA/AGS/SALAMANDRA
441	ELEC-9.4.27		Makes: SEAARA/AGS/SALAMANDRA
	ELEC-9.4.30		Makes: Reliance or equivalent approved by APSDR&FS Deptt.
	9.5		FIRE HYDRANT AND SPRINKLER SYSTEM
			ELECTRIC DRIVEN MAIN FIRE PUMPS(SPLIT CASE)
442	ELEC-9.5.1		Makes of Pumps: Kirloskar / Mather&Platt/Lubi/KSB. Makes of Motors: Siemens/ ABB/ Kirloskar/Lubi/KSB.
443	ELEC-9.5.2		Makes of Pumps: Kirloskar / Mather&Platt/Lubi/KSB. Makes of Motors: Siemens/ ABB/ Kirloskar/Lub/KSB
444	ELEC-9.5.3		Makes of Pumps: Kirloskar / Mather&Platt/Lubi/KSB Makes of Motors: Siemens/ ABB/ Kirloskar//Lubi/KSB
445	ELEC-9.5.4		Makes of Pumps: Kirloskar / Mather&Platt/Lubi/KSB. Makes of Motors: Siemens/ ABB/ Kirloskar/Lubi/KSB
446	ELEC-9.5.5		Makes of Pumps: Kirloskar / Mather&Platt/Lubi/KSB. Makes of Motors: Siemens/ ABB/ Kirloskar/Lubi/KSB
			DIESEL ENGINE DRIVEN FIRE PUMPS
447	ELEC-9.5.6		Makes of Engines : Kirloskar / Cummins. Makes of Pumps : Kirloskar / Mather&Platt/KSB
448	ELEC-9.5.7		Makes of Engines : Kirloskar / Cummins. Makes of Pumps : Kirloskar / Mather&Platt/KSB
449	ELEC-9.5.8		Makes of Engines : Kirloskar / Cummins. Makes of Pumps : Kirloskar / Mather&Platt/KSB
450	ELEC-9.5.9		Makes of Engines : Kirloskar / Cummins. Makes of Pumps : Kirloskar / Mather&Platt/KSB
451	ELEC-9.5.10		Makes of Engines : Kirloskar / Cummins. Makes of Pumps : Kirloskar / Mather&Platt/KSB
			ELECTRIC DRIVEN MAIN FIRE PUMPS(END SUCTION)
452	ELEC-9.5.11		Makes of Pumps: Kirloskar / Mather&Platt/Lubi/KSB. Makes of Motors: Siemens/ ABB/ Kirloskar/Lubi/KSB
453	ELEC 9.5.12		Makes of Pumps: Kirloskar / Mather&Platt/Lubi/KSB. Makes of Motors: Siemens/ ABB/ Kirloskar/Lubi/KSB
454	ELEC 9.5.13		Makes of Pumps: Kirloskar / Mather&Platt/Lubi/KSB. Makes of Motors: Siemens/ ABB/ Kirloskar/Lubi/KSB

			DIESEL ENGINE DRIVEN MAIN FIRE PUMPS(END SUCTION)
455	ELEC-9.5.14		Makes of Engines : Kirloskar / Cummins. Makes of Pumps : Kirloskar / Mather&Platt/KSB
456	ELEC-9.5.15		Makes of Engines : Kirloskar / Cummins. Makes of Pumps : Kirloskar / Mather&Platt/KSB
457	ELEC-9.5.16		Makes of Engines : Kirloskar / Cummins. Makes of Pumps : Kirloskar / Mather&Platt/KSB
			JOCKEY PUMPS
458	ELEC-9.5.17		Makes of Pumps : Kirloskar / Mather&Platt/KSB. Makes of Motors : Siemens/ ABB/ Kirloskar/KSB
459	ELEC-9.5.18		Makes of Pumps : Kirloskar / Mather&Platt/KSB. Makes of Motors : Siemens/ ABB/ Kirloskar/KSB
460	ELEC-9.5.19		Makes of Pumps : Kirloskar / Mather&Platt/KSB. Makes of Motors : Siemens/ ABB/ Kirloskar/KSB
			BOOSTER PUMPS
461	ELEC-9.5.20		Makes of Pumps : Kirloskar / Mather&Platt/KSB. Makes of Motors : Siemens/ ABB/ Kirloskar/KSB
462	ELEC-9.5.21		Makes of Pumps : Kirloskar / Mather&Platt/KSB. Makes of Motors : Siemens/ ABB/ Kirloskar/KSB
463	ELEC-9.5.22		Makes of Pumps : Kirloskar / Mather&Platt/KSB. Makes of Motors : Siemens/ ABB/ Kirloskar/KSB
464	ELEC-9.5.23		Makes of Pumps : Kirloskar / Mather&Platt/KSB. Makes of Motors : Siemens/ ABB/ Kirloskar/KSB
			CONTROL PANELS
465	ELEC-9.5.24		Makes Lauritz Knudsen (formerly L&T)- D shine / Schneider-NS NSX/Legrand -DP X3/ Siemens-3VL / Hager-h3/C&S -Winbreak2Makes of Meters : Schneider (Conzerve) / Lauritz Knudsen (formerly L&T) / Elmeasure / Siemens
466	ELEC-9.5.25		Makes Lauritz Knudsen (formerly L&T) / Schneider-NS NSX/Legrand -DP X3/ Siemens-3VL / Hager-h3/C&S - Winbreak2 Makes of Meters : Schneider (Conzerve) / Lauritz Knudsen (formerly L&T) / Elmeasure / Siemens
467	ELEC-9.5.26		Makes: Lauritz Knudsen (formerly L&T) - D shine / Schneider-NS NSX/Legrand -DP X3/ Siemens-3VL / Hager-h3/C&S -Winbreak2 Makes of Meters : Schneider (Conzerve) Lauritz Knudsen (formerly L&T) / Elmeasure / Siemens
468	ELEC-9.5.27		Makes: Lauritz Knudsen (formerly L&T) - D shine / Schneider-NS NSX/Legrand -DP X3/ Siemens-3VL / Hager-h3/C&S -Winbreak2 Makes of Meters : Schneider (Conzerve) / Lauritz Knudsen (formerly L&T) / Elmeasure / Siemens
469	ELEC-9.5.28		Makes: Lauritz Knudsen (formerly L&T) - D shine / Schneider-NS NSX/Legrand -DP X3/ Siemens-3VL / Hager-h3/C&S -Winbreak2 Makes of Meters : Schneider (Conzerve) / Lauritz Knudsen (formerly L&T) / Elmeasure / Siemens
470	ELEC-9.5.29		Makes of MCCBs : Lauritz Knudsen (formerly L&T) / Siemens / Legrand / Schneider / ABB / Hager

			Makes of Meters : Schneider (Conserve) / Lauritz Knudsen (formerly L&T) / Elmeasure / Siemens
			MS PIPES
471	ELEC-9.5.30		Makes: Jindal / Hissar / Tata pipes/Prakash Surya
472	ELEC-9.5.31		Makes: Newage/ Winco/ Padmini / Safex/Minimax/ Newtech/Honeywell/Kartar/Armorfire.
473	ELEC-9.5.32		Makes: Audco / Kirloskar / BDK / H-Shankar / Leader/ Zolotto / SANT/NEU-G/Honeywell//Kartar/Armorfire.
474	ELEC-9.5.33		Makes: BDK / NEU-G / Leader/ Zolotto / SANT/Honeywell//Kartar/Armorfire.
475	ELEC-9.5.34		Makes: Audco / Kirloskar / BDK / H-Shankar / Leader/ Zolotto/SANT/NEU-G/Honeywell//Kartar/Armorfire.
476	ELEC-9.5.35		Make: NEU-G /Zolotto /Padmini /SANT /Honeywell /Kartar /Armorfire.
477	ELEC-9.5.36		Makes: Newage/ Winco/ Padmini / Safex / Minimax /NewTech/Honeywell/Kartar/Armorfire.
478	ELEC-9.5.37		Makes: Newage/ Winco/ Padmini / Safex / Minimax/ NewTech/Honeywell/Kartar/Armorfire.
479	ELEC-9.5.38		Makes: Leader / Zolotto /SANT /Honeywell /Kartar /Armorfire.
480	ELEC-9.5.39		a) 36.6 Mtr Long 20mm (Nominal internal) dia water hose Thermoplastic / Textile reinforced / Rubber braided / Polypropylene Type - 2 as per IS:12585 Makes: Reliance/ Newage/ Safex /NewTech /Winco /Minimax/Kartar/Armorfire b) 20mm (Nominal internal) dia gun metal ball/gate valve and nozzle. Makes:NEU-G/SANT / Safex /Kartar /Armorfire.
481	ELEC-9.5.40		makes:Minimax/Safex/Newage/Winco /Padmini /NewTech /Kartar/Armorfire
482	ELEC-9.5.41 a-b		Makes: Newage/ Winco/ Padmini / Safex / Minimax/NewTech/Kartar/Armorfire.
483	ELEC-9.5.42		. Makes: Newage/ Winco/ Padmini / Safex / Minimax/NewTech/Honeywell/Kartar/Armorfire
484	ELEC-9.5.43		Makes: Newage/ Winco/ Padmini / Safex / Minimax/NewTech/Honeywell/Kartar/Armorfire
485	ELEC-9.5.45		Makes: HD / TYCO / VIKING / NEWAGE/ SHARP / SAFEX/Kartar/Armorfire
486	ELEC-9.5.46		Makes: HD / TYCO / VIKING / NEWAGE/ SHARP / SAFEX/Kartar/Armorfire
487	ELEC-9.5.47		Makes: Danfoss / Indfoss /System sensor/Honeywell
488	ELEC-9.5.48		Makes: System Sensor / Switzer/Honeywell
489	ELEC-9.5.49		Makes: System Sensor / Switzer/Honeywell
490	ELEC-9.5.50		MAKES: HGURU / FIEBIG
491	ELEC-9.5.51		Makes: Zoloto / Leader / SANT/NEU- G/Kartar
492	ELEC-9.5.52		Makes: Zoloto / Leader / SANT/NEU- G/Kartar
493	ELEC-9.5.53		Makes: Zoloto / Leader / SANT/Kartar
494	ELEC-9.5.54		Makes: Tyko/Newage/HD/Kartar
495	ELEC-9.5.55		Makes: HD / TYCO / NEWAGE
496	ELEC-9.5.56		Makes:Normex /SANT/Kartar
497	ELEC-9.5.58		. Make:IWL(PIPE KOT) or its equivalent

498	ELEC-9.5.60		1) DOL Starter Make C&S/ Crompton / Lauritz Knudsen (formerly L&T) /KSP/ Siemens/BCH
			2) Volt meter Make:Conzerve/Elmeasure/ Meco/ HPL/ Lauritz Knudsen (formerly L&T) / Socomec /Legrand
			3) AmmeterMake: Conzerve/Elmeasure/Meco/HPL/ Lauritz Knudsen (formerly L&T) / Schneider/AE/ Socomec /Legrand
			4) selector switch Make: Lauritz Knudsen (formerly L&T) / C&S/ Salzer/HPL
			5) Single Phase Preventor Makes: Lauritz Knudsen (formerly L&T) / Minilec / Powertec. - 1No.
			6) capacitor Makes: Lauritz Knudsen (formerly L&T) / Siemens / Schneider / Epcos/Havells/Legrand.
			7) MPCB (Motor Protection Circuit Breaker) Makes: Lauritz Knudsen (formerly L&T) - D shine / Schneider- NS NSX/Legrand -DP X3/ Siemens-3VL.
			8) ON/OFF/TRIP push button actuators and integral contact block of dia. 22.5 mm i Make:Seimens/ ABB/ Schneider/ Lauritz Knudsen (formerly L&T) / C&S/HPL
			9) power contactor Make: Seimens/ABB/ Schneider / Lauritz Knudsen (formerly L&T) /C&S /HPL /Havells/Legrand - 3 pole, 35-40A AC3 Rating, Contactor
			10) thermal over load relay Make:Seimens/ABB/Schneider/ Lauritz Knudsen (formerly L&T) /C&S/HPL/Havells/Legrand - 1 No
			11)Current Transformer Make: Kappa/ Lauritz Knudsen (formerly L&T) / Seimens/ C&S/ Schneider - 3 No
499	ELEC-9.5.61		Makes: Newage/ Winco/ Padmini / Safex / Minimax/NewTech/Honeywell/ Kartar.
500	ELEC-9.5.62		Makes: HD / TYCO / VIKING / NEWAGE/ SHARP / SAFEX/ KARTAR
501	ELEC-9.5.63		Makes: Audco / Kirloskar / BDK / H-Shankar / Leader/ Zolotto /SANT/NEUG/Honeywell/ Kartar
502	ELEC-9.5.64 a to e		Makes: Audco / Kirloskar / BDK / H-Shankar / Leader/ Zolotto / SANT/Honeywell/ Kartar
503	ELEC-9.5.65		Makes: Audco / Kirloskar / BDK / H-Shankar / Leader/ Zolotto / SANT/Honeywell/ Kartar
504	ELEC-9.5.66		Makes: HD / TYCO / VIKING / NEWAGE/ SHARP / SAFEX
505	ELEC-9.5.67		. Makes: HD / TYCO / VIKING / NEWAGE/ SHARP / SAFEX
506	ELEC-9.5.69		Make of motor: Crompton, Kirloskar, Texmo, KSB,CRI, Suguna with ISI mark. Pump:Green tech,Kisan,Ultrajet, Pressurejet, Ambica tools, Seaara or any ISI
507	ELEC-9.5.70		Make Petrol engine: Honda, Kisan, Yamaha
508	ELEC-9.5.71		Make of motor: Crompton, Kirloskar, Texmo, KSB,CRI, Suguna with ISI mark. Pump:Green tech,Kisan,Ultrajet, Pressurejet, Ambica tools, Seaara or any ISI
	10.1		GENERATORS SPECIFICATION

509	ELEC-10.1.1 a - i		Engine Makes:Cummins/Koel Green/Sterling/ mahindra/Elmot Power Gen/Ashok Leyland/Greaves Alternator Make:Stamford/ Kirloskar/ CromptonGreaves/Leroysomer
510	ELEC-10.1.1 j - n		Engine Makes:Caterpillar/Cummins/Koel Green/Mahindra/Elmot power Gen/Ashok Leyland/Greaves Alternator Make:Leroy somer/Crompton Greaves/Stamford
511	ELEC-10.1.1 o- t		Engine Makes: Caterpillar/Perkins/Cummins/Greaves/KOEL Alternator Make:Leroy somer/Crompton Greaves/Stamford
	ELEC-10.1.5 a - i		Engine Makes:Cummins/Koel Green/Sterling/ mahindra/Elmot Power Gen/Ashok Leyland/Greaves Alternator Make:Stamford/ Kirloskar/ CromptonGreaves/Leroysomer
	ELEC-10.1.5 j - n		Engine Makes:Caterpillar/Cummins/Koel Green/Mahindra/Elmot power Gen/Ashok Leyland/Greaves Alternator Make:Leroy somer/Crompton Greaves/Stamford
	ELEC-10.1.1 o- t		Engine Makes:Caterpillar/Perkins/Cummins/Greaves/KOEL Alternator Make:Leroy somer/Crompton Greaves/Stamford
	11.1		INVERTERS and ONLINE UPS SYSTEMS
512	ELEC-11.1.1		Makes: Exide / Amar Raja / Samhitha/ Microtek
513	ELEC-11.1.2		Makes: Numeric/APC/Fuji Electric/ Sakshham /Emerson/Techser.
514	ELEC-11.1.3		Makes: Numeric/APC/Fuji Electric / Sakshham /Emerson/Techser.
515	ELEC-11.1.4		Makes: Mitsubishi/ Socomec /Schiender(APC)/ Legrand/Fuji Electric (Consul Neowatt)
516	ELEC-11.1.9		Makes: Quanta / Racket / Exide.
517	ELEC-11.1.10		Makes: Quanta / Racket / Exide.
518	ELEC-11.1.11		Makes: Quanta / Racket / Exide.
519	ELEC-11.1.12		Makes: Quanta / Racket / Exide.
520	ELEC-11.1.13		Makes: Quanta / Racket / Exide.
521	ELEC-11.1.14		Makes: Quanta / Racket / Exide.
522	ELEC-11.1.15		Makes: Quanta / Racket / Exide.
523	ELEC-11.1.17		Makes: Amar Raja (Power Zone) or Equivalent model of Exide / Panasonic / Gotech.
	ELEC-11.2.1		Makes: Fuji Electric / Numeric/APC(Schneider)
	13.1		LIFTS (New Installation)
524	ELEC-13.1.1		Makes: Kone/Otis /Schindler /Mitsubishi /Johnson /ThyssenKrupp/Fujitec
525	ELEC-13.1.2		Makes:Kone /Otis /Schindler /Mitsubishi /Johnson /ThyssenKrupp/Fujitec
526	ELEC-13.1.3		Makes:Kone /Otis/Schindler/ Mitsubishi/Johnson/ ThyssenKrupp /Fujitec
527	ELEC-13.1.4		Makes:Kone/Otis /Schindler/Mitsubishi/Johnson

			/ThyssenKrupp /Fujitec
528	ELEC-13.1.5		Makes:Kone /Otis/Schindler/Mitsubishi /Johnson /ThyssenKrupp/Fujitec
529	ELEC-13.1.6		Makes:Kone /Otis/Schindler /Mitsubishi/Johnson /ThyssenKrupp/Fujitec
530	ELEC-13.1.7		Makes:Kone /Otis /Schindler /Mitsubishi /Johnson /ThyssenKrupp/Fujitec
531	ELEC-13.1.8		Makes:Kone /Otis /Schindler /Mitsubishi /Johnson /ThyssenKrupp/Fujitec
532	ELEC-13.1.9		Makes:Kone/Otis/Schindler/Mitsubishi/Johnson/Thyssen Krupp/Fujitec
			SECTION- 14 (Electrical items recommended by Chief Engineer (APMSIDC)
			MEDICAL GAS PIPE LINE SYSTEM
533	ELEC-14.1.1 to 14.1.10		Make: IBP Conex / Maxflow
534	ELEC-14.1.11 to 14.1.19		Makes: Aktiv Technologies// Atlas Capco/ Draeger Medical/ / Airox Technologies / Aastha Medical technologies/ GMP Technical Solutions / Medicare gas pipe line/Mediline Engineers
535	ELEC-14.1.20/ 14.1.21		Make: Siemens / Johnson Controls / Medicare gas pipe line/ Mediline Engineers/ Aktiv Technologies// Atlas Capco/ Draeger Medical/ / Airox Technologies
			STP & ETP WORKS (Electro-Mechanical items)
536	ELEC-14.2.1 to ELEC-14.2.5		Fabricated item as per specification with SOR approved makes of MS/SS
537	ELEC-14.2.6 to ELEC-14.2.8		Fabricated item as per specification with SOR approved makes of MS/SS
538	ELEC-14.2.9/ 14.2.10		Make: Kay/Everest/Swan/A1/Jyothi Airtech/ Crystal Air/Kruger/ System Air/ Carry Air / Aerotech
539	ELEC-14.2.11		Make: MettlerToledo/Aster/Transformium Engrs/Konvio
540	ELEC-14.2.12/ 14.2.13		Makes: Rehau/OTT/SSI/Aquaflex/Techpro/Shridevi /Sreetech
541	ELEC-14.2.14 to ELEC-14.2.17		Makes: Kishor/KSB/Grundfos/CRI/Wilo/Kirloskar
542	ELEC-14.2.18/ 14.2.19		Fabricated item as per specification with SOR approved makes of MS/SS with reputed brands of Motor like Kirloskar/KSB/Texmo/CRI/Crompton
543	ELEC-14.2.20 to ELEC-14.2.21		Makes: Kay/Everest/Swan/A1/Jyothi Airtech/ Crystal Air/ System Air/ Carry Air / Aerotech
544	ELEC-14.2.22/ 14.2.23		Pipes as per specification with SOR approved makes of MS/ SS
545	ELEC-14.2.24		Makes: Rehau/OTT/SSI/Aquaflex/Techpro/Shridevi /Sreetech/ MM Aqua/ Tecpro/Enery Equipment
546	ELEC-14.2.25 to ELEC-14.2.28		Makes: Kishor/KSB/Grundfos/CRI/Wilo/Kirloskar

547	ELEC-14.2.29 to ELEC-14.2.31		Make: ShivPAD/Eimco-KCP/PicoPuro/Voltas
548	ELEC-14.2.32 to ELEC-14.2.34		Make: Johnson/Kirloskar/KSB/Grundfos/CRI/Wilo
549	ELEC-14.2.35/14.2.36		Make: Hitech/Sukrut/Ultra Aqua/Philips/Equivalent
550	ELEC-14.2.37/14.2.39		Makes: Kishor/KSB/Grundfos/CRI/Wilo/Kirloskar
551	ELEC-14.2.40 to ELEC-14.2.2.43		Makes: Sreetech/Fluid Systems/Anju Enterprises/Any approved make
552	ELEC-14.2.44/14.2.45		Makes: Verito Engineering/Fluid Systems/ Fabricated item as per specification with SOR approved makes of MS/SS with reputed brands of accessories
553	ELEC-14.2.46/14.2.48		Makes: Kishor/KSB/Grundfos/CRI/Wilo/Kirloskar
554	ELEC-14.2.49		Make: PD pumps / Rotomac / Alpha helical /Roto
555	ELEC-14.2.50/14.2.51		Make: Hydro Press/Yo-Tana/Amar.
556	ELEC-14.2.52		Makes: Verito Engineering/Fluid Systems/ Fabricated item as per specification with SOR approved makes of MS/SS with reputed brands of accessories
557	ELEC-14.2.53		Make: MM Machinery/Safex electro mech/Vertex Cranes/Df Hoist/Reva Cranees/Aditya or any reputed brand
558	ELEC-14.2.54		Make: MM Aqua/ Tecpro/Enery Equipment/Rehau/ OTT/ SSI/Aquaflex/Techpro/Shridevi /Sreetech
559	ELEC-14.2.55 to ELEC-14.2.61		As Per Approved Makes in SOR for uPVC/D.I./KSC Pipes/ Reputed makes with ISI
560	ELEC-14.2.62/14.2.63		Makes: Metlor Tolodo/Vector Technologies/Lutron/Spectra Labs/Kytola/Any reputed brand with ISI
561	ELEC-14.2.64		Makes: HGURU / FIEBIG and Approved makes with ISI
			BUILDING MANAGEMENT SYSTEMS
562	ELEC-14.3.1/14.3.2		Makes HP/IBM/DELL
563	ELEC-14.3.3 to 14.3.17		Make: - Honeywell / Siemens/ Schneider/Johnson Controls/Delta
564	ELEC-14.3.18/14.3.19		Lauritz Knudsen (formerly L&T) /ABB/Meco/Schneider/Siemens
565	ELEC-14.3.20/14.3.21		Make: Honeywell / Siemens/ Schneider/Johnson Controls/Delta
			ACCESS CONTROL SYSTEM
566	ELEC-14.4.1 to 14.4.9		Makes - matrix/Honeywell/ESSL/Siemens /Delta/JohnsonControls /Bosch
567	ELEC-14.4.10/14.4.11		Make : Rosslare/Software house/Spectrum
			NURSE CALLING SYSTEM
568	ELEC-14.5.1		Deleted

GUIDELINES FOR ELECTRICAL WORKS

PREFACE

Electrical supply and installation are an important and essential part of Building Services. Right from initial planning, design, selection of material, installation / method of construction; to testing, commissioning and maintenance; every aspect is governed by statutory provisions referring various Standards and Codes. All such norms are oriented to minimize risk, provide safe use, operation, functionality, and convenience throughout service life.

Any lapse in any of the above aspect may lead to severe effects on human life and devastation of assets. Occasions of electrical fires are increasing with the increasing use and electrical gadgets. Unfortunately, still it is seen that Electrical Installation is given least importance. Qualities and safeties are compromised out of connivance or lack of technical knowledge. Many times, electrical work gets executed through non-qualified persons not having required knowledge and Permit in that regard. Such hired persons work on labor basis to whom non-standard material is supplied without any base of 'Design'. There is no person to supervise quality and safety aspects, most of which remains 'concealed' as the work gets completed.

In case of High-Rise buildings norms are more stringent. Fire hazard is more prominent risk factor as evacuation in high-rise building is a challenging task. Part 3 section 7 of NEC gives special guidelines in this regard.

The person who uses, operates electrical installation is not expected to know the real technical aspects of design, material used, quality of work, adherence to safety, compliance with statutory provisions. Under the circumstances it has become a need to set base line parameters. Plug the loopholes, get the work done adhering to norms and standards and make someone responsible so that in case of any lapse / mishap such person / agency can be made answerable.

Important Note:

1. SSR rates for Electrical items are purely for guidance of the officers in preparation of estimates vide Para 113 of APPWD Code. Authority who prepares the estimate is, however responsible for proper rates as envisaged in Para 45 of APPWD Code.

2. The rates published in the Buildings SoR 2025-26 are the ceiling rates only and the estimate preparing authorities are responsible for the correctness and reasonableness of the rates and technical specifications adopted in the estimates

The following guidelines / recommendations / mandates are basically given to execute work of Electrical Installation.

1. ARCHITECTURAL / CIVIL WORK PROVISIONS RELATED TO ELECTRICAL INSTALLATION

1.1 Architectural Planning requirements:

At planning stage Architect shall discuss and consider requirements of Electrical Consultant /

Contractor in respect with site and location of construction and in respect with drawings of building requirement of spaces, clearances, approach ways, raceways, shafts, recommended wall thickness, required provisions for prevention from fire hazard likely to originate from electrical installation.

If proposed construction is within vicinity of existing over-headline, underground cable compliance with Regulation 63 of CEA Safety Regulations shall be checked prior to commencement of any work on site.

Architect shall incorporate following points in the drawings related to services as per the applicable requirements.

1.1.1 Site Plan:

Site plan shall show existing overhead electrical lines / underground cables if any and proposed construction within the boundaries of the area to be developed.

1.1.2 Routes and service entry points:

Architectural drawings shall clearly mark electrical service entry points, cable routes below ground, through the building structure, so that detailing in electrical shop drawings will restrict the work within specified route and no conflict shall occur with other building utility service. The drawings shall specify required horizontal and vertical clearance to be maintained between other utility services.

1.1.3 Locations of Electrical Panels:

Locations and position for main and sub electrical panels shall be marked, and adequate space / room shall be allocated considering dimensions of panel, clearance in front, side and back. Consideration shall be given to space required for opening of the panel doors / racking out breakers, and approach boundaries (Refer NEC Part1 / section 24 Electrical Safety), and accessibility. Floor mounting panels shall preferably be located in separate Electrical Panel Rooms having outside door opening, required fire rating (two hours if not specified) and ventilation arrangement.

NOTE – Special consideration shall be given to this point in case of High-Rise buildings.

1.1.4 Electrical meter rooms:

Meter rooms shall be separate. It shall be planned to have sufficient head room and clear space in front of meters, control switches (at least 1m). Space on wall shall be sufficient to accommodate required number of meters at suitable height so that readings can be taken without aid of any tackle. Also, the switchgears shall be at least 0.5 m above floor level and within such height to have an easy access for operation. The meter room shall be well ventilated, protected from external influences like sun, rain, water seepages, entry of rodents. Location of meter room shall be suitably adjacent or nearest to cable duct / shaft / vertical route of mains.

NOTE – Meterroomsshall not be located below staircaseswhere above requirements could notbecomplied with.

1.1.5 Movement of heavy / bulky electrical equipment:

For installation of electrical equipment within building which is likely to be heavy / bulky in size or

removing it for maintenance, provision of adequate passages, stair ways or any alternate provision for its shifting / movement shall be considered.

1.1.6 Shafts /ducts:

There shall be provision of shafts with required fire rating (2 hours if not mentioned specifically) for vertical electrical distribution which shall preferably be adjacent to electrical panels. Shafts shall be separate for electrical HT cables, LT power cables / bus-bar trucking and cable work of Extra Low Voltage systems like telephones, security system, fire alarm, signaling, BMS or data networking etc. If independent shaft is not possible, there shall be an arrangement for segregation in between, which shall have required fire rating same as that of shaft. No other utility service shall run through these shafts. Shafts shall be accessible at all levels with doors having fire rating as that of shaft and shall not open in fire escape staircase. All shafts shall have fire prevention provision as per National Building Code and fire safety requirements of local statutory authorities.

NOTE- As per CEA Reg.36 provision in respect of independent electrical service shaft is mandatory for all buildings above 15m height (High-Rise buildings).

1.1.7 Interior design and Electrical Layouts:

It is recommended to prepare interior layouts so as to plan electrical points, locations of switch boards to suite the aesthetics, functionality as well as for comfort and ease of operation.

1.1.8 Aesthetics and Electrical Safety

To avoid conflicts between Architect from perspective of aesthetic and person executing electrical installation work from the point of view of safety requirements of electrical work, convenience and ease of installation and further maintenance depending on type of wiring (concealed / surface / hybrid), location of distribution boxes, requirement of under-floor trunking / false flooring / false ceiling, wall partitions and openings to enter into / work within as per the need. These points shall be decided at planning stage.

1.1.9 Illumination

Within interior work number, type, size, and location of luminaries shall be decided and agreed upon mutually between Architect and Electrical Agency, considering technical parameters of lux level, CCT, heat dissipation, accessibility and maintainability.

1.1.10 Ceiling Fans

Location of ceiling fans shall suite recommended minimum clearance between ceiling / false ceiling and fan blade (225mm), floor level and fan blade(2400mm).Sweep of fan blades shall not obstruct light source. Location and size of fan shall also suite utility from the point of view of users and aesthetically match with false ceiling design.

NOTE: Sometimes due to afterthought provision of false ceiling, it creates problems affecting required clearances. Under some cases, replacement of down rod with suitable length may solve problem but in case of limited ceiling height it is not possible.

1.1.11 Exhaust fans

Wherever provision of exhaust fans is there, cross ventilation shall be considered to allow sufficient fresh air to enter into particular envelop, e.g. For toilets where

Exhaust fans are proposed, door under cuts or louvers preferably at lower level for cross ventilation shall be provided.

NOTE: Non provision of entry for fresh air creates negative pressure within the envelope increasing load on exhaust fan resulting into heating and subsequent failure.

1.1.12 Earthing

Location of earthing pits shall be shown on drawings so that those shall always remain open and accessible for testing and maintenance throughout the service period.

1.1.13 Restricted Access

Areas requiring restricted access to designated person, authorized to carry out electrical work therein shall be provided with necessary arrangements.

1.1.14 Sub stations / Generators / Battery rooms

Location of required civil structure shall be considered in advance with required height of room, door openings, firefighting system, ventilation etc.

1.2 Civil Planning and Constructional Requirements

It is important to plan activities of civil construction and electrical works in detail on bar chart or similar tools available in project planning. The bar chart shall be updated and coordination be monitored to avoid conflicts, breakages and reworking. Following points give general guidelines.

1.2.1 Fire rating

The electrical panel rooms, doors, segregation arrangement within shaft shall have fire rating of 2 hours or as per requirements mentioned under NBC, Central Electricity Authority (measures related to Safety and Electric Supply) Regulations, 2010 and further amendments.

1.2.2 Shafts / Ducts / Chambers

Design and location of cable ducts, shafts, chambers, their covers, and entry points, shall be as per shop drawings provided by electrical agency and shall be in consultation with, considering further aspects of maintenance / repairs / replacement. Size of chambers shall be in consideration with bending radii of cables. At every flooring level, there shall be a provision to seal these shafts, so that in case of fire, it shall not spread, or smoke shall not pass from one floor to other.

1.2.3 Openings and covers

Manholes / opening of chambers shall not be less than 650mm x 550mm or 650mm India., where opening is intended for entry of person. Covers of manholes, chambers shall bear sufficient strength to withstand loads likely to be imposed on the structure. Covers shall be marked with the name of the service.

Openings / covers of Junction boxes / draw-in boxes / accessories in conduit systems with inspection openings shall always be accessible.

1.2.4 Enclosures for underground cables

Pipes to be used for cable as enclosures shall be of required diameter so that cable can pass through or removed from easily and have sufficient mechanical strength and shall be erected at required depth to suite requirements of IS 1255.

1.2.5 Wall thickness

Walls shall be of sufficient thickness to accommodate concealed boxes /switchboards / distribution boxes. So that installation of boxes will not affect strength of wall. Additional strengthening shall be considered if necessary.

NOTE : Depth of box may be 60 mm or vary depending on manufacturer's design. Under circumstances in 4"/100 mm wall it is not possible to accommodate these boxes back-to-back. Staggering may solve problem to certain extent.

1.2.6 Structural strength

In Wiring Installation where Cable Ladder, Tray system is used for cable management, its structure along with the load of cables which it is going to support, is likely to impose load on the primary structure of building. This situation occurs when supports of this system are fixed on building structure. For this building structure shall have capacity to bare the load.

At some locations there are chances of conduits getting crowded endangering structural strength due to number of circuits entering / passing out from the particular DB / panel. This situation may occur in beam, slab, and wall. If such situation is unavoidable necessary measures may be required to be taken to retain structural strength.

1.2.7 Sleeves / core cutting

As far as possible sleeves shall be got erected for entry of wires / cables through wall, flooring, RCC structure during construction to avoid core cutting, damages and reworking at finishing stage. Sometimes core cuttings may be required which shall be done with the consent of structural engineer and under supervision of civil engineer.

1.2.8 Water leakages / seepages

Design shall take into consideration possible seepages, leakages, accumulation, and ground in-surge of water, which is hazardous to electrical installation. Required provisions shall be made at such locations to prevent and work shall be executed with due care.

1.2.9 Bathrooms / washrooms

Within bathrooms / washrooms, location of showers, faucets shall be such that during use, water shall not splash on switch boards / electrical outlets / fittings.

1.2.10 Tandems in Flat Slab post tension structures

For flat slab post tension structure's locations of tandems marking shall be made to avoid puncture of / damage to tandems during electrical construction activity.

1.2.11 Earthing

Any construction work, including excavation, subsequent to construction of earthing electrode/s ; it shall not disturb / damage any part of earthing system. Any civil work on construction site shall not cause cover-up / concealing of any portion of electrical earthing system without notice

and consent of person In- Charge of electrical work.

1.2.12 Sub stations / Generators / Batteries

Trenches, ventilation, approach roads shall be provided as per necessity.

2. ELECTRICAL PROVISIONS

2.1 Statutory Obligations – Appointment of Licensed Electrical Contractor

Reg .29(1) shall be strictly followed by the Developer and work shall be got done through Licensed Electrical Contractor who shall submit Test Report of the work carried-out by him.

Developer may take undertaking from the Licensed Electrical Contractor, who shall be responsible to do the work through the qualified workmen having required permit in that regard. He shall also see that the material to be used, work and workmanship shall conform to respective norms, standards, and Regulations.

NOTE–All hidden work shall be checked for conformity with the standards prior to get it concealed, shall be certified by the contractor.

2.2 Statutory Obligations–Approvals /Permissions / Licenses

Required approvals shall be taken as per related Rules and Regulations mentioned below prior to the commissioning and handing over the installation for beneficial use.

- a) Central Electricity Authority (measures related to safety and electric supply) Regulations 2010 and amendments 2015, 2018
- b) Reg. 32 – Generator Inspection and approval for commissioning.
- c) Reg. 36 – Multi-storied building (height above 15m): inspection and NOC for commencement of supply
- d) Reg. 43 –Transformer sub-station or any installation above 660V : inspection and approval before commencement of supply

See Annexure C of above regulations for extract of Regulations.

2.3 Material

Material used for Electrical Installation shall conform to the respective Indian standards or International standards where relevant Indian Standards are not available.

Technical Specification of material shall strictly adhere to the design, based on load, use, external influences and safety.

2.4 Wiring Installation

Electrical Installation shall conform to provisions from related sections of National Electrical Code (NEC) and National Building Code (NBC). See Annexure A for minimum / basic requirements from the point of view of Safety and functionality.

2.5 Transformer sub-station

Transformer sub-station providing supply to the building if located within building shall either use dry type transformer or a transformer filled with Synthetic Ester. Transformer filled with Natural ester shall be used only if transformer is sealed (without breather). For Transformer installed in separate room detached from building structure 7.5m away Mineral oil may be allowed.

2.6 Generator standby supply

For every high-rise building there must be a provision of generator supply as a standby arrangement which shall be of adequate capacity to cater load of all emergency systems for required time. Location and system of supply shall be such that functioning, and purpose of Generator will not be affected due to emergency like fire in building. If fire authority requires standby supply arrangement for fire-fighting system also, provision of generators shall be made accordingly.

2.7 Handing over Documents

It shall be a part of obligation on the developer to handover the documents belonging to the prospective owner for his information and which he will need him for reference and maintain as a record.

2.8 MCBs

For lighting circuit 6A MCB and for power circuit of power point 16A MCB shall be used. For lighting circuits MCBs of B series may be used. For independent circuit of plug points C series MCB shall be provided. Circuits providing supply for appliances like Air-Conditioner / water-pump shall be provided MCBs of 'C' series. AC above 1.5 TR may be provided with MCB of 20 / 25 A rating.

2.9 RCDs

Complete electrical installation must be protected against electrical shock by provision of Residual Current Device (also referred as ELCB/RCCB) having sensitivity of 30mA. RCDs may be provided more than one at suitable locations, to retain supply redundancy. In three phase DBs per phase protection may be provided. For installation having load 10kw and above, it is also recommended to provide RCD of 300mA sensitivity at the source / point of supply to provide protection against Fire due to leakage currents.

2.10 Main switchgears

Depending on load provision of MCCBs, Circuit breakers shall be made with precise rating of overload, short-circuits etc.

3. Provision in respect of High-Rise Building

3.1 Supply isolation during Emergency Sub Regulation (3) of CEA Regulation No.36 provides for arrangement to completely isolate the supply at the time of emergency. It shall be interpreted as below:

3.2 The provision of a device to isolate complete supply, also called Fireman's Switch, is aimed at restricting further danger of short circuits due to fire and spread of fire and shock hazard, restriction on use of Lifts and any other activity running on electrical supply which may aggravate the situation. However supply to emergency services like rescue operation; Fire-Fighting

shall not get affected with the operation of this control.

3.3 Suitable arrangement shall be done at the point of supply to separate supply of emergency services make arrangements to identify and mark with instructions

CEA (Measures related to Safety and Electric Supply) Regulations 2010 made under section 53 read with section 177 of Electrical Act 2003 Regulation 29 (1):

No electrical installation work, including additions, alterations, repairs and adjustments to existing installations, except such replacement of lamps fans, fuses, switches, domestic appliances of voltage not exceeding 250V and fittings as in no way alters its capacity or character, shall be carried out upon the premises of or on behalf of any consumer, supplier, owner or occupier for the purpose of supply to such consumer, supplier, owner or occupier except by an Electrical Contractor licensed in this behalf by the State Government and under the direct supervision of a person holding a certificate of competency and by a person holding a permit issued or recognized by the State Government.

3.4 Regulation 12 (1):

All electric supply lines and apparatus shall be of sufficient rating for power, insulation and estimated fault current and of sufficient mechanical strength, for the duty cycle which they may be required to perform under the environmental conditions of installation, and shall be constructed, installed, protected, worked, and maintained in such a manner as to ensure safety of human beings, animals and property.

3.5 Regulation 12 (2):

Save as otherwise provided in these regulations, the relevant code of practice of The Bureau of Indian Standards or National Electrical Code, if any, may be followed to carry out the purposes of this regulation and in the event of any inconsistency, the provisions of these regulations shall prevail.

3.6 Regulation 12 (3):

The material and apparatus used shall conform to the relevant specifications of the Bureau of Indian Standards or International Electro-Technical Commission where such specifications have already been laid down.

3.7 Regulation 12 (4):

All electrical equipment shall be installed above the Mean Sea level (MSL) as declared by local Municipal Authorities and where such equipment is to be installed in the basement, consumer shall ensure that the design of the basement should be such that there is no seepage or leakage or logging of water in the basement.

3.8 Regulation 3 phases Provisions for supply and use of electricity in multistoried building more than 15 meters in height: Regulation 36 (3). The supplier or owner of the installation shall provide at the point of commencement of supply a suitable isolating device with cut-out or breaker to operate on all phases except neutral in the 3-phase, 4-wire circuit and fixed in a conspicuous position at not more than 1.70 meters above the ground so as to completely isolate the supply to the building in case of emergency.

a) Color Coding for Phase / Live – Red / yellow / Blue

- b) Color Coding for Neutral – Black
- c) Color Coding for Earth – Green
- d) For light / bell wiring shall be two wire system .
- e) For ceiling fan / exhaust fan / Separate socket wiring shall be three wire system .

Circuit main for switch boards:-

Circuit main for switch board shall be 3 runs of 2.5sq.mm copper cable i.e for phase, neutral and Earth. That is from DB to switch board.

Circuit Main for 16A socket :-

Circuit mains for 16A sockets shall be 3 runs 4.0sq.mm from DB to 16A socket. Phase, neutral and earth conductor are equal in size (i.e sq.mm).

Circuit Main for AC socket:-

Circuit mains for AC socket shall be 3 Runs of 6.0sq.mm from DB to AC socket. Phase, neutral and earth conductor are equal in size (i.e sq.mm).

Note: Power circuit rated more than 1KW, size as per calculations.

Capacity of Circuits:

- I Lighting circuits shall feed light / fan / call bell points. Each circuit shall not have more than 800W
Connected load or more than 10 points. In case of LED lights, where load per point may be less, number of points may be suitably increased.
- II Power circuit in NRB will have only one outlet per circuit.
- III Each power circuit in residential buildings can feed following outlets.
Not more than 2 No's 16A socket outlets.
Not more than 4 No's 6A/ 10A socket outlets.
c) Not more than 1 No 16A & 2Nos 6A outlets.
- IV Load more than 1 KW shall be controlled by suitable rated MCB, and cable size shall be decided as per the load calculations and length of circuit mains.
- V. Load shall be distributed equally among the three phases.