

# Flexipath Covid-19




Lightweight, slip-resistant delineated walkway and safety stand zone matting for visitors, customers and employees



Implement social distancing measures quickly and easily with Flexipath Covid-19, a single-tier, lightweight walkway mat with delineated stand zones in alternating color blocks.

As Covid-19 lockdown restrictions begin to ease, many businesses face the challenge of continuing or restarting operations while complying with social distancing measures. Our Flexipath Covid-19 matting has delineated stand zones that allow customers, visitors and employees to easily observe social distancing rules.

The mat's alternating color blocks makes it ideal for businesses with queuing customers or workplaces with standing employees. The lightweight construction means the mat is quick to install and easy to move if needed.



## Features:



Etched surface



Open-grid construction




Resistant to most acids, alkali and oils



Single tier, lightweight construction



Comes in rolls of up to 84' (24m)



## Benefits:



Certified slip resistant (ASTM 1677: 1.0/0.8)



Excellent drainage (DIN 51130:V10)



Easy to clean



Contours to uneven surfaces and comfortable to stand on



Quick to install and move if needed



## Plastex Matting Inc.

120 55th St NE  
Fort Payne, AL 35967  
+1 256 845 7725

USA + UK manufactured matting products:  
[plastexmatting.com](http://plastexmatting.com)

# Flexipath Covid-19

## Data sheet



### Standard sizes:

Product	Flexipath Covid-19
Height	1/4" (6mm)
Standard roll options	84' x 18" (24 x 0.45m)
	84' x 2' (24 x 0.6m)
	84' x 3' (24 x 0.91m)
Weight	0.76 lb/sq.ft (3.70 kg/m2)


### Standard colors:




Black



Blue



More colors available upon request



# Flexipath Covid-19

## Data sheet



### Installation:

Flexipath's one-piece construction means installation is simple:

- Comes in rolls of up to 84'
- Place where needed and unroll
- No special tools or previous site visits needed
- Contours to uneven surfaces

### Cleaning:

Flexipath's lightweight, open-grid construction makes it easy to clean:

- Simply lift or roll to clean
- Easy to clean with a high pressure hose

### Technical information:

<b>Acoustic</b>	Excellent sound absorption
<b>Chemical</b>	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this <a href="#">information sheet</a> .
<b>Composition</b>	Flexible Polyvinyl Chloride (PVC)
<b>Environment</b>	Flexipath Covid-19 is 100% recyclable. We don't use any substances included in the SVHC list under REACH in any of our matting products.
<b>Fire</b>	EN13501-1 : 2007 and classified - Cf1 - S1
<b>Hygiene</b>	Made from non-porous PVC that's naturally resistant to bacteria growth.
<b>Reversion</b>	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by <a href="#">downloading this information sheet</a> .
<b>Slip resistance</b>	ASTM F 1677 - Dry/Wet: 1.0/0.8 DIN51130: RI 1, V10 DIN51097: Classification C
<b>Thermal</b>	Designed to function at temperatures from -9°F and up to +140°F. Slight size variation may occur at temperature extremes
<b>UV light</b>	Resistant to PVC degradation. The red colour isn't colourfast in direct sunlight.
<b>Warranty</b>	One year. Visit our <a href="#">policies page</a> for more information about warranties