



## AUTOMATE™ | Motor Tube Compatability

			LIFTING CAPACITY																									
			RA 1"		RA 1-1/8"		RA 1-1/4"		RA 1-1/2"		S45 Light		S45 Standard		S45 Heavy Duty		RA 2" Ribbed		RA 2" Smooth		S60		RA 2-1/2"		RA 3-1/4"		S80	
			lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg
<b>Automate™ Mtoro Models</b>																												
<b>Motor Torque (Nm)</b>	0.20	MTDCBRF18-0.2 MTDCRF18-0.2	3.5	1.6	3.1	1.4																						
	1.10	MTDCBRF25-1.1 MTDCRF25-1.1 MTDCBSW25-1.1			15.6	7.1	13.0	5.9	11.5	5.2	11.2	5.1	10.1	4.6														
	2.00	MTDCBRFQ28-2 MTDCRFQ28-2					23.6	10.7	20.9	9.5	20.4	9.3	18.4	8.3	17.7	8.0												
	3.00	MTDCBRF35-3 MTDCRF35-3 MTDCBRFQ45-3 MTDCRFQ45-3							31.4	14.2	30.7	13.9	27.5	12.5	26.6	12.0												
	6.00	MTACRF35-6 MTACRF35-6LC MTACQRF35-6 MTACML35-6 MTACQML35-6							62.7	28.5	61.3	27.8	55.1	25.0	53.1	24.1												
	10.00	MTDCBRF45-10 MTDCRF45-10 MTACQRF45-10 MTACQRF45-10LC MTACQ45-10-M															88.5	40.1	74.9	34.0	70.8	32.1	56.2	25.5	56.2	25.5		
	15.00	MTACRF45-15															132.8	60.2	112.4	51.0	106.2	48.2	84.3	38.2	84.3	38.2		
	20.00	MTAC45-20-M															177.0	80.3	149.9	68.0	141.6	64.2	112.4	51.0	112.4	51.0		