



Non-Ferrous Cutting Saws

A specially formulated carbide makes cutting all kinds of non-ferrous metal simple and easy. Cut sheets, extrusions, or light solids of aluminum, copper, and brass. Clamp material firmly and lubricate blade with cutting fluid. **Do not use on steel or other ferrous metals.**

DIAMETER	TEETH	DESIGN	KERF	PLATE	BONE & PIMS	HOOK	ORDER #
3 7/8"	20T	TCG	.134"	.110"	3/8"	5	NF3782038
4"	20T	TCG	.095"	.062"	3/4"	0	NF420Q
4 1/2"	20T	TCG	.095"	.062"	3/4"	0	NF45020Q
7 1/4"	40T	TCG	.118"	.087"	5/8"	-5	NF72540
7 1/4"	60T	TCG	.087"	.058"	5/8"	0	NF760
8"	48T	TCG	.126"	.094"	5/8"	-5	NF848
8"	60T	TCG	.126"	.094"	5/8"	-5	NF860
8"	80T	TCG	.130"	.083"	5/8"	5	NF880
8 1/2"	60T	TCG	.102"	.071"	5/8"	-5	NF85060
9"	60T	TCG	.134"	.102"	5/8"	-5	NF960
250mm	80T	TCG	3.0mm	2.2mm	30mm, 2/7/42	0	NF2503080
10"	60T	TCG	.118"	.087"	5/8"	-5	NF1060EX
10"	60T	TCG	.134"	.102"	5/8"	-5	NF1060
10"	80T	TCG	.118"	.087"	5/8"	-5	NF1080EX
10"	80T	TCG	.134"	.110"	5/8"	-5	NF1080
10"	100T	TCG	.118"	.094"	5/8"	-5	NF1010118
10"	100T	TCG	.134"	.110"	5/8"	-5	NF1010
10"	120T	FTG	.087"	.055"	5/8"	10	NF1012
275mm	80T	TCG	3.2mm	2.4mm	32mm	0	NF2753280
300mm	90T	TCG	3.2mm	2.4mm	32mm	-5	NF30090
300mm	100T	TCG	3.4mm	2.6mm	30mm, 2+2 PH	-5	NF3003010
12"	80T	TCG	.126"	.102"	5/8"	-5	NF1280P
12"	80T	TCG	.142"	.118"	1"	-5	NF1280
12"	100T	TCG	.126"	.102"	5/8"	-5	NF1210P
12"	100T	TCG	.134"	.095"	1"	0	NF1210EX
12"	100T	TCG	.142"	.118"	1"	-5	NF1210
12"	120T	TCG	.126"	.095"	5/8"	-5	NF1212P
12"	120T	TCG	.126"	.095"	1"	-5	NF1212
330mm	90T	TCG	3.4mm	2.8mm	32mm	-5	NF3303290
350mm	60T	TCG	3.2mm	2.5mm	30mm	-5	NF3503060
350mm	84T	TCG	3.2mm	2.5mm	30mm	-5	NF3503084
350mm	84T	TCG	3.2mm	2.2mm	32mm, 4/12/64	-5	NF3503284
350mm	84T	TCG	3.6mm	3.0mm	40mm, 2/9/55 + 4/12/64	-5	NF3504084
350mm	108T	TCG	3.2mm	2.2mm	32mm, 4/12/64	-5	NF35032108
350mm	120T	TCG	3.2mm	2.5mm	1"	-5	NF350120
14"	40T	TCG	.150"	.126"	1"	-5	NF1440
14"	48T	TCG	.150"	.126"	32mm	-5	NF1448
14"	80T	TCG	.150"	.126"	1"	-5	NF1480
14"	100T	TCG	.150"	.126"	5/8"	-5	NF1410P
14"	100T	TCG	.157"	.130"	1"	-5	NF1410
14"	120T	TCG	.146"	.118"	5/8"	-5	NF1412P
14"	120T	TCG	.157"	.130"	1"	-5	NF1412
380mm	100T	TCG	3.8mm	3.2mm	32mm	0	NF38032100
15"	80T	TCG	.126"	.102"	1"	-5	NF1580
15"	100T	TCG	.126"	.102"	1"	-5	NF1510
400mm	72T	TCG	4.2mm	3.4mm	30mm	0	NF4003072
400mm	96T	TCG	3.8mm	3.8mm	50mm, 4/15/80	0	NF4005096
400mm	100T	TCG	4.2mm	3.4mm	30mm	-5	NF4003010
16"	60T	TCG	.165"	.134"	1"	-5	NF1660
16"	80T	TCG	.165"	.142"	1"	-5	NF1680
16"	100T	TCG	.165"	.134"	1"	-5	NF1610
16"	120T	CTC	.157"	.130"	1"	-5	NF1612
420mm	96T	TCG	4.2mm	3.4mm	30mm	0	NF4203096



Non-Ferrous Cutting Saws

A specially formulated carbide makes cutting all kinds of non-ferrous metal simple and easy. Cut sheets, extrusions, or light solids of aluminum, copper, and brass. Clamp material firmly and lubricate blade with cutting fluid. **Do not use on steel or other ferrous metals.**

DIAMETER	TEETH	DESIGN	KERF	PLATE	BORE & PINS	HOOK	ORDER ID
450mm	96T	TCG	4.2mm	3.4mm	30mm	0	NF4503096
18"	60T	TCG	230"	.150"	1"	-5	NF1860
18"	72T	TCG	176"	.142"	1 1/2"	0	NF1872MS*
18"	80T	TCG	176"	.138"	1"	-5	NF1880
18"	100T	TCG	176"	.138"	1"	-5	NF1810
18"	120T	CTC	180"	.150"	1"	-5	NF1812
500mm	100T	TCG	4.6mm	3.8mm	30mm, 4/12/64	0	NF5003010
500mm	100T	TCG	4.0mm	3.2mm	30mm, 4/12/64	5	NF5003010F
500mm	120T	TCG	4.6mm	3.8mm	30mm, 4/12/64	0	NF5003012
500mm	120T	TCG	4.0mm	3.2mm	30mm, 4/12/64	5	NF5003012F
500mm	120T	TCG	4.6mm	3.8mm	32mm, 4/12/64	0	NF5003212
500mm	160T	TCG	4.0mm	3.2mm	30mm	5	NF5003016F
500mm	160T	TCG	4.0mm	3.2mm	30mm	5	NF5003016FL
20"	40T	TCG	180"	.150"	1"	0	NF2040
20"	60T	TCG	180"	.150"	1"	0	NF2060
20"	60T	TCG	180"	.150"	1 1/2", 1 pin	0	NF2060MS*
20"	72T	TCG	180"	.150"	1"	0	NF2072
20"	72T	TCG	180"	.150"	1 1/2", 1 pin	0	NF2072MS*
20"	80T	TCG	180"	.150"	1"	-5	NF2080
20"	100T	TCG	180"	.150"	1"	-5	NF2010
20"	120T	TCG	180"	.150"	1"	-5	NF2012
20"	160T	TCG	180"	.150"	1"	-5	NF2016
550mm	80T	TCG	4.6mm	3.8mm	30mm	0	NF5503080
550mm	100T	TCG	4.6mm	3.8mm	30mm	0	NF5503010
550mm	120T	TCG	4.6mm	3.8mm	30mm	0	NF5503012
22"	60T	TCG	180"	.150"	1 1/2", 1 pin	-5	NF2260MS*
22"	96T	TCG	190"	.155"	40mm, 4/12/64	-5	NF2296ES
22"	100T	TCG	180"	.150"	1"	-5	NF2210
22"	120T	TCG	180"	.150"	1"	-5	NF2212
22"	150T	TCG	180"	.150"	1"	0	NF2215
24"	48T	CTC	235"	.165"	1"	0	NF2448
24"	60T	TCG	205"	.165"	1"	5	NF2460
24"	60T	TCG	205"	.165"	1 1/2", 1 pin	5	NF2460MS*
24"	72T	TCG	205"	.165"	1"	5	NF2472
24"	72T	TCG	205"	.165"	1 1/2", 2 pins	5	NF2472MS*
24"	80T	TCG	205"	.165"	1"	-5	NF2480
24"	100T	TCG	205"	.165"	1"	-5	NF2410
24"	120T	TCG	205"	.165"	1"	-5	NF2412
24"	160T	TCG	210"	.165"	1"	-5	NF2416
24"	160T	TCG	205"	.165"	30mm	-5	NF243016
26"	48T	CTC	235"	.165"	1"	0	NF2648
26"	72T	TCG	230"	.181"	1"	2	NF2672
26"	80T	TCG	235"	.165"	1"	0	NF2680
26"	120T	TCG	235"	.165"	1"	0	NF2612
28"	72T	CTC	230"	.180"	1 1/2", 2 pins	2	NF2872MS*
28"	80T	TCG	240"	.181"	1 1/2", 1+1 pin	0	NF2880MS*
28"	150T	TCG	235"	.165"	1"	0	NF2815
30"	120T	TCG	248"	.200"	1"	2	NF3012

*For Mettsaw plate saws.



Steel Cutting Saws

These steel cutting saws use micro-grain tips with titanium to provide greater impact strength and durability. Can cut through ferrous metal such as angle iron, steel pipe, flat bar, and rebar. Please note maximum RPM varies.

DIAMETER	TEETH	DESIGN	KERF	PLATE	BORE	HOOK	Max. RPM	ORDER ID
7-1/4"	48T	ST	.087"	.071"	5/8"	0	3,500	ST748K
8"	50T	ST	.087"	.071"	5/8"	0	3,000	ST850K
10"	50T	ST	.094"	.071"	5/8"	0	2,800	ST1050
12"	60T	ST	.094"	.079"	1"	0	1,800	ST1260K
12"	80T	ST	.094"	.079"	1"	0	1,800	ST1280K
14"	72T	ST	.094"	.079"	1"	0	1,700	ST1472K
14"	90T	ST	.094"	.079"	1"	0	1,700	ST1490K