



T-9050

"Duress Alarm" Personnel Badge Tag

Long Range Hands-Free Personnel Badge Tag with Duress Alarm Feature



1st Choice T-9050 "Duress Alarm" Personnel Badge Tags identify and track employees and visitors in office buildings, hospitals, warehouses, mines, schools, military bases, etc. for access control, visitor tracking, and emergency evacuation and mustering. Personnel Badge Tags can be functionally linked to each other or asset/vehicle tags to be able to match employees to laptops, drivers to vehicles, employees to visitors, and patients to nurses, etc.

The T-9050 Duress Badge Tag includes a built-in membrane Alarm Push Button for manual safe applications such as nurse duress, emergency help, manufacturing machine stop, and various Lone Worker Protection applications.

Features:

- * Lone Worker Protection Button
- * Up to 5 year battery life warranty
- * Unique Tag "sleep" feature
- * High impact UV stabilized PVC case ultrasonically sealed
- * Available with built-in Proximity or Passive UHF chips
- * Adjustable Read Range:
1' - 3,000' with various Reader Antennas
- * Tag transmissions include real-time battery life indicators
- * Access Control Systems Compatible
- * Dynamic Real-Time Tag Tracking
- * Optional Tamper Switch and Motion Sensing Capability
- * Secure Encrypted Transmission between Tags and Readers

1st Choice T-9050-DT Tags are available with built-in HID Prox, iClass, MIFARE, DESFire and most passive RFID credential chips by other manufacturers. This allows the T-9050-DT Tag to be a personal photo ID access control card, employee tracking and emergency evacuation / muster identifier, and a smart card all in one credit card size credential.



T-9050 DT - X-Ray View

The T-9050 Tags have a standard credit card ID footprint for attaching photo identification cards and/or proximity access control cards. Tags can be attached using Standard ID Card Clips or Lanyards.



T-9050 Duesess Tag on a Lanyard

APPLICATIONS

- * Transportation
- * Mining
- * Emergency Evacuation
- * Supply Chain
- * Petrochemical
- * Healthcare
- * Manufacturing
- * Warehousing
- * Education

Tag Specifications

TX Frequency.....433.92 Mhz
 ERP.....< 300 Micro Watts
 Transmission Range.....2" - 600'
 Variable Beacon Rate.....0.3 sec to 180 sec
 Operational Temperature -40° to +140° F
 Size..... 3.3" x 2.2" x 0.3"
 Weight.....0.88 oz
 Material.....UV Stabilized PVC (IP65)
 Battery.....Internal Lithium
 *This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules.

For More Information Contact:

