

Close Tolerance Rod
 Grade W1 Annealed Finish - Free of Decarbu
 Exhalant for all Machine Screw Applications

| DIAMETER | DRILL ROD | | |
|----------|------------|----------|--|
| | 36" LENGTH | | |
| | | Part No. | |
| 1/8" | | 4400 | |
| 1/4" | | 4401 | |
| 5/16" | | 4402 | |
| 3/8" | | 4403 | |
| 7/16" | | 4404 | |
| 1/2" | | 4405 | |
| 9/16" | | 4406 | |
| 5/8" | | 4408 | |
| 3/4" | | 4409 | |
| 7/8" | | 4410 | |
| 1" | | 4411 | |
| 1 1/8" | | 4412 | |
| 1 1/4" | | 4413 | |
| 1 1/2" | | 4414 | |



9/19/2019

160,000 P.S.I. Alloy Steel
Clean Rolled Threads

| DIAMETER | GRADE B7 THREADED ROD | | |
|----------|-----------------------|--|------|
| | LENGTH | | |
| | 3' | | 3' |
| | USS | | SAE |
| 1/4" | 4240 | | 4211 |
| 5/16" | 4242 | | 4213 |
| 3/8" | 4244 | | 4215 |
| 7/16" | 4246 | | 4217 |
| 1/2" | 4248 | | 4219 |
| 9/16" | 4250 | | 4221 |
| 5/8" | 4252 | | 4223 |
| 3/4" | 4254 | | 4225 |
| 7/8" | 4256 | | 4227 |
| 1" | 4258 | | 4229 |
| 1 1/4" | 4260 | | 4231 |
| 1 1/2" | 4262 | | 4233 |



Corrosion Resistant
Non Magnetic - Temp Range -300F - 800F
ASTM Spec 193-B8

| DIAMETER | 18-8 STAINLESS ALL THREAD | | |
|----------|---------------------------|----------|--|
| | | PART NO. | |
| 6-32 | | 4380 | |
| 8-32 | | 4381 | |
| 10-24 | | 4382 | |
| 1/4 | | 4383 | |
| 5/16" | | 4384 | |
| 3/8" | | 4385 | |
| 7/16" | | 4386 | |
| 1/2" | | 4387 | |
| 5/8" | | 4388 | |
| 3/4" | | 4389 | |
| 7/8" | | 4390 | |
| 1" | | 4391 | |





SAE Approved Cold Drawn Steel
 Made From 1028 Cold Drawn Steel
 Easy To Cut To Length
 + .001 To -.002 - 12" Length

| SQUARE KEYSTOCK PLATED | | | | |
|-------------------------------|-------|--|----------|-------|
| PART NO. | SIZE | | PART NO. | SIZE |
| 13988 | 1/8" | | 13994 | 1/2" |
| 13989 | 3/16" | | 13995 | 9/16" |
| 13990 | 1/4" | | 13996 | 5/8" |
| 13991 | 5/16" | | 13997 | 3/4" |
| 13992 | 3/8" | | 13998 | 7/8" |
| 13993 | 7/16" | | 13999 | 1" |

| SQUARE KEYSTOCK PLAIN | | | | |
|------------------------------|-------|--|----------|--------|
| PART NO. | SIZE | | PART NO. | SIZE |
| 15500 | 1/8" | | 15510 | 7/8" |
| 15501 | 3/16" | | 15511 | 1" |
| 15502 | 1/4" | | 15512 | 1 1/8" |
| 15503 | 5/16" | | 15513 | 1 1/4" |
| 15504 | 3/8" | | 15517 | 1 3/8" |
| 15505 | 7/16" | | 15514 | 1 1/2" |
| 15506 | 1/2" | | 15518 | 1 5/8" |
| 15507 | 9/16" | | 15515 | 1 3/4" |
| 15508 | 5/8" | | 15519 | 1 7/8" |
| 15509 | 3/4" | | 15516 | 2" |

| | |
|----------------------|----------------------------|
| TENSILE STRENGTH | 75/85,000 Lbs. Per Sq. In |
| Yield | 60/70,000 Lbs. Per Sq. In. |
| % Elongation In 2" | 18-25% |
| % Reduction In 2" In | 50-55% |
| Brinell Hardness | 165 - 180% |



9/3/2019