



Made From 304 - 18-8 Stainless Steel  
 Superior Corrosion Resistance  
 Cold Forged - Full Finished Deep Socket  
 Class 3A Threads - Precision Rolled Threads

LENGTH OF SCREW	STAINLESS SLOTTED PAN HEAD SHEET METAL SCREW					
	DIAMETER					
	4	6	8	10	12	14
1/4	12040					
5/16		12050				
3/8	12042	12051	12060			
1/2		12052	12061	12071		
5/8	12044	12053	12062	12072		
3/4	12045	12054	12063	12073		
1		12055	12064	12074	12081	12088
1 1/4		12056	12065	12075	12082	12089
1 1/2		12057	12066	12076	12083	12090
1 3/4			12067	12077		
2			12068	12078	12085	12091
2 1/2"			12069		12086	
3"			12070	12080		



Made From 304 - 18-8 Stainless Steel  
 Superior Corrosion Resistance  
 Cold Forged - Full Finished Deep Socket  
 Class 3A Threads - Precision Rolled Threads

LENGTH OF SCREW	STAINLESS FLAT HEAD SHEET METAL SCREW					
	DIAMETER					
	4	6	8	10	12	14
3/8	12097	12100	12110			
1/2		12101	12111	12121		
5/8	12098	12102	12112	12122		
3/4	12099	12103	12113	12123		
1		12104	12114	12124	12131	12138
1 1/4		12105	12115	12125	12132	12139
1 1/2		12107	12116	12126	12133	12140
1 3/4			12117	12127		
2			12118	12128	12135	12141
2 1/2			12119		12136	
3			12120	12130		



CENTRAL IOWA FASTENERS

9/23/2019



Hardened To Reduce Slippage and Breakage  
 Clean Sharp Rolled Threads  
 Deep Cross Recessed Head

LENGTH OF SCREW	PAN HEAD PHILLIPS SHEET METAL SCREW					
	DIAMETER					
	4	6	8	10	12	14
1/4	10811	10820				
3/8	10812	10821	10830	10840		
1/2	10813	10822	10831	10841	10850	10860
5/8	10814	10823	10832	10842	10851	10861
3/4	10815	10824	10831	10843	10852	10862
7/8			10832	10844		
1	10816	10825	10833	10845	10853	10863
1 1/4			10834	10846	10854	10864
1 1/2			10835	10847	10855	10865
1 3/4			10836	10848		10866
2			10837	10849	10856	10867



Hardened To Reduce Slippage and Breakage  
 Clean Sharp Rolled Threads  
 Deep Cross Recessed Head

LENGTH OF SCREW	OVAL HEAD PHILLIPS SHEET METAL SCREW					
	DIAMETER					
	4	6	8	10	12	14
3/8	10760					
1/2	10761	10762	10770	10780	10790	
5/8		10763	10771	10781	10791	10801
3/4		10764	10772	10782	10792	10802
7/8		10765	10773	10783		
1		10766	10774	10784	10793	10803
1 1/4			10775	10785	10794	10804
1 1/2			10776	10786	10795	10805



CENTRAL IOWA FASTENERS

9/21/2019



Hardened To Reduce Slippage and Breakage  
 Clean Sharp Rolled Threads  
 Deep Slotted Head to Reduce Slippage

LENGTH OF SCREW	PAN HEAD SLOTTED SHEET METAL SCREW					
	4	6	8	10	12	14
1/4	10501	10510				
3/8	10502	10511	10520	10520		
1/2	10503	10512	10521	10521	10540	10550
5/8	10504	10513	10522	10522	10541	10552
3/4	10505	10514	10523	10523	10542	10553
7/8	10506	10515	10524	10524	10543	10554
1	10507	10516	10525	10525	10544	10555
1 1/4			10527	10526	10545	10556
1 1/2				10527	10546	10557
1 3/4					10547	10558
2					10548	10559



Hardened To Reduce Slippage and Breakage  
 Clean Sharp Rolled Threads  
 Deep Slotted Head to Reduce Slippage

LENGTH OF SCREW	HEX WASHER SLOTTED SHEET METAL SCREW						
	6	8	10	12	14	5/16	3/8
3/8	10580	10590	7429	10655	10630		
1/2	10581	10591	10521	10620	10631	10657	7438
5/8	10582	15092	10522	10621	10632	10658	
3/4	10583	10593	10523	10622	10633	10640	10662
7/8	10584	10594	10524		10634	10641	
1	10585	10595	10525	10623	10635	10659	10650
1 1/4	10586	10596	10527	10624	10636	10642	10651
1 1/2	10587	10597	7430	10625	10637	10643	10652
1 3/4	7420	10598	7431	10656	10638	10660	
2	7421	10599	7432	10626	10639	10661	10664
2 1/2	7422	7424	7433	10627	7434	7436	7439
3	7423	7425	10666	10628	7435	7437	7440



CENTRAL IOWA FASTENERS

9/21/2019



Drill Points Are Heat Treated for Quick Installation  
 Meets the Following Specs ASTM C 1513, F.I.P. 1000.7,  
 SAE J78, ICC-E5, ASTM A510, ASTM F1941  
 Attaches Metal To Metal Up To 1/8"  
 Zinc Plated

LENGTH OF SCREW	PHILLIPS HEAD SELF-DRILLING SCREW				
	DIAMETER OF SCREW				
	#2 POINT #3 POINT				
	6	8	10		
3/8	<u>10100</u>	<u>10109</u>	<u>10192</u>		
1/2	<u>10102</u>	-	<u>10120</u>		
5/8	<u>10103</u>	<u>10111</u>	<u>10121</u>		
3/4	<u>10104</u>	<u>10112</u>	<b>10122</b>		
1	<u>10105</u>	<u>10113</u>	<b>10123</b>		
1 1/4	<u>10190</u>	<u>10191</u>	<b>10124</b>		
1 1/2	<u>10107</u>	<u>10116</u>	<u>10193</u>		



Drill Points Are Heat Treated for Quick Installation  
 Meets the Following Specs ASTM C 1513, F.I.P. 1000.7,  
 SAE J78, ICC-E5, ASTM A510, ASTM F1941  
 Attaches Metal To Metal Up To 1/4"  
 Zinc Plated

LENGTH OF SCREW	WAFER HEAD SELF-DRILLING SCREW				
	DIAMETER OF SCREW				
	#3 POINT				
	8	10	14		
5/8					
3/4		10175			
1	<u>10196</u>	10176			
1 1/4		10178			
1 1/2		10179			
1 7/8					
2		<u>10197</u>	10198		
2 1/2					
3					
4					
5					
6			<u>10187</u>		



9/21/2019



Needle Points for Quick Installation - No Pilot Hole  
 Meets Specs ASTM A 510, ASTM B 633  
 Used on Light Ga Sheet Metal Applications  
 Zinc Plated

LENGTH	HEX HEAD SHARP POINT METAL SCREW				
	DIAMETER				
	6	7	8	10	
3/8	109				
1/2		110	111	113	
5/8			7410		
3/4			112	<b>114</b>	
1			7411	<b>115</b>	
1 1/2			112x	<b>116</b>	
2			7412	<b>117</b>	
3				<b>7413</b>	

**BOLD IS 5/16" CROSS The Flats**



Needle Points for Quick Installation - No Pilot Hole  
 Meets Specs ASTM A 510, ASTM B 633  
 Used on Light Ga Sheet Metal Applications  
 Zinc Plated

LENGTH	PHILIPS WAFER SHARP POINT METAL SCREW				
	DIAMETER				
	8				
1/2	140				
9/16	7414				
3/4	142				
1	145				
1 1/4	146				
1 5/8	147				
1 7/8	148				
2 1/2	7415				
3	7416				

BULK 1/4 KEG ARE AVAILABLE AT A DISCOUNTED PRICE



9/21/2019

Sharp Point For Easy Installation  
 Black Phosphate Coated  
 For Wood, Aluminum and Plastic

LENGTH OF SCREW	PHILLIPS BUGLE HEAD DRYWALL COARSE THREAD				
	DIAMETER OF SCREW				
	6	7	8	10	
1	11010				
1 1/8	11011				
1 1/4	11012				
1 5/8	11013				
2	11014				
2 1/2		11015			
3			11020		
3 3/4				11021	
4 1/2				11022	
3				11023	
6				11024	

LENGTH OF SCREW	PHILLIPS BUGLE HEAD DRYWALL FINE THREAD				
	DIAMETER OF SCREW				
	6	7	8		
1	11030				
1 1/8	11031				
1 1/4	11032				
1 5/8	11033				
2	11034				
2 1/4	11035				
2 1/2		11036			
3			11039		

LENGTH OF SCREW	PHILLIPS BUGLE HEAD DRYWALL DRILL POINT				
	DIAMETER OF SCREW				
	6				
1	11040				
1 1/8	11041				
1 1/4	11042				
1 5/8	11043				
2	11046				
2 1/4	11027				



CENTRAL IOWA FASTENERS

9/21/2019



Hardened To Reduce Slippage and Breakage  
 Clean Sharp Rolled Threads  
 Deep Cross Recessed Head

LENGTH OF SCREW	FLAT HEAD PHILLIPS SHEET METAL SCREW					
	DIAMETER					
	4	6	8	10	12	14
3/8	10700	17010				
1/2	10701	10711	10720	10730		
5/8	10702	10712	10721	10731		10750
3/4	10703	10713	10722	10732	10740	10751
7/8				10733		
1		10714	10723	10734	10741	10752
1 1/4			10724	10735	10742	10753
1 1/2			10725	10736	10743	10754
1 3/4				10737		
2			10726	10738	10744	10755



Hardened To Reduce Slippage and Breakage  
 Clean Sharp Rolled Threads  
 Deep Slotted Head to Reduce Slippage

LENGTH OF SCREW	FLAT HEAD SLOTTED SHEET METAL SCREW					
	DIAMETER					
	4	6	8	10	12	14
1/4	10200	10207				
3/8	10201	10208	10216	10228		
1/2	10202	10209	10217	10229	10240	10251
5/8	10203	10210	10218	10230	10241	10252
3/4	10204	10211	10219	10231	10242	10253
7/8	10205	10212	10220	10232	10243	10254
1	10206	10213	10221	10233	10244	10255
1 1/4		10214	10222	10234	10245	10256
1 1/2		10215	10223	10235	10246	10257
1 3/4			10224	10236	10247	10258
2			10225	10237	10248	10259
2 1/2			10226	10238	10249	10260
3			10227	10239	10250	10261



CENTRAL IOWA FASTENERS

9/21/2019



Hardened To Reduce Slippage and Breakage  
 Clean Sharp Rolled Threads  
 Deep Slotted Head to Reduce Slippage

LENGTH OF SCREW	FLAT HEAD SLOTTED MACHINE SCREW									
	4-40	6-32	8-32	10-24	10-32	12-24	1/4	5/16	3/8	1/2
1/4	8620	8630	8640	8650	8670					
5/16	8621	8631	8904	8912	8919	8922				
3/8	8622	8632	8641	8651	8671	8923				
1/2	8623	8633	8642	8652	8672	8924	8690	8710	8941	
5/8	8624	8634	8643	8653	8673	8925	8691	8711	8942	
3/4	8625	8635	8644	8654	8674	8926	8692	8712	8943	8959
1	8626	8636	8645	8655	8675	8927	8693	8713	8944	8960
1 1/4	8627	8895	8646	8636	8676	8928	8594	8714	8945	8961
1 1/2	8628	8896	8647	8657	8677	8929	8695	8715	8946	8962
1 3/4		8897	8905	8658	8678	8930	8696	8934	8947	8963
2		8898	8906	8659	8679	8931	8697	8716	8948	8964
2 1/4		8899	8907	8660	8680		8698	8717	8949	8965
2 1/2		8901	8908	8661	8681	8932	8699	8718	8950	8966
3			8909	8662	8682	9833	8701	8719	8952	8967
3 1/2			8910	8913	8920			8935	8953	8968
4			8911	8914	8921			8936	8954	8969
4 1/2				8915				8937	8955	8970
5				8916				8938	8956	8971
5 1/2				8917				8939	8954	8972
6				8918				8940		8973



CENTRAL IOWA FASTENERS

9/20/2019





Hardened To Reduce Slippage and Breakage  
 Clean Sharp Rolled Threads  
 Deep Slotted Head to Reduce Slippage

LENGTH OF SCREW	TRUSS HEAD SLOTTED MACHINE SCREW								
	4-40	6-32	8-32	10-24	10-32	12-24	1/4	5/16	1/2
1/4	10300	10308	10321	10333	10347		10360		
5/16	10301	10309	10322	10334	10348		10361		
3/8	10302	10310	10323	10335	10349	10357	13062		
1/2	10303	10311	10324	10336	10350	10358	10363	10377	10388
5/8	10304	10312	10325	10337	10351	10359	10364	10378	10389
3/4	10305	10313	10326	10338	10351X	10360	10365	10379	10390
7/8	10306	10314	10327	10339	10352		10366	10380	10391
1	10307	10315	10328	10340	10353		10367	10381	10392
1 1/4		10316	10329	10341	10354		10368	10382	10393
1 1/2		10317	10330	10342	10355		10368X	10383	10394
1 3/4		10318	10331	10343			10369	10384	10395
2		10319	10332	10344	10356		10370	10385	10396
2 1/4							10371		
2 1/2							10372	10386	10397
2 3/4"							10373		
3				10345			10374	10387	10398
3 1/2							10375		
4				10346			10376		

LENGTH OF SCREW	PAN HEAD SLOTTED MACHINE SCREW					
	4-40	6-32	8-32	10-24	10-32	1/4
1/4	8200	8210	8220			
3/8	8201	8211	8221	8230	8240	8250
1/2	8202	8212	8222	8231	8241	8251
5/8	8203	8213	8223	8232	8242	8252
3/4	8204	8214	8224	8233	8243	8253
1	8205	8215	8225	8234	8244	8254
1 1/4			8226	8235	8245	8255
1 1/2			8227	8236	8246	8256
2			8228	8237	8247	8257





Hardened To Reduce Slippage and Breakage  
 Clean Sharp Rolled Threads  
 Deep Slotted Head to Reduce Slippage

LENGTH OF SCREW	TRUSS HEAD SLOTTED MACHINE SCREW								
	4-40	6-32	8-32	10-24	10-32	12-24	1/4	5/16	1/2
1/4	10300	10308	10321	10333	10347		10360		
5/16	10301	10309	10322	10334	10348		10361		
3/8	10302	10310	10323	10335	10349	10357	13062		
1/2	10303	10311	10324	10336	10350	10358	10363	10377	10388
5/8	10304	10312	10325	10337	10351	10359	10364	10378	10389
3/4	10305	10313	10326	10338	10351X	10360	10365	10379	10390
7/8	10306	10314	10327	10339	10352		10366	10380	10391
1	10307	10315	10328	10340	10353		10367	10381	10392
1 1/4		10316	10329	10341	10354		10368	10382	10393
1 1/2		10317	10330	10342	10355		10368X	10383	10394
1 3/4		10318	10331	10343			10369	10384	10395
2		10319	10332	10344	10356		10370	10385	10396
2 1/4							10371		
2 1/2							10372	10386	10397
2 3/4"							10373		
3				10345			10374	10387	10398
3 1/2							10375		
4				10346			10376		

LENGTH OF SCREW	PAN HEAD SLOTTED MACHINE SCREW					
	4-40	6-32	8-32	10-24	10-32	1/4
1/4	8200	8210	8220			
3/8	8201	8211	8221	8230	8240	8250
1/2	8202	8212	8222	8231	8241	8251
5/8	8203	8213	8223	8232	8242	8252
3/4	8204	8214	8224	8233	8243	8253
1	8205	8215	8225	8234	8244	8254
1 1/4			8226	8235	8245	8255
1 1/2			8227	8236	8246	8256
2			8228	8237	8247	8257





Type F Design For Quick Thread Cutting  
 Can Be Installed From A Blind Side  
 Hardened For Easy Installation

LENGTH OF SCREW	HEX HEAD THREAD CUTTING MACHINE SCREW						
	DIAMETER OF SCREW						
	6-32	8-32	10-24	1/4	5/16	3/8	1/2
3/16	10880						
1/4	10881	10885X	10892				
3/8	10882	10886	10893	10899			
1/2	10883	10887	18094	10900	10905	10958	
5/8	10950	10888	10895	10901	10905X	10959	
3/4	10884	10889	10896	10902	10906	10909	
7/8		10890		10953	10906X	10960	
1	10885	10891	10897	10903	10907	10910	
1 1/4			10898	10904	10908	10911	10966
1 1/2			10951	10954	10956	10912	10967
2			10952	10955	10957	10961	10968
2 1/2						10962	10969
3						10963	10970
3 1/2						10964	10971
4						10965	10972



LENGTH OF SCREW	PAN HEAD SLOTTED THREAD CUTTING SCREW					
	DIAMETER OF SCREW					
	6-32	8-32	10-24	10-32	1/4	
1/4	10920	10924	10924			
3/8	10921	10925	10925	10985	10992	
1/2	10922	10926	10926	10986	10936	
5/8	10980	10927	10927	10987	10937	
3/4	10981	10928	10928	10988	10938	
7/8	10923	10982				
1		10929	10934	10989	10939	
1 1/4			10935	10990	10940	
1 1/2		10983	10984	10991	10941	
2					10993	

Also available with Phillips Head  
 Add "P" to Part No.



CENTRAL IOWA FASTENERS

9/21/2019



DIN 963A  
 HEAT TREATED  
 DEEP CUT SLOT - ROLLED THREADS  
 ZINC PLATED

LENGTH OF SCREW	METRIC FLAT HEAD SLOTTED MACHINE SCREW							
	DIAMETER							
	2MM	2.5MM	3MM	4MM	5MM	6MM	8MM	10MM
5	4500	4510	4520	4535				
6	4501	4511	4521	4536	4552			
8	4502	4512	4522	4537	4553	4570		
10	4503	4513	4523	4538	4554	4571		
12	4504	4514	4524	4539	4555	4572	4586	
16	4645	4515	4525	4540	4556	4573	4587	4600
20	4506	4516	4526	4541	4557	4574	4588	4601
25			4527	4542	4558	4575	4589	4602
30			4528	4543	4559	4576	4590	4603
40			4529	4544	4560	4577	4591	4604
45				4545	4561	4578	4592	4605
50				4546	4562	4579	4593	4606
60					4563	4580	4394	4607



DIN 964A  
 Heat Treated  
 DEEP CUT SLOT - ROLLED THREADS  
 ZINC PLATED

LENGTH OF SCREW	METRIC OVAL HEAD SLOTTED MACHINE SCREW						
	DIAMETER						
	2MM	2.5MM	3MM	4MM	5MM	6MM	8MM
4	4700	4710					
5	4701	4711					
6	4702	4712	4720	4730			
8	4703	4713	4721	4731	4745		
10	4704	4714	4722	4732	4746	4760	
12	4705	4715	4723	4733	4747	4761	
16	4706	4716	4724	4734	4748	4762	4771
20	4707	4717	4725	4735	4749	4763	4772
25			4726	4736	4750	4764	4773
30			4727	4737	4751	4765	4774
35			4728	4738	4752	4766	4775
40			4729	4739	4573	4767	4776
45				4740	4754	4768	4777
50				4741	4755	4769	4778
60						4770	4779





Type F Design For Quick Thread Cutting  
 Can Be Installed From A Blind Side  
 Hardened For Easy Installation

LENGTH OF SCREW	HEX HEAD THREAD CUTTING MACHINE SCREW						
	DIAMETER OF SCREW						
	6-32	8-32	10-24	1/4	5/16	3/8	1/2
3/16	10880						
1/4	10881	10885X	10892				
3/8	10882	10886	10893	10899			
1/2	10883	10887	18094	10900	10905	10958	
5/8	10950	10888	10895	10901	10905X	10959	
3/4	10884	10889	10896	10902	10906	10909	
7/8		10890		10953	10906X	10960	
1	10885	10891	10897	10903	10907	10910	
1 1/4			10898	10904	10908	10911	10966
1 1/2			10951	10954	10956	10912	10967
2			10952	10955	10957	10961	10968
2 1/2						10962	10969
3						10963	10970
3 1/2						10964	10971
4						10965	10972



LENGTH OF SCREW	PAN HEAD SLOTTED THREAD CUTTING SCREW					
	DIAMETER OF SCREW					
	6-32	8-32	10-24	10-32	1/4	
1/4	10920	10924	10924			
3/8	10921	10925	10925	10985	10992	
1/2	10922	10926	10926	10986	10936	
5/8	10980	10927	10927	10987	10937	
3/4	10981	10928	10928	10988	10938	
7/8	10923	10982				
1		10929	10934	10989	10939	
1 1/4			10935	10990	10940	
1 1/2		10983	10984	10991	10941	
2					10993	

Also available with Phillips Head  
 Add "P" to Part No.



CENTRAL IOWA FASTENERS

9/21/2019



DOMESTIC FASTENERS  
 MADE OF DOUBLE HEAT TREATED  
 1040 MEDIUM CARBON STEEL  
 MINIMUM 180,000 P.S.I  
 C 36 AVERAGE ROCKWELL HARDNESS

<b>FLANGED FRAME BOLTS</b>				
<b>LENGTH</b>	<b>3/8"</b>	<b>1/2"</b>	<b>5/8"</b>	<b>3/4"</b>
1"	4265	4270		
1 1/4"	4266	4271	4282	
1 1/2"	4267	4272	4283	<b>4301</b>
1 3/4"	4268	4273	4284	4291
2"	4269	4274	4285	4292
2 1/4"		4275	4286	4293
2 1/2"		4276	4287	4294
2 3/4"		4277	<b>4299</b>	<b>4302</b>
3"		4278	4288	<b>4303</b>
3 1/4"		4279	<b>4300</b>	<b>4304</b>
3 1/2"		4280	4289	<b>4305</b>
4"		4281	4290	<b>4306</b>
<b>NUTS</b>	4295	4296	4297	4298



Easier to Drive Than Othr Floorboard Screws  
 Positive Drive Without Sliipage

<b>FLOORBOARD SCREWS</b>		
<b>LENGTH</b>	<b>1/4"</b>	<b>5/16"</b>
1 1/2"	10680	<b>10689</b>
1 3/4"	10681	10686
2"	10682	10687
2 1/4"	10683	10688
2 1/2"	10684	
3"	10685	<b>10690</b>

### TORX BITS

<b>PART NO.</b>		
9438	<b>1/4"</b>	T30
9349	<b>5/16"</b>	T40



CENTRAL IOWA FASTENERS

8/19/2019