



- > 12 Scope Storage Capacity
- > Complete Drying for Each Endoscope
- > Wide Touch Screen
- > Monitoring Cabin Temperature and Humidity
- > Endoscope Slot Display and Selection by Wide Touch Screen
- > Updating the Program by Network Connection
- > Ethernet Connection to Hospital Network for Data Transfer
- > Safe User Access
- > 6 Adjustable Programs
- > Printer for Traceability of Process
- > Qualified Drying Air by Hepa Filter and U/V Lamp
- > Barcode Controlled Door for Safe Process
- > Easy-to-clean Water Collection Tank



MODEL TABLE

| MODEL NO | NUMBER of SCOPES | DIMENSIONS | WEIGHT | SCOPE LENGHT | POWER | CATALOG CODE |
|----------|------------------|------------------|--------|--------------|-------|--------------|
| DSC-601 | 6 | 1110x821x2315 mm | 180 kg | 2050 mm | 5 kW | DSC-601 |
| DSC-602 | 6 | 1110x821x2215 mm | 170 kg | 1950 mm | 5 kW | DSC-602 |
| DSC-603 | 6 | 1110x821x2115 mm | 160 kg | 1850 mm | 5 kW | DSC-603 |
| DSC-1201 | 12 | 1110x821x2315 mm | 200 kg | 2050 mm | 5 kW | DSC-1201 |
| DSC-1202 | 12 | 1110x821x2215 mm | 190 kg | 1950 mm | 5 kW | DSC-1202 |
| DSC-1203 | 12 | 1110x821x2115 mm | 180 kg | 1850 mm | 5 kW | DSC-1203 |