



WEBB MULTICLASS READER

RFID CARDS, NFC & BLUETOOTH

FEATURES AND BENEFITS

- RFID, Bluetooth® and NFC secure identification
- Discreet and elegant integration
- Easy installation on door frames and narrow electrical pots
- Retro compatible and interoperable



MULLION READER



SINGLE-GANG READER

TYPICAL APPLICATIONS

- Residential
- Commercial
- Industrial
- Instructional
- Garage Gates
- Elevators
- Hospitals
- Universities
- Seniors Homes



Hands Free Mode— by simply passing in front of the reader



Card Mode— by placing your smartphone in front of the reader



Voice Control Mode — by using voice command on your iPhone (iOS)



Tap Tap Mode— by tapping your smartphone twice in your pocket for near or remote opening



Remote Mode— by using your smartphone as a remote control

Description: It's optimized design ensures perfect integration, whatever the installation environment and without additional spaces (even on metal). The pluggable cable and the mounting base make it very easy to install. **Virtual cards** promote acceptance of and compliance with the security policy of businesses, industries and governments.

Ordering Information

WEBB MULLION READER

Webb Studio Administrator Software hosted on the WEX

WEBB SINGLE GANG READER

Webb Studio Client Software is unlimited per WEX deployment





WEBB MULTICLASS READER

RFID CARDS, NFC & BLUETOOTH

Additional Features:

Features:	Description:
Operating frequency	13.56: ISO 14443 types A&B, ISO18092
Chip Compatibility	Webb Multiclass Reader RFID CARDS, NFC & BLUETOOTH
Functions	Insert any mpeg or Avi files
Communication interfaces and protocols	OSDP or Wiegand
Decoder Compatibility	Compatible with EasySecure interface (encrypted communication)
Reader Distances	Up to 6cm/ 2.36" with MIFARE DESFire EV2 or Classic card Up to 20m/65.6ft with Bluetooth Smartphone (adjustable distances on each reader)
Data Protection	Yes—Software protection and EAL5+ crypto processor for secure data storage.
Light Indicator	2 RGB LEDs—360 colors configurable by card software or controlled by external command.
Audio Indicator	Integrated buzzer with adjustable intensity
Power	150 mA/12VDC Max 9VDC to 15 VDC
Connectors	Cable with plug connector 3m/9.8ft
Material	ABS-PC UL -V0 (Black) / ASA-PC-UL-V0 (White)
Temperatures	-30 °C at 70 °C/ -22°F to 158 °F
Tamper Switch	Accelerometer-based tamper detection system with key deletion and/or message to the controller.
Water Resistance	IP65 level Weather, water and dust resistant
Mounting	Wall-mounted, on door jambs and on narrow electrical junction boxes. Mount on any type of support including metal without spacer.
Warranty	2 year warranty