

# AC002 AC Charger

Output Rating: 11KW\*2 Double Outlets



## Meet North America Standards



## Reliable and Safety

- Multi-Level Security Protections
- ETL certified

## Smart Charging

- SmartAPP to schedule the charging time
- OCPP communication enable connect with multiple platform
- Support dynamic load balancing (DLB) Function

## Connectivity

- Ethernet or Wi-Fi or 4G
- Authentication via APP or RFID
- 5" LCD touch-screen
- Remotely configuration and upgrades

***No more worries for your EV***

# AC002 AC Charger

## Specifications

Item		AC002
<b>Basci info</b>	Output rating	11kW*2
	Current	48A
	Voltage	230V Single Phase
	Connector	Type 1
	Dimension (H*W*D)	64" H*11" W*16" D (1630mm*280mm*400mm)
	Colour	White front or OEM Color
	Weight	115 lb. (52kg)
	Indicator	✓
	Material	Sheet Metal
	Display	5" LCD Touch Screen
<b>Features</b>	Stand-by Power	<2W
	Efficiency	≥95%
	RFID	✓
	WIFI	2.4/5GHz
	4G	Optional
	POS machine	Optional
	RS485	Optional
	OCPP1.6J	✓
	App	Optional
	Dynamic Load Blancing	Optional
<b>Safety</b>	Ingress Protection	IP54/IK10
	Overload protection	✓
	Over/Under voltage protection	✓
	Short circuit protection	✓
	Earth Leakage Protection	✓
	Ground Protection	✓
	Surge protection	✓
	Overtemperature	✓
	Certification	UL(ETL),RoHS
	Certification Standard	UL2594 UL2231.24.2-2231.24.10
<b>Enviroment</b>	Installation	Floor Stand
	Work Temperature	-22°F~+131°F (-30°C~+55°C)
	Work Humidity	5%~95% Without Condensation
	Work Altitude	<6,562 ft (2000m)