

AC003 AC Charger

Output Rating: 11KW Single Outlet



Meet North America Standards



Reliable and Safety

- Multi-Level Security Protections
- ETL certified

Smart Charging

- SmartAPP to schedule the charging time
- OCPP communication enable connect with multiple platform
- Support dynamic load balancing (DLB) Function

Connectivity

- Ethernet or Wi-Fi or 4G
- Authentication via APP or RFID
- 5" LCD touch-screen
- Remotely configuration and upgrades

No more worries for your EV

AC003 AC Charger

Specifications

Item		AC003
Basci info	Output rating	11kW
	Current	48A
	Voltage	230V Single Phase
	Connector	Type 1
	Dimension (H*W*D)	15" H*10" W*4" D (375mm*260mm*104mm)
	Colour	Black front+ black back or OEM Color
	Weight	11 lb. (5kg)
	Indicator	√
	Material	Sheet Metal
	Display	5" LCD Touch Screen
Features	Stand-by Power	<2W
	Efficiency	≥95%
	RFID	√
	WIFI	2.4/5GHz
	RS485	Optional
	OCPP1.6J	√
	App	Optional
	Dynamic Load Blancing	Optional
Safety	Ingress Protection	IP54/IK10
	Overload protection	√
	Over/Under voltage protection	√
	Short circuit protection	√
	Earth Leakage Protection	√
	Ground Protection	√
	Surge protection	√
	Overtemperature	√
	Certification	UL(ETL),RoHS
	Certification Standard	UL2594 UL2231.24.2-2231.24.10
Enviroment	Installation	Wall/Pole mounted
	Work Temperature	-22°F~+131°F (-30°C~+55°C)
	Work Humidity	5%~95% Without Condensation
	Work Altitude	<6,562 ft (2000m)