

DC02 DC Fast Charger

Output Rating: 180KW Double Outlets



Meet North America Standards



Reliable and Safety

- Multi-Level Security Protections
- ETL certified

Smart Charging

- SmartAPP to schedule the charging time
- OCPP communication enable connect with multiple platform
- Support dynamic load balancing (DLB) Function

Connectivity

- Ethernet or Wi-Fi or 4G
- Authentication via APP or RFID
- 7" LCD touch-screen
- Remotely configuration and upgrades

No more worries for your EV

DC02 DC Fast Charger

Specifications

| Item | | DC02 |
|------------|-------------------------------|--|
| Basci info | Output rating | 180kW |
| | Current | 200A |
| | Voltage | 480V Three Phases |
| | Connector | CCS1 |
| | Dimension (H*W*D) | 71" H*32" W*19" D (1800mm*800mm*490mm) |
| | Colour | Grey or OEM Color |
| | Weight | 1,058 lb. (480kg) |
| | Indicator | ✓ |
| | Material | Sheet Metal |
| | Display | 7" LCD Touch Screen |
| Features | Stand-by Power | <60W |
| | Efficiency | ≥95% |
| | RFID | ✓ |
| | WIFI | 2.4/5GHz |
| | 4G | ✓ |
| | POS machine | Optional |
| | RS485 | ✓ |
| | OCPP1.6J | ✓ |
| | App | Optional |
| | Dynamic Load Blancing | Optional |
| Safety | Ingress Protection | IP55/IK10 |
| | Overload protection | ✓ |
| | Over/Under voltage protection | ✓ |
| | Short circuit protection | ✓ |
| | Earth Leakage Protection | ✓ |
| | Ground Protection | ✓ |
| | Surge protection | ✓ |
| | Overtemperature | ✓ |
| | Certification | UL(ETL),RoHS |
| | Certification Standard | UL2202, UL2231.24 |
| Enviroment | Installation | Floor Stand |
| | Work Temperature | -22°F~+131°F (-30°C~+55°C) |
| | Work Humidity | 5%~95% Without Condensation |
| | Work Altitude | <6,562 ft (2000m) |

Website: Blueview-usa.com

Email: info@blueviewelectricity.com

No more worries for your EV