

UAC 50H HOME CHARGING AC CHARGER

OUTPUT RATING: 50A SINGLE OUTLET

■ Meet North American Standards



■ Reliable and Safe

- Multi-layer security protections
- ETL certified



■ Smart Charging

- Smart APP to schedule the charging time
- OCPP-based communication, supporting connections to multiple platforms
- Support dynamic load balancing (DLB) function

■ Connectivity

- Ethernet / Wi-Fi
- Authentication via APP or RFID
- Remote configurations and upgrades

UAC 50H

HOME CHARGING AC CHARGER

SPECIFICATIONS

ITEM		UAC 50H
BASIC INFO	Output Rating	12kW
	Current	50A
	Voltage	208V / 240V, 50Hz / 60Hz
	Connector	Type 1 (SAE J1772), 25 feet (7.5m) cable
	Dimension (H*W*D)	16"H*11"W*5"D (404mm*284mm*127mm)
	Color	Grey and green (turquoise)
	Weight (Connector Incl.)	17.2 lb. (7.8kg)
	LED Indicator	✓
FEATURES	RFID	✓
	WIFI	2.4GHz
	OCPP1.6J	✓
	APP	Optional
	Dynamic Load Blancing	Optional
SAFETY	Ingress Protection	NEMA Type 4
	Overload Protection	✓
	Over/Undervoltage Protection	✓
	Short Circuit Protection	✓
	Earth Leakage Protection	✓
	Ground Protection	✓
	Surge Protection	✓
	Overtemperature Protection	✓
	Certification	UL (ETL), FCC, Energy Star
	Certification Standards	UL 2202, UL 2231-2, UL 2594
ENVIROMENT	Installation	Wall mounted
	Working Temperature	-22°F~+131°F (-30°C~+55°C)
	Working Humidity	5%~95% without condensation
	Working Altitude	<6,562 ft (2,000m)

WEBSITE: blueview-usa.com

EMAIL: info@blueviewelectricity.com