

UDC 360 DC FAST CHARGER

OUTPUT RATING: 360kW DOUBLE OUTLETS

■ Meet North American Standards



■ Reliable and Safe

- Multi-layer security protections
- ETL certified

■ Smart Charging

- Smart APP to schedule the charging time
- OCPP-based communication, supporting connections to multiple platforms
- Support dynamic load balancing (DLB) function

■ Connectivity

- Ethernet / Wi-Fi / 4G
- Authentication via APP or RFID
- 10" LCD touch screen
- Remote configurations and upgrades



UDC 360 DC FAST CHARGER

SPECIFICATIONS

ITEM		UDC 360
BASIC INFO	Output Rating (Max.)	360kW
	Current (Max.)	400A (200~1000V)
	Voltage	480V three phases
	Connector	CCS1 * 2
	Dimension (H*W*D)	71"H*32"W*32"D (1800mm*800mm*800mm)
	Color	Grey and white
	Weight	1,058 lb. (480kg)
	Indicator	✓
	Material	Sheet metal
	Display	10" LCD touch screen
FEATURES	Stand-by Power	<60W
	Efficiency	≥95%
	RFID	✓
	WIFI	2.4GHz
	4G	✓
	POS Terminal	Optional
	RS485	✓
	OCPP1.6J	✓
	APP	Optional
SAFETY	Dynamic Load Blancing	Optional
	Ingress Protection	IP54
	Overload Protection	✓
	Over/Undervoltage Protection	✓
	Short Circuit Protection	✓
	Earth Leakage Protection	✓
	Ground Protection	✓
	Surge Protection	✓
	Overtemperature	✓
	Certication	UL (ETL), Energy Star
ENVIROMENT	Certication Standards	UL2202 UL2231 .24
	Installation	Floor stand
	Working Temperature	-40°F~+131°F (-40°C~+55°C)
	Working Humidity	5%~95% without condensation
	Working Altitude	<6,562 ft (2,000m)

WEBSITE: blueview-usa.com

EMAIL: info@blueviewelectricity.com