

Q48

Up to 10 **printheads** in three rows. **Belt System**. Multiple printhead configuration.



Multi function joystick



Linear encoder



Magnetic rail



Scan for more
information

Main Features:

- **Belt System** to ensure maximum productivity.
- Automatic material height sensor.
- Vacuum table and registration pins.
- Anti-collision device to protect printheads.
- Safety “curtain sensors” to protect the operator.

Applications:

Direct printing to a wide variety of rigid materials, such as: acrylic sheets, PVC, MDF, Wood, Aluminum, Glass, ACM, and similar materials.

Technical Specifications

Print Heads	Ricoh Gen6
Drop Volume	5 pl.
Printhead Quantity	10 Max. / 3 rows
Ink Types	UV-LED
Color scale	CMYK + Lc + Lm + W + V
Print Height	100 mm. (3.9in)
Print Resolution	2400 DPI
Print Table Area	120 in. x 80 in.
Print Speed Up to	232m ² (2496 sqft ² h)
Interface Port	Ethernet
Machine Size	86 in. x 205 in. x 60 in.
Machine Weight	3000 lbs. / 1370 kg.
Power Requirements	230v (+/-) 10% - 40A - 50/60HZ (Three circuit)
RIP Software	Caldera
*Specification can be changed without any previous notice.	
*Max speed without feather.	