

**KAB5L, 6L**

CATALOGUE 2024-25



220g / 0.0001g (0.1mg)

320g / 0.0001g (0.1mg)

Keypad  
**Analytical Balance**  
KAB5L & KAB6L



E - Catalogue

**SALIENT FEATURES**



Electro Magnetic Force Compensation



RS232C Interface



Underhook Weighing



Piece Counting Function



Internal Auto Calibration



TARE



LCD display



Multiple Weighing Units

**KAB5L, 6L**

CATALOGUE 2024-25



Keypad **Analytical Balance**

HSN Code - 90160010

SPECIFICATIONS	MODEL	KAB5L	KAB6L
	Capacity	220g	320g
Make	WENSAR		
Readability	0.1mg (0.0001g)		
Repeatability	0.1mg		
Linearity ( ± )	0.3mg		
Min.(Capacity)	10mg		
Display	LCD		
Pan Size	90 mm Ø		
Response Time	4 - 6 Sec		
Calibration	Internal Calibration		
Tare Range	Full		
Operating Temperature	15°C to 30°C		
Unit	mg, g,ct, ozt, oz, GN, dwt, lb		
Key Sound	Yes		
Weighing Chamber Height	210mm		
Baud rate	200, 2400, 4800, 9600		
Class	I		
Interface	RS232C		
Data Output Mode	Command and continuous Output		
Power Supply	AC 220V / 50-60 Hz		
Dimension (LxWxH)	220 x 360 x 345mm		
Weight	9.5kg		

★ Specifications are subject to change without notice.

**STANDARD ACCESSORIES :** Main Instrument, SS PAN Set, Power Cable, Dust Cover, Test Certificate.