

Sales and Service:



MAUSER
SPEZIAL

Single Needle Walking Foot Machine

Mauser Spezial MH1235-G-6/01 CLMN8

Proven single-needle lockstitch sewing machine with narrow cylinder arm for medium-weight materials. Equipped with bottom feed, needle feed and alternating top feed.

The 1235 series is the latest development of the well-known and most widely used 335 triple feed cylinder arm machine worldwide. In the equipment line with automatic functions, such as electromagnetic thread trimmer, electropneumatic foot lift and seam backtacking, the Mauser Spezial 1235 also has an integrated 750W direct drive with built-in control panel.

Thus equipped, the Mauser Spezial 1235 continues to be a reliable production tool in the manufacture of leather goods, handbags and suitcases.



Typical applications:



Sales and Service:



MAUSER
S P E Z I A L

Single Needle Walking Foot Machine

Mauser Spezial MH1235-G-6/01 CLMN8

The Mauser Spezial MH1235 is a universally applicable free-arm machine that is used in particular for processing tubular or pre-assembled, closed articles.

The narrow cylinder arm with a diameter of only 51mm allows the machine to be used on workpieces with a small cross-section. Typical applications are in the production of small leather goods and leather garments as well as the manufacture of bags, suitcases and upholstery.

The use of a horizontal hook ensures precise and uniform thread take-up and even bobbin thread tension.

The bottom feed and needle feed in conjunction with the alternating top feed ensure not only a high pull-through force but also a uniform material feed. With the top feed stroke of 7 mm, material thickenings and cross seams can be passed over effortlessly.

The MH1235 is also widely used for binding operations on shoes and leather goods. For this purpose, the machine can be equipped with special components with moving binder (subclass -17/01).

The binding device is recessed in the throat plate. As a result, the sewing material enters the sewing machine evenly. The binding tape lies tightly against the material edge even with inside and outside radii.



Standard version of the Mauser Spezial MH1235. Footlift by knee switch, backtacking by hand lever.



Sewing area with 51mm arm diameter and standard sewing components. Narrow presser feet for sewing applications close to the material edge.



Binding operation with special device with moving binder attachment. (Subclass -17/01)