YOURPURE WATER FILTERS AZ503 SERIES



AZ503 SERIES - SINGLE, TWIN, TRIPLE & QUAD STAGE SYSTEMS





AZ-503-(L)

42000 L

20 Inch

AZ-503 SINGLE-STAGE SPECIFICATIONS

Flow Rate

6.32 Lpm

Water

2-38°

Scale

Lead

Cartridge(s)	Capacity	Dimensions	Flow Rate	Pressure	Temperature	Phosphate	Reduction	Inhibition
AZ-503-(S)	25000 L	12 Inch	3.2 Lpm	125 PSI	2-38°			√
AZ-503-(M)	33000 L	16 Inch	4.9 Lpm	125 PSI	2-38°		√	✓

125 PSI



AZ-503-MX2

AZ-503-LX2

66000 L

84000 L

16 Inch

20 Inch

AZ-503 TWIN-STAGE SPECIFICATIONS

Water

2-38°

2-38°

Lead

Scale

Cartridge(s)	Capacity	Dimensions	Flow Rate	Pressure	Temperature	Priospilate	Reduction	Inhibition
AZ-503-SX2	50000 L	12 Inch	6.4 Lpm	125 PSI	2-38°		✓	✓

125 PSI

125 PSI

9.8 Lpm

12.64 Lpm



AZ-503 TRIPLE-STAGE SPECIFICATIONS

Cartridge(s)	Capacity	Dimensions	Flow Rate	Pressure	Water Temperature	Phosphate	Lead Reduction	Scale Inhibition
AZ-503-SX3	75000 L	12 Inch	9.6 Lpm	125 PSI	2-38°		✓	✓

AZ-503-MX3 99000 L 16 Inch 14.7 Lpm 125 PSI 2-38° --- ✓ ✓

AZ-503-LX3 126000 L 20 Inch 18.96 Lpm 125 PSI 2-38° --- ✓



AZ-503-LX4

168000 L

20 Inch

AZ-503 QUAD-STAGE SPECIFICATIONS

Scale

Cartridge(s)	Capacity	Dimensions	Flow Rate	Pressure	Temperature	Phosphate	Reduction	Inhibition
AZ-503-SX4	100000 L	12 Inch	12.8 Lpm	125 PSI	2-38°		√	✓
AZ-503-MX4	132000L	16 Inch	19.6 Lpm	125 PSI	2-38°			√

125 PSI

2-38°

25.28 Lpm

YOURPURE WATER FILTERS AZ505 SERIES



AZ505 SERIES - SINGLE, TWIN, TRIPLE & QUAD STAGE SYSTEMS





AZ-505-(L)

42000 L

20 Inch

AZ-505 SINGLE-STAGE SPECIFICATIONS

Water

2-38°

Scale

Lead

Cartridge(s)	Capacity	Dimensions	Flow Rate	Pressure	Temperature	Phosphate	Reduction	Inhibition
AZ-505-(S)	25000 L	12 Inch	3.2 Lpm	125 PSI	2-38°		Pure	✓
AZ-505-(M)	33000 L	16 Inch	4.9 Lpm	125 PSI	2-38°	✓	<i>√</i>	✓

125 PSI

6.32 Lpm



AZ-505-LX2

84000 L

20 Inch

12.64 Lpm

AZ-505 TWIN-STAGE SPECIFICATIONS

		AZ-5	005 I WIN-51A	IGE SPECIFIC	ATIONS	0	0	
Cartridge(s)	Capacity	Dimensions	Flow Rate	Pressure	Water Temperature	Phosphate	Lead Reduction	Scale Inhibition
AZ-505-SX2	50000 L	12 Inch	6.4 Lpm	125PSI	2-38°		✓	√
AZ-505-MX2	66000 L	16 Inch	9.8 Lpm	125PSI	2-38°	✓	√	√

125PSI

2-38°



AZ-505-LX3

126000 L

20 Inch

AZ-505 TRIPLE-STAGE SPECIFICATIONS

Cartridge(s)	Capacity	Dimensions	Flow Rate	Pressure	Temperature	Phosphate	Reduction	Inhibition
AZ-505-SX3	75000 L	12 Inch	9.6 Lpm	125PSI	2-38°		✓	✓
AZ-505-MX3	99000 L	16 Inch	14.7 Lpm	125PSI	2-38°			✓

125PSI

2-38°

18.96 Lpm



AZ-505-LX4

168000 L

20 Inch

AZ-505 QUAD-STAGE SPECIFICATIONS

Water

2-38°

Scale

Cartridge(s)	Capacity	Dimensions	Flow Rate	Pressure	Temperature	Phosphate	Reduction	Inhibition
AZ-505-SX4	100000 L	12 Inch	12.8 Lpm	125 PSI	2-38°	The state of the s	✓	~
AZ-505-MX4	132000 L	16 Inch	19.6 Lpm	125 PSI	2-38°	✓	✓	✓

125 PSI

25.28 Lpm

YOURPURE WATER FILTER FOR HOT BEVERAGE/EQUIPMENTS



www.e-netway.com

AZ-505L & 505S

The YOURPURE AZ-505 Series is designed for use in hot & cold beverage applications. AZ-505 Series incorporates filter cartridges that reduce filter chlorine, odor, asbestos, cyst, Plastic particles, reduce lead, heavy metals, copper, antimony, uranium, zinc, selenium, chrome +6, and scale inhibition in the incoming water source feeding hot & cold drink dispensers. AZ-505 Series filters models incorporate with Specific system AZ-505S, AZ-505M, and AZ-505L filter elements for the reduction of Chlorine, frequently present in municipal water supplies. All YOURPURE AZ-505 incorporates a pressure gauge, water shutoff, and flush valves.

Specifications and Performance Capabilities:

- Dimensions: 3-inch (W) x 12 inch (H) S 20 inch (H)
- Flow rate: 3.2 LPM/S & 6.32 LPM/L per filter
- Capacity: 25,000 litter/S & 42,000 litters/L per filter
- Temperature range: 2 38 degrees C
- Maximum pressure: 125 lbs PSI





YOURPURE WATER FILTER FOR COLD BEVAREGES/DRINKING



AZ-503L & 503S

The YOURPURE AZ-503 Series is designed for use in hot & cold beverage applications. AZ-503 Series incorporates filter cartridges that reduce filter chlorine, odor, asbestos, cyst, plastic particles and reduce scale inhibition in the incoming water source feeding hot & cold drink dispensers. AZ503 Series filters models incorporate with Specific system AZ-503S, AZ-503M, and AZ-503L filter elements for the reduction of Chlorine, frequently present in municipal water supplies. All YOURPURE AZ-503 incorporates a pressure gauge, water shutoff, and flush valves.

Specifications and Performance Capabilities:

- Dimensions: 3-inch (W) x 12 inch (H) S 20 inch (H)
- Flow rate: 3.2 LPM/S & 6.32 LPM/L per filter
- Capacity: 25,000 litter/S & 42,000 litters/L per filter
- Temperature range: 2 38 degrees C
- Maximum pressure: 125 lbs PSI



