



75Z LOUVRE NBS SPECIFICATION


NBS SPECIFICATION 75 'Z' LOUVRE SYSTEM

NBS. The product information below is from Two Point Seven Facades Ltd and is intended for inclusion in project specifications. The details can be copied and pasted into your project specification document. **Please note that NBS product guidance is not a replacement for the manufacturer's literature and it is recommended that Two Point Seven Facades Ltd be consulted before specifying.**

75Z Louvre System

An extruded aluminium louvre system available in a discrete 75 mm pitch configurations for screening, ventilation and rain defence applications.

Manufacturer:	Two Point Seven Facades Ltd							
Website:	www.twopointseven.co.uk							
Tel:	+44(0)1204 302551							
Product Reference:	75 Z Louvre for rain defence, screening & ventilation							
Size:	As detailed on the drawing or schedule.							
Material:	Extruded aluminium 6063-H T5.							
Finish:	Mill finish aluminium	<input type="checkbox"/>	Anodised	<input type="checkbox"/>	Colour ref: ()		
			PPC	<input type="checkbox"/>	Colour ref: ()		
Coverage:	Total:	<input type="checkbox"/>	All components except insect/bird mesh					
	Partial:	<input type="checkbox"/>	Louvre blade and visible outer frames only					
Frame/flashings:	Head:	<input type="checkbox"/>	Cill:	<input type="checkbox"/>	Jamb:	<input type="checkbox"/>		
	Internal flange frame (perimeter)	<input type="checkbox"/>						
	External flange frame (perimeter)	<input type="checkbox"/>						
Guards:	Bird guard:	<input type="checkbox"/>	Expanded aluminium 1050-H14 (SW12mm; LW 8x8mm).				<input type="checkbox"/>	
		<input type="checkbox"/>	Polypropylene mesh structural netting (15mm x 15mm).				<input type="checkbox"/>	
	Insect mesh:	<input type="checkbox"/>	Polypropylene mesh netting (1.9mm x 1.9mm).				<input type="checkbox"/>	
Ancillary items:	None:	<input type="checkbox"/>	Welded mitred corners				<input type="checkbox"/>	
Blanking panels:	Not required:	<input type="checkbox"/>						
	Single skin:	<input type="checkbox"/>	Mill:	<input type="checkbox"/>	PPC:	<input type="checkbox"/>	Anodised:	<input type="checkbox"/>
	Insulated:	<input type="checkbox"/>	25mm	<input type="checkbox"/>	50mm	<input type="checkbox"/>	100mm	<input type="checkbox"/>
Fixings:	Mill finish Stainless Steel							



Guidance for 75Z Louvre System

More about 75Z Louvre systems: As standard - Options.

As standard:	Static louvre	
Materials:	Extruded blades:	Aluminium 6063-H T5
	All other components:	Aluminium 5251 H 22
	Fixings:	Stainless steel
	Anodising grade:	Aluminium J57S
Louvre blade pitch:	75mm	
Louvre blade angle:	45°	
Seals:	Not required	
Finish:	Available in mill, PPC or anodised aluminium. Consult with Two Point Seven Facades Ltd for colours and samples.	
PPC coverage:	Total - All exposed surfaces and edges of components/assemblies excluding fixings, bird guard and insect mesh.	
	Partial - Only external louvre blades, flashings, corners are coated, the remaining components are mill finish.	
Flashings:	The louvres are available with either cill, head, jamb, all perimeter, internal or external flange frame.	
Bird/Insect mesh:	Available in aluminium, galvanized, stainless steel and polypropylene .	
	When mesh is used, the louvre design should allow for additional resistance to airflow/reduced performance.	

Further information

Additional information may be obtained by contacting Two Point Seven Facades Ltd.

Contacts:	www.twopointseven.co.uk
	info@twopointseven.co.uk
	+44(0)1204 302551
	+44(0)7741 556958