

The Mini Pipe Handler WATER SOLUTIONS



Attaches to an excavator arm for sliplining and manoeuvring PE up to 125mm

The process of inserting small diameter PE pipe, live or dead, is now made easier, safer and faster with the use of the new Mini Pipe Handler from **Steve Vick International.**

The lightweight insertion tool attaches to a mini excavator using bucket pins.

During operation, the Mini Pipe Handler can be controlled entirely from the safety of the cab, removing the need for operatives to be in the trench at any time.



the hydraulic upper jaw clamps the pipe and inserts it into the host pipe using the hydraulic power of the excavator. Typical insertion speeds of up to 10 metres per minute can be achieved.

For use with a typical 1.5 - 3 tonne class hydraulic excavator, the Mini Pipe Handler accommodates pipe diameters up to 125mm, with a full range of shell inserts available to handle specific pipe sizes.

The fixed J-shape lower jaw is designed for side loading of the PE; it then cradles the pipe, while


The spring loaded jaw feature allows the Mini Pipe Handler to fit to an excavator with either single or dual flow hydraulics.

BENEFITS

- The side loading jaw avoids the need for operatives to work in the trench
- Safer alternative to using an excavator bucket and sling to insert pipe
- One-stage set up for entire insertion operation
- A Lightweight tool to avoid handling problems
- The Mini Pipe Handler can be fitted to either a single or dual fed excavator
- Adaptable to fit most excavators Achievable insertion speeds of 5—10 metres per minute
- Minimum clearance required—as little as 35mm
- Lower fixed J-shaped jaw keeps a constant controlled depth of pipe for ease of insertion
- Offers efficient, controlled pushing force: pushing action can be reversed if necessary
- Clamp design prevents pipe damage and slipping in wet weather
- Shell inserts from a Steve Vick International pushing machine may be used



NEW! A SAFER & FASTER way to insert coiled PE



Can be fitted to single and dual fed hydraulic excavators

Mini Handler accommodates 25mm or 30mm bucket pins

Fixed J-shaped lower jaw



Hydraulically operated upper jaw

Shell inserts accommodate PE pipe up to 125mm



Steve Vick International Ltd Treenwood Industrial Estate Bradford on Avon Wiltshire BA15 2AU

Phone: +44 (0) 1225 864 864 Email: info@stevevick.com Website: www.stevevick.com











