SEGUIN DRIVELINE SERVICES

612 E. KINGSBURY STREET. SEGUIN. TX 78155 — SEGUINDRIVELINE.COM

2 Piece Shaft using Your Slip yoke and Regular Rear Pinion Yoke

Important: Suspension must be at Normal Ride Height.

Wheels on Ground or Diff. Loaded (wheels not hanging on lift)

Please take all length dimensions from vehicle - NOT the old driveshaft

Slip Yoke Fully Inserted all the way into Trans. (We will calculate correct slip travel) Flat edge of pinion voke is centerline of UJ cap Front Length? Rear Length? Trans. Center of UJ M2-2 Center of UJ Cap Tab or No Tab Note: If Slip Yoke will not bottom out against Center of Carrier Bearing Bolt Holes. When seal. Mark on yoke where it stops at seal. measuring the frame of truck, most carrier bolt holes are slotted for some flex. Go to middle of slots. Front Length from Vehicle Type: _____ center of UJ cap to center of carrier Trans. Type and output spline count ______ bearing bolt holes in frame. Rear Length from center Differential Type if known of carrier bolt holes to flat edge of UJ Series of Pinion Yoke. See UJ Identification for pinion yoke. assistance or call us for assistance. Boot seal on Trans? Pinion Yoke UJ Width: Cap Diameter How Long is boot? Name Phone Address _____ Email or Fax

Fill out all form fields and email to service@seguindriveline.com
Or call us at (830) 372-5356 for assistance.