CRC MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: Brakleen® Brake Parts Cleaner – Non-chlorinated (aerosol)

Product Number (s): 05088, 75088

Product Use: Brake parts cleaner

Manufacturer / Supplier Contact Information:

In United States: CRC Industries, Inc. 885 Louis Drive Warminster, PA 18974 <u>www.crcindustries.com</u> 1-215-674-4300 (General) (800) 521-3168 (Technical) (800) 272-4620 (Customer Service) In Canada: CRC Canada Co. 2-1246 Lorimar Drive Mississauga, Ontario L5S 1R2 <u>www.crc-canada.ca</u> 1-905-670-2291 In Mexico: CRC Industries Mexico Av. Benito Juárez 4055 G Colonia Orquídea San Luís Potosí, SLP CP 78394 www.crc-mexico.com 52-444-824-1666

24-Hr Emergency - CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Extremely Flammable. Harmful or Fatal if Swallowed. May Cause Blindness if Swallowed. Vapor Harmful. Eye and Skin Irritant. Contents Under Pressure. Appearance & Odor: Clear liquid; solvent odor

Potential Health Effects:

ACUTE EFFECTS:

- EYE: Moderate eye irritant. Exposure can cause irritation including stinging, tearing, redness, blurred vision, and swelling of the eyes.
- SKIN: Moderate skin irritant. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of the skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.
- INHALATION: Breathing large amounts of this material may be harmful. Symptoms include irritation of the nose and throat and central nervous system excitation (giddiness), followed by CNS depression (dizziness, drowsiness, weakness, headache, nausea, unconsciousness).
- INGESTION: Swallowing small amounts is not likely to cause harmful effects. May cause stomach or intestinal upset. Swallowing larger amounts may be harmful as this material may be aspirated into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

CHRONIC EFFECTS: Overexposure to methanol may lead to visual impairment.

TARGET ORGANS: liver, kidneys, blood, central nervous system, eyes

Medical Conditions Aggravated by Exposure: skin sensitivities, lung conditions, central nervous system conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Methanol	67-56-1	40 - 50
Toluene	108-88-3	15 – 25
Heptane	142-82-5 / 64742-49-0	15 – 25
Acetone	67-64-1	5 – 15
Carbon dioxide	124-38-9	5 – 10

Section 4: First Aid Measures

Eye Contact:	Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.
Skin Contact:	Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.
Inhalation:	Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.
Ingestion:	Seek medical attention. Do NOT induce vomiting unless instructed by medical personnel. Have victim drink a glass of water if conscious.
Note to Physicians:	This material is an aspiration hazard. This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion. Inhalation of high concentrations of this material may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This product contains methanol. The metabolites of methanol can cause metabolic acidosis, visual disturbances and blindness.

Section 5: Fire-Fighting Measures

Flammable Properties:	This product is extremely flamm (See 16 CFR 1500.3(c)(6)).	nable in accordance with	aerosol flammability definitions.
Flash Poir	nt: 0°F / -18°C (TCC)	Upper Explosive Limit:	ND
Autoignition Temperatur	re: 725°F / 385°C	Lower Explosive Limit:	ND
Fire and Explosion Data:			
Suitable Extinguishing Media	a: Dry chemical, carbon dioxid	de, alcohol-resistant foam	, Class B extinguishers
Products of Combustion:	Oxides of carbon		
•	Aerosol containers, when expos may accumulate in a confined sp		build pressure and explode. Vapors ble atmosphere.
Protection of Fire-Fighters:		and possible toxic deconvided. Use water spray to	nposition products. Proper eye and b keep fire-exposed containers cool

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

- Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.
- Methods for Containment & Clean-up: Eliminate all sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures:	Do not use near potential sources of ignition. Do not use on energized equipment. Use with adequate ventilation. Avoid contact with skin and eyes. Avoid inhaling vapors. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product label.
Storage Procedures:	Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F / 49°C to prevent cans from rupturing.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	OSHA		ACGIH		OTHER		
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Methanol	200	NE	200	250 (s)	NE		ppm
Toluene	200	300 (c)	20	NE	NE		ppm
Heptane	500	NE	400	500	NE		ppm
Acetone	1000	NE	500	750	NE		ppm
Carbon dioxide	5000	30000(v)	5000	30000	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Product Name: Brakleen® Brake Parts Cleaner – Non-Chlorinated (aerosol) **Product Number (s): 05088, 75088**

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, PVA, or neoprene. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: I	iquid					
Color: clear						
Odor: solvent						
Odor Threshold:	ND					
Specific Gravity:	0.782					
Initial Boiling Point:	132°F / 56°C					
Freezing Point:	ND					
Vapor Pressure:	ND					
Vapor Density:	> 1	(air = 1)				
Evaporation Rate:	fast					
Solubility: slight	tly soluble in wat	ter				
Coefficient of water	/oil distribution:	ND				
pH: NA						
Volatile Organic Co	mpounds: <u>w</u>	<u>vt %</u> : 84.0	<u>g/L</u> :	657.2	<u>lbs./gal</u> :	5.5

Section 10: Stability and Reactivity

Stability: Stable		
Conditions to Avoid:	Sources of i	gnition; temperature extremes
Incompatible Materials:		s, reducing agents, strong oxidizing agents, hypochlorites, peroxides, reactive as aluminum and magnesium, sodium, zinc
Hazardous Decomposition Products:		Oxides of carbon, various hydrocarbons
Possibility of Hazardous Reactions:		No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Methanol	5600 mg/kg	15,800 mg/kg	81,000 mg/m ³ /14H
Toluene	636 mg/kg	14,100 μL/kg	49 g/m ³ /4H
Heptane	No data	No data	103 g/m ³ /4H
Acetone	5800 mg/kg	No data	50,100 mg/m ³ /8H
Carbon dioxide	No data	No data	470,000 ppm/30M

No information available

Chronic Toxicity:

Synergistic Effects:

	OSHA	IARC	NTP		
Component	Carcinogen	Carcinogen	Carcinogen	Irritant	<u>Sensitizer</u>
Methanol	No	No	No	E & S (moderate)	Unknown
Toluene	No	No	No	E, S, R (mild)	Unknown
Heptane isomers	No	No	No	E & R (mild) / S (moderate)	Unknown
Acetone	No	No	No	E & S (moderate) / R (mild)	Yes
Carbon dioxide	No	No	No	No	No
			E	– Eye S – Skin	R - Respiratory
Reproductive Toxicity:	No information av	ailable			
Teratogenicity:	No information av	ailable			
Mutagenicity:	No information av	ailable			

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:	Acetone – 48H	LC50 Daphnia:	10 mg/l
Persistence / Degr	adability:	No information	available
Bioaccumulation / Accumulation:		No information	available
Mobility in Environr	ment:	No information	available

Section 13: Disposal Considerations

<u>Waste Classification</u>: The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with the following potential waste code(s): D001, F005. (See 40 CFR Part 261.20 – 261.33) Aerosol containers should be fully emptied and depressurized before disposal. Empty aerosol containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): Consumer Commodity, ORM-D

ICAO/IATA (air): Consumer Commodity, ID8000, 9

IMO/IMDG (water): Aerosols, UN1950, 2.1, Limited Quantity

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Acetone (5000 lbs), Toluene (1000 lbs), Methanol (5000 lbs)

Toluene

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III: Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard Reactive Hazard Release of Pressure Acute Health Hazard Chronic Health Hazard	Yes No Yes Yes No
	Chronic Health Hazard	NO

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: Toluene (< 20%), Methanol (< 46%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): Toluene, Methanol

Occupational Safety and Health Administration:

This product is regulated by the Hazard Communications Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65): This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

<u>Consumer Products VOC Regulations</u>: This product does not comply with Consumer Products VOC regulations and cannot be used in California, Connecticut, Delaware, The District of Columbia, Illinois, Indiana, Maine, Maryland, Massachusetts, Michigan, New Jersey, New Hampshire, New York, Ohio, Pennsylvania, Rhode Island, and parts of Virginia.

State Right to Know:

New Jersey:	67-64-1, 108-88-3, 67-56-1, 124-38-9, 142-82-5
Pennsylvania:	67-64-1, 108-88-3, 67-56-1, 124-38-9, 142-82-5
Massachusetts:	67-64-1, 108-88-3, 67-56-1, 124-38-9, 142-82-5
Rhode Island :	67-64-1, 108-88-3, 67-56-1, 124-38-9 142-82-5

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D1A, D2A, D2B

<u>Canadian DSL Inventory</u>: All ingredients are either listed on the DSL Inventory or are exempt.


European Union Regulations:

<u>RoHS Compliance</u>: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)		
Health:	2	
Flammability:	3	
Reactivity:	0	
PPE:	В	



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick CRC #: 483A Revision Date: 10/06/2011

Changes since last revision: formula change

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH:	American Conference of Governmental Industrial Hygienists	NA:	Not Applicable
CAS:	Chemical Abstract Service	ND:	Not Determined
CFR:	Code of Federal Regulations	NIOSH:	National Institute of Occupational Safety & Health
DOT:	Department of Transportation	NFPA:	National Fire Protection Association
DSL:	Domestic Substance List	NTP:	National Toxicology Program
g/L:	grams per Liter	OSHA:	Occupational Safety and Health Administration
HMIS:	Hazardous Materials Identification System	PMCC:	Pensky-Martens Closed Cup
IARC:	International Agency for Research on Cancer	PPE:	Personal Protection Equipment
IATA:	International Air Transport Association	ppm:	Parts per Million
ICAO:	International Civil Aviation Organization	RoHS:	Restriction of Hazardous Substances
IMDG:	International Maritime Dangerous Goods	STEL:	Short Term Exposure Limit
IMO:	International Maritime Organization	TCC:	Tag Closed Cup
lbs./gal:	pounds per gallon	TWA:	Time Weighted Average
LC:	Lethal Concentration	WHMIS:	Workplace Hazardous Materials Information
LD:	Lethal Dose		System