

Fortane NEXT Premium Wood Adhesive



Flooring Type	Trowel Size	Approximate Coverage	
	For Glue-Down Only Installations		
Engineered Wood		50-60 ft²/gal.	
	$^{3}\!/_{16}$ " x $^{1}\!\!/_{1}$ " x $^{5}\!/_{16}$ " (4.8 x 6.4 x 7.9 mm) Flat V-notch trowel	(1.2-1.5 m ² /L)	
	For Subfloor Moisture Vapor Protection	1	
Engineered Wood And ¾" Solid-Shorts up to 18" Long	1/4" x 1/4" (6.4 x 6.4 mm) V-notch trowel	30-35 ft²/gal. (0.7-0.9 m²/L)	
I	For Gluing Sound Control Materials to the Su	ıbfloor	
For Gluing Sound Control Materials to the Subfloor	½6" x ½6" (1.6 x 1.6 mm) U-notch trowel	165-175 ft²/gal. (4.0-4.3 m²/L)	

A revolutionary and versatile, high performance wood flooring adhesive, that is designed to provide industry-leading moisture vapor control, therefore eliminating the need for a roll-on moisture barrier. Fortane NEXT is suitable for solid, engineered, and parquet wood flooring as well as crumb rubber and cork underlayments. Fortane NEXT combines excellent green grab and strong adhesion while providing easier board replacement without the substrate destruction typically seen with urethane adhesive installations.

Product Features

- No moisture testing required when moisture control installation method is used
 - Extra application of all "roll-on" moisture barriers are not needed
- · Some "hollow spot areas" can be repaired, WITHOUT expensive and time-consuming drilling and injecting
 - Can be used to glue down 3/4" solids (up to 18" long)
 - Excellent elongation; will bridge subfloor cracks up to 1/8"
- · Can be used to glue down recycled rubber and cork sound control underlayment products, up to 5 mm thick
 - · Environmentally friendly, contains no alcohol or solvents
 - · Shelf Life: Two years in unopened container
 - · Open Time: 40-60 minutes

(615) 915-3821

(256) 233-7850

200 Fesslers Lane Nashville, TN 37210

28260 McKee Road Toney, AL 35773