





# A H SUPPLIES

FLOORING TRIM EPOXY & MORE

## Fortane Universal PSA



Substrate/Flooring Type	Recommended Trowel Size	Approximate Coverage*
Porous substrates	$\frac{1}{16}'' \times \frac{1}{16}'' \times \frac{1}{16}''$ (1.6 x 1.6 x 1.6 mm) 	125-175 ft <sup>2</sup> /gal. or 14-20 yd <sup>2</sup> /gal. (12-16 m <sup>2</sup> /3.78 L)
Non-Porous substrates	$\frac{1}{16}'' \times \frac{1}{32}'' \times \frac{1}{32}''$ (1.6 x 0.8 x 0.8 mm) 	175-250 ft <sup>2</sup> /gal. or 19-28 yd <sup>2</sup> /gal. (16-23 m <sup>2</sup> /3.78 L)
Cushion-Backed or Fiber Glass-Backed Sheet Vinyl / Smooth-Backed Vinyl or Non-PVC Carpet Tile	$\frac{3}{8}''$ Nap roller	250-350 ft <sup>2</sup> /gal. or 27-38 yd <sup>2</sup> /gal. (23-32 m <sup>2</sup> /3.78 L)

Fortane Universal PSA is formulated for the installation of dimensionally stable LVT Tile & Vinyl Plank (including foam-backed tile and plank), carpet tile (including PVC and olefin-backed), VCT, stone composite vinyl tile, bio-based tile, recycled rubber, fiberglass-backed sheet flooring and vinyl backed resilient sheet flooring. Fortane Universal PSA is CRI Green Label Plus Certified, and is SCAQMD 1168 compliant.

### Product Features

- Ultra-aggressive pressure sensitive adhesive
  - High tack and robust adhesion
- Immediate foot traffic after PSA method installation
  - Moisture tolerance on concrete up to 99% RH
- Ideal for LVT/LVP – including difficult foam back planks
  - Bonds carpet tile, VCT, and vinyl sheet goods
  - Low VOC
- Shelf Life: Two years in unopened container
  - Open Time: up to 12 hours

(615) 915-3821

200 Fesslers Lane  
Nashville, TN 37210

(256) 233-7850

28260 McKee Road  
Toney, AL 35773