

Farm Stock Rules

One size larger tire width is allowed if rim is one size smaller in diameter

(Example 20.8x38 = 23.1x34)

ABSOLUTELY **NO CUT TIRES** ARE ALLOWED IN "FARM STOCK" CLASSES RULES:

1 Contest is open to farm tractors with rubber tires, no dual wheels, no tire studs, or chains, no governor strings or wires, etc. Four wheel drive allowed; front drive must be disengaged during the pull.

2. Only one pull will be allowed per contestant unless a tie is declared. Last three pullers of prior class will have the option to align in a way that they will not fall into first, second, or third puller, prior to the start of the next class.

3. Drivers must be 16 years of age or at least 14 years of age with parent or guardian's signed consent.

4. Tractor being entered must have the correct series block for the model of the tractor - not just the manufacture's brand.

5. Tractors that exceed the speed of 16 mph or faster **MUST** have the following.

-Roll bar

-Seat belt

-Kill switch

-Side shields

6. NO water injection; NO after market intercooler

7. Tractors must be equipped with factory operational PTO. If the tractor came equipped from factory with a three point hitch, fenders, and/or hydraulics, it must be on to pull and not removed.

8. Tractors must be equipped with a safe drawbar. The drawbar does not have to be stock. Hook point is measured from the center point of the rear axle to the point of hook. Minimum drawbar length shall be 24 inches. Minimum thickness at hitch point must be 1" with a 3 X 3.5 inch hole or clevis.

9. Tractors shall not exceed 3,000 RPM's. Tractors running for points **MUST** have club issued throttle stop which must be set by club official and cannot be tampered with. If the stop is tampered with tractor's rpms must be checked and set by official before the pull. (3001 will result in a DQ)

10. Turbocharger – No bigger than a 2.8 inlet, No bigger than a T4 base.
11. No weight shall extend more than 24 inches beyond the front of the tractor.
12. For all 12,000 lbs, turbo classes and above, "Farm Stock" tractors must pull with factory rear wheels with cast centers if it was equipped from the manufacturer.
13. Tractors must have the correct make and model fuel pump for that make and model being pulled. (example An IH 1066 must run a Rotary fuel pump.)
14. The Hood and Grill must match the make and model of tractor being pulled, NO aftermarket fiberglass or wood grills.
15. All Farm Stock tractors MUST have a wide front end. NO homemade front ends will be allowed.
16. Wheelie bars: Tractors must be equipped with stabilizer bars. stabilizer bars to have pads, not wheels, on bottom of bars. pads to be a minimum of 5 sq. in. pads to be a minimum of 32" rearward from the center of the rearend housing. pads maximum of 10" off the ground. outside to outside length of pads to be a minimum of 20". minimum 12" high bumper bars - top to be fastened to stabilizer bar framing. bars must support weight of tractor for weight class being pulled .