

AC Commercial Single/Dual-Gun EV Charger

Single Phase - 7kW | 3 Phase - 11kW, 22kW



- AC Commercial single or dual plug/socket connection EV Charger.
- **Simple installation:** No complicated installation process is required, it can be used when power is connected.
- **Wide Compatibility:** Compatible with AC charging and Tesla three-phase charging on the market.
- **Charging Function:** Adaptive 220V/380V(400V) power supply.
- **Emergency Stop Button:** Equipped with emergency stop button on the side to ensure charging safety.



Simple Operation

- Start/Stop charging by RFID card
- 4.3-inch LCD touch screen
- 3 LED indicators-Power/ Charging/ Fault



Cost Effective

- Aluminum alloy integral molding
- Enclosure Material PC Plastic

Flexible Option

- Type 1 or Type 2 charging cable
- SAE J1172 and IEC 62196-2 standards

Secure and Safe

- Residual current protection
- Over temperature protection
- Over current protection
- Short circuit protection

	Category	Power	Voltage	Input Max Current
AC EV Charger (COMMERCIAL USE)	Type 1 S	7kW	220V	32A
	Type 2 S	11kW	380V	16A
		22kW	380V	32A
	Type 1 D	7+7kW	220V	64A
Type 2 D	11+11kW	380V	32A	
	22+22kW	380V	64A	
External Communication	RJ45, 4G(Optional)			
OCPP	OCPP 1.6 (Optional)			
Protection Rating	IP55			
Weight	34Kg			
Dimension (HxWxD)	1450x350x160mm			
Cable Length	5 meter			

Visit our Website at:

www.arbarr-ess.co.uk

email: enquiries@arbarr.co.uk

Arbarr Electronics Ltd

Unit 3, Aghanloo Industrial Estate, Limavady, BT490EF

Telephone: 02877766611

© 2022 Arbarr Electronics Ltd. All rights reserved.



AC Wallbox Intelligent EV Charger

Single Phase - 3.5kW, 7kW | 3 Phase - 11kW, 22kW



Socket - Type1/Type2



Plug - Type1/Type2

- AC Wallbox Intelligent EV Charger with plug charger with type 1 or type 2 plug to charge cars. (TESLA needs an adapter.)
- Screens show EV car charger electricity consumption, current, voltage, hours, etc.
- Managing system for adjusting the current, observing charging data and history, etc.
- Build-in type B RCD leakage protection: detect all leakages from cars.
- App control start and stop EV cars charging, make an appointment for charging.

Simple Operation

- Start/Stop charging by RFID card
- Simple HMI with LED indicators



Cost Effective

- Half size of A4 paper, compact design
- Home use with competitive price

Flexible Option

- Type 1 or Type 2 charging cable
- Wall-mount or floor-stand installation

Secure and Safe

- Residual current protection
- Over temperature protection
- Over current protection
- Surge protection
- Short circuit protection

	Category	Power	Voltage	Input Max Current
AC EV Charger (HOME USE)	TYPE 1	3.6kW	220V	16A
		7kW	220V	32A
	TYPE 2	3.6kW	220V	16A
		7kW	220V	32A
		11kW	380V	16A
		22kW	380V	32A
External Communication	WiFi, 4G(Optional)			
OCPP	OCPP 1.6 (Optional)			
Protection Rating	IP66			
Weight	8.5kg			
Dimension (HxWxD)	320x197x90mm			
Cable Length	5 meter			

Visit our Website at:
www.arbarr-ess.co.uk

email: enquiries@arbarr.co.uk

Arbarr Electronics Ltd

Unit 3, Aghanloo Industrial Estate, Limavady, BT490EF

Telephone: 02877766611

© 2022 Arbarr Electronics Ltd. All rights reserved.

