



DAEWOO

POWER PRODUCTS



PRODUCTS CATALOGUE


WWW.DAEWOOPowerPRODUCTS.COM



- AIR COMPRESSORS
- VACUUM CLEANERS
- WATER PUMPS
- POWER TOOLS
- WELDING MACHINES

 **DAEWOO**
POWER PRODUCTS





AIR COMPRESSOR

DAC24D

⚡ 2 hp / 1.5 kW

Pressure: 8 bar

Cylinders: 1*42 mm

Max flow: 195 L/min

Engine speed: 3450 rpm

Tank Capacity: 24 L

Engine insulation: B

Protection: IP20

Phase: 1

Support antivibration feet: 1



AIR COMPRESSOR

DAC50D

⚡ 2.5 HP / 1.87 KW

Pressure: 8 bar

Cylinders: 1*42 mm

Max Flow: 195 L/min

Tank capacity: 50 L

Engine speed: 3450 rpm

Engine insulation: B

Protection: IP20

Phase: 1

Support antivibration feet: 1



VACUUM CLEANER

DAVC90-60L

⚡ 1200 W

Vacuity: ≥20 Kpa

Flow: 1.5 m³/min

Suction hose diameter: 32 mm

Suction hose length: 1.5 m

Tank capacity: 60 L

Includes: Hose assembly, round brush, Crevice nozzle.

waterproof
POWER
SWITCH

eco
Friendly



VACUUM CLEANER

DAVC90-80L

⚡ 2000 W

Vacuity: ≥23 Kpa

Flow: 3.2 m³/min

Suction hose diameter: 38 mm

Suction hose length: 1.5 m

Tank capacity: 80 L

Includes: Hose assembly, round brush, Crevice nozzle.

waterproof
POWER
SWITCH

eco
Friendly



GASOLINE WATER PUMPS

GAE50

⚡ 2.5 KW

Pump Type: Self-priming centrifugal pump

Suction diameter: 2" / 50 mm

Exit diameter: 2"/50 mm

Max suction head: 7 m

Max discharge head: 28 m

Flow: 30 m³/h

Engine type: 4 Stroke/25° Single cylinder / Air Cooled

Starting system: Recoil

Engine speed: 3600 rpm

Oil capacity: 0.6 L

Fuel tank capacity: 3.6 L

Tool kit: Spark Plug, Extension Bar, Hoop

SUPER STRONG 38mm Frame



GASOLINE WATER PUMPS

GAE80

⚡ 2.5 KW

Pump type: Self-priming centrifugal pump

Suction diameter: 3" / 80 mm

Exit diameter: 3"/80 mm

Max suction head: 7 m

Max discharge head: 30 m

Flow: 60 m³/h

Engine type: 4 Stroke / 25° Single cylinder/Air Cooled

Starting system: Recoil

Engine speed: 3600 rpm

Oil type/oil capacity: 10W30 / 0.6 L

Fuel tank capacity: 3.6 L

Tool kit: Spark Plug, Extension Bar, Hoop

SUPER STRONG 38mm Frame



CENTRIFUGAL PUMPS

DAECPM130

⚡ 370 W

Speed: 3450 rpm

Max height: 15 m

Max flow: 4500 L/h

Max suction: 8 m

Suction: 1"

Discharge diameter: 1"

CENTRIFUGAL PUMPS

DAECPM158

⚡ 750 W

Speed: 3450 rpm

Max height: 25 m

Max flow: 6500 L/h

Max suction: 8 m

Suction: 1"

Discharge diameter: 1"

CENTRIFUGAL PUMPS

DAECPM146

⚡ 550 W

Speed: 3450 rpm

Max height: 22 m

Max flow: 5360 L/h

Max suction: 8 m

Suction: 1"

Discharge diameter: 1"



PERIPHERAL PUMPS

DAEQB60

⚡ 370 W

Speed: 3450 rpm
 Max height: 30 m
 Max flow: 2400 L/h
 Max suction: 8 m
 Suction: 1"
 Discharge diameter: 1"



SUCTION PUMPS

DAEJET100S

⚡ 750 W

Speed: 3450 rpm
 Max height: 45 m
 Max flow: 2760 L/h
 Max suction: 8 m
 Suction: 1"
 Discharge diameter: 1"



PRESSURIZING EQUIPMENT

AUTOJET100S

⚡ 750 W

Speed: 3450 rpm
 Max height: 28 m
 Max flow: 2520 L/h
 Max suction: 8 m
 Suction: 1"
 Discharge diameter: 1"



ANGLE GRINDER

DAAG115-85

⚡ 850 W

Disc diameter: 115 mm
 No load speed: 11000 rpm



IMPACT DRILL

DAID500

⚡ 500 W

No load speed: 0-2700 rpm
 Chuck diameter: 13 mm
 Max in steel: 10 mm
 Max in concrete: 13 mm
 Max in wood: 20 mm
 Includes: Chuck key. Side handle,
 Depth gauge.



INVERTER WELDING MACHINE

MINIDW160IMMA

⚡ 3.7 kW

Input capacity: 5.1 kVA
 No-load loss: 40 W
 Input current: 26 A
 Output current range: 20-160 A
 Rated duty cycle: 60%
 No load voltage: 56 V
 Efficiency: 80%
 Power factor: 0,73
 Insulation class: H
 Protect class: IP21S

IGBT TECHNOLOGY
 ENERGY SAVING AND THERMAL STABILITY


ARC WELDER MACHINE

DAX1-180C1

⚡ 7 kW

Output current: 60/180 A
 Current range: 60 - 180 A
 Input capacity: 7 kW
 No load voltage: 48 V
 Protection grade: IP21S
 Duty cycle: 10%
 Insulation class: F
 Welding rod diameter:
 2.0 - 4.0 mm

ARC WELDER MACHINE

DAX1-250C1

⚡ 10 kW

Output range: 200/220 A
 Current range: 85-250 A
 Input capacity: 10 kW
 No load voltage: 60 V
 Protection grade: IP21S
 Duty cycle: 10%
 Insulation class: F
 Welding rod diameter:
 2.5 - 5.0 mm



ARC WELDER MACHINE DABX1-160B

5 kW

Output current: 140/160 A

Current range: 55 - 160 A

Input capacity: 5 kW

No load voltage: 48 V

Protection grade: IP21S

Duty cycle: 10%

Insulation class: F

Welding rod

diameter: 1.6 - 3.2 mm



CAR VACUUM CLEANER DAVC12C

60-80 W

Voltage: 12 V

Cord with cigarette lighter: 10 feet

Net weight: 1.5 kg

Includes: 12 V Lighter plug, Hose, Adaptor connection, Brush, Crevice tool, Inflation.



FLOOR JACK DASJ01

Lifting weight: 1.5 ton

Min. height: 105 mm

Max. height: 385 mm

Net weight: 3.1 kg



FLOOR JACK DAFJ03

Lifting weight: 2 ton

Min. height: 125 mm

Hydraulic height: 175 mm

Max. height: 300 mm

Net weight: 6.65 kg



HYVC100A HIGH PRESSURE WASHER AND VACUUM CLEANER

1700 W

Voltage / frequency: 110V~ 60Hz

Power (High Pressure Washer): 1700 W

Max. Pressure: 15 MPa

Max. Flow: 300 L/h

Max. temperature: 40° C

Power (Vacuum cleaner): 700 W

Sound level: 90 dB (A)

Degree of protection: IPX5



WASHING
POWER



MAX
FLOW



EASY
TRANSPORTATION

ERGONOMIC
DESIGNS

SOFT
GRIP

2IN1



Energizer®

TM



PRODUCTS CATALOGUE

www.energizerpowerproducts.com



• AIR COMPRESSORS

Energizer.

EZC 24D

Air compressor



Compressor



Wheels
for easy
transportation



Fast inflate



Electric start



Manometer



Max power

ERGONOMIC HANDLE
Safe to carry and use
the machine.



SAFETY VALVE
Avoids the equipment failure
cause by pressure excess.



EASY TRANSPORT
Rough wheels that never
flat to ease its maneuverability.



EZC 50D

Air compressor



Compressor



Wheels
for easy
transportation



Fast inflate



Electric start



Manometer



Max power

SAFETY VALVE
Avoids the equipment failure
cause by pressure excess.



ERGONOMIC HANDLE
Safe to carry and use
the machine.



EASY TRANSPORT
Rough wheels that never
flat to ease its maneuverability.



SPECIFICATIONS

Voltage/Frecuency	120 V / 60 Hz
Power	2 hp / 1.5 kW
Cylinders	1*42 mm
Phases	1
Speed	2800 rpm
Isolation	B
Protection	IP20
Flow	195 L/min
Capacity	24 L
Pressure	8 bar / 115 psi
Wheels	2
Anti-vibration support feet	1

SPECIFICATIONS

Voltage/Frecuency	120 V / 60 Hz
Power	2 hp / 1.87 kW
Cylinders	1*42 mm
Phases	1
Speed	2800 rpm
Isolation	B
Protection	IP20
Flow	195 L/min
Capacity	50 L
Pressure	8 bar / 115 psi
Wheels	2
Anti-vibration support feet	2

EZC 100D

Air compressor



Compressor



Wheels
for easy
transportation



Fast inflate



Electric start



Manometer



Max power

SAFETY VALVE

Avoids the equipment failure
cause by pressure excess.



ERGONOMIC HANDLE

Safe to carry and use
the machine.



EASY TRANSPORT
Rough wheels that never
flat to ease its maneuverability.

SPECIFICATIONS

Voltage/Frequency	120 V / 60 Hz
Power	3 hp / 2.2 kW
Cylinders	1*48 mm
Phases	1
Speed	2800 rpm
Isolation	B
Protection	IP20
Flow	195 L/min
Capacity	100 L
Pressure	8 bar / 115 psi
Wheels	2
Anti-vibration support feet	2



HYUNDAI
POWER PRODUCTS

Energizer

GBR CORP.

GBR CORPORATION LTD.

Room 03, 16th Floor, Block A,
China Resources Plaza, Xiejiawan,
Jiulongpo District, Chongqing, China.
Ph: (0086) 23 68166136