

SUPREMUS

QED/



WWW.QED.CO.UK



THE ULTIMATE EXPRESSION

OF SOUND BORN FROM
PURE SCIENCE



"its overall sense of balance most impressed... QED's Supremus...One Cable To Rule Them All." Hi-Fi+ Awards 2017





A NEW ENAMELLED CONDUCTOR INSULATION

The conductors are uniquely individually insulated by a nearly invisible layer of enamel.

This material was chosen because it has extremely good insulating properties and sets new standards in the insulation hierarchy.



QED AIRCORE™ TECHNOLOGY

QED's proprietary Aircore™ Technology keeps inductance and capacitance at vanishly low levels. This changes the magnetic field within the cable to ensure high frequencies travel through the central part of the conductor. The result is an unrivalled level of high frequency detail and cable timing.



6.2mm² CROSS SECTIONAL AREA

Boasting two bundles of 16 Silver plated, cryogenically treated oxygen free copper conductors for ultralow resistance exerting beautiful control, bringing your amplifier and speaker electrically closer together.



SUPREMUS LOCKING AIRLOC™ PLUGS

A dedicated pure copper, Rhodium plated locking design to ensure maximum surface contact between the plug and terminals. Utilising QED's propriety Airloc™ technology for an oxygen free, cold weld connection made for life.



OVER 40 YEARS IN THE MAKING

UNMATCHED IN QUALITY

BRITISH FROM START TO FINISH

UNRIVALLED IN COMPETITION

LIFETIME GUARANTEE



"Undoubtedly audiophile class, this ambitious and physically impressive UK loudspeaker cable is one of very few to gain an Audio Excellence rating."

Hi-Fi Critic Audio Excellence 2017





OUR LARGEST EVER CROSS SECTIONAL AREA

Vanishingly low resistance for better speaker and amplifier control

QED AIRCORE™ TECHNOLOGY - A UNIQUE GEOMETRY AND CONSTRUCTION

For unrivalled high frequency detail and cable timing

ENAMEL COATED CONDUCTORS

 $\ensuremath{\mathsf{A}}$ new superior insulation for reduced capacitance and consistent energy flow

RHODIUM PLATED AIRLOC™ LOCKING PLUGS

Maintaining the fidelity of the audio signal from start to finish



"Superbly constructed and intelligently engineered... They'll bring the best out of your equipment"

Hi-Fi World 2017



THE SOUND OF SCIENCE

SUPREMUS SPECIFICATIONS

CROSS-SECTIONAL AREA

6.16 mm²

WIRE GAUGE

10 AWG

JACKET OUTSIDE DIAMETER

17 m m

JACKET INTERNAL DIAMETER

8 m m

LOOP RESISTANCE

 $0.005 \Omega/m$

CAPACITANCE

48 pF/m

INDUCTANCE

 $0.49 \mu H/m$

DISSIPATION FACTOR

0.009

CONDUCTORS

2 x 16 solid core silver plated 99.999% oxygen free copper conductors

INSULATION

Unique enamel with low loss surrounding foamed polyethylene dielectric insulation

PLUGS AND SPADES

Pure copper, Rhodium plated locking Airloc™ Plugs and Spades available

OTHER

Aircore™ Technology Cryogenically treated



www.qed.co.uk

ZB0265

Our policy is one of continuous product improvement, we reserve the right to change the designs and specifications without notice. All information is given in good faith. The manufacturer accepts no responsibility for errors, omissions or incorrect assumptions. Armour Home Electronics 2018. E&OE.





gedofficial



QED Supremus