

Warranty: (90) days install, (1) year parts & labor, (5) years compressor

Model No.		KPP20-1	KPP33-1	KPP50-1	KPP50-2	KPP75-1	KPP75-2	KPP75-1-230	KPP75-2-230	KPP75-3-230
Electrical	Voltage	120V	120V	120V	120V	120V	120V	230V**	230V**	230V**
	Frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
	Phase	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø	1Ø
	Electrical Connection	Cord & Plug NEMA 5-20P	Cord & Plug NEMA 5-20P	Hard Wire	Hard Wire	Hard Wire	Hard Wire	Hard Wire	Hard Wire	Hard Wire
120V Single Pump (Models ending '-1')	RLA	11A	12.5A	15.3A	-	19.6A	-	-	-	-
	MCA	20A	20A	20A	-	25A	-	-	-	-
120V Double Pump (Models ending '-2')	RLA	-	-	-	21.3A	-	24.5A	-	-	-
	MCA	-	-	-	25A	-	30A	-	-	-
230V Single Pump (Models ending '-1-230')	RLA	-	-	-	-	-	-	11A	-	-
	MCA	-	-	-	-	-	-	20A	-	-
230V Double Pump (Models ending '-2-230')	RLA	-	-	-	-	-	-	-	14A	-
	MCA	-	-	-	-	-	-	-	20A	-
230V Triple Pump (Models ending '-3-230')	RLA	-	-	-	-	-	-	-	-	17A
	MCA	-	-	-	-	-	-	-	-	25A
Length (A)		27"	27"	27"	27"	27"	27"	27"	27"	27"
Width (B)		17"	17"	17"	17"	20"	20"	20"	20"	20"
Height (C)		24-1/2"	24-1/2"	24-1/2"	24-1/2"	26"	26"	26"	26"	26"
Weight		119 lbs	124 lbs	129 lbs	143 lbs	159 lbs	173 lbs	159 lbs	173 lbs	187 lbs
Compressor		1/5 HP	1/3 HP	1/2 HP	1/2 HP	3/4 HP	3/4 HP	3/4 HP	3/4 HP	3/4 HP
Evaporator Rating @ 15° F (BTUH)		1680	2600	4100	4100	6950	6950	6950	6950	6950
Heat Rejection (average) (BTUH)		2184	3380	5330	5330	9035	9035	9035	9035	9035
Refrigerant		R134A	R134A	R134A	R134A	R134A	R134A	R134A	R134A	R134A
Cabinet Material		Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Circulating Pump		80 GPH / 100 PSI	80 GPH / 100 PSI	80 GPH / 100 PSI	80 GPH / 100 PSI	80 GPH / 100 PSI	80 GPH / 100 PSI	80 GPH / 100 PSI	80 GPH / 100 PSI	80 GPH / 100 PSI
Reservoir Capacity (gallons)		1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8
Refrigerant Charge		12.5 oz.	14 oz.	15.5 oz.	15.5 oz.	20 oz.	20 oz.	20 oz.	20 oz.	20 oz.
Glycol Concentration		33%	33%	33%	33%	33%	33%	33%	33%	33%

RLA = Rated Load Amps
MCA = Minimum Circuit Ampacity

** 230V models require four wires - 2 hot, 1 neutral, and 1 ground

