

TABLE OF CONTENTS

Product Lines

- High Relief Liners | Pages 3-5
- Colorways | Pages 6-7
- 4 Shades of Gray | Pages 8-11
- City Scape | Pages 12-16
- Grout-Ready Niche | Pages 17-19
- The Jolly | Pages 20-22
- Bath Accessories | Pages 23-28
- Cast Metal Mosaics | Page 29-31
- Cast Metal Tile & Trim | Page 32-34

Merchandising | Pages 35-38

FAQ's, Technical Specifications & Installation Instructions | Pages 39-47

About Questech | Pages 48-51







HIGH RELIEF LINERS

CAST STONE | SEAMLESS TRANSITION

POLISHED BRIGHT WHITE 2" X 12" LINEAR CHAIR RAIL 34" X 12" SOHO BULLNOSE ½" X 12" SOHO PENCIL 34" X 12" LINEAR LINER SL823-23 SL826-23 SL825-23 SL824-23 ½" X 12" LINEAR PENCIL ½" X 12" NAIL HEAD PENCIL ½" X 12" CORNICE PENCIL SL827-23 SL829-23 SL828-23 MATTE BRIGHT WHITE 2" X 12" LINEAR CHAIR RAIL 34" X 12" SOHO BULLNOSE ½" X 12" SOHO PENCIL 34" X 12" LINEAR LINER SL823-67 SL824-67 SL826-67 SL825-67 ½" X 12" LINEAR PENCIL 1/2" X 12" NAIL HEAD PENCIL 1/2" X 12" CORNICE PENCIL SI 827-67 SI 829-67 SI 828-67 MATTE GRAPHITE 2" X 12" LINEAR CHAIR RAIL 34" X 12" SOHO BULLNOSE ½" X 12" SOHO PENCIL 34" X 12" LINEAR LINER ML823086 ML824086 ML825086 ML826086 ½" X 12" NAIL HEAD PENCIL ½" X 12" LINEAR PENCIL ½" X 12" CORNICE PENCIL

ML828086



ML829086

ML827086



HIGH RELIEF LINERS

CAST STONE | SEAMLESS TRANSITION

POLISHED GRAY 2" X 12" LINEAR CHAIR RAIL 34" X 12" SOHO BULLNOSE 1/2" X 12" SOHO PENCIL 34" X 12" LINEAR LINER SL825-21 SL823-21 SL824-21 SL826-21 1/2" X 12" LINEAR PENCIL ½" X 12" NAIL HEAD PENCIL ½" X 12" CORNICE PENCIL SL827-21 SL829-21 SL828-21 MATTE GRAY 2" X 12" LINEAR CHAIR RAIL 34" X 12" SOHO BULLNOSE ½" X 12" SOHO PENCIL 34" X 12" LINEAR LINER SL823-12 SL824-12 SL826-12 SL825-12

½" X 12" CORNICE PENCIL

SL828-12

½" X 12" NAIL HEAD PENCIL

SL829-12



1/2" X 12" LINEAR PENCIL

SL827-12







BRING US A COLOR THAT INSPIRES YOU AND WE'LL MATCH IT!

COLORWAYS CUSTOM COLOR PROGRAM - AVAILABLE ON OUR DECORATIVE TRIM DESIGNS

ColorWays by Questech allows you to add the perfect finishing touch to complete your installation with custom color trim and high relief tile liners. Decorative liners are a great way to create a seamless transition between your wall and tile installation and now you can get this finished look in any custom color. The ColorWays program is a new custom color process that allows us to march any color sample. Create your own color palette and submit it to us to develop and apply new colors to any of our high relief liners, jollys, and chair rail designs. If you have a paint sample, fabric swatch, Pantone chip or seasonal colorway, we can create a color formula to bring you vision to life with our decorative finishing pieces.

HOW IT WORKS:

BRING US YOUR COLOR INSPIRATION AND WE'LL MATCH IT WITH OUR IN HOUSE CUSTOM COLORIMETER PROCESS.

COLORWAYS PROCESS

- 1. Provide a product sample or swatch with the desired colorway and chose from any of our 8 different liner, jolly and chair rail design (minimum orders apply).
- 2. Questech technicians will create a ColorWays custom color formula based on the color submission and produce a sample for review.
- 3. If adjustments are needed from the initial samples, adjustments will be made and a final sample provided for approval before production.
- 4. Approximately 4-6 weeks after approvals, the products will be ready to ship.

LINER DESIGNS:

APPLY YOUR CUSTOM COLOR TO ANY OF THESE 8 DECORATIVE TRIM DESIGNS:

2" X 12" LINEAR CHAIR RAIL

½" X 12" SOHO BULLNOSE

½" X 12" SOHO PENCIL

½" X 12" LINEAR LINER

½" X 12" LINEAR PENCIL







4 SHADES OF GRAY

ON-TREND COLLECTION OF NEUTRALS | FLOOR & WALL

ARABESQUE | CAST METAL

SILVER LINING POLISHED (RES)



2" X 2" TILE768035001



4" X 8" TILE771035001





2" X 12" TILE770035001



2.5" X 15" MOSA600-003

TITANIUM
POLISHED (RES)



2" X 2" TILE768039001



4" X 8" TILE771039001





2" X 12" TILE770039001

BRUSHED NICKEL EGGSHELL @



2" X 2" TILE768024011



4" X 8" TILE771024011





2" X 12" TILE770024011





2" X 2" TILE768068011



4" X 8" TILE771068011





2" X 12" TILE770068011







4 SHADES OF GRAY

ON-TREND COLLECTION OF NEUTRALS | FLOOR & WALL

BASKETWEAVE | CAST METAL

SILVER LINING POLISHED RES



2" X 2" TILE758035001



4" X 8" TILE761035001



2" X 12" TILE760035001



TITANIUM POLISHED ®ES



2" X 2" TILE758039001



4" X 8" TILE761039001





2" X 12" TILE760039001

BRUSHED NICKEL EGGSHELL @



2" X 2" TILE758024011



4" X 8" TILE761024011





2" X 12" TILE760024011





2" X 2" TILE758068011



4" X 8" TILE761068011





" X 12" TILE760068011





4 SHADES OF GRAY

ON-TREND COLLECTION OF NEUTRALS | FLOOR & WALL





2" X 2" TILE763035001



4" X 8" TILE766035001





2" X 12" TILE765035001



TITANIUM
POLISHED (RES)



2" X 2" TILE763039001



4" X 8" TILE766039001





BRUSHED NICKEL EGGSHELL @



2" X 2" TILE763024011



4" X 8" TILE766024011





2" X 12" TILE765024011





2" X 2" TILE763068011



4" X 8" TILE766068011





2" X 12" TILE765068011







FOR COMMERCIAL OR RESIDENTIAL USE | FLOOR & WALL

BURNISHED - EGGSHELL

BRUSHED NICKEL @

1" X 18" BULLNOSE TILE502024011



12" X 18" TILE501024011



4" X 18" TILE506024011



4" X 12" TILE505024011



4" X 8" TILE504024011

BRONZE @

1" X 18" BULLNOSE TILE502002011



12" X 18" TILE501002011



2" X 18" TILE503002011



4" X 18" TILE506002011



4" X 12" TILE505002011



4" X 8" TILE504002011

GOID @

1" X 18" BULLNOSE TILE502040011



12" X 18" TILE501040011





4" X 18" TILE506040011



4" X 12" TILE505040011



4" X 8" TILE504040011





FOR COMMERCIAL OR RESIDENTIAL USE | FLOOR & WALL

BURNISHED - EGGSHELL

COPPER @

1" X 18" BULLNOSE TILE502003011



12" X 18" TILE501003011



2" X 18" TILE503003011



4" X 18" TILE506003011



4" X 12" TILE505003011



4" X 8" TILE504003011

DARK OIL RUBBED BRONZE @

1" X 18" BULLNOSE TILE514070003



12" X 18" TILE513070003



2" X 18" TILE515070003



4" X 18" TILE518070003



4" X 12" TILE517070003



4" X 8" TILE516070003

IRON 🕮

1" X 18" BULLNOSE TILE502068011



12" X 18" TILE501068011






4" X 18" TILE506068011



4" X 12" TILE505068011



4" X 8" TILE504068011





FOR COMMERCIAL OR RESIDENTIAL USE | FLOOR & WALL

WATER - EGGSHELL BRUSHED NICKEL @

1" X 18" BULLNOSE TILE496024011




1" X 18" BULLNOSE TILE496002011



1" X 18" BULLNOSE TILE496040011



1" X 18" BULLNOSE TILE496068011



TILE495024011

12" X 18"









12" X 18"

2" X 18"





TILE495002011

















4" X 12" TILE499002011



4" X 18" TILE500068011







4" X 12" TILE499040011







4" X 8" TILE498002011



4" X 8" TILE498040011



4" X 8" TILE498068011





FOR COMMERCIAL OR RESIDENTIAL USE | FLOOR & WALL

HAMMERED - POLISHED

BRUSHED NICKEL ®ES

BRONZE RES

1" X 18" BULLNOSE TILE508024001

1" X 18" BULLNOSE TILE508002001

COPPER RES

1" X 18" BULLNOSE TILE508003001

IRON ®ES

1" X 18" BULLNOSE TILE508068001



12" X 18" TILE507024001



12" X 18" TILE507002001



12" X 18" TILE507003001



12" X 18" TILE507068001



2" X 18" TILE509024001



2" X 18" TILE509002001



2" X 18" TILE509003001



2" X 18" TILE509068001



4" X 18" TILE512024001



4" X 18" TILE512002001



4" X 18" TILE512003001



4" X 18" TILE512068001



4" X 12" TILE511024001



4" X 12" TILE511002001



4" X 12" TILE511003001



4" X 12" TILE511068001



4" X 8" TILE510024001



4" X 8" TILE510002001



4" X 8" TILE510003001



4" X 8" TILE510068001









PAGE 16



GROUT-READY NICHE

READY TO INSTALL BUILT-IN STYLE

CLASSIC POLISHED WHITE



12" X 12" SNCH745-13

POLISHED GRAY



12" X 12" SNCH745-21

BRUSHED NICKEL



12" X 12" MNCH741-024

DARK OIL RUBBED BRONZE



12" X 12" MNCH741-070

COTTAGE
POLISHED WHITE



12" X 12" SNCH754-13

POLISHED GRAY




12" X 12" SNCH754-21

BRUSHED NICKEL



12" X 12" MNCH751-024

DARK OIL RUBBED BRONZE



12" X 12" MNCH751-070



GROUT-READY NICHE

READY TO INSTALL BUILT-IN STYLE

ARABESQUE POLISHED WHITE



12" X 12" SNCH752-13

POLISHED GRAY



12" X 12" SNCH752-21

BRUSHED NICKEL



12" X 12" MNCH749-024

DARK OIL RUBBED BRONZE



12" X 12" MNCH749-070

WAVE
POLISHED WHITE



12" X 12" SNCH753-13

POLISHED GRAY



12" X 12" SNCH753-21

BRUSHED NICKEL - POLISHED



12" X 12" MNCH750-024

DARK OIL RUBBED BRONZE



12" X 12" MNCH750-070





THE JOLLY 1/4 ROUND WITH INNOVATIVE VERSATILITY

THE JOLLY | CAST METAL BRUSHED NICKEL - POLISHED

BRUSHED NICKEL - POLISHED	
½" X 12" - ¼ ROUND	TILE700024001
BRONZE - POLISHED	
½" X 12" - ¼ ROUND	TILE700002001
TITANIUM - POLISHED	
½" X 12" - ¼ ROUND	TILE700039001
BRUSHED NICKEL - EGGSHELL	
½" X 12" - ¼ ROUND	TILE700024011
BRONZE - EGGSHELL	
½" X 12" - ¼ ROUND	TILE700002011
TITANIUM - EGGSHELL	
½" X 12" - ¼ ROUND	TILE700039011

WROUGHT IRON - POLISHED

1/2" X 12" - 1/4 ROUND

WROUGHT IRON - POLISHED	
½" X 12" - ¼ ROUND	TILE7000680
COPPER - POLISHED	
½" X 12" - ¼ ROUND	TILE7000030
DARK OIL RUBBED BRONZE - BF	RIGHT SATIN
½" X 12" - ¼ ROUND	TILE7010700
WROUGHT IRON - EGGSHELL	
½" X 12" - ¼ ROUND	TILE7000680
COPPER - EGGSHELL	
½" X 12" - ¼ ROUND	TILE7000030
GOLD - EGGSHELL	



TILE700040011

THE JOLLY 1/4 ROUND WITH INNOVATIVE VERSATILITY

THE JOLLY | CAST STONE

GRAY - POLISHED

½" X 12" - ¼ ROUND SL700-21

GRAY - MATTE

½" X 12" - ¼ ROUND SL700-12

WHITE - POLISHED

½" X 12" - ¼ ROUND SL700-13

WHITE - MATTE

½" X 12" - ¼ ROUND SL700-25

SAND - POLISHED

½" X 12" - ¼ ROUND SL700-26

SAND - MATTE

½" X 12" - ¼ ROUND SL700-03

TRAVERTINE - POLISHED

½" X 12" - ¼ ROUND SL700-27

TRAVERTINE - MATTE

½" X 12" - ¼ ROUND SL700-01

more about


THE JOLLY

COMMERCIAL + RESIDENTIAL

With six metals in polished and eggshell finishes as well as 4 stones in polished and matte finishes, the Jolly is protected from water, stains, mold and abrasions by Q-Seal, the world's first factory-applied lifetime sealer.

THE FINISHING TOUCH: INSPIRED DESIGN, MADE EASY.

INNOVATIVE VERSATILITY







METRO + RETROFIT

BATH ACCESSORIES | CAST STONE POLISHED BRIGHT WHITE



10" CORNER SHELF METRO SBA117-23 RETRO SBA153-23



5" CORNER SHELF METRO SBA113-23 RETRO SBA157-23



8" CORNER SHELF METRO SBA115-23 RETRO SBA155-23



5" FOOT REST METRO SBA121-23 RETRO SBA159-23

POLISHED GRAY



10" CORNER SHELF METRO SBA117-21 RETRO SBA153-21



5" CORNER SHELF METRO SBA113-21 RETRO SBA157-21



8" CORNER SHELF METRO SBA115-21 RETRO SBA155-21



5" FOOT REST METRO SBA121-21 RETRO SBA159-21

POLISHED WHITE



10" CORNER SHELF METRO SBA117-13 RETRO SBA153-13



5" CORNER SHELF METRO SBA113-13 RETRO SBA157-13



8" CORNER SHELF METRO SBA115-13 RETRO SBA155-13



5" FOOT REST METRO SBA121-13 RETRO SBA159-13

MATTE BRIGHT WHITE



10" CORNER SHELF METRO SBA116-67 RETRO SBA153-67



5" CORNER SHELF METRO SBA112-67 RETRO SBA157-67



8" CORNER SHELF METRO SBA114-67 RETRO SBA155-67



5" FOOT REST METRO SBA120-67 RETRO SBA159-67

MATTE GRAY



10" CORNER SHELF METRO SBA116-12 RETRO SBA153-12



5" CORNER SHELF METRO SBA112-12 RETRO SBA157-12



8" CORNER SHELF METRO SBA114-12 RETRO SBA155-12



5" FOOT REST METRO SBA120-12 RETRO SBA159-12

MATTE SAND



10" CORNER SHELF METRO SBA116-03 RETRO SBA153-03



5" CORNER SHELF METRO SBA112-03 RETRO SBA157-03





5" FOOT REST METRO SBA120-03 RETRO SBA159-03



METRO + RETROFIT

BATH ACCESSORIES | CAST STONE & CAST METAL

MATTE GRAPHITE



10" CORNER SHELF METRO MBA116-086 RETRO MBA153-086



5" CORNER SHELF METRO MBA112-086 RETRO MBA157-086



8" CORNER SHELF METRO MBA114-086 RETRO MBA155-086



5" FOOT REST METRO MBA120-086 RETRO MBA159-086



8" CORNER SHELF METRO SBA114-024 RETRO SBA154-024



5" CORNER SHELF METRO SBA112-024 RETRO SBA156-024



5" FOOT REST METRO SBA120-024 RETRO SBA158-024

DARK OIL RUBBED BRONZE



8" CORNER SHELF METRO SBA114-070 RETRO SBA154-070



5" CORNER SHELF METRO SBA112-070 RETRO SBA156-070



5" FOOT REST METRO SBA120-070 RETRO SBA158-070



GEO + GEO RETROFIT

BATH ACCESSORIES | CAST STONE POLISHED BRIGHT WHITE



10" CORNER SHELF GEO SBA195-23 RETRO SBA185-23



5" CORNER SHELF GEO SBA194-23 RETRO SBA184-23



8" CORNER SHELF GEO SBA193-23 RETRO SBA183-23



5" FOOT REST GEO SBA196-23 RETRO SBA186-23

POLISHED GRAY



10" CORNER SHELF GEO SBA195-21 RETRO SBA185-21



5" CORNER SHELF GEO SBA194-21 RETRO SBA184-21



8" CORNER SHELF GEO SBA193-21 RETRO SBA183-21



5" FOOT REST GEO SBA196-21 RETRO SBA186-21

POLISHED WHITE



10" CORNER SHELF GEO SBA195-13 RETRO SBA185-13



5" CORNER SHELF GEO SBA194-13 RETRO SBA184-13



8" CORNER SHELF GEO SBA193-13 RETRO SBA183-13



5" FOOT REST GEO SBA196-13 RETRO SBA186-13

MATTE BRIGHT WHITE



10" CORNER SHELF GEO SBA195-67 RETRO SBA185-67



5" CORNER SHELF GEO SBA194-67 RETRO SBA184-67



8" CORNER SHELF GEO SBA193-67 RETRO SBA183-67



5" FOOT REST GEO SBA196-67 RETRO SBA186-67

MATTE GRAY



10" CORNER SHELF GEO SBA195-12 RETRO SBA185-12



5" CORNER SHELF GEO SBA194-12 RETRO SBA184-12



8" CORNER SHELF GEO SBA193-12 RETRO SBA183-12



5" FOOT REST GEO SBA196-12 RETRO SBA186-12

MATTE SAND



10" CORNER SHELF GEO SBA195-03 RETRO SBA185-03



5" CORNER SHELF GEO SBA194-03 RETRO SBA184-03



8" CORNER SHELF GEO SBA193-03 RETRO SBA183-03



5" FOOT REST GEO SBA196-03 RETRO SBA186-03



GEO + GEO RETROFIT

BATH ACCESSORIES | CAST STONE & CAST METAL

MATTE GRAPHITE



10" CORNER SHELF GEO MBA195-086 RETRO MBA185-086



5" CORNER SHELF GEO MBA194-086 RETRO MBA184-086



8" CORNER SHELF GEO MBA193-086 RETRO MBA183-086



5" FOOT REST GEO MBA196-086 RETRO MBA186-086

BRUSHED NICKEL



8" CORNER SHELF GEO SBA193-024 RETRO SBA183-024



5" CORNER SHELF GEO SBA194-024 RETRO SBA184-024



5" FOOT REST GEO SBA196-024 RETRO SBA186-024

DARK OIL RUBBED BRONZE



8" CORNER SHELF GEO SBA193-070 RETRO SBA183-070



5" CORNER SHELF GEO SBA194-070 RETRO SBA184-070



5" FOOT REST GEO SBA196-070 RETRO SBA186-070





- Retrofit (Flatback) is easy and less costly install with same holding power (+300 PSI) as the Metro/Geo Shelves
 - Flat back Easy as 1,2,3 Installation Video on Questech's YouTube site.
 - https://www.youtube.com/watch?v=kuhqxb-pG9w
- Retrofit (Flatback) Corner Shelf Breaking Strength Video
 - https://www.youtube.com/watch?v=b8_NTxQdClg





MOSAICS CAST METAL

STARLIGHT | CAST METAL



11.75" X 11.75" BRUSHED NICKEL MOSA100-003



11.75" X 11.75" ANTIQUE BRONZE MOSA100-002



11.75" X 11.75" WROUGHT IRON MOSA100-001

TWILL | CAST METAL



10.68" X 10.68" BRUSHED NICKEL BLEND MOSA200-005



10.68" X 10.68" ANTIQUE BRONZE BLEND MOSA200-006



10.68" X 10.68" DARK OIL RUBBED BRONZE BLEND MOSA200-004





MOSAICS CAST METAL

VISTA | CAST METAL



11.75" X 10.62" BRUSHED NICKEL BLEND MOSA300-008



11.75" X 10.62" ANTIQUE BRONZE BLEND MOSA300-009



11.75" X 10.62" DARK OIL RUBBED BRONZE BLEND MOSA300-007







CAST METAL COLLECTION

TILE & TRIM | CAST METAL












M2L004068

2" X 12" TRADITIONAL OGEE

CAST METAL COLLECTION

TILE & TRIM | CAST METAL





2" X 12" BRAIDED ROPE OGEE M2L302021



2" X 12" NOUVEAU BORDER M2L308021



3" X 12" EMPRESS BORDER M2I 303021



4" X 4" SOHO FIELD MD403021



2" X 2" NOUVEAU DOT M2D310021



4" X 4" FLEUR DECO M2D312021



2" X 2" FLEUR DOT M2D309021

DARK OIL RUBBED BRONZE



ML402070

½" X 12" SOHO LISTEL



½" X 12" BRAIDED ROPE LISTEL M2L300070

1" X 12" TRADITIONAL LINER M2L001070

1" X 12" COVE LINER M2L305070



1" X 12" BEADED LINER M2L307070

2" X 12" COVE OGEE M2L304070



2" X 12" TRADITIONAL OGEE M2L004070



2" X 12" BRAIDED ROPE OGEE M2L302070



2" X 12" NOUVEAU BORDER M2L308070



3" X 12" EMPRESS BORDER M2L303070



4" X 4" SOHO FIELD MD403070



2" X 2" NOUVEAU DOT M2D310070



4" X 4" FLEUR DECO M2D312070



2" X 2" FLEUR DOT M2D309070



M2L004021

2" X 12" TRADITIONAL OGEE



MERCHANDISING

GROUT-READY NICHE & CORNER SHELF KIT



NICHE STAND (WITH SAMPLE) \$120.00 ITEM# INFO132

The Niche Stand (with sample) is designed to simply feature an upright sample niche. The stand can also accommodate INFO129 (8 photo boards) or our Questech Product Brochure - all sold separately.

*To order INFO132 (Niche Display Stand), please include the Item Number (#) of your choice of Niche on the purchase order. Choose from any of the 16 designs.

SET OF 8 BOARD REPLENISHMENT PACK \$60.00 ITEM# INFO129

Each of the 8 boards in this pack are double-sided and show beautiful photography for all color and designs available in the Grout-Ready Niche.



METRO + GEO RETROFIT CORNER SHELF KIT \$38.00 ITEM# S-INFO 110

"The Kit" is a collection of essentials tools for the ultimate Metro
+ Geo Bath Accessories package. Each kit includes the Metro
+ Geo Retrofit Bath Accessory Point of Purchase Display and
a USB Flash Drive, containing the Retrofit Flatback Installation
DIY Video, Use and Care Instructions, and Contractor Sheet.







MERCHANDISING


WATERFALL DISPLAY & INDIVIDUAL BOARDS

WATERFALL DISPLAY - THE ESSENTIAL COLLECTION \$425.00 ITEM# S-INFO114 | INDIVIDUAL BOARDS \$65.00

This powerful 3' 6", 8-board in-store waterfall display presents every line in the Sandgate Collection.

- Metro + Geo Bath Accessories
 - Item# S-INFO700
- High-Relief Liners
 - Item# S-INFO701
- The Jolly
 - Item# S-INFO120
- City Scape
 - Item# S-INFO122

- Grout-Ready Niche
 - Item# S-INFO123
- 4 Shades of Gray
 - Item# S-INFO124
- 4 Shades of Gray
 - Item# S-INFO125
- Cast Metal Collection
 - Item# S-INFO126





MERCHANDISING

MINI GALLERY SALES KIT & JOLLY



MINI GALLERY SET - 18 BOARD COMPLETE SET \$225.00 ITEM# SANDGATESALESKIT | INDIVIDUAL BOARDS \$15.00

A comprehensive review of the full line of Questech products, conveniently displayed

in two galvanized boxes.





INFO S1

INFO S2

GALVANIZED JOLLY CANISTER \$5.00 ITEM# S-INFO111


A beautiful canister to conveniently display the full suite of the Jolly ¼ round trim/liner pieces (refill pack sold separately, ITEM# INFO112). This merchandising vehicle coordinates perfectly with the existing mini gallery.



JOLLY CANISTER REFILL PACK \$25.00 ITEM# INFO112

Fill you Jolly canister with the complete collection of Jolly ¼ round trim/liner pieces. Set of 20 includes all colors and finishes.





FREQUENTLY ASKED QUESTIONS

HOW ARE THE CAST METAL TILES. LINERS AND BATH ACCESSORIES MADE?

Made in the USA, the Cast Metal tiles and bath accessories are "Cast in Questech", a proprietary composite of metal, resin and ceramic. The surface is real premium metal. Each tile and bath accessory comes from an original hand carved design.

HOW ARE THE CAST STONE TILES. LINERS AND BATH ACCESSORIES MADE?

Made in the USA, the Cast Stone tiles and bath accessories are "Cast in Questech", a proprietary composite of crushed marble and resin. Each tile and bath accessory comes from an original hand carved design.

ARE THERE VARIATIONS IN TONE AND COLOR?

The Questech product will vary naturally from piece to piece. However, they do not vary from lot to lot like ceramic tile, and will always coordinate beautifully together.

WHERE CAN I USE THE TILES & LINERS?

They can be used on any interior wall, including wet areas. The tiles can also be used as a counter edge molding. Designated floor products may be used on both interior walls and residential/light commercial floors. Tiles are not suitable for counter top surfaces or exterior installations.

HOW DO I INSTALL THE TILES & LINERS?

Tiles that are "Cast in Questech" can be installed using standard tile setting methods (polymer fortified thin-set, epoxy and mastic). They cut easily with a wet saw or a spiral saw and can be drilled with a high-speed drill. Do not score and snap.

ARE THERE SPECIAL INSTALLATION SITUATIONS FOR TILE & LINERS?

To ensure proper bond, high temperature installations might require epoxy adhesive and grout. Examples where epoxy is recommended includes behind some kitchen cook-tops, fireplace surrounds and steam showers. See installation instructions for more information.

HOW DO I INSTALL THE FLAT BACK BATH ACCESSORIES?

Our Flat back bath accessories are designed for easy no cut installations over new & existing shower walls. They complement any ceramic, porcelain, metal and stone tile. Our Easy as 1, 2, 3 Installation instructions are included in every product box. Adhesive is sold separately; use either a Polyurethane Construction Adhesive or GEL Epoxy. See installation instructions for more information.

WHAT IS Q-SEAL™?

Questech tiles are protected by Q-Seal, a factory-applied, permanent sealer that is guaranteed to be water and stain resistant for as long as you own your home. The sealer also provides abrasion resistance and includes an anti-bacterial ingredient – Ultra-Fresh®, that inhibits the growth of mold and mildew.

WHAT HAPPENS IF I ACCIDENTALLY GET STONE OR GROUT SEALER ON THE QUESTECH PRODUCT?

Sealers cannot penetrate or adversely affect Q-Seal. Simply wipe excess sealer off the piece.

HOW DO I CLEAN THE TILES. LINERS AND BATH ACCESSORIES?

The surface can be cleaned with any ordinary household cleaner. Harsh chemicals like bleach should be wiped away shortly after application. Do not use abrasive implements for cleaning, for example, scouring pads and steel wool are not recommended.



TECHNICAL PERFORMANCE SUMMARY

TEST	TEST METHOD	ANSI SPECIFICATION SUMMARY	QUESTECH RESULTS	PASS/ FAIL
Bond Strength to Polymer Fortified Portland-Cement Mortar		ANSI A137.1 50 PSI or greater	131 PSI	Pass
Breaking Strength	ASTM C648	ANSI A137.1 90 lbs. or greater	130-170 lbs. (¼" nominal thickness)	Pass
Facial Dimensions	ASTM C499	ANSI A137.1 Average facial dimension not to vary more than 4.0% from nominal Range of facial dimension not to exceed 0.6%	Average ≤ 4.0% Range/Max ≤ 0.6%	Pass
Coefficient of Friction (Floor Tile)	ASTM C1028-89 (withdrawn 2012) with no replacement ASTM standard	ANSI A137.1-2012 Section 9.61 for wet DCOF	<0.42	Approved for Dry & Level Interior Floors
Wedging	ASTM C502	ANSI A137.1 Not to exceed 0.6%	≤ 0.6%	Pass
Water Absorption	ASTM C373	ANSI A137.1 Not to exceed 20.0%	0.73%-1.21%	Pass
24 hr. Resistance to Household Chemical Substances	ASTM C650	No ANSI Specification	No effect. Ten (10) cleaning chemicals, two (2) base concentrations and two (2) acid concentrations	N/A
24 hr. Resistance to Staining	ASTM C1378	No ANSI Specification	No visual effect. Six (6) staining agents and two (2) cleaning procedures.	N/A
Surface Burning	ASTM E84-95b	No ANSI Specification	Class B	N/A
Surface Resistivity		No ANSI Specification	Questech is non-conductive	N/A





INSTALLATION, USE & CARE INSTRUCTIONS

Thank you for your purchase, please enjoy your new Questech Tile. Surface markings and natural color variations are inherent qualities of Questech Cast Stone, Cast Metal and Natural Stone; adding to the beauty of all Questech products. Please inspect your product prior to installation.

QUESTECH TILE WARRANTY

The Questech limited warranty for Questech Cast Stone Tile, Questech Cast Metal Tile, and Questech Natural Stone Tile can be found at: www.Questech.com/Warranty

Q-SEAL™ PERMANENT PROTECTION

Tile surfaces are protected by Q-Seal, a permanent sealer that is water and stain resistant, protects against abrasion, and features Ultra-Fresh® anti-microbial protection, which inhibits the growth of stain and odorcausing mold and mildew. Q-Seal is factory-applied and never needs re-sealing.

Q-SEAL WARRANTY

Q-Seal is guaranteed to be water and stain resistant for as long as you own your home. For complete warranty information please visit: www.Questech.com/Warranty

APPLICATIONS

- WALL: All tiles are recommended for use as a wall covering in interior applications.
- FLOOR: Tiles designated as "floor" are recommended for use as a wall or floor covering.
- COUNTERTOPS: Tiles are NOT recommended for use as a surface for countertops.
- WET AREAS: The tiles can be installed in wet areas such as backsplashes, bathroom walls and shower enclosures (including steam showers), but are NOT recommended in or near swimming pools & hot tubs because pool chemicals may harm our protective sealer (Q-Seal™).
- EXTERIOR: Tiles are NOT recommended for exterior applications.
- RESIDENTIAL & COMMERCIAL: Tiles are recommended for residential and light commercial applications.

Installations Instructions

Follow generally accepted good practices for installation of ceramic tile. Take careful note of the following instructions specific to tiles *Cast in Questech*.

SETTING MATERIALS

Use the following setting materials for proper adhesion:

- Thin-Set: A liquid latex (polymer) fortified premium thin-set Portland cement mortar conforming to ANSI A118.4.
- Epoxy Adhesives: A water-cleanable epoxy mortar conforming to ANSI A118.3.
- Mastics & Adhesives: A Type 1 organic adhesive conforming to ANSI A136.1

(examples: latex mastic adhesive; acrylic latex adhesive).

SETTING METHODS

- Follow adhesive manufacturer's instructions for preparation, mixing, application, and cleanup.
- Trowel a layer of adhesive on the back of each tile prior to placing on the combed adhesive bed to obtain 100% coverage.
- Do NOT beat in with the butt-end of the trowel.

GROUTING MATERIALS

Use the following grouting materials:

- Cement: A liquid latex (polymer) fortified premium Portland cement grout conforming to ANSI A118.6.
- Epoxy: A water-cleanable grouting epoxy conforming to ANSI A118.3.

GROUTING METHODS

- Follow grout manufacturer's instructions for preparation, mixing, application, and cleanup.
- To help with cleanup, we recommend covering the tile surface with a high quality painter's tape.
- Clean-up residue as soon as possible after grouting. Grout that is allowed to harden may be difficult to remove.
- Do NOT use scouring pads, steel wool, sandpaper, or other abrasive implements to remove grout haze, or damage to the tile surface may result.

CUTTING INSTRUCTIONS AND SAFETY

Be sure to wear appropriate eye protection and an approved dust respirator when cutting, grinding or drilling tiles.

- The tiles are best cut or mitered with a diamond abrasive wet-saw.
- Tiles can be drilled with a high-speed drill or a hole saw.
- Tiles can also be cut or drilled with a rotary saw (ex. Roto Zip, Dremel).
- Do NOT use tile cutters designed to score and break tiles.

CARE AND MAINTENANCE

- To clean, use an ordinary household cleaner. For best results, we recommend a liquid, non-abrasive cleaner.
- Liquid abrasive household cleaners should be used only after being tested in a small inconspicuous area to ensure that no damage will result.
- Do NOT clean with scouring pads, steel wool, or other abrasive implements or damage to the tile surface may result.
- Cleaners containing ammonia, bleach or other harsh chemicals should be wiped up shortly after application or damage to the tile surface may result.


HIGH-TEMPERATURE INSTALLATION

High-temperature installations are those where tiled surfaces will be subject to temperatures 130°F (55°C) or greater. Common applications include: Certain kitchen cook tops, fireplace surrounds and steam rooms. Follow the high temperature installation instructions to ensure proper adhesion.

Important Note: Tiles are not recommended in areas where the tiled surface temperature will exceed 212°F (100°C). For example, do not install tiles as a heat shield behind a wood (or gas) stove.

<u>Behind Cook-Tops without a Back-Guard (or</u> back mount control panel)

To ensure proper bond, maintain a minimum distance of 4.5" inches between tiled surfaces and heat source. For the wall area directly behind and within 18 inches above the cooking surface, follow the high-temperature installation instructions.



Fireplace Surrounds

To ensure proper bond, maintain a minimum clearance of 6" from the fireplace opening. When used above and projecting more than 1½" from a fireplace face, maintain a minimum clearance of 12" above the fireplace opening. Consult state and local building codes to determine if more clearance is required in your area. Follow the high-temperature installation instructions.

Steam Rooms

To ensure proper bond, follow the high-temperature installation instructions.

HIGH-TEMPERATURE INSTALLATION INSTRUCTIONS

- Set tile with a water-cleanable epoxy mortar conforming to ANSI A118.3.
- Grout tile with a water-cleanable grouting epoxy conforming to ANSI A118.3.
- Follow setting and grouting instructions found in the Installation Instructions section of this document.



CITY SCAPE & 4 SHADES OF GRAY

Light Commercial (Floor/Wall): 4 Shades of Gray | Brushed Nickel & Iron City Scape | Burnished & Water

Residential (Floor/Wall): 4 Shades of Gray | Silver Lining & Titanium City Scape | Hammered

INSTALLATION, USE & CARE INSTRUCTIONS

Thank you for your purchase, please enjoy your new Questech Tile. Surface markings and natural color variations are inherent qualities of Questech Cast Stone and Cast Metal; adding to the beauty of all Questech products. Please inspect your product prior to installation.

QUESTECH TILE WARRANTY

The Questech limited warranty for Questech Cast Stone Tile and Questech Cast Metal Tile be found at: www.Questech.com/Warranty

Q-SEAL" PERMANENT PROTECTION

Tile surfaces are protected by Q-Seal, a permanent sealer that is water and stain resistant, protects against abrasion, and features Ultra-Fresh® anti-microbial protection, which inhibits the growth of stain and odorcausing mold and mildew. Q-Seal is factory-applied and never needs re-sealing.

Q-SEAL WARRANTY

Q-Seal is guaranteed to be water and stain resistant for as long as you own your home. For complete warranty information please visit: www.Questech.com/Warranty

APPLICATIONS

- LIGHT COMMERCIAL FLOOR: 4 SHADES OF GRAY (Brushed Nickel and Iron) & CITY SCAPE (Burnished and Water) are recommended for dry and level interior floors.
- RESIDENTAL FLOOR: 4 SHADES OF GRAY (Silver Lining and Titanium) & CITY SCAPE (Hammered) are recommended for dry and level interior floors.
- WET AREAS: (For Wall Only) Tiles can be installed in light commercial and residential wet areas such as backsplashes, bathroom walls and shower enclosures (including steam showers), but are NOT recommended in or near swimming pools & hot tubs because pool chemicals may harm our protective sealer (Q-Seal™).
- COUNTERTOPS: Tiles are NOT recommended for use as a surface for countertops.
- EXTERIOR: Tiles are NOT recommended for exterior applications.

SUBSTRATES

The performance of a properly installed tile application is dependent upon the durability and dimensional stability of the substrate to which it is bonded. Various substrate preparation methods are detailed in the Tile Council of North America's Handbook for Ceramic Tile Installation and are general in nature (www.tileusa.com).

SUBFLOORS

- Install floor tile over properly prepared concrete and wood subfloors.
- Wood subfloors should consist of 5/8" exterior grade plywood with an underlayment of i) 5/8" exterior grade plywood where joints offset, or ii) 1/2"+ cementitious backer unit.

INSTALLATIONS INSTRUCTIONS

Follow generally accepted good practices for installation of ceramic tile.

HIGH-TEMPERATURE INSTALLATION INSTRUCTIONS (WALL)

- Set tile with a water-cleanable epoxy mortar conforming to ANSI A118.3.
- Grout tile with a water-cleanable grouting epoxy conforming to ANSI A118.3.
- Follow setting and grouting instructions found in the Installation Instructions section of this document.


HIGH-TEMPERATURE INSTALLATION (WALL)

High-temperature installations are those where tiled surfaces will be subject to temperatures 130°F (55°C) or greater. Common applications include: Certain kitchen cook tops, fireplace surrounds and steam rooms. Follow the high temperature installation instructions to ensure proper adhesion.

Important Note: Tiles are not recommended in areas where the tiled surface temperature will exceed 212°F (100°C). For example, do not install tiles as a heat shield behind a wood (or gas) stove.

Behind Cook-Tops without a Back-Guard (or back mount control panel)

To ensure proper bond, maintain a minimum distance of 4.5" inches between tiled surfaces and heat source.



For the wall area directly behind and within 18 inches above the cooking surface, follow the high-temperature installation instructions.

Fireplace Surrounds

To ensure proper bond, maintain a minimum clearance of 6" from the fireplace opening. When used above and projecting more than 1½" from a fireplace face, maintain a minimum clearance of 12" above the fireplace opening. Consult state and local building codes to determine if more clearance is required in your area. Follow the high-temperature installation instructions.

Steam Rooms

To ensure proper bond, follow the high-temperature installation instructions.

TYPICAL INSTALLTION

STEP 1 | SETTING

SETTING MATERIALS

Use the following setting materials for proper adhesion:

- Thin-Set: A liquid latex (polymer) fortified premium thin-set Portland cement mortar conforming to ANSI A118.4.
- Epoxy Adhesives: A water-cleanable epoxy mortar conforming to ANSI A118.3.
- Mastics & Adhesives: A Type 1 organic adhesive conforming to ANSI A136.1 (examples: latex mastic adhesive; acrylic latex adhesive).

SETTING METHODS

- Follow adhesive manufacturer's instructions for preparation, mixing, application, and cleanup.
- Trowel a layer of adhesive on the back of each tile prior to placing on the combed adhesive bed to obtain 100% coverage.
- Do NOT beat in with the butt-end of the trowel.

STEP 2 | CUTTING

CUTTING INSTRUCTIONS AND SAFETY

Be sure to wear appropriate eye protection and an approved dust respirator when cutting, grinding or drilling tiles.

- The tiles are best cut or mitered with a diamond abrasive wet-saw.
- Tiles can be drilled with a high-speed drill or a hole saw.
- Tiles can also be cut or drilled with a rotary saw (ex. Roto Zip, Dremel).
- Do NOT use tile cutters designed to score and break tiles.

STEP 3 | GROUTING

GROUTING MATERIALS

Use the following grouting materials:

- Cement: A latex (polymer) fortified premium Portland cement grout conforming to ANSI A118.6.
- Epoxy: A water-cleanable grouting epoxy conforming to ANSI A118.3.

GROUTING METHODS

- Follow grout manufacturer's instructions for preparation, mixing, application, and cleanup.
- To help with cleanup, we recommend covering the tile surface with a high quality painter's tape.
- Clean-up residue as soon as possible after grouting. Grout that is allowed to harden may be difficult to remove.
- Do NOT use scouring pads, steel wool, sandpaper, or other abrasive implements to remove grout haze, or damage to the tile surface may result.

CARE AND MAINTENANCE

- To clean, use an ordinary household cleaner. For best results, we recommend a liquid, non-abrasive cleaner.
- Liquid abrasive household cleaners should be used only after being tested in a small inconspicuous area to ensure that no damage will result.
- Do NOT clean with scouring pads, steel wool, or other abrasive implements or damage to the tile surface may result.
- Cleaners containing ammonia, bleach or other harsh chemicals should be wiped up shortly after application or damage to the tile surface may result.



METRO + GEO BATH ACCESSORIES

INSTALLATION, USE & CARE INSTRUCTIONS

Thank you for your purchase, please enjoy your new Bath Accessory. They complement any ceramic, porcelain, metal or stone tile. Surface markings and natural color variations are inherent qualities of Questech Cast Stone, Cast Metal and Natural Stone; adding to the beauty of all Questech products. Please inspect your product prior to installation.

QUESTECH TILE WARRANTY

The Questech limited warranty for Questech Cast Stone Tile, Questech Cast Metal Tile, and Questech Natural Stone Tile can be found at: www.Questech.com/Warranty

Q-SEAL PERMANENT PROTECTION

Accessory surfaces are protected by Q-Seal, a permanent sealer that is water and stain resistant, protects against abrasion, and inhibits the growth of stain and odor-causing mold and mildew. Q-Seal is factory-applied and never needs re-sealing.

Q-SEAL WARRANTY

Q-Seal is guaranteed to be water and stain resistant for as long as you own your home. For complete warranty information please visit: www.Questech.com/Warranty

INSTALLATION INSTRUCTIONS

- Following the adhesive manufacturer's instructions.
- Set wall tile to height accessory will be located.
- Trowel a layer of adhesive on the dove-tails (teeth) of each accessory prior to placing on the combed adhesive bed to obtain 100% coverage.
- Dove-tail should be pushed into adhesive to ensure good contact. The accessory's back should overlap the wall tile.
- Continue wall installation around the accessory, noting that the accessory's back should overlap the wall tile.
- Tape accessory in place until adhesive bonds.
- Do NOT beat in with the butt-end of the trowel.

CARE AND MAINTENANCE

- To clean, use any ordinary household cleaner. For best results, we recommend a liquid, non-abrasive cleaner.
- Liquid abrasive household cleaners should only be used after being tested in a small inconspicuous area to ensure that no damage will result.
- Do NOT clean with scouring pads, steel wool, or other abrasive implements or damage to the surface may result.
- Cleaners containing ammonia, bleach or other harsh chemicals should be wiped up shortly after application or damage to the surface may result.

SETTING MATERIALS

Select one of the following two adhesives:

- Thin-Set: A liquid latex (polymer) fortified premium thin-set Portland cement mortar conforming to ANSIA118.4.
- Epoxy: A water-cleanable epoxy mortar conforming to ANSIA118.3.





METRO + GEO RETROFIT BATH ACCESSORIES

INSTALLATION, USE & CARE INSTRUCTIONS

Thank you for your purchase, please enjoy your new Bath Accessory. These products are designed for easy no-cut installation over new or existing shower walls. They complement any ceramic, porcelain, metal or stone tile. Surface markings and natural color variations are inherent qualities of Questech Cast Stone, Cast Metal and Natural Stone; adding to the beauty of all Questech products. Please inspect your product prior to installation.

QUESTECH TILE WARRANTY

The Questech limited warranty for Questech Cast Stone Tile, Questech Cast Metal Tile, and Questech Natural Stone Tile can be found at: www.Questech.com/Warranty

Q-SEAL" PERMANENT PROTECTION


Accessory surfaces are protected by Q-Seal, a permanent sealer that is water and stain resistant, protects against abrasion, and inhibits the growth of stain and odor-causing mold and mildew. Q-Seal is factory-applied and never needs re-sealing.

Q-SEAL WARRANTY


Q-Seal is guaranteed to be water and stain resistant for as long as you own your home. For complete warranty information please visit: www.Questech.com/Warranty

INSTALLATION INSTRUCTIONS

- · Prior to installation, clean surface with alcohol
- Locate position at desired height for install and mark it (use grout line when available and for easy clean up apply painter's tape along the top and bottom edge)
- Use double sided tape provided and place on the 4 specified areas on the back of accessory - remove paper tabs before installing *Note: If corner is not square use additional tape (included) to ensure contact with the wall.



- Following the adhesive manufacturer's instructions, apply adhesive along guideline on back edges of accessory
- Optional: Once adhesive is applied and the part is positioned, it can be supported until the adhesive sets up sufficiently to form a final bond.
- Once fully cured, thoroughly caulk around the perimeter of the accessory to seal out water.







APPLY TAPE HELUDED & ADHESIVE SOLD SEPARATELY

PRESS & HOLD

CARE AND MAINTENANCE

- To clean, use any ordinary household cleaner. For best results, we recommend a liquid, non-abrasive cleaner.
- Liquid abrasive household cleaners should only be used after being tested in a small inconspicuous area to ensure that no damage will result.

- Do NOT clean with scouring pads, steel wool, or other abrasive implements or damage to the surface may result.
- · Cleaners containing ammonia, bleach or other harsh chemicals should be wiped up shortly after application or damage to the surface may result.

APPROVED SUBSTRATES

 Marble, ceramic, glass, fiberglass reinforced wall panels and unpainted drywall

SETTING MATERIALS

Select one of the following adhesive types most suitable for your application, that is:

- Gap filling
- Water resistant
- Recommended for tile and stone
- Rapid set time

TWO-PART EPOXY GEL/PASTE ADHESIVE:

- Designed for vertical and overhead surfaces
- No-run no drip formula RECOMMENDED

Laticrete Latapoxy 310 Stone Adhesive

- Mapei Kerapoxy Adhesive
- Custom Building EBM-Lite Premium **Epoxy Bonding Mortar**
- Devcon 5 Minute Epoxy Gel
- Loctite Epoxy Gel

2. POLYURETHANE CONSTRUCTION ADHESIVE:

- 1 part polyurethane formula RECOMMENDED
 - Loctite PL Premium Polyurethane
 - Loctite Premium Fast Grab Polyurethane
 - Sika Pro Select
- Liquid Nails Polyurethane
- Titebond Fast Set Polyurethane



THE QUESTECH ADVANTAGE

- Product Development led by Roger Questel, a true artist, founder and innovator
 - Inventive design using premium materials
- Exceptional quality and service at every point of contact
- All products protected by Q-Seal, factory-applied lifetime sealer
 - Water, stain and scratch and smudge resistant
 - For use in wet areas, never needs resealing, anti-microbial
 - Only permanent protection in market for metal and stone
 - No special cleaner required
- Made in the USA



"MADE IN THE USA" MATTERS TO SHOPPERS

In a recent shopper research survey conducted by Perception Research Services International (PRS), results indicated that 4 out of 5 shoppers notice "Made in the USA" claims on packaging. And most of those shoppers (76%) claim that they are more likely to purchase a product after noticing the "Made in the USA" claim.



4 out of 5 shoppers notice "Made in the USA" claims on packaging.





KEY CONTACT INFORMATION

Questech Corporation

Headquarters & Factory 92 Park Street Rutland, Vermont 05701 (802) 773-1228

Peter L. Schelle

Vice President of Sales pschelle@questech.com Cell #: (847) 778-6327

Joanne Bania

Customer Service & Sales
Admin. Supervisor
jbania@questech.com
PH #: (802) 773-1228 ext. 242

Louise Graham

Customer Service Rep. lgraham@questech.com PH #: (802) 773-1228 ext. 235



