



REPOSADO® ADVANTAGE

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 178 mm x 1220 mm
Overall Thickness*	0.08" / 2.0 mm (nom)
Wear Layer	12 mil / 0.30 mm featuring Tuff Shield® finish
Edge	Square
Standard Colors	8 colors
Installation Method	Glue-Down
Wear Limited Warranty	30-Year Residential / 20-Year Light Commercial
Recycled Content	This product does not contain recycled content.
Packaging	51.34 ft² (4.77 m²) per carton 22 pieces per carton 60 cartons per pallet
Weight Per Carton	37.70 lbs / 17.10 kg



Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
STC Sound Testing	ASTM E 90 / E 413	55
IIC Sound Testing	ASTM E 492 / E 989	67



BEST 1 WEAR LIMITED WARRANTY



Paloma RAD-1201




Barrel RAD-1205



Sunrise RAD-1202



Casa RAD-1206




Matador RAD-1203



Agave RAD-1207



Siesta RAD-1204



Spirit RAD-1208

*All measurements are nominal. Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit www.earthwerks.com for full warranty details & installation guidelines. All specifications & offerings are subject to change without notice.